

TEAS
Internet-Draft
Intended status: Standards Track
Expires: September 24, 2015

C. Margaria, Ed.
Juniper
G. Martinelli
Cisco
S. Balls
B. Wright
Metaswitch
March 23, 2015

LSP Attribute in ERO
draft-ietf-teas-lsp-attribute-ro-05

Abstract

[RFC5420](#) extends RSVP-TE to specify or record generic attributes which apply to the whole of the path of a Label Switched Path (LSP). This document defines an extension to the RSVP Explicit Route Object (ERO) and Record Route Object (RRO) objects to allow it to specify or record generic attributes which apply to a given hop.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 24, 2015.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements Language	3
2.	ERO Hop Attributes Subobject	3
2.1.	Encoding	3
2.2.	HOP Attributes TLVs	4
2.3.	Procedures	5
3.	RRO Hop Attributes Subobject	6
3.1.	Encoding	6
3.2.	Procedures	7
3.2.1.	Subobject Presence Rule	7
3.2.2.	Reporting Compliance with ERO Hop Attributes	7
3.2.3.	Compatibility with RRO Attributes subobject	7
4.	IANA Considerations	8
4.1.	ERO Hop Attribute Subobject	8
4.2.	RRO LSP Attribute Subobject	8
4.3.	Existing Attribute Flags	8
4.4.	Existing LSP Attribute TLVs	9
5.	Security Considerations	10
6.	Acknowledgments	11
7.	References	11
7.1.	Normative References	11
7.2.	Informative References	13
	Authors' Addresses	14

1. Introduction

Generalized MPLS (GMPLS) Traffic Engineering (TE) Label Switched Paths (LSPs) can be route-constrained by making use of the Explicit Route object (ERO) and related sub-objects as defined in [[RFC3209](#)], [[RFC3473](#)], [[RFC3477](#)], [[RFC4873](#)], [[RFC4874](#)], [[RFC5520](#)] and [[RFC5553](#)]. Several documents have identified the need for attributes that can be targeted at specific hops in the path of an LSP, including [[RFC6163](#)], [[I-D.ietf-ccamp-wson-signaling](#)], [[I-D.ietf-teas-rsvp-te-li-lb](#)] or [[I-D.ali-ccamp-rc-objective-function-metric-bound](#)]. This document provides a generic mechanism for use by these other documents.

RSVP already supports generic extension of LSP Attributes in [[RFC5420](#)]. In order to support current and future ERO constraint extensions this document provides a mechanism to define per-Hop attributes.

The document describes a generic mechanism for carrying information related to specific nodes when signaling an LSP. This document does not restrict what that information can be used for. The defined approach builds on LSP Attributes defined in [\[RFC5420\]](#), and enables attributes to be expressed in ERO and Secondary Explicit Route object (SERO) objects. A new ERO sub-object is defined, containing a list of generic per-Hop attributes.

[1.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [\[RFC2119\]](#).

[2.](#) ERO Hop Attributes Subobject

The ERO Hop Attributes subobject is OPTIONAL. If used it is carried in the ERO or SERO. The subobject uses the standard format of an ERO subobject.

[2.1.](#) Encoding

The length is variable and content is a list of HOP Attributes TLVs defined in [Section 2.2](#). The size of the ERO sub-object limits the size of the attribute TLV to 250 bytes. The typical size of currently defined and forthcoming LSP_ATTRIBUTE TLVs applicable to a specific hop (WSON_SIGNALING, Objective Function (OF) and Metric) is not foreseen to exceed this limit.

The ERO Hop Attributes subobject is defined as follows:

```

0                               1                               2                               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|L|  Type  |      Length      |      Reserved      |R|
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|
//                               Attributes TLVs                               //
|
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

The L, Type and Length parameters are as defined in [\[RFC3209\]](#) [Section 4.3.3](#). The L bit MUST be set to 0. The Type for the ERO Hop Attributes subobject is TBA-1 by IANA. The attributes TLV are encoded as defined in [Section 2.2](#).

Reserved Reserved, MUST be set to 0 when the subobject is inserted in the ERO, MUST NOT be changed when a node processes the ERO and MUST be ignored on the node addressed by the preceding ERO subobjects.

R This bit reflects the LSP_REQUIRED_ATTRIBUTE and LSP_ATTRIBUTE semantic defined in [\[RFC5420\]](#). When set it indicates required hop attributes to be processed by the node. When cleared, it indicates that the hop attributes are not required as described in [Section 2.3](#).

Attributes TLVs The TLVs as defined in [Section 2.2](#).

2.2. HOP Attributes TLVs

ERO Attributes carried by the new objects defined in this document are encoded within TLVs. Each object MAY contain one or more TLVs. There are no ordering rules for TLVs, and interpretation SHOULD NOT be placed on the order in which TLVs are received. The TLV format is defined in [\[RFC5420\] Section 3](#).

The Attribute Flags TLV defined in [\[RFC5420\]](#) are carried in an ERO Hop Attributes Subobject. Flags set in the an Attribute Flags TLV [\[RFC5420\]](#) carried in an ERO Hop Attributes Subobject SHALL be interpreted in the context of the received ERO. Only a subset of defined flags are defined as valid for use in Attribute Flags TLV carried in an ERO Hop Attributes Subobject. Invalid flags SHALL be silently ignored. Unknown flags SHOULD trigger the generation of a PathErr with Error Code "Unknown Attributes Bit" as defined in [\[RFC5420\] Section 5.2](#). The set of valid flags are defined in [Section 4.3](#).

The presence and ordering rule of the Attribute Flags TLV in an ERO Hop Attributes Subobject is defined by each Flag. A document defining a Flag to be used in an Attribute Flags TLV carried in the ERO Hop Attributes Subobject has to describe:

- o after which kinds of ERO subobject the Flag is valid
- o if ordering of the Flag and other ERO subobjects associated with the same hop (e.g., Label subobjects) is significant,
- o if ordering is significant, how the Flag is interpreted in association with the preceding subobjects,
- o any Flag modification rules that might apply.

2.3. Procedures

As described in [\[RFC3209\]](#) the ERO is managed as a list of subobjects each identifying a specific entity, an abstract node or a link that defines a waypoint in the network path. Identifying subobjects of various types are defined in [\[RFC3209\]](#), [\[RFC3477\]](#), [\[RFC4873\]](#), [\[RFC4874\]](#), [\[RFC5520\]](#) and [\[RFC5553\]](#).

[\[RFC3473\]](#) modified the ERO list by allowing one or two Label subobjects to be interposed in the list after a subobject identifying a link. One or more ERO Hop Attributes subobjects applicable to a particular hop MAY be inserted directly after any of the existing identifying subobjects defined in [\[RFC3209\]](#), [\[RFC3477\]](#), [\[RFC4873\]](#), [\[RFC4874\]](#), [\[RFC5520\]](#) and [\[RFC5553\]](#). If any Label subobjects are present for a hop, the ERO Hop Attributes subobject(s) MAY also be inserted after the Label subobjects.

The attributes specified in an ERO Hop Attributes subobject apply to the immediately preceding subobject(s) in the ERO subobject list.

A document defining a specific Hop Attribute TLV has to describe:

- o after which kinds of ERO subobject they are valid ,
- o if ordering of the Hop Attributes subobject and other ERO subobjects associated with the same hop (e.g., Label subobjects) is significant,
- o if ordering is significant, how the attribute is interpreted in association with the preceding ERO subobjects, and
- o any TLV modification rules that might apply.

For instance, subobject presence rules can be defined by describing rules similar to [\[RFC4990\] Section 6.1](#).

If a node is processing an ERO Hop Attributes subobject and does not support handling of the subobject it will behave as described in [\[RFC3209\]](#) when an unrecognized ERO subobject is encountered. This node will return a PathErr with error code "Routing Error" and error value "Bad EXPLICIT_ROUTE object" with the EXPLICIT_ROUTE object included, truncated (on the left) to the offending unrecognized subobject.

When the R bit is set a node MUST examine the attribute TLV present in the subobject following the rules described in [\[RFC5420\] Section 5.2](#). When the R bit is not set a node MUST examine the

attribute TLV present in the subobject following the rules described in [\[RFC5420\] Section 4.2](#).

A node processing an ERO Hop Attributes subobject with a HOP Attributes TLV longer than the ERO subobject SHOULD return a PathErr with error code "Routing Error" and error value "Bad EXPLICIT_ROUTE object" with the EXPLICIT_ROUTE object included, truncated (on the left) to the offending malformed subobject. A processing node MUST NOT originate a HOP Attributes TLV longer than the ERO HOP Attributes Subobject. The processing of the Hop attribute TLVs SHOULD be described in the documents defining them.

3. RRO Hop Attributes Subobject

In some cases it is important to determine if an OPTIONAL Hop attribute has been processed by a node.

3.1. Encoding

The RRO Hop Attributes subobject is OPTIONAL. If used it is carried in the RECORD_ROUTE object. The subobject uses the standard format of an RRO subobject.

The RRO Hop Attributes subobject is defined as follows:

```

      0               1               2               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|          Type          |      Length      |      Reserved      |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|                                                                  |
//                               Attributes TLVs                               //
|                                                                  |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

The Type and Length parameters are as defined in [\[RFC3209\] Section 4.4.1](#). The Type for the RRO Hop Attributes subobject is TBA-2 by IANA. The attributes TLV are encoded as defined in [Section 2.2](#).

Reserved Reserved, MUST be set to 0 when the subobject is inserted in the RRO, MUST NOT be changed when a node process the RRO and MUST be ignored on the node addressed by the preceding RRO subobjects.

Attributes TLVs The processed or additional HOP Attributes, using the format defined in [Section 2.2](#).

3.2. Procedures

3.2.1. Subobject Presence Rule

The RRO rules defined in [[RFC3209](#)] are not changed. The RRO Hop Attributes subobject **MUST** be pushed after the RRO Attributes subobject (if present) defined in [[RFC5420](#)]. The RRO Hop Attributes subobject **MAY** be present between a pair of subobjects identifying Label Switching Router (LSR) or links. Unless local policy apply all such subobjects **SHOULD** be forwarded unmodified by transit LSRs.

It is noted that a node (e.g., a domain edge node) **MAY** edit the RRO to prune/modify the RRO, including the RRO Hop Attribute subobject before forwarding due to confidentiality policy or other reasons (for instance RRO size reduction).

3.2.2. Reporting Compliance with ERO Hop Attributes

To report that an ERO Hop attribute has been considered, or to report an additional attribute, an LSR can add a RRO Hop Attributes subobject with the HOP Attribute TLV which describes the attribute to be reported. The requirement to report compliance **MUST** be specified in the document that defines the usage of a Hop attribute.

3.2.3. Compatibility with RRO Attributes subobject

The RRO Hop Attributes subobject extends the capability of the RRO Attributes subobject defined in [[RFC5420](#)] [Section 7.2](#) by allowing the node to report the attribute value. The mechanism defined in this document is compatible with the RRO Attributes subobject using the following procedures.

For LSP attributes signaled in the LSP_ATTRIBUTES or LSP_REQUIRED_ATTRIBUTES objects, a node **SHOULD** use the RRO Attributes subobject to report processing of those attributes.

For LSP attributes signaled in the ERO Hop Attributes subobject and not in the LSP_ATTRIBUTES or LSP_REQUIRED_ATTRIBUTES objects, if a node desires to report the attributes, it **SHOULD** use the RRO Hop Attributes subobject and **SHOULD NOT** use the RRO Attributes subobject. Ingress nodes not supporting the RRO Hop Attributes subobject will drop the information, as described in [[RFC3209](#)] [Section 4.4.5](#).

A node can use the RRO Hop Attribute to report an LSP Attribute signaled in LSP_ATTRIBUTES or LSP_REQUIRED_ATTRIBUTES only if the following conditions are met:

The Attribute and its corresponding flag is allowed on both the LSP_ATTRIBUTES or LSP_REQUIRED_ATTRIBUTES and LSP Hop Attributes subobject.

The document defining this Attribute specify this specific behavior.

4. IANA Considerations

4.1. ERO Hop Attribute Subobject

IANA manages the "RSVP PARAMETERS" registry located at <http://www.iana.org/assignments/rsvp-parameters/rsvp-parameters.xml>. We request IANA to make an allocation in the Sub-object type 20 EXPLICIT_ROUTE - Type 1 Explicit Route registry.

This document introduces a new ERO sub-object:

Value	Description	Reference
-----	-----	-----
TBA-1	Hop Attributes	This document, Section 2

4.2. RRO LSP Attribute Subobject

IANA manages the "RSVP PARAMETERS" registry located at <http://www.iana.org/assignments/rsvp-parameters/rsvp-parameters.xml>. We request IANA to make an allocation in the Sub-object type 21 ROUTE_RECORD - Type 1 Route Record registry. We request the value to be the same as [Section 4.1](#).

This document introduces a new RRO sub-object:

Value	Description	Reference
-----	-----	-----
TBA-2	Hop Attributes	This document, Section 3

4.3. Existing Attribute Flags

IANA manages the "Attribute Flags" registry as part of the "RSVP-TE PARAMETERS" registry located at <http://www.iana.org/assignments/rsvp-te-parameters/rsvp-te-parameters.xml>. A new column in the registry is introduced by this document. This column indicates if the flag is permitted to be used in an Attribute Flags TLV carried in the ERO Hop Attributes Subobject. The column uses the heading "ERO" and the registry is to be updated as follows:

Bit	Name	Attribute FlagsPath	Attribute FlagsResv	RRO	ERO	Reference
0	End-to-end re-routing	Yes	No	No	No	[RFC4920] This Document
1	Boundary re-routing	Yes	No	No	No	[RFC4920] This Document
2	Segment-based re- routing	Yes	No	No	No	[RFC4920] This Document
3	LSP Integrity Required	Yes	No	No	No	[RFC4875] This Document
4	Contiguous LSP	Yes	No	Yes	No	[RFC5151] This Document
5	LSP stitching desired	Yes	No	Yes	No	[RFC5150] This Document
6	Pre-Planned LSP Flag	Yes	No	No	No	[RFC6001] This Document
7	Non-PHP behavior flag	Yes	No	Yes	No	[RFC6511] This Document
8	OoB mapping flag	Yes	No	Yes	No	[RFC6511] This Document
9	Entropy Label Capability	Yes	Yes	No	No	[RFC6790] This Document
10	OAM MEP entities desired	Yes	Yes	Yes	No	[RFC7260] This Document
11	OAM MIP entities desired	Yes	Yes	Yes	No	[RFC7260] This Document
12	SRLG collection Flag (TEMPORARY - registered 2014-09-11, expires 2015-09-11)	Yes	Yes	Yes	No	This Document [I.D.draft- ietf-teas- rsvp-te- srlg-collect] This Document

New allocation requests to this registry SHALL indicate the value to be used in the ERO column.

4.4. Existing LSP Attribute TLVs

IANA manages the "RSVP-TE PARAMETERS" registry located at <http://www.iana.org/assignments/rsvp-te-parameters/rsvp-te-parameters.xml>. The "Attributes TLV Space" registry manage the following attributes, as defined in [RFC5420]:

- o TLV Type (T-field value)

- o TLV Name
- o Whether allowed on LSP_ATTRIBUTES object
- o Whether allowed on LSP_REQUIRED_ATTRIBUTES object

We request IANA to add the following information for each TLV in the RSVP TLV type identifier registry.

- o Whether allowed on LSP Hop Attributes ERO subobject

The existing registry is modified for existing TLVs as follows: The following abbreviation are used in the table:

LSP_A Whether allowed on LSP_ATTRIBUTES object.

LSP_RA Whether allowed on LSP_REQUIRED_ATTRIBUTES object.

HOP_A Whether allowed on LSP Hop Attributes subobject.

T	Name	LSP_A	LSP_RA	HOP_A	Ref.
-	-	-	-	-	-
1	Attribute Flags	Yes	Yes	Yes	[RFC5420] This Document
2	Service ID TLV	Yes	No	No	[RFC6060] This Document
3	OAM Configuration TLV	Yes	Yes	No	[RFC7260] This Document

5. Security Considerations

This document adds new subobject in the EXPLICIT_ROUTE and the ROUTE_RECORD object carried in RSVP message used in MPLS and GMPLS signaling. It builds on mechanism defined in [\[RFC3209\]](#) and [\[RFC5420\]](#) and does not introduce any new security. The existing security considerations described in [\[RFC2205\]](#), [\[RFC3209\]](#), [\[RFC3473\]](#) and [\[RFC5420\]](#) do apply.

As any RSVP-TE signaling request, the procedures defined in this document permit the transfer and reporting of functional preferences on specific node. The mechanism added in this document does allow more control of LSP attributes at a given node. As other inputs, a node SHOULD check the Hop Attributes against his policies and admission procedures. A node MAY reject the message using existing RSVP error code like "Policy Control Failure" or "Admission Control Failure". The node MAY also, depending on the specific TLV procedures, modify the requested attribute. This can reveal information about the LSP request and status to anyone with

unauthorized access. The mechanism described in this document do not contribute to this issue, which can be only resolved by encrypting the content of the whole signaling message.

In addition the reporting of attributes using the RRO can reveal details about the node that the operator wishes to remains confidential. The same strategy and policies that apply to other RRO subobjects also apply to this new mechanism. It is RECOMMENDED that domain boundary policies take the releasing of RRO hop attributes into consideration.

6. Acknowledgments

The authors would like to thanks Lou Berger for his directions and Attila Takacs for inspiring this [[I-D.kern-ccamp-rsvpte-hop-attributes](#)]. The authors also thanks Dirk Schroetter for his contribution to the initial versions of the documents (version -00 up to -02).

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2205] Braden, B., Zhang, L., Berson, S., Herzog, S., and S. Jamin, "Resource ReSerVation Protocol (RSVP) -- Version 1 Functional Specification", [RFC 2205](#), September 1997.
- [RFC3209] Awduche, D., Berger, L., Gan, D., Li, T., Srinivasan, V., and G. Swallow, "RSVP-TE: Extensions to RSVP for LSP Tunnels", [RFC 3209](#), December 2001.
- [RFC3473] Berger, L., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) Extensions", [RFC 3473](#), January 2003.
- [RFC3477] Kompella, K. and Y. Rekhter, "Signalling Unnumbered Links in Resource ReSerVation Protocol - Traffic Engineering (RSVP-TE)", [RFC 3477](#), January 2003.
- [RFC4873] Berger, L., Bryskin, I., Papadimitriou, D., and A. Farrel, "GMPLS Segment Recovery", [RFC 4873](#), May 2007.
- [RFC4874] Lee, CY., Farrel, A., and S. De Cnodder, "Exclude Routes - Extension to Resource ReserVation Protocol-Traffic Engineering (RSVP-TE)", [RFC 4874](#), April 2007.

- [RFC4875] Aggarwal, R., Papadimitriou, D., and S. Yasukawa, "Extensions to Resource Reservation Protocol - Traffic Engineering (RSVP-TE) for Point-to-Multipoint TE Label Switched Paths (LSPs)", [RFC 4875](#), May 2007.
- [RFC4920] Farrel, A., Satyanarayana, A., Iwata, A., Fujita, N., and G. Ash, "Crankback Signaling Extensions for MPLS and GMPLS RSVP-TE", [RFC 4920](#), July 2007.
- [RFC5150] Ayyangar, A., Kompella, K., Vasseur, JP., and A. Farrel, "Label Switched Path Stitching with Generalized Multiprotocol Label Switching Traffic Engineering (GMPLS TE)", [RFC 5150](#), February 2008.
- [RFC5151] Farrel, A., Ayyangar, A., and JP. Vasseur, "Inter-Domain MPLS and GMPLS Traffic Engineering -- Resource Reservation Protocol-Traffic Engineering (RSVP-TE) Extensions", [RFC 5151](#), February 2008.
- [RFC5420] Farrel, A., Papadimitriou, D., Vasseur, JP., and A. Ayyangars, "Encoding of Attributes for MPLS LSP Establishment Using Resource Reservation Protocol Traffic Engineering (RSVP-TE)", [RFC 5420](#), February 2009.
- [RFC5520] Bradford, R., Vasseur, JP., and A. Farrel, "Preserving Topology Confidentiality in Inter-Domain Path Computation Using a Path-Key-Based Mechanism", [RFC 5520](#), April 2009.
- [RFC5553] Farrel, A., Bradford, R., and JP. Vasseur, "Resource Reservation Protocol (RSVP) Extensions for Path Key Support", [RFC 5553](#), May 2009.
- [RFC6001] Papadimitriou, D., Vigoureux, M., Shiimoto, K., Brungard, D., and JL. Le Roux, "Generalized MPLS (GMPLS) Protocol Extensions for Multi-Layer and Multi-Region Networks (MLN/MRN)", [RFC 6001](#), October 2010.
- [RFC6060] Fedyk, D., Shah, H., Bitar, N., and A. Takacs, "Generalized Multiprotocol Label Switching (GMPLS) Control of Ethernet Provider Backbone Traffic Engineering (PBB-TE)", [RFC 6060](#), March 2011.
- [RFC6511] Ali, Z., Swallow, G., and R. Aggarwal, "Non-Penultimate Hop Popping Behavior and Out-of-Band Mapping for RSVP-TE Label Switched Paths", [RFC 6511](#), February 2012.

- [RFC6790] Kompella, K., Drake, J., Amante, S., Henderickx, W., and L. Yong, "The Use of Entropy Labels in MPLS Forwarding", [RFC 6790](#), November 2012.
- [RFC7260] Takacs, A., Fedyk, D., and J. He, "GMPLS RSVP-TE Extensions for Operations, Administration, and Maintenance (OAM) Configuration", [RFC 7260](#), June 2014.

7.2. Informative References

- [I-D.ali-ccamp-rc-objective-function-metric-bound]
Ali, Z., Swallow, G., Filsfils, C., Fang, L., Kumaki, K., Kunze, R., Ceccarelli, D., and X. Zhang, "Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) Extension for Signaling Objective Function and Metric Bound", [draft-ali-ccamp-rc-objective-function-metric-bound-05](#) (work in progress), February 2014.
- [I-D.ietf-ccamp-wson-signaling]
Bernstein, G., Xu, S., Lee, Y., Martinelli, G., and H. Harai, "Signaling Extensions for Wavelength Switched Optical Networks", [draft-ietf-ccamp-wson-signaling-10](#) (work in progress), March 2015.
- [I-D.ietf-teas-rsvp-te-li-lb]
Dong, J., Chen, M., Li, Z., and D. Ceccarelli, "GMPLS RSVP-TE Extensions for Lock Instruct and Loopback", [draft-ietf-teas-rsvp-te-li-lb-05](#) (work in progress), March 2015.
- [I-D.ietf-teas-rsvp-te-srlg-collect]
Zhang, F., Dios, O., Li, D., Margaria, C., Hartley, M., and Z. Ali, "RSVP-TE Extensions for Collecting SRLG Information", [draft-ietf-teas-rsvp-te-srlg-collect-00](#) (work in progress), December 2014.
- [I-D.kern-ccamp-rsvpte-hop-attributes]
Kern, A. and A. Takacs, "Encoding of Attributes of LSP intermediate hops using RSVP-TE", [draft-kern-ccamp-rsvpte-hop-attributes-00](#) (work in progress), October 2009.
- [RFC4990] Shiomoto, K., Papneja, R., and R. Rabbat, "Use of Addresses in Generalized Multiprotocol Label Switching (GMPLS) Networks", [RFC 4990](#), September 2007.
- [RFC6163] Lee, Y., Bernstein, G., and W. Imajuku, "Framework for GMPLS and Path Computation Element (PCE) Control of Wavelength Switched Optical Networks (WSONs)", [RFC 6163](#), April 2011.

Authors' Addresses

Cyril Margaria (editor)
Juniper
200 Somerset Corporate Boulevard, , Suite 4001
Bridgewater, NJ 08807
USA

Email: cmargaria@juniper.net

Giovanni Martinelli
Cisco
via Philips 12
Monza 20900
IT

Phone: +39 039 209 2044
Email: giomarti@cisco.com

Steve Balls
Metaswitch
100 Church Street
Enfield EN2 6BQ
GB

Phone: +44 208 366 1177
Email: steve.balls@metaswitch.com

Ben Wright
Metaswitch
100 Church Street
Enfield EN2 6BQ
GB

Phone: +44 208 366 1177
Email: Ben.Wright@metaswitch.com

