

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: May 6, 2020

X. Liu
Volta Networks
I. Bryskin
Individual
V. Beeram
T. Saad
Juniper Networks
H. Shah
Ciena
S. Litkowski
Cisco
November 3, 2019

YANG Data Model for SR and SR TE Topologies
draft-ietf-teas-yang-sr-te-topo-06

Abstract

This document defines a YANG data model for Segment Routing (SR) topology and Segment Routing (SR) traffic engineering (TE) topology.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 6, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Terminology	2
1.2.	Tree Diagrams	3
2.	Modeling Considerations	3
2.1.	Segment Routing (SR) Topology	3
2.2.	Segment Routing (SR) TE Topology	3
2.3.	Relations to ietf-segment-routing	4
2.4.	Topology Type Modeling	5
2.5.	Topology Attributes	5
2.6.	Node Attributes	5
2.7.	Link Attributes	6
3.	Model Structure	7
4.	YANG Module	9
5.	IANA Considerations	16
6.	Security Considerations	17
7.	References	18
7.1.	Normative References	18
7.2.	Informative References	19
Appendix A.	Companion YANG Model for Non-NMDA Compliant Implementations	21
A.1.	SR Topology State Module	21
Appendix B.	Data Tree Example	24
Appendix C.	Contributors	31
	Authors' Addresses	31

[1.](#) Introduction

This document defines a YANG [[RFC7950](#)] data model for describing the presentations of Segment Routing (SR) topology and Segment Routing (SR) traffic engineering (TE) topology. The version of the model limits the transport type to an MPLS dataplane.

[1.1.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

The following terms are defined in [[RFC7950](#)] and are not redefined here:

- o augment
- o data model
- o data node


[1.2.](#) Tree Diagrams

Tree diagrams used in this document follow the notation defined in [[RFC8340](#)].

[2.](#) Modeling Considerations


[2.1.](#) Segment Routing (SR) Topology

The Layer 3 network topology model is discussed in [[RFC8346](#)]. The Segment Routing (SR) topology model proposed in this document augments and uses the `ietf-l3-unicast-igp-topology` module defined in [[RFC8346](#)]. SR related attributes are covered in the `ietf-sr-topology` model.



[2.2.](#) Segment Routing (SR) TE Topology

When traffic engineering is enabled on an SR topology, there will be associations between objects in SR topologies and objects in TE topologies. An SR TE topology is both an SR topology and a layer 3 TE topology. Multiple inheritance is used to achieve such relations.



Each type of topologies is indicated by "network-types" defined in [\[RFC8345\]](#). For the three types of topologies above, the data representations are:

L3 Topology:

```
/nd:networks/nd:network/nd:network-types/l3-unicast-topology
```

L3 TE Topology:

```
/nd:networks/nd:network/nd:network-types/l3-unicast-topology/l3-te
```

SR Topology:

```
/nd:networks/nd:network/nd:network-types/l3-unicast-topology/sr-mpls
```

SR TE Topology: (multiple inheritance)

```
/nd:networks/nd:network/nd:network-types/l3-unicast-topology/l3-te
/nd:networks/nd:network/nd:network-types/l3-unicast-topology/sr-mpls
```

2.3. Relations to ietf-segment-routing

[I-D.ietf-spring-sr-yang] defines `ietf-segment-routing` that is a model intended to be used on network elements to configure or operate segment routing; `ietf-sr-topology` defined in this document is intended to be used on a controller for the network-wide operations such as path computation.

SR topology model shares many modeling constructs defined in `ietf-segment-routing`. The module `ietf-sr-topology` uses the types and groupings defined in `ietf-segment-routing`.

2.4. Topology Type Modeling

A new topology type is defined in this document, to indicate a topology that is a Segment Routing (SR) topology on an MPLS dataplane.

```
augment /nw:networks/nw:network/nw:network-types
    /l3t:l3-unicast-topology:
    +--rw sr-mpls!
```

2.5. Topology Attributes

The Segment Routing attributes with topology-wide impacts are modeled by augmenting the container "l3-topology-attributes" in the L3 topology model. SRGB (Segment Routing Global Block) is covered in this augmentation. A SR domain is mapped to a topology in this model.

```
augment /nw:networks/nw:network/l3t:l3-topology-attributes:
    +--rw sr
        +--rw srgb* [lower-bound upper-bound]
            +--rw lower-bound    uint32
            +--rw upper-bound    uint32
```

2.6. Node Attributes

The Segment Routing attributes within the node scope are modeled by augmenting the sub tree /nw:networks/nw:network/nw:node/ in the L3 topology model.

The SR attributes that have node-scope impact are modeled by augmenting the container "l3-node-attributes" in the L3 topology model, including the SR capabilities, SRGB (Segment Routing Global Block), and SRLB (Segment Routing Local Block) specified on this mode. This model also provides the information about how these SR attributes are learned:


```
augment /nw:networks/nw:network/nw:node/l3t:l3-node-attributes:
```

```
  +--rw sr
    +--rw srgb* [lower-bound upper-bound]
      | +--rw lower-bound    uint32
      | +--rw upper-bound    uint32
    +--rw srlb* [lower-bound upper-bound]
      | +--rw lower-bound    uint32
      | +--rw upper-bound    uint32
    +--ro node-capabilities
      | +--ro transport-planes* [transport-plane]
      | | +--ro transport-plane  identityref
      | +--ro entropy-readable-label-depth?  uint8
    +--rw msd?                uint8 {msd}?
    +--ro information-source?  enumeration
    +--ro information-source-state
      +--ro credibility-preference?  uint16
```

The SR attributes that are related to a IGP-Prefix segment are modeled by augmenting the list entry "prefix" in the L3 topology model:

```
augment /nw:networks/nw:network/nw:node/l3t:l3-node-attributes
```

```
  /l3t:prefix:
```

```
  +--rw sr!
    +--rw value-type?      enumeration
    +--rw start-sid        uint32
    +--rw range?           uint32
    +--rw algorithm?       identityref
    +--rw last-hop-behavior? enumeration
      | {sid-last-hop-behavior}?
    +--rw is-local?        boolean
    +--rw is-node?         boolean
    +--ro is-readvertisement? boolean
```

2.7. Link Attributes

A link in the topology model connects the termination point on the source node to the termination point on the destination node. When such a link is instantiated, the bindings between the nodes and the corresponding Adj-SIDs are formed, and the resulting FIB entries are installed.

A link in the topology model is mapped to an SR Adjacency Segment, formed by a pair of interfaces on two respective adjacent nodes. The SR Adjacency Segment attributes are modeled by augmenting the link attributes of the L3 topology model. The modeling structure is as follows:


```
augment /nw:networks/nw:network/nt:link/l3t:l3-link-attributes:
```

```
  +--rw sr!
    +--rw value-type?          enumeration
    +--rw sid                  uint32
    +--rw advertise-protection? enumeration
    +--rw is-local?           boolean
    +--rw msd?                uint8 {msd}?
    +--rw address-family?     enumeration
    +--rw is-backup?          boolean
    +--rw is-part-of-set?     boolean
    +--rw is-persistent?      boolean
    +--rw is-on-lan?          boolean
    +--ro information-source?  enumeration
    +--ro information-source-state
      +--ro credibility-preference? uint16
```

The usage of the leaf "advertise-protection" is described in [\[I-D.ietf-spring-sr-yang\]](#).

Both IGP and BGP can be supported by the model, the leaf "information-source" is used to indicate where the information is from.

The bundling capability of the Adjacency Segment is achieved by re-using the existing modeling construct (i.e. "bundle-stack-level") under /nw:networks/nw:network/nt:link/tet:te [\[I-D.ietf-teas-yang-te-topo\]](#)

3. Model Structure

The model tree structure of the Segment Routing (SR) topology module is as shown below:

```
module: ietf-sr-topology
  augment /nw:networks/nw:network/nw:network-types
    /l3t:l3-unicast-topology:
      +--rw sr-mpls!
  augment /nw:networks/nw:network/l3t:l3-topology-attributes:
    +--rw sr
      +--rw srgb* [lower-bound upper-bound]
      +--rw lower-bound    uint32
      +--rw upper-bound    uint32
  augment /nw:networks/nw:network/nw:node/l3t:l3-node-attributes:
    +--rw sr
      +--rw srgb* [lower-bound upper-bound]
      | +--rw lower-bound    uint32
```



```
    | +--rw upper-bound      uint32
+--rw srlb* [lower-bound upper-bound]
    | +--rw lower-bound      uint32
    | +--rw upper-bound      uint32
+--ro node-capabilities
    | +--ro transport-planes* [transport-plane]
    | | +--ro transport-plane  identityref
    | +--ro entropy-readable-label-depth?  uint8
+--rw msd?                      uint8 {msd}?
+--ro information-source?        enumeration
+--ro information-source-instance?  string
+--ro information-source-state
    +--ro credibility-preference?  uint16
augment /nw:networks/nw:network/nw:node/l3t:l3-node-attributes
    /l3t:prefix:
+--rw sr!
    +--rw value-type?          enumeration
    +--rw start-sid            uint32
    +--rw range?              uint32
    +--rw algorithm?          identityref
    +--rw last-hop-behavior?   enumeration
    | {sid-last-hop-behavior}?
    +--rw is-local?           boolean
    +--rw is-node?            boolean
    +--ro is-readvertisement?  boolean
augment /nw:networks/nw:network/nt:link/l3t:l3-link-attributes:
+--rw sr!
    +--rw value-type?          enumeration
    +--rw sid                  uint32
    +--rw advertise-protection? enumeration
    +--rw is-local?           boolean
    +--rw msd?                uint8 {msd}?
    +--rw address-family?     enumeration
    +--rw is-backup?          boolean
    +--rw is-part-of-set?     boolean
    +--rw is-persistent?      boolean
    +--rw is-on-lan?          boolean
    +--ro information-source?   enumeration
    +--ro information-source-instance?  string
    +--ro information-source-state
        +--ro credibility-preference?  uint16
```


4. YANG Module

```
<CODE BEGINS> file "ietf-sr-topology@2019-11-02.yang"
module ietf-sr-topology {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-sr-topology";
  prefix "srt";

  import ietf-network {
    prefix "nw";
    reference "RFC 8345: A YANG Data Model for Network Topologies";
  }
  import ietf-network-topology {
    prefix "nt";
    reference "RFC 8345: A YANG Data Model for Network Topologies";
  }
  import ietf-l3-unicast-topology {
    prefix "l3t";
    reference "RFC 8346: A YANG Data Model for Layer 3 Topologies";
  }
  import ietf-segment-routing-common {
    prefix "sr-cmn";
    reference
      "I-D.ietf-spring-sr-yang: YANG Data Model for Segment Routing";
  }

  organization
    "IETF Traffic Engineering Architecture and Signaling (TEAS)
    Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/teas/>
    WG List:  <mailto:teas@ietf.org>

    Editor:   Xufeng Liu
              <mailto:xufeng.liu.ietf@gmail.com>

    Editor:   Igor Bryskin
              <mailto:Igor.Bryskin@huawei.com>

    Editor:   Vishnu Pavan Beeram
              <mailto:vbeeram@juniper.net>

    Editor:   Tarek Saad
              <mailto:tsaad@cisco.com>

    Editor:   Himanshu Shah
```


<mailto:hshah@ciena.com>

Editor: Stephane Litkowski
<mailto:stephane.litkowski@orange.com>;

description

"YANG data model for representing and manipulating Segment Routing Topologies.

Copyright (c) 2018 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](http://trustee.ietf.org/license-info) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

```
revision 2019-11-02 {
  description "Initial revision";
  reference
    "RFC XXXX: YANG Data Model for SR and SR TE Topologies";
}

feature msd {
  description
    "Support of signaling MSD (Maximum SID Depth) in IGP.";
}

grouping sr-topology-type {
  description
    "Identifies the SR-MPLS topology type. This type of network
    topologies use Segment Routing (SR) technology over the MPLS
    data plane";
  container sr-mpls {
    presence "Indicates SR-MPLS topology";
    description
      "Its presence identifies the SR topology type.";
  }
}

augment "/nw:networks/nw:network/nw:network-types/"
+ "l3t:l3-unicast-topology" {
  description
```



```
    "Defines the SR topology type.";
    uses sr-topology-type;
}

augment "/nw:networks/nw:network/l3t:l3-topology-attributes" {
    when "../nw:network-types/l3t:l3-unicast-topology/srt:sr-mpIs" {
        description "Augment only for SR topology.";
    }
    description "Augment topology configuration";
    uses sr-topology-attributes;
}

augment "/nw:networks/nw:network/nw:node/l3t:l3-node-attributes" {
    when "../nw:network-types/l3t:l3-unicast-topology/"
        + "srt:sr-mpIs" {
        description "Augment only for SR topology.";
    }
    description "Augment node configuration.";
    uses sr-node-attributes;
}

augment "/nw:networks/nw:network/nw:node/l3t:l3-node-attributes"
    + "/l3t:prefix" {
    when "../nw:network-types/l3t:l3-unicast-topology/"
        + "srt:sr-mpIs" {
        description "Augment only for SR topology.";
    }
    description "Augment node prefix.";
    uses sr-node-prefix-attributes;
}

augment "/nw:networks/nw:network/nt:link/l3t:l3-link-attributes" {
    when "../nw:network-types/l3t:l3-unicast-topology/"
        + "srt:sr-mpIs" {
        description "Augment only for SR topology.";
    }
    description "Augment link configuration";
    uses sr-link-attributes;
}

grouping sr-topology-attributes {
    description "SR topology scope attributes.";
    container sr {
        description
            "Containing SR attributes.";
        uses sr-cmn:srgb;
    } // sr
} // sr-topology-attributes
```



```
grouping information-source-attributes {
  description
    "The attributes identifying source that has provided the
    related information, and the source credibility.";
  leaf information-source {
    type enumeration {
      enum "unknown" {
        description "The source is unknown.";
      }
      enum "locally-configured" {
        description "Configured entity.";
      }
      enum "ospfv2" {
        description "OSPFv2.";
      }
      enum "ospfv3" {
        description "OSPFv3.";
      }
      enum "isis" {
        description "ISIS.";
      }
      enum "bgp-ls" {
        description "BGP-LS.";
        reference
          "RFC 7752: North-Bound Distribution of Link-State and
          Traffic Engineering (TE) Information Using BGP";
      }
      enum "system-processed" {
        description "System processed entity.";
      }
      enum "other" {
        description "Other source.";
      }
    }
    config false;
    description
      "Indicates the type of the information source.";
  }
  leaf information-source-instance {
    type string;
    config false;
    description
      "The name indicating the instance of the information
      source.";
  }
  container information-source-state {
    config false;
    description
```



```
    "The container contains state attributes related to
    the information source.";
  leaf credibility-preference {
    type uint16;
    description
      "The preference value to calculate the traffic
      engineering database credibility value used for
      tie-break selection between different
      information-source values.
      Higher value is more preferable.";
  }
}
} // information-source-attributes

grouping sr-node-attributes {
  description "SR node scope attributes.";
  container sr {
    description
      "Containing SR attributes.";
    uses sr-cmn:srgb;
    uses sr-cmn:srlb;
    uses sr-cmn:node-capabilities;
    leaf msd {
      if-feature "msd";
      type uint8;
      description
        "Node MSD is the lowest MSD supported by the node.";
    }
    // Operational state data
    uses information-source-attributes;
  } // sr
} // sr-node-attributes

grouping sr-node-prefix-attributes {
  description "Containing SR attributes for a prefix.";
  container sr {
    presence "Presence indicates SR is enabled.";
    description
      "Containing SR attributes for a prefix.";
    uses sr-cmn:prefix-sid-attributes;
    uses sr-cmn:last-hop-behavior;
    leaf is-local {
      type boolean;
      default false;
      description
        "'true' if the SID is local.";
    }
    leaf is-node {
```



```
    type boolean;
    default false;
    description
        "'true' if the Prefix-SID refers to the router identified
        by the prefix. Typically, the leaf 'is-node' (N-Flag)
        is set on Prefix-SIDs attached to a router loopback
        address.";
}
leaf is-readvertisement {
    type boolean;
    config false;
    description
        "'true' if the prefix to which this Prefix-SID is attached,
        has been propagated by the router from another
        topology by redistribution.";
}
} // sr
} // sr-node-prefix-attributes

grouping sr-link-attributes {
    description "SR link scope attributes";
    container sr {
        presence "Presence indicates SR is enabled.";
        description
            "Containing SR attributes.";
        uses sr-cmn:sid-value-type;
        leaf sid {
            type uint32;
            mandatory true;
            description
                "Adjacency SID, which can be either IGP-Adjacency SID
                or BGP PeerAdj SID, depending on the context.";
        }
        leaf advertise-protection {
            type enumeration {
                enum "single" {
                    description
                        "A single Adj-SID is associated
                        with the adjacency and reflects
                        the protection configuration.";
                }
                enum "dual" {
                    description
                        "Two Adj-SIDs will be associated
                        with the adjacency if interface
                        is protected. In this case
                        one will be enforced with
                        backup flag set, the other
```



```
        will be enforced to backup flag unset.
        In case, protection is not configured,
        a single Adj-SID will be advertised
        with backup flag unset.";
    }
}
default "single";
description
    "If set, the Adj-SID refers to an
    adjacency being protected.";
}
leaf is-local {
    type boolean;
    default false;
    description
        "'true' if the SID is local.";
}
leaf msd {
    if-feature "msd";
    type uint8;
    description
        "SID depth of the interface associated with the link.";
}
leaf address-family {
    type enumeration {
        enum "ipv4" {
            description
                "The Adj-SID refers to an adjacency with outgoing IPv4
                encapsulation.";
        }
        enum "ipv6" {
            description
                "The Adj-SID refers to an adjacency with outgoing IPv6
                encapsulation.";
        }
    }
    default "ipv4";
    description
        "This leaf defines the F-Flag (Address-Family flag) of the
        SID.";
}
leaf is-backup {
    type boolean;
    default false;
    description
        "'true' if the SID is a backup.";
}
leaf is-part-of-set {
```



```
        type boolean;
        default false;
        description
            "'true' if the SID is part of a set.";
    }
    leaf is-persistent {
        type boolean;
        default true;
        description
            "'true' if the SID is persistently allocated.";
    }
    leaf is-on-lan {
        type boolean;
        default false;
        description
            "'true' if on a lan.";
    }
    uses information-source-attributes;
} // sr
} // sr-tp-attributes
}
<CODE ENDS>
```

5. IANA Considerations

RFC Ed.: In this section, replace all occurrences of 'XXXX' with the actual RFC number (and remove this note).

This document registers the following namespace URIs in the IETF XML registry [[RFC3688](#)]:

```
-----
URI: urn:ietf:params:xml:ns:yang:ietf-sr-topology
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.
-----
```

```
-----
URI: urn:ietf:params:xml:ns:yang:ietf-sr-topology-state
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.
-----
```

This document registers the following YANG modules in the YANG Module Names registry [[RFC6020](#)]:


```
-----
name:      ietf-sr-topology
namespace: urn:ietf:params:xml:ns:yang:ietf-sr-topology
prefix:    srt
reference:  RFC XXXX
-----

-----
name:      ietf-sr-topology-state
namespace: urn:ietf:params:xml:ns:yang:ietf-sr-topology-state
prefix:    srt-s
reference:  RFC XXXX
-----
```

6. Security Considerations

The YANG module specified in this document defines a schema for data that is designed to be accessed via network management protocols such as NETCONF [[RFC6241](#)] or RESTCONF [[RFC8040](#)]. The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure transport is Secure Shell (SSH) [[RFC6242](#)]. The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [[RFC8446](#)].

The Network Configuration Access Control Model (NACM) [[RFC8341](#)] provides the means to restrict access for particular NETCONF or RESTCONF users to a preconfigured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in this YANG module that are writable/creatable/deletable (i.e., config true, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., edit-config) to these data nodes without proper protection can have a negative effect on network operations. These are the subtrees and data nodes and their sensitivity/vulnerability:

`nw:network-types/l3t:l3-unicast-topology/sr-mpls`

This subtree specifies the SR topology type. Modifying the configurations can make SR topology type invalid and cause interruption to all SR networks.

`/nw:networks/nw:network/l3t:l3-topology-attributes/sr`

This subtree specifies the topology-wide configurations, including the SRGB (Segment Routing Global Block). Modifying the configurations here can cause traffic disabled or rerouted in this topology and the connected topologies.

/nw:networks/nw:network/nw:node/l3t:l3-node-attributes

This subtree specifies the SR configurations for nodes. Modifying the configurations in this subtree can add, remove, or modify SR nodes, causing traffic disabled or rerouted in the specified nodes and the related TE topologies.

/nw:networks/nw:network/nt:link/l3t:l3-link-attributes/sr

This subtree specifies the configurations for SR Adjacency Segments. Modifying the configurations in this subtree can add, remove, or modify SR Adjacency Segments causing traffic disabled or rerouted on the specified SR adjacencies, the related nodes, and the related SR topologies.

Some of the readable data nodes in this YANG module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via get, get-config, or notification) to these data nodes. These are the subtrees and data nodes and their sensitivity/vulnerability:

nw:network-types/l3t:l3-unicast-topology/sr-mpls

Unauthorized access to this subtree can disclose the SR topology type.

/nw:networks/nw:network/l3t:l3-topology-attributes/sr

Unauthorized access to this subtree can disclose the topology-wide configurations, including the SRGB (Segment Routing Global Block).

/nw:networks/nw:network/nw:node/l3t:l3-node-attributes

Unauthorized access to this subtree can disclose the operational state information of the SR nodes.

/nw:networks/nw:network/nt:link/l3t:l3-link-attributes/sr

Unauthorized access to this subtree can disclose the operational state information of SR Adjacency Segments.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.

- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8341] Bierman, A. and M. Bjorklund, "Network Configuration Access Control Model", STD 91, [RFC 8341](#), DOI 10.17487/RFC8341, March 2018, <<https://www.rfc-editor.org/info/rfc8341>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [RFC8446] Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [RFC 8446](#), DOI 10.17487/RFC8446, August 2018, <<https://www.rfc-editor.org/info/rfc8446>>.

[7.2.](#) Informative References

- [RFC7951] Lhotka, L., "JSON Encoding of Data Modeled with YANG", [RFC 7951](#), DOI 10.17487/RFC7951, August 2016, <<https://www.rfc-editor.org/info/rfc7951>>.

- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [RFC8345] Clemm, A., Medved, J., Varga, R., Bahadur, N., Ananthakrishnan, H., and X. Liu, "A YANG Data Model for Network Topologies", [RFC 8345](#), DOI 10.17487/RFC8345, March 2018, <<https://www.rfc-editor.org/info/rfc8345>>.
- [RFC8346] Clemm, A., Medved, J., Varga, R., Liu, X., Ananthakrishnan, H., and N. Bahadur, "A YANG Data Model for Layer 3 Topologies", [RFC 8346](#), DOI 10.17487/RFC8346, March 2018, <<https://www.rfc-editor.org/info/rfc8346>>.
- [I-D.ietf-teas-yang-te-topo]
Liu, X., Bryskin, I., Beeram, V., Saad, T., Shah, H., and O. Dios, "YANG Data Model for Traffic Engineering (TE) Topologies", [draft-ietf-teas-yang-te-topo-22](#) (work in progress), June 2019.
- [I-D.ietf-spring-sr-yang]
Litkowski, S., Qu, Y., Lindem, A., Sarkar, P., and J. Tantsura, "YANG Data Model for Segment Routing", [draft-ietf-spring-sr-yang-13](#) (work in progress), July 2019.

Appendix A. Companion YANG Model for Non-NMDA Compliant Implementations

The YANG module `ietf-sr-topology` defined in this document is designed to be used in conjunction with implementations that support the Network Management Datastore Architecture (NMDA) defined in [\[RFC8342\]](#). In order to allow implementations to use the model even in cases when NMDA is not supported, the following companion module, `ietf-sr-topology-state`, is defined as state model, which mirrors the module `ietf-sr-topology` defined earlier in this document. However, all data nodes in the companion module are non-configurable, to represent the applied configuration or the derived operational states.

The companion module, `ietf-sr-topology-state`, is redundant and SHOULD NOT be supported by implementations that support NMDA.

As the structure of the companion module mirrors that of the cooresponding NMDA model, the YANG tree of the companion module is not depicted separately.

A.1. SR Topology State Module

```
<CODE BEGINS> file "ietf-sr-topology-state@2019-11-02.yang"
module ietf-sr-topology-state {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-sr-topology-state";
  prefix "srt-s";

  import ietf-sr-topology {
    prefix "srt";
  }
  import ietf-network-state {
    prefix "nw-s";
    reference "RFC 8345: A YANG Data Model for Network Topologies";
  }
  import ietf-network-topology-state {
    prefix "nt-s";
    reference "RFC 8345: A YANG Data Model for Network Topologies";
  }
  import ietf-l3-unicast-topology-state {
    prefix "l3t-s";
    reference "RFC 8346: A YANG Data Model for Layer 3 Topologies";
  }
  import ietf-segment-routing-common {
    prefix "sr-cmn";
    reference
      "I-D.ietf-spring-sr-yang: YANG Data Model for Segment Routing";
```



```
}
```

```
organization
```

```
"IETF Traffic Engineering Architecture and Signaling (TEAS)  
Working Group";
```

```
contact
```

```
"WG Web: <http://tools.ietf.org/wg/teas/>
```

```
WG List: <mailto:teas@ietf.org>
```

```
Editor: Xufeng Liu  
<mailto:xufeng.liu.ietf@gmail.com>
```

```
Editor: Igor Bryskin  
<mailto:Igor.Bryskin@huawei.com>
```

```
Editor: Vishnu Pavan Beeram  
<mailto:vbeeram@juniper.net>
```

```
Editor: Tarek Saad  
<mailto:tsaad@cisco.com>
```

```
Editor: Himanshu Shah  
<mailto:hshah@ciena.com>
```

```
Editor: Stephane Litkowski  
<mailto:stephane.litkowski@orange.com>";
```

```
description
```

```
"YANG data model for representing operational state information  
of Segment Routing Topologies, when NMDA is not supported.
```

```
Copyright (c) 2018 IETF Trust and the persons identified as  
authors of the code. All rights reserved.
```

```
Redistribution and use in source and binary forms, with or  
without modification, is permitted pursuant to, and subject to  
the license terms contained in, the Simplified BSD License set  
forth in Section 4.c of the IETF Trust's Legal Provisions  
Relating to IETF Documents  
(http://trustee.ietf.org/license-info).
```

```
This version of this YANG module is part of RFC XXXX; see the  
RFC itself for full legal notices.";
```

```
revision 2019-11-02 {
```

```
description "Initial revision";
```

```
reference
```



```
    "RFC XXXX: YANG Data Model for SR and SR TE Topologies";
}

augment "/nw-s:networks/nw-s:network/nw-s:network-types/"
  + "l3t-s:l3-unicast-topology" {
  description
    "Defines the SR topology type.";
  uses srt:sr-topology-type;
}

augment "/nw-s:networks/nw-s:network/"
  + "l3t-s:l3-topology-attributes" {
  when "../nw-s:network-types/l3t-s:l3-unicast-topology/"
    + "srt-s:sr-mpls" {
    description "Augment only for SR topology.";
  }
  description "Augment topology configuration";
  uses srt:sr-topology-attributes;
}

augment "/nw-s:networks/nw-s:network/nw-s:node/"
  + "l3t-s:l3-node-attributes" {
  when "../nw-s:network-types/l3t-s:l3-unicast-topology/"
    + "srt-s:sr-mpls" {
    description "Augment only for SR topology.";
  }
  description "Augment node configuration.";
  uses srt:sr-node-attributes;
}

augment "/nw-s:networks/nw-s:network/nw-s:node/"
  + "l3t-s:l3-node-attributes/l3t-s:prefix" {
  when "../nw-s:network-types/l3t-s:l3-unicast-topology/"
    + "srt-s:sr-mpls" {
    description "Augment only for SR topology.";
  }
  description "Augment node prefix.";
  uses srt:sr-node-prefix-attributes;
}

augment "/nw-s:networks/nw-s:network/nt-s:link/"
  + "l3t-s:l3-link-attributes" {
  when "../nw-s:network-types/l3t-s:l3-unicast-topology/"
    + "srt-s:sr-mpls" {
    description "Augment only for SR topology.";
  }
  description "Augment link configuration";
  uses srt:sr-link-attributes;
```



```

}


grouping sr-topology-attributes {
    description "SR topology scope attributes.";
    container sr {
        description
            "Containing SR attributes.";
        uses sr-cmn:srgb;
    } // sr
} // sr-topology-attributes
}

<CODE ENDS>

```

Appendix B. Data Tree Example

This section contains an example of an instance data tree in the JSON encoding [[RFC7951](#)]. The example instantiates "ietf-sr-topology" for the topology that is depicted in the following diagram.



The corresponding instance data tree is depicted below. Note that some lines have been wrapped to adhere to the 72-character line limitation of RFCs.


```
{
  "ietf-network:networks": {
    "network": [
      {
        "network-types": {
          "ietf-l3-unicast-topology:l3-unicast-topology": {
            "ietf-sr-topology:sr-mpls": {}
          }
        },
        "network-id": "sr-topo-example",
        "ietf-l3-unicast-topology:l3-topology-attributes": {
          "ietf-sr-topology:sr": {
            "srgb": [
              {
                "lower-bound": 16000,
                "upper-bound": 23999
              }
            ]
          }
        },
        "node": [
          {
            "node-id": "D1",
            "ietf-network-topology:termination-point": [
              {
                "tp-id": "1-0-1",
                "ietf-l3-unicast-topology:l3-termination-point-attributes": {
                  "unnumbered-id": 101
                }
              },
              {
                "tp-id": "1-2-1",
                "ietf-l3-unicast-topology:l3-termination-point-attributes": {
                  "unnumbered-id": 121
                }
              },
              {
                "tp-id": "1-3-1",
                "ietf-l3-unicast-topology:l3-termination-point-attributes": {
                  "unnumbered-id": 131
                }
              }
            ],
            "ietf-l3-unicast-topology:l3-node-attributes": {
              "router-id": ["203.0.113.1"],
              "prefix": [
                {
                  "prefix": "203.0.113.1/32",
```



```
        "ietf-sr-topology:sr": {
          "start-sid": 101,
          "range": 1,
          "is-local": false,
          "is-node": true
        }
      },
    ],
    "ietf-sr-topology:sr": {
      "srgb": [
        {
          "lower-bound": 16000,
          "upper-bound": 23999
        }
      ],
      "sr1b": [
        {
          "lower-bound": 15000,
          "upper-bound": 15999
        }
      ]
    }
  },
},
{
  "node-id": "D2",
  "ietf-network-topology:termination-point": [
    {
      "tp-id": "2-0-1",
      "ietf-l3-unicast-topology:l3-termination-point-attributes": {
        "unnumbered-id": 201
      }
    },
    {
      "tp-id": "2-1-1",
      "ietf-l3-unicast-topology:l3-termination-point-attributes": {
        "unnumbered-id": 211
      }
    },
    {
      "tp-id": "2-3-1",
      "ietf-l3-unicast-topology:l3-termination-point-attributes": {
        "unnumbered-id": 231
      }
    }
  ],
  "ietf-l3-unicast-topology:l3-node-attributes": {
    "router-id": ["203.0.113.2"],
```



```
    "prefix": [
      {
        "prefix": "203.0.113.2/32",
        "ietf-sr-topology:sr": {
          "start-sid": 102,
          "range": 1,
          "is-local": false,
          "is-node": true
        }
      }
    ],
    "ietf-sr-topology:sr": {
      "srgb": [
        {
          "lower-bound": 16000,
          "upper-bound": 23999
        }
      ],
      "sr1b": [
        {
          "lower-bound": 15000,
          "upper-bound": 15999
        }
      ]
    }
  },
  {
    "node-id": "D3",
    "ietf-network-topology:termination-point": [
      {
        "tp-id": "3-1-1",
        "ietf-l3-unicast-topology:l3-termination-point-attributes": {
          "unnumbered-id": 311
        }
      },
      {
        "tp-id": "3-2-1",
        "ietf-l3-unicast-topology:l3-termination-point-attributes": {
          "unnumbered-id": 321
        }
      }
    ],
    "ietf-l3-unicast-topology:l3-node-attributes": {
      "router-id": ["203.0.113.3"],
      "prefix": [
        {
          "prefix": "203.0.113.3/32",
```



```
        "ietf-sr-topology:sr": {
          "start-sid": 101,
          "range": 1,
          "is-local": false,
          "is-node": true
        }
      },
    ],
    "ietf-sr-topology:sr": {
      "srgb": [
        {
          "lower-bound": 16000,
          "upper-bound": 23999
        }
      ],
      "sr1b": [
        {
          "lower-bound": 15000,
          "upper-bound": 15999
        }
      ]
    }
  }
},
"ietf-network-topology:link": [
  {
    "link-id": "D1,1-2-1,D2,2-1-1",
    "source": {
      "source-node": "D1",
      "source-tp": "1-2-1"
    },
    "destination": {
      "dest-node": "D2",
      "dest-tp": "2-1-1"
    },
    "ietf-l3-unicast-topology:l3-link-attributes": {
      "metric1": "100",
      "ietf-sr-topology:sr": {
        "sid": 121,
        "is-local": true
      }
    }
  },
  {
    "link-id": "D2,2-1-1,D1,1-2-1",
    "source": {
      "source-node": "D2",
```



```
        "source-tp": "2-1-1"
      },
      "destination": {
        "dest-node": "D1",
        "dest-tp": "1-2-1"
      },
      "ietf-l3-unicast-topology:l3-link-attributes": {
        "metric1": "100",
        "ietf-sr-topology:sr": {
          "sid": 211,
          "is-local": true
        }
      }
    },
    {
      "link-id": "D1,1-3-1,D3,3-1-1",
      "source": {
        "source-node": "D1",
        "source-tp": "1-3-1"
      },
      "destination": {
        "dest-node": "D3",
        "dest-tp": "3-1-1"
      },
      "ietf-l3-unicast-topology:l3-link-attributes": {
        "metric1": "100",
        "ietf-sr-topology:sr": {
          "sid": 131,
          "is-local": true
        }
      }
    },
    {
      "link-id": "D3,3-1-1,D1,1-3-1",
      "source": {
        "source-node": "D3",
        "source-tp": "3-1-1"
      },
      "destination": {
        "dest-node": "D1",
        "dest-tp": "1-3-1"
      },
      "ietf-l3-unicast-topology:l3-link-attributes": {
        "metric1": "100",
        "ietf-sr-topology:sr": {
          "sid": 311,
          "is-local": true
        }
      }
    }
  ]
}
```



```
    }
  },
  {
    "link-id": "D2,2-3-1,D3,3-2-1",
    "source": {
      "source-node": "D2",
      "source-tp": "2-3-1"
    },
    "destination": {
      "dest-node": "D3",
      "dest-tp": "3-2-1"
    },
    "ietf-l3-unicast-topology:l3-link-attributes": {
      "metric1": "100",
      "ietf-sr-topology:sr": {
        "sid": 231,
        "is-local": true
      }
    }
  },
  {
    "link-id": "D3,3-2-1,D2,2-3-1",
    "source": {
      "source-node": "D3",
      "source-tp": "3-2-1"
    },
    "destination": {
      "dest-node": "D2",
      "dest-tp": "2-3-1"
    },
    "ietf-l3-unicast-topology:l3-link-attributes": {
      "metric1": "100",
      "ietf-sr-topology:sr": {
        "sid": 321,
        "is-local": true
      }
    }
  }
]
}
]
```


Appendix C. Contributors

Jeff Tantsura
Email: jefftant.ietf@gmail.com

Yingzhen Qu
Email: yingzhen.qu@huawei.com

Authors' Addresses

Xufeng Liu
Volta Networks

EMail: xufeng.liu.ietf@gmail.com

Igor Bryskin
Individual

EMail: i_bryskin@yahoo.com

Vishnu Pavan Beeram
Juniper Networks

EMail: vbeeram@juniper.net

Tarek Saad
Juniper Networks

EMail: tsaad@juniper.net

Himanshu Shah
Ciena

EMail: hshah@ciena.com

Stephane Litkowski
Cisco

EMail: slitkows.ietf@gmail.com

