

Telnet Authentication: Kerberos Version 4

Status of this Memo

This document is an Internet Draft. Internet Drafts are working documents of the Internet Engineering Task Force (IETF), its Areas, and its Working Groups. Note that other groups may also distribute working documents as Internet Drafts.

Internet Drafts are draft documents valid for a maximum of six months. Internet Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet Drafts as reference material or to cite them other than as a "working draft" or "work in progress."

Please check the `ltd-abstracts.txt` listing contained in the internet-drafts Shadow Directories on `nic.ddn.mil`, `nnsf.net`, `nic.nordu.net`, `ftp.nisc.sri.com`, or `munari.oz.au` to learn the current status of any Internet Draft.

1. Command Names and Codes

Authentication Types

KERBEROS_V4 1

Suboption Commands

AUTH	0
REJECT	1
ACCEPT	2
CHALLENGE	3
RESPONSE	4

2. Command Meanings

IAC SB AUTHENTICATION IS <authentication-type-pair> AUTH <kerberos ticket and authenticator> IAC SE

This is used to pass the Kerberos ticket to the remote side of the

connection. The first octet of the <authentication-type-pair> value is KERBEROS_V4, to indicate the usage of Kerberos version 4.

IAC SB AUTHENTICATION REPLY <authentication-type-pair> ACCEPT IAC SE

This command indicates that the authentication was successful.

IAC SB AUTHENTICATION REPLY <authentication-type-pair> REJECT <optional reason for rejection> IAC SE

This command indicates that the authentication was not successful, and if there is any more data in the sub-option, it is an ASCII text message of the reason for the rejection.

IAC SB AUTHENTICATION IS <authentication-type-pair> CHALLENGE <encrypted challenge> IAC SE

IAC SB AUTHENTICATION REPLY <authentication-type-pair> RESPONSE <encrypted response> IAC SE

These two commands are used to perform mutual authentication. They are only used when the AUTH_HOW_MUTUAL bit is set in the second octet of the authentication-type-pair. After successfully sending an AUTH and receiving an ACCEPT, a CHALLENGE is sent. The challenge is a random 8 byte number with the most significant byte first, and the least significant byte last. When the CHALLENGE command is sent, the "encrypted challenge" is the 8-byte-challenge encrypted in the session key. When the CHALLENGE command is received, the contents are decrypted to get the original 8-byte-challenge, this value is then incremented by one, re-encrypted with the session key, and returned as the "encrypted response" in the RESPONSE command. The receiver of the RESPONSE command decrypts the "encrypted response", and verifies that the resultant value is the original 8-byte-challenge incremented by one.

The "encrypted challenge" value sent/received in the CHALLENGE command is also encrypted with the session key on both sides of the session, to produce a random 8-byte key to be used as the default key for the ENCRYPTION option.

3. Implementation Rules

If the second octet of the authentication-type-pair has the AUTH_WHO bit set to AUTH_CLIENT_TO_SERVER, then the client sends the initial AUTH command, and the server responds with either ACCEPT or REJECT. In addition, if the AUTH_HOW bit is set to AUTH_HOW_MUTUAL, and the server responds with ACCEPT, then the client then sends a CHALLENGE, and the server sends a RESPONSE.

If the second octet of the authentication-type-pair has the AUTH_WHO

bit set to AUTH_SERVER_TO_CLIENT, then the server sends the initial AUTH command, and the client responds with either ACCEPT or REJECT. In addition, if the AUTH_HOW bit is set to AUTH_HOW_MUTUAL, and the client responds with ACCEPT, then the server then sends a CHALLENGE, and the client sends a RESPONSE.

The authenticator (Kerberos Principal) used is of the form "rcmd.host@realm".

4. Examples

User "joe" may wish to log in as user "pete" on machine "foo". If "pete" has set things up on "foo" to allow "joe" access to his account, then the client would send IAC SB AUTHENTICATION NAME "pete" IAC SE IAC SB AUTHENTICATION IS KERBEROS_V4 AUTH <joe's kerberos ticket> IAC SE The server would then authenticate the user as "joe" from the ticket information, and since "pete" is allowing "joe" to use his account, the server would send back ACCEPT. If mutual authentication is being used, the the client would send a CHALLENGE, and verify the RESPONSE that the server sends back.

Client	Server
	IAC DO AUTHENTICATION
IAC WILL AUTHENTICATION	
[The server is now free to request authentication information.	
]	
	IAC SB AUTHENTICATION SEND
	KERBEROS_V4 CLIENT MUTUAL
	KERBEROS_V4 CLIENT ONE_WAY IAC
	SE
[The server has requested mutual Version 4 Kerberos	
authentication. If mutual authentication is not supported,	
then the server is willing to do one-way authentication.	
The client will now respond with the name of the user that it	
wants to log in as, and the Kerberos ticket.]	
IAC SB AUTHENTICATION NAME	
"pete" IAC SE	
IAC SB AUTHENTICATION IS	
KERBEROS_V4 CLIENT MUTUAL AUTH	
<kerberos ticket information>	
IAC SE	
[The server responds with an ACCEPT command to state that the	
authentication was successful.]	
	IAC SB AUTHENTICATION REPLY
	KERBEROS_V4 CLIENT MUTUAL ACCEPT
	IAC SE

[Next, the client sends across a CHALLENGE to verify that it is really talking to the right server.]

```
IAC SB AUTHENTICATION IS
KERBEROS_V4 CLIENT|MUTUAL
CHALLENGE xx xx xx xx xx xx xx
xx IAC SE
```

[Lastly, the server sends across a RESPONSE to prove that it really is the right server.

```
IAC SB AUTHENTICATION REPLY
KERBEROS_V4 CLIENT|MUTUAL
RESPONSE yy yy yy yy yy yy yy yy
IAC SE
```

Author's Address

David A. Borman, Editor
Cray Research, Inc.
655F Lone Oak Drive
Eagan, MN 55123

Phone: (612) 452-6650

Mailing List: telnet-ietf@CRAY.COM
EMail: dab@CRAY.COM

Chair's Address

The working group can be contacted via the current chair:

Steve Alexander
INTERACTIVE Systems Corporation
1901 North Naper Boulevard
Naperville, IL 60563-8895

Phone: (708) 505-9100 x256
EMail: stevea@isc.com

