

Network Working Group
Internet Draft
Category: Experimental
<[draft-ietf-tewg-diff-te-mar-06.txt](#)>
Expiration Date: June 2005

Jerry Ash
AT&T

December, 2004

**Max Allocation with Reservation Bandwidth Constraints Model for
DiffServ-aware MPLS Traffic Engineering & Performance Comparisons**

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of RFC 3668](#).

Internet-Drafts are Working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/lid-abstracts.html>.

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

Copyright Notice

Copyright (C) The Internet Society (2004). All Rights Reserved.

Abstract

This document complements the DiffServ-aware MPLS TE (DS-TE) requirements document by giving a functional specification for the Maximum Allocation with Reservation (MAR) Bandwidth Constraints Model. Assumptions, applicability, and examples of the operation of the MAR Bandwidth Constraints Model are presented. MAR performance is analyzed relative to the criteria for selecting a Bandwidth Constraints Model, in order to provide guidance to user implementation of the model in their networks.

Table of Contents

1.	Introduction	3
2.	Definitions.	4
3.	Assumptions & Applicability	5
4.	Functional Specification of the MAR Bandwidth Constraints Model	6
5.	Setting Bandwidth Constraints	7
6.	Example of MAR Operation	7
7.	Summary	8
8.	Security Considerations	9
9.	Acknowledgments	9
10.	IANA Considerations	9
11.	Normative References	9
12.	Informative References	9
13.	Intellectual Property Considerations	10
14.	Authors' Addresses	11
Appendix A.	MAR Operation & Performance Analysis	11
Appendix B.	Bandwidth Prediction for Path Computation	17

Specification of Requirements

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

1. Introduction

DiffServ-aware MPLS traffic engineering (DS-TE) requirements and protocol extensions are specified in [[DSTE-REQ](#), [DSTE-PROTO](#)]. A requirement for DS-TE implementation is the specification of Bandwidth Constraints Models for use with DS-TE. The Bandwidth Constraints Model provides the 'rules' to support the allocation of bandwidth to individual class types (CTs). CTs are groupings of service classes in the DS-TE model, which are provided separate bandwidth allocations, priorities, and QoS objectives. Several CTs can share a common bandwidth pool on an integrated, multiservice MPLS/DiffServ network.

This document is intended to complement the DS-TE requirements document [[DSTE-REQ](#)] by giving a functional specification for the Maximum Allocation with Reservation (MAR) Bandwidth Constraints Model. Examples of the operation of the MAR Bandwidth Constraints Model are presented. MAR performance is analyzed relative to the criteria for selecting a Bandwidth Constraints Model, in order to provide guidance to user implementation of the model in their networks.

Two other Bandwidth Constraints Models are being specified for use in DS-TE:

- 1. Maximum Allocation Model (MAM) [MAM]** - the maximum allowable bandwidth usage of each CT is explicitly specified.
- 2. Russian Doll Model (RDM) [RDM]** - the maximum allowable bandwidth usage is done cumulatively by grouping successive CTs according to priority classes.

MAR is similar to MAM in that a maximum bandwidth allocation is given to each CT. However, through the use of bandwidth reservation and protection mechanisms, CTs are allowed to exceed their bandwidth allocations under conditions of no congestion but revert to their allocated bandwidths when overload and congestion occurs.

All Bandwidth Constraints Models should meet these objectives:

- 1. applies equally when preemption is either enabled or disabled** (when preemption is disabled, the model still works 'reasonably' well),
- 2. bandwidth efficiency, i.e., good bandwidth sharing among CTs** under both normal and overload conditions,
- 3. bandwidth isolation, i.e., a CT cannot hog the bandwidth of another CT** under overload conditions,
- 4. protection against QoS degradation, at least of the high-priority CTs** (e.g. high-priority voice, high-priority data, etc.), and
- 5. reasonably simple, i.e., does not require additional IGP extensions** and minimizes signaling load processing requirements.

In [Appendix A](#) modeling analysis is presented which shows that the MAR Model meets all these objectives, and provides good network performance

relative to MAM and full sharing models, under normal and abnormal operating conditions. It is demonstrated that MAR simultaneously achieves bandwidth efficiency, bandwidth isolation, and protection against QoS degradation without preemption.

In [Section 3](#) we give the assumptions and applicability, in [Section 4](#) a functional specification of the MAR Bandwidth Constraints Model, and in [Section 5](#) we give examples of its operation. In [Appendix A](#), MAR performance is analyzed relative to the criteria for selecting a Bandwidth Constraints Model, in order to provide guidance to user implementation of the model in their networks. In [Appendix B](#), bandwidth prediction for path computation is discussed.

2. Definitions

For readability a number of definitions from [[DSTE-REQ](#), [DSTE-PROTO](#)] are repeated here:

Traffic Trunk: an aggregation of traffic flows of the same class (i.e. which are to be treated equivalently from the DS-TE perspective) which are placed inside an LSP.

Class-Type (CT): the set of Traffic Trunks crossing a link that is governed by a specific set of Bandwidth constraints. CT is used for the purposes of link bandwidth allocation, constraint based routing and admission control. A given Traffic Trunk belongs to the same CT on all links.

Up to 8 CTs ($\text{MaxCT} = 8$) are supported. They are referred to as CT_c, $0 \leq c \leq \text{MaxCT}-1 = 7$. Each CT is assigned either a Bandwidth Constraint, or a set of Bandwidth Constraints. Up to 8 Bandwidth Constraints ($\text{MaxBC} = 8$) are supported and they are referred to as BC_c, $0 \leq c \leq \text{MaxBC}-1 = 7$.

TE-Class: A pair of: a) a CT, and b) a preemption priority allowed for that CT. This means that an LSP transporting a Traffic Trunk from that CT can use that preemption priority as the set-up priority, as the holding priority or both.

MAX_RESERVABLE_BW_k: maximum reservable bandwidth on link k specifies the maximum bandwidth that may be reserved; this may be greater than the maximum link bandwidth in which case the link may be oversubscribed [OSPF-TE].

BC_{ck}: bandwidth constraint for CT_c on link k = allocated (minimum guaranteed) bandwidth for CT_c on link k (see [Section 4](#)).

RBW_THRES_k: reservation bandwidth threshold for link k (see [Section 4](#)).

RESERVED_BW_{ck}: reserved bandwidth-in-progress on CT_c on link k ($0 \leq c \leq \text{MaxCT}-1$), RESERVED_BW_{ck} = total amount of the bandwidth reserved by all the established LSPs which belong to CT_c.

UNRESERVED_BWk: unreserved link bandwidth on link k specifies the amount of bandwidth not yet reserved for any CT, $UNRESERVED_BWk = MAX_RESERVABLE_BWk - \sum [RESERVED_BWck \ (0 \leq c \leq MaxCT-1)]$.

UNRESERVED_BWck: unreserved link bandwidth on CTc on link k specifies the amount of bandwidth not yet reserved for CTc, $UNRESERVED_BWck = UNRESERVED_BWk - \delta_{0/1}(CTck) * RBW-THRESk$

where

$\delta_{0/1}(CTck) = 0$ if $RESERVED_BWck < BCck$

$\delta_{0/1}(CTck) = 1$ if $RESERVED_BWck \geq BCck$

A number of recovery mechanisms under investigation in the IETF take advantage of the concept of bandwidth sharing across particular sets of LSPs. "Shared Mesh Restoration" in [GMPLS-RECOV] and "Facility-based Computation Model" in [MPLS-BACKUP] are example mechanisms which increase bandwidth efficiency by sharing bandwidth across backup LSPs protecting against independent failures. To ensure that the notion of RESERVED_BWck introduced in [DSTE-REQ] is compatible with such a concept of bandwidth sharing across multiple LSPs, the wording of the definition provided in [DSTE-REQ] is generalized. With this generalization, the definition is compatible with Shared Mesh Restoration defined in [GMPLS-RECOV], so that DS-TE and Shared Mesh Protection can operate simultaneously, under the assumption that Shared Mesh Restoration operates independently within each DS-TE Class-Type and does not operate across Class-Types. For example, backup LSPs protecting primary LSPs of CTc need to also belong to CTc; excess traffic LSPs sharing bandwidth with backup LSPs of CTc need to also belong to CTc.

3. Assumptions & Applicability

In general, DS-TE is a bandwidth allocation mechanism, for different classes of traffic allocated to various CTs (e.g., voice, normal data, best-effort data). Network operations functions such as capacity design, bandwidth allocation, routing design, and network planning are normally based on traffic measured load and forecast [ASH1].

As such, the following assumptions are made according to the operation of MAR:

- 1. connection admission control (CAC) allocates bandwidth for network flows/LSPs according to the traffic load assigned to each CT, based on traffic measurement and forecast.**
- 2. CAC could allocate bandwidth per flow, per LSP, per traffic trunk, or otherwise.** That is, no specific assumption is made on a specific CAC method, only that CT bandwidth allocation is related to the measured/forecast traffic load, as per assumption #1.
- 3. CT bandwidth allocation is adjusted up or down according to measured/forecast traffic load.** No specific time period is assumed for this adjustment, it could be short term (seconds, minutes, hours), daily, weekly, monthly, or otherwise.

4. Capacity management and CT bandwidth allocation thresholds (e.g., BCc) are designed according to traffic load, and are based on traffic measurement and forecast. Again, no specific time period is assumed for this adjustment, it could be short term (hours), daily, weekly, monthly, or otherwise.

5. No assumption is made on the order in which traffic is allocated to various CTs, again traffic allocation is assumed to be based only on

traffic load as it is measured and/or forecast.

6. If link bandwidth is exhausted on a given path for a flow/LSP/traffic trunk, alternate paths may be attempted to satisfy CT bandwidth allocation.

Note that the above assumptions are not unique to MAR, but are generic, common assumptions for all BC Models.

4. Functional Specification of the MAR Bandwidth Constraints Model

A DS-TE LSR implementing MAR MUST support enforcement of bandwidth constraints in compliance with the specifications in this Section.

In the MAR Bandwidth Constraints Model, the bandwidth allocation control for each CT is based on estimated bandwidth needs, bandwidth use, and status of links. The LER makes needed bandwidth allocation changes, and uses [RSVP-TE], for example, to determine if link bandwidth can be allocated to a CT. Bandwidth allocated to individual CTs is protected as needed but otherwise shared. Under normal non-congested network conditions, all CTs/services fully share all available bandwidth. When congestion occurs for a particular CTc, bandwidth reservation acts to prohibit traffic from other CTs from seizing the allocated capacity for CTc.

On a given link k , a small amount of bandwidth RBW_THRES_k , the reservation bandwidth threshold for link k , is reserved and governs the admission control on link k . Also associated with each CTc on link k are the allocated bandwidth constraints BC_{ck} to govern bandwidth allocation and protection. The reservation bandwidth on a link, RBW_THRES_k , can be accessed when a given CTc has bandwidth-in-use $RESERVED_BW_{ck}$ below its allocated bandwidth constraint BC_{ck} . However, if $RESERVED_BW_{ck}$ exceeds its allocated bandwidth constraint BC_{ck} , then the reservation bandwidth RBW_THRES_k cannot be accessed. In this way, bandwidth can be fully shared among CTs if available, but is otherwise protected by bandwidth reservation methods.

Bandwidth can be accessed for a bandwidth request = DBW for CTc on a given link k based on the following rules:

Table 1: Rules for Admitting LSP Bandwidth Request = DBW on Link k

For LSP on a high priority or normal priority CTc:

If $RESERVED_BW_{ck} \leq BC_{ck}$: admit if $DBW \leq UNRESERVED_BW_k$

If $RESERVED_BW_{ck} > BC_{ck}$: admit if $DBW \leq UNRESERVED_BW_k - RBW_THRES_k$;
or, equivalently:

If $DBW \leq UNRESERVED_BW_{ck}$, admit the LSP.

For LSP on a best-effort priority CTc:

allocated bandwidth $BC_{ck} = 0$;

DiffServ queuing admits BE packets only if there is available link

bandwidth.

The normal semantics of setup and holding priority are applied in the MAR Bandwidth Constraints Model, and cross-CT preemption is permitted when preemption is enabled.

Ash

<[draft-ietf-tewg-diff-te-mar-06.txt](#)>

[Page 6]

The bandwidth allocation rules defined in Table 1 are illustrated with an example in [Section 6](#) and simulation analysis in [Appendix A](#).

5. Setting Bandwidth Constraints

For a normal priority CT_c, the bandwidth constraints BC_{ck} on link k are set by allocating the maximum reservable bandwidth (MAX_RESERVABLE_BW_k) in proportion to the forecast or measured traffic load bandwidth TRAF_LOAD_BW_{ck} for CT_c on link k. That is:

$$\text{PROPORTIONAL_BW}_{ck} = \text{TRAF_LOAD_BW}_{ck} / [\text{sum } \{\text{TRAF_LOAD_BW}_{ck}, c=0, \text{MaxCT}-1\}] \times \text{MAX_RESERVABLE_BW}_k$$

For normal priority CT_c:

$$\text{BC}_{ck} = \text{PROPORTIONAL_BW}_{ck}$$

For a high priority CT, the bandwidth constraint BC_{ck} is set to a multiple of the proportional bandwidth. That is:

For high priority CT_c:

$$\text{BC}_{ck} = \text{FACTOR} \times \text{PROPORTIONAL_BW}_{ck}$$

where FACTOR is set to a multiple of the proportional bandwidth (e.g., FACTOR = 2 or 3 is typical). This results in some 'over-allocation' of the maximum reservable bandwidth, and gives priority to the high priority CTs. Normally the bandwidth allocated to high priority CTs should be a relatively small fraction of the total link bandwidth, a maximum of 10-15 percent being a reasonable guideline.

As stated in [Section 4](#), the bandwidth allocated to a best-effort priority CT_c should be set to zero. That is:

For best-effort priority CT_c:

$$\text{BC}_{ck} = 0$$

6. Example of MAR Operation

In the example, assume there are three class-types: CT₀, CT₁, CT₂. We consider a particular link with

$$\text{MAX-RESERVABLE_BW} = 100$$

And with the allocated bandwidth constraints set as follows:

$$\text{BC}_0 = 30$$

$$\text{BC}_1 = 20$$

$$\text{BC}_2 = 20$$

These bandwidth constraints are based on the normal traffic loads, as discussed in [Section 5](#). With MAR, any of the CTs is allowed to exceed

its bandwidth constraint BCc as long a there is at least RBW_THRES
(reservation bandwidth threshold on the link) units of spare bandwidth
remaining. Let's assume

RBW_THRES = 10

Ash

<[draft-ietf-tewg-diff-te-mar-06.txt](#)>

[Page 7]

So under overload, if

RESERVED_BW0 = 50
RESERVED_BW1 = 30
RESERVED_BW2 = 10

Therefore, for this loading

UNRESERVED_BW = 100 - 50 - 30 - 10 = 10

CT0 and CT1 can no longer increase their bandwidth on the link, since they are above their BC values and there is only RBW_THRES=10 units of spare bandwidth left on the link. But CT2 can take the additional bandwidth (up to 10 units) if the demand arrives, since it is below its BC value.

As also discussed in [Section 4](#), if best effort traffic is present, it can always seize whatever spare bandwidth is available on the link at the moment, but is subject to being lost at the queues in favor of the higher priority traffic.

Let's say an LSP arrives for CT0 needing 5 units of bandwidth (i.e., DBW = 5). We need to decide based on Table 1 whether to admit this LSP or not. Since for CT0

RESERVED_BW0 > BC0 (50 > 30), and
DBW > UNRESERVED_BW - RBW_THRES (i.e., 5 > 10 - 10)

Table 1 says the LSP is rejected/blocked.

Now let's say an LSP arrives for CT2 needing 5 units of bandwidth (i.e., DBW = 5). We need to decide based on Table 1 whether to admit this LSP or not. Since for CT2

RESERVED_BW2 < BC2 (10 < 20), and
DBW < UNRESERVED_BW (i.e., 5 < 10)

Table 1 says to admit the LSP.

Hence, in the above example, in the current state of the link and the current CT loading, CT0 and CT1 can no longer increase their bandwidth on the link, since they are above their BCc values and there is only RBW_THRES=10 units of spare bandwidth left on the link. But CT2 can take the additional bandwidth (up to 10 units) if the demand arrives, since it is below its BCc value.

[7. Summary](#)

The proposed MAR Bandwidth Constraints Model includes the following:

- 1. allocate bandwidth to individual CTs,**
- 2. protect allocated bandwidth by bandwidth reservation methods, as needed, but otherwise fully share bandwidth,**
- 3. differentiate high-priority, normal-priority, and best-effort priority services, and**

4. provide admission control to reject connection requests when needed to meet performance objectives.

Modeling results presented in [Appendix A](#) show that MAR bandwidth allocation a) achieves greater efficiency in bandwidth sharing while still providing bandwidth isolation and protection against QoS degradation, and b) achieves service differentiation for high-priority, normal-priority, and best-effort priority services.

8. Security Considerations

Security considerations related to the use of DS-TE are discussed in [\[DSTE-PROTO\]](#). Those apply independently of the Bandwidth Constraints Model, including MAR specified in this document.

9. Acknowledgements

DS-TE and Bandwidth Constraints Models have been an active area of discussion in the TEWG. I would like to thank Wai Sum Lai for his support and review of this draft. I also appreciate helpful discussions with Francois Le Faucheur.

10. IANA Considerations

[\[DSTE-PROTO\]](#) defines a new name space for "Bandwidth Constraints Model Id". The guidelines for allocation of values in that name space are detailed in Section 14 of [\[DSTE-PROTO\]](#). In accordance with these guidelines, IANA was requested to assign a Bandwidth Constraints Model Id for MAR from the range 0-127 (which is to be managed as per the "Specification Required" policy defined in [\[IANA-CONS\]](#)).

Bandwidth Constraints Model Id = TBD was allocated by IANA to MAR.

<IANA-note> To be removed by the RFC editor at the time of publication We request IANA to assign value 2 for the MAR model. Once the value has been assigned, please replace "TBD" above by the assigned value.
</IANA-note>

11. Normative References

[\[DSTE-REQ\]](#) Le Faucheur, F., Lai, W., et. al., "Requirements for Support of Diff-Serv-aware MPLS Traffic Engineering," [RFC 3564](#), July 2003.
[\[DSTE-PROTO\]](#) Le Faucheur, F., et. al., "Protocol Extensions for Support of Diff-Serv-aware MPLS Traffic Engineering," work in progress.
[\[KEY\]](#) Bradner, S., "Key words for Use in RFCs to Indicate Requirement Levels", [RFC 2119](#), March 1997.
[\[IANA-CONS\]](#) Narten, T., "Guidelines for Writing an IANA Considerations Section in RFCs," [RFC 2434](#), October 1998.

12. Informative References

[AKI] Akinpelu, J. M., "The Overload Performance of Engineered Networks with Nonhierarchical & Hierarchical Routing," BSTJ, Vol. 63, 1984.
[ASH1] Ash, G. R., "Dynamic Routing in Telecommunications Networks," McGraw-Hill, 1998.

Ash

<[draft-ietf-tewg-diff-te-mar-06.txt](#)>

[Page 9]

- [ASH2] Ash, G. R., et. al., "Routing Evolution in Multiservice Integrated Voice/Data Networks," Proceeding of ITC-16, Edinburgh, June 1999.
- [ASH3] Ash, G. R., "Performance Evaluation of QoS-Routing Methods for IP-Based Multiservice Networks," Computer Communications Magazine, May 2003.
- [BUR] Burke, P. J., Blocking Probabilities Associated with Directional Reservation, unpublished memorandum, 1961.
- [DSTE-PERF] Lai, W., "Bandwidth Constraints Models for DiffServ-TE: Performance Evaluation", work in progress.
- [E.360.1 --> E.360.7] ITU-T Recommendations, "QoS Routing & Related Traffic Engineering Methods for Multiservice TDM-, ATM-, & IP-Based Networks".
- [GMPLS-RECOV] Lang, J., et. al., "Generalized MPLS Recovery Functional Specification", work in progress.
- [KRU] Krupp, R. S., "Stabilization of Alternate Routing Networks", Proceedings of ICC, Philadelphia, 1982.
- [LAI] Lai, W., "Traffic Engineering for MPLS, Internet Performance and Control of Network Systems III Conference", SPIE Proceedings Vol. 4865, pp. 256-267, Boston, Massachusetts, USA, 29 July-1 August 2002 (<http://www.columbia.edu/~ffl15/waisum/bcmodel.pdf>).
- [MAM] Le Faucheur, F., Lai, W., "Maximum Allocation Bandwidth Constraints Model for Diff-Serv-aware MPLS Traffic Engineering", work in progress.
- [MPLS-BACKUP] Vasseur, J. P., et. al., "MPLS Traffic Engineering Fast Reroute: Bypass Tunnel Path Computation for Bandwidth Protection", work in progress.
- [MUM] Mummert, V. S., "Network Management and Its Implementation on the No. 4ESS, International Switching Symposium", Japan, 1976.
- [NAK] Nakagome, Y., Mori, H., Flexible Routing in the Global Communication Network, Proceedings of ITC-7, Stockholm, 1973.
- [OSPF-TE] Katz, D., et. al., "Traffic Engineering (TE) Extensions to OSPF Version 2," [RFC 3630](#), September 2003.
- [RDM] Le Faucheur, F., "Russian Dolls Bandwidth Constraints Model for Diff-Serv-aware MPLS Traffic Engineering", work in progress.
- [[RFC2026](#)] Bradner, S., "The Internet Standards Process -- Revision 3", [BCP 9](#), [RFC 2026](#), October 1996.
- [RSVP-TE] Awduche, D., et. al., "RSVP-TE: Extensions to RSVP for LSP Tunnels", [RFC 3209](#), December 2001.

13. Intellectual Property Considerations

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in BCP

[78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at

Ash

<[draft-ietf-tewg-diff-te-mar-06.txt](#)>

[Page 10]

<http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

14. Authors' Addresses

Jerry Ash
AT&T
Room MT D5-2A01
200 Laurel Avenue
Middletown, NJ 07748, USA
Phone: +1 732-420-4578
Email: gash@att.com

Appendix A. MAR Operation & Performance Analysis

A.1 MAR Operation

In the MAR Bandwidth Constraints Model, the bandwidth allocation control for each CT is based on estimated bandwidth needs, bandwidth use, and status of links. The LER makes needed bandwidth allocation changes, and uses [RSVP-TE], for example, to determine if link bandwidth can be allocated to a CT. Bandwidth allocated to individual CTs is protected as needed but otherwise shared. Under normal non-congested network conditions, all CTs/services fully share all available bandwidth. When congestion occurs for a particular CTc, bandwidth reservation acts to prohibit traffic from other CTs from seizing the allocated capacity for CTc. Associated with each CT is the allocated bandwidth constraint (BCc) to govern bandwidth allocation and protection, these parameters are illustrated with examples in this Appendix.

In performing MAR bandwidth allocation for a given flow/LSP, the LER first determines the egress LSR address, service-identity, and CT. The connection request is allocated an equivalent bandwidth to be routed on a particular CT. The LER then accesses the CT priority, QoS/traffic parameters, and routing table between the LER and egress LSR, and sets up the connection request using the MAR bandwidth allocation rules. The LER selects a first choice path and determines if bandwidth can be allocated on the path based on the MAR bandwidth allocation rules given in [Section 4](#). If the first choice path has insufficient bandwidth, the LER may then try alternate paths, and again applies the MAR bandwidth allocation rules now described.

MAR bandwidth allocation is done on a per-CT basis, in which aggregated CT bandwidth is managed to meet the overall bandwidth requirements of CT service needs. Individual flows/LSPs are allocated bandwidth in the

corresponding CT according to CT bandwidth availability. A fundamental principle applied in MAR bandwidth allocation methods is the use of bandwidth reservation techniques.

Bandwidth reservation gives preference to the preferred traffic by allowing it to seize idle bandwidth on a link more easily than the

non-preferred traffic. Burke [BUR] first analyzed bandwidth reservation behavior from the solution of the birth-death equations for the bandwidth reservation model. Burke's model showed the relative lost-traffic level for preferred traffic, which is not subject to bandwidth reservation restrictions, as compared to non-preferred traffic, which is subject to the restrictions. Bandwidth reservation protection is robust to traffic variations and provides significant dynamic protection of particular streams of traffic. It is widely used in large-scale network applications [ASH1, MUM, AKI, KRU, NAK].

Bandwidth reservation is used in MAR bandwidth allocation to control sharing of link bandwidth across different CTs. On a given link, a small amount of bandwidth RBW_THRES is reserved (say 1% of the total link bandwidth), and the reservation bandwidth can be accessed when a given CT has reserved bandwidth-in-progress RESERVED_BW below its allocated bandwidth BC. That is, if the available link bandwidth (unreserved idle link bandwidth UNRESERVED_BW) exceeds RBW_THRES, then any CT is free to access the available bandwidth on the link. However, if UNRESERVED_BW is less than RBW_THRES, then the CT can utilize the available bandwidth only if its current bandwidth usage is below the allocated amount BC. In this way, bandwidth can be fully shared among CTs if available, but is protected by bandwidth reservation if below the reservation level.

Through the bandwidth reservation mechanism, MAR bandwidth allocation also gives preference to high-priority CTs, in comparison to normal-priority and best-effort priority CTs.

Hence, bandwidth allocated to each CT is protected by bandwidth reservation methods, as needed, but otherwise shared. Each LER monitors CT bandwidth use on each CT, and determines if connection requests can be allocated to the CT bandwidth. For example, for a bandwidth request of DBW on a given flow/LSP, the LER determines the CT priority (high, normal, or best-effort), CT bandwidth-in-use, and CT bandwidth allocation thresholds, and uses these parameters to determine the allowed load state threshold to which capacity can be allocated. In allocating bandwidth DBW to a CT on given LSP, say A-B-E, each link in the path is checked for available bandwidth in comparison to the allowed load state. If bandwidth is unavailable on any link in path A-B-E, another LSP could be tried, such as A-C-D-E. Hence determination of the link load state is necessary for MAR bandwidth allocation, and two link load states are distinguished: available (non-reserved) bandwidth (ABW_STATE), and reserved-bandwidth (RBW_STATE). Management of CT capacity uses the link state and the allowed load state threshold to determine if a bandwidth allocation request can be accepted on a given CT.

[A.2 Analysis of MAR Performance](#)

In this Appendix, modeling analysis is presented in which MAR bandwidth allocation is shown to provide good network performance relative to full sharing models, under normal and abnormal operating conditions. A large-scale DiffServ-aware MPLS traffic engineering simulation model is used, in which several CTs with different priority classes share the pool of bandwidth on a multiservice, integrated voice/data network. MAR methods have also been analyzed in practice for TDM-based networks

[ASH1], and in modeling studies for IP-based networks [ASH2, ASH3, E.360].

All Bandwidth Constraints Models should meet these objectives:

- 1. applies equally when preemption is either enabled or disabled** (when preemption is disabled, the model still works 'reasonably' well),
- 2. bandwidth efficiency, i.e., good bandwidth sharing among CTs** under both normal and overload conditions,
- 3. bandwidth isolation, i.e., a CT cannot hog the bandwidth of another CT** under overload conditions,
- 4. protection against QoS degradation, at least of the high-priority CTs** (e.g. high-priority voice, high-priority data, etc.), and
- 5. reasonably simple, i.e., does not require additional IGP extensions** and minimizes signaling load processing requirements.

The use of any given Bandwidth Constraints Model has significant impacts on the performance of a network, as explained later. Therefore, the criteria used to select a model need to enable us to evaluate how a particular model delivers its performance, relative to other models. Lai [LAI, DSTE-PERF] has analyzed the MAM and RDM Models and provided valuable insights into the relative performance of these models under various network conditions.

In environments where preemption is not used, MAM is attractive because a) it is good at achieving isolation, and b) it achieves reasonable bandwidth efficiency with some QoS degradation of lower classes. When preemption is used, RDM is attractive because it can achieve bandwidth efficiency under normal load. However, RDM cannot provide service isolation under high load or when preemption is not used.

Our performance analysis of MAR bandwidth allocation methods is based on a full-scale, 135-node simulation model of a national network together with a multiservice traffic demand model to study various scenarios and tradeoffs [ASH3, E.360]. Three levels of traffic priority - high, normal, and best effort -- are given across 5 CTs: normal priority voice, high priority voice, normal priority data, high priority data, and best effort data.

The performance analyses for overloads and failures include a) the MAR Bandwidth Constraints Model, as specified in [Section 4](#), b) the MAM Bandwidth Constraints Model, and c) the No-DSTE Bandwidth Constraints Model.

The allocated bandwidth constraints for MAR are as described in [Section 5](#):

Normal priority CTs:	BCck = PROPORTIONAL_BWk,
High priority CTs:	BCck = FACTOR X PROPORTIONAL_BWk
Best-effort priority CTs:	BCck = 0

In the MAM Bandwidth Constraints Model, the bandwidth constraints for each CT are set to a multiple of the proportional bandwidth allocation:

Ash

[<draft-ietf-tewg-diff-te-mar-06.txt>](#)

[Page 13]

Normal priority CTs: $BC_{ck} = \text{FACTOR1} \times \text{PROPORTIONAL_Bwk}$,
 High priority CTs: $BC_{ck} = \text{FACTOR2} \times \text{PROPORTIONAL_Bwk}$
 Best-effort priority CTs: $BC_{ck} = 0$

Simulations show that for MAM, the sum (BCc) should exceed MAX_RESERVABLE_BWk for better efficiency, as follows:

- 1. The normal priority CTs the BCc values need to be over-allocated to** get reasonable performance. It was found that over-allocating by 100%, that is, setting FACTOR1 = 2, gave reasonable performance.
- 2. The high priority CTs can be over-allocated by a larger multiple** FACTOR2 in MAM and this gives better performance.

The rather large amount of over-allocation improves efficiency but somewhat defeats the 'bandwidth protection/isolation' needed with a BC Model, since one CT can now invade the bandwidth allocated to another CT. Each CT is restricted to its allocated bandwidth constraint BCck, which is the maximum level of bandwidth allocated to each CT on each link, as in normal operation of MAM.

In the No-DSTE Bandwidth Constraints Model, no reservation or protection of CT bandwidth is applied, and bandwidth allocation requests are admitted if bandwidth is available. Furthermore, no queuing priority is applied to any of the CTs in the No-DSTE Bandwidth Constraints Model.

Table 2 gives performance results for a six-times overload on a single network node at Oakbrook IL. The numbers given in the table are the total network percent lost (blocked) or delayed traffic. Note that in the focused overload scenario studied here, the percent lost/delayed traffic on the Oakbrook node is much higher than the network-wide average values given.

Table 2
Performance Comparison for MAR, MAM, & No-DSTE
Bandwidth Constraints (BC) Models

6X Focused Overload on Oakbrook (Total Network % Lost/Delayed Traffic)

Class Type	MAR BC Model	MAM BC Model	No-DSTE BC Model
NORMAL PRIORITY VOICE	0.00	1.97	10.30
HIGH PRIORITY VOICE	0.00	0.00	7.05
NORMAL PRIORITY DATA	0.00	6.63	13.30
HIGH PRIORITY DATA	0.00	0.00	7.05
BEST EFFORT PRIORITY DATA	12.33	11.92	9.65

Clearly the performance is better with MAR bandwidth allocation, and the results show that performance improves when bandwidth reservation is used. The reason for the poor performance of the No-DSTE Model, without bandwidth reservation, is due to the lack of protection of allocated

bandwidth. If we add the bandwidth reservation mechanism, then performance of the network is greatly improved.

The simulations showed that the performance of MAM is quite sensitive to the over-allocation factors discussed above. For example, if the BCc values are proportionally allocated with FACTOR1 = 1, then the results are much worse, as shown in Table 3:

Ash

<[draft-ietf-tewg-diff-te-mar-06.txt](#)>

[Page 14]

Table 3

Performance Comparison for MAM Bandwidth Constraints Model
with Different Over-allocation Factors

6X Focused Overload on Oakbrook (Total Network % Lost/Delayed Traffic)

Class Type	(FACTOR1 = 1)	(FACTOR1 = 2)
NORMAL PRIORITY VOICE	31.69	1.97
HIGH PRIORITY VOICE	0.00	0.00
NORMAL PRIORITY DATA	31.22	6.63
HIGH PRIORITY DATA	0.00	0.00
BEST EFFORT PRIORITY DATA	8.76	11.92

Table 4 illustrates the performance of the MAR, MAM, and No-DSTE Bandwidth Constraints Models for a high-day network load pattern with a 50% general overload. The numbers given in the table are the total network percent lost (blocked) or delayed traffic.

Table 4

Performance Comparison for MAR, MAM, & No-DSTE
Bandwidth Constraints (BC) Models

50% General Overload (Total Network % Lost/Delayed Traffic)

Class Type	MAR BC Model	MAM BC Model	No-DSTE BC Model
NORMAL PRIORITY VOICE	0.02	0.13	7.98
HIGH PRIORITY VOICE	0.00	0.00	8.94
NORMAL PRIORITY DATA	0.00	0.26	6.93
HIGH PRIORITY DATA	0.00	0.00	8.94
BEST EFFORT PRIORITY DATA	10.41	10.39	8.40

Again, we can see the performance is always better when MAR bandwidth allocation and reservation is used.

Table 5 illustrates the performance of the MAR, MAM, and No-DSTE Bandwidth Constraints Models for a single link failure scenario (3 OC-48). The numbers given in the table are the total network percent lost (blocked) or delayed traffic.

Table 5

Performance Comparison for MAR, MAM, & No-DSTE
Bandwidth Constraints (BC) Models

Single Link Failure (2 OC-48)

(Total Network % Lost/Delayed Traffic)

Class Type	MAR BC Model	MAM BC Model	No-DSTE BC Model
NORMAL PRIORITY VOICE	0.00	0.62	0.63
HIGH PRIORITY VOICE	0.00	0.31	0.32
NORMAL PRIORITY DATA	0.00	0.48	0.50

HIGH PRIORITY DATA	0.00	0.31	0.32
BEST EFFORT PRIORITY DATA	0.12	0.72	0.63

Again, we can see the performance is always better when MAR bandwidth allocation and reservation is used.

Ash

<[draft-ietf-tewg-diff-te-mar-06.txt](#)>

[Page 15]

Table 6 illustrates the performance of the MAR, MAM, and No-DSTE Bandwidth Constraints Models for a multiple link failure scenario (3 links with 3 OC-48, 3 OC-3, 4 OC-3 capacity, respectively). The numbers given in the table are the total network percent lost (blocked) or delayed traffic.

Table 6
Performance Comparison for MAR, MAM, & No-DSTE
Bandwidth Constraints (BC) Models
Multiple Link Failure
(3 Links with 2 OC-48, 2 OC-12, 1 OC-12, Respectively)
(Total Network % Lost/Delayed Traffic)

Class Type	MAR BC Model	MAM BC Model	No-DSTE BC Model
NORMAL PRIORITY VOICE	0.00	0.91	0.92
HIGH PRIORITY VOICE	0.00	0.44	0.44
NORMAL PRIORITY DATA	0.00	0.70	0.72
HIGH PRIORITY DATA	0.00	0.44	0.44
BEST EFFORT PRIORITY DATA	0.14	1.03	1.04

Again, we can see the performance is always better when MAR bandwidth allocation and reservation is used.

Lai's results [LAI, DSTE-PERF] show the trade-off between bandwidth sharing and service protection/isolation, using an analytic model of a single link. He shows that RDM has a higher degree of sharing than MAM. Furthermore, for a single link, the overall loss probability is the smallest under full sharing and largest under MAM, with RDM being intermediate. Hence, on a single link, Lai shows that the full sharing model yields the highest link efficiency and MAM the lowest, and that full sharing has the poorest service protection capability.

The results of the present study show that when considering a network context, in which there are many links and multiple-link routing paths are used, full sharing does not necessarily lead to maximum network-wide bandwidth efficiency. In fact, the results in Table 4 show that the No-DSTE Model not only degrades total network throughput, but also degrades the performance of every CT that should be protected. Allowing

more bandwidth sharing may improve performance up to a point, but can severely degrade performance if care is not taken to protect allocated bandwidth under congestion.

Both Lai's study and this study show that increasing the degree of bandwidth sharing among the different CTs leads to a tighter coupling between CTs. Under normal loading conditions, there is adequate capacity for each CT, which minimizes the effect of such coupling. Under overload conditions, when there is a scarcity of capacity, such coupling can

cause severe degradation of service, especially for the lower priority CTs.

Thus, the objective of maximizing efficient bandwidth usage, as stated in Bandwidth Constraints Model objectives, needs to be exercised with care. Due consideration needs to be given also to achieving bandwidth isolation under overload, in order to minimize the effect of

Ash

<[draft-ietf-tewg-diff-te-mar-06.txt](#)>

[Page 16]

interactions among the different CTs. The proper tradeoff of bandwidth sharing and bandwidth isolation needs to be achieved in the selection of a Bandwidth Constraints Model. Bandwidth reservation supports greater efficiency in bandwidth sharing while still providing bandwidth isolation and protection against QoS degradation.

In summary, the proposed MAR Bandwidth Constraints Model includes the following: a) allocate bandwidth to individual CTs, b) protect allocated bandwidth by bandwidth reservation methods, as needed, but otherwise fully share bandwidth, c) differentiate high-priority, normal-priority, and best-effort priority services, and d) provide admission control to reject connection requests when needed to meet performance objectives.

In the modeling results, the MAR Bandwidth Constraints Model compares favorably with methods that do not use bandwidth reservation. In particular, some of the conclusions from the modeling are as follows:

- o MAR bandwidth allocation is effective in improving performance over methods that lack bandwidth reservation and that allow more bandwidth sharing under congestion,
- o MAR achieves service differentiation for high-priority, normal-priority, and best-effort priority services,
- o bandwidth reservation supports greater efficiency in bandwidth sharing while still providing bandwidth isolation and protection against QoS degradation, and is critical to stable and efficient network performance.

[Appendix B](#). Bandwidth Prediction for Path Computation

As discussed in [[DSTE-PROTO](#)], there are potential advantages for a Head-end in trying to predict the impact of an LSP on the unreserved bandwidth when computing the path for the LSP. One example would be to perform better load-distribution of multiple LSPs across multiple paths. Another example would be to avoid CAC rejection when the LSP would no longer fit on a link after establishment.

Where such predictions are used on Head-ends, the optional Bandwidth Constraints sub-TLV and the optional Maximum Reservable Bandwidth sub-TLV MAY be advertised in the IGP. This can be used by Head-ends to predict how an LSP affects unreserved bandwidth values. Such predictions can be made with MAR by using the unreserved bandwidth values advertised by the IGP, as discussed in Sections [2](#) and [4](#):

$$\text{UNRESERVED_BWck} = \text{MAX_RESERVABLE_BWk} - \text{UNRESERVED_BWk} - \text{delta0/1(CTck)} * \text{RBW-THRESK}$$

where

$$\text{delta0/1(CTck)} = 0 \text{ if } \text{RESERVED_BWck} < \text{BCck}$$

$\text{delta0/1(CTck)} = 1$ if $\text{RESERVED_BWck} \geq \text{BCck}$

Furthermore, the following estimate can be made for RBW_THRESk :

$\text{RBW_THRESk} = \text{RBW_}\% * \text{MAX_RESERVABLE_BWk},$

Ash

<[draft-ietf-tewg-diff-te-mar-06.txt](#)>

[Page 17]

where RBW_% is a locally configured variable, which could take on different values for different link speeds. This information could be used in conjunction with the BC sub-TLV, MAX_RESERVABLE_BW sub-TLV, and UNRESERVED_BW sub-TLV to make predictions of available bandwidth on each link for each CT. Since admission control algorithms are left for vendor differentiation, predictions can only be performed effectively when the Head-end LSR predictions are based on the same (or a very close) admission control algorithm as used by other LSRs.

There may be occasional rejected LSPs when head-ends are establishing LSPs through a common link. As an example, consider some link L, and two head-ends H1 and H2. If only H1 or only H2 is establishing LSPs through L, then the prediction is accurate. But, if both H1 and H2 are establishing LSPs through L at the same time, then the prediction would not work perfectly. That is, the CAC will occasionally run into a rejected LSP on a link with such 'race' conditions. Also, as mentioned in [Appendix A](#), such prediction is optional and outside the scope of the document.

Full Copyright Statement

Copyright (C) The Internet Society (2004). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#) and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.