

TLS
Internet-Draft
Intended status: Standards Track
Expires: July 30, 2018

A. Ghedini
Cloudflare, Inc.
V. Vasiliev
Google
January 26, 2018

Transport Layer Security (TLS) Certificate Compression
draft-ietf-tls-certificate-compression-02

Abstract

In Transport Layer Security (TLS) handshakes, certificate chains often take up the majority of the bytes transmitted.

This document describes how certificate chains can be compressed to reduce the amount of data transmitted and avoid some round trips.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 30, 2018.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

Internet-Draft

TLS Certificate Compression

January 2018

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Notational Conventions	2
3.	Negotiating Certificate Compression	2
4.	Compressed Certificate Message	3
5.	Security Considerations	4
6.	Middlebox Compatibility	5
7.	IANA Considerations	5
7.1.	Update of the TLS ExtensionType Registry	5
7.2.	Update of the TLS HandshakeType Registry	5
7.3.	Registry for Compression Algorithms	5
8.	Normative References	6
Appendix A.	Acknowledgements	7
	Authors' Addresses	7

[1.](#) Introduction

In order to reduce latency and improve performance it can be useful to reduce the amount of data exchanged during a Transport Layer Security (TLS) handshake.

[RFC7924] describes a mechanism that allows a client and a server to avoid transmitting certificates already shared in an earlier handshake, but it doesn't help when the client connects to a server for the first time and doesn't already have knowledge of the server's certificate chain.

This document describes a mechanism that would allow certificates to be compressed during full handshakes.

[2.](#) Notational Conventions

The words "MUST", "MUST NOT", "SHALL", "SHOULD", and "MAY" are used in this document. It's not shouting; when they are capitalized, they have the special meaning defined in [[RFC2119](#)].

[3.](#) Negotiating Certificate Compression

This extension is only supported with TLS 1.3 and newer; if TLS 1.2

or earlier is negotiated, the peers MUST ignore this extension.

This document defines a new extension type (compress_certificate(TBD)), which can be used to signal the supported compression formats for the Certificate message to the

peer. Whenever it is sent by the client as a ClientHello message extension ([[I-D.ietf-tls-tls13](#)], Section 4.1.2), it indicates the support for compressed server certificates. Whenever it is sent by the server as a CertificateRequest extension ([[I-D.ietf-tls-tls13](#)], Section 4.3.2), it indicates the support for compressed client certificates.

By sending a compress_certificate extension, the sender indicates to the peer the certificate compression algorithms it is willing to use for decompression. The "extension_data" field of this extension SHALL contain a CertificateCompressionAlgorithms value:

```
enum {
    zlib(0),
    brotli(1),
    (255)
} CertificateCompressionAlgorithm;

struct {
    CertificateCompressionAlgorithm algorithms<1..2^8-1>;
} CertificateCompressionAlgorithms;
```

There is no ServerHello extension that the server is required to echo back.

[4.](#) Compressed Certificate Message

If the peer has indicated that it supports compression, server and client MAY compress their corresponding Certificate messages and send them in the form of the CompressedCertificate message (replacing the Certificate message).

The CompressedCertificate message is formed as follows:

```
struct {
    CertificateCompressionAlgorithm algorithm;
```

```
uint24 uncompressed_length;  
opaque compressed_certificate_message<1..2^24-1>;  
} CompressedCertificate;
```

algorithm The algorithm used to compress the certificate. The algorithm **MUST** be one of the algorithms listed in the peer's `compress_certificate` extension.

uncompressed_length The length of the Certificate message once it is uncompressed. If after decompression the specified length does not match the actual length, the party receiving the invalid

message **MUST** abort the connection with the "bad_certificate" alert.

compressed_certificate_message The compressed body of the Certificate message, in the same format as it would normally be expressed in. The compression algorithm defines how the bytes in the `compressed_certificate_message` field are converted into the Certificate message.

If the specified compression algorithm is `zlib`, then the Certificate message **MUST** be compressed with the ZLIB compression algorithm, as defined in [\[RFC1950\]](#). If the specified compression algorithm is `brotli`, the Certificate message **MUST** be compressed with the Brotli compression algorithm as defined in [\[RFC7932\]](#).

If the received `CompressedCertificate` message cannot be decompressed, the connection **MUST** be torn down with the "bad_certificate" alert.

If the format of the Certificate message is altered using the `server_certificate_type` extension [\[RFC7250\]](#), the resulting altered message is compressed instead.

[5.](#) Security Considerations

After decompression, the Certificate message **MUST** be processed as if it were encoded without being compressed. This way, the parsing and the verification have the same security properties as they would have in TLS normally.

Since certificate chains are typically presented on a per-server name or per-user basis, the attacker does not have control over any individual fragments in the Certificate message, meaning that they cannot leak information about the certificate by modifying the plaintext.

The implementations SHOULD bound the memory usage when decompressing the CompressedCertificate message.

The implementations MUST limit the size of the resulting decompressed chain to the specified uncompressed length, and they MUST abort the connection if the size exceeds that limit. TLS framing imposes 16777216 byte limit on the certificate message size, and the implementations MAY impose a limit that is lower than that; in both cases, they MUST apply the same limit as if no compression were used.

[6.](#) Middlebox Compatibility

It's been observed that a significant number of middleboxes intercept and try to validate the Certificate message exchanged during a TLS handshake. This means that middleboxes that don't understand the CompressedCertificate message might misbehave and drop connections that adopt certificate compression. Because of that, the extension is only supported in the versions of TLS where the certificate message is encrypted in a way that prevents middleboxes from intercepting it, that is, TLS version 1.3 [[I-D.ietf-tls-tls13](#)] and higher.

[7.](#) IANA Considerations

[7.1.](#) Update of the TLS ExtensionType Registry

Create an entry, `compress_certificate(TBD)`, in the existing registry for ExtensionType (defined in [[I-D.ietf-tls-tls13](#)]), with "TLS 1.3" column values being set to "CH, CR".

[7.2.](#) Update of the TLS HandshakeType Registry

Create an entry, `compressed_certificate(TBD)`, in the existing registry for `HandshakeType` (defined in [\[RFC5246\]](#)).

[7.3.](#) Registry for Compression Algorithms

This document establishes a registry of compression algorithms supported for compressing the Certificate message, titled "Certificate Compression Algorithm IDs", under the existing "Transport Layer Security (TLS) Extensions" heading.

The entries in the registry are:

Algorithm Number	Description
0	zlib
1	brotli
224 to 255	Reserved for Private Use

The values in this registry shall be allocated under "IETF Review" policy for values strictly smaller than 64, and under "Specification Required" policy otherwise (see [\[RFC8126\]](#) for the definition of relevant policies).

[8.](#) Normative References

[I-D.ietf-tls-tls13]

Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", [draft-ietf-tls-tls13-23](#) (work in progress), January 2018.

[RFC1950] Deutsch, P. and J-L. Gailly, "ZLIB Compressed Data Format Specification version 3.3", [RFC 1950](#), DOI 10.17487/RFC1950, May 1996, <https://www.rfc-editor.org/info/rfc1950>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997,

<<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC4366] Blake-Wilson, S., Nystrom, M., Hopwood, D., Mikkelsen, J., and T. Wright, "Transport Layer Security (TLS) Extensions", [RFC 4366](#), DOI 10.17487/RFC4366, April 2006, <<https://www.rfc-editor.org/info/rfc4366>>.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), DOI 10.17487/RFC5246, August 2008, <<https://www.rfc-editor.org/info/rfc5246>>.
- [RFC7250] Wouters, P., Ed., Tschofenig, H., Ed., Gilmore, J., Weiler, S., and T. Kivinen, "Using Raw Public Keys in Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS)", [RFC 7250](#), DOI 10.17487/RFC7250, June 2014, <<https://www.rfc-editor.org/info/rfc7250>>.
- [RFC7924] Santesson, S. and H. Tschofenig, "Transport Layer Security (TLS) Cached Information Extension", [RFC 7924](#), DOI 10.17487/RFC7924, July 2016, <<https://www.rfc-editor.org/info/rfc7924>>.
- [RFC7932] Alakuujala, J. and Z. Szabadka, "Brotli Compressed Data Format", [RFC 7932](#), DOI 10.17487/RFC7932, July 2016, <<https://www.rfc-editor.org/info/rfc7932>>.
- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 8126](#), DOI 10.17487/RFC8126, June 2017, <<https://www.rfc-editor.org/info/rfc8126>>.

[Appendix A](#). Acknowledgements

Certificate compression was originally introduced in the QUIC Crypto protocol, designed by Adam Langley and Wan-Teh Chang.

This document has benefited from contributions and suggestions from David Benjamin, Ryan Hamilton, Ilari Liusvaara, Piotr Sikora, Ian Swett, Martin Thomson, Sean Turner and many others.

Authors' Addresses

Alessandro Ghedini
Cloudflare, Inc.

Email: alessandro@cloudflare.com

Victor Vasiliev
Google

Email: vasilvv@google.com