

**Using OpenPGP keys for TLS authentication
draft-ietf-tls-openpgp-keys-07**

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on July 1, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This memo proposes extensions to the TLS protocol to support the OpenPGP trust model and keys. The extensions discussed here include a certificate type negotiation mechanism, and the required modifications to the TLS Handshake Protocol.

Table of Contents

1.	Introduction	3
2.	Extension Type	4
3.	Changes to the Handshake Message Contents	5
3.1.	Client Hello	5
3.2.	Server Hello	5
3.3.	Server Certificate	6
3.4.	Certificate request	7
3.5.	Client certificate	7
3.6.	Server key exchange	8
3.7.	Certificate verify	8
3.8.	Finished	8
4.	Cipher suites	9
5.	Security Considerations	10
6.	References	11
6.1.	Normative References	11
6.2.	Informative References	11
Appendix A.	Acknowledgements	12
	Author's Address	13
	Intellectual Property and Copyright Statements	14

1. Introduction

At the time of writing, TLS [[1](#)] uses the PKIX [[4](#)] infrastructure, to provide certificate services. Currently the PKIX protocols are limited to a hierarchical key management and as a result, applications which follow different - non hierarchical - trust models, like the "web of trust" model, could not be benefited by TLS.

OpenPGP keys (sometimes called OpenPGP certificates), provide security services for electronic communications. They are widely deployed, especially in electronic mail applications, provide public key authentication services, and allow distributed key management.

This document will extend the TLS protocol to support OpenPGP keys and trust model using the existing TLS cipher suites. In brief this would be achieved by adding a negotiation of the certificate type in addition to the normal handshake negotiations. Then the required modifications to the handshake messages, in order to hold OpenPGP keys as well, will be described. The the normal handshake procedure with X.509 certificates will not be altered, to preserve compatibility with existing TLS servers and clients.

This document uses the same notation used in the TLS Protocol specification.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#).

2. Extension Type

A new value, "cert_type(7)", is added to the enumerated ExtensionType, defined in TLSEXT [\[3\]](#). This value is used as the extension number for the extensions in both the client hello message and the server hello message. This new extension type will be used for certificate type negotiation.

3. Changes to the Handshake Message Contents

This section describes the changes to the TLS handshake message contents when OpenPGP keys are to be used for authentication.

3.1. Client Hello

In order to indicate the support of multiple certificate types clients will include an extension of type "cert_type" to the extended client hello message. The hello extension mechanism is described in TLSEXT [3].

This extension carries a list of supported certificate types the client can use, sorted by client preference. This extension MAY be omitted if the client only supports X.509 certificates. The "extension_data" field of this extension will contain a CertificateTypeExtension structure.

```
enum { client, server } ClientOrServerExtension;

enum { X.509(0), OpenPGP(1), (255) } CertificateType;

struct {
    select(ClientOrServerExtension) {
        case client:
            CertificateType certificate_types<1..2^8-1>;
        case server:
            CertificateType certificate_type;
    }
} CertificateTypeExtension;
```

3.2. Server Hello

Servers that receive an extended client hello containing the "cert_type" extension, and have chosen a cipher suite that supports certificates, then they MUST select a certificate type from the certificate_types field in the extended client hello, or terminate the connection with a fatal alert of type "unsupported_certificate".

The certificate type selected by the server, is encoded in a CertificateTypeExtension structure, which is included in the extended server hello message, using an extension of type "cert_type". Servers that only support X.509 certificates MAY omit including the "cert_type" extension in the extended server hello.

3.3. Server Certificate

The contents of the certificate message sent from server to client and vice versa are determined by the negotiated certificate type and the selected cipher suite's key exchange algorithm.

If the OpenPGP certificate type is negotiated then it is required to present an OpenPGP key in the Certificate message. The OpenPGP key must contain a public key that matches the selected key exchange algorithm, as shown below.

Key Exchange Algorithm	OpenPGP Key Type
RSA	RSA public key which can be used for encryption.
DHE_DSS	DSS public key.
DHE_RSA	RSA public key which can be used for signing.

An OpenPGP public key appearing in the Certificate message will be sent using the binary OpenPGP format. The term public key is used to describe a composition of OpenPGP packets to form a block of data which contains all information needed by the peer. This includes public key packets, user ID packets and all the fields described in "Transferable Public Keys" section in OpenPGP [2].

The option is also available to send an OpenPGP fingerprint, instead of sending the entire key. The process of fingerprint generation is described in OpenPGP [2]. The peer shall respond with a "certificate_unobtainable" fatal alert if the key with the given key fingerprint cannot be found. The "certificate_unobtainable" fatal alert is defined in [section 4](#) of TLSEXT [3].

If the key is not valid, expired, revoked, corrupt, the appropriate fatal alert message is sent from section A.3 of the TLS specification. If a key is valid and neither expired nor revoked, it is accepted by the protocol. The key validation procedure is a local matter outside the scope of this document.


```

enum {
    key_fingerprint (0), key (1), (255)
} PGPKKeyDescriptorType;

opaque PGPKKeyFingerprint<16..20>;

opaque PGPKKey<0..2^24-1>;

struct {
    PGPKKeyDescriptorType descriptorType;
    select (descriptorType) {
        case key_fingerprint: PGPKKeyFingerprint;
        case key: PGPKKey;
    }
} Certificate;

```

3.4. Certificate request

The semantics of this message remain the same as in the TLS specification. However the structure of this message has been modified for OpenPGP keys. The PGPCertificateRequest structure will only be used if the negotiated certificate type is OpenPGP.

```

enum {
    rsa_sign(1), dss_sign(2), (255)
} ClientCertificateParamsType;

struct {
    ClientCertificateParamsType certificate_params_types<1..2^8-1>;
} PGPCertificateRequest;

```

The certificate_params_types is a list of accepted client certificate parameter types, sorted in order of the server's preference.

3.5. Client certificate

This message is only sent in response to the certificate request message. The client certificate message is sent using the same formatting as the server certificate message and it is also required to present a certificate that matches the negotiated certificate type. If OpenPGP keys have been selected, and no key is available from the client, then a Certificate that contains an empty PGPKKey should be sent. The server may respond with a "handshake_failure" fatal alert if client authentication is required. This transaction follows the TLS specification.

3.6. Server key exchange

The server key exchange message for OpenPGP keys is identical to the TLS specification.

3.7. Certificate verify

The certificate verify message for OpenPGP keys is identical to the TLS specification.

3.8. Finished

The finished message for OpenPGP keys is identical to the description in the specification.

4. Cipher suites

No new cipher suites are required to use OpenPGP keys. OpenPGP keys can be combined with existing cipher suites defined in TLS [[1](#)], except the ones marked as "Exportable". Exportable cipher suites SHOULD NOT be used with OpenPGP keys.

5. Security Considerations

As with X.509 ASN.1 formatted keys, OpenPGP keys need specialized parsers. Care must be taken to make those parsers safe against maliciously modified keys, that could cause arbitrary code execution.

Security considerations about the use of the web of trust or the verification procedure are outside the scope of this document and they are considered an issue to be handled by local policy.

6. References

6.1. Normative References

- [1] Dierks, T. and C. Allen, "The TLS Protocol", [RFC 2246](#), January 1999.
- [2] Callas, J., Donnerhackle, L., Finey, H., and R. Thayer, "OpenPGP Message Format", [RFC 2440](#), November 1998.
- [3] Blake-Wilson, S., Nystrom, M., Hopwood, D., Mikkelsen, J., and T. Wright, "TLS Extensions", [RFC 3546](#), June 2003.

6.2. Informative References

- [4] Housley, R., Ford, W., Polk, W., and D. Solo, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 3280](#), April 2002.
- [5] "Recommendation X.509: The Directory - Authentication Framework", 1988.

[Appendix A](#). Acknowledgements

The author wishes to thank Werner Koch, David Taylor and Timo Schulz for their suggestions on improving this document.

Author's Address

Nikos Mavrogiannopoulos
Independent Consultant
Arkadias 8
Halandri, Attiki 15234
Greece

Email: nmav@gnutls.org

URI: <http://www.gnutls.org/>

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

