

Trade Working Group
INTERNET-DRAFT

June 2002
Masayuki Terada
Ko Fujimura
NTT

Expires: December 2002

Voucher Trading System Application Programming Interface (VTS-API)
<draft-ietf-trade-vtsapi-02.txt>

Status of This Document

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at
<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at
<http://www.ietf.org/shadow.html>.

Distribution of this document is unlimited. Please send comments to the TRADE working group at <ietf-trade@lists.elistx.com>, which may be joined by sending a message with subject "subscribe" to <ietf-trade-request@lists.elistx.com>.

Discussions of the TRADE working group are archived at
<http://lists.elistx.com/archives/ietf-trade>.

Abstract

This document specifies the Voucher Trading System Application Programming Interface (VTS-API). The VTS-API allows a wallet or other application to issue, transfer, and redeem vouchers in a uniform manner independent of the VTS implementation. The VTS is a system to securely transfer vouchers, e.g., coupons, tickets, loyalty points, and gift certificates; this process is often necessary in the course of payment and/or delivery transactions.

Acknowledgements

The following persons, in alphabetic order, contributed substantially to the material herein:

Donald Eastlake 3rd
 Iguchi Makoto
 Yoshitaka Nakamura
 Ryuji Shoda

Table of Contents

Status of this Memo	1
Abstract	1
Acknowledgements	2
1. Introduction	3
2. Processing Model	4
3. Design Overview	5
4. Concepts	5
5. Interface Definitions	7
5.1 VTSManger	7
5.1.1 getParticipantRepository	7
5.1.2 getVoucherComponentRepository	7
5.2 ParticipantRepository	7
5.2.1 lookup	8
5.3 Participant	8
5.3.1 getIdentifier	8
5.3.2 getVTSAgent	9
5.4 VTSAgent	9
5.4.1 login	9
5.4.2 logout	10
5.4.3 prepare	10
5.4.4 issue	11
5.4.5 transfer	12
5.4.6 consume	12
5.4.7 present	13
5.4.8 cancel	14
5.4.9 resume	14
5.4.10 create	15
5.4.11 delete	15
5.4.12 getContents	15
5.4.13 getSessions	16
5.4.14 getLog	16
5.4.15 addReceptionListener	17
5.4.16 removeReceptionListener	17
5.5 Session	17
5.5.1 getIdentifier	17
5.5.2 getVoucher	18

5.5.3	getSender	18
5.5.4	getReceiver	18
5.5.5	isPrepared	18
5.5.6	isActivated	19

5.5.7	isSuspended	19
5.5.8	isCompleted	19
5.6	Voucher	19
5.6.1	getIssuer	19
5.6.2	getPromise	19
5.6.3	getCount	20
5.7	VoucherComponentRepository	20
5.7.1	register	20
5.8	VoucherComponent	21
5.8.1	getIdentifier	21
5.8.2	getDocument	21
5.9	ReceptionListener	22
5.9.1	arrive	22
5.10	Exceptions	22
6.	Example Code	23
7.	Security Considerations	24
8.	References	25
9.	Author's Address	25
	Full Copyright Statement	26

[1. Introduction](#)

This document specifies the Voucher Trading System Application Programming Interface (VTS-API). The motivation and background of the Voucher Trading System (VTS) are described in Requirements for Generic Voucher Trading [[VTS](#)].

A voucher is a logical entity that represents a certain right and is logically managed by the VTS. A voucher is generated by the issuer, traded among users, and finally collected using VTS. The terminology and model of the VTS are also described in [[VTS](#)].

The VTS-API allows a caller application to issue, transfer, and redeem vouchers in a uniform manner independent of the VTS implementation. Several attempts have been made at providing a generic payment API. Java Commerce Client [[JCC](#)] and Generic Payment Service Framework [[GPSF](#)], for example, introduce a modular wallet architecture that permits diverse types of payment modules to be added as plug-ins and supports both check-like/cash-like payment models. This document is inspired by these approaches but the scope of this document is limited to the VTS model, in which cash-like payment model is assumed and vouchers are directly or indirectly transferred between sender (transferor) and receiver (transferee) via the VTS. This document is not intended to support API for SET, e-check or other payment schemes that do not fit the VTS model.

Unlike the APIs provided in JCC and GPSF, which are designed to transfer only monetary values, this API enables the transfer of a wide-range of values through the use of XML-based Generic Voucher

Language [[GVL](#)]. The monetary meaning of the voucher is interpreted by the upper application layer using the information described in the language. This approach makes it possible to provide a simpler API in the voucher-transfer layer and enhances runtime efficiency.

The API specification in this document is described in the Java language syntax. Bindings for other programming languages may be completed in a future version of this document or separate related specifications.


The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC 2119](#)]

2. Processing Model

This section provides the processing model in which the VTS-API is used. Most of the text in this section has been taken from the Generic Voucher Language specification [[GVL](#)].

There are several ways of implementing VTS. For discount coupons or event tickets, for example, the smart-card-based decentralized offline VTS is often preferred, whereas for bonds or securities, the centralized online VTS is preferred. It is impractical to define standard protocols for issuing, transferring, or redeeming vouchers at this moment.

To provide implementation flexibility, this document assumes a modular wallet architecture that allows multiple VTS to be added as plug-ins. In this architecture, instead of specifying a standard voucher transfer protocol, two specifications, i.e., Voucher Component and VTS-API specifications, are standardized (Figure 1).



(*1) Registration is optional. Note also that the VTS plug-ins are usually pre-registered when the wallet or collecting system is started.

(*2) If a listener is registered.

Figure 1. Wallet architecture with VTS plug-ins

After sender and receiver agree on what vouchers are to be traded and which VTS is to be used, the issuing system or wallet system requests the corresponding VTS plug-in to permit the issue, transfer, or redeem transactions to be performed via the VTS-API. The VTS then rewrites the ownership of the vouchers using the VTS-specific protocol. Finally, a completion event is sent to the wallet systems or issuing/collecting systems.

This document describes the VTS-API specification. See [[GVL](#)] for the Voucher Component specification.

3. Design Overview

We have adopted the following approach to specify the VTS-API.

- 1) Provide an abstract and uniform API that encapsulates the VTS implementation. For example, a common API is provided for both centralized and decentralized VTS. It brings more freedom of VTS selection for issuers and application developers.
- 2) To provide an abstract and uniform API, this document introduces an interface called VTSAgent that is associated with a holder and provides methods to manipulate vouchers held by its holder. Vouchers are accessed through the methods provided by the VTSAgent.
- 3) Use existing standards for the VTS branding mechanism (negotiation). This document assumes that the VTS to be used for sending a voucher has settled before calling the VTS-APIs. Negotiation can be done within the upper application layer using other standards, e.g., [[IOTP](#)] or [[ECML](#)], if necessary.
- 4) Support only push-type voucher transfer interface in which voucher transfer session is initiated by the transferor side. Pull-type voucher transfer interface can be implemented on top of the push-type VTS interface at application level.

4. Concepts

The VTS-API consists of the following interfaces. A VTS is required to implement all of the interfaces except ReceptionLister, which is intended to be implemented by wallets or other applications that use VTS.

VTSTManager

Provides the starting point to use a VTS plug-in. All of the objects needed to manipulate vouchers can be directly or indirectly acquired via the VTSManger. A VTSManger maintains the two

repositories; a ParticipantRepository and a VoucherComponentRepository described below.

ParticipantRepository

Provides the access points of Participants, which are to be trading partners. A ParticipantRepository maintains Participants and acts as an "address book" of trading partners.

Participant

Represents a participant (such as issuers, holders, and collectors). A Participant knows how to obtain the corresponding VTSAgent described below.

VTSAgent (extends Participant)

Provides the access point of vouchers in Valid Voucher Set (VVS) that is logically managed by VTS. A VTSAgent provides a means of manipulating vouchers held by its holder; basic trading methods, i.e., issue, transfer, consume, and present. Before calling trading methods, the application must create a Session which is described below.

Session

Represents the logical connection established by the trade. A Session has references to two Participants, i.e., the sender and the receiver. After trading methods are called using a Session, the Session holds a reference to the Vouchers to be traded.

Voucher

Represents one or more vouchers of which all of the issuer part and promise part of vouchers are the same. A Voucher holds references to the Participant (issuer) who issued the voucher and a VoucherComponent (promise) which is described below.

VoucherComponent

Represents a Voucher Component described in [\[GVL\]](#). It defines the promise part of the voucher.

VoucherComponentRepository

Provides the access points of VoucherComponents. A VoucherComponentRepository maintains VoucherComponents and acts as a "voucher type book" managed by the VTS. This document assumes that a set of VoucherComponents has been acquired and stored in this repository. Delivery of VoucherComponents is beyond the scope of this

document. It may be delivered within the VTS from the trading partners or manually acquired from a trusted third party (See [Section 3](#) of [[GVL](#)]).

ReceptionListener

Provides a listener function with regard to the receipt of a voucher by VTSAgent to wallets or other applications that implement this interface. (This interface may not be implemented as part of VTS)

5. Interface Definitions

The interfaces defined in this document reside in the package named "org.ietf.vts". Wallets or other applications that use this API, should import this package as "import org.ietf.vts.*;".

5.1 VTSManger

```
public interface VTSManger
```

Provides the starting point to use a VTS plug-in.

All of the objects needed to manipulate vouchers can be directly or indirectly acquired via a VTSManger, so that wallets or other applications can make the VTS available by instantiating an object implementing this interface.

A class that implements the VTSManger interface must have a public default constructor (a constructor without any parameters). The VTS provides a name for such constructor so that the implementation class can bootstrap the interface.

5.1.1 getParticipantRepository

```
public ParticipantRepository getParticipantRepository()
```

Returns a repository that maintains Participants.

Returns:

the ParticipantRepository of the VTS, or null if no ParticipantRepository is available.

5.1.2 getVoucherComponentRepository

```
public VoucherComponentRepository getVoucherComponentRepository()
```

Returns a repository that maintains VoucherComponents.

Returns:

the VoucherComponentRepository of the VTS, or null if no VoucherComponentRepository is available.

5.2 ParticipantRepository


```
public interface ParticipantRepository
```

Provides the access points of Participants. A ParticipantRepository maintains Participants and acts as an "address book" of trading partners.

The object implementing this interface maintains Participants (or holds a reference to an object maintaining Participants), which are to be trading partners.

The implementation of ParticipantRepository may be either (an adaptor to) "yellow pages" which is a network-wide directory service like LDAP, or "pocket address book" which maintains only personal acquaintances.

5.2.1 lookup

```
public Participant lookup(String id)
```

Retrieves the participant that has the specified id.

Returns:

the participant associated with the specified id or null if the id is null or the corresponding participant cannot be found.

5.3 Participant

```
public interface Participant
```

Represents the participants (such as issuers, holders, and collectors).

This interface is used as representation of the trade partners and issuers of vouchers. Anyone can retrieve objects implementing Participant from the participant repository.

5.3.1 getIdentifier

```
public String getIdentifier()
```

Returns the identifier of the participant. Each participant must have a unique identifier.

The identifier can be used for looking up and retrieving the participant via the ParticipantRepository.

The format of the identifier is implementation-specific.

Returns:

the identifier string of the participant.

[5.3.2](#) getVTSAgent

VTSAgent getVTSAgent()

Returns a VTSAgent, whose identifier is the same as the identifier of the participant.

Returns:

an object implementing VTSAgent.

[5.4](#) VTSAgent

public interface VTSAgent extends Participant

Represents contact points to access vouchers in Valid Voucher Set (VVS) that is managed by the VTS.

Each VTSAgent is associated with a holder and provides a means for managing vouchers owned by the holder. The holder must be authenticated using the login() method before being called by any other method, or VTSSecurityException will be issue.

Before calling any trading method, i.e., issue(), transfer(), consume(), and present(), the application must establish a session by the prepare() method.

Sessions may often be suspended due to network failure when the voucher is sent via a network. The suspended sessions can be restarted by the resume() method. Details on the state management of a session are described in [Section 5.5](#).

Some VTSAgents may not have all of the trading methods; a voucher collecting system doesn't require its VTSAgent to provide method for issuing or creating vouchers. A VTSAgent returns FeatureNotAvailableException when an unsupported method is invoked.

[5.4.1](#) login

public void login(String passphrase)
throws VTSEException

Authenticates the VTSAgent. The passphrase is specified if the VTS requires it for authentication, otherwise it must be null. Nothing is performed if the VTSAgent has already been logged-in. The authentication scheme is implementation-specific. Examples of the implementation are as follows:

- 1) Vouchers are managed on a remote centralized server (central VVS), and the server requires a password to login. In this case, the

application may prompt the user to input the password and can be given to the VTSAgent through this method.

- 2) Vouchers are managed on a remote centralized server (central VVS); they require challenge-and-response authentication using smartcards held by users. In this case, the passphrase may be null since access to the smartcard can be done without contacting the application or user, i.e., the VTSAgent receives the challenge from the server, sends the challenge to the smartcard (within the VTS), and returns the response from the smartcard to the server. Note that a PIN to unlock the smartcard may be given through this method depending on the implementation.
- 3) Each user holds their own smartcard in which their own vouchers are stored (decentralized VVS). In this case, the passphrase may be null since no authentication is required. Note that a PIN to unlock the smartcard may be given through this depends on the implementation.

Throws:

VTSSecurityException - if authentication fails.

5.4.2 logout

```
public void logout()  
    throws VTSEException
```

Voids the authentication performed by the login() method.

After calling this method, calling any other method (except login()) will cause VTSSecurityException.

The VTSAgent can login again by the login() method.

Throws:

VTSSecurityException - if the VTSAgent is not authenticated correctly.

5.4.3 prepare

```
public Session prepare(Participant receiver)  
    throws VTSEException
```

Establishes a session that is required for trading vouchers. The trading partner who receives the vouchers is specified as receiver. The vouchers to be traded will be specified later (when a trading method is called).

The establishment of a session is implementation-specific. An implementation that has a central VVS may start a transaction, while other implementations that have decentralized VVS may get, from the

receiver, the challenge needed to authenticate the sender during the establishment of the session.

If the VTSAgent has no ability to establish a session with the specified receiver (permanent error), the VTSAgent throws an `InvalidParticipantException`. If the VTSAgent can not establish a session due to network failure (transient error), the VTSAgent throws a `CannotProceedException`.

Parameters:

receiver - the trading partner who receives vouchers.

Returns:

an established session whose state is "prepared" (see [Section 5.5](#)).

Throws:

`CannotProceedException` - if the preparation of the session is aborted (e.g. network failures).

`FeatureNotAvailableException` - if the VTSAgent does not provide any trading methods.

`InvalidParticipantException` - if the specified participant is invalid.

`VTSSecurityException` - if the VTSAgent cannot be authenticated correctly.

[5.4.4](#) issue

```
public void issue(Session session,
                  VoucherComponent promise,
                  java.lang.Number num)
    throws VTSException
```

Issues vouchers. This method creates the specified number of vouchers <this, promise, receiver> and adds them to the VVS. Note that receiver is specified when the `prepare()` method is called. Nothing is performed if the specified number is 0.

The session MUST be "prepared" when calling this method. The state of the session will be "activated" when the vouchers are created, and it will be "completed" when the transaction is successfully completed or "suspended" if the transaction is interrupted abnormally (e.g., network failures).

Parameters:

session - the session used by the issue transaction.

promise - the promise part of the voucher.

num - the number of vouchers to be issued.

Throws:

CannotProceedException - if the transaction cannot be successfully completed.

FeatureNotAvailableException - if the VTSAgent does not provide a means of issuing vouchers.

InvalidStateException - if the session is not "prepared".

VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

5.4.5 transfer

```
public void transfer(Session session,
                    Participant issuer,
                    VoucherComponent promise,
                    java.lang.Number num)
    throws VTSEException
```

Transfers vouchers. This method rewrites the specified number of vouchers <issuer, promise, this> to <issuer, promise, receiver> in the VVS. Note that receiver is specified when the prepare() method is called. The VTSAgent must have sufficient vouchers in the VVS. Nothing is performed if the specified number is 0.

The session MUST be "prepared" when calling this method. The state of the session will be "activated" when the voucher are retrieved from the sender, and it will be "completed" when the transaction is successfully completed or "suspended" if the transaction is interrupted abnormally (e.g., network failures).

If null is specified for the issuer parameter, it indicates "any issuer". This method selects vouchers to be transferred from the set of vouchers returned by the getContents(null, promise).

Parameters:

session - the session used by the transfer transaction.
issuer - the issuer part of the voucher, or null.
promise - the promise part of the voucher.
num - the number of vouchers to be transferred.

Throws:

CannotProceedException - if the transaction cannot be successfully completed.
FeatureNotAvailableException - if the VTSAgent does not provide a means of transferring vouchers.
InsufficientVoucherException - if the VTSAgent doesn't have a sufficient number of vouchers to transfer.
InvalidStateException - if the session is not "prepared".
VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

5.4.6 consume

```
public void consume(Session session,  
                    Participant issuer,
```

M. Terada, K. Fujimura

[Page 12]


```
VoucherComponent promise,  
    java.lang.Number num)  
    throws VTSEException
```

Consumes vouchers. This method deletes the specified number of specified vouchers <issuer, promise, this> from the VVS. The VTSAgent must have sufficient vouchers in the VVS. Nothing is performed if the specified number is 0.

The session MUST be "prepared" when calling this method. The state of the session will be "activated" when the vouchers are deleted, and it will be "completed" when the transaction is successfully completed or "suspended" if the transaction is interrupted abnormally (e.g., network failures).

If null is specified for the issuer parameter, it indicates "any issuer". This method selects vouchers to be consumed from the set of vouchers returned by the `getContents(null, promise)`.

Parameters:

session - the session used by the consume transaction.
issuer - the issuer part of the voucher, or null.
promise - the promise part of the voucher.
num - the number of vouchers to be consumed.

Throws:

CannotProceedException - if the transaction cannot be successfully completed.
FeatureNotAvailableException - if the VTSAgent does not provide a means of consuming vouchers.
InsufficientVoucherException - if the VTSAgent doesn't have a sufficient number of vouchers to consume.
InvalidStateException - if the session is not "prepared".
VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

[5.4.7](#) present

```
public void present(Session session,  
    Participant issuer,  
    VoucherComponent promise,  
    java.lang.Number num)  
    throws VTSEException
```

Presents vouchers. This method shows that the sender has the specified number of vouchers <issuer, promise, this> in the VVS to the receiver of the session; No modification is performed to the VVS. The VTSAgent must have a sufficient vouchers in the VVS. Nothing

is performed if the specified number is 0.

The session MUST be "prepared" when calling this method. The state

of the session will be "activated" when the vouchers are retrieved, and it will be "completed" when the transaction is successfully completed or "suspended" if the transaction is interrupted abnormally (e.g., by network failures).

If null is specified for the issuer parameter, it indicates "any issuer". This method selects vouchers to be presented from the set of vouchers returned by the `getContents(null, promise)`.

Parameters:

session - the session used by the present transaction.
issuer - the issuer part of the voucher, or null.
promise - the promise part of the voucher.
num - the number of the voucher to be presented.

Throws:

`CannotProceedException` - if the transaction cannot be successfully completed.
`InsufficientVoucherException` - if the `VTSAgent` doesn't have a sufficient number of vouchers to present.
`InvalidStateException` - if the session is not "prepared".
`FeatureNotAvailableException` - if the `VTSAgent` does not provide a means of presenting vouchers.
`VTSSecurityException` - if the `VTSAgent` cannot be authenticated correctly.

[5.4.8](#) **cancel**

```
public void cancel(Session session)
    throws VTSEException
```

Releases the session. "Prepared" sessions MUST be canceled. An implementation MAY be permitted to cancel "activated" or "suspended" sessions.

Throws:

`InvalidStateException` - if the state of the session isn't cancelable.
`VTSSecurityException` - if the `VTSAgent` cannot be authenticated correctly.

[5.4.9](#) **resume**

```
public void resume(Session session)
    throws VTSEException
```

Restarts the session. Only "suspended" sessions can be resumed.

The state of the session will be re-"activated" immediately, and it will be "completed" when the transaction is successfully completed or

"suspended" again if the transaction is interrupted abnormally (e.g., network failures).

Throws:

CannotProceedException - if the transaction cannot be successfully completed.

InvalidStateException - if the session is not "suspended".

VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

[5.4.10](#) **create**

```
public void create(VoucherComponent promise, java.lang.Number num)
    throws VTSEException
```

Creates vouchers where the issuer is the VTSAgent itself. This method creates the specified number of vouchers <this, promise, this> and adds them to the VVS. Nothing is performed if the specified number is 0.

Throws:

FeatureNotAvailableException - if the VTSAgent does not provide a means of creating vouchers.

VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

[5.4.11](#) **delete**

```
public void delete(Participant issuer,
    VoucherComponent promise,
    java.lang.Number num)
    throws VTSEException
```

Deletes vouchers. This method deletes the specified number of vouchers <issuer, promise, this> from the VVS. The VTSAgent must have sufficient vouchers in the VVS. Nothing is performed if the specified number is 0.

Throws:

InsufficientVoucherException - if the VTSAgent doesn't have sufficient number of vouchers to delete.

VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

[5.4.12](#) **getContents**

```
public java.util.Set getContents(Participant issuer,
```

throws VTSEException VoucherComponent promise)

Returns the set of vouchers whose issuer and promise both match the issuer and promise specified in the parameters.

If null is specified for the issuer or promise parameter, it indicates "any issuer" or "any promise", respectively. If null is specified for both parameters, this method selects all vouchers owned by the holder from the VVS.

Returns:

the set of vouchers held by the holder of the VTSAgent.

Throws:

VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

5.4.13 getSession()

```
public java.lang.Set getSession()  
    throws VTSEException
```

Returns a set of not-completed sessions prepared by the VTSAgent.

Returns:

the set of sessions prepared by the VTSAgent and not yet completed.

Throws:

VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

5.4.14 getLog()

```
public java.lang.Set getLog()  
    throws VTSEException
```

Returns a set of completed sessions prepared or received by the VTSAgent. This set represents the trading log of the VTSAgent. A VTS may delete an old log eventually, so that the entire log may not be returned; the amount of the log kept by the VTSAgent is implementation-specific.

Returns:

the set of completed sessions prepared or received by the VTSAgent.

Throws:

VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

5.4.15 addReceptionListener

```
public void addReceptionListener(ReceptionListener l)
    throws VTSEException
```

Adds a ReceptionListener to the listener list.

After a ReceptionListener l is registered by this method, l.arrive() will be called whenever the VTSAgent receives a voucher.

Nothing is performed if the specified listener is null.

Throws:

VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

5.4.16 removeReceptionListener

```
public void removeReceptionListener(ReceptionListener l)
    throws VTSEException
```

Removes a ReceptionListener from the listener list.

Nothing is performed when the specified listener is null or not registered.

Throws:

VTSSecurityException - if the VTSAgent cannot be authenticated correctly.

5.5 Session

```
public interface Session
```

Represents the logical connection established by the trade. Sessions are established by VTSAgent#prepare().

A session has four states: prepared, activated, suspended, and completed. The initial state of a session is "prepared", and the session will be "activated" immediately when any of the trading methods of VTSAgent is called. The "activated" session will be "completed" after the trading method is successfully completed. If the trading method is transiently failed (e.g. network failure), the session will be "suspended". Suspended sessions can be re-"activated" and restarted by calling VTSAgent#resume().

A completed session may disappear from the VTSAgent; the session will be collected by the GC unless other objects keep its reference.

[5.5.1](#) `getIdentifier`

M. Terada, K. Fujimura

[Page 17]

```
public String getIdentifier()
```

Returns the identifier of the session. The generation scheme of the identifier is implementation-specific. An implementation may use a transaction ID as the identifier of the session.

Returns:

the string of the identifier of the session.

[5.5.2](#) **getVoucher**

```
public Voucher getVoucher()
```

Returns the voucher to be traded using the session, or returns null if the session has not been activated.

Returns:

the voucher to be traded or null if the state of the session is "prepared".

[5.5.3](#) **getSender**

```
public Participant getSender()
```

Returns the sender of the session, i.e., the creator who prepared the session.

Returns:

the sender of the session.

[5.5.4](#) **getReceiver**

```
public Participant getReceiver()
```

Returns the receiver of the session, i.e., the participant specified when preparing the session (by the VTSAgent#prepare() method).

Returns:

the receiver of the session.

[5.5.5](#) **isPrepared**

```
public boolean isPrepared()
```

Verifies if the session is "prepared".

Returns:

true if the session is in "prepared" state, or false.

[5.5.6](#) **isActivated**

```
public boolean isActivated()
```

Verifies if the session is "activated".

Returns:

true if the session is in "activated" state, or false.

[5.5.7](#) **isSuspended**

```
public boolean isSuspended()
```

Verifies if the session is "suspended".

Returns:

true if the session is in "suspended" state, or false.

[5.5.8](#) **isCompleted**

```
public boolean isCompleted()
```

Verifies if the session is "completed".

Returns:

true if the session is in "completed" state, or false.

[5.6](#) **Voucher**

```
public interface Voucher
```

Represents voucher(s) described in [[VTS](#)]. An object implementing this interface can represent more than one voucher if all of the issuer part and the promise part of the vouchers are the same.

[5.6.1](#) **getIssuer**

```
public Participant getIssuer()
```

Returns the issuer part of the voucher(s).

Returns:

the participant who issued the voucher(s).

[5.6.2](#) **getPromise**

```
public VoucherComponent getPromise()
```


Returns the promise part of the voucher(s).

Returns:

the voucher component that defines the promise of the voucher.

5.6.3 getCount

```
public java.lang.Number getCount()
```

Returns the number of the voucher(s).

Returns:

the positive (>0) number of the voucher(s).

5.7 VoucherComponentRepository

```
public interface VoucherComponentRepository
```

Maintains VoucherComponents.

An object implementing VoucherComponentRepository provides a means of retrieving the voucher components that are the promises of vouchers in the VVS.

Before issuing a voucher, the promise of the voucher must be registered with this repository. The repository can be implemented as either a network-wide directory service or personal storage like the ParticipantRepository.

5.7.1 register

```
public VoucherComponent register(org.w3c.dom.Document document)
```

Creates a voucher component associated with the specified DOM object and registers the voucher component with the repository.

A voucher component of the voucher to be issued must be registered using this method.

Nothing is performed (and the method returns null) if the specified document is null or the syntax of the document does not conform to the VTS.

The method returns the registered voucher component if the specified DOM object has been already registered. (No new voucher component is created in this case).

Returns:

a registered voucher component associated with the
specified document, or null if the document is null or has wrong

syntax.

5.8 VoucherComponent

```
public interface VoucherComponent
```

Represents the voucher component that defines the promise of the voucher.

Each VoucherComponent object has its own unique identifier, and it is associated with an XML document that describes the promise made by the issuer of the voucher, e.g., the goods or services can be claimed in exchange for redeeming the voucher.

This interface can be implemented as sort of a "smart pointer" to the XML document. An implementation may have a reference to a voucher component repository instead of the voucher component and retrieve the document dynamically from the repository when the `getDocument()` method is called.

5.8.1 getIdentifier

```
public String getIdentifier()
```

Returns the identifier of the voucher component. Each voucher component must have a unique identifier. The identifier may be used to check for equivalence of voucher components.

The format of the identifier is implementation-specific.

Returns:

The identifier string of the voucher component.

5.8.2 getDocument

```
public org.w3c.dom.Document getDocument()
```

Returns a Document Object Model [[DOM](#)] representation of the document associated with the voucher component by the `VoucherComponentRepository#register()` method.

The DOM object to be returned may be retrieved from a `VoucherComponentRepository` on demand, instead of the `VoucherComponent` always keeping a reference to the DOM object.

The VTS must guarantee that the `getDocument` method will eventually return the DOM object provided that the voucher associated with the corresponding voucher component exists in the VVS.

Returns:

a DOM representation of the document associated with the voucher

M. Terada, K. Fujimura

[Page 21]

component.

Throws:

DocumentNotFoundException - if the associated DOM object cannot be retrieved.

5.9 ReceptionListener

public interface ReceptionListener extends java.util.EventListener

Provides a listener interface that provides notification that a VTSAgent has been received a voucher.

When a voucher arrives at VTSAgent, the VTSAgent invokes arrive() method of each registered ReceptionListener. ReceptionListeners can obtain a Session object, which contains information about the received voucher and the sender of the voucher.

This interface is intended to provide a means of notifying a wallet that "You have new vouchers", so that this interface may be implemented by wallets or other applications using VTS.

5.9.1 arrive

public void arrive(Session session)

Provides notification of the arrival of a voucher.

After the listener is registered to a VTSAgent (by the VTSAgent#addReceptionListener() method), the VTSAgent invokes this method whenever it receives a voucher.

The specified session is equivalent to the session used by the sender to trade the voucher. The state of the session is "completed" when this method is called.

5.10 Exceptions

java.lang.Exception

+-- VTSEException

- +-- CannotProceedException
- +-- DocumentNotFoundException
- +-- FeatureNotAvailableException
- +-- InsufficientVoucherException
- +-- InvalidParticipantException
- +-- InvalidStateException
- +-- VTSSecurityException

VTSEException

This is the superclass of all exceptions thrown by the methods in the interfaces constructs the VTS-API.

CannotProceedException

This exception is thrown when a trading is interrupted due to network failures or other errors.

DocumentNotFoundException

This exception is thrown when the document associated with a voucher component cannot be found.

FeatureNotAvailableException

This exception is thrown when the invoked method is not supported.

InsufficientVoucherException

This exception is thrown when the number of the voucher is less than the number specified to trade.

InvalidParticipantException

This exception is thrown when the specified participant cannot be located.

InvalidStateException

This exception is thrown when the state of the session is invalid to proceed the operation.

VTSSecurityException

This exception is thrown when authentication fails or a method which requires authentication in advance is called without authentication.

6. Example Code

```
// Issue a voucher

VTSManger vts = new FooVTSManger();
ParticipantRepository addrBook = vts.getParticipantRepository();
VoucherComponentRepository vcr = vts.getVoucherComponentRepository();

Participant you = addrBook.lookup("http://foo.bar/baz");
VTSAgent me = addrBook.lookup("myName").getVTSAgent();

VoucherComponent promise = vcr.register(anXMLVoucherDocument);

try {
    me.login();
}
```

```
s = me.prepare(you);  
me.issue(s, promise, 1);
```

```
    me.logout();
} catch (VTSEException e) {
    System.err.println("Sorry!");
    e.printStackTrace();
}

// Transfer all my vouchers

VTManager vts = new FooVTManager();
ParticipantRepository addrBook = vts.getParticipantRepository();

Participant you = addrBook.lookup("http://foo.bar/baz");
VTSAgent me = addrBook.lookup("myName").getVTSAgent();

try {
    me.login();
    Iterator i = me.getContents(null, null).iterator();

    while (i.hasNext) {
        Voucher v = (Voucher) i.next();
        s = me.prepare(you);
        me.transfer(s, v.getIssuer(), v.getPromise(), v.getCount());
    }

    me.logout();
} catch (VTSEException e) {
    System.err.println("Sorry!");
    e.printStackTrace();
}

// Register an incoming voucher notifier (biff)

VTManager vts = new FooVTManager();

ParticipantRepository addrBook = vts.getParticipantRepository();
VTSAgent me = addrBook.lookup("myName").getVTSAgent();

ReceptionListener listener = new ReceptionListener() {
    public void arrive(Session s) {
        System.out.println("You got a new voucher.");
    }
};

try {
    me.login();
    me.addReceptionListener(listener);
    me.logout();
} catch (VTSEException e) {
    System.err.println("Sorry!");
    e.printStackTrace();
}
```

}

[7.](#) **Security Considerations**

M. Terada, K. Fujimura

[Page 24]

This document assumes that the VTS plug-in is trusted. The caller application of a VTS should authenticate the VTS plug-in and bind it securely using the VTS Provider information specified in the Voucher Component. This document, however, does not specify any application authentication scheme and it is assumed to be specified by other related standards. Until various VTS systems are deployed, it is enough to manually check and install VTS plug-ins like other download applications.

To protect vouchers from being stolen, the VTSAgent must be authenticated securely. This document introduced a login/logout facility for this purpose (see [Section 5.4](#)).

8. References

[DOM] "Document Object Model (DOM), Level 1 Specification", October <<http://www.w3.org/TR/REC-DOM-Level-1/>>, 1998.

[DOMHash] H. Maruyama, K. Tamura, and N. Uramoto, "Digest Values for DOM (DOMHASH)", [RFC 2803](#), 2000.

[ECML] J. W. Parsons and D. Eastlake "Electronic Commerce Modeling Language (ECML) Version 2 Specification", [draft-ietf-trade-ecml2-spec-03.txt](#), 2002.

[GPSF] G. Lacoste, B. Pfitzmann, M. Steiner, and M. Waidner (Eds.), "SEMPER - Secure Electronic Marketplace for Europe," LNCS 1854, Springer-Verlag, 2000.

[GVL] K. Fujimura and M. Terada, "XML Voucher: Generic Voucher Language", [draft-ietf-trade-voucher-lang-03.txt](#), 2002.

[VTS] K. Fujimura, "Requirements and Design for Voucher Trading System (VTS)", [draft-ietf-trade-drt-requirements-03.txt](#), 2002.

[IOTP] D. Burdett, "Internet Open Trading Protocol - IOTP Version 1.0", [RFC 2801](#), 2000.

[JCC] Sun Microsystems Inc., "Java Commerce Client", <<http://java.sun.com/products/commerce/>>.

[RFC2119] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), 1997.

9. Author's Address

Masayuki Terada and Ko Fujimura
NTT Corporation
1-1 Hikari-no-oka, Yokosuka-shi, Kanagawa, 239-0847 JAPAN
Phone: +81-(0)468-59-3814

Fax: +81-(0)468-59-8329

Email: terada@isl.ntt.co.jp, fujimura@isl.ntt.co.jp

M. Terada, K. Fujimura

[Page 25]

Full Copyright Statement

Copyright (C) The Internet Society (2002). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

