

TRILL Working Group  
INTERNET-DRAFT  
Intended status: Proposed Standard  
Updates: [6325](#), [6327](#), [6439](#)

Donald Eastlake  
Mingui Zhang  
Huawei  
Anoop Ghanwani  
Dell  
Vishwas Manral  
Hewlett-Packard  
Ayan Banerjee  
Cumulus Networks  
July 15, 2012

Expires: January 14, 2013

**TRILL: Clarifications, Corrections, and Updates**  
**<[draft-ietf-trill-clear-correct-05.txt](#)>**

**Abstract**

The IETF TRILL (TRAnsparent Interconnection of Lots of Links) protocol provides least cost pair-wise data forwarding without configuration in multi-hop networks with arbitrary topology and link technology, safe forwarding even during periods of temporary loops, and support for multipathing of both unicast and multicast traffic. TRILL accomplishes this by using IS-IS (Intermediate System to Intermediate System) link state routing and by encapsulating traffic using a header that includes a hop count. Since the TRILL base protocol was approved in March 2010, active development of TRILL has revealed errata in the original [RFC 6325](#) and some cases that could use clarifications or updates.

[RFC 6327](#) and [RFC 6439](#) provide clarifications and updates with respect to Adjacency and Appointed Forwarders. This document provides other known clarifications, corrections, and updates to [RFC 6325](#), [RFC 6327](#), and [RFC 6439](#).

**Status of This Memo**

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#). Distribution of this document is unlimited. Comments should be sent to the TRILL working group mailing list <rbridge@postel.org>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."



The list of current Internet-Drafts can be accessed at <http://www.ietf.org/1id-abstracts.html>. The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.



## Table of Contents

<a href="#">1. Introduction.....</a>	<a href="#">4</a>
<a href="#">1.1 Precedence.....</a>	<a href="#">4</a>
<a href="#">1.2 Changes That Are Not Backwards Compatible.....</a>	<a href="#">4</a>
<a href="#">1.3 Terminology and Acronyms.....</a>	<a href="#">5</a>
<a href="#">2. Overloaded and/or Unreachable RBridges.....</a>	<a href="#">6</a>
<a href="#">2.1 Reachability.....</a>	<a href="#">6</a>
<a href="#">2.2 Distribution Trees.....</a>	<a href="#">7</a>
<a href="#">2.3 Overloaded Receipt of TRILL Data Frames.....</a>	<a href="#">7</a>
<a href="#">2.3.1 Known Unicast Receipt.....</a>	<a href="#">7</a>
<a href="#">2.3.2 Multi-Destination Receipt.....</a>	<a href="#">8</a>
<a href="#">2.4 Overloaded Origination of TRILL Data Frames.....</a>	<a href="#">8</a>
<a href="#">2.4.1 Known Unicast Origination.....</a>	<a href="#">8</a>
<a href="#">2.4.2 Multi-Destination Origination.....</a>	<a href="#">8</a>
<a href="#">2.4.2.1 An Example Network.....</a>	<a href="#">8</a>
<a href="#">2.4.2.2 Indicating OOMF Support.....</a>	<a href="#">9</a>
<a href="#">2.4.2.3 Using OOMF Service.....</a>	<a href="#">10</a>
<a href="#">3. Distribution Trees.....</a>	<a href="#">11</a>
<a href="#">3.1 Number of Distribution Trees.....</a>	<a href="#">11</a>
<a href="#">3.2 Clarification of Distribution Tree Updates.....</a>	<a href="#">11</a>
<a href="#">3.3 IP Address Based Multicast Pruning.....</a>	<a href="#">11</a>
<a href="#">3.4 Numbering of Distribution Trees.....</a>	<a href="#">12</a>
<a href="#">4. Nickname Selection.....</a>	<a href="#">13</a>
<a href="#">5. MTU (Maximum Transmission Unit).....</a>	<a href="#">15</a>
<a href="#">5.1 MTU Related Errata in <a href="#">RFC 6325</a>.....</a>	<a href="#">15</a>
<a href="#">5.1.1 MTU PDU Addressing.....</a>	<a href="#">15</a>
<a href="#">5.1.2 MTU PDU Processing.....</a>	<a href="#">16</a>
<a href="#">5.1.3 MTU Testing.....</a>	<a href="#">16</a>
<a href="#">5.2 Ethernet MTU Values.....</a>	<a href="#">16</a>
<a href="#">6. Port Modes.....</a>	<a href="#">18</a>
<a href="#">7. The CFI / DEI Bit.....</a>	<a href="#">19</a>
<a href="#">8. Graceful Restart.....</a>	<a href="#">20</a>
<a href="#">9. Updates to <a href="#">RFC 6327</a>.....</a>	<a href="#">21</a>
<a href="#">10. Updates on Appointed Forwarders and Inhibition.....</a>	<a href="#">22</a>
<a href="#">10.1 Optional TRILL Hello Reduction.....</a>	<a href="#">22</a>
<a href="#">10.2 Overload and Appointed Forwarders.....</a>	<a href="#">24</a>
<a href="#">11. IANA Considerations.....</a>	<a href="#">25</a>
<a href="#">12. Security Considerations.....</a>	<a href="#">26</a>
<a href="#">Acknowledgements.....</a>	<a href="#">26</a>
<a href="#">Change History.....</a>	<a href="#">26</a>
<a href="#">Normative References.....</a>	<a href="#">27</a>

Informative References.....	<a href="#">28</a>
-----------------------------	--------------------

## **1. Introduction**

The IETF TRILL (Transparent Interconnection of Lots of Links) protocol [[RFC6325](#)] provides optimal pair-wise data frame forwarding without configuration in multi-hop networks with arbitrary topology and link technology, safe forwarding even during periods of temporary loops, and support for multipathing of both unicast and multicast traffic. TRILL accomplishes this by using IS-IS (Intermediate System to Intermediate System) [[IS-IS](#)] [[RFC1195](#)] [[RFC6326bis](#)] link state routing and encapsulating traffic using a header that includes a hop count. The design supports VLANs (Virtual Local Area Networks) and optimization of the distribution of multi-destination frames based on VLANs and IP derived multicast groups.

In the more than two years since the TRILL base protocol [[RFC6325](#)] was approved, the active development of TRILL has revealed five errors in the original specification document [[RFC6325](#)] and cases that could use clarifications or updates.

[[RFC6327](#)] and [[RFC6439](#)] provide clarifications with respect to Adjacency and Appointed Forwarders. This document provides other known clarifications, corrections, and updates to [[RFC6325](#)], [[RFC6327](#)], and [[RFC6439](#)].

### **1.1 Precedence**

In case of conflict between this document and any of [[RFC6325](#)], [[RFC6327](#)], or [[RFC6439](#)], this document takes precedence. In addition, [Section 1.2](#) (Normative Content and Precedence) of [[RFC6325](#)] is updated to provide a more complete precedence ordering of the sections of [[RFC6325](#)] as following, where sections to the left take precedence over sections to their right:

$$4 > 3 > 7 > 5 > 2 > 6 > 1$$

### **1.2 Changes That Are Not Backwards Compatible**

The change made by [Section 3.4](#) below is not backward compatible with [[RFC6325](#)] but has nevertheless been adopted to reduce distribution tree changes resulting from topology changes.

The several other changes herein that are fixes to previously posted [[RFC6325](#)] Errata [[Err3002](#)] [[Err3003](#)] [[Err3004](#)] [[Err3052](#)] [[Err3053](#)] may not be backward compatible with previous implementations that conformed to errors in the specification.





### **1.3 Terminology and Acronyms**

This document uses the acronyms defined in [[RFC6325](#)] and the following additional acronyms:

CFI - Canonical Format Indicator [[802](#)]

DEI - Drop Eligibility Indicator [[802.1Q-2011](#)]

EISS - Enhanced Internal Sublayer Service

OOMF - Overload Originated Multi-destination Frame

TRILL Switch - An alternative name for an RBridge

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].



## **2. Overloaded and/or Unreachable RBridges**

RBridges may be in overload as indicated by the [\[IS-IS\]](#) overload flag in their LSPs (Link State PDUs (Protocol Data Units)). This means that either (1) they are incapable of holding the entire link state database and thus do not have a view of the entire topology or (2) they have been configured to have the overload bit set. Although networks should be engineered to avoid actual link state overload, it might occur under various circumstances. For example, if a large campus included one or more low-end TRILL Switches.

It is a common operational practice to set the overload bit in an [\[IS-IS\]](#) router (such as an RBridge) when performing maintenance on that router that might affect its ability to correctly forward frames; this will usually leave the router reachable for maintenance traffic but transit traffic will not be routed through it. (Also, in some cases, TRILL provides for setting the overload bit in the pseudonode of a link to stop TRILL Data traffic on an access link (see [Section 4.9.1 of \[RFC6325\]](#)).)

[IS-IS] and TRILL make a reasonable effort to do what they can even if some RBridges/routers are in overload. They can do reasonably well if a few scattered nodes are in overload. However, actual least cost paths are no longer assured if any RBridges are in overload.

For the effect of overload on the appointment of forwarders, see [Section 10.2](#).

In this [Section 2](#), the term "neighbor" refers only to actual RBridges and ignores pseudonodes.

### **2.1 Reachability**

Frames are not least cost routed through an overloaded TRILL Switch, although they may originate or terminate at an overloaded TRILL Switch. In addition, frames will not be least cost routed over links with cost  $2^{24} - 1$  [\[RFC5305\]](#); such links are reserved for traffic engineered frames, the handling of which is beyond the scope of this document.

As a result, a portion of the campus may be unreachable for least cost routed TRILL Data because all paths to it would be through a link with cost  $2^{24} - 1$  or through an overloaded RBridge. For example, an RBridge RB1 is not reachable by TRILL Data if all of its neighbors are connected to RB1 by links with cost  $2^{24} - 1$ . Such RBridges are called "data unreachable".

The link state database at an RBridge RB1 can also contain

information on TRILL Switches that are unreachable by IS-IS link state flooding due to link or RBridge failures. When such failures partition the campus, the TRILL Switches adjacent to the failure and on the same side of the failure as RB1 will update their LSPs to show the lack of connectivity and RB1 will receive those updates. As a result, RB1 will be aware of the partition. Nodes on the far side of the partition are both "IS-IS unreachable" and data unreachable. However, LSPs held by RB1 for TRILL Switches on the far side of the failure will not be updated and may stay around until they time out, which could be tens of minutes or longer. (The default in [\[IS-IS\]](#) is twenty minutes.)

## **[2.2](#) Distribution Trees**

An RBridge in overload cannot be trusted to correctly calculate distribution trees or correctly perform the RPFC (Reverse Path Forwarding Check). Therefore, it cannot be trusted to forward multi-destination TRILL Data frames. It can only appear as a leaf node in a TRILL multi-destination distribution tree. Furthermore, if all the immediate neighbors of an RBridge are overloaded, then it is omitted from all trees in the campus and is unreachable by multi-destination frames.

When an RBridge determines what nicknames to use as the roots of the distribution trees it calculates, it **MUST** ignore all nicknames held by TRILL Switches that are in overload or are data unreachable. When calculating RPFCs for multi-destination frames, an RBridge RB1 **MAY**, to avoid calculating unnecessary RPF check state, ignore any trees that cannot reach to RB1 even if other RBridges list those trees as trees those other TRILL Switches might use. (But see [Section 3](#).)

## **[2.3](#) Overloaded Receipt of TRILL Data Frames**

The receipt of TRILL Data frames by overloaded RBridge RB2 is discussed in the subsections below. In all cases, the normal Hop Count decrement is performed and the TRILL Data frame is discarded if the result is less than one or if the egress nickname is illegal.

### **[2.3.1](#) Known Unicast Receipt**

RB2 will not usually receive unicast TRILL Data frames unless it is the egress, in which case it decapsulates and delivers the frames normally. If RB2 receives a unicast TRILL Data frame for which it is

not the egress, perhaps because a neighbor does not yet know it is in

overload, RB2 MUST NOT discard the frame because the egress is an unknown nickname as it might not know about all nicknames due to its overloaded condition. If any neighbor, other than the neighbor from which it received the frame, is not overloaded it MUST attempt to forward the frame to one of those neighbors. If there is no such neighbor, the frame is discarded.

### **2.3.2 Multi-Destination Receipt**

If RB2 in overload receives a multi-destination TRILL Data frame, RB2 MUST NOT apply an RPFC since, due to overload, it might not do so correctly. RB2 decapsulates and delivers the frame locally where it is Appointed Forwarder for the frame's VLAN, subject to any multicast pruning. But since, as stated above, RB2 can only be the leaf of a distribution tree, it MUST NOT forward a multi-destination TRILL Data frame (except as an egressed native frame where RB2 is Appointed Forwarder).

## **2.4 Overloaded Origination of TRILL Data Frames**

Overloaded origination of unicast frames with known egress and of multi-destination frames are discussed in the subsections below.

### **2.4.1 Known Unicast Origination**

When an overloaded RBridge RB2 ingresses or creates a known destination unicast TRILL Data frame, it delivers it locally if the destination MAC is local. Otherwise RB2 unicasts it to any neighbor TRILL Switch that is not overloaded. It MAY use what routing information it has to help select the neighbor.

### **2.4.2 Multi-Destination Origination**

Overloaded RBridge RB2 ingressing or creating a multi-destination TRILL Data frame is more complex than for a known unicast frame.


#### **2.4.2.1 An Example Network**

For example, consider the network below in which, for simplicity, end stations and any bridges are not shown. There is one distribution





tree of which RB4 is the root and which is represented by double lines. Only RBridge RB2 is overloaded.



Since RB2 is overloaded it does not know what the distribution tree or trees are for the network. Thus there is no way it can provide normal TRILL Data encapsulation for multi-destination native frames. So RB2 tunnels the frame to a neighbor that is not overloaded if it has such a neighbor that has signaled it is willing to offer this service. RBridges indicate this in their Hellos as described below. This service is called OOMF (Overloaded Origination of Multi-destination Frame) service.

- The multi-destination frame MUST NOT be locally distributed in native form at RB2 before tunneling to a neighbor because this would cause the frame to be delivered twice. For example, if RB2 locally distributed a multicast native frame and then tunneled it to RB5, RB2 would get a copy of the frame when RB3 transmitted it as a TRILL Data frame on the multi-access RB2-RB3-RB4 link. Since RB2 would, in general, not be able to tell that this was a frame it had tunneled for distribution, RB2 would decapsulate it and locally distribute it a second time.
- On the other hand, if there is no neighbor of RB2 offering RB2 the OOMF service, RB2 cannot tunnel the frame to a neighbor. In this case RB2 MUST locally distribute the frame where it is Appointed Forwarder for the frame's VLAN and optionally subject to multicast pruning.

#### **2.4.2.2 Indicating OOMF Support**

A RBridge RB3 indicates its willingness to offer the OOMF service to RB2 in the TRILL Neighbor TLV in RB3's TRILL Hellos by setting a bit associated with the SNPA (SubNetwork Point of Attachment, also known as MAC address) of RB2 on the link. (See [Section 11](#).) Overloaded RBridge RB2 can only distribute multi-destination TRILL Data frames

to the campus if a neighbor of RB2 not in overload offers RB2 the

OOMF service. If RB2 does not have OOMF service available to it, RB2 can still receive multi-destination frames from non-overloaded neighbors and, if RB2 should originate or ingress such a frame, it distributes it locally in native form.

#### **2.4.2.3 Using OOMF Service**

If RB2 sees this OOMF (Overloaded Origination of Multi-destination Frame) service advertised for it by any of its neighbors on any link to which RB2 connects, it selects one such neighbor by a means beyond the scope of this document. Assuming RB2 selects RB3 to handle multi-destination frames it originates. RB2 MUST advertise in its LSP that it might use any of the distribution trees that RB3 advertises so that the RPFC will work in the rest of the campus. Thus, notwithstanding its overloaded state, RB2 MUST retain this information from RB3 LSPs, which it will receive as it is directly connected to RB3.

RB2 then encapsulates such frames as TRILL Data frames to RB3 as follows: M bit = 0, Hop Count = 2, ingress nickname = a nickname held by RB2, and, since RB2 cannot tell what distribution tree RB3 will use, egress nickname = a special nickname indicating an OOMF frame (see [Section 11](#)). RB2 then unicasts this TRILL Data frame to RB3. (Implementation of Item 4 in [Section 4](#) below provides reasonable assurance that, notwithstanding its overloaded state, the ingress nickname used by RB2 will be unique within at least the portion of the campus that is IS-IS reachable from RB2.)

On receipt of such a frame, RB3 does the following:

- change the egress nickname field to designate a distribution tree that RB3 normally uses,
- set the M bit to one,
- change the Hop Count to the value it would normally use if it were the ingress, and
- forward the frame on that tree.

RB3 MAY rate limit the number of frames for which it is providing this service by discarding some such frames from RB2. The provision of even limited bandwidth for OOMFs by RB3, perhaps via the slow path, may be important to the bootstrapping of services at RB2 or at end stations connected to RB2, such as supporting DHCP and ARP/ND. (Everyone sometimes needs a little OOMF (pronounced oomph) to get off the ground.)



### **3. Distribution Trees**

A correction, a clarification, and two updates related to distribution trees appear in the subsections below. See also [Section 2.2](#).

#### **3.1 Number of Distribution Trees**

In [\[RFC6325\]](#), [Section 4.5.2](#), page 56, Point 2, 4th paragraph, the parenthetical "(up to the maximum of {j,k})" is incorrect [\[Err3052\]](#). It should read "(up to k if j is zero or the minimum of (j, k) if j is non-zero)".

#### **3.2 Clarification of Distribution Tree Updates**

When a link state database change causes a change in the distribution tree(s), there are several possibilities. If a tree root remains a tree root but the tree changes, then local forwarding and RPFC entries for that tree should be updated as soon as practical. Similarly, if a new nickname becomes a tree root, forwarding and RPFC entries for the new tree should be installed as soon as practical. However, if a nickname ceases to be a tree root and there is sufficient room in local tables, the forwarding and RPFC entries for the former tree MAY be retained so that any multi-destination TRILL Data frames already in flight on that tree have a higher probability of being delivered.

#### **3.3 IP Address Based Multicast Pruning**

The TRILL base protocol specification [\[RFC6325\]](#) provides for and recommends the pruning of multi-destination frame distribution trees based on the location of IP multicast routers and listeners; however, multicast listening is identified by derived MAC addresses as communicated in the Group MAC Address sub-TLV [\[RFC6326bis\]](#).

TRILL Switches MAY communicate multicast listeners and prune distribution trees based on the actual IPv4 or IPv6 multicast addresses involved. Additional Group Address sub-TLVs are provided in [\[RFC6326bis\]](#) to carry this information. A TRILL Switch that is only capable of pruning based on derived MAC address SHOULD calculate and use such derived MAC addresses from multicast listener IPv4/IPv6 address information it receives.



### **3.4 Numbering of Distribution Trees**

[Section 4.5.1 of \[RFC6325\]](#) specifies that, when building distribution tree number  $j$ , node (RBridge)  $N$  that has multiple possible parents in the tree is attached to possible parent number  $j \bmod p$ . Trees are numbered starting with 1 but possible parents are numbered starting with 0. As a result, if there are two trees and two possible parents, in tree 1 parent 1 will be selected and in tree 2 parent 0 will be selected.

This is changed so that the selected parent **MUST** be  $(j-1) \bmod p$ . As a result, in the case above, tree 1 will select parent 0 and tree 2 will select parent 1. This change is not backwards compatible with [\[RFC6325\]](#). If all RBridges in a campus do not determine distribution trees in the same way then, for most topologies, the reverse path forwarding checking will drop many multi-destination frames before they have been properly delivered.





#### 4. Nickname Selection

Nickname selection is covered by [Section 3.7.3 of \[RFC6325\]](#). However, the following should be noted:

1. The second sentence in the second bullet item in [Section 3.7.3 of \[RFC6325\]](#) on page 25 is erroneous [[Err3002](#)] and is corrected as follows:

- 1.a The occurrence of "IS-IS ID (LAN ID)" is replaced with "priority".

- 1.b The occurrence of "IS-IS System ID" is replaced with "seven byte IS-IS ID (LAN ID)".

The resulting corrected [\[RFC6325\]](#) sentence reads as follows: "If RB1 chooses nickname x, and RB1 discovers, through receipt of an LSP for RB2 at any later time, that RB2 has also chosen x, then the RBridge or pseudonode with the numerically higher priority keeps the nickname, or if there is a tie in priority, the RBridge with the numerically higher seven byte IS-IS ID (LAN ID) keeps the nickname, and the other RBridge MUST select a new nickname."

2. In examining the link state database for nickname conflicts, nicknames held by IS-IS unreachable TRILL Switches MUST be ignored but nicknames held by IS-IS reachable TRILL Switches MUST NOT be ignored even if they are data unreachable.
3. An RBridge may need to select a new nickname, either initially because it has none or because of a conflict. When doing so, the RBridge MUST consider as available all nicknames that do not appear in its link state database or that appear to be held by IS-IS unreachable TRILL Switches; however, it SHOULD give preference to selecting new nicknames that do not appear to be held by any TRILL Switch in the campus, reachable or unreachable, so as to minimize conflicts if IS-IS unreachable TRILL Switches later become reachable.
4. An RBridge, even after it has acquired a nickname for which there appears to be no conflicting claimant, MUST continue to monitor for conflicts with the nickname or nicknames it holds. It does so by checking in LSPs it receives that should update its link state database for any of its nicknames held with higher priority by another TRILL Switch that is IS-IS reachable. If it finds such a conflict, it MUST select a new nickname. (It is possible to receive an LSP that should update the link state database but does not due to overload.)

5. In the very unlikely case that an RBridge is unable to obtain a

nickname because all valid RBridge nicknames (0x0001 through

0xFFBF inclusive) are in use with higher priority by IS-IS reachable TRILL Switches, it will be unable to act as an ingress, egress, or tree root but will still be able to function as a transit TRILL Switch. Although it cannot be a tree root, such an RBridge is included in distribution trees computed for the campus unless all its neighbors are overloaded. It would not be possible to send a unicast RBridge Channel message specifically to such a TRILL Switch [[Channel](#)]; however, it will receive unicast Channel messages sent by a neighbor to the Any-RBridge egress nickname and will receive appropriate multi-destination Channel messages.



## **5. MTU (Maximum Transmission Unit)**

MTU values in TRILL key off the `originatingL1LSPBufferSize` value communicated in the IS-IS `originatingLSPBufferSize` TLV [[IS-IS](#)]. The campus-wide value `Sz`, as described in [[RFC6325](#)] [Section 4.3.1](#), is the minimum value of `originatingL1LSPBufferSize` for the RBridges in a campus, but not less than 1470. The MTU testing mechanism and limiting LSPs to `Sz` assures that the LSPs can be flooded by IS-IS and thus that IS-IS can operate properly.

If nothing is known about the MTU of the links or the `originatingL1LSPBufferSize` of other RBridges in a campus, the `originatingL1LSPBufferSize` for an RBridge should default to the minimum of the LSP size that its TRILL IS-IS software can handle and the minimum MTU of the ports that it might use to receive or transmit LSPs. If an RBridge does have knowledge of link MTUs or other RBridge `originatingL1LSPBufferSize` then, to avoid having to refragment LSPs, the RBridge's `originatingL1LSPBufferSize` SHOULD be configured to the minimum of (1) the smallest value that other RBridges are or will be announcing as their `originatingL1LSPBufferSize` and (2) a value small enough that the campus will not partition due to a significant number of links with limited MTU. However, as provided in [[RFC6325](#)], in no case can `originatingL1LSPBufferSize` be less than 1470. In a well configured campus, to minimize any LSP re-sizing, it is desirable for all RBridges to be configured with the same `originatingL1LSPBufferSize`.

[Section 5.1](#) below corrects errata in [[RFC6325](#)] and [Section 5.2](#) clarifies the meaning of various MTU (Maximum Transmission Unit) limits for TRILL Ethernet links.

### **5.1 MTU Related Errata in [RFC 6325](#)**

Three MTU related errata in [[RFC6325](#)] are corrected in the subsections below.

#### **5.1.1 MTU PDU Addressing**

[Section 4.3.2 of \[\[RFC6325\]\(#\)\]](#) incorrectly states that multi-destination MTU-probe and MTU-ack TRILL IS-IS PDUs are sent on Ethernet links with the All-RBridges multicast address as the Outer.MacDA [[Err3004](#)]. As TRILL IS-IS PDUs, when multicast on an Ethernet link, they MUST be sent to the All-IS-IS-RBridges multicast address.



### 5.1.2 MTU PDU Processing

As discussed in [\[RFC6325\]](#) and, in more detail, in [\[RFC6327\]](#), MTU-probe and MTU-ack PDUs MAY be unicast; however, [Section 4.6 of \[RFC6325\]](#) erroneously does not allow for this possibility [\[Err3003\]](#). It is corrected by replacing Item numbered "1" in [Section 4.6.2 of \[RFC6325\]](#) with the following quoted text to which TRILL Switches MUST conform:

"1. If the Ethertype is L2-IS-IS and the Outer.MacDA is either All-IS-IS-RBridges or the unicast MAC address of the receiving RBridge port, the frame is handled as described in [Section 4.6.2.1](#)"

The reference to "[Section 4.6.2.1](#)" in the above quoted text is to that Section in [\[RFC6325\]](#).

### 5.1.3 MTU Testing

The last two sentences of [Section 4.3.2 of \[RFC6325\]](#) have errors [\[Err3053\]](#). They currently read:

If X is not greater than Sz, then RB1 sets the "failed minimum MTU test" flag for RB2 in RB1's Hello. If size X succeeds, and  $X > Sz$ , then RB1 advertises the largest tested X for each adjacency in the TRILL Hellos RB1 sends on that link, and RB1 MAY advertise X as an attribute of the link to RB2 in RB1's LSP.

They should read:

If X is not greater than or equal to Sz, then RB1 sets the "failed minimum MTU test" flag for RB2 in RB1's Hello. If size X succeeds, and  $X \geq Sz$ , then RB1 advertises the largest tested X for each adjacency in the TRILL Hellos RB1 sends on that link, and RB1 MAY advertise X as an attribute of the link to RB2 in RB1's LSP.

## 5.2 Ethernet MTU Values

originatingL1LSPBufferSize is the maximum permitted size of LSPs starting with the 0x83 Intradomain Routing Protocol Discriminator byte. In layer 3 IS-IS, originatingL1LSPBufferSize defaults to 1492 bytes. (This is because, in its previous life as DECnet Phase V, IS-IS was encoded using the SNAP SAP [\[RFC5342\]](#) format which takes 8 bytes of overhead and  $1492 + 8 = 1500$ , the classic Ethernet maximum. When standardized by ISO/IEC [\[IS-IS\]](#) to use LLC encoding, this

default could have been increased by a few bytes but was not.)



In TRILL, `originatingL1LSPBufferSize` defaults to 1470 bytes. This allows 27 bytes of headroom or safety margin to accommodate legacy devices with the classic Ethernet maximum MTU despite headers such as an `Outer.VLAN`. This safety margin is called "Margin" below.

Assuming the campus wide minimum link MTU is `Sz`, RBridges on Ethernet links MUST limit most TRILL IS-IS PDUs so that PDUz (the length of the PDU starting just after the L2-IS-IS Ethertype and ending just before the Ethernet frame FCS) does not to exceed `Sz`. The PDU exceptions are TRILL Hello PDUs, which MUST NOT exceed 1470 bytes, and MTU-probe and MTU-ack PDUs that are padded, depending on the size being tested (which may exceed `Sz`).

`Sz` does not limit TRILL Data frames. They are only limited by the MTU of the devices and links that they actually pass through; however, links that can accommodate IS-IS PDUs up to `Sz` would accommodate, with a generous safety margin, TRILL Data frame payloads, starting after the `Inner.VLAN` and ending just before the FCS, of `Sz - 24` bytes. Most modern Ethernet equipment has ample headroom for frames with extensive headers and is sometimes engineered to accommodate 9K byte jumbo frames.



[Section 4.9.1 of \[RFC6325\]](#) specifies four mode bits for RBridge ports but may not be completely clear on the effects of various combinations of bits.

The table below explicitly indicates the effect of all possible combinations of the TRILL port mode bits. "\*" in one of the first four columns indicates that the bit can be either zero or one. The following columns indicate allowed frame types. The Disable bit normally disables all frames but, as an implementation choice, some or all low level Layer 2 control frames (as specified in [RFC6325 Section 1.4](#)) can still be sent or received.

[illegible]

(The formal name of the "access bit" is the "TRILL traffic disable bit" and the formal name of the "trunk bit" is the "end-station service disable bit" [RFC6325].)



## **7. The CFI / DEI Bit**

In May 2011, the IEEE promulgated [[802.1Q-2011](#)] which changes the meaning of the bit between the priority and VLAN ID bits in the payload of C-VLAN tags. Previously this bit was called the CFI (Canonical Format Indicator) bit [[802](#)] and had a special meaning in connection with IEEE 802.5 (Token Ring) frames. Now, under [[802.1Q-2011](#)], it is a DEI (Drop Eligibility Indicator) bit, similar to that bit in S-VLAN / B-VLAN tags where this bit has always been a DEI bit.

The TRILL base protocol specification [[RFC6325](#)] assumed, in effect, that the link by which end stations are connected to TRILL Switches and the restricted virtual link provided by the TRILL Data frame are IEEE 802.3 Ethernet links on which the CFI bit is always zero. Should an end station be attached by some other type of link, such as a Token Ring link, [[RFC6325](#)] implicitly assumed that such frames would be canonicalized to 802.3 frames before being ingressed and similarly, on egress, such frames would be converted from 802.3 to the appropriate frame type for the link. Thus, [[RFC6325](#)] required that the CFI bit in the Inner.VLAN always be zero.

However, for TRILL Switches with ports conforming to the change incorporated in the IEEE 802.1Q-2011 standard, the bit in the Inner.VLAN, now a DEI bit, MUST be set to the DEI value provided by the EISS (Enhanced Internal Sublayer Service) interface on ingressing a native frame. Similarly, this bit MUST be provided to the EISS when transiting or egressing a TRILL Data frame. As with the 3-bit priority field, the DEI bit to use in forwarding a transit frame MUST be taken from the Inner.VLAN. The exact effect on the Outer.VLAN DEI and priority bits and whether or not an Outer.VLAN appears at all on the wire for output frames may depend on output port configuration.

TRILL campuses with a mixture of ports, some compliant with [[802.1Q-2011](#)] and some compliant with pre-802.1Q-2011 standards, especially if they have actual Token Ring links, may operate incorrectly and may corrupt data, just as a bridged LAN with such mixed ports and links would.



## **8. Graceful Restart**

TRILL Switches SHOULD support the features specified in [[RFC5306](#)] which describes a mechanism for a restarting IS-IS router to signal to its neighbors that it is restarting, allowing them to reestablish their adjacencies without cycling through the down state, while still correctly initiating link state database synchronization.





## 9. Updates to [RFC 6327](#)

[RFC6327] provides for multiple states of the potential adjacency between two TRILL Switches. It makes clear that only an adjacency in the "Report" state is reported in LSPs. LSP synchronization (LSP and SNP transmission and receipt), however, is performed if and only if there is at least one adjacency on the link in either the "Two-Way" or "Report" state.

To support the PORT-TRILL-VER sub-TLV specified in [[RFC6326bis](#)], the following updates are made to [[RFC6327](#)]:

1. The first sentence of the last paragraph in [[RFC6327](#)] [Section 3.1](#) is modified from  
"All TRILL LAN Hellos issued by an RBridge on a particular port MUST have the same source MAC address, priority, desired Designated VLAN, and Port ID, regardless of the VLAN in which the Hello is sent."  
to  
"All TRILL LAN Hellos issued by an RBridge on a particular port MUST have the same source MAC address, priority, desired Designated VLAN, Port ID, and PORT-TRILL-VER sub-TLV [[RFC6326bis](#)] if included, regardless of the VLAN in which the Hello is sent."
2. An additional bullet item is added to the end of [Section 3.2](#) as follows:  
  - o The 5 bytes of data from the PORT-TRILL-VER received in the most recent TRILL Hello from the neighbor RBridge.
3. In [[RFC6327](#)] [Section 3.3](#), near the bottom of page 12, a bullet item as follows is added:  
  - o The five bytes of PORT-TRILL-VER data are set from that sub-TLV in the Hello or set to zero if that sub-TLV does not occur in the Hello.
4. At the beginning of [[RFC6327](#)] [Section 4](#), a bullet item is added to the list as follows:  
  - o The five bytes of PORT-TRILL-VER sub-TLV data used in TRILL Hellos sent on the port.



## **10. Updates on Appointed Forwarders and Inhibition**

An optional method of Hello reduction is specified in [Section 10.1](#) below and a recommendation on forwarder appointments in the face of overload is given in [Section 10.2](#).

### **10.1 Optional TRILL Hello Reduction**

If a network manager has sufficient confidence that they know the configuration of bridges, ports, and the like, within a link, they may be able to reduce the number of TRILL Hellos sent on that link; for example, if all R Bridges on the link will see all Hellos regardless of VLAN constraints, Hellos could be sent on fewer VLANs. However, because adjacencies are established in the Designated VLAN, an R Bridge MUST always attempt to send Hellos in the Designated VLAN. Hello reduction makes TRILL less robust in the face of decreased VLAN connectivity in a link such as partitioned VLANs, many VLANs disabled on ports, or disagreement over the Designated VLAN; however, as long as all R Bridge ports on the link are configured for the same desired Designated VLAN, can see each other's frames in that VLAN, and utilize the mechanisms specified below to update VLAN inhibition timers, operations will be safe. (These considerations do not arise on links between R Bridges that are configured as point-to-point since, in that case, each R Bridge sends point-to-point Hellos, other TRILL IS-IS PDUs, and TRILL Data frames only in what it believes to be the Designated VLAN of the link and no native frame end-station service is provided.)

The provision for a configurable set of "Announcing VLANs", as described in [Section 4.4.3 of \[RFC6325\]](#) provides a mechanism in the TRILL base protocol for a reduction in TRILL Hellos.

To maintain loop safety in the face of occasional lost frames, R Bridge failures, link failures, new R Bridges coming up on a link, and the like, the inhibition mechanism specified in [\[RFC6439\]](#) is still required. Under [Section 3 of \[RFC6439\]](#), a VLAN inhibition timer can only be set by the receipt of a Hello sent or received in that VLAN. Thus, to safely send a reduced number of TRILL Hellos on a reduced number of VLANs requires additional mechanisms to set the VLAN inhibition timers at an R Bridge, thus extending [Section 3](#), Item 4, of [\[RFC6439\]](#). Two such mechanisms are specified below. Support for both of these mechanisms is indicated by a capability bit in the PORT-TRILL-VER sub-TLV (see [Section 9](#) above and [\[RFC6326bis\]](#)). It may be unsafe for an R Bridge to send TRILL Hellos on fewer VLANs than the set of VLANs recommended in [\[RFC6325\]](#) on a link unless all its adjacencies on that link (excluding those in the Down state

[[RFC6327](#)]) indicate support of these mechanisms and these mechanisms are in use.

1. An RBridge RB2 MAY include in any TRILL Hello an Appointed Forwarders sub-TLV [[RFC6326bis](#)] appointing itself for one or more ranges of VLANs. The Appointee Nickname field(s) in the Appointed Forwarder sub-TLV MUST be the same as the Sender Nickname in the Special VLANs and Flags sub-TLV in the TRILL Hello. This indicates the sending RBridge believes it is Appointed Forwarder for those VLANs. An RBridge receiving such a sub-TLV sets each of its VLAN inhibition timers for every VLAN in the block or blocks listed in the Appointed Forwarders sub-TLV to the maximum of its current value and the Holding Time of the Hello containing the sub-TLV. This is backwards compatible because such sub-TLVs will have no effect on any receiving RBridge not implementing this mechanism unless RB2 is the DRB (Designated RBridge) sending Hello on the Designated VLAN in which case, as specified in [[RFC6439](#)], RB2 MUST include in the Hello all forwarder appointments, if any, for RBridges other than itself on the link.
2. An RBridge MAY use the new VLANs Appointed sub-TLV [[RFC6326bis](#)]. When RB1 receives a VLANs Appointed sub-TLV in a TRILL Hello from RB2 on any VLAN, RB1 updates the VLAN inhibition timers for all the VLANs that RB2 lists in that sub-TLV as VLANs for which RB2 is Appointed Forwarder. Each such timer is updated to the maximum of its current value and the Holding Time of the TRILL Hello containing the VLANs Appointed sub-TLV. This sub-TLV will be an unknown sub-TLV to RBridge not implementing it and such RBridges will ignore it. Even if a TRILL Hello send by the DRB on the Designated VLAN includes one or more VLANs Appointed sub-TLVs, as long as no Appointed Forwarders sub-TLVs appear, the Hello is not required to indicate all forwarder appointments.

Two different encodings are providing above to optimize the listing of VLANs. Large blocks of contiguous VLANs are more efficiently encoded with the Appointed Forwarders sub-TLV and scattered VLANs are more efficiently encoded with the VLANs Appointed sub-TLV. These encodings may be mixed in the same Hello. The use of these sub-TLVs does not affect the requirement that the "AF" bit in the Special VLANs and Flags sub-TLV MUST be set if the originating RBridge believes it is Appointed Forwarder for the VLAN in which the Hello is sent. If the above mechanisms are used on a link, then each RBridge on the link MUST send Hellos in one or more VLANs with such VLANs Appointed sub-TLV(s) and/or self-appointment Appointed Forwarders sub-TLV(s) and the "AF" bit appropriately set such that no VLAN inhibition timer will improperly expire unless three or more Hellos are lost. For example, an RBridge could announce all VLANs for which it believes it is Appointed Forwarder in a Hello sent on the Designated VLAN three times per Holding Time.



## **10.2 Overload and Appointed Forwarders**

An RBridge in overload (see [Section 2](#)) will, in general, do a poorer job of ingressing and forwarding frames than an RBridge not in overload that has full knowledge of the campus topology. For example, an overloaded RBridge may not be able to distribute multi-destination TRILL Data frames at all.

Therefore, the DRB SHOULD NOT appoint an RBridge in overload as an Appointed Forwarder unless there is no alternative. Furthermore, if an Appointed Forwarder becomes overloaded, the DRB SHOULD re-assign VLANs from the overloaded RBridge to another RBridge on the link that is not overloaded, if one is available. DRB election is not affected by overload.

A counter-example would be if all campus end stations in VLAN-x were on links attached to RB1 via ports where VLAN-x was enabled. In such a case, RB1 SHOULD be made the VLAN-x Appointed Forwarder on all such links even if RB1 is overloaded.





## **11. IANA Considerations**

The following IANA actions are required:

1. The nickname 0xTBD [0xFFC1 suggested], which was reserved by [RFC6325], is allocated for use in the TRILL Header egress nickname field to indicate an OOMF (Overload Originated Multi-destination Frame).
2. Bit 1 from the seven previously reserved (RESV) bits in the per neighbor "Neighbor RECORD" in the TRILL Neighbor TLV [RFC6326bis] is allocated to indicate that the RBridge sending the TRILL Hello volunteers to provide the OOMF forwarding service described in [Section 2.4.2](#) to such frames originated by the TRILL Switch whose SNPA (MAC address) appears in that Neighbor RECORD.
3. Bit 0 is allocated from the Capability bits in the PORT-TRILL-VER sub-TLV [RFC6326bis] to indicate support of the VLANs Appointed sub-TLV [RFC6326bis] and the VLAN inhibition setting mechanisms specified in [Section 10.1](#).



## **12. Security Considerations**

This memo improves the documentation of the TRILL protocol, corrects five errata in [[RFC6325](#)], and updates [[RFC6325](#)], [[RFC6327](#)], and [[RFC6439](#)]. It does not change the security considerations of these RFCs.

## Acknowledgements

The contributions of the following persons are gratefully acknowledged:

Somnath Chatterjee, Weiguo Hao, Rakesh Kumar, Yizhou Li, Radia Perlman, Mike Shand, Meral Shirazipour, and Varun Varshah.

This document was produced with raw nroff. All macros used were defined in the source file.

## Change History

RFC Editor Note: Please delete this Change History section before publication.

Changes from -01 to -02:

Add [Section 3.4](#). Minor editorial changes and update of the version and dates.

Changes from -02 to -03:

Emphasize in [Section 3.4](#) that the change is not backwards compatible and that all the RBridges in a campus must calculate the distribution trees the same way or RPFC will discard too much. Provide additional detail at the end of Item 5, [Section 4](#), as to what Channel messages can be received by an RBridge without a nickname. Add [Section 1.2](#) on incompatible changes, renumbering the former [Section 1.2](#) as 1.3.

Changes from -03 to -04:

Update author information. Numerous typos fixes and editorial changes based on the GENART review and various Area Director reviews. The update from -03 to -04 is not intended to make any technical change.

Changes from -04 to -06:

Change text to make it clear that frames are not lead cost routed through overloaded RBridges. Minor editorial changes, some to

resolve second-pass GENART comments.

## Normative References

- [802.1Q-2011] - IEEE 802.1, "IEEE Standard for Local and metropolitan area networks - Virtual Bridged Local Area Networks", IEEE Std 802.1Q-2011, May 2011.
- [Err3002] - RFC Errata, Errata ID 3002, [RFC 6325](#), <http://www.rfc-editor.org>.
- [Err3003] - RFC Errata, Errata ID 3003, [RFC 6325](#), <http://www.rfc-editor.org>.
- [Err3004] - RFC Errata, Errata ID 3004, [RFC 6325](#), <http://www.rfc-editor.org>.
- [Err3052] - RFC Errata, Errata ID 3052, [RFC 6325](#), <http://www.rfc-editor.org>.
- [Err3053] - RFC Errata, Errata ID 3053, [RFC 6325](#), <http://www.rfc-editor.org>.
- [IS-IS] - ISO/IEC 10589:2002, Second Edition, "Intermediate System to Intermediate System Intra-Domain Routing Exchange Protocol for use in Conjunction with the Protocol for Providing the Connectionless-mode Network Service (ISO 8473)", 2002.
- [RFC1195] - Callon, R., "Use of OSI IS-IS for routing in TCP/IP and dual environments", [RFC 1195](#), December 1990.
- [RFC2119] - Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC5305] - Li, T. and H. Smit, "IS-IS Extensions for Traffic Engineering", [RFC 5305](#), October 2008.
- [RFC5306] - Shand, M. and L. Ginsberg, "Restart Signaling for IS-IS", [RFC 5306](#), October 2008.
- [RFC6325] - Perlman, R., Eastlake 3rd, D., Dutt, D., Gai, S., and A. Ghanwani, "Routing Bridges (RBridges): Base Protocol Specification", [RFC 6325](#), July 2011.
- [RFC6327] - Eastlake 3rd, D., Perlman, R., Ghanwani, A., Dutt, D., and V. Manral, "Routing Bridges (RBridges): Adjacency", [RFC 6327](#), July 2011.
- [RFC6439] - Perlman, R., Eastlake, D., Li, Y., Banerjee, A., and F. Hu, "Routing Bridges (RBridges): Appointed Forwarders", [RFC 6439](#), November 2011.



[RFC6326bis] - Eastlake, D., Banerjee, A., Dutt, D., Perlman, R., and A. Ghanwani, [draft-eastlake-isis-rfc6326bis](#), work in progress.

#### Informative References

[802] - IEEE 802, "IEEE Standard for Local and metropolitan area networks: Overview and Architecture", IEEE Std 802.1-2001, 8 March 2002.

[Channel] - Eastlake, E., Manral, V., Li, Y., Ward, D., [draft-ietf-trill-rbridge-channel](#), work in progress.

[RFC5342] - Eastlake 3rd, D., "IANA Considerations and IETF Protocol Usage for IEEE 802 Parameters", [BCP 141](#), [RFC 5342](#), September 2008.





Authors' Addresses

Donald Eastlake  
Huawei R&D USA  
155 Beaver Street  
Milford, MA 01757 USA

Phone: +1-508-333-2270  
Email: d3e3e3@gmail.com

Mingui Zhang  
Huawei Technologies Co., Ltd  
Huawei Building, No.156 Beiqing Rd.  
Z-park, Shi-Chuang-Ke-Ji-Shi-Fan-Yuan, Hai-Dian District,  
Beijing 100095 P.R. China

Email: zhangmingui@huawei.com

Anoop Ghanwani  
Dell  
350 Holger Way  
San Jose, CA 95134 USA

Phone: +1-408-571-3500  
Email: anoop@alumni.duke.edu

Vishwas Manral  
HP Networking  
19111 Pruneridge Avenue  
Cupertino, CA 95014 USA

Tel: +1-408-477-0000  
Email: vishwas.manral@hp.com

Ayan Banerjee  
Cumulus Networks  
1089 West Evelyn Avenue  
Sunnyvale, CA 94086 USA

Email: ayabaner@gmail.com



## Copyright and IPR Provisions

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License. The definitive version of an IETF Document is that published by, or under the auspices of, the IETF. Versions of IETF Documents that are published by third parties, including those that are translated into other languages, should not be considered to be definitive versions of IETF Documents. The definitive version of these Legal Provisions is that published by, or under the auspices of, the IETF. Versions of these Legal Provisions that are published by third parties, including those that are translated into other languages, should not be considered to be definitive versions of these Legal Provisions. For the avoidance of doubt, each Contributor to the IETF Standards Process licenses each Contribution that he or she makes as part of the IETF Standards Process to the IETF Trust pursuant to the provisions of [RFC 5378](#). No language to the contrary, or terms, conditions or rights that differ from or are inconsistent with the rights and licenses granted under [RFC 5378](#), shall have any effect and shall be null and void, whether published or posted by such Contributor, or included with or in such Contribution.

