

URNBIS  
Internet-Draft  
Obsoletes: [2141](#) (if approved)  
Intended status: Standards Track  
Expires: May 31, 2013

P. Saint-Andre, Ed.  
Cisco Systems, Inc.  
R. Moats  
November 27, 2012

**Uniform Resource Name (URN) Syntax**  
**draft-ietf-urnbis-rfc2141bis-urn-04**

Abstract

A Uniform Resource Name (URN) is a Uniform Resource Identifier (URI) that is intended to serve as a persistent, location-independent resource identifier. The general class of URNs is differentiated from all other URIs through the use of the 'urn' URI scheme. This document defines the canonical syntax for URNs, guidelines for URN namespaces, requirements for URN presentation and transmission, and methods for determining URN equivalence. This document obsoletes [RFC 2141](#).

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 31, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.



Table of Contents

- [1. Introduction . . . . .](#) [4](#)
- [2. Discussion Venue . . . . .](#) [4](#)
- [3. Terminology . . . . .](#) [4](#)
- [4. Requirements . . . . .](#) [4](#)
- [5. URN Syntax . . . . .](#) [4](#)
  - [5.1. Namespace Identifier Syntax . . . . .](#) [5](#)
  - [5.2. Namespace Specific String Syntax . . . . .](#) [5](#)
- [6. URN Presentation and Transport . . . . .](#) [6](#)
- [7. Lexical Equivalence in URNs . . . . .](#) [6](#)
  - [7.1. Procedure . . . . .](#) [6](#)
  - [7.2. Examples . . . . .](#) [6](#)
- [8. Functional Equivalence in URNs . . . . .](#) [7](#)
- [9. Handling of URNs by URI Processors . . . . .](#) [7](#)
- [10. Security Considerations . . . . .](#) [7](#)
- [11. IANA Considerations . . . . .](#) [7](#)
- [12. References . . . . .](#) [8](#)
  - [12.1. Normative References . . . . .](#) [8](#)
  - [12.2. Informative References . . . . .](#) [8](#)
- [Appendix A. Changes from \[RFC 2141\]\(#\) . . . . .](#) [9](#)
- [Appendix B. Acknowledgements . . . . .](#) [9](#)
- [Authors' Addresses . . . . .](#) [9](#)



## **1. Introduction**

A Uniform Resource Name (URN) is a Uniform Resource Identifier (URI) [[RFC3986](#)] that is intended to serve as a persistent, location-independent resource identifier. The general class of URNs is differentiated from all other URIs through the use of the 'urn' URI scheme. This document defines the canonical syntax for URNs, guidelines for URN namespaces, requirements for URN presentation and transmission, and methods for determining URN equivalence.

URNs were originally defined in [[RFC2141](#)]. The goal of this document is to specify URNs with the smallest reasonable set of changes from the original definition while ensuring consistency with the updated specification of URIs in [[RFC3986](#)]. If approved, this document will obsolete [RFC 2141](#).

The discussion venue for this specification is the mailing list of the URNBIS Working Group; further information can be found at <https://www.ietf.org/mailman/listinfo/urn>.

## **2. Discussion Venue**

The discussion venue for this document is mailing list of the URNBIS WG; visit <https://www.ietf.org/mailman/listinfo/urn> for subscription and archive information.

## **3. Terminology**

Several important terms used in this document are defined in the URI specification [[RFC3986](#)].

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

## **4. Requirements**

The requirements for URNs are specified in [[RFC1737](#)]. This document does not modify or update those requirements.

## **5. URN Syntax**

The syntax for a URN is defined as follows using the Augmented



Backus-Naur Form (ABNF) as specified in [[RFC5234](#)].

```
URN      = "urn" ":" NID ":" NSS
          ;
          ; the URI scheme ("urn") is case-insensitive
          ;
NID      = (alphanum) 0*30(ldh) (alphanum)
          ;
          ; alphanum is defined in RFC 3986
          ;
ldh      = alphanum / "-"
NSS      = 1*(pchar)
          ;
          ; pchar is defined in RFC 3986
          ;
```

The following sections describe provide additional information about these rules.

### **[5.1.](#) Namespace Identifier Syntax**

The syntax here is slightly more restrictive than what was defined in [[RFC2141](#)], since it forbids the hyphen character "-" at the end of a NID.

NIDs are case insensitive (e.g., "ISBN" and "isbn" identify the same namespace).

### **[5.2.](#) Namespace Specific String Syntax**

Depending on the rules governing a namespace, names that are valid in a namespace might contain characters that are not allowed in URNs according to the urnchar rule (e.g., characters outside the ASCII range or characters that are reserved in URIs, such as "/", "?", and "#"). Such a string MUST be translated into a conformant NSS before using it as a protocol element or otherwise passing it on to other applications. Translation is done by percent-encoding each disallowed character using the method defined in [[RFC3986](#)].

The "%" character is allowed only for the purpose of percent-encoding.

If a namespace designates one or more characters conforming to the urnchar rule as having special meaning for that namespace (e.g., "@") and the namespace also uses that character in a literal sense, when used in a literal sense the character MUST be percent-encoded (e.g., "%40"). For related considerations with regard to NID registration, see [[RFC3406](#)].





## **6. URN Presentation and Transport**

The URN syntax defines the canonical format for URNs. All URN transport and interchanges **MUST** take place in this format. Further, all URN-aware applications **MUST** offer the option of displaying URNs in this canonical form to allow for direct transcription (for example by cut and paste techniques). Such applications might support display of URNs in a more human-friendly form and might use a character set that includes characters that are not permitted in URN syntax as defined in this RFC (i.e., when displaying URNs to humans, such applications might replace percent-encoded strings with characters in an extended character set such as Unicode).

## **7. Lexical Equivalence in URNs**

### **7.1. Procedure**

For various purposes such as caching, often it is desirable to determine if two URNs are "the same". This is done by testing for "lexical equivalence".

Two URNs are lexically equivalent if they are octet-by-octet equal after the following preprocessing rules:

1. normalize the case of the URI scheme "urn"
2. normalize the case of the NID
3. normalize the case of any percent-encoding

Note: Percent-encoded characters **MUST NOT** be decoded.

URN namespaces **MAY** define additional rules for lexical equivalence, such as case-insensitivity of the NSS (or parts thereof). Such rules **MUST** always have the effect of eliminating some of the false negatives obtained by the procedure above and **MUST NOT** result in treating two URNs as not equivalent if the procedure here says they are equivalent. For related considerations with regard to NID registration, see [[RFC3406](#)].

### **7.2. Examples**

The following URN comparisons highlight the lexical equivalence rules:

1. URN:foo:a123,456
2. urn:foo:a123,456



3. urn:F00:a123,456
4. urn:foo:A123,456
5. urn:foo:a123%2C456
6. URN:F00:a123%2c456

URNs 1, 2, and 3 are lexically equivalent. URN 4 is not lexically equivalent to any of the other URNs in the above set. URNs 5 and 6 are lexically equivalent only to each other.

## **8. Functional Equivalence in URNs**

Functional equivalence is determined within a given namespace and managed by resolvers for that namespace, and thus is beyond the scope of this document. For related considerations with regard to NID registration, see [[RFC3406](#)].

## **9. Handling of URNs by URI Processors**

The URN syntax has been defined so that URNs can be used in places where URIs are expected. A resolver that conforms to the URI specification [[RFC3986](#)] will extract a scheme of "urn" rather than a scheme value of "urn:<nid>".

A URN MUST be considered an opaque URI by URI resolvers and passed (with the "urn" scheme) to a URN resolver for resolution. The URN resolver can either be an external resolver that the URI resolver knows of, or it can be functionality built-in to the URI resolver.

To minimize user confusion, a URI browser SHOULD display the complete URN (including the "urn" scheme) to ensure that there is no confusion between URN namespace identifiers and URL scheme identifiers.

## **10. Security Considerations**

This document specifies the syntax for URNs. While some namespaces resolvers may assign special meaning to certain of the characters of the Namespace Specific String, any security consideration resulting from such assignment are outside the scope of this document. For related considerations with regard to NID registration, see [[RFC3406](#)].

## **11. IANA Considerations**

This section formally registers a URI scheme of 'urn'.



[Note to RFC Editor: please change "XXXX" to the number assigned to this document upon publication.]

URI Scheme Name: urn

Status: permanent

URI Scheme Syntax: See [Section 4](#) of RFCXXXX.

URI Scheme Semantics: The 'urn' scheme identifies Uniform Resource Names, which are persistent, location-independent resource identifiers.

Encoding Considerations: See [Section 4.2](#) of RFCXXXX.

Applications/Protocols That Use This URI Scheme Name: Uniform Resource Names are used in a wide variety of applications, including bibliographical reference systems and as names for Extensible Markup Language (XML) namespaces.

Interoperability Considerations: There are no known interoperability concerns related to use of the 'urn' URI scheme.

Security Considerations: See [Section 9](#) of RFCXXXX.

Contact: URNBIS WG [mailto:urn@ietf.org]

Author/Change Controller: This scheme is registered under the IETF tree. As such, the IETF maintains change control.

References None.

## [12.](#) References

### [12.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.

### [12.2.](#) Informative References

- [RFC1737] Sollins, K. and L. Masinter, "Functional Requirements for Uniform Resource Names", [RFC 1737](#), December 1994.
- [RFC2141] Moats, R., "URN Syntax", [RFC 2141](#), May 1997.
- [RFC3406] Daigle, L., van Gulik, D., Iannella, R., and P. Faltstrom, "Uniform Resource Names (URN) Namespace Definition Mechanisms", [BCP 66](#), [RFC 3406](#), October 2002.



### **Appendix A. Changes from RFC 2141**

This document makes the following substantive changes from [[RFC2141](#)]:

- o Disallowed "-" at the end of a NID.
- o Allowed the "~" and "&" characters in an NSS.
- o Formally registered 'urn' as a URI scheme.

### **Appendix B. Acknowledgements**

[RFC 2141](#), which provided the basis for this document, was authored by Ryan Moats.

Thanks to Julian Reschke for his corrections to the ABNF.

#### Authors' Addresses

Peter Saint-Andre (editor)  
Cisco Systems, Inc.  
1899 Wynkoop Street, Suite 600  
Denver, CO 80202  
USA

Phone: +1-303-308-3282  
Email: [psaintan@cisco.com](mailto:psaintan@cisco.com)

Ryan Moats



