

Network Working Group  
[draft-ietf-v6ops-ipv4survey-ops-05.txt](#)  
Internet Draft

Philip J. Nesser II  
Nesser & Nesser Consulting  
Andreas Bergstrom (Ed.)  
Ostfold University College  
December 2003  
Expires May 2004

## **Survey of IPv4 Addresses in Currently Deployed IETF Operations & Management Area Standards**

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Status of this Memo

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at  
<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at  
<http://www.ietf.org/shadow.html>.

### **Abstract**

This document seeks to document all usage of IPv4 addresses in currently deployed IETF Operations & Management Area documented standards. In order to successfully transition from an all IPv4 Internet to an all IPv6 Internet, many interim steps will be taken. One of these steps is the evolution of current protocols that have IPv4 dependencies. It is hoped that these protocols (and their implementations) will be redesigned to be network address independent, but failing that will at least dually support IPv4 and IPv6. To this end, all Standards (Full, Draft, and Proposed) as well as Experimental RFCs will be surveyed and any dependencies will be documented.

### **Table of Contents**

- [1. Introduction](#)**
- [2. Document Organisation](#)**
- [3. Full Standards](#)**
- [4. Draft Standards](#)**
- [5. Proposed Standards](#)**

<a href="#">6. Experimental RFCs</a>	
<a href="#">7. Summary of Results</a>	
<a href="#">7.1 Standards</a>	
7.2 Draft Standards	
7.3 Proposed Standards	7.4 Experimental RFCs
<a href="#">8. Security Consideration</a>	
<a href="#">9. Acknowledgements</a>	
<a href="#">10. References</a>	
<a href="#">11. Authors' Addresses</a>	
<a href="#">12. Intellectual Property Statement</a>	
<a href="#">13. Full Copyright Statement</a>	

## [1.0 Introduction](#)

This document is part of a document set aiming to document all usage of IPv4 addresses in IETF standards. In an effort to have the information in a manageable form, it has been broken into 7 documents conforming to the current IETF areas (Application, Internet, Management & Operations, Routing, Security, Sub-IP and Transport).

For a full introduction, please see the introduction [[1](#)].

## [2.0 Document Organization](#)

The document is organized as described below:

Sections [3](#), [4](#), [5](#), and [6](#) each describe the raw analysis of Full, Draft, and Proposed Standards, and Experimental RFCs. Each RFC is discussed in its turn starting with [RFC 1](#) and ending with (around) [RFC 3100](#). The comments for each RFC are "raw" in nature. That is, each RFC is discussed in a vacuum and problems or issues discussed do not "look ahead" to see if the problems have already been fixed.

[Section 7](#) is an analysis of the data presented in Sections [3](#), [4](#), [5](#), and [6](#). **It is here that all of the results are considered as a whole and the problems that have been resolved in later RFCs are correlated.**

## [3.0 Full Standards](#)

Full Internet Standards (most commonly simply referred to as "Standards") are fully mature protocol specification that are widely implemented and used throughout the Internet.

### [3.1 RFC 1155](#) Structure of Management Information

[Section 3.2.3.2](#). IPAddress defines the following:

This application-wide type represents a 32-bit internet address. It is represented as an OCTET STRING of length 4, in network byte-order.

There are several instances of the use of this definition in the rest of the document.

### **[3.2 RFC 1212](#) Concise MIB definitions**

In [section 4.1.6](#) `IpAddress` is defined as:

- (6) `IpAddress-valued`: 4 sub-identifiers, in the familiar a.b.c.d notation.

### **[3.3 RFC 1213](#) Management Information Base**

There are far too many instances of IPv4 addresses in this document to enumerate here. The particular object groups that are affected are the IP group, the ICMP group, the TCP group, the UDP group, and the EGP group.

### **[3.4 RFC 2578](#) Structure of Management Information Version 2 (SMIV2)**

[Section 7.1.5](#) defines the `IpAddress` data type:

The `IpAddress` type represents a 32-bit internet address. It is represented as an OCTET STRING of length 4, in network byte-order.

Note that the `IpAddress` type is a tagged type for historical reasons. Network addresses should be represented using an invocation of the `TEXTUAL-CONVENTION` macro.

Note the deprecated status of this type; see [RFC 3291](#) for details on the replacement `TEXTUAL-CONVENTION` definitions.

### **[3.5 RFC 2579](#) Textual Conventions for SMIV2**

There are no IPv4 dependencies in this specification.

### **[3.6 RFC 2580](#) Conformance Statements for SMIV2**

There are no IPv4 dependencies in this specification.

### **[3.7 RFC 2819](#) Remote Network Monitoring Management Information Base**

There are no IPv4 dependencies in this specification.

### **[3.8 RFC 3411](#) An Architecture for Describing SNMP Management Frameworks**

There are no IPv4 dependencies in this specification.

### [3.9 RFC 3412](#) Message Processing and Dispatching for the Simple Network Management Protocol (SNMP)

There are no IPv4 dependencies in this specification.

### [3.10 RFC 3413](#) SNMP Applications

There are no IPv4 dependencies in this specification.

### [3.11 RFC 3414](#) User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)

There are no IPv4 dependencies in this specification.

### [3.12 RFC 3415](#) View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)

There are no IPv4 dependencies in this specification.

### [3.13 RFC 3416](#) Protocol Operations for Version 2 of the Simple Network Management Protocol (SNMP)

[Section 4.2.2.1](#). Example of Table Traversal and [Section 4.2.3.1](#). Another Example of Table Traversal both use objects from MIB2 whose data contains IPv4 addresses. Other than their use in these example sections there are no IPv4 dependencies in this specification.

### [3.14 RFC 3417](#) Transport Mappings for Version 2 of the Simple Network Management Protocol (SNMP)

[Section 2](#) Definitions contains the following definition:

```
SnmpUDPAddress ::= TEXTUAL-CONVENTION
    DISPLAY-HINT "1d.1d.1d.1d/2d"
    STATUS      current
    DESCRIPTION
        "Represents a UDP address:

            octets  contents      encoding
            1-4     IP-address    network-byte order
            5-6     UDP-port      network-byte order
        "
    SYNTAX      OCTET STRING (SIZE (6))
```

[Section 8.1](#), "Usage Example," also contains examples which uses IPv4 address, but it has no significance in the operation of the specification.

### **[3.15 RFC 3418](#) Management Information Base for Version 2 of the Simple Network Management Protocol (SNMP)**

There are no IPv4 dependencies in this specification.

## **[4.0](#) Draft Standards**

Draft Standards represent the penultimate standard level in the IETF. A protocol can only achieve draft standard when there are multiple, independent, interoperable implementations. Draft Standards are usually quite mature and widely used.

### **[4.01 RFC 1493](#) Definitions of Managed Objects for Bridges**

There are no IPv4 dependencies in this specification.

### **[4.02 RFC 1559](#) DECnet Phase IV MIB Extensions**

There are no IPv4 dependencies in this specification.

### **[4.03 RFC 1657](#) Definitions of Managed Objects for the Fourth Version of the Border Gateway Protocol (BGP-4) using SMIPv2**

The MIB defined in this RFC deals with objects in a BGP4 based routing system and therefore contain many objects that are limited by the IPAddress 32-bit value defined in MIB2. Clearly the values of this MIB are limited to IPv4 addresses. No update is needed, although a new MIB should be defined for BGP4+ to allow management of IPv6 addresses and routes.

### **[4.04 RFC 1658](#) Definitions of Managed Objects for Character Stream Devices using SMIPv2**

There are no IPv4 dependencies in this specification.

### **[4.05 RFC 1659](#) Definitions of Managed Objects for RS-232-like Hardware Devices using SMIPv2**

There are no IPv4 dependencies in this specification.

### **[4.06 RFC 1660](#) Definitions of Managed Objects for Parallel-printer-like Hardware Devices using SMIPv2**

There are no IPv4 dependencies in this specification.

#### [4.07 RFC 1694](#) Definitions of Managed Objects for SMDS Interfaces using SMIV2

This MIB module definition defines the following subtree:

```
ipOverSMDS OBJECT IDENTIFIER ::= { smdsApplications 1 }

-- Although the objects in this group are read-only, at the
-- agent's discretion they may be made read-write so that the
-- management station, when appropriately authorized, may
-- change the addressing information related to the
-- configuration of a logical IP subnetwork implemented on
-- top of SMDS.

-- This table is necessary to support RFC1209 (IP-over-SMDS)
-- and gives information on the Group Addresses and ARP
-- Addresses used in the Logical IP subnetwork.
-- One SMDS address may be associated with multiple IP
-- addresses. One SNI may be associated with multiple LISs.

ipOverSMDSTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF IpOverSMDSEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "The table of addressing information relevant to
        this entity's IP addresses."
    ::= { ipOverSMDS 1 }

ipOverSMDSEntry OBJECT-TYPE
    SYNTAX      IpOverSMDSEntry
    MAX-ACCESS   not-accessible
    STATUS       current
    DESCRIPTION
        "The addressing information for one of this
        entity's IP addresses."
    INDEX       { ipOverSMDSIndex, ipOverSMDSAddress }
    ::= { ipOverSMDSTable 1 }

IpOverSMDSEntry ::=
    SEQUENCE {
        ipOverSMDSIndex      IfIndex,
        ipOverSMDSAddress     IPAddress,
        ipOverSMDSHA          SMDSAddress,
        ipOverSMDSLISGA       SMDSAddress,
        ipOverSMDSARPReq      SMDSAddress
    }

ipOverSMDSIndex OBJECT-TYPE
```

```

SYNTAX      IfIndex
MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The value of this object identifies the
    interface for which this entry contains management
    information. "
 ::= { ipOverSMDSEntry 1 }

```

```

ipOverSMDSEntry 1 OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The IP address to which this entry's addressing
        information pertains."
    ::= { ipOverSMDSEntry 2 }

```

```

ipOverSMDSEntry 2 OBJECT-TYPE
    SYNTAX      SMDSEntry
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The SMDSEntry Individual address of the IP station."
    ::= { ipOverSMDSEntry 3 }

```

```

ipOverSMDSEntry 3 OBJECT-TYPE
    SYNTAX      SMDSEntry
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The SMDSEntry Group Address that has been configured
        to identify the SMDSEntry Subscriber-Network Interfaces
        (SNIs) of all members of the Logical IP Subnetwork
        (LIS) connected to the network supporting SMDSEntry."
    ::= { ipOverSMDSEntry 4 }

```

```

ipOverSMDSEntry 4 OBJECT-TYPE
    SYNTAX      SMDSEntry
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The SMDSEntry address (individual or group) to which
        ARP Requests are to be sent."
    ::= { ipOverSMDSEntry 5 }

```

Although these object definitions are intended for IPv4 addresses, a similar MIB can be defined for IPv6 addressing.

#### [4.08 RFC 1724](#) **RIP Version 2 MIB Extension**

As might be expected, this RFC is filled with IPv4 dependencies since it defines a MIB module for an IPv4-only routing protocol. A new MIB for RIPng is required.

#### [4.09 RFC 1748](#) **IEEE 802.5 MIB using SMIV2**

There are no IPv4 dependencies in this specification.

#### [4.10 RFC 1850](#) **OSPF Version 2 Management Information Base**

This MIB defines managed objects for OSPFv2 which is a protocol used to exchange IPv4 routing information. Since OSPFv2 is limited to IPv4 addresses a new MIB is required to support a new version of OSPF that is IPv6 aware.

#### [4.11 RFC 2115](#) **Management Information Base for Frame Relay DTEs Using SMIV2**

This specification has several examples of how IPv4 addresses might be mapped to Frame Relay DLCIs. Other than those examples there are no IPv4 dependencies in this specification.

#### [4.12 RFC 2790](#) **Host Resources MIB**

There are no IPv4 dependencies in this specification.

#### [4.13 RFC 2863](#) **The Interfaces Group MIB**

There are no IPv4 dependencies in this specification. There is some discussion in one object definition about an interface performing a self test, but the object itself is IP version independent.

#### [4.14 RFC 3592](#) **Definitions of Managed Objects for the Synchronous Optical Network/Synchronous Digital Hierarchy (SONET/SDH)**

There are no IPv4 dependencies in this specification.

#### [4.15 RFC 3593](#) **Textual Conventions for MIB Modules Using Performance History Based on 15 Minute Intervals.**

There are no IPv4 dependencies in this specification.



## **[5.0](#) Proposed Standards**

Proposed Standards are introductory level documents. There are no requirements for even a single implementation. In many cases Proposed are never implemented or advanced in the IETF standards process. They therefore are often just proposed ideas that are presented to the Internet community. Sometimes flaws are exposed or they are one of many competing solutions to problems. In these later cases, no discussion is presented as it would not serve the purpose of this discussion.

### **[5.001](#) [RFC 1239](#) Reassignment of experimental MIBs to standard MIBs**

There are no IPv4 dependencies in this specification.

### **[5.002](#) [RFC 1269](#) Definitions of Managed Objects for the Border Gateway Protocol: Version 3**

The use of BGP3 has been deprecated and is not discussed.

### **[5.003](#) [RFC 1285](#) FDDI Management Information Base**

There are no IPv4 dependencies in this specification.

### **[5.004](#) [RFC 1381](#) SNMP MIB Extension for X.25 LAPB**

There are no IPv4 dependencies in this specification.

### **[5.005](#) [RFC 1382](#) SNMP MIB Extension for the X.25 Packet Layer**

There are no IPv4 dependencies in this specification.

### **[5.006](#) [RFC 1414](#) Identification MIB**

There are no IPv4 dependencies in this specification.

### **[5.007](#) [RFC 1418](#) SNMP over OSI**

There are no IPv4 dependencies in this specification.

### **[5.008](#) [RFC 1419](#) SNMP over AppleTalk**

There are no IPv4 dependencies in this specification.

### [5.009 RFC 1420](#) SNMP over IPX

There are no IPv4 dependencies in this specification.

### [5.010 RFC 1461](#) SNMP MIB extension for Multiprotocol Interconnect over X.25

The following objects are defined in [Section 4](#) "Definitions":

```
mioxPleLastFailedEnAddr OBJECT-TYPE
    SYNTAX  OCTET STRING (SIZE(2..128))
    ACCESS  read-only
    STATUS  mandatory
    DESCRIPTION
        "The last Encapsulated address that failed
        to find a corresponding X.121 address and
        caused mioxPleEnAddrToX121LkupFlrs to be
        incremented.  The first octet of this object
        contains the encapsulation type, the
        remaining octets contain the address of that
        type that failed.  Thus for an IP address,
        the length will be five octets, the first
        octet will contain 204 (hex CC), and the
        last four octets will contain the IP
        address.  For a snap encapsulation, the
        first byte would be 128 (hex 80) and the
        rest of the octet string would have the snap
        header."
    ::= { mioxPleEntry 4 }
```

  

```
mioxPeerEnAddr OBJECT-TYPE
    SYNTAX  OCTET STRING (SIZE (0..128))
    ACCESS  read-write
    STATUS  mandatory
    DESCRIPTION
        "The Encapsulation address of the remote
        host mapped by this table entry.  A length
        of zero indicates the remote IP address is
        unknown or unspecified for use as a PLE
        default.

        The first octet of this object contains the
        encapsulation type, the remaining octets
        contain an address of that type.  Thus for
        an IP address, the length will be five
        octets, the first octet will contain 204
        (hex CC), and the last four octets will
        contain the IP address.  For a snap
        encapsulation, the first byte would be 128
        (hex 80) and the rest of the octet string
```

```

        would have the snap header."
DEFVAL { 'h }
::= { mioxPeerEntry 7 }

```

mioxPeerEncType OBJECT-TYPE

SYNTAX INTEGER (0..256)

ACCESS read-write

STATUS mandatory

DESCRIPTION

"The value of the encapsulation type. For IP encapsulation this will have a value of 204 (hex CC). For SNAP encapsulated packets, this will have a value of 128 (hex 80). For CLNP, ISO 8473, this will have a value of 129 (hex 81). For ES-ES, ISO 9542, this will have a value of 130 (hex 82). A value of 197 (hex C5) identifies the Blacker X.25 encapsulation. A value of 0, identifies the Null encapsulation.

This value can only be written when the mioxPeerStatus object with the same mioxPeerIndex has a value of underCreation. Setting this object to a value of 256 deletes the entry. When deleting an entry, all other entries in the mioxPeerEncTable with the same mioxPeerIndex and with an mioxPeerEncIndex higher then the deleted entry, will all have their mioxPeerEncIndex values decremented by one."

```

::= { mioxPeerEncEntry 2 }

```

Updated values of the first byte of these objects can be defined to support IPv6 addresses.

#### **5.011 RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol**

There are no IPv4 dependencies in this specification.

#### **5.012 RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol**

There are no IPv4 dependencies in this specification.

#### **5.013 RFC 1473 The Definitions of Managed Objects for the IP Network Control Protocol of the Point-to-Point Protocol**

This MIB module is targeted specifically at IPv4 over PPP. A new

MIB moduld would need to be defined to support IPv6 over PPP.

**[5.014 RFC 1474](#) The Definitions of Managed Objects for the Bridge Network Control Protocol of the Point-to-Point Protocol**

There are no IPv4 dependencies in this specification.

**[5.015 RFC 1512](#) FDDI Management Information Base**

There are no IPv4 dependencies in this specification.

**[5.016 RFC 1513](#) Token Ring Extensions to the Remote Network Monitoring MIB**

There are no IPv4 dependencies in this specification.

**[5.017 RFC 1525](#) Definitions of Managed Objects for Source Routing Bridges**

There are no IPv4 dependencies in this specification.

**[5.018 RFC 1628](#) UPS Management Information Base**

There are no IPv4 dependencies in this specification.

**[5.019 RFC 1666](#) Definitions of Managed Objects for SNA NAUs using SMIV2**

There are no IPv4 dependencies in this specification.

**[5.020 RFC 1696](#) Modem Management Information Base (MIB) using SMIV2**

There are no IPv4 dependencies in this specification.

**[5.021 RFC 1697](#) Relational Database Management System (RDBMS) Management Information Base (MIB) using SMIV2**

There are no IPv4 dependencies in this specification.

**[5.022 RFC 1742](#) AppleTalk Management Information Base II**

The following OIDs are defined:

```
KipEntry ::= SEQUENCE {  
    kipNetStart      ATNetworkNumber,
```

```

        kipNetEnd      ATNetworkNumber,
        kipNextHop     IPAddress,
        kipHopCount    INTEGER,
        kipBCastAddr   IPAddress,
        kipCore        INTEGER,
        kipType        INTEGER,
        kipState       INTEGER,
        kipShare       INTEGER,
        kipFrom        IPAddress
    }

kipNextHop OBJECT-TYPE
    SYNTAX IPAddress
    ACCESS read-write
    STATUS mandatory
    DESCRIPTION
        "The IP address of the next hop in the route to this
        entry's destination network."
    ::= { kipEntry 3 }

kipBCastAddr OBJECT-TYPE
    SYNTAX IPAddress
    ACCESS read-write
    STATUS mandatory
    DESCRIPTION
        "The form of the IP address used to broadcast on this
        network."
    ::= { kipEntry 5 }

kipFrom OBJECT-TYPE
    SYNTAX IPAddress
    ACCESS read-only
    STATUS mandatory
    DESCRIPTION
        "The IP address from which the routing entry was
        learned via the AA protocol.  If this entry was not
        created via the AA protocol, it should contain IP
        address 0.0.0.0."
    ::= { kipEntry 10 }

```

#### **5.023 RFC 1747 Definitions of Managed Objects for SNA Data Link Control (SDLC) using SMIV2**

There are no IPv4 dependencies in this specification.

#### **5.024 RFC 1749 IEEE 802.5 Station Source Routing MIB using SMIV2**

There are no IPv4 dependencies in this specification.

#### **[5.025 RFC 1759](#) Printer MIB**

There are no IPv4 dependencies in this specification.

#### **[5.026 RFC 2006](#) The Definitions of Managed Objects for IP Mobility Support using SMIPv2**

This document defines a MIB for the Mobile IPv4. Without enumeration, let it be stated that a new MIB for IPv6 Mobility is required.

#### **[5.027 RFC 2011](#) SNMPv2 Management Information Base for the Internet Protocol using SMIPv2**

Approximately 1/3 of the objects defined in this document are IPv4-dependent. New objects need to be defined to support IPv6.

#### **[5.028 RFC 2012](#) SNMPv2 Management Information Base for the Transmission Control Protocol using SMIPv2**

A number of object definitions in this MIB assumes IPv4 addresses, as is noted in the note reproduced below:

IESG Note:

The IP, UDP, and TCP MIB modules currently support only IPv4. These three modules use the IpAddress type defined as an OCTET STRING of length 4 to represent the IPv4 32-bit internet addresses. (See [RFC 1902](#), SMI for SNMPv2.) They do not support the new 128-bit IPv6 internet addresses.

#### **[5.029 RFC 2013](#) SNMPv2 Management Information Base for the User Datagram Protocol using SMIPv2**

A number of OIDs in this MIB assumes IPv4 addresses, as is noted in the note reproduced below:

IESG Note:

The IP, UDP, and TCP MIB modules currently support only IPv4. These three modules use the IpAddress type defined as an OCTET STRING of length 4 to represent the IPv4 32-bit internet addresses. (See [RFC 1902](#), SMI for SNMPv2.) They do not support the new 128-bit IPv6 internet addresses.

#### **[5.030 RFC 2020](#) IEEE 802.12 Interface MIB**

There are no IPv4 dependencies in this specification.

### [5.031 RFC 2021](#) Remote Network Monitoring Management Information Base Version 2 using SMIV2

The following objects are defined:

#### addressMapNetworkAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS not-accessible

STATUS current

##### DESCRIPTION

"The network address for this relation.

This is represented as an octet string with specific semantics and length as identified by the protocolDirLocalIndex component of the index.

For example, if the protocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { addressMapEntry 2 }

#### nlHostAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS not-accessible

STATUS current

##### DESCRIPTION

"The network address for this nlHostEntry.

This is represented as an octet string with specific semantics and length as identified by the protocolDirLocalIndex component of the index.

For example, if the protocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { nlHostEntry 2 }

#### nlMatrixSDSourceAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS not-accessible

STATUS current

##### DESCRIPTION

"The network source address for this nlMatrixSDEntry.

This is represented as an octet string with specific semantics and length as identified by the protocolDirLocalIndex component of the index.

For example, if the protocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { nlMatrixSDEntry 2 }

nlMatrixSDDestAddress OBJECT-TYPE

SYNTAX        OCTET STRING  
MAX-ACCESS   not-accessible  
STATUS        current  
DESCRIPTION

"The network destination address for this nlMatrixSDEntry.

This is represented as an octet string with specific semantics and length as identified by the protocolDirLocalIndex component of the index.

For example, if the protocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { nlMatrixSDEntry 3 }

nlMatrixDSSourceAddress OBJECT-TYPE

SYNTAX        OCTET STRING  
MAX-ACCESS   not-accessible  
STATUS        current  
DESCRIPTION

"The network source address for this nlMatrixDSEntry.

This is represented as an octet string with specific semantics and length as identified by the protocolDirLocalIndex component of the index.

For example, if the protocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { nlMatrixDSEntry 2 }

nlMatrixDSDestAddress OBJECT-TYPE

SYNTAX        OCTET STRING  
MAX-ACCESS   not-accessible  
STATUS        current  
DESCRIPTION

"The network destination address for this nlMatrixDSEntry.

This is represented as an octet string with specific semantics and length as identified



by the protocolDirLocalIndex component of the index.

For example, if the protocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { nlMatrixDSEntry 3 }

#### nlMatrixTopNSourceAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-only

STATUS current

##### DESCRIPTION

"The network layer address of the source host in this conversation.

This is represented as an octet string with specific semantics and length as identified by the associated nlMatrixTopNProtocolDirLocalIndex.

For example, if the protocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { nlMatrixTopNEntry 3 }

#### nlMatrixTopNDestAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-only

STATUS current

##### DESCRIPTION

"The network layer address of the destination host in this conversation.

This is represented as an octet string with specific semantics and length as identified by the associated nlMatrixTopNProtocolDirLocalIndex.

For example, if the nlMatrixTopNProtocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { nlMatrixTopNEntry 4 }

#### alMatrixTopNSourceAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-only

STATUS current

##### DESCRIPTION

"The network layer address of the source host in this conversation.

This is represented as an octet string with specific semantics and length as identified by the associated alMatrixTopNProtocolDirLocalIndex.

For example, if the alMatrixTopNProtocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { alMatrixTopNEntry 3 }

alMatrixTopNDestAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The network layer address of the destination host in this conversation.

This is represented as an octet string with specific semantics and length as identified by the associated alMatrixTopNProtocolDirLocalIndex.

For example, if the alMatrixTopNProtocolDirLocalIndex indicates an encapsulation of ip, this object is encoded as a length octet of 4, followed by the 4 octets of the ip address, in network byte order."

::= { alMatrixTopNEntry 4 }

trapDestProtocol OBJECT-TYPE

SYNTAX INTEGER {  
    ip(1),  
    ipx(2)  
}

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The protocol with which to send this trap."

::= { trapDestEntry 3 }

trapDestAddress OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The address to send traps on behalf of this entry.

If the associated trapDestProtocol object is equal to ip(1), the encoding of this object is the same as the snmpUDPAddress textual convention in [\[RFC1906\]](#):

```
-- for a SnmpUDPAddress of length 6:  
--
```

```

-- octets    contents    encoding
-- 1-4       IP-address   network-byte order
-- 5-6       UDP-port     network-byte order

```

If the associated trapDestProtocol object is equal to ipx(2), the encoding of this object is the same as the snmpIPXAddress textual convention in [\[RFC1906\]](#):

```

-- for a SnmpIPXAddress of length 12:
--
-- octets    contents    encoding
-- 1-4       network-number    network-byte order
-- 5-10      physical-address   network-byte order
-- 11-12     socket-number     network-byte order

```

This object may not be modified if the associated trapDestStatus object is equal to active(1)."

```
 ::= { trapDestEntry 4 }
```

All of the object definitions above (except trapDestProtocol) mention only IPv4 addresses but since they use a SYNTAX of OCTET STRING, they should work fine for IPv6 addresses. A new legitimate value of trapDestProtocol (i.e. SYNTAX addition of ipv6(3) should make this specification functional for IPv6.

### **5.032 RFC 2024 Definitions of Managed Objects for Data Link Switching using SMIV2**

The following textual conventions are defined:

```
TAddress ::= TEXTUAL-CONVENTION
```

```
    STATUS    current
```

```
    DESCRIPTION
```

```
        "Denotes a transport service address.
```

```
        For dlswTCPDomain, a TAddress is 4 octets long,
        containing the IP-address in network-byte order."
```

```
    SYNTAX    OCTET STRING (SIZE (0..255))
```

```
-- DLsw over TCP
```

```
dlswTCPDomain OBJECT IDENTIFIER ::= { dlswDomains 1 }
```

```
-- for an IP address of length 4:
```

```
--
```

```

-- octets    contents    encoding
-- 1-4       IP-address   network-byte order
--

```

```
DlswTCPAddress ::= TEXTUAL-CONVENTION
```

```
    DISPLAY-HINT "1d.1d.1d.1d"
```

```
    STATUS    current
```

```
    DESCRIPTION
```

```
        "Represents the IP address of a DLsw which uses
        TCP as a transport protocol."
```

SYNTAX            OCTET STRING (SIZE (4))

Additionally there are many object definitions that use a SYNTAX of TAddress within the document. Interestingly the SYNTAX for TAddress is an OCTET string of up to 256 characters. It could easily accommodate a similar hybrid format for IPv6 addresses.

A new OID to enhance functionality for DlswTCPAddress could be added to support IPv6 addresses.

#### **[5.033 RFC 2051](#) Definitions of Managed Objects for APPC using SMIV2**

There are no IPv4 dependencies in this specification.

#### **[5.034 RFC 2096](#) IP Forwarding Table MIB**

The MIB module's main conceptual table ipCidrRouteTable uses IPv4 addresses as index objects and is therefore incapable of representing an IPv6 forwarding information base. A new conceptual table needs to be defined to support IPv6 addresses.

#### **[5.035 RFC 2108](#) Definitions of Managed Objects for IEEE 802.3 Repeater Devices using SMIV2 802**

There are no IPv4 dependencies in this specification.

#### **[5.036 RFC 2127](#) ISDN Management Information Base using SMIV2**

There are no IPv4 dependencies in this specification.

#### **[5.037 RFC 2128](#) Dial Control Management Information Base using SMIV2**

There are no IPv4 dependencies in this specification.

#### **[5.038 RFC 2206](#) RSVP Management Information Base using SMIV2**

All of the relevant object definitions in this MIB have options for both IPv4 and IPv6. There are no IPv4 dependencies in this specification.

#### **[5.039 RFC 2213](#) Integrated Services Management Information Base using SMIV2**

This MIB is IPv6 aware and therefore there are no IPv4 dependencies in this specification.

**[5.040 RFC 2214](#) Integrated Services Management Information  
Base Guaranteed Service Extensions using SMIPv2**

There are no IPv4 dependencies in this specification.

**[5.041 RFC 2232](#) Definitions of Managed Objects for DLUR using  
SMIPv2**

There are no IPv4 dependencies in this specification.

**[5.042 RFC 2238](#) Definitions of Managed Objects for HPR using  
SMIPv2**

There are no IPv4 dependencies in this specification.

**[5.043 RFC 2266](#) Definitions of Managed Objects for IEEE 802.12  
Repeater Devices**

There are no IPv4 dependencies in this specification.

**[5.044 RFC 2287](#) Definitions of System-Level Managed Objects for  
Applications**

There are no IPv4 dependencies in this specification.

**[5.045 RFC 2320](#) Definitions of Managed Objects for Classical IP  
and ARP Over ATM Using SMIPv2 (IPOA-MIB)**

This MIB is wholly dependent on IPv4. A new MIB for IPv6 is required to provide the same functionality.

**[5.046 RFC 2417](#) Definitions of Managed Objects for Multicast  
over UNI 3.0/3.1 based ATM Networks**

This MIB is wholly dependent on IPv4. A new MIB for IPv6 is required to provide the same functionality.

**[5.047 RFC 2452](#) IP Version 6 Management Information Base for the  
Transmission Control Protocol**

This RFC documents a soon to be obsoleted IPv6 MIB and is not considered in this discussion.

**[5.048 RFC 2454](#) IP Version 6 Management Information Base for the User Datagram Protocol**

This RFC documents a soon to be obsoleted IPv6 MIB and is not considered in this discussion.

**[5.049 RFC 2455](#) Definitions of Managed Objects for APPN**

There are no IPv4 dependencies in this specification.

**[5.050 RFC 2456](#) Definitions of Managed Objects for APPN TRAPS**

There are no IPv4 dependencies in this specification.

**[5.051 RFC 2457](#) Definitions of Managed Objects for Extended Border Node**

There are no IPv4 dependencies in this specification.

**[5.052 RFC 2465](#) Management Information Base for IP Version 6: Textual Conventions and General Group**

This RFC documents a soon to be obsoleted IPv6 MIB and is not considered in this discussion.

**[5.053 RFC 2466](#) Management Information Base for IP Version 6: ICMPv6 Group**

This RFC documents a soon to be obsoleted IPv6 MIB and is not considered in this discussion.

**[5.054 RFC 2494](#) Definitions of Managed Objects for the DS0 and DS0 Bundle Interface Type**

There are no IPv4 dependencies in this specification.

**[5.055 RFC 2495](#) Definitions of Managed Objects for the DS1, E1, DS2 and E2 Interface Types**

There are no IPv4 dependencies in this specification.

**[5.056 RFC 2496](#) Definitions of Managed Object for the DS3/E3 Interface Type**

There are no IPv4 dependencies in this specification.

#### [5.057 RFC 2512](#) Accounting Information for ATM Networks

There are no IPv4 dependencies in this specification.

#### [5.058 RFC 2513](#) Managed Objects for Controlling the Collection and Storage of Accounting Information for Connection-Oriented Networks

There are no IPv4 dependencies in this specification.

#### [5.059 RFC 2514](#) Definitions of Textual Conventions and OBJECT-IDENTITIES for ATM Management

There are no IPv4 dependencies in this specification.

#### [5.060 RFC 2515](#) Definitions of Managed Objects for ATM Management

This MIB defines the following objects:

```
AtmInterfaceConfEntry ::= SEQUENCE {
    atmInterfaceMaxVpcs          INTEGER,
    atmInterfaceMaxVccs          INTEGER,
    atmInterfaceConfVpcs         INTEGER,
    atmInterfaceConfVccs         INTEGER,
    atmInterfaceMaxActiveVpiBits INTEGER,
    atmInterfaceMaxActiveVciBits INTEGER,
    atmInterfaceIlmiVpi          AtmVpIdentifier,
    atmInterfaceIlmiVci          AtmVcIdentifier,
    atmInterfaceAddressType      INTEGER,
    atmInterfaceAdminAddress     AtmAddr,
    atmInterfaceMyNeighborIpAddress IpAddress,
    atmInterfaceMyNeighborIfName  DisplayString,
    atmInterfaceCurrentMaxVpiBits INTEGER,
    atmInterfaceCurrentMaxVciBits INTEGER,
    atmInterfaceSubscrAddress     AtmAddr
}
```

atmInterfaceMyNeighborIpAddress OBJECT-TYPE

```
SYNTAX      IpAddress
MAX-ACCESS  read-write
STATUS      current
DESCRIPTION
```

"The IP address of the neighbor system connected to the far end of this interface, to which a Network Management Station can send SNMP messages, as IP datagrams sent to UDP port 161, in order to access

network management information concerning the operation of that system. Note that the value of this object may be obtained in different ways, e.g., by manual configuration, or through ILMI interaction with the neighbor system."

```
::= { atmInterfaceConfEntry 11 }
```

```
atmInterfaceConfGroup2    OBJECT-GROUP
    OBJECTS {
        atmInterfaceMaxVpcs, atmInterfaceMaxVccs,
        atmInterfaceConfVpcs, atmInterfaceConfVccs,
        atmInterfaceMaxActiveVpiBits,
        atmInterfaceMaxActiveVciBits,
        atmInterfaceIlmiVpi,
        atmInterfaceIlmiVci,
        atmInterfaceMyNeighborIpAddress,
        atmInterfaceMyNeighborIfName,
        atmInterfaceCurrentMaxVpiBits,
        atmInterfaceCurrentMaxVciBits,
        atmInterfaceSubscrAddress }
    STATUS      current
    DESCRIPTION
        "A collection of objects providing configuration
        information about an ATM interface."
    ::= { atmMIBGroups 10 }
```

Clearly a subsequent revision of this MIB module should define equivalent IPv6 objects.

#### **5.061 RFC 2561 Base Definitions of Managed Objects for TN3270E Using SMIV2**

The document states:

The MIB defined by this memo supports use of both IPv4 and IPv6 addressing.

This specification is both IPv4 and IPv6 aware.

#### **5.062 RFC 2562 Definitions of Protocol and Managed Objects for TN3270E Response Time Collection Using SMIV2**

This MIB module inherits IP version-independence by virtue of importing the appropriate definitions from [RFC 2561](#).

#### **5.063 RFC 2564 Application Management MIB**

The following textual convention is defined:



```

ApplTAddress ::= TEXTUAL-CONVENTION
    STATUS      current
    DESCRIPTION
        "Denotes a transport service address.

        For snmpUDPDomain, an ApplTAddress is 6 octets long,
        the initial 4 octets containing the IP-address in
        network-byte order and the last 2 containing the UDP
        port in network-byte order. Consult 'Transport Mappings
        for Version 2 of the Simple Network Management Protocol
        (SNMPv2)' for further information on snmpUDPDomain."
    SYNTAX      OCTET STRING (SIZE (0..255))

```

A new TC should be defined to handle IPv6 addresses.

#### **[5.064 RFC 2584](#) Definitions of Managed Objects for APPN/HPR in IP Networks**

Many of the object definitions described in this document assume the use of the IPv4 only TOS header bits. It is therefore IPv4-only in nature and will not support IPv6.

#### **[5.065 RFC 2594](#) Definitions of Managed Objects for WWW Services**

There are no IPv4 dependencies in this specification.

#### **[5.066 RFC 2605](#) Directory Server Monitoring MIB**

There are no IPv4 dependencies in this specification.

#### **[5.067 RFC 2613](#) Remote Network Monitoring MIB Extensions for Switched Networks Version 1.0**

There are no IPv4 dependencies in this specification.

#### **[5.068 RFC 2618](#) RADIUS Authentication Client MIB**

This RFC defines the following OIDs:

```

RadiusAuthServerEntry ::= SEQUENCE {
    radiusAuthServerIndex      Integer32,
    radiusAuthServerAddress    IPAddress,
    radiusAuthClientServerPortNumber Integer32,
    radiusAuthClientRoundTripTime TimeTicks,
    radiusAuthClientAccessRequests Counter32,
    radiusAuthClientAccessRetransmissions Counter32,

```

```

radiusAuthClientAccessAccepts          Counter32,
radiusAuthClientAccessRejects          Counter32,
radiusAuthClientAccessChallenges       Counter32,
radiusAuthClientMalformedAccessResponses Counter32,
radiusAuthClientBadAuthenticators       Counter32,
radiusAuthClientPendingRequests         Gauge32,
radiusAuthClientTimeouts                Counter32,
radiusAuthClientUnknownTypes            Counter32,
radiusAuthClientPacketsDropped          Counter32
}

```

```

radiusAuthServerAddress OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The IP address of the RADIUS authentication server
         referred to in this table entry."
    ::= { radiusAuthServerEntry 2 }

```

There needs to be an update to allow an IPv6 based object for this value.

#### [5.069 RFC 2619](#) RADIUS Authentication Server MIB

This MIB defines the followings objects:

```

RadiusAuthClientEntry ::= SEQUENCE {
    radiusAuthClientIndex          Integer32,
    radiusAuthClientAddress        IpAddress,
    radiusAuthClientID             SnmpAdminString,
    radiusAuthServAccessRequests   Counter32,
    radiusAuthServDupAccessRequests Counter32,
    radiusAuthServAccessAccepts    Counter32,
    radiusAuthServAccessRejects    Counter32,
    radiusAuthServAccessChallenges Counter32,
    radiusAuthServMalformedAccessRequests Counter32,
    radiusAuthServBadAuthenticators Counter32,
    radiusAuthServPacketsDropped   Counter32,
    radiusAuthServUnknownTypes     Counter32
}

```

```

radiusAuthClientAddress OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The NAS-IP-Address of the RADIUS authentication client
         referred to in this table entry."
    ::= { radiusAuthClientEntry 2 }

```

This object needs to be deprecated and replaced by one that supports both IPv4 and IPv6 addresses.

#### **[5.070 RFC 2622](#) Routing Policy Specification Language (RPSL)**

The only objects in the version of RPSL that deal with IP addresses are defined as:

<ipv4-address> An IPv4 address is represented as a sequence of four integers in the range from 0 to 255 separated by the character dot ".". For example, 128.9.128.5 represents a valid IPv4 address. In the rest of this document, we may refer to IPv4 addresses as IP addresses.

<address-prefix> An address prefix is represented as an IPv4 address followed by the character slash "/" followed by an integer in the range from 0 to 32. The following are valid address prefixes: 128.9.128.5/32, 128.9.0.0/16, 0.0.0.0/0; and the following address prefixes are invalid: 0/0, 128.9/16 since 0 or 128.9 are not strings containing four integers.

There seems to be an awareness of IPv6 because of the terminology but it is not specifically defined. Therefore additional objects for IPv6 addresses and prefixes need to be defined.

#### **[5.071 RFC 2662](#) Definitions of Managed Objects for the ADSL Lines**

There are no IPv4 dependencies in this specification.

#### **[5.072 RFC 2667](#) IP Tunnel MIB**

The Abstract of this document says:

This memo defines a Management Information Base (MIB) for use with network management protocols in the Internet community. In particular, it describes managed objects used for managing tunnels of any type over IPv4 networks. Extension MIBs may be designed for managing protocol-specific objects. Likewise, extension MIBs may be designed for managing security-specific objects. This MIB does not support tunnels over non-IPv4 networks (including IPv6 networks). Management of such tunnels may be supported by other MIBs.

A similar MIB for tunneling over IPv6 should be defined.

#### **[5.073 RFC 2669](#) DOCSIS Cable Device MIB Cable Device Management Information Base for DOCSIS compliant Cable Modems and**

## Cable Modem Termination Systems

This document states:

Please note that the DOCSIS 1.0 standard only requires Cable Modems to implement SNMPv1 and to process IPv4 customer traffic. Design choices in this MIB reflect those requirements. Future versions of the DOCSIS standard are expected to require support for SNMPv3 and IPv6 as well.

### [5.074 RFC 2670](#) Radio Frequency (RF) Interface Management Information Base for MCNS/DOCSIS compliant RF interfaces

This MIB defines the following objects:

```
DocsIfCmtsCmStatusEntry ::= SEQUENCE {
    docsIfCmtsCmStatusIndex      Integer32,
    docsIfCmtsCmStatusMacAddress  MacAddress,
    docsIfCmtsCmStatusIpAddress  IpAddress,
    docsIfCmtsCmStatusDownChannelIfIndex  InterfaceIndexOrZero,
    docsIfCmtsCmStatusUpChannelIfIndex  InterfaceIndexOrZero,
    docsIfCmtsCmStatusRxPower      TenthdBmV,
    docsIfCmtsCmStatusTimingOffset  Unsigned32,
    docsIfCmtsCmStatusEqualizationData  OCTET STRING,
    docsIfCmtsCmStatusValue        INTEGER,
    docsIfCmtsCmStatusUnerroreds    Counter32,
    docsIfCmtsCmStatusCorrecteds    Counter32,
    docsIfCmtsCmStatusUncorrectables  Counter32,
    docsIfCmtsCmStatusSignalNoise    TenthdB,
    docsIfCmtsCmStatusMicroreflections  Integer32
}
```

docsIfCmtsCmStatusIpAddress OBJECT-TYPE

SYNTAX IpAddress

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"IP address of this Cable Modem. If the Cable Modem has no IP address assigned, or the IP address is unknown, this object returns a value of 0.0.0.0. If the Cable Modem has multiple IP addresses, this object returns the IP address associated with the Cable interface."

::= { docsIfCmtsCmStatusEntry 3 }

This object needs to be deprecated and replaced by one that supports both IPv4 and IPv6 addresses.

### [5.075 RFC 2674](#) Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering and Virtual LAN Extensions

There are no IPv4 dependencies in this specification.

**[5.076 RFC 2677](#) Definitions of Managed Objects for the NBMA Next Hop Resolution Protocol (NHRP)**

There are no IPv4 dependencies in this specification.

**[5.077 RFC 2720](#) Traffic Flow Measurement: Meter MIB**

This specification is both IPv4 and IPv6 aware and needs no changes.

**[5.078 RFC 2725](#) Routing Policy System Security**

There are no IPv4 dependencies in this specification.

**[5.079 RFC 2726](#) PGP Authentication for RIPE Database Updates**

There are no IPv4 dependencies in this specification.

**[5.080 RFC 2737](#) Entity MIB (Version 2)**

There are no IPv4 dependencies in this specification.

**[5.081 RFC 2741](#) Agent Extensibility (AgentX) Protocol Version 1**

Although the examples in the document are for IPv4 transport only, there is no IPv4 dependency in the AgentX protocol itself.

**[5.082 RFC 2742](#) Definitions of Managed Objects for Extensible SNMP Agents**

There are no IPv4 dependencies in this specification.

**[5.083 RFC 2748](#) The COPS (Common Open Policy Service) Protocol**

This specification is both IPv4 and IPv6 aware and needs no changes.

**[5.084 RFC 2749](#) COPS usage for RSVP**

There are no IPv4 dependencies in this specification.

**[5.085 RFC 2769](#) Routing Policy System Replication**

There are no IPv4 dependencies in this specification.

#### **[5.086 RFC 2787](#) Definitions of Managed Objects for the Virtual Router Redundancy Protocol**

As stated in the Overview section:

Since the VRRP protocol is intended for use with IPv4 routers only, this MIB uses the SYNTAX for IP addresses which is specific to IPv4. Thus, changes will be required for this MIB to interoperate in an IPv6 environment.

#### **[5.087 RFC 2788](#) Network Services Monitoring MIB**

There are no IPv4 dependencies in this specification.

#### **[5.088 RFC 2789](#) Mail Monitoring MIB**

There are no IPv4 dependencies in this specification.

#### **[5.089 RFC 2837](#) Definitions of Managed Objects for the Fabric Element in Fibre Channel Standard**

There are no IPv4 dependencies in this specification.

#### **[5.090 RFC 2856](#) Textual Conventions for Additional High Capacity Data Types**

There are no IPv4 dependencies in this specification.

#### **[5.091 RFC 2864](#) The Inverted Stack Table Extension to the Interfaces Group MIB**

There are no IPv4 dependencies in this specification.

#### **[5.092 RFC 2895](#) Remote Network Monitoring MIB Protocol Identifier Reference**

This specification is both IPv4 and IPv6 aware and needs no changes.

#### **[5.093 RFC 2925](#) Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations**

This MIB mostly is IPv4 and IPv6 aware. There are a few assumptions that are problems, though. In the following object

definitions:

```
pingCtlDataSize OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65507)
    UNITS        "octets"
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "Specifies the size of the data portion to be
        transmitted in a ping operation in octets. A ping
        request is usually an ICMP message encoded
        into an IP packet. An IP packet has a maximum size
        of 65535 octets. Subtracting the size of the ICMP
        or UDP header (both 8 octets) and the size of the IP
        header (20 octets) yields a maximum size of 65507
        octets."
    DEFVAL { 0 }
    ::= { pingCtlEntry 5 }
```

```
traceRouteCtlDataSize OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65507)
    UNITS        "octets"
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "Specifies the size of the data portion of a traceroute
        request in octets. A traceroute request is essentially
        transmitted by encoding a UDP datagram into a
        IP packet. So subtracting the size of a UDP header
        (8 octets) and the size of a IP header (20 octets)
        yields a maximum of 65507 octets."
    DEFVAL { 0 }
    ::= { traceRouteCtlEntry 6 }
```

The DESCRIPTION clauses need to be updated to remove the IPv4 dependencies.

#### [5.094 RFC 2932](#) **IPv4 Multicast Routing MIB**

This specification is only defined for IPv4 and a similar MIB must be defined for IPv6.

#### [5.095 RFC 2933](#) **Internet Group Management Protocol MIB**

As stated in this document:

Since IGMP is specific to IPv4, this MIB does not support management of equivalent functionality for other address families, such as IPv6.

**[5.096 RFC 2940](#) Definitions of Managed Objects for Common Open Policy Service (COPS) Protocol Clients**

This MIB is both IPv4 and IPv6 aware and needs no changes.

**[5.097 RFC 2954](#) Definitions of Managed Objects for Frame Relay Service**

There are no IPv4 dependencies in this specification.

**[5.098 RFC 2955](#) Definitions of Managed Objects for Monitoring and Controlling the Frame Relay/ATM PVC Service Interworking Function**

There are no IPv4 dependencies in this specification.

**[5.099 RFC 2959](#) Real-Time Transport Protocol Management Information Base**

There are no IPv4 dependencies in this specification.

**[5.100 RFC 2981](#) Event MIB**

There are no IPv4 dependencies in this specification.

**[5.101 RFC 2982](#) Distributed Management Expression MIB**

There are no IPv4 dependencies in this specification.

**[5.102 RFC 3014](#) Notification Log MIB**

There are no IPv4 dependencies in this specification.

**[5.103 RFC 3019](#) IP Version 6 Management Information Base for The Multicast Listener Discovery Protocol**

This is an IPv6 related document and is not discussed in this document.

**[5.104 RFC 3020](#) Definitions of Managed Objects for Monitoring and Controlling the UNI/NNI Multilink Frame Relay Function**

There are no IPv4 dependencies in this specification.



#### **[5.105 RFC 3055](#) Management Information Base for the PINT Services Architecture**

There are no IPv4 dependencies in this specification.

#### **[5.106 RFC 3060](#) Policy Core Information Model -- Version 1 Specification (CIM)**

There are no IPv4 dependencies in this specification.

#### **[5.107 RFC 3084](#) COPS Usage for Policy Provisioning (COPS-PR)**

This specification builds on [RFC 2748](#), and is both IPv4 and IPv6 capable. The specification defines a sample filter in [section 4.3](#), which has "ipv4" in it; however, it's just an example, and available to IPv6 as well with a simple replacement of "ipv4" with "ipv6".

#### **[5.108 RFC 3165](#) Definitions of Managed Objects for the Delegation of Management Scripts.**

There are no IPv4 dependencies in this specification.

#### **[5.109 RFC 3231](#) Definitions of Managed Objects for Scheduling Management Operations.**

There are no IPv4 dependencies in this specification.

#### **[5.110 RFC 3291](#) Textual Conventions for Internet Network Addresses**

There are no IPv4 dependencies in this specification.

#### **[5.111 RFC 3635](#) Definitions of Managed Objects for the Ethernet-like Interface Types**

There are no IPv4 dependencies in this specification.

#### **[5.112 RFC 3636](#) Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)**

There are no IPv4 dependencies in this specification.

### **[6.0](#) Experimental RFCs**

Experimental RFCs typically define protocols that do not have widescale implementation or usage on the Internet. They are often propriety in nature or used in limited arenas. They are documented to the Internet community in order to allow potential interoperability or some other potential useful scenario. In a few cases they are presented as alternatives to the mainstream solution to an acknowledged problem.

#### **[6.01 RFC 1187](#) Bulk Table Retrieval with the SNMP**

There are no IPv4 dependencies in this specification.

#### **[6.02 RFC 1224](#) Techniques for managing asynchronously generated alerts**

There are no IPv4 dependencies in this specification.

#### **[6.03 RFC 1238](#) CLNS MIB for use with Connectionless Network Protocol (ISO 8473) and End System to Intermediate System (ISO 9542)**

There are no IPv4 dependencies in this specification.

#### **[6.04 RFC 1592](#) Simple Network Management Protocol Distributed Protocol Interface Version 2.0**

There are no IPv4 dependencies in this specification.

#### **[6.05 RFC 1792](#) TCP/IPX Connection Mib Specification**

There are no IPv4 dependencies in this specification.

#### **[6.06 RFC 2724](#) RTFM: New Attributes for Traffic Flow Measurement**

There are no IPv4 dependencies in this specification.

#### **[6.07 RFC 2758](#) Definitions of Managed Objects for Service Level Agreements Performance Monitoring**

This specification is both IPv4 and IPv6 aware and needs no changes.

#### **[6.08 RFC 2786](#) Diffie-Helman USM Key Management Information Base and Textual Convention**

There are no IPv4 dependencies in this specification.

## [6.09 RFC 2903](#) Generic AAA Architecture

There are no IPv4 dependencies in this specification.

## [6.10 RFC 2934](#) Protocol Independent Multicast MIB for IPv4

This document is specific to IPv4.

## [6.11 RFC 3179](#) Script MIB Extensibility Protocol Version 1.1

There are no IPv4 dependencies in this specification.

## [7.0](#) Summary of Results

In the initial survey of RFCs 36 positives were identified out of a total of 153, broken down as follows:

Standards	6 of 15 or 40.00%
Draft Standards	4 of 15 or 26.67%
Proposed Standards	26 of 112 or 23.21%
Experimental RFCs	0 of 11 or 0.00%

Of those identified many require no action because they document outdated and unused protocols, while others are document protocols that are actively being updated by the appropriate working groups. Additionally there are many instances of standards that should be updated but do not cause any operational impact if they are not updated. The remaining instances are documented below.

## [7.1](#) Standards

### [7.1.1](#) STD 16, Structure of Management Information (RFCs 1155 and 1212)

RFCs 1155 and RFCs 1212 (along with the informational document RFC 1215) define SMIV1. These documents have been superseded by RFCs 2578, 2579, and 2580 which define SMIV2. Since SMIV1 is no longer being used as the basis for new IETF MIB modules, the limitations identified in this Internet Standard do not require any action.

### [7.1.2](#) STD 17 Simple Network Management Protocol ([RFC 1213](#))

The limitations identified have been addressed, because [RFC 1213](#) has been split into multiple modules which are all IPv6 capable.

## **7.2 Draft Standards**

### **7.2.1 BGP4 MIB ([RFC 1657](#))**

This problem is currently being addressed by the Inter Domain Routing (IDR) WG and an ID exists ([draft-ietf-idr-bgp4-mib-11.txt](#)).

### **7.2.2 SMDS MIB ([RFC 1694](#))**

See Internet Area standards. Once a specification for IPv6 over SMDS is created a new MIB must be defined.

### **7.2.3 RIPv2 MIB ([RFC 1724](#))**

There is no updated MIB module to cover the problems outlined. A new MIB module should be defined.

### **7.2.4 OSPFv2 MIB ([RFC 1850](#))**

This problem is currently being addressed by the OSPF WG and an ID exists ([draft-ietf-ospf-ospfv3-mib-07.txt](#)).

### **7.2.5 Transport MIB ([RFC 1906](#))**

[RFC 1906](#) has been obsoleted by [RFC 3417](#), Transport Mappings for SNMP, and the limitations of this specification have been addressed by that RFC, which defines TCs that can be used to specify transport domains in an IP version-independent way. [RFC 3419](#) recommends that those TCs be used in place of SnmpUDPAddress when IPv6 support is required and for all new applications that are not SNMP-specific.

## **7.3 Proposed Standards**

### **7.3.01 MIB for Multiprotocol Interconnect over X.25 ([RFC 1461](#))**

This problem has not been addressed. If a user requirement for IPv6 over X.25 develops (which is thought to be unlikely) then this MIB module will need to be updated in order to accomodate it.

### **7.3.02 PPP IPCP MIB ([RFC 1473](#))**

There is no updated MIB to cover the problems outlined. A new MIB should be defined.

### **7.3.03 Appletalk MIB ([RFC 1742](#))**

This problem has not been addressed. If a user requirement for IPv6 over Appletalk develops (which is thought to be unlikely) then this MIB module will need to be updated (or a new MIB module will need to be created) in order to accomodate it.

### **7.3.04 The Definitions of Managed Objects for IP Mobility Support using SMIPv2 ([RFC 2006](#))**

The problems are being resolved by the MIP6 WG and there is an ID ([draft-ietf-mip6-mipv6-mib-00.txt](#)).

### **7.3.05 SMIPv2 IP MIB ([RFC 2011](#))**

This issue is being resolved by the IPv6 WG and there is an ID ([draft-ietf-ipv6-rfc2011-update-04.txt](#)).

### **7.3.06 SNMPv2 TCP MIB ([RFC 2012](#))**

This issue is being resolved by the IPv6 WG and there is an ID ([draft-ietf-ipv6-rfc2012-update-04.txt](#)).

### **7.3.07 SNMPv2 UDP MIB ([RFC 2013](#))**

This issue is being resolved by the IPv6 WG and there is an ID ([draft-ietf-ipv6-rfc2013-update-01.txt](#)).

### **7.3.08 RMON-II MIB ([RFC 2021](#))**

This issue has been brought to the attention of the RMONMIB WG. Currently there is an ID ([draft-ietf-rmonmib-rmon2-v2-00.txt](#)) to update [RFC 2021](#), but it does not address the problems that have been identified; it is expected that there will be a resolution in a future version of that ID.

### **7.3.09 DataLink Switching using SMIPv2 MIB ([RFC 2024](#))**

The problems have not been addressed and an updated MIB should be defined.

### **7.3.10 IP Forwarding Table MIB ([RFC 2096](#))**

This issue is being worked on by the IPv6 WG and an ID exists to address this ([draft-ietf-ipngwg-rfc2096-update-05.txt](#))

#### **[7.3.11](#) Classical IP & ARP over ATM MIB ([RFC 2320](#))**

The current version of Classical IP and ARP over ATM ([RFC 2225](#)) does not support IPv6. If and when that protocol specification is updated to add IPv6 support, then new MIB objects to represent IPv6 addresses will need to be added to this MIB module.

#### **[7.3.12](#) Multicast over UNI 3.0/3.1 ATM MIB ([RFC 2417](#))**

The current version of Multicast over UNI 3.0/3.1 ATM (RFC 2022) does not support IPv6. If and when that protocol specification is updated to add IPv6 support, then new MIB objects to represent IPv6 addresses will need to be added to this MIB module.

#### **[7.3.13](#) ATM MIB ([RFC 2515](#))**

The ATOM MIB WG is currently collecting implementation reports for RFC [2515](#) and is considering whether to advance, revise, or retire this specification. The problems identified have been brought to the attention of the WG.

#### **[7.3.14](#) TN3270 MIB ([RFC 2562](#))**

The problems identified are not being addressed and a new MIB module may need to be defined.

#### **[7.3.15](#) Application MIB ([RFC 2564](#))**

The problems identified are not being addressed and a new MIB module may need to be defined. One possible solution might be to use the [RFC 3419](#) TCs.

#### **[7.3.16](#) Definitions of Managed Objects for APPN/HPR in IP Networks ([RFC 2584](#))**

The problems identified are not addressed and a new MIB may be defined.

#### **[7.3.17](#) RADIUS MIB ([RFC 2618](#))**

The problems have not been addressed and a new MIB should be defined.

#### **[7.3.18](#) RADIUS Authentication Server MIB ([RFC 2619](#))**

The problems have not been addressed and a new MIB should be defined.

#### **[7.3.19](#) RPSL ([RFC 2622](#))**

Additional objects must be defined for IPv6 addresses and prefixes.

[draft-blunk-rpslmg-01.txt](#) defines extensions to solve this issue, and it is being considered for publication.

#### **[7.3.20](#) IPv4 Tunnel MIB ([RFC 2667](#))**

The issue is being resolved and an ID exists ([draft-thaler-inet-tunnel-mib-00.txt](#)).

#### **[7.3.21](#) DOCSIS MIB ([RFC 2669](#))**

This problem is currently being addressed by the IPCDN WG and an ID is available ([draft-ietf-ipcdn-device-mibv2-05.txt](#)).

#### **[7.3.22](#) RF MIB For DOCSIS ([RFC 2670](#))**

This problem is currently being addressed by the IPCDN WG and an ID is available ([draft-ietf-ipcdn-docs-rfmibv2-06.txt](#)).

#### **[7.3.23](#) VRRP MIB ([RFC 2787](#))**

The problems have not been addressed and a new MIB may need to be defined.

#### **[7.3.24](#) MIB For Traceroute, Pings and Lookups ([RFC 2925](#))**

The problems have not been addressed and a new MIB may need to be defined.

#### **[7.3.25](#) IPv4 Multicast Routing MIB ([RFC 2932](#))**

The problems have not been addressed a new MIB must be defined.

#### **[7.3.26](#) IGMP MIB ([RFC 2933](#))**

This problem is currently being addressed by the MAGMA WG and an ID exists ([draft-ietf-magma-mgmd-mib-01.txt](#)).

## **[7.4](#) Experimental RFCs**

### **[7.4.1](#) Protocol Independent Multicast MIB for IPv4 ([RFC 2934](#))**

The problems have not been addressed and a new MIB may need to be defined.

## **[8.0](#) Security Consideration**

This memo examines the IPv6-readiness of specifications; this does not have security considerations in itself.

## **[9.0](#) Acknowledgements**

The authors would like to acknowledge the support of the Internet Society in the research and production of this document. Additionally the author, Philip J. Nesser II, would like to thanks his partner in all ways, Wendy M. Nesser.

The editor, Andreas Bergstrom, would like to thank Pekka Savola for guidance and collection of comments for the editing of this document.

He would further like to thank Juergen Schoenwaelder, Brian Carpenter, Bert Wijnen and especially C. M. Heard for feedback on many points of this document.

## **[10.0](#) References**

### **[10.1](#) Normative**

- [1] Philip J. Nesser II, Andreas Bergstrom. "Introduction to the Survey of IPv4 Addresses in Currently Deployed IETF Standards", [draft-ietf-v6ops-ipv4survey-intro-05.txt](#) IETF work in progress, November 2003

## **[11.0](#) Authors' Addresses**

Please contact the author with any questions, comments or suggestions at:

Philip J. Nesser II  
Principal  
Nesser & Nesser Consulting  
[13501](#) 100th Ave NE, #5202  
Kirkland, WA 98034

Email: phil@nesser.com



Phone: +1 425 481 4303

Fax: +1 425 48

Andreas Bergstrom (Editor)

Ostfold University College

Email: andreas.bergstrom@hiof.no

Address: Rute 503 Buer

N-1766 Halden

Norway

## **12.0 Intellectual Property Statement**

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in [BCP-11](#). Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

## **13.0 Full Copyright Statement**

Copyright (C) The Internet Society (2000). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English. The limited permissions granted above are perpetual and will not be revoked

by the Internet Society or its successors or assigns. This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.