

Network Working Group  
Daboo  
Internet-Draft  
Apple  
Intended status: Standards Track  
2009  
Expires: January 14, 2010

C.

July 13,

**vCard Extensions to WebDAV (CardDAV)  
draft-ietf-vcarddav-carddav-07**

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#). This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on January 14, 2010.

Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal

Daboo  
1]

Expires January 14, 2010

[Page

Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Abstract

This document defines extensions to the Web Distributed Authoring and Versioning (WebDAV) protocol to specify a standard way of accessing, managing, and sharing contact information based on the vCard format.

Table of Contents

- [1](#). Introduction and Overview . . . . . 4
- [2](#). Conventions . . . . . 5
- [3](#). Requirements Overview . . . . . 6
- [4](#). Address Book Data Model . . . . . 7
  - [4.1](#). Address Book Server . . . . . 7
- [5](#). Address Book Resources . . . . . 7
  - [5.1](#). Address Object Resources . . . . . 7
  - [5.2](#). Address Book Collections . . . . . 8
- [6](#). Address Book Feature . . . . . 9
  - [6.1](#). Address Book Support . . . . . 9
    - 6.1.1. Example: Using OPTIONS for the Discovery of Support for CardDAV . . . . . 9
  - [6.2](#). Address Book Properties . . . . . 9
    - [6.2.1](#). CARDDAV:addressbook-description Property . . . . . 10
    - [6.2.2](#). CARDDAV:supported-address-data Property . . . . . 10
    - [6.2.3](#). CARDDAV:max-resource-size Property . . . . . 11
  - [6.3](#). Creating Resources . . . . . 12
    - [6.3.1](#). Extended MKCOL Method . . . . . 12
      - [6.3.1.1](#). Example - Successful MKCOL request . . . . .

<a href="#">13</a>	<a href="#">6.3.2.</a> Creating Address Object Resources . . . . .
<a href="#">15</a>	6.3.2.1. Additional Preconditions for PUT, COPY and MOVE .
<a href="#">16</a>	<a href="#">6.3.2.2.</a> Non-Standard vCard Properties, and Parameters . .
<a href="#">17</a>	<a href="#">6.3.2.3.</a> Address Object Resource Entity Tag . . . . .
<a href="#">17</a>	<a href="#">7.</a> Address Book Access Control . . . . .
<a href="#">18</a>	<a href="#">7.1.</a> Additional Principal Properties . . . . .
<a href="#">18</a>	<a href="#">7.1.1.</a> CARDDAV:addressbook-home-set Property . . . . .
<a href="#">18</a>	<a href="#">7.1.2.</a> CARDDAV:principal-address Property . . . . .
<a href="#">19</a>	<a href="#">8.</a> Address Book Reports . . . . .
<a href="#">20</a>	<a href="#">8.1.</a> REPORT Method . . . . .
<a href="#">20</a>	<a href="#">8.2.</a> Ordinary Collections . . . . .
<a href="#">20</a>	<a href="#">8.3.</a> Searching Text: Collations . . . . .
<a href="#">20</a>	<a href="#">8.3.1.</a> CARDDAV:supported-collation-set Property . . . . .
<a href="#">21</a>	<a href="#">8.4.</a> Partial Retrieval . . . . .
<a href="#">22</a>	<a href="#">8.5.</a> Non-standard Properties and Parameters . . . . .
<a href="#">22</a>	

- [8.6.](#) CARDDAV:addressbook-query Report . . . . .  
[23](#)
- [8.6.1.](#) Limiting Results . . . . .  
[24](#)
- [8.6.2.](#) Truncation of Results . . . . .  
[25](#)
- [8.6.3.](#) Example: Partial Retrieval of vCards Matching  
NICKNAME . . . . .  
[25](#)
- [8.6.4.](#) Example: Partial Retrieval of vCards Matching a  
Full Name or Email Address . . . . .  
[27](#)
- [8.6.5.](#) Example: Truncated Results . . . . .  
[30](#)
- [8.7.](#) CARDDAV:addressbook-multiget Report . . . . .  
[31](#)
- [8.7.1.](#) Example: CARDDAV:addressbook-multiget Report . . . . .  
[33](#)
- [9.](#) Guidelines . . . . .  
[34](#)
- [9.1.](#) Restrict the Properties Returned . . . . .  
[34](#)
- [9.2.](#) Use of Locking . . . . .  
[35](#)
- [9.3.](#) Client Configuration . . . . .  
[35](#)
- [9.4.](#) Finding Other Users' Address Books . . . . .  
[36](#)
- [10.](#) XML Element Definitions . . . . .  
[36](#)
- [10.1.](#) CARDDAV:addressbook XML Element . . . . .  
[36](#)
- [10.2.](#) CARDDAV:supported-collation XML Element . . . . .  
[37](#)
- [10.3.](#) CARDDAV:addressbook-query XML Element . . . . .  
[37](#)
- [10.4.](#) CARDDAV:address-data XML Element . . . . .  
[37](#)
- [10.4.1.](#) CARDDAV:allprop XML Element . . . . .  
[39](#)
- [10.4.2.](#) CARDDAV:prop XML Element . . . . .  
[39](#)
- [10.5.](#) CARDDAV:filter XML Element . . . . .  
[40](#)
- [10.5.1.](#) CARDDAV:prop-filter XML Element . . . . .  
[41](#)
- [10.5.2.](#) CARDDAV:param-filter XML Element . . . . .  
[42](#)
- [10.5.3.](#) CARDDAV:is-not-defined XML Element . . . . .  
[43](#)
- [10.5.4.](#) CARDDAV:text-match XML Element . . . . .  
[43](#)

<a href="#">44</a>	<a href="#">10.6.</a> CARDDAV:limit XML Element . . . . .
<a href="#">44</a>	<a href="#">10.6.1.</a> CARDDAV:nresults XML Element . . . . .
<a href="#">45</a>	<a href="#">10.7.</a> CARDDAV:addressbook-multiget XML Element . . . . .
<a href="#">45</a>	<a href="#">11.</a> Service Discovery via SRV Records . . . . .
<a href="#">46</a>	<a href="#">12.</a> Internationalization Considerations . . . . .
<a href="#">46</a>	<a href="#">13.</a> Security Considerations . . . . .
<a href="#">47</a>	<a href="#">14.</a> IANA Consideration . . . . .
<a href="#">47</a>	<a href="#">14.1.</a> Namespace Registration . . . . .
<a href="#">47</a>	<a href="#">15.</a> Acknowledgments . . . . .
<a href="#">47</a>	<a href="#">16.</a> References . . . . .
<a href="#">47</a>	<a href="#">16.1.</a> Normative References . . . . .
<a href="#">48</a>	<a href="#">16.2.</a> Informative References . . . . .
<a href="#">49</a>	<a href="#">Appendix A.</a> Change History (to be removed prior to publication as an RFC) . . . . .
<a href="#">52</a>	Author's Address . . . . .

## 1. Introduction and Overview

Address books containing contact information are a key component of personal information management tools, such as email, calendaring and

scheduling, and instant messaging clients. To date several protocols

have been used for remote access to contact data, including Lightweight Directory Access Protocol (LDAP) [[RFC4511](#)], Internet Message Support Protocol (IMSP) [[IMSP](#)] and Application Configuration Access Protocol (ACAP) [[RFC2244](#)], together with SyncML used for synchronization of such data.

WebDAV [[RFC4918](#)] offers a number of advantages as a framework or basis for address book access and management. Most of these advantages boil down to a significant reduction in design costs, implementation costs, interoperability test costs and deployment costs.

The key features of address book support with WebDAV are:

1. Ability to use multiple address books with hierarchical layout.
2. Ability to control access to individual address books and address entries.
3. Principal namespace can be used to enumerate and find other users on the system.
4. Server-side searching of address data, avoiding the need for clients to download an entire address book in order to do a quick address 'expansion' operation.
5. Well-defined internationalization support through standard HTTP.
6. Use of vCards for well defined address schema to enhance client interoperability.
7. Many limited clients (e.g. mobile devices) contain an HTTP stack which makes implementing WebDAV much easier than other protocols.

The key disadvantages of address book support in WebDAV are:

1. Lack of change notification. Many of the alternative protocols also lack this ability. However, an extension for push notifications could easily be developed.
2. Stateless nature of protocol can result in more data being sent

with each transaction to maintain per-user session across requests.

Daboo  
4]

Expires January 14, 2010

[Page



vCard is a MIME directory profile aimed at encapsulating personal addressing and contact information about people. The specification of vCard was originally done by the Versit consortium, with a subsequent 3.0 version standardized by the IETF [[RFC2426](#)]. vCard is in wide spread use in email clients and mobile devices as a means of encapsulating address information for transport via email, or for import/export and synchronization operations.

An update to vCard is currently being developed [[I-D.ietf-vcaddav-vcaddrev](#)] and is compatible with this specification.

## 2. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

The term "protected" is used in the Conformance field of property definitions as defined in [Section 15 of \[RFC4918\]](#).

This document uses XML DTD fragments ([\[W3C.REC-xml-20081126\]](#), [Section 3.2](#)) as a purely notational convention. WebDAV request and response bodies cannot be validated by a DTD due to the specific extensibility

rules defined in [Section 17 of \[RFC4918\]](#) and due to the fact that all

XML elements defined by this specification use the XML namespace name

"DAV:". In particular:

1. element names use the "DAV:" namespace,
2. element ordering is irrelevant unless explicitly stated,
3. extension elements (elements not already defined as valid child elements) may be added anywhere, except when explicitly stated otherwise,
4. extension attributes (attributes not already defined as valid for this element) may be added anywhere, except when explicitly stated otherwise.

The namespace "urn:ietf:params:xml:ns:carddav" is reserved for the XML elements defined in this specification, its revisions, and related CardDAV specifications. XML elements defined by individual implementations MUST NOT use the "urn:ietf:params:xml:ns:carddav" namespace, and instead should use a namespace that they control.

When XML element types in the namespaces "DAV:" and

Daboo  
5]

Expires January 14, 2010

[Page

"urn:ietf:params:xml:ns:carddav" are referenced in this document outside of the context of an XML fragment, the strings "DAV:" and "CARDDAV:" will be prefixed to the element types, respectively.

This document inherits, and sometimes extends, DTD productions from [Section 14 of \[RFC4918\]](#).

Also note that some CardDAV XML element names are identical to WebDAV

XML element names, though their namespace differs. Care must be taken not to confuse the two sets of names.

### **3. Requirements Overview**

This section lists what functionality is required of a CardDAV server. To advertise support for CardDAV, a server:

- o MUST support vCard [[RFC2426](#)] as a media type for the address object resource format;
- o MUST support WebDAV Class 3 [[RFC4918](#)];
- o MUST support WebDAV ACL [[RFC3744](#)];
- o MUST support secure transport as defined in [[RFC2818](#)] using TLS [[RFC5246](#)];
- o MUST support ETags [[RFC2616](#)] with additional requirements specified in [Section 6.3.2.3](#) of this document;
- o MUST support all address book reports defined in [Section 8](#) of this document; and
- o MUST advertise support on all address book collections and address object resources for the address book reports in the DAV:supported-report-set property, as defined in Versioning Extensions to WebDAV [[RFC3253](#)].

In addition, a server:

- o SHOULD support the extended MKCOL method [[I-D.ietf-vcarddav-webdav-mkcol](#)] to create address book collections as defined in [Section 6.3.1](#) of this document.
- o SHOULD support the DAV:current-user-principal-URL property as defined in [[RFC5397](#)] to give clients a fast way to locate user principals.

Daboo  
6]

Expires January 14, 2010

[Page

## **4. Address Book Data Model**

As a brief overview, a CardDAV address book is modeled as a WebDAV collection with a well defined structure; each of these address book collections contain a number of resources representing address objects as their direct child resources. Each resource representing an address object is called an "address object resource". Each address object resource and each address book collection can be individually locked and have individual WebDAV properties. Requirements derived from this model are provided in [Section 5.1](#) and [Section 5.2](#).

### **4.1. Address Book Server**

A CardDAV server is an address-aware engine combined with a WebDAV server. The server may include address data in some parts of its URL namespace, and non-address data in other parts.

A WebDAV server can advertise itself as a CardDAV server if it supports the functionality defined in this specification at any point

within the root of its repository. That might mean that address data is spread throughout the repository and mixed with non-address data in nearby collections (e.g. address data may be found in /lisa/addressbook/ as well as in /bernard/addressbook/, and non-address data in /lisa/calendars/). Or, it might mean that address data can be found only in certain sections of the repository (e.g. /addressbooks/user/). Address book features are only required in the repository sections that are or contain address objects. So a repository confining address data to the /carddav/ collection would only need to support the CardDAV required features within that collection.

The CardDAV server is the canonical location for address data and state information. Clients may submit requests to change data or download data. Clients may store address objects offline and attempt

to synchronize at a later time. Address data on the server can change between the time of last synchronization and when attempting an update, as address book collections may be shared and accessible via multiple clients. Entity tags and locking help this work.

## **5. Address Book Resources**

### **5.1. Address Object Resources**

This specification uses vCard as the default format for address or contact information being stored on the server. However, this

specification does allow other formats for address data provided that

Daboo  
7]

Expires January 14, 2010

[Page

the server advertises support for those additional formats as described below. The requirements in this section pertain to vCard address data, or formats that follow the semantics of vCard data.

Address object resources contained in address book collections MUST contain a single vCard component only.

vCard components in an address book collection MUST have a UID property value that MUST be unique in the scope of the address book collection in which it is contained.

## **5.2. Address Book Collections**

Address book collections appear to clients as a WebDAV collection resource, identified by a URL. An address book collection MUST report the DAV:collection and CARDDAV:addressbook XML elements in the

value of the DAV:resourcetype property. The element type declaration

for CARDDAV:addressbook is:

```
<!ELEMENT addressbook EMPTY>
```

An address book collection can be created through provisioning (e.g., automatically created when a user's account is provisioned), or it can be created with the extended MKCOL method (see [Section 6.3.1](#)). This can be used by a user to create additional address books (e.g., "soccer team members") or for users to share an address book (e.g., "sales team contacts"). Note however that this document doesn't define what extra address book collections are for. Users must rely on non-standard cues to find out what an address book collection is for, or use the CARDDAV:addressbook-description property defined in [Section 6.2.1](#) to provide such a cue.

The following restrictions are applied to the resources within an address book collection:

- a. Address book collections MUST only contain address object resources and collections that are not address book collections. i.e., the only "top-level" non-collection resources allowed in

an

address book collection are address object resources. This ensures that address book clients do not have to deal with non-address data in an address book collection, though they do have to distinguish between address object resources and collections when using standard WebDAV techniques to examine the contents of a collection.

- b. Collections contained in address book collections MUST NOT contain address book collections at any depth. i.e., "nesting"

of

address book collections within other address book collections  
at

Daboo  
8]

Expires January 14, 2010

[Page



any depth is not allowed. This specification does not define how collections contained in an address book collection are used or how they relate to any address object resources contained in the address book collection.

Multiple address book collections MAY be children of the same collection.

## **6. Address Book Feature**

### **6.1. Address Book Support**

A server supporting the features described in this document, MUST include "addressbook" as a field in the DAV response header from an OPTIONS request on any resource that supports any address book properties, reports, or methods. A value of "addressbook" in the DAV response header MUST indicate that the server supports all MUST level requirements and REQUIRED features specified in this document.

#### **6.1.1. Example: Using OPTIONS for the Discovery of Support for CardDAV**

>> Request <<

```
OPTIONS /addressbooks/users/ HTTP/1.1
Host: addressbook.example.com
```

>> Response <<

```
HTTP/1.1 200 OK
Allow: OPTIONS, GET, HEAD, POST, PUT, DELETE, TRACE, COPY, MOVE
Allow: MKCOL, PROPFIND, PROPPATCH, LOCK, UNLOCK, REPORT, ACL
DAV: 1, 2, 3, access-control, addressbook
DAV: extended-mkcol
Date: Sat, 11 Nov 2006 09:32:12 GMT
Content-Length: 0
```

In this example, the OPTIONS response indicates that the server supports CardDAV in this namespace, therefore the '/addressbooks/users/' collection may be used as a parent for address book collections as the extended MKCOL method is available, and as a possible target for REPORT requests for address book reports.

### **6.2. Address Book Properties**

Daboo  
9]

Expires January 14, 2010

[Page

### **6.2.1. CARDDAV:addressbook-description Property**

Name: addressbook-description

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Provides a human-readable description of the address book collection.

Value: Any text.

Protected: SHOULD NOT be protected so that users can specify a description.

COPY/MOVE behavior: This property value SHOULD be preserved in COPY and MOVE operations.

allprop behavior: SHOULD NOT be returned by a PROPFIND DAV:allprop request.

Description: This property contains a description of the address book collection that is suitable for presentation to a user.

Definition:

```
<!ELEMENT addressbook-description (#PCDATA)>  
<!-- PCDATA value: string -->
```

Example:

```
<C:addressbook-description xml:lang="fr-CA"  
  xmlns:C="urn:ietf:params:xml:ns:carddav"  
>Adresses de Oliver Daboo</C:addressbook-description>
```

### **6.2.2. CARDDAV:supported-address-data Property**

Name: supported-address-data

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Specifies what media types are allowed for address object resources in an address book collection.

Protected: MUST be protected as it indicates the level of support provided by the server.

Daboo  
10]

Expires January 14, 2010

[Page

COPY/MOVE behavior: This property value MUST be preserved in COPY and MOVE operations.

allprop behavior: SHOULD NOT be returned by a PROPFIND DAV:allprop request.

Description: The CARDDAV:supported-address-data property is used to specify the media type supported for the address object resources contained in a given address book collection (e.g., vCard version 3.0). Any attempt by the client to store address object resources with a media type not listed in this property MUST result in an error, with the CARDDAV:supported-address-data precondition ([Section 6.3.2.1](#)) being violated. In the absence of this property the server MUST only accept data with the media type "text/vcard" and vCard version 3.0, and clients can assume that.

Definition:

```
<!ELEMENT supported-address-data (address-data-type+)>

<!ELEMENT address-data-type EMPTY>
<!ATTLIST address-data-type content-type CDATA "text/vcard"
          version CDATA "3.0">
<!-- content-type value: a MIME media type -->
<!-- version value: a version string -->
```

Example:

```
<C:supported-address-data
  xmlns:C="urn:ietf:params:xml:ns:carddav">
  <C:address-data-type content-type="text/vcard" version="3.0"/>
</C:supported-address-data>
```

### **6.2.3. CARDDAV:max-resource-size Property**

Name: max-resource-size

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Provides a numeric value indicating the maximum size in octets of a resource that the server is willing to accept when an address object resource is stored in an address book collection.

Daboo  
11]

Expires January 14, 2010

[Page

Value: Any text representing a numeric value.

Protected: MUST be protected as it indicates limits provided by the server.

COPY/MOVE behavior: This property value MUST be preserved in COPY and MOVE operations.

allprop behavior: SHOULD NOT be returned by a PROPFIND DAV:allprop request.

Description: The CARDDAV:max-resource-size is used to specify a numeric value that represents the maximum size in octets that the server is willing to accept when an address object resource is stored in an address book collection. Any attempt to store an address book object resource exceeding this size MUST result in an error, with the CARDDAV:max-resource-size precondition ([Section 6.3.2.1](#)) being violated. In the absence of this property the client can assume that the server will allow storing a resource of any reasonable size.

Definition:

```
<!ELEMENT max-resource-size (#PCDATA)>  
<!-- PCDATA value: a numeric value (positive integer) -->
```

Example:

```
<C:max-resource-size xmlns:C="urn:ietf:params:xml:ns:carddav"  
>102400</C:max-resource-size>
```

### **6.3. Creating Resources**

Address book collections and address object resources may be created by either a CardDAV client or by the CardDAV server. This specification defines restrictions and a data model that both clients and servers MUST adhere to when manipulating such address data.

#### **6.3.1. Extended MKCOL Method**

An HTTP request using the extended MKCOL method [[I-D.ietf-vcarddav-webdav-mkcol](#)] can be used to create a new address book collection resource. A server MAY restrict address book collection creation to particular collections.

To create an address book, the client sends an extended MKCOL request to the server and in the body of the request sets the DAV:resourcetype property to the resource type for an address book

Daboo  
12]

Expires January 14, 2010

[Page



collection as defined in [Section 5.2](#).

Support for creating address books on the server is only RECOMMENDED and not REQUIRED because some address book stores only support one address book per user (or principal), and those are typically pre-created for each account. However, servers and clients are strongly encouraged to support address book creation whenever possible to allow users to create multiple address book collections to help organize their data better.

The DAV:displayname property can be used for a human-readable name of the address book. Clients can either specify the value of the DAV:displayname property in the request body of the extended MKCOL request, or alternatively issue a PROPPATCH request to change the DAV:displayname property to the appropriate value immediately after using the extended MKCOL request. When displaying address book collections to users, clients SHOULD check the DAV:displayname property and use that value as the name of the address book. In the event that the DAV:displayname property is not set, the client MAY use the last part of the address book collection URI as the name, however that path segment may be "opaque" and not represent any meaningful human-readable text.

#### **6.3.1.1. Example - Successful MKCOL request**

This example creates an address book collection called /home/lisa/addressbook/ on the server addressbook.example.com with specific values for the properties DAV:resourcetype, DAV:displayname and CARDDAV:addressbook-description.



>> Request <<

MKCOL /home/lisa/addressbook/ HTTP/1.1  
Host: addressbook.example.com  
Content-Type: text/xml; charset="utf-8"  
Content-Length: xxx

```
<?xml version="1.0" encoding="utf-8" ?>
<D:mkcol xmlns:D="DAV:"
          xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:set>
    <D:prop>
      <D:resourcetype>
        <D:collection/>
        <C:addressbook/>
      </D:resourcetype>
      <D:displayname>Lisa's Contacts</D:displayname>
      <C:addressbook-description xml:lang="en"
>My primary address book.</C:addressbook-description>
    </D:prop>
  </D:set>
</D:mkcol>
```

>> Response <<

HTTP/1.1 201 Created  
Cache-Control: no-cache  
Date: Sat, 11 Nov 2006 09:32:12 GMT  
Content-Type: application/xml; charset="utf-8"  
Content-Length: xxxx

```
<?xml version="1.0" encoding="utf-8" ?>
<D:mkcol-response xmlns:D="DAV:"
                  xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:propstat>
    <D:prop>
      <D:resourcetype/>
      <D:displayname/>
      <C:addressbook-description/>
    </D:prop>
    <D:status>HTTP/1.1 200 OK</D:status>
  </D:propstat>
</D:mkcol-response>
```

Daboo  
14]

Expires January 14, 2010

[Page

### 6.3.2. Creating Address Object Resources

Clients populate address book collections with address object resources. The URL for each address object resource is entirely arbitrary, and does not need to bear a specific relationship (but might) to the address object resource's vCard properties or other metadata. New address object resources MUST be created with a PUT request targeted at an unmapped URI. A PUT request targeted at a mapped URI updates an existing address object resource.

When servers create new resources, it's not hard for the server to choose a unique URL. It's slightly tougher for clients, because a client might not want to examine all resources in the collection,

and might not want to lock the entire collection to ensure that a new one

isn't created with a name collision. However, there is an HTTP feature to mitigate this. If the client intends to create a new address resource the client SHOULD use the HTTP header "If-None-Match: \*" on the PUT request. The Request-URI on the PUT request MUST include the target collection, where the resource is to be created, plus the name of the resource in the last path segment.

The

"If-None-Match" header ensures that the client will not inadvertently

overwrite an existing resource even, if the last path segment turned out to already be used.

>> Request <<

```
PUT /lisa/addressbook/newvcard.vcf HTTP/1.1
If-None-Match: *
Host: addressbook.example.com
Content-Type: text/vcard
Content-Length: xxx
```

```
BEGIN:VCARD
VERSION:3.0
FN:Cyrus Daboo
N:Daboo;Cyrus
ADR;TYPE=POSTAL;;2822 Email HQ;Suite 2821;RFCVille;PA;15213;USA
EMAIL;TYPE=INTERNET,PREF:cyrus@example.com
NICKNAME:me
NOTE:Example VCard.
ORG:Self Employed
TEL;TYPE=WORK,VOICE:412 605 0499
TEL;TYPE=FAX:412 605 0705
URL:http://www.example.com
UID:1234-5678-9000-1
END:VCARD
```

Daboo  
15]

Expires January 14, 2010

[Page

>> Response <<

```
HTTP/1.1 201 Created
Date: Thu, 02 Sep 2004 16:53:32 GMT
Content-Length: 0
ETag: "123456789-000-111"
```

The request to change an existing address object resource without overwriting a change made on the server, uses a specific ETag in an "If-Match" header, rather than the "If-None-Match" header.

File names for vCards are commonly suffixed by ".vcf", and clients may choose to use the same convention for URLs.

#### **6.3.2.1. Additional Preconditions for PUT, COPY and MOVE**

This specification creates additional Preconditions for PUT, COPY and MOVE methods. These preconditions apply:

- o When a PUT operation of an address object resource into an address book collection occurs.
- o When a COPY or MOVE operation of an address object resource into an address book collection occurs.

The new preconditions are:

(CARDDAV:supported-address-data): The resource submitted in the PUT request, or targeted by a COPY or MOVE request MUST be a supported media type (i.e., vCard) for address object resources;

(CARDDAV:valid-address-data): The resource submitted in the PUT request, or targeted by a COPY or MOVE request MUST be valid data for the media type being specified (i.e., MUST contain valid vCard data);

(CARDDAV:no-uid-conflict): The resource submitted in the PUT request, or targeted by a COPY or MOVE request MUST NOT specify a vCard UID property value already in use in the targeted address book collection or overwrite an existing address object resource with one that has a different UID property value. Servers SHOULD report the URL of the resource that is already making use of the same UID property value in the DAV:href element;

```
<!ELEMENT no-uid-conflict (DAV:href)>
```

Daboo  
16]

Expires January 14, 2010

[Page



(CARDDAV:addressbook-collection-location-ok): In a COPY or MOVE request, when the Request-URI is an address book collection, the URI targeted by the Destination HTTP Request header MUST identify a location where an address book collection can be created;

(CARDDAV:max-resource-size): The resource submitted in the PUT request, or targeted by a COPY or MOVE request MUST have a size

in

octets less than or equal to the value of the CARDDAV:max-resource-size property value ([Section 6.2.3](#)) on the address book collection where the resource will be stored;

### **6.3.2.2. Non-Standard vCard Properties, and Parameters**

vCard provides a "standard mechanism for doing non-standard things". This extension support allows implementers to make use of non-standard vCard properties and parameters whose names are prefixed with the text "X-".

Servers MUST support the use of non-standard properties and parameters in address object resources stored via the PUT method.

Servers may need to enforce rules for their own "private" properties or parameters, so servers MAY reject any attempt by the client to change those or use values for those outside of any restrictions the server may have. Servers SHOULD ensure that any "private"

properties

or parameters it uses follow the convention of including a vendor id in the "X-" name, as described in [Section 3.8 of \[RFC2426\]](#), e.g., "X-ABC-PRIVATE".

### **6.3.2.3. Address Object Resource Entity Tag**

The DAV:getetag property MUST be defined and set to a strong entity tag on all address object resources.

A response to a GET request targeted at an address object resource MUST contain an ETag response header field indicating the current value of the strong entity tag of the address object resource.

Servers SHOULD return a strong entity tag (ETag header) in a PUT response when the stored address object resource is equivalent by octet equality to the address object resource submitted in the body of the PUT request. This allows clients to reliably use the

returned

strong entity tag for data synchronization purposes. For instance, the client can do a PROPFIND request on the stored address object resource and have the DAV:getetag property returned, and compare

that

value with the strong entity tag it received on the PUT response,

and

know that if they are equal, then the address object resource on the

server has not been changed.

Daboo  
17]

Expires January 14, 2010

[Page

In the case where the data stored by a server as a result of a PUT request is not equivalent by octet equality to the submitted address object resource, the behavior of the ETag response header is not specified here, with the exception that a strong entity tag MUST NOT be returned in the response. As a result, clients may need to retrieve the modified address object resource (and ETag) as a basis for further changes, rather than use the address object resource it had sent with the PUT request.

## **7. Address Book Access Control**

CardDAV servers MUST support and adhere to the requirements of WebDAV

ACL [[RFC3744](#)]. WebDAV ACL provides a framework for an extensible set

of privileges that can be applied to WebDAV collections and ordinary resources.

### **7.1. Additional Principal Properties**

This section defines additional properties for WebDAV principal resources as defined in [[RFC3744](#)].

#### **7.1.1. CARDDAV:addressbook-home-set Property**

Name: addressbook-home-set

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Identifies the URL of any WebDAV collections that contain address book collections owned by the associated principal resource.

Protected: MAY be protected if the server has fixed locations in which address books are created.

COPY/MOVE behavior: This property value MUST be preserved in COPY and MOVE operations.

allprop behavior: SHOULD NOT be returned by a PROPFIND DAV:allprop request.

Description: The CARDDAV:addressbook-home-set property is meant to allow users to easily find the address book collections owned by the principal. Typically, users will group all the address book collections that they own under a common collection. This property specifies the URL of collections that either are address book collections or ordinary collections that have child or descendant address book collections owned by the principal.

Daboo  
18]

Expires January 14, 2010

[Page

Definition:

```
<!ELEMENT addressbook-home-set (DAV:href*)>
```

Example:

```
<C:addressbook-home-set xmlns:D="DAV:"  
  xmlns:C="urn:ietf:params:xml:ns:carddav">  
  <D:href>/bernard/addresses/</D:href>  
</C:addressbook-home-set>
```

### **7.1.2. CARDDAV:principal-address Property**

Name: principal-address

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Identifies the URL of an address object resource that corresponds to the user represented by the principal.

Protected: MAY be protected if the server provides a fixed location for principal addresses.

COPY/MOVE behavior: This property value MUST be preserved in COPY and MOVE operations.

allprop behavior: SHOULD NOT be returned by a PROPFIND DAV:allprop request.

Description: The CARDDAV:principal-address property is meant to allow users to easily find contact information for users represented by principals on the system. This property specifies the URL of the resource containing the corresponding contact information. The resource could be an address object resource in an address book collection, or it could be a resource in a "regular" collection.

Definition:

```
<!ELEMENT principal-address (DAV:href)>
```

Example:

```
<C:principal-address xmlns:D="DAV:"  
  xmlns:C="urn:ietf:params:xml:ns:carddav">  
  <D:href>/system/cyrus.vcf</D:href>  
</C:principal-address>
```



## **8. Address Book Reports**

This section defines the reports that CardDAV servers MUST support on address book collections and address object resources.

CardDAV servers MUST advertise support for these reports on all address book collections and address object resources with the DAV:supported-report-set property defined in [Section 3.1.5 of \[RFC3253\]](#). CardDAV servers MAY also advertise support for these reports on ordinary collections.

Some of these reports allow address data (from possibly multiple resources) to be returned.

### **8.1. REPORT Method**

The REPORT method (defined in [Section 3.6 of \[RFC3253\]](#)) provides an extensible mechanism for obtaining information about a resource. Unlike the PROPFIND method, which returns the value of one or more named properties, the REPORT method can involve more complex processing. REPORT is valuable in cases where the server has access to all of the information needed to perform the complex request (such as a query), and where it would require multiple requests for the client to retrieve the information needed to perform the same request.

A server that supports this specification MUST support the DAV:expand-property report (defined in [Section 3.8 of \[RFC3253\]](#)).

### **8.2. Ordinary Collections**

Servers MAY support the reports defined in this document on ordinary collections (collections that are not address book collections) in addition to address book collections or address object resources. In computing responses to the reports on ordinary collections, servers MUST only consider address object resources contained in address book collections that are targeted by the REPORT based on the value of the Depth request header.

### **8.3. Searching Text: Collations**

Some of the reports defined in this section do text matches of character strings provided by the client and compared to stored address data. Since vCard data is by default encoded in the UTF-8 charset and may include characters outside of the US-ASCII charset range in some property and parameter values, there is a need to ensure that text matching follows well-defined rules.

Daboo  
20]

Expires January 14, 2010

[Page



To deal with this, this specification makes use of the IANA Collation

Registry defined in [\[RFC4790\]](#) to specify collations that may be used to carry out the text comparison operations with a well-defined rule.

Collations supported by the server MUST support "equality" and "substring" match operations as per [\[RFC4790\] Section 4.2](#), including the "prefix" and "suffix" options for "substring" matching. CardDAV uses these match options for "equals", "contains", "starts-with" and "ends-with" match operations.

CardDAV servers are REQUIRED to support the "i;ascii-casemap" [\[RFC4790\]](#) and "i;unicode-casemap" [\[RFC5051\]](#) collations, and MAY support other collations.

Servers MUST advertise the set of collations that they support via the CARDDAV:supported-collation-set property defined on any resource that supports reports that use collations.

In the absence of a collation explicitly specified by the client, or if the client specifies the "default" collation identifier (as defined in [\[RFC4790\] Section 3.1](#)), the server MUST default to using "i;unicode-casemap" as the collation.

Wildcards (as defined in [\[RFC4790\] Section 3.2](#)) MUST NOT be used in the collation identifier.

If the client chooses a collation not supported by the server, the server MUST respond with a CARDDAV:supported-collation precondition error response.

### **8.3.1. CARDDAV:supported-collation-set Property**

Name: supported-collation-set

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Identifies the set of collations supported by the server for text matching operations.

Protected: MUST be protected as it indicates support provided by the server.

COPY/MOVE behavior: This property value MUST be preserved in COPY and MOVE operations.

Daboo  
21]

Expires January 14, 2010

[Page

allprop behavior: SHOULD NOT be returned by a PROPFIND DAV:allprop request.

Description: The CARDDAV:supported-collation-set property contains zero or more CARDDAV:supported-collation elements which specify the collection identifiers of the collations supported by the server.

Definition:

```
<!ELEMENT supported-collation-set (supported-collation*)>
```

```
<!ELEMENT supported-collation (#PCDATA)>
```

Example:

```
<C:supported-collation-set
  xmlns:C="urn:ietf:params:xml:ns:carddav">
  <C:supported-collation>i;ascii-casemap</C:supported-collation>
  <C:supported-collation>i;octet</C:supported-collation>
  <C:supported-collation>i;unicode-casemap</C:supported-
collation>
</C:supported-collation-set>
```

#### **8.4. Partial Retrieval**

Some address book reports defined in this document allow partial retrieval of address object resources. A CardDAV client can specify what information to return in the body of an address book REPORT request.

A CardDAV client can request particular WebDAV property values, all WebDAV property values, or a list of the names of the resource's WebDAV properties. A CardDAV client can also request address data to

be returned and whether all vCard properties should be returned or only particular ones. See CARDDAV:address-data in [Section 10.4](#).

#### **8.5. Non-standard Properties and Parameters**

Servers MUST support the use of non-standard vCard property or parameter names in the CARDDAV:address-data XML element in address book REPORT requests to allow clients to request that non-standard properties and parameters be returned in the address data provided in the response.

Servers MAY support the use of non-standard vCard property or parameter names in the CARDDAV:prop-filter and CARDDAV:param-filter XML elements specified in the CARDDAV:filter XML element of address book REPORT requests.

Daboo  
22]

Expires January 14, 2010

[Page

Servers MUST fail with the CARDDAV:supported-filter precondition if an address book REPORT request uses a CARDDAV:prop-filter or CARDDAV: param-filter XML element that makes reference to a non-standard vCard property or parameter name which the server does not support queries on.

### **8.6. CARDDAV:addressbook-query Report**

The CARDDAV:addressbook-query REPORT performs a search for all address object resources that match a specified filter. The response of this report will contain all the WebDAV properties and address object resource data specified in the request. In the case of the CARDDAV:address-data XML element, one can explicitly specify the vCard properties that should be returned in the address object resource data that matches the filter.

The format of this report is modeled on the PROPFIND method. The request and response bodies of the CARDAV:addressbook-query report use XML elements that are also used by PROPFIND. In particular the request can include XML elements to request WebDAV properties to be returned. When that occurs the response should follow the same behavior as PROPFIND with respect to the DAV:multistatus response elements used to return specific WebDAV property results. For instance, a request to retrieve the value of a WebDAV property which does not exist is an error and MUST be noted with a response XML element which contains a 404 (Not Found) status value.

Support for the CARDDAV:addressbook-query REPORT is REQUIRED.

Marshalling:

The request body MUST be a CARDDAV:addressbook-query XML element as defined in [Section 10.3](#).

The request MUST include a Depth header. The scope of the query is determined by the value of the Depth header. e.g., to query all address object resources in an address book collection, the REPORT would use the address book collection as the request-URI and specify a Depth of 1 or infinity.

The response body for a successful request MUST be a DAV:multistatus XML element (i.e., the response uses the same format as the response for PROPFIND). In the case where there are no response elements, the returned DAV:multistatus XML element is empty.

The response body for a successful CARDDAV:addressbook-query

REPORT request MUST contain a DAV:response element for each

Daboo  
23]

Expires January 14, 2010

[Page

address object that matched the search filter. address data is returned in the CARDDAV:address-data XML element inside the DAV:propstat XML element.

Preconditions:

(CARDDAV:supported-address-data): The attributes "content-type" and "version" of the CARDDAV:address-data XML element (see [Section 10.4](#)) specify a media type supported by the server for address object resources.

(CARDDAV:supported-filter): The CARDDAV:prop-filter (see [Section 10.5.1](#)) and CARDDAV:param-filter (see [Section 10.5.2](#)) XML elements used in the CARDDAV:filter XML element (see [Section 10.5](#))

in the REPORT request only make reference to vCard properties and parameters for which queries are supported by the server. i.e.,  
if  
the CARDDAV:filter element attempts to reference an unsupported vCard property or parameter, this precondition is violated. Servers SHOULD report the CARDDAV:prop-filter or CARDDAV:param-filter for which it does not provide support.

```
<!ELEMENT supported-filter (prop-filter*,  
                             param-filter*)>
```

(CARDDAV:supported-collation): Any XML attribute specifying a collation MUST specify a collation supported by the server as described in [Section 8.3](#).

Postconditions:

(DAV:number-of-matches-within-limits): The number of matching address object resources must fall within server-specific, predefined limits. For example, this condition might be  
triggered  
if a search specification would cause the return of an extremely large number of responses.

### **8.6.1. Limiting Results**

A client can limit the number of results returned by the server through use of the CARDDAV:limit element in the request body. This is useful when clients are only interested in a few matches, or only have limited space to display results to users and thus don't need the overhead of receiving more than that. When the results are truncated by the server, the server MUST follow the rules below for indicating a result set truncation to the client.

Daboo  
24]

Expires January 14, 2010

[Page



### **8.6.2. Truncation of Results**

A server MAY limit the number of resources in a response, for example, to limit the amount of work expended in processing a query, or as the result of an explicit limit set by the client. If it does so, the response MUST use status code 207, return a DAV:multistatus response body, and indicate a status of 507 (Insufficient Storage) for the request URI. That DAV:response element SHOULD include a

DAV:

error element with the DAV:number-of-matches-within-limits precondition, as defined in [[RFC3744](#)] ([Section 9.2](#)).

The server SHOULD also include the partial results in additional

DAV:

response elements. If a client requested limit is being applied, the

507 response for the request URI MUST NOT be included in calculating the limit (e.g., if the client requests that only a single result be returned, and multiple matches are present, then the DAV:multistatus response will include one DAV:response for the matching resource and one DAV:response for the 507 status on the request URI).

### **8.6.3. Example: Partial Retrieval of vCards Matching NICKNAME**

In this example, the client requests the server to search for address

object resources that contain a NICKNAME property whose value equals some specific text, and to return specific vCard properties for those

vCards found. In addition the DAV:getetag property is also requested

and returned as part of the response.

Daboo  
25]

Expires January 14, 2010

[Page

>> Request <<

```
REPORT /home/bernard/addressbook/ HTTP/1.1
Host: addressbook.example.com
Depth: 1
Content-Type: text/xml; charset="utf-8"
Content-Length: xxxx
```

```
<?xml version="1.0" encoding="utf-8" ?>
<C:addressbook-query xmlns:D="DAV:"
                    xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:prop>
    <D:getetag/>
    <C:address-data>
      <C:prop name="VERSION"/>
      <C:prop name="UID"/>
      <C:prop name="NICKNAME"/>
      <C:prop name="EMAIL"/>
      <C:prop name="FN"/>
    </C:address-data>
  </D:prop>
  <C:filter>
    <C:prop-filter name="NICKNAME">
      <C:text-match collation="i;unicode-casemap"
                    match-type="equals"
                    >me</C:text-match>
    </C:prop-filter>
  </C:filter>
</C:addressbook-query>
```



>> Response <<

```
HTTP/1.1 207 Multi-Status
Date: Sat, 11 Nov 2006 09:32:12 GMT
Content-Type: text/xml; charset="utf-8"
Content-Length: xxxx

<?xml version="1.0" encoding="utf-8" ?>
<D:multistatus xmlns:D="DAV:"
                xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:response>
    <D:href>/home/bernard/addressbook/v102.vcf</D:href>
    <D:propstat>
      <D:prop>
        <D:getetag>"23ba4d-ff11fb"</D:getetag>
        <C:address-data>BEGIN:VCARD
VERSION:3.0
NICKNAME:me
UID:34222-232@example.com
FN:Cyrus Daboo
EMAIL:daboo@example.com
END:VCARD
</C:address-data>
      </D:prop>
      <D:status>HTTP/1.1 200 OK</D:status>
    </D:propstat>
  </D:response>
</D:multistatus>
```

#### **8.6.4. Example: Partial Retrieval of vCards Matching a Full Name or Email Address**

In this example, the client requests the server to search for address object resources that contain a FN property whose value contains some specific text or that contain an EMAIL property whose value contains other text, and to return specific vCard properties for those vCards found. In addition the DAV:getetag property is also requested and returned as part of the response.

Daboo  
27]

Expires January 14, 2010

[Page

>> Request <<

```
REPORT /home/bernard/addressbook/ HTTP/1.1
Host: addressbook.example.com
Depth: 1
Content-Type: text/xml; charset="utf-8"
Content-Length: xxxx
```

```
<?xml version="1.0" encoding="utf-8" ?>
<C:addressbook-query xmlns:D="DAV:"
                    xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:prop>
    <D:getetag/>
    <C:address-data>
      <C:prop name="VERSION"/>
      <C:prop name="UID"/>
      <C:prop name="NICKNAME"/>
      <C:prop name="EMAIL"/>
      <C:prop name="FN"/>
    </C:address-data>
  </D:prop>
  <C:filter test="anyof">
    <C:prop-filter name="FN">
      <C:text-match collation="i;unicode-casemap"
                    match-type="contains"
                    >daboo</C:text-match>
    </C:prop-filter>
    <C:prop-filter name="EMAIL">
      <C:text-match collation="i;unicode-casemap"
                    match-type="contains"
                    >daboo</C:text-match>
    </C:prop-filter>
  </C:filter>
</C:addressbook-query>
```

Daboo  
28]

Expires January 14, 2010

[Page



>> Response <<

HTTP/1.1 207 Multi-Status  
Date: Sat, 11 Nov 2006 09:32:12 GMT  
Content-Type: text/xml; charset="utf-8"  
Content-Length: xxxx

```
<?xml version="1.0" encoding="utf-8" ?>
<D:multistatus xmlns:D="DAV:"
                xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:response>
    <D:href>/home/bernard/addressbook/v102.vcf</D:href>
    <D:propstat>
      <D:prop>
        <D:getetag>"23ba4d-ff11fb"</D:getetag>
        <C:address-data>BEGIN:VCARD
VERSION:3.0
NICKNAME:me
UID:34222-232@example.com
FN:David Boo
EMAIL:daboo@example.com
END:VCARD
</C:address-data>
        </D:prop>
        <D:status>HTTP/1.1 200 OK</D:status>
      </D:propstat>
    </D:response>
  <D:response>
    <D:href>/home/bernard/addressbook/v104.vcf</D:href>
    <D:propstat>
      <D:prop>
        <D:getetag>"23ba4d-ff11fc"</D:getetag>
        <C:address-data>BEGIN:VCARD
VERSION:3.0
NICKNAME:oliver
UID:34222-23222@example.com
FN:Oliver Daboo
EMAIL:oliver@example.com
END:VCARD
</C:address-data>
      </D:prop>
      <D:status>HTTP/1.1 200 OK</D:status>
    </D:propstat>
  </D:response>
</D:multistatus>
```

Daboo  
29]

Expires January 14, 2010

[Page

### **8.6.5. Example: Truncated Results**

In this example, the client requests the server to search for address object resources that contain a FN property whose value contains some specific text, and to return the DAV:getetag property for two results only. The server response includes a 507 status for the request URI indicating that there were more than two resources that matched the query, but that the server truncated the result set as requested by the client.

>> Request <<

```
REPORT /home/bernard/addressbook/ HTTP/1.1
Host: addressbook.example.com
Depth: 1
Content-Type: text/xml; charset="utf-8"
Content-Length: xxxx
```

```
<?xml version="1.0" encoding="utf-8" ?>
<C:addressbook-query xmlns:D="DAV:"
    xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:prop>
    <D:getetag/>
  </D:prop>
  <C:filter test="anyof">
    <C:prop-filter name="FN">
      <C:text-match collation="i;unicode-casemap"
        match-type="contains"
        >daboo</C:text-match>
    </C:prop-filter>
  </C:filter>
  <C:limit>
    <C:nresults>2</C:nresults>
  </C:limit>
</C:addressbook-query>
```

Daboo  
30]

Expires January 14, 2010

[Page

>> Response <<

```
HTTP/1.1 207 Multi-Status
Date: Sat, 11 Nov 2006 09:32:12 GMT
Content-Type: text/xml; charset="utf-8"
Content-Length: xxxx

<?xml version="1.0" encoding="utf-8" ?>
<D:multistatus xmlns:D="DAV:"
                xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:response>
    <D:href>/home/bernard/addressbook/</D:href>
    <D:status>HTTP/1.1 507 OK</D:status>
    <D:error><D:number-of-matches-within-limits/></D:error>
    <D:responsedescription xml:lang="en">
      Only two matching records were returned
    </D:responsedescription>
  </D:response>
  <D:response>
    <D:href>/home/bernard/addressbook/v102.vcf</D:href>
    <D:propstat>
      <D:prop>
        <D:getetag>"23ba4d-ff11fb"</D:getetag>
      </D:prop>
      <D:status>HTTP/1.1 200 OK</D:status>
    </D:propstat>
  </D:response>
  <D:response>
    <D:href>/home/bernard/addressbook/v104.vcf</D:href>
    <D:propstat>
      <D:prop>
        <D:getetag>"23ba4d-ff11fc"</D:getetag>
      </D:prop>
      <D:status>HTTP/1.1 200 OK</D:status>
    </D:propstat>
  </D:response>
</D:multistatus>
```

### **8.7. CARDDAV:addressbook-multiget Report**

The CARDDAV:addressbook-multiget REPORT is used to retrieve specific address object resources from within a collection, if the Request-URI

is a collection, or to retrieve a specific address object resource, if the Request-URI is a address object resource. This report is similar to the CARDDAV:addressbook-query REPORT (see [Section 8.6](#)), except that it takes a list of DAV:href elements instead of a



CARDDAV:filter element to determine which address object resources to return.

Support for the addressbook-multiget REPORT is REQUIRED.

Marshalling:

The request body MUST be a CARDDAV:addressbook-multiget XML element (see [Section 10.7](#)), which MUST contain at least one DAV:href XML element, and one optional CARDDAV:address-data element as defined in [Section 10.4](#). If DAV:href elements are present, the scope of the request is the set of resources identified by these elements, which all need to be members (not necessarily internal members) of the resource identified by the Request-URI. Otherwise, the scope is the resource identified by the Request-URI itself.

The request MUST include a Depth: 0 header, however the actual scope of the REPORT is determined as described above.

The response body for a successful request MUST be a DAV:multistatus XML element.

The response body for a successful CARDDAV:addressbook-multiget REPORT request MUST contain a DAV:response element for each address object resource referenced by the provided set of DAV:href elements. Address data is returned in the CARDDAV:address-data element inside the DAV:prop element.

In the case of an error accessing any of the provided DAV:href resources, the server MUST return the appropriate error status code in the DAV:status element of the corresponding DAV:response element.

Preconditions:

(CARDDAV:supported-address-data): The attributes "content-type" and "version" of the CARDDAV:address-data XML elements (see [Section 10.4](#)) specify a media type supported by the server for address object resources.

Postconditions:

None.

Daboo  
32]

Expires January 14, 2010

[Page



### **8.7.1. Example: CARDDAV:addressbook-multiget Report**

In this example, the client requests the server to return specific vCard properties of the address components referenced by specific URIs. In addition the DAV:getetag property is also requested and returned as part of the response. Note that in this example, the resource at <http://addressbook.example.com/home/bernard/addressbook/vcf1.vcf> does not exist, resulting in an error status response.

>> Request <<

```
REPORT /home/bernard/addressbook/ HTTP/1.1
Host: addressbook.example.com
Depth: 1
Content-Type: text/xml; charset="utf-8"
Content-Length: xxxx
```

```
<?xml version="1.0" encoding="utf-8" ?>
<C:addressbook-multiget xmlns:D="DAV:"
                        xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:prop>
    <D:getetag/>
    <C:address-data>
      <C:prop name="VERSION"/>
      <C:prop name="UID"/>
      <C:prop name="NICKNAME"/>
      <C:prop name="EMAIL"/>
      <C:prop name="FN"/>
    </C:address-data>
  </D:prop>
  <D:href>/home/bernard/addressbook/vcf102.vcf</D:href>
  <D:href>/home/bernard/addressbook/vcf1.vcf</D:href>
</C:addressbook-multiget>
```



>> Response <<

```
HTTP/1.1 207 Multi-Status
Date: Sat, 11 Nov 2006 09:32:12 GMT
Content-Type: text/xml; charset="utf-8"
Content-Length: xxxx

<?xml version="1.0" encoding="utf-8" ?>
<D:multistatus xmlns:D="DAV:"
                xmlns:C="urn:ietf:params:xml:ns:carddav">
  <D:response>
    <D:href>/home/bernard/addressbook/vcf102.vcf</D:href>
    <D:propstat>
      <D:prop>
        <D:getetag>"23ba4d-ff11fb"</D:getetag>
        <C:address-data>BEGIN:VCARD
VERSION:3.0
NICKNAME:me
UID:34222-232@example.com
FN:Cyrus Daboo
EMAIL:daboo@example.com
END:VCARD
</C:address-data>
      </D:prop>
      <D:status>HTTP/1.1 200 OK</D:status>
    </D:propstat>
  </D:response>
  <D:response>
    <D:href>/home/bernard/addressbook/vcf1.vcf</D:href>
    <D:status>HTTP/1.1 404 Resource not found</D:status>
  </D:response>
</D:multistatus>
```

## **9. Guidelines**

### **9.1. Restrict the Properties Returned**

Clients may not need all the properties in a vCard object when presenting information to the user, or looking up specific items for their email address, for example. Since some property data can be large (e.g., PHOTO or SOUND with inline content) clients can choose to ignore those by only requesting the specific items it knows it will use, through use of the CARDDAV:address-data XML element in the relevant reports.



However, if a client needs to make a change to a vCard, it can only change the entire vCard data via a PUT request. There is no way to incrementally make a change to a set of properties within a vCard object resource. As a result the client will have to cache the entire set of properties on a resource that is being changed.

## **9.2. Use of Locking**

WebDAV locks can be used to prevent two clients modifying the same resource from either overwriting each others' changes (though that problem can also be solved by using ETags) and also to prevent the user from making changes that will conflict with another set of changes. In a multi-user address book system, the address book client could lock an address object resource while the user is editing the vCard data, and unlock the address object resource when the user finishes or cancels. Locks can also be used to prevent changes while data is being reorganized. For example, an address book client might lock two address book collections prior to moving

a bunch of address object resources from one to another.

Clients may request a lock timeout period that is appropriate to the use case. When the user explicitly decides to reserve a resource and

prevent other changes, a long timeout might be appropriate, but in cases when the client automatically decides to lock the resource the timeout should be short (and the client can always refresh the lock should it need to). A short lock timeout means that if the client is

unable to remove the lock, the other address book users aren't prevented from making changes.

## **9.3. Client Configuration**

When CardDAV clients need to be configured, the key piece of information that they require is the principal-URL of the user whose address book information is desired. Servers SHOULD support the

DAV:current-user-principal-URL property as defined in [[RFC5397](#)] to give clients a fast way to locate user principals.

Given support for SRV records ([Section 11](#)) and DAV:current-user-principal-URL [[RFC5397](#)], users only need enter a user identifier, host name and password to configure their client. The client would take the host name and do an SRV lookup to locate the CardDAV

server,  
then execute an authenticated PROPFIND on the root / resource

looking for the DAV:current-user-principal-URL property. The value returned gives the client direct access to the user's principal-URL and from there all the related CardDAV properties needed to locate address books.

Daboo  
35]

Expires January 14, 2010

[Page

#### **9.4. Finding Other Users' Address Books**

For address book sharing use cases, one might wish to find the address book belonging to another user. If the other user has an address book in the same repository, that address book can be found by using the principal namespace required by WebDAV ACL support.

To find other users' address books, the DAV:principal-property-search

REPORT can be used to filter on some properties and return others. To search for an address book owned by a user named "Laurie", the REPORT request body would look like this:

```
<?xml version="1.0" encoding="utf-8" ?>
<D:principal-property-search xmlns:D="DAV:">
  <D:property-search>
    <D:prop>
      <D:displayname/>
    </D:prop>
    <D:match>Laurie</D:match>
  </D:property-search>
  <D:prop>
    <C:addressbook-home-set
      xmlns:C="urn:ietf:params:xml:ns:carddav"/>
    <D:displayname/>
  </D:prop>
</D:principal-property-search>
```

The server performs a case-sensitive or caseless search for a matching string subset of "Laurie" within the DAV:displayname property. Thus, the server might return "Laurie Dusseault", "Laurier Desruisseaux" or "Wilfrid Laurier" all as matching DAV:displayname values, and the address books for each of these.

### **10. XML Element Definitions**

#### **10.1. CARDDAV:addressbook XML Element**

Name: addressbook

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Specifies the resource type of an address book collection.

Description: See [Section 5.2](#).

Daboo  
36]

Expires January 14, 2010

[Page



Definition:

```
<!ELEMENT addressbook EMPTY>
```

### **10.2. CARDDAV:supported-collation XML Element**

Name: supported-collation

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Identifies a single collation via its collation identifier as defined by [\[RFC4790\]](#).

Description: The CARDDAV:supported-collation contains the text of a collation identifier as described in [Section 8.3.1](#).

Definition:

```
<!ELEMENT supported-collation (#PCDATA)>  
<!-- PCDATA value: collation identifier -->
```

### **10.3. CARDDAV:addressbook-query XML Element**

Name: addressbook-query

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Defines a report for querying address book data

Description: See [Section 8.6](#).

Definition:

```
<!ELEMENT addressbook-query ((DAV:allprop |  
                             DAV:propname |  
                             DAV:prop)?, filter, limit?)>
```

### **10.4. CARDDAV:address-data XML Element**

Name: address-data

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Specifies one of the following:

1. The parts of an address object resource which should be returned by a given address book REPORT request, and the media type and version for the returned data;



2. The content of an address object resource in a response to an address book REPORT request.

Description: When used in an address book REPORT request, the CARDDAV:address-data XML element specifies which parts of address object resources need to be returned in the response. If the CARDDAV:address-data XML element doesn't contain any CARDDAV:prop elements, address object resources will be returned in their entirety. Additionally a media type and version can be specified to request that the server return the data in that format if possible.

Finally, when used in an address book REPORT response, the CARDDAV:address-data XML element specifies the content of a address object resource. Given that XML parsers normalize the two-character sequence CRLF (US-ASCII decimal 13 and US-ASCII decimal 10) to a single LF character (US-ASCII decimal 10), the

CR

character (US-ASCII decimal 13) MAY be omitted in address object resources specified in the CARDDAV:address-data XML element. Furthermore, address object resources specified in the CARDDAV:address-data XML element MAY be invalid per their media type specification if the CARDDAV:address-data XML element part of the address book REPORT request did not specify required vCard properties (e.g., UID, etc.) or specified a CARDDAV:prop XML element with the "novalue" attribute set to "yes".

Note: The CARDDAV:address-data XML element is specified in requests and responses inside the DAV:prop XML element as if it were a WebDAV property. However, the CARDDAV:address-data XML element

is

not a WebDAV property and as such it is not returned in PROPFIND responses nor used in PROPPATCH requests.

Note: The address data embedded within the CARDDAV:address-data XML element MUST follow the standard XML character data encoding rules, including use of &lt;, &gt;, &amp; etc entity encoding or the use of a <![CDATA[ ... ]]> construct. In the later case the vCard data cannot contain the character sequence "]]>" which is the end delimiter for the CDATA section.

Definition:

Daboo  
38]

Expires January 14, 2010

[Page

```
<!ELEMENT address-data (allprop | prop*)>
```

when nested in the DAV:prop XML element in an address book REPORT request to specify which parts of address object resources should be returned in the response;

```
<!ELEMENT address-data (#PCDATA)>  
<!-- PCDATA value: address data -->
```

when nested in the DAV:prop XML element in an address book REPORT response to specify the content of a returned address object resource.

```
<!ATTLIST address-data content-type CDATA "text/vcard"  
                        version CDATA "3.0">  
<!-- content-type value: a MIME media type -->  
<!-- version value: a version string -->
```

attributes can be used on each variant of the CALDAV:address-data XML element.

#### **10.4.1. CARDDAV:allprop XML Element**

Name: allprop

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Specifies that all vCard properties shall be returned.

Description: This element can be used when the client wants all vCard properties of components returned by a report.

Definition:

```
<!ELEMENT allprop EMPTY>
```

NOTE: The CARDDAV:allprop element defined here has the same name as the DAV:allprop element defined in WebDAV. However, the CARDDAV:allprop element defined here uses the "urn:ietf:params:xml:ns:carddav" namespace, as opposed to the "DAV:" namespace used for the DAV:allprop element defined in WebDAV.

#### **10.4.2. CARDDAV:prop XML Element**



Name: prop

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Defines which vCard properties to return in the response.

Description: The "name" attribute specifies the name of the vCard property to return (e.g., "NICKNAME"). The "novalue" attribute can be used by clients to request that the actual value of the property not be returned (if the "novalue" attribute is set to "yes"). In that case the server will return just the vCard property name and any vCard parameters and a trailing ":" without the subsequent value data.

vCard allows a "group" prefix to appear before a property name in the vCard data. When the "name" attribute does not specify a group prefix, it MUST match properties in the vCard data without

a

group prefix or with any group prefix. When the "name" attribute includes a group prefix, it MUST match properties that have exactly the same group prefix and name. e.g.: a "name" set to "TEL" will match "TEL", "X-ABC.TEL", "X-ABC-1.TEL" vCard properties. A "name" set to "X-ABC.TEL" will match an "X-

ABC.TEL"

vCard property only, it will not match "TEL" or "X-ABC-1.TEL".

Definition:

```
<!ELEMENT prop EMPTY>

<!ATTLIST prop name CDATA #REQUIRED
              novalue (yes | no) "no">
<!-- name value: a vCard property name -->
<!-- novalue value: "yes" or "no" -->
```

NOTE: The CARDDAV:prop element defined here has the same name as the DAV:prop element defined in WebDAV. However, the CARDDAV:prop element defined here uses the "urn:ietf:params:xml:ns:carddav" namespace, as opposed to the "DAV:" namespace used for the DAV:prop element defined in WebDAV.

#### **10.5. CARDDAV:filter XML Element**

Name: filter

Namespace: urn:ietf:params:xml:ns:carddav

Daboo  
40]

Expires January 14, 2010

[Page



Purpose: Determines which matching objects are returned.

Description: The "filter" element specifies the search filter used to match address objects that should be returned by a report.

The

"test" attribute specifies whether any (logical OR) or all (logical AND) of the prop-filter tests needs to match in order

for

the overall filter to match.

Definition:

```
<!ELEMENT filter (prop-filter*)>

<!ATTLIST filter test (anyof | allof) "anyof">
<!-- test value:
      anyof logical OR for prop-filter matches
      allof logical AND for prop-filter matches -->
```

#### **10.5.1. CARDDAV:prop-filter XML Element**

Name: prop-filter

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Limits the search to specific vCard properties.

Description: The CARDDAV:prop-filter XML element specifies a search criteria on a specific vCard property (e.g., NICKNAME). An address object is said to match a CARDDAV:prop-filter if:

\* A vCard property of the type specified by the "name" attribute exists, and the CARDDAV:prop-filter is empty, or it matches any CARDDAV:text-match conditions if specified, and that CARDDAV:param-filter child elements also match. The "test" attribute specifies whether any (logical OR) or all (logical AND) of the text-filter and param-filter tests need to match in order for the overall filter to match.

or:

\* A vCard property of the type specified by the "name" attribute does not exist, and the CARDAV:is-not-defined element is specified.

vCard allows a "group" prefix to appear before a property name in the vCard data. When the "name" attribute does not specify a group prefix, it MUST match properties in the vCard data without

a

group prefix or with any group prefix. When the "name" attribute includes a group prefix, it MUST match properties that have

Daboo  
41]

Expires January 14, 2010

[Page

exactly the same group prefix and name. e.g.: a "name" set to "TEL" will match "TEL", "X-ABC.TEL", "X-ABC-1.TEL" vCard properties. A "name" set to "X-ABC.TEL" will match an "X-ABC.TEL" vCard property only, it will not match "TEL" or "X-ABC-1.TEL".

Definition:

```
<!ELEMENT prop-filter (is-not-defined |
                        (text-match*, param-filter*))>

<!ATTLIST prop-filter name CDATA #REQUIRED
                        test (anyof | allof) "anyof">
<!-- name value: a vCard property name (e.g., "NICKNAME")
     test value:
         anyof logical OR for text-match/param-filter matches
         allof logical AND for text-match/param-filter matches -->
```

#### **10.5.2. CARDDAV:param-filter XML Element**

Name: param-filter

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Limits the search to specific parameter values.

Description: The CARDDAV:param-filter XML element specifies a search

criteria on a specific vCard property parameter (e.g., TYPE) in the scope of a given CARDDAV:prop-filter. A vCard property is said to match a CARDDAV:param-filter if:

- \* A parameter of the type specified by the "name" attribute exists, and the CARDDAV:param-filter is empty, or it matches the CARDDAV:text-match conditions if specified.

or:

- \* A parameter of the type specified by the "name" attribute does not exist, and the CARDDAV:is-not-defined element is specified.

Definition:

```
<!ELEMENT param-filter (is-not-defined | text-match)?>

<!ATTLIST param-filter name CDATA #REQUIRED>
<!-- name value: a property parameter name (e.g., "TYPE") -->
```

Daboo  
42]

Expires January 14, 2010

[Page

### **10.5.3. CARDDAV:is-not-defined XML Element**

Name: is-not-defined

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Specifies that a match should occur if the enclosing vCard property or parameter does not exist.

Description: The CARDDAV:is-not-defined XML element specifies that  
a match occurs if the enclosing vCard property or parameter value specified in an address book REPORT request does not exist in the address data being tested.

Definition:

```
<!ELEMENT is-not-defined EMPTY>
```

### **10.5.4. CARDDAV:text-match XML Element**

Name: text-match

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Specifies a substring match on a vCard property or parameter value.

Description: The CARDDAV:text-match XML element specifies text used for a substring match against the vCard property or parameter value specified in an address book REPORT request.

The "collation" attribute is used to select the collation that  
the server MUST use for character string matching. In the absence of this attribute the server MUST use the "i;unicode-casemap" collation.

The "negate-condition" attribute is used to indicate that this  
value test returns a match if the text matches, when the attribute is set to "no", or return a match if the text does not match, if the attribute value is set to "yes". For example, this can be used to match components with a CATEGORIES property not set to PERSON.

The "match-type" attribute is used to indicate the type of match operation to use. Possible choices are:

Daboo  
43]

Expires January 14, 2010

[Page

"equals" - an exact match to the target string

"contains" - a substring match, matching anywhere within the target string

"starts-with" - a substring match, matching only at the start of the target string

"ends-with" - a substring match, matching only at the end of the target string

Definition:

```
<!ELEMENT text-match (#PCDATA)>
<!-- PCDATA value: string -->

<!ATTLIST text-match
  collation          CDATA "i;unicode-casemap"
  negate-condition (yes | no) "no"
  match-type (equals|contains|starts-with|ends-with)
```

"contains">

#### **10.6. CARDDAV:limit XML Element**

Name: limit

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: Specifies different types of limits that can be applied to the results returned by the server.

Description: The CARDDAV:limit XML element can be used to specify different types of limits that the client can request the server to apply to the results returned by the server. Currently only the CARDDAV:nresults limit can be used, other types of limit could be defined in the future.

Definition:

```
<!ELEMENT limit (nresults)>
```

#### **10.6.1. CARDDAV:nresults XML Element**

Name: nresults

Namespace: urn:ietf:params:xml:ns:carddav

Daboo  
44]

Expires January 14, 2010

[Page



Purpose: Specifies a limit on the number of results returned by the server.

Description: The CARDDAV:nresults XML element contains a requested maximum number of DAV:response elements to be returned in the response body of a query. The server MAY disregard this limit. The value of this element is an unsigned integer.

Definition:

```
<!ELEMENT nresults (#PCDATA)>
<!-- nresults value: unsigned integer, must be digits -->
```

### **10.7. CARDDAV:addressbook-multiget XML Element**

Name: addressbook-multiget

Namespace: urn:ietf:params:xml:ns:carddav

Purpose: CardDAV report used to retrieve specific address objects via their URIs.

Description: See [Section 8.7](#).

Definition:

```
<!ELEMENT addressbook-multiget ((DAV:allprop |
                                DAV:propname |
                                DAV:prop)?,
                                DAV:href+)>
```

## **11. Service Discovery via SRV Records**

[RFC2782] defines a DNS-based service discovery protocol that has been widely adopted as a means of locating particular services within

a local area network and beyond, using SRV RR records.

This specification adds two service types for use with SRV records:

carddav: Identifies a CardDAV server that uses HTTP without SSL.

carddavs: Identifies a CardDAV server that uses HTTP with SSL.

Example: non-SSL service record

```
_carddav._tcp SRV 0 1 80 addressbook.example.com.
```



Example: SSL service

```
_carddavs._tcp SRV 0 1 443 addressbook.example.com.
```

## **12. Internationalization Considerations**

CardDAV allows internationalized strings to be stored and retrieved for the description of address book collections (see [Section 6.2.1](#)).

The CARDDAV:addressbook-query REPORT ([Section 8.6](#)) includes a text searching option controlled by the CARDDAV:text-match element and details of character handling are covered in the description of that element (see [Section 10.5.4](#)).

## **13. Security Considerations**

HTTP protocol transactions are sent in the clear over the network unless protection from snooping is negotiated. This can be accomplished by use of TLS as defined in [[RFC2818](#)]. In particular, if HTTP Basic authentication is available, the server MUST allow TLS to be used at the same time, and SHOULD prevent use of Basic authentication when TLS is not in use.

With the ACL extension present, WebDAV allows control over who can access (read or write) any resource on the WebDAV server. In addition, WebDAV ACL provides for an "inheritance" mechanism, whereby resources may inherit access privileges from other resources. Often the "other" resource is a parent collection of the resource itself. Clients MUST take care to ensure users are aware of which address books may be "private" (i.e. only accessible to them) and which are "shared" (i.e. accessible to others).

Since web servers are often the target of automated indexing applications that gather data from the server, analyze it and extract 'interesting' parts, great care must be taken when allowing unauthenticated access to any address book or address object data. Clients MAY choose to warn users when they create address data in a public address book, copy or move address data into public address books, or change access privileges in such a way as to expose address data to unauthenticated users.

This specification currently relies on standard HTTP authentication mechanisms for identifying users. These comprise Basic and Digest authentication as well as SSL using client-side certificates.

Daboo  
46]

Expires January 14, 2010

[Page

## **14. IANA Consideration**

This document uses a URN to describe a new XML namespace conforming to the registry mechanism described in [[RFC3688](#)].

### **14.1. Namespace Registration**

Registration request for the carddav namespace:

URI: urn:ietf:params:xml:ns:carddav

Registrant Contact: See the "Author's Address" section of this document.

XML: None - not applicable for namespace registrations.

## **15. Acknowledgments**

Thanks go to Lisa Dusseault and Bernard Desruisseaux for their work on CalDAV, on which CardDAV is heavily based. The following individuals contributed their ideas and support for writing this specification: Mike Douglass, Stefan Eissing, Helge Hess, Arnaud Quillaud, Julian Reschke, Elias Sinderson, Greg Stein, Wilfredo Sanchez, and Simon Vaillancourt.

## **16. References**

### **16.1. Normative References**

- [I-D.ietf-vcarddav-vcardrev]  
Perreault, S. and P. Resnick, "vCard Format Specification", [draft-ietf-vcarddav-vcardrev-08](#) (work in progress), July 2009.
- [I-D.ietf-vcarddav-webdav-mkcol]  
Daboo, C., "Extended MKCOL for WebDAV", [draft-ietf-vcarddav-webdav-mkcol-04](#) (work in progress), March 2009.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2426] Dawson, F. and T. Howes, "vCard MIME Directory Profile", [RFC 2426](#), September 1998.
- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H.,



Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.

[RFC2782] Gulbrandsen, A., Vixie, P., and L. Esibov, "A DNS RR for specifying the location of services (DNS SRV)", [RFC 2782](#), February 2000.

[RFC2818] Rescorla, E., "HTTP Over TLS", [RFC 2818](#), May 2000.

[RFC3253] Clemm, G., Amsden, J., Ellison, T., Kaler, C., and J. Whitehead, "Versioning Extensions to WebDAV (Web Distributed Authoring and Versioning)", [RFC 3253](#), March 2002.

[RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.

[RFC3744] Clemm, G., Reschke, J., Sedlar, E., and J. Whitehead,  
"Web Distributed Authoring and Versioning (WebDAV) Access Control Protocol", [RFC 3744](#), May 2004.

[RFC4790] Newman, C., Duerst, M., and A. Gulbrandsen, "Internet Application Protocol Collation Registry", [RFC 4790](#), March 2007.

[RFC4918] Dusseault, L., "HTTP Extensions for Web Distributed Authoring and Versioning (WebDAV)", [RFC 4918](#), June 2007.

[RFC5051] Crispin, M., "i;unicode-casemap - Simple Unicode Collation Algorithm", [RFC 5051](#), October 2007.

[RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), August 2008.

[RFC5397] Sanchez, W. and C. Daboo, "WebDAV Current Principal Extension", [RFC 5397](#), December 2008.

[W3C.REC-xml-20081126]

Paoli, J., Yergeau, F., Bray, T., Sperberg-McQueen, C., and E. Maler, "Extensible Markup Language (XML) 1.0

(Fifth

Edition)", World Wide Web Consortium Recommendation REC-xml-20081126, November 2008,  
<<http://www.w3.org/TR/2008/REC-xml-20081126>>.

## **16.2. Informative References**

[IMSP] Myers, J., "IMSP - Internet Message Support Protocol", June 1995.

Daboo  
48]

Expires January 14, 2010

[Page



- [RFC2244] Newman, C. and J. Myers, "ACAP -- Application Configuration Access Protocol", [RFC 2244](#), November 1997.
- [RFC4511] Sermersheim, J., "Lightweight Directory Access Protocol (LDAP): The Protocol", [RFC 4511](#), June 2006.

#### Appendix A. Change History (to be removed prior to publication as an RFC)

##### Changes in -07

1. WGLC: changed all allprop behaviors to SHOULD NOT return in allprop PROPFIND.
2. WGLC: Reworked XML conventions section to come into line with text in extended MKCOL, and also updated W3C reference.
3. WGLC: Changed a couple of examples to use absolute path DAV:href values.
4. WGLC: Simplified IANA Considerations section.
5. WGLC: Added new Client Configuration section and removed reference to principal-match.
6. address-data element in supported-address-data changed to address-data-type.
7. REPORTs now require Depth to be present and the scope of matching resources is determined by the value of the Depth header.
8. Removed requirement that DAV:displayname should be unique at each level.

##### Changes in -06

1. WGLC: addressbook-home-set changed to SHOULD NOT return in allprop PROPFIND.
2. WGLC: principal-address description changed to note that the resource pointed to could be in a regular collection too.
3. Added new section describing how SRV and current-user-principal are used to bootstrap client configuration.
4. Removed discussion of using principal-match report.

Daboo  
49]

Expires January 14, 2010

[Page

Changes in -05

1. Removed mailing list discussion note from abstract.

Changes in -04

1. Tweaked limit element text to not imply any formal ordering of results.
2. Changed prop-filter element to allow zero or more text-match elements rather than zero or one.
3. Updated to [RFC5397](#) reference.
4. Updated TLS reference to latest version [RFC5246](#).
5. Boiler plate update.

Changes in -03

1. Added limit element to addressbook-query.
2. Specified how a server signals that query results have been truncated.
3. Minor stylistic changes.

Changes in -02

1. Added text to CARDDAV:prop and CARDDAV:prop-filter elements to explain how vCard "group" prefix on property names is handled.

Changes in -01

1. Added section on SRV records.

Changes in -00

1. Removed text describing other protocols.
2. Added comment about a new vcard spec being developed.
3. Added SHOULD support for the DAV:current-user-principal-URL property.
4. Added "anyof"/"allof" test attribute to query XML elements to support simple or/and combinations of tests.



Changes in pre-04

1. Renamed addressbook-data to address-data for consistency.
2. Fixed address-data element definition.

Changes in pre-03

1. Replaced MKADDRESSBOOK with extended MKCOL.
2. Now require i;unicode-casemap as a supported collation and make it the default.
3. No longer require i;octet as a supported collation.
4. Allow different types of match operations via the "match-type" attribute on the "text-match" element.
5. Updated to 4918 reference and removed some text/sections duplicating 4918.
6. WebDAV Level 3 now required.
7. TLS requirement text tweaked to match latest text approved by IESG.
8. Added principal-address property to principal resources to allow a vcard to be associated with a principal.
9. XML definition clean-up.

Changes in pre-02

1. Added commentary on SyncML.
2. Changed 'adbk' to 'addressbook'.
3. Support for MKADDRESSBOOK is now a SHOULD.
4. Updated to [RFC4790](#) reference.
5. Removed synchronization report.
6. Removed BNF conventions section as we have no BNF.
7. Reworded and reformatted several items to match the final CalDAV spec.

Daboo  
51]

Expires January 14, 2010

[Page

8. Added section on use of nonstandard properties and parameters (as per CalDAV).
9. Added section of behavior of ETags (as per CalDAV).
10. Generalized the text so that vCard need not be the only format supported by the server (i.e., allow xml version of vCard etc).
11. Renamed supported-addressbook-data to supported-address-data.
12. Renamed valid-addressbook-data to valid-address-data.
13. Now requires "i;unicasemao" collation.

#### Changes in pre-01

1. Fixed various incorrect references and typos.
2. Major changes to sync with latest CalDAV spec behaviors.

#### Author's Address

Cyrus Daboo  
Apple Inc.  
1 Infinite Loop  
Cupertino, CA 95014  
USA

Email: [cyrus@daboo.name](mailto:cyrus@daboo.name)  
URI: <http://www.apple.com/>

