

Network Working Group  
Internet-Draft  
Obsoletes: [2425](#), [2426](#), [4770](#)  
(if approved)  
Updates: [2739](#) (if approved)  
Intended status: Standards Track  
Expires: October 11, 2011

S. Perreault  
Viagenie  
April 9, 2011

**vCard Format Specification**  
**draft-ietf-vcarddav-vcardrev-19**

**Abstract**

This document defines the vCard data format for representing and exchanging a variety of information about individuals and other entities (e.g., formatted and structured name and delivery addresses, email address, multiple telephone numbers, photograph, logo, audio clips, etc.). This document obsoletes RFCs 2425, 2426, 2739, and 4770.

**Status of This Memo**

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 11, 2011.

**Copyright Notice**

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">6</a>
<a href="#">2.</a>	<a href="#">Conventions</a>	<a href="#">6</a>
<a href="#">3.</a>	<a href="#">vCard Format Specification</a>	<a href="#">6</a>
<a href="#">3.1.</a>	<a href="#">Character Set</a>	<a href="#">6</a>
<a href="#">3.2.</a>	<a href="#">Line Delimiting and Folding</a>	<a href="#">6</a>
<a href="#">3.3.</a>	<a href="#">ABNF Format Definition</a>	<a href="#">7</a>
<a href="#">3.4.</a>	<a href="#">Property Value Escaping</a>	<a href="#">9</a>
<a href="#">4.</a>	<a href="#">Property Value Data Types</a>	<a href="#">10</a>
<a href="#">4.1.</a>	<a href="#">TEXT</a>	<a href="#">12</a>
<a href="#">4.2.</a>	<a href="#">URI</a>	<a href="#">12</a>
<a href="#">4.3.</a>	<a href="#">DATE, TIME, DATE-TIME, DATE-AND-OR-TIME, and TIMESTAMP</a>	<a href="#">13</a>
<a href="#">4.3.1.</a>	<a href="#">DATE</a>	<a href="#">13</a>
<a href="#">4.3.2.</a>	<a href="#">TIME</a>	<a href="#">13</a>
<a href="#">4.3.3.</a>	<a href="#">DATE-TIME</a>	<a href="#">14</a>
<a href="#">4.3.4.</a>	<a href="#">DATE-AND-OR-TIME</a>	<a href="#">14</a>
<a href="#">4.3.5.</a>	<a href="#">TIMESTAMP</a>	<a href="#">15</a>
<a href="#">4.4.</a>	<a href="#">BOOLEAN</a>	<a href="#">15</a>
<a href="#">4.5.</a>	<a href="#">INTEGER</a>	<a href="#">15</a>
<a href="#">4.6.</a>	<a href="#">FLOAT</a>	<a href="#">16</a>
<a href="#">4.7.</a>	<a href="#">LANGUAGE-TAG</a>	<a href="#">16</a>
<a href="#">5.</a>	<a href="#">Property Parameters</a>	<a href="#">16</a>
<a href="#">5.1.</a>	<a href="#">LANGUAGE</a>	<a href="#">16</a>
<a href="#">5.2.</a>	<a href="#">VALUE</a>	<a href="#">17</a>
<a href="#">5.3.</a>	<a href="#">PREF</a>	<a href="#">17</a>
<a href="#">5.4.</a>	<a href="#">ALTID</a>	<a href="#">18</a>
<a href="#">5.5.</a>	<a href="#">PID</a>	<a href="#">20</a>
<a href="#">5.6.</a>	<a href="#">TYPE</a>	<a href="#">20</a>
<a href="#">5.7.</a>	<a href="#">MEDIATYPE</a>	<a href="#">21</a>
<a href="#">5.8.</a>	<a href="#">CALSCALE</a>	<a href="#">21</a>

Perreault

Expires October 11, 2011

[Page 2]

5.9.	SORT-AS	21
5.10.	GEO	23
5.11.	TZ	23
6.	vCard Properties	23
6.1.	General Properties	23
6.1.1.	BEGIN	23
6.1.2.	END	24
6.1.3.	SOURCE	24
6.1.4.	KIND	25
6.1.5.	XML	28
6.2.	Identification Properties	28
6.2.1.	FN	29
6.2.2.	N	29
6.2.3.	NICKNAME	30
6.2.4.	PHOTO	30
6.2.5.	BDAY	31
6.2.6.	ANNIVERSARY	32
6.2.7.	GENDER	32
6.3.	Delivery Addressing Properties	33
6.3.1.	ADR	33
6.4.	Communications Properties	34
6.4.1.	TEL	34
6.4.2.	EMAIL	36
6.4.3.	IMPP	37
6.4.4.	LANG	37
6.5.	Geographical Properties	38
6.5.1.	TZ	38
6.5.2.	GEO	39
6.6.	Organizational Properties	39
6.6.1.	TITLE	39
6.6.2.	ROLE	40
6.6.3.	LOGO	41
6.6.4.	ORG	41
6.6.5.	MEMBER	42
6.6.6.	RELATED	43
6.7.	Explanatory Properties	44
6.7.1.	CATEGORIES	44
6.7.2.	NOTE	45
6.7.3.	PRODID	45
6.7.4.	REV	46
6.7.5.	SOUND	46
6.7.6.	UID	47
6.7.7.	CLIENTPIDMAP	47
6.7.8.	URL	48
6.7.9.	VERSION	49
6.8.	Security Properties	49
6.8.1.	KEY	49
6.9.	Calendar Properties	50

Perreault

Expires October 11, 2011

[Page 3]

<a href="#">6.9.1.</a>	FBURL . . . . .	<a href="#">50</a>
<a href="#">6.9.2.</a>	CALADRURI . . . . .	<a href="#">51</a>
<a href="#">6.9.3.</a>	CALURI . . . . .	<a href="#">51</a>
<a href="#">6.10.</a>	Extended Properties and Parameters . . . . .	<a href="#">52</a>
<a href="#">7.</a>	Synchronization . . . . .	<a href="#">52</a>
<a href="#">7.1.</a>	Mechanisms . . . . .	<a href="#">52</a>
<a href="#">7.1.1.</a>	Matching vCard Instances . . . . .	<a href="#">52</a>
<a href="#">7.1.2.</a>	Matching Property Instances . . . . .	<a href="#">53</a>
<a href="#">7.1.3.</a>	PID Matching . . . . .	<a href="#">53</a>
<a href="#">7.2.</a>	Example . . . . .	<a href="#">54</a>
<a href="#">7.2.1.</a>	Creation . . . . .	<a href="#">54</a>
<a href="#">7.2.2.</a>	Initial Sharing . . . . .	<a href="#">54</a>
<a href="#">7.2.3.</a>	Adding and Sharing a Property . . . . .	<a href="#">55</a>
<a href="#">7.2.4.</a>	Simultaneous Editing . . . . .	<a href="#">55</a>
<a href="#">7.2.5.</a>	Global Context Simplification . . . . .	<a href="#">57</a>
<a href="#">8.</a>	Example: Authors' vCards . . . . .	<a href="#">58</a>
<a href="#">9.</a>	Security Considerations . . . . .	<a href="#">58</a>
<a href="#">10.</a>	IANA Considerations . . . . .	<a href="#">59</a>
<a href="#">10.1.</a>	MIME Type Registration . . . . .	<a href="#">59</a>
<a href="#">10.2.</a>	Registering New vCard Elements . . . . .	<a href="#">60</a>
<a href="#">10.2.1.</a>	Registration Procedure . . . . .	<a href="#">61</a>
<a href="#">10.2.2.</a>	Vendor Namespace . . . . .	<a href="#">61</a>
<a href="#">10.2.3.</a>	Registration Template for Properties . . . . .	<a href="#">62</a>
<a href="#">10.2.4.</a>	Registration Template for Parameters . . . . .	<a href="#">63</a>
<a href="#">10.2.5.</a>	Registration Template for Value Data Types . . . . .	<a href="#">63</a>
<a href="#">10.2.6.</a>	Registration Template for Values . . . . .	<a href="#">63</a>
<a href="#">10.3.</a>	Initial vCard Elements Registries . . . . .	<a href="#">64</a>
<a href="#">10.3.1.</a>	Properties Registry . . . . .	<a href="#">64</a>
<a href="#">10.3.2.</a>	Parameters Registry . . . . .	<a href="#">65</a>
<a href="#">10.3.3.</a>	Value Data Types Registry . . . . .	<a href="#">66</a>
<a href="#">10.3.4.</a>	Values Registries . . . . .	<a href="#">66</a>
<a href="#">11.</a>	Acknowledgements . . . . .	<a href="#">69</a>
<a href="#">12.</a>	References . . . . .	<a href="#">69</a>
<a href="#">12.1.</a>	Normative References . . . . .	<a href="#">69</a>
<a href="#">12.2.</a>	Informative References . . . . .	<a href="#">72</a>
<a href="#">Appendix A.</a>	Differences from RFCs 2425 and 2426 . . . . .	<a href="#">73</a>
<a href="#">A.1.</a>	New Structure . . . . .	<a href="#">74</a>
<a href="#">A.2.</a>	Removed Features . . . . .	<a href="#">74</a>
<a href="#">A.3.</a>	New Properties and Parameters . . . . .	<a href="#">74</a>
<a href="#">A.4.</a>	Other Changes . . . . .	<a href="#">75</a>
<a href="#">Appendix B.</a>	Change Log (to be removed by RFC Editor prior to publication) . . . . .	<a href="#">75</a>
<a href="#">B.1.</a>	Changes in -19 . . . . .	<a href="#">75</a>
<a href="#">B.2.</a>	Changes in -18 . . . . .	<a href="#">75</a>
<a href="#">B.3.</a>	Changes in -17 . . . . .	<a href="#">75</a>
<a href="#">B.4.</a>	Changes in -16 . . . . .	<a href="#">76</a>
<a href="#">B.5.</a>	Changes in -15 . . . . .	<a href="#">76</a>
<a href="#">B.6.</a>	Changes in -14 . . . . .	<a href="#">77</a>



<a href="#">B.7.</a>	Changes in -13 . . . . .	<a href="#">78</a>
<a href="#">B.8.</a>	Changes in -12 . . . . .	<a href="#">78</a>
<a href="#">B.9.</a>	Changes in -11 . . . . .	<a href="#">79</a>
<a href="#">B.10.</a>	Changes in -10 . . . . .	<a href="#">80</a>
<a href="#">B.11.</a>	Changes in -09 . . . . .	<a href="#">80</a>
<a href="#">B.12.</a>	Changes in -08 . . . . .	<a href="#">80</a>
<a href="#">B.13.</a>	Changes in -07 . . . . .	<a href="#">81</a>
<a href="#">B.14.</a>	Changes in -06 . . . . .	<a href="#">81</a>
<a href="#">B.15.</a>	Changes in -05 . . . . .	<a href="#">82</a>
<a href="#">B.16.</a>	Changes in -04 . . . . .	<a href="#">82</a>
<a href="#">B.17.</a>	Changes in -03 . . . . .	<a href="#">83</a>
<a href="#">B.18.</a>	Changes in -02 . . . . .	<a href="#">83</a>
<a href="#">B.19.</a>	Changes in -01 . . . . .	<a href="#">84</a>
<a href="#">B.20.</a>	Changes in -00 . . . . .	<a href="#">84</a>





## **1. Introduction**

Electronic address books have become ubiquitous. Their increased presence on portable, connected devices as well as the diversity of platforms exchanging contact data call for a standard. This memo defines the vCard format, which allows the capture and exchange of information normally stored within an address book or directory application.

## **2. Conventions**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

## **3. vCard Format Specification**

The text/vcard MIME content type (hereafter known as "vCard", see [Section 10.1](#)) contains contact information, typically pertaining to a single contact or group of contacts. The content consists of one or more lines in the format given below.

### **3.1. Character Set**

The character set for vCard is UTF-8 as defined in [\[RFC3629\]](#). There is no way to override this. It is invalid to specify a different character set in the "charset" MIME parameter (see [Section 10.1](#)).

### **3.2. Line Delimiting and Folding**

Individual lines within vCard are delimited by the [\[RFC5322\]](#) line break, which is a CRLF sequence (ASCII decimal 13, followed by ASCII decimal 10). Long logical lines of text can be split into a multiple-physical-line representation using the following folding technique. Content lines SHOULD be folded to a maximum width of 75 octets, excluding the line break. Multi-octet characters MUST remain contiguous. The rationale for this folding process can be found in [\[RFC5322\]](#), [Section 2.1.1](#).

A logical line MAY be continued on the next physical line anywhere between two characters by inserting a CRLF immediately followed by a single white space character (space (ASCII decimal 32) or horizontal tab, (ASCII decimal 9)). The folded line MUST contain at least one character. Any sequence of CRLF followed immediately by a single white space character is ignored (removed) when processing the content type. For example the line:



NOTE:This is a long description that exists on a long line.

can be represented as:

NOTE:This is a long description  
that exists on a long line.

It could also be represented as:

NOTE:This is a long descrip  
tion that exists o  
n a long line.

The process of moving from this folded multiple-line representation of a property definition to its single line representation is called unfolding. Unfolding is accomplished by regarding CRLF immediately followed by a white space character (namely HTAB ASCII decimal 9 or SPACE ASCII decimal 32) as equivalent to no characters at all (i.e., the CRLF and single white space character are removed).

Note: It is possible for very simple implementations to generate improperly folded lines in the middle of a UTF-8 multi-octet sequence. For this reason, implementations SHOULD unfold lines in such a way as to properly restore the original sequence.

Note: Unfolding is done differently than in [\[RFC5322\]](#). Unfolding in [\[RFC5322\]](#) only removes the CRLF, not the space following it.

Folding is done after any content encoding of a type value. Unfolding is done before any decoding of a type value in a content line.

### **3.3. ABNF Format Definition**

The following ABNF uses the notation of [\[RFC5234\]](#), which also defines CRLF, WSP, DQUOTE, VCHAR, ALPHA, and DIGIT.

vcard-entity = 1\*vcard

vcard = "BEGIN:VCARD" CRLF  
"VERSION:4.0" CRLF  
1\*contentline  
"END:VCARD" CRLF

; A vCard object MUST include the VERSION and FN properties.  
; VERSION MUST come immediately after BEGIN:VCARD.

contentline = [group "."] name \*("; " param) ":" value CRLF  
; When parsing a content line, folded lines must first



```

; be unfolded according to the unfolding procedure
; described above.
; When generating a content line, lines longer than 75
; characters SHOULD be folded according to the folding
; procedure described above.

```

```

group = 1*(ALPHA / DIGIT / "-")
name  = "SOURCE" / "KIND" / "FN" / "N" / "NICKNAME"
      / "PHOTO" / "BDAY" / "ANNIVERSARY" / "GENDER" / "ADR" / "TEL"
      / "EMAIL" / "IMPP" / "LANG" / "TZ" / "GEO" / "TITLE" / "ROLE"
      / "LOGO" / "ORG" / "MEMBER" / "RELATED" / "CATEGORIES"
      / "NOTE" / "PROPID" / "REV" / "SOUND" / "UID" / "CLIENTPIDMAP"
      / "URL" / "KEY" / "FBURL" / "CALADRURI" / "CALURI" / "XML"
      / iana-token / x-name
; Parsing of the param and value is based on the "name" as
; defined in ABNF sections below.
; Group and name are case-insensitive.

```

```

iana-token = 1*(ALPHA / DIGIT / "-")
; identifier registered with IANA

```

```

x-name = "x-" 1*(ALPHA / DIGIT / "-")
; Names that begin with "x-" or "X-" are
; reserved for experimental use, not intended for released
; products, or for use in bilateral agreements.

```

```

param = language-param / value-param / pref-param / pid-param
      / type-param / geo-parameter / tz-parameter / sort-as-param
      / calscale-param / any-param
; Allowed parameters depend on property name.

```

```

param-value = *SAFE-CHAR / DQUOTE *QSAFE-CHAR DQUOTE

```

```

any-param  = (iana-token / x-name) "=" param-value *(", " param-value)

```

```

NON-ASCII = %x80-FF
; Use is restricted by UTF-8

```

```

QSAFE-CHAR = WSP / "!" / %x23-7E / NON-ASCII
; Any character except CTLs, DQUOTE

```

```

SAFE-CHAR = WSP / "!" / %x23-39 / %x3C-7E / NON-ASCII
; Any character except CTLs, DQUOTE, ";", ":"

```

```

VALUE-CHAR = WSP / VCHAR / NON-ASCII
; Any textual character

```

A line that begins with a white space character is a continuation of



the previous line, as described above. The white space character and immediately preceeding CRLF should be discarded when reconstructing the original line. Note that this line-folding convention differs from that found in [\[RFC5322\]](#), in that the sequence <CRLF><WSP> found anywhere in the content indicates a continued line and should be removed.

Property names and parameter names are case insensitive (e.g., the property name "fn" is the same as "FN" and "Fn"). Parameter values MAY be case sensitive or case insensitive, depending on their definition. Based on experience with vCard 3 interoperability, it is RECOMMENDED that property and parameter names be upper-case on output.

The group construct is used to group related properties together. The group name is a syntactic convention used to indicate that all property names prefaced with the same group name SHOULD be grouped together when displayed by an application. It has no other significance. Implementations that do not understand or support grouping MAY simply strip off any text before a "." to the left of the type name and present the types and values as normal.

Property cardinalities are indicated using the following notation, which is based on ABNF (see [\[RFC5234\]](#), [section 3.6](#)):

+-----+-----+-----+-----+			
Cardinality	Meaning		
+-----+-----+-----+-----+			
1	Exactly one instance per vCard	MUST be present.	
*1	Exactly one instance per vCard	MAY be present.	
1*	One or more instances per vCard	MUST be present.	
*	One or more instances per vCard	MAY be present.	
+-----+-----+-----+-----+			

Properties defined in a vCard instance may have multiple values depending on the property cardinality. The general rule for encoding multi-valued properties is to simply create a new content line for each value (including the property name). However, it should be noted that some value types support encoding multiple values in a single content line by separating the values with a comma ",". This approach has been taken for several of the content types defined below (date, time, integer, float).

### **[3.4.](#) Property Value Escaping**

Some properties may contain one or more values delimited by a COMMA character (ASCII decimal 44). Therefore, a COMMA character in a value MUST be escaped with a BACKSLASH character (ASCII decimal 92),





even for properties that don't allow multiple instances (for consistency).

Some properties (e.g. N and ADR) comprise multiple fields delimited by a SEMI-COLON character (ASCII decimal 59). Therefore, a SEMI-COLON in a field of such a "compound" property MUST be escaped with a BACKSLASH character. SEMI-COLON characters in non-compound properties MAY be escaped. On input, an escaped SEMI-COLON character is never a field separator. An unescaped SEMI-COLON character may be a field separator, depending on the property in which it appears.

Furthermore, some fields of compound properties may contain a list of values delimited by a COMMA character. Therefore, a COMMA character in one of a field's values MUST be escaped with a BACKSLASH character, even for fields that don't allow multiple values (for consistency). Compound properties allowing multiple instances MUST NOT be encoded in a single content line.

Finally, BACKSLASH characters in values MUST be escaped with a BACKSLASH character. NEWLINE (ASCII decimal 10) characters in values MUST be encoded by two characters: a BACKSLASH followed by an 'n' (ASCII decimal 110).

In all other cases, escaping MUST NOT be used.

#### 4. Property Value Data Types

Standard value types are defined below.

```
value = text
      / text-list
      / date-list
      / time-list
      / date-time-list
      / date-and-or-time-list
      / timestamp-list
      / boolean
      / integer-list
      / float-list
      / URI ; from Section 3 of \[RFC3986\]
      / iana-valuespec
; Actual value type depends on property name and VALUE parameter.
```

```
text = *TEXT-CHAR
```

```
TEXT-CHAR = "\\\" / "\",\" / \"\n"
           / <any VALUE-CHAR except , or \>
           ; Backslashes, commas, and newlines must be encoded.
```



```

component = "\\\" / "\",\" / \"\;" / "\\n\" / WSP / NON-ASCII
           / %x21-2B / %x2D-3A / %x3C-5B / %x5D-7E

```

```

list-component = component *(",\" component)

```

```

text-list      = text          *(",\" text)
date-list      = date          *(",\" date)
time-list      = time          *(",\" time)
date-time-list = date-time     *(",\" date-time)
date-and-or-time-list = date-and-or-time *(",\" date-and-or-time)
timestamp-list = timestamp     *(",\" timestamp)
integer-list   = integer       *(",\" integer)
float-list     = float         *(",\" float)

```

```

boolean = "TRUE\" / "FALSE\"

```

```

integer = [sign] 1*DIGIT

```

```

float   = [sign] 1*DIGIT [\".\" 1*DIGIT]

```

```

sign = "+" / "-"

```

```

year   = 4DIGIT ; 0000-9999

```

```

month  = 2DIGIT ; 01-12

```

```

day    = 2DIGIT ; 01-28/29/30/31 depending on month and leap year

```

```

hour   = 2DIGIT ; 00-23

```

```

minute = 2DIGIT ; 00-59

```

```

second = 2DIGIT ; 00-58/59/60 depending on leap second

```

```

zone   = utc-designator / utc-offset

```

```

utc-designator = %x5A ; uppercase "Z"

```

```

date      = year      [month day]
           / year "-" month
           / "--"      month [day]
           / "--"      "-" day

```

```

date-noreduc = year      month day
           / "--"      month day
           / "--"      "-" day

```

```

date-complete = year      month day

```

```

time      = hour [minute [second]] [zone]
           / "-" minute [second] [zone]
           / "-" "-" second [zone]

```

```

time-notrunc = hour [minute [second]] [zone]

```

```

time-complete = hour minute second [zone]

```

```

time-designator = %x54 ; uppercase "T"

```

```

date-time = date-noreduc time-designator time-notrunc

```

```

timestamp = date-complete time-designator time-complete

```

```

date-and-or-time = date-time / date / time-designator time

```



utc-offset = sign hour [minute]

Language-Tag = <Language-Tag, defined in [\[RFC5646\]](#), [Section 2.1](#)>

iana-valuespec = <value-spec, see [Section 12](#)>  
; a publicly-defined valuetype format, registered  
; with IANA, as defined in [section 12](#) of this  
; document

#### [4.1.](#) TEXT

"text": The "text" value type should be used to identify values that contain human-readable text. As for the language, it is controlled by the LANGUAGE property parameter defined in [Section 5.1](#).

Examples for "text":

```
this is a text value
this is one value,this is another
this is a single value\, with a comma encoded
```

A formatted text line break in a text value type MUST be represented as the character sequence backslash (ASCII decimal 92) followed by a Latin small letter n (ASCII decimal 110) or a Latin capital letter N (ASCII decimal 78), that is "\n" or "\N".

For example a multiple line NOTE value of:

```
Mythical Manager
Hyjinx Software Division
BabsCo, Inc.
```

could be represented as:

```
NOTE:Mythical Manager\nHyjinx Software Division\n
      BabsCo\, Inc.\n
```

demonstrating the \n literal formatted line break technique, the CRLF-followed-by-space line folding technique, and the backslash escape technique.

#### [4.2.](#) URI

"uri": The "uri" value type should be used to identify values that are referenced by a URI (including a Content-ID URI), instead of encoded in-line. These value references might be used if the value is too large, or otherwise undesirable to include directly. The format for the URI is as defined in [Section 3 of \[RFC3986\]](#). Note



that the value of a property of type "uri" is what the URI points to, not the URI itself.

Examples for "uri":

```
http://www.example.com/my/picture.jpg
ldap://ldap.example.com/cn=babs%20jensen
```

### **4.3. DATE, TIME, DATE-TIME, DATE-AND-OR-TIME, and TIMESTAMP**

"date", "time", "date-time", and "timestamp": Each of these value types is based on the definitions in [[ISO.8601.2004](#)] standard. Multiple such values can be specified using the comma-separated notation.

Only the basic format is supported.

#### **4.3.1. DATE**

A calendar date as specified in [[ISO.8601.2004](#)] [section 4.1.2](#).

Reduced accuracy, as specified in [[ISO.8601.2004](#)] sections [4.1.2.3](#) a) and b), but not c), is permitted.

Expanded representation, as specified in [[ISO.8601.2004](#)] [section 4.1.4](#), is forbidden.

Truncated representation, as specified in [[ISO.8601.2000](#)] sections 5.2.1.3 d), e), and f), is permitted.

Examples for "date":

```
19850412
1985-04
1985
--0412
---12
```

Note the use of YYYY-MM in the second example above. YYYYMM is disallowed to prevent confusion with YYMMDD. Note also that YYYY-MM-DD is disallowed since we are using the basic format instead of the extended format.

#### **4.3.2. TIME**

A time of day as specified in [[ISO.8601.2004](#)] [section 4.2](#).

Reduced accuracy, as specified in [[ISO.8601.2004](#)] [section 4.2.2.3](#), is





permitted.

Representation with decimal fraction, as specified in [[ISO.8601.2004](#)] [section 4.2.2.4](#), is forbidden.

The midnight hour is always represented by 00, never 24 (see [[ISO.8601.2004](#)] [section 4.2.3](#)).

Truncated representation, as specified in [[ISO.8601.2000](#)] [sections 5.3.1.4 a\), b\), and c\)](#), is permitted.

Examples for "time":

```
102200
1022
10
-2200
--00
102200Z
102200-0800
```

#### **[4.3.3.](#) DATE-TIME**

A date and time of day combination as specified in [[ISO.8601.2004](#)] [section 4.3](#).

Truncation of the date part, as specified in [[ISO.8601.2000](#)] [section 5.4.2 c\)](#), is permitted.

Examples for "date-time":

```
19961022T140000
--1022T1400
---22T14
```

#### **[4.3.4.](#) DATE-AND-OR-TIME**

Either a DATE-TIME, a DATE, or a TIME value. To allow unambiguous interpretation, a standalone TIME value is always preceded by a "T".



Examples for "date-and-or-time":

```
19961022T140000
--1022T1400
---22T14
19850412
1985-04
1985
--0412
---12
T102200
T1022
T10
T-2200
T--00
T102200Z
T102200-0800
```

#### **4.3.5. TIMESTAMP**

A complete date and time of day combination as specified in [\[ISO.8601.2004\]](#) [section 4.3.2](#).

Examples for "timestamp":

```
19961022T140000
19961022T140000Z
19961022T140000-05
19961022T140000-0500
```

#### **4.4. BOOLEAN**

"boolean": The "boolean" value type is used to express boolean values. These values are case insensitive.

Examples:

```
TRUE
false
True
```

#### **4.5. INTEGER**

"integer": The "integer" value type is used to express signed integers in decimal format. If sign is not specified, the value is assumed positive "+". Multiple "integer" values can be specified using the comma-separated notation.



Examples:

```
1234567890
-1234556790
+1234556790,432109876
```

#### **4.6. FLOAT**

"float": The "float" value type is used to express real numbers. If sign is not specified, the value is assumed positive "+". Multiple "float" values can be specified using the comma-separated notation.

Note: Scientific notation is disallowed. Implementors wishing to use their favorite language's %f formatting should be careful.

Examples:

```
20.30
1000000.0000001
1.333,3.14
```

#### **4.7. LANGUAGE-TAG**

"language-tag": A single language tag, as defined in [[RFC5646](#)].

### **5. Property Parameters**

A property can have attributes associated with it. These "property parameters" contain meta-information about the property or the property value. In some cases the property parameter can be multi-valued in which case the property parameter value elements are separated by a COMMA (US-ASCII decimal 44).

Property parameter value elements that contain the COLON (US-ASCII decimal 58), SEMICOLON (US-ASCII decimal 59) or COMMA (US-ASCII decimal 44) character separators MUST be specified as quoted-string text values. Property parameter values MUST NOT contain the DQUOTE (US-ASCII decimal 34) character. The DQUOTE character is used as a delimiter for parameter values that contain restricted characters or URI text.

Applications MUST ignore x-param and iana-param values they don't recognize.

#### **5.1. LANGUAGE**

The LANGUAGE property parameter is used to identify data in multiple languages. There is no concept of "default" language, except as



specified by any "Content-Language" MIME header parameter that is present [[RFC3282](#)]. The value of the LANGUAGE property parameter is a language tag as defined in [Section 2 of \[RFC5646\]](#).

Examples:

```
ROLE;LANGUAGE=tr:hoca
```

ABNF:

```
language-param = "LANGUAGE=" Language-Tag
                  ; Language-Tag is defined in section 2.1 of RFC 5646
```

## [5.2.](#) VALUE

The VALUE parameter is optional, used to identify the value type (data type) and format of the value. The use of these predefined formats is encouraged even if the value parameter is not explicitly used. By defining a standard set of value types and their formats, existing parsing and processing code can be leveraged. The predefined data type values MUST NOT be repeated in COMMA separated value lists except within the N, NICKNAME, ADR, and CATEGORIES properties.

ABNF:

```
value-param = "VALUE=" value-type
```

```
value-type = "text"
             / "uri"
             / "date"
             / "time"
             / "date-time"
             / "timestamp"
             / "boolean"
             / "integer"
             / "float"
             / "language-tag"
             / "utc-offset"
             / iana-token ; registered as described in section 12
             / x-name
```

## [5.3.](#) PREF

The PREF parameter is optional and is used to indicate that the corresponding instance of a property is preferred by the vCard author. Its value MUST be an integer between 1 and 100 that quantifies the level of preference. Lower values correspond to a





higher level of preference, 1 being most preferred.

When the parameter is absent, the default MUST be to interpret the property instance as being least preferred.

Note that the value of this parameter is to be interpreted only in relation to values assigned to other instances of the same property in the same vCard. A given value, or the absence of a value, MUST NOT be interpreted on its own.

This parameter MAY be applied to any property that allows multiple instances.

ABNF:

```
pref-param = "PREF=" (1*2DIGIT / "100")  
              ; An integer between 1 and 100.
```

#### **5.4. ALTID**

The ALTID parameter is used to "tag" property instances as being alternative representations of the same logical property. For example, translations of a property in multiple languages generates multiple property instances having different LANGUAGE ([Section 5.1](#)) parameter which are tagged with the same ALTID value.

This parameter's value is treated as an opaque string. Its sole purpose is to be compared for equality against other ALTID parameter values.

Two property instances are considered alternative representations of the same logical property if and only if their names as well as the value of their ALTID parameters are identical. Property instances without the ALTID parameter MUST NOT be considered an alternative representation of any other property instance. Values for the ALTID parameter are not globally unique: they MAY be reused for different property names.

Property instances having the same ALTID parameter value count as 1 toward cardinality. Therefore, since N ([Section 6.2.2](#)) has cardinality \*1 and TITLE ([Section 6.6.1](#)) has cardinality \*, these three examples would be legal:



```
N;ALTID=1;LANGUAGE=jp:<U+5C71><U+7530>;<U+592A><U+90CE>;;  
N;ALTID=1;LANGUAGE=en:Yamada;Taro;;;  
(<U+XXXX> denotes a UTF8-encoded Unicode character.)
```

```
TITLE;ALTID=1;LANGUAGE=fr:Patron  
TITLE;ALTID=1;LANGUAGE=en:Boss
```

```
TITLE;ALTID=1;LANGUAGE=fr:Patron  
TITLE;ALTID=1;LANGUAGE=en:Boss  
TITLE;ALTID=2;LANGUAGE=en:Chief vCard Evangelist
```

while this one would not:

```
N;ALTID=1;LANGUAGE=jp:<U+5C71><U+7530>;<U+592A><U+90CE>;;  
N:Yamada;Taro;;;  
(Two instances of the N property.)
```

and these three would be legal but questionable:

```
TITLE;ALTID=1;LANGUAGE=fr:Patron  
TITLE;ALTID=2;LANGUAGE=en:Boss  
(Should probably have the same ALTID value.)
```

```
TITLE;ALTID=1;LANGUAGE=fr:Patron  
TITLE:LANGUAGE=en:Boss  
(Second line should probably have ALTID=1.)
```

```
N;ALTID=1;LANGUAGE=jp:<U+5C71><U+7530>;<U+592A><U+90CE>;;  
N;ALTID=1;LANGUAGE=en:Yamada;Taro;;;  
N;ALTID=1;LANGUAGE=en:Smith;John;;;  
(The last line should probably have ALTID=2. But that would be  
illegal because N has cardinality *1.)
```

The ALTID property MAY also be used in may contexts other than with the LANGUAGE parameter. Here's an example with two representations of the same photo in different file formats:

```
PHOTO;ALTID=1:data:image/jpeg;base64,...  
PHOTO;ALTID=1:data:image/jp2;base64,...
```

ABNF:

```
altid-param = "ALTID=" param-value
```



### 5.5. PID

The PID parameter is used to identify a specific property among multiple instances. It plays a role analogous to the UID property ([Section 6.7.6](#)) on a per-property instead of per-vCard basis. It MAY appear more than once in a given property. It MUST NOT appear on properties that may have only one instance per vCard. Its value is either a single small positive integer or a pair of small positive integers separated by a dot. Multiple values may be encoded in a single PID parameter by separating the values with a comma ",". See [Section 7](#) for more details on its usage.

ABNF:

```
pid-param = "PID=" pid-value *("," pid-value)
pid-value = 1*DIGIT [ "." 1*DIGIT ]
```

### 5.6. TYPE

The TYPE parameter has multiple, different uses. In general, it is a way of specifying class characteristics of the associated property. Most of the time, its value is a comma-separated subset of a pre-defined enumeration. In this document, the following properties make use of this parameter: FN, NICKNAME, PHOTO, ADR, TEL, EMAIL, IMPP, LANG, TZ, GEO, TITLE, ROLE, LOGO, ORG, RELATED, CATEGORIES, NOTE, SOUND, URL, KEY, FBURL, CALADRURI, and CALURI. The TYPE parameter MUST NOT be applied on other properties defined in this document.

The "work" and "home" values act like tags. The "work" value implies that the property is related to an individual's work place, while the "home" value implies that the property is related to an individual's personal life. When neither "work" nor "home" is present, it is implied that the property is related to both an individual's work place and personal life in the case that the KIND property's value is "individual", or to none in other cases.

ABNF:

```
type-param = "TYPE=" type-value *("," type-value)

type-value = "work" / "home" / type-param-tel
            / type-param-related / iana-token / x-name
            ; This is further defined in individual property sections.
```



### 5.7. MEDIATYPE

The MEDIATYPE parameter is used with properties whose value is a URI. Its use is OPTIONAL. It provides a hint to the vCard consumer application about the media type of the resource identified by the URI. Some URI schemes do not need this parameter. For example, the "data" scheme allows the media type to be explicitly indicated as part of the URI [RFC2397]. Another scheme, "http", provides the media type as part of the URI resolution process, with the Content-Type HTTP header [RFC2616]. The MEDIATYPE parameter is intended to be used with URI schemes that do not provide such functionality (e.g. "ftp" [RFC1738]).

ABNF:

```
mediatype-param = "MEDIATYPE=" mediatype
mediatype = type-name "/" subtype-name *( ";" attribute "=" value )
; "attribute" and "value" are from [RFC2045]
; "type-name" and "subtype-name" are from [RFC4288]
```

### 5.8. CALSCALE

The CALSCALE parameter is identical to the CALSCALE property in iCalendar (see [RFC5545], section 3.7.1). It is used to define the calendar system in which a date or date-time value is expressed. The only value specified by iCalendar is "gregorian", which stands for the Gregorian system. It is the default when the parameter is absent. Additional values may be defined in extension documents and registered from IANA (see Section 10.3.4). A vCard implementation MUST ignore properties with a CALSCALE parameter value that it does not understand.

ABNF:

```
calscale-param = "CALSCALE=" calscale-value

calscale-value = "gregorian" / iana-token / x-name
```

### 5.9. SORT-AS

The "sort-as" parameter is used to specify the string to be used for national-language-specific sorting. Without this information, sorting algorithms could incorrectly sort this vCard within a sequence of sorted vCards. When this property is present in a vCard, then the given strings are used for sorting the vCard.

This parameter's value is a comma-separated list which MUST have as many or less elements as the corresponding property value has





components.

ABNF:

```
sort-as-param = "SORT-AS=" sort-as-value
```

```
sort-as-value = param-value *("," param-value)
```

Examples: For the case of surname and given name sorting, the following examples define common sort string usage with the N property.

```
FN:Rene van der Harten  
N;SORT-AS="Harten,Rene":van der Harten;Rene,J.;Sir;R.D.O.N.
```

```
FN:Robert Pau Shou Chang  
N;SORT-AS="Pau Shou Chang,Robert":Shou Chang;Robert,Pau;;
```

```
FN:Osamu Koura  
N;SORT-AS="Koura,Osamu":Koura;Osamu;;
```

```
FN:Oscar del Pozo  
N;SORT-AS="Pozo,Oscar":del Pozo Triscon;Oscar;;
```

```
FN:Chistine d'Aboville  
N;SORT-AS="Aboville,Christine":d'Aboville;Christine;;
```

```
FN:H. James de Mann  
N;SORT-AS="Mann,James":de Mann;Henry,James;;
```

If sorted by surname the results would be:

```
Christine d'Aboville  
Rene van der Harten  
Osamu Koura  
H. James de Mann  
Robert Pau Shou Chang  
Oscar del Pozo
```

If sorted by given name the results would be:

```
Christine d'Aboville  
H. James de Mann  
Osamu Koura  
Oscar del Pozo  
Rene van der Harten  
Robert Pau Shou Chang
```



### [5.10.](#) GEO

The GEO parameter can be used to indicate global positioning information that is specific to an address. Its value is the same as that of the GEO property (see [Section 6.5.2](#)).

ABNF:

```
geo-parameter = "GEO=" DQUOTE URI DQUOTE
```

### [5.11.](#) TZ

The TZ parameter can be used to indicate time zone information that is specific to an address. Its value is the same as that of the TZ property.

ABNF:

```
tz-parameter = "TZ=" (param-value / DQUOTE URI DQUOTE)
```

## [6.](#) vCard Properties

What follows is an enumeration of the standard vCard properties.

### [6.1.](#) General Properties

#### [6.1.1.](#) BEGIN

Purpose: To denote the beginning of a syntactic entity within a text/vcard content-type.

Value type: text

Cardinality: 1

Special notes: The content entity MUST begin with the BEGIN property with a value of "VCARD". The value is case-insensitive.

The BEGIN property is used in conjunction with the END property to delimit an entity containing a related set of properties within an text/vcard content-type. This construct can be used instead of or in addition to wrapping separate sets of information inside additional MIME headers. It is provided for applications that wish to define content that can contain multiple entities within the same text/vcard content-type or to define content that can be identifiable outside of a MIME environment.



ABNF:

```
BEGIN-param = 0<nothing> ; no parameter allowed  
BEGIN-value = "VCARD"
```

Example:

```
BEGIN:VCARD
```

#### [6.1.2.](#) **END**

Purpose: To denote the end of a syntactic entity within a text/vcard content-type.

Value type: text

Cardinality: 1

Special notes: The content entity MUST end with the END type with a value of "VCARD". The value is case-insensitive.

The END property is used in conjunction with the BEGIN property to delimit an entity containing a related set of properties within an text/vcard content-type. This construct can be used instead of or in addition to wrapping separate sets of information inside additional MIME headers. It is provided for applications that wish to define content that can contain multiple entities within the same text/vcard content-type or to define content that can be identifiable outside of a MIME environment.

ABNF:

```
END-param = 0<nothing> ; no parameter allowed  
END-value = "VCARD"
```

Example:

```
END:VCARD
```

#### [6.1.3.](#) **SOURCE**

Purpose: To identify the source of directory information contained in the content type.

Value type: uri



Cardinality: \*

Special notes: The SOURCE property is used to provide the means by which applications knowledgeable in the given directory service protocol can obtain additional or more up-to-date information from the directory service. It contains a URI as defined in [\[RFC3986\]](#) and/or other information referencing the vCard to which the information pertains. When directory information is available from more than one source, the sending entity can pick what it considers to be the best source, or multiple SOURCE properties can be included.

ABNF:

```
SOURCE-param = "VALUE=uri" / pid-param / pref-param / altid-param
               / mediatype-param / any-param
SOURCE-value  = URI
```

Examples:

```
SOURCE:ldap://ldap.example.com/cn=Babs%20Jensen,%20o=Babsco,%20c=US
```

```
SOURCE:http://directory.example.com/addressbooks/jdoe/
Jean%20Dupont.vcf
```

#### [6.1.4.](#) **KIND**

Purpose: To specify the kind of object the vCard represents.

Value type: A single text value.

Cardinality: \*1

Special notes: The value may be one of the following:

"individual" for a vCard representing a single person or entity.  
This is the default kind of vCard.

"group" for a vCard representing a group of persons or entities.  
The group's member entities can be other vCards or other types of entities, such as email addresses or web sites. A group vCard will usually contain MEMBER properties to specify the members of the group, but it is not required to. A group vCard without MEMBER properties can be considered an abstract grouping, or one whose members are known empirically (perhaps "IETF Participants" or "Republican U.S. Senators").





All properties in a group vCard apply to the group as a whole, and not to any particular MEMBER. For example, an EMAIL property might specify the address of a mailing list associated with the group, and an IMPP property might refer to a group chat room.

"org" for a vCard representing an organization. An organization vCard will not (in fact, MUST NOT) contain MEMBER properties, and so these are something of a cross between "individual" and "group". An organization is a single entity, but not a person. It might represent a business or government, a department or division within a business or government, a club, an association, or the like.

All properties in an organization vCard apply to the organization as a whole, as is the case with a group vCard. For example, an EMAIL property might specify the address of a contact point for the organization.

"location" for a named geographical place. A location vCard will usually contain a GEO property, but it is not required to. A location vCard without a GEO property can be considered an abstract location, or one whose definition is known empirically (perhaps "New England" or "The Seashore").

All properties in a location vCard apply to the location itself, and not with any entity that might exist at that location. For example, in a vCard for an office building, an ADR property might give the mailing address for the building, and a TEL property might specify the telephone number of the receptionist.

An x-name. vCards MAY include private or experimental values for KIND. Remember that x-name values are not intended for general use, and are unlikely to interoperate.

An iana-token. Additional values may be registered with IANA (see [Section 10.3.4](#)). A new value's specification document MUST specify which properties make sense for that new kind of vCard and which do not.

Implementations MUST support the specific string values defined above. If this property is absent, "individual" MUST be assumed as the default. If this property is present but the implementation does not understand its value (the value is an x-name or iana-token that the implementation does not support), the implementation SHOULD act in a neutral way, which usually means treating the vCard as though its kind were "individual".



The presence of MEMBER properties MAY, however, be taken as an indication that the unknown kind is an extension of "group".

Clients often need to visually distinguish contacts based on what they represent, and the KIND property provides a direct way for them to do so. For example, when displaying contacts in a list, an icon could be displayed next to each one, using distinctive icons for the different kinds; a client might use an outline of a single person to represent an "individual", an outline of multiple people to represent a "group", and so on. Alternatively, or in addition, a client might choose to segregate different kinds of vCards to different panes, tabs, or selections in the user interface.

Some clients might also make functional distinctions among the kinds, ignoring "location" vCards for some purposes and considering only "location" vCards for others.

When designing those sorts of visual and functional distinctions, client implementations have to decide how to fit unsupported kinds into the scheme. What icon is used for them? The one for "individual"? A unique one, such as an icon of a question-mark? Which tab do they go into? It is beyond the scope of this specification to answer these questions, but these are things implementors need to consider.

ABNF:

```
KIND-param = "VALUE=text" / any-param
KIND-value = "individual" / "group" / "org" / "location"
             / iana-token / x-name
```

Example:

This represents someone named Jane Doe working in the marketing department of the North American division of ABC Inc.

```
BEGIN:VCARD
VERSION:4.0
KIND:individual
FN:Jane Doe
ORG:ABC\, Inc.;North American Division;Marketing
END:VCARD
```



This represents the department itself, commonly known as ABC Marketing.

```
BEGIN:VCARD
VERSION:4.0
KIND:org
FN:ABC Marketing
ORG:ABC\, Inc.;North American Division;Marketing
END:VCARD
```

#### [6.1.5.](#) XML

Purpose: To include extended XML-encoded vCard data in a plain vCard.

Value type: A single text value.

Cardinality: \*

Special notes: The content of this property is a single XML 1.0 [[W3C.REC-xml-20081126](#)] element whose namespace MUST be explicitly specified using the xmlns attribute and MUST NOT be the vCard 4 namespace ("urn:ietf:params:xml:ns:vcard-4.0"). (This implies that it cannot duplicate a standard vCard property.) The element is to be interpreted as if it was contained in a <vcard> element, as defined in [[I-D.ietf-vcarddav-vcardxml](#)].

The fragment is subject to normal line folding and escaping, i.e. replace all backslashes with "\\ ", then replace all newlines with "\\n", then fold long lines.

Support for this property is OPTIONAL, but implementations of this specification MUST preserve instances of this property when propagating vCards.

See [[I-D.ietf-vcarddav-vcardxml](#)] for more information on the intended use of this property.

ABNF:

```
XML-param = "VALUE=text" / altid-param
XML-value = text
```

## [6.2.](#) Identification Properties

These types are used to capture information associated with the identification and naming of the entity associated with the vCard.



### [6.2.1.](#) FN

Purpose: To specify the formatted text corresponding to the name of the object the vCard represents.

Value type: A single text value.

Cardinality: 1\*

Special notes: This property is based on the semantics of the X.520 Common Name attribute. The property **MUST** be present in the vCard object.

ABNF:

```
FN-param = "VALUE=text" / type-param / language-param / altid-param  
          / pid-param / pref-param / any-param  
FN-value = text
```

Example:

```
FN:Mr. John Q. Public\, Esq.
```

### [6.2.2.](#) N

Purpose: To specify the components of the name of the object the vCard represents.

Value type: A single structured text value. Each component can have multiple values.

Cardinality: \*1

Special note: The structured property value corresponds, in sequence, to the Family Names (also known as surnames), Given Names, Additional Names, Honorific Prefixes, and Honorific Suffixes. The text components are separated by the SEMI-COLON character (ASCII decimal 59). Individual text components can include multiple text values separated by the COMMA character (ASCII decimal 44). This property is based on the semantics of the X.520 individual name attributes. The property **SHOULD** be present in the vCard object when the name of the object the vCard represents follows the X.520 model.

The SORT-AS parameter **MAY** be applied to this property.





ABNF:

```
N-param = "VALUE=text" / sort-as-param / language-param
          / altid-param / any-param
N-value = list-component 4(";" list-component)
```

Examples:

```
N:Public;John;Quinlan;Mr.;Esq.
```

```
N:Stevenson;John;Philip,Paul;Dr.;Jr.,M.D.,A.C.P.
```

### **6.2.3. NICKNAME**

Purpose: To specify the text corresponding to the nickname of the object the vCard represents.

Value type: One or more text values separated by a COMMA character (ASCII decimal 44).

Cardinality: \*

Special note: The nickname is the descriptive name given instead of or in addition to the one belonging to a the object the vCard represents. It can also be used to specify a familiar form of a proper name specified by the FN or N properties.

ABNF:

```
NICKNAME-param = "VALUE=text" / type-param / language-param
                  / altid-param / pid-param / pref-param / any-param
NICKNAME-value = text-list
```

Examples:

```
NICKNAME:Robbie
```

```
NICKNAME:Jim,Jimmie
```

```
NICKNAME;TYPE=work:Boss
```

### **6.2.4. PHOTO**

Purpose: To specify an image or photograph information that annotates some aspect of the object the vCard represents.



Value type: A single URI.

Cardinality: \*

ABNF:

```
PHOTO-param = "VALUE=uri" / altid-param / type-param
              / mediatype-param
PHOTO-value = URI
```

Examples:

```
PHOTO:http://www.example.com/pub/photos/jqpublic.gif
```

```
PHOTO:
AQEEBQAwdzELMAKGA1UEBhMCVVMxLDAqBgNVBAoTI05ldHNjYXB1IENvbW11bm
ljYXRpb25zIENvcnBvcnF0aW9uMRwwGgYDVQLExNjbWZvcmlhdGlvbiBTeXN0
<...remainder of base64-encoded data...>
```

#### [6.2.5.](#) BDAY

Purpose: To specify the birth date of the object the vCard represents.

Value type: The default is a single date-and-or-time value. It can also be reset to a single text value.

Cardinality: \*1

ABNF:

```
BDAY-param = BDAY-param-date / BDAY-param-text
BDAY-value = date-and-or-time / text
            ; Value and parameter MUST match.
```

```
BDAY-param-date = "VALUE=date-and-or-time"
BDAY-param-text = "VALUE=text" / language-param
```

```
BDAY-param =/ altid-param / calscale-param / any-param
            ; calscale-param can only be present when BDAY-value is
            ; date-and-or-time and actually contains a date or date-time.
```

Examples:

```
BDAY:19960415
BDAY:--0415
BDAY;19531015T231000Z
BDAY;VALUE=text:circa 1800
```



#### **6.2.6. ANNIVERSARY**

Purpose: The date of marriage, or equivalent, of the object the vCard represents.

Value type: The default is a single date-and-or-time value. It can also be reset to a single text value.

Cardinality: \*1

ABNF:

```
ANNIVERSARY-param = "VALUE=" ("date-and-or-time" / "text")
```

```
ANNIVERSARY-value = date-and-or-time / text
```

```
; Value and parameter MUST match.
```

```
ANNIVERSARY-param =/ altid-param / calscale-param / any-param
```

```
; calscale-param can only be present when ANNIVERSARY-value is
```

```
; date-and-or-time and actually contains a date or date-time.
```

Examples:

```
ANNIVERSARY:19960415
```

#### **6.2.7. GENDER**

Purpose: To specify the components of the sex and gender identity of the object the vCard represents.

Value type: A single structured value with two components. Each component has a single text value.

Cardinality: \*1

Special notes: The components correspond, in sequence, to the sex (biological), and gender identity. Each component is optional.

Sex component: A single letter. M stands for "male", F stands for "female", O stands for "other", N stands for "none or not applicable", U stands for "unknown".

Gender identity component: Free-form text.

ABNF:

```
GENDER-param = "VALUE=text" / any-param
```

```
GENDER-value = sex [";" text]
```



sex = "" / "M" / "F" / "O" / "N" / "U"

Examples:

GENDER:M  
GENDER:F  
GENDER:M;Fellow  
GENDER:F;Bird  
GENDER:O;intersex  
GENDER;;queer

### **6.3. Delivery Addressing Properties**

These types are concerned with information related to the delivery addressing or label for the vCard object.

#### **6.3.1. ADR**

Purpose: To specify the components of the delivery address for the vCard object.

Value type: A single structured text value, separated by the SEMI-COLON character (ASCII decimal 59).

Cardinality: \*

Special notes: The structured type value consists of a sequence of address components. The component values MUST be specified in their corresponding position. The structured type value corresponds, in sequence, to the post office box; the extended address (e.g. apartment or suite number); the street address; the locality (e.g., city); the region (e.g., state or province); the postal code; the country name (full name in the language specified in [Section 5.1](#)). When a component value is missing, the associated component separator MUST still be specified.

Experience with vCard 3 has shown that the first two components (post office box and extended address) are plagued with many interoperability issues. To ensure maximal interoperability, their values SHOULD be empty.

The text components are separated by the SEMI-COLON character (ASCII decimal 59). Where it makes semantic sense, individual text components can include multiple text values (e.g., a "street" component with multiple lines) separated by the COMMA character (ASCII decimal 44).





The property can include the "PREF" parameter to indicate the preferred delivery address when more than one address is specified.

The GEO and TZ parameters MAY be used with this property.

The property can also include a "LABEL" parameter to present a delivery delivery address label for the address. Its value is a plain-text string representing the formatted address. Newlines are encoded as \n, as they are for property values.

ABNF:

```
label-param = "LABEL=" param-value

ADR-param = "VALUE=text" / label-param / language-param
           / geo-parameter / tz-parameter / altid-param / pid-param
           / pref-param / type-param / any-param
ADR-value = ADR-component-pobox ";" ADR-component-ext ";"
           ADR-component-street ";" ADR-component-locality ";"
           ADR-component-region ";" ADR-component-code ";"
           ADR-component-country
ADR-component-pobox    = list-component
ADR-component-ext      = list-component
ADR-component-street   = list-component
ADR-component-locality = list-component
ADR-component-region   = list-component
ADR-component-code     = list-component
ADR-component-country  = list-component
```

Example: In this example the post office box and the extended address are absent.

```
ADR;GEO="geo:12.3457,78.910";LABEL="Mr. John Q. Public, Esq.\n
Mail Drop: TNE QB\n123 Main Street\nAny Town, CA 91921-1234\n
U.S.A.";;;123 Main Street;Any Town;CA;91921-1234;U.S.A.
```

## **6.4. Communications Properties**

These properties describe information about how to communicate with the object the vCard represents.

### **6.4.1. TEL**



**Purpose:** To specify the telephone number for telephony communication with the object the vCard represents.

**Value type:** By default it is a single free-form text value (for backward compatibility with vCard 3), but it SHOULD be reset to a URI value. It is expected that the URI scheme will be "tel", as specified in [[RFC3966](#)], but other schemes MAY be used.

**Cardinality:** \*

**Special notes:** This property is based on the X.520 Telephone Number attribute.

The property can include the "PREF" parameter to indicate a preferred-use telephone number.

The property can include the parameter "TYPE" to specify intended use for the telephone number. The predefined values for the TYPE parameter are:

Value	Description
text	Indicates that the telephone number supports text messages (SMS).
voice	Indicates a voice telephone number.
fax	Indicates a facsimile telephone number.
cell	Indicates a cellular or mobile telephone number.
video	Indicates a video conferencing telephone number.
pager	Indicates a paging device telephone number.
textphone	Indicates a telecommunication device for people with hearing or speech difficulties..

The default type is "voice". These type parameter values can be specified as a parameter list (e.g., TYPE=text;TYPE=voice) or as a value list (e.g., TYPE="text,voice"). The default can be overridden to another set of values by specifying one or more alternate values. For example, the default TYPE of "voice" can be reset to a VOICE and FAX telephone number by the value list TYPE="voice,fax".

If this property's value is a URI that can also be used for instant messaging, the IMPP ([Section 6.4.3](#)) property SHOULD be used in addition to this property.



ABNF:

```
TEL-param = TEL-text-param / TEL-uri-param
TEL-value = TEL-text-value / TEL-uri-value
           ; Value and parameter MUST match

TEL-text-param = "VALUE=text"
TEL-text-value = text

TEL-uri-param = "VALUE=uri" / mediatype-param
TEL-uri-value = URI

TEL-param =/ type-param / pid-param / pref-param / altid-param
           / any-param

type-param-tel = "text" / "voice" / "fax" / "cell" / "video"
                / "pager" / "textphone" / iana-token / x-name
                ; type-param-tel MUST NOT be used with a property other than TEL.
```

Example:

```
TEL;VALUE=uri;PREF=1;TYPE="voice,home":tel:+1-555-555-5555;ext=5555
TEL;VALUE=uri;TYPE=home:tel:+33-01-23-45-67
```

#### **6.4.2. EMAIL**

Purpose: To specify the electronic mail address for communication with the object the vCard represents.

Value type: A single text value.

Cardinality: \*

Special notes: The property can include the "PREF" parameter to indicate a preferred-use email address when more than one is specified.

Even though the value is free-form UTF-8 text, it is likely to be interpreted by an MUA as an "addr-spec", as defined in [\[RFC5322\]](#), [section 3.4.1](#). Readers should also be aware of the current work toward internationalized email addresses [\[I-D.ietf-eai-rfc5335bis\]](#).

ABNF:

```
EMAIL-param = "VALUE=text" / pid-param / pref-param / type-param
              / altid-param / any-param
EMAIL-value = text
```



Example:

```
EMAIL;TYPE=work:jpublic@xyz.example.com
```

```
EMAIL;PREF=1:jane_doe@example.com
```

#### **6.4.3. IMPP**

Purpose: To specify the URI for instant messaging and presence protocol communications with the object the vCard represents.

Value type: A single URI.

Cardinality: \*

Special notes: The property may include the "PREF" parameter to indicate that this is a preferred address and has the same semantics as the "PREF" parameter in a TEL property.

If this property's value is a URI that can be used for voice and/or video, the TEL property ([Section 6.4.1](#)) SHOULD be used in addition to this property.

This property is adapted from [[RFC4770](#)], which is made obsolete by this document.

ABNF:

```
IMPP-param = "VALUE=uri" / pid-param / pref-param / type-param  
            / mediatype-param / altid-param / any-param  
IMPP-value = URI
```

Example:

```
IMPP;PREF=1:xmpp:alice@example.com
```

#### **6.4.4. LANG**

Purpose: To specify the language(s) that may be used for contacting the entity associated with the vCard.

Value type: A single language-tag value.

Cardinality: \*





ABNF:

```
LANG-param = "VALUE=language-tag" / pid-param / pref-param
            / altid-param / type-param / any-param
LANG-value = Language-Tag
```

Example:

```
LANG;TYPE=work;PREF=1:en
LANG;TYPE=work;PREF=2:fr
LANG;TYPE=home:fr
```

## **6.5. Geographical Properties**

These properties are concerned with information associated with geographical positions or regions associated with the object the vCard represents.

### **6.5.1. TZ**

Purpose: To specify information related to the time zone of the object the vCard represents.

Value type: The default is a single text value. It can also be reset to a single URI or utc-offset value.

Cardinality: \*

Special notes: It is expected that names from the public-domain Olson database [[TZ-DB](#)] will be used, but this is not a restriction.

Efforts are currently being directed at creating a standard URI scheme for expressing time zone information. Usage of such a scheme would ensure a high level of interoperability between implementations that support it.

Note that utc-offset values SHOULD NOT be used because the UTC offset varies with time - not just because of the usual daylight saving time shifts that occur in many regions, but often entire regions will "re-base" their overall offset. The actual offset may be +/- 1 hour (or perhaps a little more) than the one given.

ABNF:



TZ-param = "VALUE=" ("text" / "uri" / "utc-offset")

TZ-value = text / URI / utc-offset

; Value and parameter MUST match

TZ-param =/ altid-param / pid-param / pref-param / type-param  
/ mediatype-param / any-param

Examples:

TZ:Raleigh/North America

TZ;VALUE=utc-offset:-0500

; Note: utc-offset format is NOT RECOMMENDED.

### **6.5.2. GEO**

Purpose: To specify information related to the global positioning of the object the vCard represents.

Value type: A single URI.

Cardinality: \*

Special notes: The "geo" URI scheme [[RFC5870](#)] is particularly well-suited for this property, but other schemes MAY be used.

ABNF:

GEO-param = "VALUE=uri" / pid-param / pref-param / type-param  
/ mediatype-param / altid-param / any-param

GEO-value = URI

Example:

GEO:geo:37.386013, -122.082932

## **6.6. Organizational Properties**

These properties are concerned with information associated with characteristics of the organization or organizational units of the object that the vCard represents.

### **6.6.1. TITLE**



Purpose: To specify the position or job of the object the vCard represents.

Value type: A single text value.

Cardinality: \*

Special notes: This property is based on the X.520 Title attribute.

ABNF:

```
TITLE-param = "VALUE=text" / language-param / pid-param  
              / pref-param / altid-param / type-param / any-param  
TITLE-value = text
```

Example:

```
TITLE:Research Scientist
```

#### **6.6.2. ROLE**

Purpose: To specify the function or part played in a particular situation by the object the vCard represents.

Value type: A single text value.

Cardinality: \*

Special notes: This property is based on the X.520 Business Category explanatory attribute. This property is included as an organizational type to avoid confusion with the semantics of the TITLE property and incorrect usage of that property when the semantics of this property is intended.

ABNF:

```
ROLE-param = "VALUE=text" / language-param / pid-param / pref-param  
              / type-param / altid-param / any-param  
ROLE-value = text
```

Example:

```
ROLE:Project Leader
```



### **6.6.3. LOGO**

Purpose: To specify a graphic image of a logo associated with the object the vCard represents.

Value type: A single URI.

Cardinality: \*

ABNF:

```
LOGO-param = "VALUE=uri" / language-param / pid-param / pref-param  
            / type-param / mediatype-param / altid-param / any-param  
LOGO-value = URI
```

Examples:

```
LOGO:http://www.example.com/pub/logos/abccorp.jpg
```

```
LOGO:  
AQEEBQAwdzELMAkGA1UEBhMCVVMxLDAqBgNVBAoTI05ldHNjYXB1IENvbW11bm  
ljYXRpb25zIENvcnBvcnF0aW9uMRwwGgYDVQQLExNJbmZvcn1hdGlvbiBTexN0  
<...the remainder of base64-encoded data...>
```

### **6.6.4. ORG**

Purpose: To specify the organizational name and units associated with the vCard.

Value type: A single structured text value consisting of components separated by the SEMI-COLON character (ASCII decimal 59).

Cardinality: \*

Special notes: The property is based on the X.520 Organization Name and Organization Unit attributes. The property value is a structured type consisting of the organization name, followed by zero or more levels of organizational unit names.

The SORT-AS parameter MAY be applied to this property.

ABNF:

```
ORG-param = "VALUE=text" / sort-as-param / language-param  
            / pid-param / pref-param / altid-param / type-param  
            / any-param  
ORG-value = component *(";" component)
```





Example: A property value consisting of an organizational name, organizational unit #1 name and organizational unit #2 name.

ORG:ABC\, Inc.;North American Division;Marketing

#### **6.6.5. MEMBER**

Purpose: To include a member in the group this vCard represents.

Value type: A single URI. It MAY refer to something other than a vCard object. For example, an e-mail distribution list could employ the "mailto" URI scheme [[RFC6068](#)] for efficiency.

Cardinality: \*

Special notes: This property MUST NOT be present unless the value of the KIND property is "group".

ABNF:

```
MEMBER-param = "VALUE=uri" / pid-param / pref-param / altid-param
               / mediatype-param / any-param
MEMBER-value  = URI
```

Examples:

```
BEGIN:VCARD
VERSION:4.0
KIND:group
FN:The Doe family
MEMBER:urn:uuid:03a0e51f-d1aa-4385-8a53-e29025acd8af
MEMBER:urn:uuid:b8767877-b4a1-4c70-9acc-505d3819e519
END:VCARD
BEGIN:VCARD
VERSION:4.0
FN:John Doe
UID:urn:uuid:03a0e51f-d1aa-4385-8a53-e29025acd8af
END:VCARD
BEGIN:VCARD
VERSION:4.0
FN:Jane Doe
UID:urn:uuid:b8767877-b4a1-4c70-9acc-505d3819e519
END:VCARD
```



```
BEGIN:VCARD
VERSION:4.0
KIND:group
FN:Funky distribution list
MEMBER:mailto:subscriber1@example.com
MEMBER:xmpp:subscriber2@example.com
MEMBER:sip:subscriber3@example.com
MEMBER:tel:+1-418-555-5555
END:VCARD
```

#### **6.6.6. RELATED**

Purpose: To specify a relationship between another entity and the entity represented by this vCard.

Value type: A single URI. It can also be reset to a single text value. The text value can be used to specify textual information.

Cardinality: \*

Special notes: The TYPE parameter MAY be used to characterize the related entity. It contains a comma-separated list of values that are registered from IANA as described in [Section 10.2](#). The registry is pre-populated with the values defined in [\[xfn\]](#). This document also specifies two additional values:

agent: an entity who may sometimes act on behalf of the entity associated with the vCard.

emergency: indicates an emergency contact

ABNF:



RELATED-param = RELATED-param-uri / RELATED-param-text

RELATED-value = URI / text

; Parameter and value MUST match.

RELATED-param-uri = "VALUE=uri" / mediatype-param

RELATED-param-text = "VALUE=text" / language-param

RELATED-param =/ pid-param / pref-param / altid-param / type-param  
/ any-param

type-param-related = related-type-value \*("," related-type-value)  
; type-param-related MUST NOT be used with a property other than  
; RELATED.

related-type-value = "contact" / "acquaintance" / "friend" / "met"  
/ "co-worker" / "colleague" / "co-resident"  
/ "neighbor" / "child" / "parent"  
/ "sibling" / "spouse" / "kin" / "muse"  
/ "crush" / "date" / "sweetheart" / "me"  
/ "agent" / "emergency"

Examples:

RELATED;TYPE=friend:urn:uuid:f81d4fae-7dec-11d0-a765-00a0c91e6bf6

RELATED;TYPE=contact:http://example.com/directory/jdoe.vcf

RELATED;TYPE=co-worker;VALUE=text:Please contact my assistant Jane  
Doe for any inquiries.

## **6.7. Explanatory Properties**

These properties are concerned with additional explanations, such as that related to informational notes or revisions specific to the vCard.

### **6.7.1. CATEGORIES**

Purpose: To specify application category information about the vCard. Also known as "tags".

Value type: One or more text values separated by a COMMA character (ASCII decimal 44).

Cardinality: \*

ABNF:

CATEGORIES-param = "VALUE=text" / pid-param / pref-param  
/ type-param / altid-param / any-param



CATEGORIES-value = text-list

Example:

CATEGORIES:TRAVEL AGENT

CATEGORIES:INTERNET,IETF,INDUSTRY,INFORMATION TECHNOLOGY

#### **6.7.2. NOTE**

Purpose: To specify supplemental information or a comment that is associated with the vCard.

Value type: A single text value.

Cardinality: \*

Special notes: The property is based on the X.520 Description attribute.

ABNF:

NOTE-param = "VALUE=text" / language-param / pid-param / pref-param  
/ type-param / altid-param / any-param  
NOTE-value = text

Example:

NOTE:This fax number is operational 0800 to 1715  
EST\, Mon-Fri.

#### **6.7.3. PROPID**

Purpose: To specify the identifier for the product that created the vCard object.

Type value: A single text value.

Cardinality: \*1

Special notes: Implementations SHOULD use a method such as that specified for Formal Public Identifiers in [[IS09070](#)] or for Universal Resource Names in [[RFC3406](#)] to ensure that the text value is unique.





ABNF:

```
PROPID-param = "VALUE=text" / any-param
PROPID-value = text
```

Example:

```
PROPID:-//ONLINE DIRECTORY//NONSGML Version 1//EN
```

#### [6.7.4.](#) **REV**

Purpose: To specify revision information about the current vCard.

Value type: A single timestamp value.

Cardinality: \*1

Special notes: The value distinguishes the current revision of the information in this vCard for other renditions of the information.

ABNF:

```
REV-param = "VALUE=timestamp" / any-param
REV-value = timestamp
```

Example:

```
REV:19951031T222710Z
```

#### [6.7.5.](#) **SOUND**

Purpose: To specify a digital sound content information that annotates some aspect of the vCard. This property is often used to specify the proper pronunciation of the name property value of the vCard.

Value type: A single URI.

Cardinality: \*

ABNF:

```
SOUND-param = "VALUE=uri" / language-param / pid-param / pref-param
              / type-param / mediatype-param / altid-param
              / any-param
SOUND-value = URI
```

Example:



SOUND:CID:JOHNQPUBLIC.part8.19960229T080000.xyzMail@example.com

SOUND:data:audio/basic;base64,MIICajCCAdOgAwIBAgICBEUwDQYJKoZIh  
AQEEBQAwdzELMAkGA1UEBhMCVVMxLDAqBgNVBAoTI05ldHNjYXB1IENvbW11bm  
ljYXRpb25zIENvcnBvcnF0aW9uMRwwGgYDVQQLExNJbmZvcn1hdGlvbiBTexN0  
<...the remainder of base64-encoded data...>

#### **6.7.6. UID**

Purpose: To specify a value that represents a globally unique identifier corresponding to the entity associated with the vCard.

Value type: A single URI value. It MAY also be reset to free-form text.

Cardinality: \*1

Special notes: This property is used to uniquely identify the object that the vCard represents. The "uuid" URN namespace defined in [\[RFC4122\]](#) is particularly well-suited to this task, but other URI schemes MAY be used. Free-form text MAY also be used.

ABNF:

UID-param = UID-uri-param / UID-text-param  
UID-value = UID-uri-value / UID-text-value  
; Value and parameter MUST match.

UID-uri-param = "VALUE=uri"  
UID-uri-value = URI

UID-text-param = "VALUE=text"  
UID-text-value = text

UID-param =/ any-param

Example:

UID:urn:uuid:f81d4fae-7dec-11d0-a765-00a0c91e6bf6

#### **6.7.7. CLIENTPIDMAP**

Purpose: To give a global meaning to a local PID source identifier.

Value type: A semicolon-separated pair of values. The first field is a small integer corresponding to the second field of a PID parameter instance. The second field is a URI. The "uuid" URN namespace defined in [\[RFC4122\]](#) is particularly well-suited to this



task, but other URI schemes MAY be used.

Cardinality: \*

Special notes: PID source identifiers (the source identifier is the second field in a PID parameter instance) are small integers that only have significance within the scope of a single vCard instance. Each distinct source identifier present in a vCard MUST have an associated CLIENTPIDMAP. See [Section 7](#) for more details on the usage of CLIENTPIDMAP.

PID source identifiers MUST be strictly positive. Zero is not allowed.

As a special exception, the PID parameter MUST NOT be applied to this property.

ABNF:

```
CLIENTPIDMAP-param = any-param  
CLIENTPIDMAP-value = 1*DIGIT ";" URI
```

Example:

```
TEL;PID=3.1,4.2;VALUE=uri:tel:+1-555-555-5555  
EMAIL;PID=4.1,5.2:jdoe@example.com  
CLIENTPIDMAP:1;urn:uuid:3df403f4-5924-4bb7-b077-3c711d9eb34b  
CLIENTPIDMAP:2;urn:uuid:d89c9c7a-2e1b-4832-82de-7e992d95faa5
```

#### [6.7.8.](#) URL

Purpose: To specify a uniform resource locator associated with the object that the vCard refers to. Examples for individuals include personal web sites, blogs, and social networking site identifiers.

Cardinality: \*

Value type: A single uri value.

ABNF:

```
URL-param = "VALUE=uri" / pid-param / pref-param / type-param  
           / mediatype-param / altid-param / any-param  
URL-value = URI
```

Example:

```
URL:http://example.org/restaurant.french/~chezchic.html
```



#### **6.7.9. VERSION**

Purpose: To specify the version of the vCard specification used to format this vCard.

Value type: A single text value.

Cardinality: 1

Special notes: This property MUST be present in the vCard object, and it must appear immediately after BEGIN:VCARD. The value MUST be "4.0" if the vCard corresponds to this specification. Note that earlier versions of vCard allowed this property to be placed anywhere in the vCard object, or even to be absent.

ABNF:

```
VERSION-param = "VALUE=text" / any-param  
VERSION-value = "4.0"
```

Example:

```
VERSION:4.0
```

### **6.8. Security Properties**

These properties are concerned with the security of communication pathways or access to the vCard.

#### **6.8.1. KEY**

Purpose: To specify a public key or authentication certificate associated with the object that the vCard represents.

Value type: A single URI. It can also be reset to a text value.

Cardinality: \*

ABNF:





```
KEY-param = KEY-uri-param / KEY-text-param
KEY-value = KEY-uri-value / KEY-text-value
; Value and parameter MUST match.
```

```
KEY-uri-param = "VALUE=uri" / mediatype-param
KEY-uri-value = URI
```

```
KEY-text-param = "VALUE=text"
KEY-text-value = text
```

```
KEY-param =/ altid-param / pid-param / pref-param / type-param
/ any-param
```

Examples:

```
KEY:http://www.example.com/keys/jdoe
```

```
KEY;MEDIATYPE=application/pgp-keys:ftp://example.com/keys/jdoe
```

```
KEY:data:application/pgp-keys;base64,MIICajCCAdOgAwIBAgICBE
UwDQYJKoZIhvcNAQEEBQAwdzELMAkGA1UEBhMCVVMxLDAqBgNVBAoTI05l
<... remainder of base64-encoded data ...>
```

## 6.9. Calendar Properties

These properties are further specified in [[RFC2739](#)].

### 6.9.1. FBURL

Purpose: To specify the URI for the busy time associated with the object that the vCard represents.

Value type: A single URI value.

Cardinality: \*

Special notes: Where multiple FBURL properties are specified, the default FBURL property is indicated with the PREF parameter. The FTP [[RFC1738](#)] or HTTP [[RFC2616](#)] type of URI points to an iCalendar [[RFC5545](#)] object associated with a snapshot of the next few weeks or months of busy time data. If the iCalendar object is represented as a file or document, its file extension should be ".ifb".

ABNF:

```
FBURL-param = "VALUE=uri" / pid-param / pref-param / type-param
/ mediatype-param / altid-param / any-param
```



FBURL-value = URI

Examples:

FBURL;PREF=1:http://www.example.com/busy/janedoe

FBURL;MEDIATYPE=text/calendar:ftp://example.com/busy/project-a.ifb

### **6.9.2. CALADRURI**

Purpose: To specify the calendar user address [[RFC5545](#)] to which a scheduling request [[RFC5546](#)] should be sent for the object represented by the vCard.

Value type: A single URI value.

Cardinality: \*

Special notes: Where multiple CALADRURI properties are specified, the default CALADRURI property is indicated with the PREF parameter.

ABNF:

```
CALADRURI-param = "VALUE=uri" / pid-param / pref-param / type-param  
                  / mediatype-param / altid-param / any-param  
CALADRURI-value = URI
```

Example:

CALADRURI;PREF=1:mailto:janedoe@example.com

CALADRURI:http://example.com/calendar/jdoe

### **6.9.3. CALURI**

Purpose: To specify the URI for a calendar associated with the object represented by the vCard.

Value type: A single URI value.

Cardinality: \*

Special notes: Where multiple CALURI properties are specified, the default CALURI property is indicated with the PREF parameter. The property should contain a URI pointing to an iCalendar [[RFC5545](#)] object associated with a snapshot of the user's calendar store. If the iCalendar object is represented as a file or document, its file extension should be ".ics".



ABNF:

```
CALURI-param = "VALUE=uri" / pid-param / pref-param / type-param  
              / mediatype-param / altid-param / any-param  
CALURI-value = URI
```

Examples:

```
CALURI;PREF=1:http://cal.example.com/calA  
CALURI;MEDIATYPE=text/calendar:ftp://ftp.example.com/calA.ics
```

### **[6.10.](#) Extended Properties and Parameters**

The properties and parameters defined by this document can be extended. Non-standard, private properties and parameters with a name starting with "X-" may be defined bilaterally between two cooperating agents without outside registration or standardization.

## **[7.](#) Synchronization**

vCard data often needs to be synchronized between devices. In this context, synchronization is defined as the intelligent merging of two representations of the same object. vCard 4.0 includes mechanisms to aid this process.

### **[7.1.](#) Mechanisms**

Two mechanisms are available: the UID property is used to match multiple instances of the same vCard, while the PID parameter is used to match multiple instances of the same property.

The term "matching" is used here to mean recognizing that two instances are in fact representations of the same object. For example, a single vCard that is shared with someone results in two vCard instances. After they have evolved separately, they still represent the same object, and therefore may be matched by a synchronization engine.

#### **[7.1.1.](#) Matching vCard Instances**

vCard instances for which the UID properties ([Section 6.7.6](#)) are equivalent MUST be matched. Equivalence is determined as specified in [\[RFC3986\]](#), [Section 6](#).

In all other cases, vCard instances MAY be matched at the discretion of the synchronization engine.



### **7.1.2. Matching Property Instances**

Property instances belonging to unmatched vCards MUST NOT be matched.

Property instances whose name (e.g. EMAIL, TEL, etc.) is not the same MUST NOT be matched.

Property instances whose name is CLIENTPIDMAP are handled separately and MUST NOT be matched. The synchronization MUST ensure that there is consistency of CLIENTPIDMAPs among matched vCard instances.

Property instances belonging to matched vCards, whose name is the same, and whose maximum cardinality is 1 MUST be matched.

Property instances belonging to matched vCards, whose name is the same, and whose PID parameters match MUST be matched. See [Section 7.1.3](#) for details on PID matching.

In all other cases, property instances MAY be matched at the discretion of the synchronization engine.

### **7.1.3. PID Matching**

Two PID values for which the first fields are equivalent represent the same local value.

Two PID values representing the same local value and for which the second fields point to CLIENTPIDMAP properties whose second field URIs are equivalent (as specified in [\[RFC3986\]](#), [Section 6](#)) also represent the same global value.

PID parameters for which at least one pair of their values represent the same global value MUST be matched.

In all other cases, PID parameters MAY be matched at the discretion of the synchronization engine.





For example, PID value "5.1", in the first vCard below, and PID value "5.2", in the second vCard below, represent the same global value.

```
BEGIN:VCARD
VERSION:4.0
EMAIL;PID=4.2,5.1:jdoe@example.com
CLIENTPIDMAP:1;urn:uuid:3eef374e-7179-4196-a914-27358c3e6527
CLIENTPIDMAP:2;urn:uuid:42bcd5a7-1699-4514-87b4-056edf68e9cc
END:VCARD
```

```
BEGIN:VCARD
VERSION:4.0
EMAIL;PID=5.1,5.2:john@example.com
CLIENTPIDMAP:1;urn:uuid:0c75c629-6a8d-4d5e-a07f-1bb35846854d
CLIENTPIDMAP:2;urn:uuid:3eef374e-7179-4196-a914-27358c3e6527
END:VCARD
```

## [7.2.](#) Example

### [7.2.1.](#) Creation

The following simple vCard is first created on a given device.

```
BEGIN:VCARD
VERSION:4.0
UID:urn:uuid:4fbe8971-0bc3-424c-9c26-36c3e1eff6b1
FN;PID=1.1:J. Doe
N:Doe;J.;.;
EMAIL;PID=1.1:jdoe@example.com
CLIENTPIDMAP:1;urn:uuid:53e374d9-337e-4727-8803-a1e9c14e0556
END:VCARD
```

This new vCard is assigned the UID "urn:uuid:4fbe8971-0bc3-424c-9c26-36c3e1eff6b1" by the creating device. The FN and EMAIL properties are assigned the same local value of 1, and this value is given global context by associating it with "urn:uuid:53e374d9-337e-4727-8803-a1e9c14e0556", which represents the creating device. We are at liberty to reuse the same local value since instances of different properties will never be matched. The N property has no PID because it is forbidden by its maximum cardinality of 1.

### [7.2.2.](#) Initial Sharing

This vCard is shared with a second device. Upon inspecting the UID property, the second device understands that this is a new vCard (i.e. unmatched) and thus the synchronization results in a simple copy.



### **7.2.3. Adding and Sharing a Property**

A new phone number is created on the first device, then the vCard is shared with the second device. This is what the second device receives:

```
BEGIN:VCARD
VERSION:4.0
UID:urn:uuid:4fbc8971-0bc3-424c-9c26-36c3e1eff6b1
FN;PID=1.1:J. Doe
N:Doe;J.;.;
EMAIL;PID=1.1:jdoe@example.com
TEL;PID=1.1;VALUE=uri:tel:+1-555-555-5555
CLIENTPIDMAP:1;urn:uuid:53e374d9-337e-4727-8803-a1e9c14e0556
END:VCARD
```

Upon inspecting the UID property, the second device matches the vCard it received to the vCard that it already has stored. It then starts comparing the properties of the two vCards in same-named pairs.

The FN properties are matched because the PID parameters have the same global value. Since the property value is the same, no update takes place.

The N properties are matched automatically because their maximum cardinality is 1. Since the property value is the same, no update takes place.

The EMAIL properties are matched because the PID parameters have the same global value. Since the property value is the same, no update takes place.

The TEL property in the new vCard is not matched to any in the stored vCard because no property in the stored vCard has the same name. Therefore, this property is copied from the new vCard to the stored vCard.

The CLIENTPIDMAP property is handled separately by the synchronization engine. It ensures that it is consistent with the stored one. If it was not, the results would be up to the synchronization engine, and thus undefined by this document.

### **7.2.4. Simultaneous Editing**

A new email address and a new phone number are added to the vCard on each of the two devices, and then a new synchronization event happens. Here are the vCards that are communicated to each other:



```
BEGIN:VCARD
VERSION:4.0
UID:urn:uuid:4fbc8971-0bc3-424c-9c26-36c3e1eff6b1
FN;PID=1.1:J. Doe
N:Doe;J.;;;
EMAIL;PID=1.1:jdoe@example.com
EMAIL;PID=2.1:boss@example.com
TEL;PID=1.1;VALUE=uri:tel:+1-555-555-5555
TEL;PID=2.1;VALUE=uri:tel:+1-666-666-6666
CLIENTPIDMAP:1;urn:uuid:53e374d9-337e-4727-8803-a1e9c14e0556
END:VCARD
```

```
BEGIN:VCARD
VERSION:4.0
UID:urn:uuid:4fbc8971-0bc3-424c-9c26-36c3e1eff6b1
FN;PID=1.1:J. Doe
N:Doe;J.;;;
EMAIL;PID=1.1:jdoe@example.com
EMAIL;PID=2.2:ceo@example.com
TEL;PID=1.1;VALUE=uri:tel:+1-555-555-5555
TEL;PID=2.2;VALUE=uri:tel:+1-666-666-6666
CLIENTPIDMAP:1;urn:uuid:53e374d9-337e-4727-8803-a1e9c14e0556
CLIENTPIDMAP:2;urn:uuid:1f762d2b-03c4-4a83-9a03-75ff658a6eee
END:VCARD
```

On the first device, the same PID source identifier (1) is reused for the new EMAIL and TEL properties. On the second device, a new source identifier (2) is generated, and a corresponding CLIENTPIDMAP property is created. It contains the second device's identifier, "urn:uuid:1f762d2b-03c4-4a83-9a03-75ff658a6eee".

The new EMAIL properties are unmatched on both sides since the PID global value is new in both cases. The sync thus results in a copy on both sides.

Although the situation appears to be the same for the TEL properties, in this case the synchronization engine is particularly smart and matches the two new TEL properties even though their PID global values are different. Note that in this case, the rules of [Section 7.1.2](#) state that two properties MAY be matched at the discretion of the synchronization engine. Therefore, the two properties are merged.

All this results in the following vCard which is stored on both devices:



```
BEGIN:VCARD
VERSION:4.0
UID:urn:uuid:4fbe8971-0bc3-424c-9c26-36c3e1eff6b1
FN:J. Doe
N:Doe;J.;;;
EMAIL;PID=1.1:jdoe@example.com
EMAIL;PID=2.1:boss@example.com
EMAIL;PID=2.2:ceo@example.com
TEL;PID=1.1;VALUE=uri:tel:+1-555-555-5555
TEL;PID=2.1,2.2;VALUE=uri:tel:+1-666-666-6666
CLIENTPIDMAP:1;urn:uuid:53e374d9-337e-4727-8803-a1e9c14e0556
CLIENTPIDMAP:2;urn:uuid:1f762d2b-03c4-4a83-9a03-75ff658a6eee
END:VCARD
```

#### **7.2.5. Global Context Simplification**

The two devices finish their synchronization procedure by simplifying their global contexts. Since they haven't talked to any other device, the following vCard is for all purposes equivalent to the above. It is also shorter.

```
BEGIN:VCARD
VERSION:4.0
UID:urn:uuid:4fbe8971-0bc3-424c-9c26-36c3e1eff6b1
FN:J. Doe
N:Doe;J.;;;
EMAIL;PID=1.1:jdoe@example.com
EMAIL;PID=2.1:boss@example.com
EMAIL;PID=3.1:ceo@example.com
TEL;PID=1.1;VALUE=uri:tel:+1-555-555-5555
TEL;PID=2.1;VALUE=uri:tel:+1-666-666-6666
CLIENTPIDMAP:1;urn:uuid:53e374d9-337e-4727-8803-a1e9c14e0556
END:VCARD
```

The details of global context simplification are unspecified by this document. They are left up to the synchronization engine. This example is merely intended to illustrate the possibility, which investigating would be, in the authors' opinion, worthwhile.





## 8. Example: Authors' vCards

```
BEGIN:VCARD
VERSION:4.0
FN:Simon Perreault
N:Perreault;Simon;;;ing. jr,M.Sc.
BDAY:--0203
ANNIVERSARY:20090808T1430-0500
GENDER:M
LANG;PREF=1:fr
LANG;PREF=2:en
ORG;TYPE=work:Viagenie
ADR;TYPE=work:;Suite D2-630;2875 Laurier;
  Quebec;QC;G1V 2M2;Canada
TEL;VALUE=uri;TYPE="work,voice";PREF=1:tel:+1-418-656-9254;ext=102
TEL;VALUE=uri;TYPE="work,cell,voice,video,text":tel:+1-418-262-6501
EMAIL;TYPE=work:simon.perreault@viagenie.ca
GEO;TYPE=work:geo:46.772673,-71.282945
KEY;TYPE=work;VALUE=uri:
http://www.viagenie.ca/simon.perreault/simon.asc
TZ:-0500
END:VCARD
```

```
BEGIN:VCARD
VERSION:4.0
FN:Pete Resnick
N:Resnick;Pete;;;
GENDER:M
ORG;TYPE=work:QUALCOMM Incorporated
ADR;TYPE=work:;;5775 Morehouse Drive;San Diego;CA;92121-1714;US
TEL;VALUE=uri;TYPE="work,voice":tel:+1-858-651-4478
EMAIL;TYPE=work:presnick@qualcomm.com
URL;TYPE=work:http://www.qualcomm.com/~presnick/
END:VCARD
```

## 9. Security Considerations

- o Internet mail is often used to transport vCards and is subject to many well known security attacks, including monitoring, replay, and forgery. Care should be taken by any directory service in allowing information to leave the scope of the service itself, where any access controls or confidentiality can no longer be guaranteed. Applications should also take care to display directory data in a "safe" environment
- o vCards can carry cryptographic keys or certificates, as described in [Section 6.8.1](#).



- o The vCard objects have no inherent authentication or privacy, but can easily be carried by any security mechanism that transfers MIME objects with authentication or privacy (e.g. S/MIME [RFC5751], OpenPGP [RFC4880]). In cases where the threat of "spoofed" vCard information is a concern, the vCard SHOULD BE transported using one of these secure mechanisms.
- o The information in a vCard may become out of date. In cases where the vitality of data is important to an originator of a vCard, the SOURCE property ([Section 6.1.3](#)) SHOULD be specified. In addition, the "REV" type described in [section 6.7.4](#) can be specified to indicate the last time that the vCard data was updated.

## **[10.](#) IANA Considerations**

### **[10.1.](#) MIME Type Registration**

IANA is asked to register the following MIME Media Type (in <http://www.iana.org/assignments/media-types/>).

To: ietf-types@iana.org

Subject: Registration of media type text/vcard

Type name: text

Subtype name: vcard

Required parameters: none

Optional parameters: version

The "version" parameter is to be interpreted identically as the VERSION vCard property. If this parameter is present, all vCards in a text/vcard body part MUST have a VERSION property with value identical to that of this MIME parameter.

"charset": as defined for text/plain [RFC2046]; encodings other than UTF-8 [RFC3629] MUST NOT be used.

Encoding considerations: 8bit

Security considerations: See [Section 9](#).

Interoperability considerations: The text/vcard media type is intended to identify vCard data of any version. There are older specifications of vCard [RFC2426][vCard21] still in common use. While these formats are similar, they are not strictly compatible.



In general, it is necessary to inspect the value of the VERSION property (see [Section 6.7.9](#)) for identifying the standard to which a given vCard object conforms.

In addition, the following media types are known to have been used to refer to vCard data. They should be considered deprecated in favor of text/vcard.

- \* text/directory
- \* text/directory; profile=vcard
- \* text/x-vcard

Published specification: [draft-ietf-vcarddav-vcardrev-19](#)

Applications that use this media type: They are numerous, diverse, and include mail user agents, instant messaging clients, address book applications, directory servers, customer relationship management software.

Additional information:

Magic number(s):

File extension(s): .vcf .vcard

Macintosh file type code(s):

Person & email address to contact for further information: Simon Perreault <simon.perreault@viagenie.ca>

Intended usage: COMMON

Restrictions on usage: none

Author: Simon Perreault

Change controller: IETF

## **[10.2. Registering New vCard Elements](#)**

This section defines the process for registering new or modified vCard elements (i.e. properties, parameters, value data types, and values) with IANA. It does not contain any immediate IANA actions.



### **10.2.1. Registration Procedure**

The IETF will create a mailing list, `vcard@ietf.org` [1], which can be used for public discussion of vCard element proposals prior to registration. Use of the mailing list is strongly encouraged. The IESG will appoint a designated expert who will monitor the `vcard@ietf.org` [1] mailing list and review registrations.

Registration of new vCard elements MUST be reviewed by the designated expert and published in an RFC. A Standard Tracks RFC is REQUIRED for the registration of new value data types that modify existing properties. A Standard Tracks RFC is also REQUIRED for registration of vCard elements that modify vCard elements previously documented in a Standard Tracks RFC.

The registration procedure begins when a completed registration template, defined in the sections below, is sent to `vcard@ietf.org` [1] and `iana@iana.org` [2]. The designated expert is expected to tell IANA and the submitter of the registration within two weeks whether the registration is approved, approved with minor changes, or rejected with cause. When a registration is rejected with cause, it can be re-submitted if the concerns listed in the cause are addressed. Decisions made by the designated expert can be appealed to the IESG Applications Area Director, then to the IESG. They follow the normal appeals procedure for IESG decisions.

Once the registration procedure concludes successfully, IANA creates or modifies the corresponding record in the vCard registry. The completed registration template is discarded.

An RFC specifying new vCard elements MUST include the completed registration templates, which MAY be expanded with additional information. These completed templates will go in the body of the document, and SHOULD NOT be included or repeated in the IANA Considerations section.

Finally, note that there is an XML representation for vCard defined in [I-D.ietf-vcarddav-vcardxml]. An XML representation SHOULD be defined for new vCard objects.

### **10.2.2. Vendor Namespace**

The vendor namespace is used for vCard elements associated with commercially available products. "Vendor" or "producer" are construed as equivalent and very broadly in this context.

A registration may be placed in the vendor namespace by anyone who needs to interchange files associated with the particular product.





However, the registration formally belongs to the vendor or organization handling the vCard elements in the namespace being registered. Changes to the specification will be made at their request, as discussed in subsequent sections.

vCard elements belonging to the vendor namespace will be distinguished by the "VND-" prefix. This is followed by an IANA-registered Private Enterprise Number (PEN), a dash, and a vCard element designation of the vendor's choosing (e.g., "VND-123456-MUDPIE").

While public exposure and review of vCard elements to be registered in the vendor namespace is not required, using the [vcards@ietf.org](mailto:vcards@ietf.org) [1] mailing list for review is strongly encouraged to improve the quality of those specifications. Registrations in the vendor namespace may be submitted directly to the IANA.

### **10.2.3. Registration Template for Properties**

A property is defined by completing the following template.

Namespace: Empty for the global namespace, "VND-NNNN-" for a vendor-specific property (where NNNN is replaced by the vendor's PEN).

Property name: The name of the property.

Purpose: The purpose of the property. Give a short but clear description.

Value type: Any of the valid value types for the property value needs to be specified. The default value type also needs to be specified.

Cardinality: See [Section 6](#).

Property parameters: Any of the valid property parameters for the property MUST be specified.

Description: Any special notes about the property, how it is to be used, etc.

Format definition: The ABNF for the property definition needs to be specified.

Example(s): One or more examples of instances of the property needs to be specified.



#### **10.2.4. Registration Template for Parameters**

A parameter is defined by completing the following template.

Namespace: Empty for the global namespace, "VND-NNNN-" for a vendor-specific property (where NNNN is replaced by the vendor's PEN).

Parameter name: The name of the parameter.

Purpose: The purpose of the parameter. Give a short but clear description.

Description: Any special notes about the parameter, how it is to be used, etc.

Format definition: The ABNF for the parameter definition needs to be specified.

Example(s): One or more examples of instances of the parameter needs to be specified.

#### **10.2.5. Registration Template for Value Data Types**

A value data type is defined by completing the following template.

Value name: The name of the value type.

Purpose: The purpose of the value type. Give a short but clear description.

Description: Any special notes about the value type, how it is to be used, etc.

Format definition: The ABNF for the value type definition needs to be specified.

Example(s): One or more examples of instances of the value type needs to be specified.

#### **10.2.6. Registration Template for Values**

A value is defined by completing the following template.

Value: The value literal.



**Purpose:** The purpose of the value. Give a short but clear description.

**Conformance:** The vCard properties and/or parameters that can take this value needs to be specified.

**Example(s):** One or more examples of instances of the value needs to be specified.

The following is a fictitious example of a registration of a vCard value:

**Value:** supervisor

**Purpose:** It means that the related entity is the direct hierarchical superior (i.e. supervisor or manager) of the entity this vCard represents.

**Conformance:** This value can be used with the "TYPE" parameter applied on the "RELATED" property.

**Example(s):**

RELATED;TYPE=supervisor:urn:uuid:f81d4fae-7dec-11d0-a765-00a0c91e6bf6

### **10.3. Initial vCard Elements Registries**

The IANA is requested to create and maintain the following registries for vCard elements with pointers to appropriate reference documents. The registries will be grouped together under the heading "vCard Elements".

#### **10.3.1. Properties Registry**

The following table is to be used to initialize the properties registry.



Namespace	Property	Reference
	SOURCE	RFCXXXX, <a href="#">Section 6.1.3</a>
	KIND	RFCXXXX, <a href="#">Section 6.1.4</a>
	XML	RFCXXXX, <a href="#">Section 6.1.5</a>
	FN	RFCXXXX, <a href="#">Section 6.2.1</a>
	N	RFCXXXX, <a href="#">Section 6.2.2</a>
	NICKNAME	RFCXXXX, <a href="#">Section 6.2.3</a>
	PHOTO	RFCXXXX, <a href="#">Section 6.2.4</a>
	BDAY	RFCXXXX, <a href="#">Section 6.2.5</a>
	ANNIVERSARY	RFCXXXX, <a href="#">Section 6.2.6</a>
	GENDER	RFCXXXX, <a href="#">Section 6.2.7</a>
	ADR	RFCXXXX, <a href="#">Section 6.3.1</a>
	TEL	RFCXXXX, <a href="#">Section 6.4.1</a>
	EMAIL	RFCXXXX, <a href="#">Section 6.4.2</a>
	IMPP	RFCXXXX, <a href="#">Section 6.4.3</a>
	LANG	RFCXXXX, <a href="#">Section 6.4.4</a>
	TZ	RFCXXXX, <a href="#">Section 6.5.1</a>
	GEO	RFCXXXX, <a href="#">Section 6.5.2</a>
	TITLE	RFCXXXX, <a href="#">Section 6.6.1</a>
	ROLE	RFCXXXX, <a href="#">Section 6.6.2</a>
	LOGO	RFCXXXX, <a href="#">Section 6.6.3</a>
	ORG	RFCXXXX, <a href="#">Section 6.6.4</a>
	MEMBER	RFCXXXX, <a href="#">Section 6.6.5</a>
	RELATED	RFCXXXX, <a href="#">Section 6.6.6</a>
	CATEGORIES	RFCXXXX, <a href="#">Section 6.7.1</a>
	NOTE	RFCXXXX, <a href="#">Section 6.7.2</a>
	PRODID	RFCXXXX, <a href="#">Section 6.7.3</a>
	REV	RFCXXXX, <a href="#">Section 6.7.4</a>
	SOUND	RFCXXXX, <a href="#">Section 6.7.5</a>
	UID	RFCXXXX, <a href="#">Section 6.7.6</a>
	CLIENTPIDMAP	RFCXXXX, <a href="#">Section 6.7.7</a>
	URL	RFCXXXX, <a href="#">Section 6.7.8</a>
	VERSION	RFCXXXX, <a href="#">Section 6.7.9</a>
	KEY	RFCXXXX, <a href="#">Section 6.8.1</a>
	FBURL	RFCXXXX, <a href="#">Section 6.9.1</a>
	CALADRURI	RFCXXXX, <a href="#">Section 6.9.2</a>
	CALURI	RFCXXXX, <a href="#">Section 6.9.3</a>

### [10.3.2.](#) Parameters Registry

The following table is to be used to initialize the parameters registry.





Namespace	Parameter	Reference
	LANGUAGE	RFCXXXX, <a href="#">Section 5.1</a>
	VALUE	RFCXXXX, <a href="#">Section 5.2</a>
	PREF	RFCXXXX, <a href="#">Section 5.3</a>
	ALTID	RFCXXXX, <a href="#">Section 5.4</a>
	PID	RFCXXXX, <a href="#">Section 5.5</a>
	TYPE	RFCXXXX, <a href="#">Section 5.6</a>
	MEDIATYPE	RFCXXXX, <a href="#">Section 5.7</a>
	CALSCALE	RFCXXXX, <a href="#">Section 5.8</a>
	SORT-AS	RFCXXXX, <a href="#">Section 5.9</a>
	GEO	RFCXXXX, <a href="#">Section 5.10</a>
	TZ	RFCXXXX, <a href="#">Section 5.11</a>

### [10.3.3.](#) Value Data Types Registry

The following table is to be used to initialize the parameters registry.

Value Data Type	Reference
BOOLEAN	RFCXXXX, <a href="#">Section 4.4</a>
DATE	RFCXXXX, <a href="#">Section 4.3.1</a>
TIME	RFCXXXX, <a href="#">Section 4.3.2</a>
DATE-TIME	RFCXXXX, <a href="#">Section 4.3.3</a>
DATE-AND-OR-TIME	RFCXXXX, <a href="#">Section 4.3.4</a>
TIMESTAMP	RFCXXXX, <a href="#">Section 4.3.5</a>
FLOAT	RFCXXXX, <a href="#">Section 4.6</a>
INTEGER	RFCXXXX, <a href="#">Section 4.5</a>
TEXT	RFCXXXX, <a href="#">Section 4.1</a>
URI	RFCXXXX, <a href="#">Section 4.2</a>
LANGUAGE-TAG	RFCXXXX, <a href="#">Section 4.7</a>

### [10.3.4.](#) Values Registries

Separate tables will be used for property and parameter values.

The following table is to be used to initialize the property values registry.



Property	Value	Reference
BEGIN	VCARD	RFCXXXX, <a href="#">Section 6.1.1</a>
END	VCARD	RFCXXXX, <a href="#">Section 6.1.2</a>
KIND	individual	RFCXXXX, <a href="#">Section 6.1.4</a>
KIND	group	RFCXXXX, <a href="#">Section 6.1.4</a>
KIND	org	RFCXXXX, <a href="#">Section 6.1.4</a>
KIND	location	RFCXXXX, <a href="#">Section 6.1.4</a>

The following table is to be used to initialize the parameter values registry.

Property	Parameter	Value	Reference
FN, NICKNAME, PHOTO, ADR, TEL, EMAIL, IMPP, LANG, TZ, GEO, TITLE, ROLE, LOGO, ORG, RELATED, CATEGORIES, NOTE, SOUND, URL, KEY, FBURL, CALADRURI, and CALURI	TYPE	work	RFCXXXX, <a href="#">Section 5.6</a>
FN, NICKNAME, PHOTO, ADR, TEL, EMAIL, IMPP, LANG, TZ, GEO, TITLE, ROLE, LOGO, ORG, RELATED, CATEGORIES, NOTE, SOUND, URL, KEY, FBURL, CALADRURI, and CALURI	TYPE	home	RFCXXXX, <a href="#">Section 5.6</a>
TEL	TYPE	text	RFCXXXX, <a href="#">Section 6.4.1</a>
TEL	TYPE	voice	RFCXXXX, <a href="#">Section 6.4.1</a>
TEL	TYPE	fax	RFCXXXX, <a href="#">Section 6.4.1</a>
TEL	TYPE	cell	RFCXXXX, <a href="#">Section 6.4.1</a>
TEL	TYPE	video	RFCXXXX, <a href="#">Section 6.4.1</a>
TEL	TYPE	pager	RFCXXXX, <a href="#">Section 6.4.1</a>
BDAY, ANNIVERSARY	CALSCALE	gregorian	RFCXXXX, <a href="#">Section 6.2.5</a>



RELATED	TYPE	contact	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	acquaintance	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	friend	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	met	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	co-worker	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	colleague	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	co-resident	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	neighbor	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	child	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	parent	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	sibling	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	spouse	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	kin	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	muse	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	crush	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>
RELATED	TYPE	date	RFCXXXX, <a href="#">Section 6.6.6</a> and <a href="#">[xfn]</a>



RELATED	TYPE	sweetheart	RFCXXXX,	
			<a href="#">Section 6.6.6</a>	
			and [xfn]	
RELATED	TYPE	me	RFCXXXX,	
			<a href="#">Section 6.6.6</a>	
			and [xfn]	
RELATED	TYPE	agent	RFCXXXX,	
			<a href="#">Section 6.6.6</a>	
RELATED	TYPE	emergency	RFCXXXX,	
			<a href="#">Section 6.6.6</a>	
+-----+-----+-----+-----+				

## **11. Acknowledgements**

The authors would like to thank Tim Howes, Mark Smith, and Frank Dawson, the original authors of [[RFC2425](#)] and [[RFC2426](#)], Pete Resnick, who got this effort started and provided help along the way, as well as the following individuals who have participated in the drafting, review and discussion of this memo:

Aki Niemi, Andy Mabbett, Alexander Mayrhofer, Alexey Melnikov, Anil Srivastava, Barry Leiba, Ben Fortuna, Bernard Desruisseaux, Bernie Hoeneisen, Bjoern Hoehrmann, Caleb Richarson, Chris Bryant, Chris Newman, Cyrus Daboo, Daisuke Miyakawa, Dan Brickley, Dan Mosedale, Dany Cauchie, Darryl Champagne, Dave Thewlis, Filip Navara, Florian Zeitz, Helge Hess, Jari Urpalainen, Javier Godoy, Jean-Luc Schellens, Joe Hildebrand, Jose Luis Gayosso, Joseph Smarr, Julian Reschke, Kepeng Li, Kevin Marks, Kevin Wu Won, Kurt Zeilenga. Lisa Dusseault, Marc Blanchet, Mark Paterson, Markus Lorenz, Michael Haardt, Mike Douglass, Nick Levinson, Peter K. Sheerin, Peter Mogensen, Peter Saint-Andre, Renato Iannella, Rohit Khare, Sly Gryphon, Stephane Bortzmeyer, Tantek Celik, and Zoltan Ordogh.

## **12. References**

### **12.1. Normative References**

[CCITT.E163.1988]	International Telephone and Telegraph Consultative Committee, "Numbering Plan for the International Telephone Service", CCITT Recommendation E.163, 1988.
[CCITT.X121.1988]	International Telephone and Telegraph Consultative Committee, "International Numbering Plan for the Public Data Networks", CCITT Recommendation X.121, 1988.





- [CCITT.X520.1988] International International Telephone and Telegraph Consultative Committee, "Information Technology - Open Systems Interconnection - The Directory: Selected Attribute Types", CCITT Recommendation X.520, November 1988.
- [CCITT.X521.1988] International International Telephone and Telegraph Consultative Committee, "Information Technology - Open Systems Interconnection - The Directory: Selected Object Classes", CCITT Recommendation X.521, November 1988.
- [I-D.ietf-vcarddav-vcardxml] Perreault, S., "vCard XML Representation", [draft-ietf-vcarddav-vcardxml-08](#) (work in progress), April 2011.
- [ISO.8601.2000] International Organization for Standardization, "Data elements and interchange formats - Information interchange - Representation of dates and times", ISO Standard 8601, December 2000.
- [ISO.8601.2004] International Organization for Standardization, "Data elements and interchange formats - Information interchange - Representation of dates and times", ISO Standard 8601, December 2004.
- [RFC2045] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", [RFC 2045](#), November 1996.
- [RFC2046] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", [RFC 2046](#), November 1996.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels",



[BCP 14](#), [RFC 2119](#), March 1997.

- [RFC2739] Small, T., Hennessey, D., and F. Dawson, "Calendar Attributes for vCard and LDAP", [RFC 2739](#), January 2000.
- [RFC3629] Yergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, [RFC 3629](#), November 2003.
- [RFC3966] Schulzrinne, H., "The tel URI for Telephone Numbers", [RFC 3966](#), December 2004.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC4122] Leach, P., Mealling, M., and R. Salz, "A Universally Unique IDentifier (UUID) URN Namespace", [RFC 4122](#), July 2005.
- [RFC4288] Freed, N. and J. Klensin, "Media Type Specifications and Registration Procedures", [BCP 13](#), [RFC 4288](#), December 2005.
- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.
- [RFC5322] Resnick, P., Ed., "Internet Message Format", [RFC 5322](#), October 2008.
- [RFC5545] Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification (iCalendar)", [RFC 5545](#), September 2009.
- [RFC5546] Daboo, C., "iCalendar Transport-Independent Interoperability Protocol (iTIP)", [RFC 5546](#), December 2009.
- [RFC5646] Phillips, A. and M. Davis, "Tags for Identifying Languages", [BCP 47](#), [RFC 5646](#), September 2009.



- [RFC5870] Mayrhofer, A. and C. Spanring, "A Uniform Resource Identifier for Geographic Locations ('geo' URI)", [RFC 5870](#), June 2010.
- [W3C.REC-xml-20081126] Bray, T., Yergeau, F., Maler, E., Paoli, J., and C. Sperberg-McQueen, "Extensible Markup Language (XML) 1.0 (Fifth Edition)", World Wide Web Consortium Recommendation REC-xml-20081126, November 2008, <<http://www.w3.org/TR/2008/REC-xml-20081126>>.
- [xfn] Celik, T., Mullenweg, M., and E. Meyer, "XHTML Friends Network 1.1", <<http://gmpg.org/xfn/11>>.

## **[12.2.](#) Informative References**

- [I-D.ietf-eai-rfc5335bis] Yang, A. and S. Steele, "Internationalized Email Headers", [draft-ietf-eai-rfc5335bis-10](#) (work in progress), March 2011.
- [ISO9070] The International Organization for Standardization, "ISO 9070, Information Processing - SGML support facilities - Registration Procedures for Public Text Owner Identifiers", April 1991.
- [RFC1738] Berners-Lee, T., Masinter, L., and M. McCahill, "Uniform Resource Locators (URL)", [RFC 1738](#), December 1994.
- [RFC2397] Masinter, L., "The "data" URL scheme", [RFC 2397](#), August 1998.
- [RFC2425] Howes, T., Smith, M., and F. Dawson, "A MIME Content-Type for Directory Information", [RFC 2425](#), September 1998.
- [RFC2426] Dawson, F. and T. Howes, "vCard MIME Directory Profile", [RFC 2426](#), September 1998.
- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer



Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.

- [RFC3282] Alvestrand, H., "Content Language Headers", [RFC 3282](#), May 2002.
- [RFC3406] Daigle, L., van Gulik, D., Iannella, R., and P. Faltstrom, "Uniform Resource Names (URN) Namespace Definition Mechanisms", [BCP 66](#), [RFC 3406](#), October 2002.
- [RFC4770] Jennings, C. and J. Reschke, Ed., "vCard Extensions for Instant Messaging (IM)", [RFC 4770](#), January 2007.
- [RFC4880] Callas, J., Donnerhacke, L., Finney, H., Shaw, D., and R. Thayer, "OpenPGP Message Format", [RFC 4880](#), November 2007.
- [RFC5751] Ramsdell, B. and S. Turner, "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 3.2 Message Specification", [RFC 5751](#), January 2010.
- [RFC6068] Duerst, M., Masinter, L., and J. Zawinski, "The 'mailto' URI Scheme", [RFC 6068](#), October 2010.
- [TZ-DB] Olson, A., "Time zone code and data", [<ftp://elsie.nci.nih.gov/pub/>](ftp://elsie.nci.nih.gov/pub/).
- [vCard21] Internet Mail Consortium, "vCard - The Electronic Business Card Version 2.1", September September.

#### URIs

- [1] [<mailto:vcard@ietf.org>](mailto:vcard@ietf.org)
- [2] [<mailto:iana@iana.org>](mailto:iana@iana.org)

#### [Appendix A](#). Differences from RFCs 2425 and 2426

This appendix contains a list of changes that have been made in the vCard specification from RFCs 2425 and 2426.





### **A.1. New Structure**

- o [\[RFC2425\]](#) and [\[RFC2426\]](#) have been merged.
- o vCard is now not only a MIME type but a stand-alone format.
- o A proper MIME type registration form has been included.
- o UTF-8 is now the default character set.
- o New vCard elements can be registered from IANA.
- o Expanded text on character set.

### **A.2. Removed Features**

- o The CONTEXT and CHARSET parameters are no more.
- o The NAME, MAILER, LABEL, and CLASS properties are no more.
- o The "intl", "dom", "postal", and "parcel" TYPE parameter values for the ADR property have been removed.
- o Inline vCards (such as the value of the AGENT property) are no longer supported.
- o In the N property, each component may now contain multiple comma-separated values.

### **A.3. New Properties and Parameters**

- o The KIND, GENDER, LANG, ANNIVERSARY, XML, and CLIENTPIDMAP properties have been added.
- o [\[RFC2739\]](#), which defines the FBURL, CALADRURI, CAPURI, and CALURI properties, has been merged in.
- o [\[RFC4770\]](#), which defines the IMPP property, has been merged in.
- o The "work", "home", and "uri" TYPE parameter values for the EMAIL property have been added.
- o The "pref" value of the TYPE parameter is now a parameter of its own, with a positive integer value indicating the level of preference.
- o The ALTID and PID parameters have been added.



#### **A.4. Other Changes**

- o Synchronization is addressed in [Section 7](#).
- o The N property is no longer mandatory.
- o The value of TEL is now a URI.
- o The AGENT property was replaced with a type of RELATED.
- o Date and time values now only support the basic format. Truncation is now supported.

#### **Appendix B. Change Log (to be removed by RFC Editor prior to publication)**

##### **B.1. Changes in -19**

- o Fixed nits.
- o Fixed MEDIATYPE ABNF.

##### **B.2. Changes in -18**

- o Fix missing text in KIND section.

##### **B.3. Changes in -17**

- o s/individual/entity/
- o Moved [section 3.4](#) for better flow.
- o Removed text overriding general MIME and HTTP rules.
- o Fixed redundant ABNF.
- o Fixed parameter value quoting in examples.
- o Added informative reference for Content-Language header.
- o Moved cardinality table earlier for better flow.
- o Added normative reference for XML 1.0.
- o Added informative reference for mailto: scheme.
- o Clarified where the VERSION property must go.



- o Created the MEDIATYPE parameter.
- o Fixed text/vcard encoding considerations.
- o Added .vcard file extension.
- o Removed need for extension documents to contain tables in their IANA Considerations section.
- o Removed underspecified "Status" column in IANA registry.
- o Moved obsoleted references to Informative section.
- o Moved iCalendar references to Normative section.
- o Expanded specification of KIND values.
- o Recommend defining an XML representation for new vCard objects.

#### **B.4. Changes in -16**

- o RELATED: Added XFN values into IANA registry.
- o RELATED: Added values "agent" and "emergency".
- o EMAIL is now free-form text, with informative reference to EAI.
- o GENDER now has two components: one for biological sex, the other for gender identity.
- o Bugfixes to the core ABNF.
- o Clarified IANA considerations.
- o UID may be reset to free-form text.

#### **B.5. Changes in -15**

- o Reverted N to the 5-component format of vCard 3.
- o Removed DDAY, BIRTH, and DEATH.
- o First two components in ADR SHOULD be empty.
- o Removed the LABEL property.
- o Removed the binary value type and the ENCODING and FMTTYPE parameters.



- o Renamed SEX to GENDER. Set predefined values to "male" and "female".
- o Reverted TEL to take a text value by default, but SHOULD be reset to a URI.
- o Refer to iCalendar for CALSCALE.
- o Removed the "thing" value for KIND.
- o RELATED now uses XFN 1.1 for its value.
- o Dropped the VERSION parameter. XML MUST be version 1.0.
- o Dropped the CLASS property.
- o Property and parameter names SHOULD be upper-case.
- o Use ABNF for cardinality notation.

#### **B.6. Changes in -14**

- o DQUOTE is US-ASCII decimal 34, not 22.
- o Removed unused reference to [RFC 2046](#).
- o Updated reference to [draft-ietf-vcarddav-vcardxml](#).
- o Small fixes to the IANA registration text.
- o Added notes on the usage of TEL and IMPP properties.
- o Clarified "country name" component of ADR property.
- o Removed usage of undefined type value "msg" in TEL example.
- o Fixed parameter value quoting rules and ABNF.
- o Added example to LANGUAGE property.
- o Fixed synchronization example regarding the cardinality of FN.
- o Added implementation note for float value type.
- o Removed advice for always including VALUE parameter.
- o FMTTYPE MUST include the full MIME type.





- o Made ADR's ABNF more verbose.
- o Organized TEL TYPE values in a table.
- o Replaced TOP-SECRET example with NOINDEX.

#### **B.7. Changes in -13**

- o Changed global ABNF to make explicit that VERSION comes first.
- o Reworked example for LANGUAGE property.
- o s/TYPE/FMTTYPE/ in two examples.
- o Allow LANGUAGE parameter for text-valued BDAY, DDAY, and RELATED.
- o Tightened language on LANGUAGE parameter regarding cardinality.
- o Removed the NAME property.
- o Adjusted semi-colon escaping rules.
- o Added the ALTID parameter.

#### **B.8. Changes in -12**

- o Fixed example of LANGUAGE cardinality.
- o Added note about YYYY-MM date format.
- o Fixed [appendix A](#).
- o VERSION property must come first.
- o Fixed mistake in PID example.
- o Removed two changes from [Appendix A](#) which were probably intended to go into this change log section.
- o Explicitly state that the value for the BEGIN and END properties is case-insensitive.
- o Removed the SORT-STRING property. Created the SORT-AS parameter.
- o "T" and "Z" in dates and times are now mandatory uppercase.
- o Added the "version" MIME parameter.



- o More consistent capitalization.
- o Added missing "ANNIVERSARY" in name production rule.
- o Added missing calscale-param in param production rule.
- o Moved definition of GEO and TZ parameters to [section 5](#).
- o Simplified discussion of encoding.
- o Removed restriction for "work" and "home" values of TYPE parameter w.r.t. the KIND property.
- o XML value may now be binary.
- o Created VERSION parameter for XML.
- o BIRTH and DEATH can now have URI values.
- o Created the FMTTYPE parameter.
- o KEY can now take a text value.
- o Added references to [RFC 5545](#) (iCalendar).
- o Added namespace column in parameters registry.

#### **[B.9.](#) Changes in -11**

- o Change "XML chunk" to "XML fragment".
- o Cite W3C document containing definition of "fragment".
- o Added "XML" to property name ABNF.
- o Clarified newline escaping rule.
- o Replaced one remaining "type" with "property".
- o Removed case insensitivity of parameter values.
- o XML property can now only contain one element that is not in the vCard 4 namespace.
- o Clarified interrelationship between LANGUAGE, cardinality, and PID.



- o Added "textphone" TEL type.
- o Fixed quoting of comma in ORG examples.

#### **B.10. Changes in -10**

- o Added component in SORT-STRING for sorting by given name. Fixed and expanded the examples.
- o Fixed KIND-value ABNF.
- o Fixed deprecated media type.
- o Created the CALSCALE parameter.
- o Strengthened the stance on character set.
- o Defined the Language-Tag ABNF.
- o Made explicit the fact that IANA does not register templates.
- o Created the XML property.
- o Added social networking examples to URL property.

#### **B.11. Changes in -09**

- o Removed special meaning for groups. Removed the "work" and "home" groups. Removed the group registry. Re-introduced the "work" and "home" TYPE parameter values. Applied the TYPE parameter to properties which supported the "work" and "home" groups.
- o Vendor namespace now uses private enterprise number in prefix.
- o Added "thing" value for KIND property.

#### **B.12. Changes in -08**

- o Allow 1985 (year only) in date ABNF.
- o Fixed missing country in ADR example.
- o Added the DATE-AND-OR-TIME value.
- o Made BDAY and DDAY use DATE-AND-OR-TIME.
- o Prefixed "param" and "value" production rules specific to properties with the property name.



- o Replaced the GENDER property with the SEX property.
- o Added the ANNIVERSARY property.
- o Added the "friend" and "spouse" types of RELATED.
- o TZ property now has text / uri value.
- o Refined the definitions of TITLE and ROLE.

#### **B.13. Changes in -07**

- o PREF is now bounded. 100 is the maximum value.
- o Added the "emergency" RELATED type.
- o Made GEO a URI.
- o Added GEO and TZ parameters to ADR.
- o Changed wording of "default" use of SOUND property.
- o Completely reworked the date, time, and date-time grammars.
- o Added the timestamp value type.
- o REV now has the timestamp value type.
- o Rewrote ABNF.
- o ORG can now have a single level.

#### **B.14. Changes in -06**

- o Corrected omission of resetability to text value for RELATED.
- o Let KEY value type be reset to a URI value.
- o ABNF fixes.
- o Made gender values extensible.
- o Gave the PREF parameter a positive integer value.
- o Removed usage of the undefined "word" ABNF production rule.
- o Defined property cardinalities.





- o Defined properties allowable in WORK and HOME groups.
- o Simplified the LANG property to use the vCard preference mechanism.
- o Created the "language-tag" value type.
- o Added PID to ABNF of SOURCE allowed parameters.
- o Clarified escaping rules.
- o Changed ABNF definition of non-standard X- properties.
- o Removed TYPE parameter from EMAIL properties in examples.
- o Created the CLIENTPIDMAP property.
- o Changed PID value to a pair of small integers.
- o Completely reworked synchronization mechanisms.
- o Created brand new synchronization example.

#### **B.15. Changes in -05**

- o Added multi PID value proposal.

#### **B.16. Changes in -04**

- o Added "location" value for KIND property.
- o Some fixes to ABNF.
- o Moved "pref" from being a TYPE value to a parameter in its own right.
- o Removed the "work" and "home" TYPE values.
- o Reintroduced the group construct.
- o Assigned meaning to WORK and HOME groups.
- o Restricted the TEL TYPE parameter value set.
- o In N property, removed additional names, and replaced with multiple given names.



- o Removed TYPE parameter from EMAIL and IMPP properties.
- o Replaced AGENT with a type of RELATED.
- o Use example.org domain in URL example.
- o Created initial IANA table of values.
- o Defined meaning of PUBLIC, PRIVATE, CONFIDENTIAL.

#### **B.17. Changes in -03**

- o Various changes to the synchronization mechanisms.
- o Allowed truncated format for dated. See issue #236.

#### **B.18. Changes in -02**

- o Removed useless text in IMPP description.
- o Added CalDAV-SCHED example to CALADRURI.
- o Removed CAPURI property.
- o Dashes in dates and colons in times are now mandatory.
- o Allow for dates such as 2008 and 2008-05 and times such as 07 and 07:54.
- o Removed inline vCard value.
- o Made AGENT only accept URI references instead of inline vCards.
- o Added the MEMBER property.
- o Renamed the UID parameter to PID.
- o Changed the value type of the PID parameter to "a small integer."
- o Changed the presence of UID and PID when synchronization is to be used from MUST to SHOULD.
- o Added the RELATED ([Section 6.6.6](#)) property.
- o Fixed many ABNF typos (issue #252).
- o Changed formatting of ABNF comments to make them easier to read (issue #226).



**B.19. Changes in -01**

- o Merged [[RFC2739](#)] in.
- o Converted all foobar.com, abc.com, etc. to example.com.
- o Fixed bugs in ABNF.
- o Made explicit that coordinates in the GEO property are expressed in the WGS 84 reference system.
- o Clarified folding issues with multi-byte characters.
- o Made the value of TEL a URI.
- o Added the UID parameter.
- o Made the UID property's value type a URI.
- o Added [Section 7](#).
- o Created IANA process for registering new parameters, value types, and properties.
- o Created the initial IANA registries.
- o Created vendor namespace based on text from [RFC 4288](#).

**B.20. Changes in -00**

- o Name change because draft has been accepted as WG item. Otherwise, same as [draft-resnick-vcarddav-vcardrev-01](#).
- o Removed reference to [RFC 2234](#).
- o Fixed errata from [http://www.rfc-editor.org/errata\\_search.php/doc/html/rfc2426](http://www.rfc-editor.org/errata_search.php/doc/html/rfc2426).
- o Removed passage referring to [RFC 2425](#) profiles.
- o Renamed [Section 6.4](#) from "Telecommunications Addressing Properties" to "Communications Properties."
- o Added [Appendix A](#) and [Appendix B](#).
- o Added reference to [[RFC4770](#)].



- o Removed the group construct.
- o Made the N property no longer mandatory.
- o Added the KIND property.
- o Clarified meaning of TYPE parameter value for PHOTO, LOGO, KEY, and SOUND.
- o Removed the CONTEXT parameter.
- o Removed the MAILER property.
- o Made reference to [[ISO9070](#)] informative.
- o Removed "intl", "dom", "postal", and "parcel" TYPE parameter values for the ADR and LABEL properties.
- o Clarified meaning of "extended address" ADR field.
- o Mentioned [[RFC3406](#)] as another method of generating PROPID values.
- o Updated obsolete references.
- o Allowed BDAY and DDAY value types to be text values for fuzzy dates.
- o Removed the CHARSET property. Now the encoding is always UTF-8, except when overridden by the Content-Type (which is considered a compatibility feature).

#### Author's Address

Simon Perreault  
Viagenie  
2875 Laurier, suite D2-630  
Quebec, QC G1V 2M2  
Canada

Phone: +1 418 656 9254  
EMail: [simon.perreault@viagenie.ca](mailto:simon.perreault@viagenie.ca)  
URI: <http://www.viagenie.ca>



