

Internet Engineering Task Force  
Internet-Draft  
Intended status: Standards Track  
Expires: February 6, 2015

S. Hollenbeck  
Verisign Labs  
N. Kong  
CNNIC  
August 5, 2014

**Security Services for the Registration Data Access Protocol**  
**draft-ietf-weirds-rdap-sec-07**

Abstract

The Registration Data Access Protocol (RDAP) provides "RESTful" web services to retrieve registration metadata from domain name and regional internet registries. This document describes information security services including authentication, authorization, availability, data confidentiality, and data integrity for RDAP.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 6, 2015.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">2</a>
<a href="#">2.</a>	<a href="#">Conventions Used in This Document</a>	<a href="#">2</a>
<a href="#">2.1.</a>	<a href="#">Acronyms and Abbreviations</a>	<a href="#">3</a>
<a href="#">3.</a>	<a href="#">Information Security Services and RDAP</a>	<a href="#">3</a>
<a href="#">3.1.</a>	<a href="#">Authentication</a>	<a href="#">3</a>
<a href="#">3.1.1.</a>	<a href="#">Federated Authentication</a>	<a href="#">4</a>
<a href="#">3.2.</a>	<a href="#">Authorization</a>	<a href="#">5</a>
<a href="#">3.3.</a>	<a href="#">Availability</a>	<a href="#">5</a>
<a href="#">3.4.</a>	<a href="#">Data Confidentiality</a>	<a href="#">6</a>
<a href="#">3.5.</a>	<a href="#">Data Integrity</a>	<a href="#">6</a>
<a href="#">4.</a>	<a href="#">IANA Considerations</a>	<a href="#">7</a>
<a href="#">5.</a>	<a href="#">Security Considerations</a>	<a href="#">7</a>
<a href="#">6.</a>	<a href="#">Acknowledgements</a>	<a href="#">8</a>
<a href="#">7.</a>	<a href="#">References</a>	<a href="#">8</a>
<a href="#">7.1.</a>	<a href="#">Normative References</a>	<a href="#">8</a>
<a href="#">7.2.</a>	<a href="#">Informative References</a>	<a href="#">9</a>
<a href="#">Appendix A.</a>	<a href="#">Change Log</a>	<a href="#">10</a>
	<a href="#">Authors' Addresses</a>	<a href="#">10</a>

## [1.](#) Introduction

The Registration Data Access Protocol (RDAP) is specified in multiple documents, including "Registration Data Access Protocol Lookup Format" [[I-D.ietf-weirds-rdap-query](#)], "JSON Responses for the Registration Data Access Protocol (RDAP)" [[I-D.ietf-weirds-json-response](#)], and "HTTP usage in the Registration Data Access Protocol (RDAP)" [[I-D.ietf-weirds-using-http](#)].

One goal of RDAP is to provide security services that do not exist in the WHOIS [[RFC3912](#)] protocol, including authentication, authorization, availability, data confidentiality, and data integrity. This document describes how each of these services is achieved by RDAP. Where applicable, informational references to requirements for a WHOIS replacement service [[RFC3707](#)] are noted.

## [2.](#) Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].



### **2.1. Acronyms and Abbreviations**

DNR: Domain Name Registry

HTTP: Hypertext Transfer Protocol

JSON: JavaScript Object Notation

RDAP: Registration Data Access Protocol

RIR: Regional Internet Registry

TLS: Transport Layer Security

## **3. Information Security Services and RDAP**

RDAP itself does not include native security services. Instead, RDAP relies on features that are available in other protocol layers to provide needed security services including authentication, authorization, availability, data confidentiality, and data integrity. A description of each of these security services can be found in "Internet Security Glossary, Version 2" [[RFC4949](#)]. No requirements have been identified for other security services.

### **3.1. Authentication**

WHOIS does not provide features to identify and authenticate clients. As noted in [section 3.1.4.2](#) of "Cross Registry Internet Service Protocol (CRISP) Requirements" [[RFC3707](#)], there is utility in allowing server operators to offer "varying degrees of access depending on policy and need". Clients have to be identified and authenticated to provide that utility.

RDAP's authentication framework needs to accommodate anonymous access as well as verification of identities using a range of authentication methods and credential services. To that end, RDAP clients and servers MUST implement the authentication framework specified in "HTTP Authentication: Basic and Digest Access Authentication" [[RFC2617](#)]. The "basic" scheme can be used to send a client's user name and password to a server in plaintext, base64-encoded form. The "digest" scheme can be used to authenticate a client without exposing the client's plaintext password. If the "basic" scheme is used, HTTP Over TLS [[RFC2818](#)] MUST be used to protect the client's credentials from disclosure while in transit (see [Section 3.4](#)).

Servers MUST support either Basic or Digest authentication; they are not required to support both. Clients MUST support both to interoperate with servers that support one or the other.



The Transport Layer Security Protocol [[RFC5246](#)] includes an optional feature to identify and authenticate clients who possess and present a valid X.509 digital certificate [[RFC5280](#)]. Support for this feature is OPTIONAL.

RDAP does not impose any unique server authentication requirements. The server authentication provided by TLS fully addresses the needs of RDAP. In general, transports for RDAP must either provide a TLS-protected transport (e.g., HTTPS) or a mechanism that provides an equivalent level of server authentication.

Work on HTTP authentication methods continues. RDAP ought to be agile enough to support additional methods as they are defined.

### **3.1.1. Federated Authentication**

The traditional client-server authentication model requires clients to maintain distinct credentials for every RDAP server. This situation can become unwieldy as the number of RDAP servers increases. Federated authentication mechanisms allow clients to use one credential to access multiple RDAP servers and reduce client credential management complexity. RDAP MAY include a federated authentication mechanism that permits a client to access multiple RDAP servers in the same federation with one credential.

Federated authentication mechanisms used by RDAP are OPTIONAL. If used, they MUST be fully supported by HTTP. OAuth, OpenID, and CA-based mechanisms are three possible approaches to provide federated authentication.

The OAuth authorization framework [[RFC6749](#)] describes a method for users to access protected web resources without having to hand out their credentials. Instead, clients are issued access tokens by authorization servers with the permission of the resource owners. Using OAuth, multiple RDAP servers can form a federation and the clients can access any server in the same federation by providing one credential registered in any server in that federation. The OAuth authorization framework is designed for use with HTTP and thus can be used with RDAP.

OpenID [[OpenID](#)] is a decentralized single sign-on authentication system that allows users to log in at multiple web sites with one ID instead of having to create multiple unique accounts. An end user can freely choose which OpenID provider to use, and can preserve their Identifier if they switch OpenID providers.

Note that OAuth and OpenID do not consistently require data confidentiality services to protect interactions between providers



and consumers. HTTP Over TLS [[RFC2818](#)] can be used as needed to provide protection against man-in-the-middle attacks.

The Transport Layer Security Protocol [[RFC5246](#)], [Section 7.4.6](#), describes the specification of a client certificate. Clients who possess and present a valid X.509 digital certificate, issued by an entity called a "Certification Authority" (CA), could be identified and authenticated by a server who trusts the corresponding CA. A certificate authentication method can be used to achieve federated authentication in which multiple RDAP servers all trust the same CAs and then any client with a certificate issued by a trusted CA can access any RDAP server in the federation. This certificate-based mechanism is supported by HTTPS and can be used with RDAP.

### **[3.2.](#) Authorization**

WHOIS does not provide services to grant different levels of access to clients based on a client's authenticated identity. As noted in [section 3.1.4.2](#) of "Cross Registry Internet Service Protocol (CRISP) Requirements" [[RFC3707](#)], there is utility in allowing server operators to offer "varying degrees of access depending on policy and need". Access control decisions can be made once a client's identity has been established and authenticated (see [Section 3.1](#)).

Server operators SHOULD offer varying degrees of access depending on policy and need in conjunction with the authentication methods described in [Section 3.1](#). If such varying degrees of access are supported, an RDAP server MUST provide granular access controls (that is, on a per registration data object basis) in order to implement authorization policies. Some examples:

- Clients will be allowed access only to data for which they have a relationship.
- Unauthenticated or anonymous access status may not yield any contact information.
- Full access may be granted to a special group of authenticated clients.

The type of access allowed by a server will most likely vary from one operator to the next.

### **[3.3.](#) Availability**

An RDAP service has to be available to be useful. There are no RDAP-unique requirements to provide availability, but as a general security consideration a service operator needs to be aware of the





issues associated with denial of service. A thorough reading of "Internet Denial-of-Service Considerations" [[RFC4732](#)] is advised.

An RDAP service MAY use a throttling mechanism to limit the number of queries that a single client can send in a given period of time. If used, the server SHOULD return a 429 response code as described in "Additional HTTP Status Codes" [[RFC6585](#)]. A client that receives a 429 response SHOULD decrease its query rate, and honor the Retry-After header field if one is present. Note that this is not a defense against denial-of-service attacks, since a malicious client could ignore the code and continue to send queries at a high rate. A server might use another response code if it did not wish to reveal to a client that rate limiting is the reason for the denial of a reply.

### **[3.4.](#) Data Confidentiality**

WHOIS does not provide the ability to protect data from inadvertent disclosure while in transit. Web services such as RDAP commonly use HTTP Over TLS [[RFC2818](#)] to provide that protection by encrypting all traffic sent on the connection between client and server. It is also possible to encrypt discrete objects (such as command path segments and JSON-encoded response objects) at one endpoint, send them to the other endpoint via an unprotected transport protocol, and decrypt the object on receipt. Encryption algorithms as described in "Internet Security Glossary, Version 2" [[RFC4949](#)] are commonly used to provide data confidentiality at the object level.

There are no current requirements for object-level data confidentiality using encryption. Support for this feature could be added to RDAP in the future.

As noted in [Section 3.1](#), the HTTP "basic" authentication scheme can be used to authenticate a client. When this scheme is used, HTTP Over TLS MUST be used to protect the client's credentials from disclosure while in transit. If the policy of the server operator requires encryption to protect client-server data exchanges (such as to protect non-public data that can not be accessed without client identification and authentication), HTTP Over TLS MUST be used to protect those exchanges.

### **[3.5.](#) Data Integrity**

WHOIS does not provide the ability to protect data from modification while in transit. Web services such as RDAP commonly use HTTP Over TLS [[RFC2818](#)] to provide that protection by using a keyed Message Authentication Code (MAC) to detect modifications. It is also possible to sign discrete objects (such as command path segments and



JSON-encoded response objects) at one endpoint, send them to the other endpoint via a transport protocol, and validate the signature of the object on receipt. Digital signature algorithms as described in "Internet Security Glossary, Version 2" [RFC4949] are commonly used to provide data integrity at the object level.

There are no current requirements for object-level data integrity using digital signatures. Support for this feature could be added to RDAP in the future.

The most specific need for this service is to provide assurance that HTTP 30x redirection hints [RFC2616] and response elements returned from the server are not modified while in transit. If the policy of the server operator requires message integrity for client-server data exchanges, HTTP Over TLS MUST be used to protect those exchanges.

#### **4. IANA Considerations**

This document does not specify any IANA actions. This section can be removed if this document is published as an RFC.

#### **5. Security Considerations**

One of the goals of RDAP is to provide security services that do not exist in the WHOIS protocol. This document describes the security services provided by RDAP and associated protocol layers, including authentication, authorization, availability, data confidentiality, and data integrity. Non-repudiation services were also considered and ultimately rejected due to a lack of requirements. There are, however, currently-deployed WHOIS servers that can return signed responses that provide non-repudiation with proof of origin. RDAP might need to be extended to provide this service in the future.

As an HTTP-based protocol RDAP is susceptible to code injection attacks. Code injection refers to adding code into a computer system or program to alter the course of execution. There are many types of code injection, including SQL injection, dynamic variable or function injection, include file injection, shell injection, and HTML-script injection among others. Data confidentiality and integrity services provide a measure of defense against man-in-the-middle injection attacks, but vulnerabilities in both client-side and server-side software make it possible for injection attacks to succeed. Consistently checking and validating server credentials can help detect man-in-the-middle attacks.

As noted in [Section 3.1.1](#), digital certificates can be used to implement federated authentication. There is a risk of too-promiscuous, or even rogue, CAs being included in the list of



acceptable CAs that the TLS server sends the client as part of the TLS client-authentication handshake and lending the appearance of trust to certificates signed by those CAs. Periodic monitoring of the list of CAs that RDAP servers trust for client authentication can help reduce this risk.

The Transport Layer Security Protocol [[RFC5246](#)] includes a null cipher suite that does not encrypt data and thus does not provide data confidentiality. This option must not be used when data confidentiality services are needed.

Data integrity services are sometimes mistakenly associated with directory service operational policy requirements focused on data accuracy. "Accuracy" refers to the truthful association of data elements (such as names, addresses, and telephone numbers) in the context of a particular directory object (such as a domain name). Accuracy requirements are out of scope for this protocol.

Additional security considerations are described in the specifications for HTTP [[RFC2616](#)], HTTP basic and digest access authentication [[RFC2617](#)], HTTP Over TLS [[RFC2818](#)], and additional HTTP status codes [[RFC6585](#)]. Security considerations for federated authentication systems can be found in the OAuth [[RFC6749](#)] and OpenID [[OpenID](#)] specifications.

## **6. Acknowledgements**

The authors would like to acknowledge the following individuals for their contributions to this document: Richard Barnes, Marc Blanchet, Ernie Dainow, Spencer Dawkins, Jean-Philippe Dionne, Byron Ellacott, Stephen Farrell, Tony Hansen, Peter Koch, Murray Kucherawy, Barry Leiba, Andrew Newton, and Linlin Zhou.

## **7. References**

### **7.1. Normative References**

- [I-D.ietf-weirds-json-response]  
Newton, A. and S. Hollenbeck, "JSON Responses for the Registration Data Access Protocol (RDAP)", [draft-ietf-weirds-json-response-07](#) (work in progress), April 2014.
- [I-D.ietf-weirds-rdap-query]  
Newton, A. and S. Hollenbeck, "Registration Data Access Protocol Query Format", [draft-ietf-weirds-rdap-query-11](#) (work in progress), July 2014.



[I-D.ietf-weirds-using-http]

Newton, A., Ellacott, B., and N. Kong, "HTTP usage in the Registration Data Access Protocol (RDAP)", [draft-ietf-weirds-using-http-08](#) (work in progress), February 2014.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.

[RFC2617] Franks, J., Hallam-Baker, P., Hostetler, J., Lawrence, S., Leach, P., Luotonen, A., and L. Stewart, "HTTP Authentication: Basic and Digest Access Authentication", [RFC 2617](#), June 1999.

[RFC2818] Rescorla, E., "HTTP Over TLS", [RFC 2818](#), May 2000.

[RFC6585] Nottingham, M. and R. Fielding, "Additional HTTP Status Codes", [RFC 6585](#), April 2012.

## **[7.2. Informative References](#)**

[OpenID] OpenID Foundation, "OpenID Authentication 2.0 - Final", December 2007, <<http://specs.openid.net/auth/2.0>>.

[RFC3707] Newton, A., "Cross Registry Internet Service Protocol (CRISP) Requirements", [RFC 3707](#), February 2004.

[RFC3912] Daigle, L., "WHOIS Protocol Specification", [RFC 3912](#), September 2004.

[RFC4732] Handley, M., Rescorla, E., and IAB, "Internet Denial-of-Service Considerations", [RFC 4732](#), December 2006.

[RFC4949] Shirey, R., "Internet Security Glossary, Version 2", [RFC 4949](#), August 2007.

[RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), August 2008.

[RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 5280](#), May 2008.





[RFC6749] Hardt, D., "The OAuth 2.0 Authorization Framework", [RFC 6749](#), October 2012.

## [Appendix A](#). Change Log

Initial -00: Adopted as working group document.

- 01: Extensive text additions and revisions based on in-room discussion at IETF-85. Sections for data integrity and non-repudiation have been removed due to a lack of requirements, but both topics are now addressed in the Security Considerations section.
- 02: Fixed document names in the Introduction. Modified text in [Section 3.1.1](#) to clarify requirement. Added text to [Section 3.3](#) to describe rate limiting. Added new data integrity section. Updated security considerations to describe injection attacks.
- 03: Extensive updates to address WG last call comments: rewrote introduction, removed references to draft documents, changed "HTML" to "HTTP" in [Section 5](#), eliminated upper case words that could be misunderstood to be normative guidance, rewrote [Section 3.4](#) and [Section 3.5](#).
- 04: Address AD evaluation comments: In [Section 3.1](#) change "RDAP MUST include an authentication framework that can accommodate" to "RDAP's authentication framework needs to accommodate"; in [Section 3.2](#) change "RDAP MUST include an authorization framework that is capable of providing granular (per registration data object) access controls according to the policies of the operator" to "An RDAP server MUST provide granular access controls (that is, on a per registration data object basis) in order to implement authorization policies"; move RFCs 4732, 5280, and 6749 from normative to informative subsection.
- 05: Address IETF last call comments: Added text to [Section 3.1.1](#) to recommend the use of HTTP over TLS. Modified [Section 3.2](#) to clarify granular access control text. Added additional Security Considerations. Made references to [RFC 5246](#) and OpenID informative. Minor typo fixes.
- 06: Keepalive refresh. No content updates.
- 07: Keepalive refresh. No content updates.

## Authors' Addresses

Scott Hollenbeck  
Verisign Labs  
12061 Bluemont Way  
Reston, VA 20190  
US

Email: [shollenbeck@verisign.com](mailto:shollenbeck@verisign.com)  
URI: <http://www.verisignlabs.com/>



Ning Kong  
China Internet Network Information Center  
4 South 4th Street, Zhongguancun, Haidian District  
Beijing 100190  
China

Phone: +86 10 5881 3147

Email: [nkong@cnnic.cn](mailto:nkong@cnnic.cn)