Network Working Group Internet-Draft Expires: August 22, 2003

P. Saint-Andre Jabber Software Foundation J. Hildebrand Jabber, Inc. February 21, 2003

Nodeprep: A Stringprep Profile for Node Identifiers in XMPP draft-ietf-xmpp-nodeprep-01

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of Section 10 of RFC2026.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at http:// www.ietf.org/ietf/1id-abstracts.txt.

The list of Internet-Draft Shadow Directories can be accessed at http://www.ietf.org/shadow.html.

This Internet-Draft will expire on August 22, 2003.

Copyright Notice

Copyright (C) The Internet Society (2003). All Rights Reserved.

Abstract

This document defines a stringprep profile for node identifiers in the eXtensible Messaging and Presence Protocol (XMPP).

T 1	AL I	- I 0000
Internet-Draft	Nodeprep	February 2003

Table of Contents

<u>1</u> .	Introduction	3
<u>1.1</u>	Terminology	<u>3</u>
<u>1.2</u>	Discussion Venue	<u>3</u>
<u>1.3</u>	Intellectual Property Notice	3
<u>2</u> .	Character Repertoire	<u>5</u>
<u>3</u> .	Mapping	<u>6</u>
<u>4</u> .	Normalization	7
<u>5</u> .	Prohibited Output	8
<u>6</u> .	Bidirectional Characters	9
<u>7</u> .	Security Considerations	<u>10</u>
<u>8</u> .	IANA Considerations	11
	References	12
	Authors' Addresses	12
<u>A</u> .	Revision History	<u>13</u>
<u>A.1</u>	Changes from <u>draft-ietf-xmpp-nodeprep-00</u>	<u>13</u>
	Full Copyright Statement	14

Internet-Draft Nodeprep February 2003

1. Introduction

This document, which defines a profile of stringprep (RFC 3454 [1]), specifies processing rules that will enable users to enter internationalized node identifiers in XMPP (see XMPP Core [2]) and have the highest chance of getting the content of the strings correct. These processing rules are intended for XMPP node identifiers only, and not for arbitrary text.

This profile defines the following, as required by RFC 3454 [1]:

- o The intended applicability of the profile: internationalized node identifiers within XMPP
- o The character repertoire that is the input and output to stringprep: Unicode 3.2, specified in <u>section 2</u>
- o The mappings used: specified in section 3
- o The Unicode normalization used: specified in section 4
- o The characters that are prohibited as output: specified in $\underline{\text{section}}$ $\underline{5}$
- o Bidirectional character handling: specified in section 6

1.1 Terminology

This document inherits the terminology defined in XMPP Core [2].

The capitalized key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [3].

1.2 Discussion Venue

The authors welcome discussion and comments related to the topics presented in this document. The preferred forum is the <mppwg@jabber.org> mailing list, for which archives and subscription information are available at <http://www.jabber.org/cgi-bin/mailman/listinfo/xmppwg/>.

1.3 Intellectual Property Notice

This document is in full compliance with all provisions of <u>Section 10</u> of <u>RFC 2026</u>. Parts of this specification use the term "jabber" for

identifying namespaces and other protocol syntax. Jabber[tm] is a registered trademark of Jabber, Inc. Jabber, Inc. grants permission to the IETF for use of the Jabber trademark in association with this specification and its successors, if any.

2. Character Repertoire

This profile uses Unicode 3.2 with the list of unassigned code points being Table A.1, both defined in Appendix A of RFC 3454 [1].

3. Mapping

This profile specifies mapping using the following tables from ${\underline{\tt RFC}}$ <u>3454</u> [<u>1</u>]:

Table B.1

Table B.2

4. Normalization

This profile specifies using Unicode normalization form KC, as described in RFC 3454 [1].

5. Prohibited Output

This profile specifies prohibiting use of the following tables from $\overline{\text{RFC 3454}}$ [1].

Table C.1.1

Table C.1.2

Table C.2.1

Table C.2.2

Table C.3

Table C.4

Table C.5

Table C.6

Table C.7

Table C.8

Table C.9

In addition, the following Unicode characters are also prohibited:

#x22 (")

#x26 (&)

#x27 (')

#x2F (/)

#x3A (:)

#x3C (<)

#x3E (>)

#x40 (@)

6. Bidirectional Characters

This profile specifies checking bidirectional strings as described in <u>section 6 of RFC 3454</u> [1].

7. Security Considerations

The Unicode and ISO/IEC 10646 repertoires have many characters that look similar. In many cases, users of security protocols might do visual matching, such as when comparing the names of trusted third parties. Because it is impossible to map similar-looking characters without a great deal of context such as knowing the fonts used, stringprep does nothing to map similar-looking characters together nor to prohibit some characters because they look like others.

Node identifiers are commonly employed as the username of users who connect to XMPP servers for instant messaging and presence services. The security of such services could be compromised if a user entering a single internationalized node identifier could access another user's account information based on different interpretations of the internationalized node identifier.

8. IANA Considerations

This is a profile of stringprep. If and when it becomes an RFC, it should be registered in the stringprep profile registry maintained by the IANA [4].

Name of this profile:

Nodeprep

RFC in which the profile is defined:

This document

Indicator whether or not this is the newest version of the profile:

This is the first version of Nodeprep

Internet-Draft Nodeprep February 2003

References

[1] Hoffman, P. and M. Blanchet, "Preparation of Internationalized Strings ("stringprep")", <u>RFC 3454</u>, December 2002.

- [2] Saint-Andre, P. and J. Miller, "XMPP Core (<u>draft-ietf-xmpp-core-03</u>, work in progress)", February 2003.
- [3] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, March 1997.
- [4] Internet Assigned Numbers Authority, "Internet Assigned Numbers Authority", January 1998, http://www.iana.org/>.

Authors' Addresses

Peter Saint-Andre Jabber Software Foundation

EMail: stpeter@jabber.org

URI: http://www.jabber.org/people/stpeter.php

Joe Hildebrand Jabber, Inc.

EMail: jhildebrand@jabber.com

URI: http://www.jabber.org/people/hildjj.php

<u>Appendix A</u>. Revision History

Note to RFC editor: please remove this entire appendix, and the corresponding entries in the table of contents, prior to publication.

A.1 Changes from <u>draft-ietf-xmpp-nodeprep-00</u>

o Clarified references to Unicode 3.2 and unassigned code points.

Full Copyright Statement

Copyright (C) The Internet Society (2003). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.