

Audio/Video Transport Working Group	G. Hunt
Internet-Draft	Unaffiliated
Intended status: Standards Track	A. Clark
Expires: April 19, 2012	Telchemy
	R. Huang, Ed.
	Q. Wu
	Huawei
	October 17, 2011

RTCP XR Report Block for Burst/Gap Discard metric Reporting
draft-ietf-xrblock-rtcp-xr-burst-gap-discard-00.txt

[Abstract](#)

This document defines an RTCP XR Report Block that allows the reporting of Burst and Gap Discard metrics for use in a range of RTP applications.

[Status of this Memo](#)

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 19, 2012.

[Copyright Notice](#)

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

[Table of Contents](#)

- *1. [Introduction](#)

- *1.1. [Burst and Gap Discard Report Block](#)
- *1.2. [RTCP and RTCP XR Reports](#)
- *1.3. [Performance Metrics Framework](#)
- *1.4. [Applicability](#)
- *2. [Terminology](#)
- *2.1. [Standards Language](#)
- *3. [Burst/Gap Discard Block](#)
- *3.1. [Report Block Structure](#)
- *3.2. [Definition of Fields in Burst/Gap Loss Report Block](#)
- *3.3. [Derived metrics based on reported metrics](#)
- *4. [Considerations for Voice-over-IP applications](#)
- *5. [SDP Signaling](#)
- *6. [IANA Considerations](#)
- *6.1. [New RTCP XR Block Type value](#)
- *6.2. [New RTCP XR SDP Parameter](#)
- *6.3. [Contact information for registrations](#)
- *7. [Security Considerations](#)
- *8. [Contributors](#)
- *9. [Changes from previous version](#)
- *10. [References](#)
- *10.1. [Normative References](#)
- *10.2. [Informative References](#)
- *[Authors' Addresses](#)

1. Introduction

1.1. Burst and Gap Discard Report Block

This draft defines a new block type to augment those defined in [\[RFC3611\]](#) for use in a range of RTP applications. The new block type supports the reporting of the proportion of packets discarded by the receiver due to jitter. The discards during discard bursts are reported, together with the number of bursts and additional data allowing the calculation of statistical parameters (mean and variance) of the distribution of burst lengths. This block is intended to be used in conjunction with [\[DISCARD\]](#) which provides the total packets discarded, and on which this block therefore depends. However the metric in [\[DISCARD\]](#) may be used independently of the metrics in this block.

This block provides information on transient IP problems. Burst/Gap metrics are typically used in Cumulative reports however MAY be used in Interval reports. The burstiness of packet discard affects user experience, may influence any sender strategies to mitigate the problem, and may also have diagnostic value.

The metric belongs to the class of transport-related terminal metrics defined in [\[MONARCH\]](#) (work in progress).

The definitions of Burst, Gap, Loss and Discard are consistent with definitions in [\[RFC3611\]](#). To accommodate the range of jitter buffer algorithms and packet discard logic that may be used by implementors, the method used to distinguish between bursts and gaps may be an equivalent method to that defined in [\[RFC3611\]](#).

1.2. RTCP and RTCP XR Reports

The use of RTCP for reporting is defined in [\[RFC3550\]](#). [\[RFC3611\]](#) defined an extensible structure for reporting using an RTCP Extended Report (XR). This draft defines a new Extended Report block that MUST be used as defined in [\[RFC3550\]](#) and [\[RFC3611\]](#).

1.3. Performance Metrics Framework

The Performance Metrics Framework [\[PMOLFRAME\]](#) provides guidance on the definition and specification of performance metrics. Metrics described in this draft either reference external definitions or define metrics generally in accordance with the guidelines in [\[PMOLFRAME\]](#).

1.4. Applicability

These metrics are applicable to a range of RTP applications.

2. Terminology

2.1. Standards Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [RFC2119]. In addition, the following terms are defined:

Received, Lost and Discarded

A packet shall be regarded as lost if it fails to arrive within an implementation-specific time window. A packet that arrives within this time window but is too early or late to be played out shall be regarded as discarded. A packet shall be classified as one of received (or OK), discarded or lost.

Bursts and Gaps

The terms Burst and Gap are used in a manner consistent with that of RTCP XR [RFC3611]. RTCP XR views a RTP stream as being divided into bursts, which are periods during which the loss rate is high enough to cause noticeable quality degradation (generally over 5 percent loss rate), and gaps, which are periods during which lost packets are infrequent and hence quality is generally acceptable.

3. Burst/Gap Discard Block

Metrics in this block report on Burst/Gap Loss in the stream arriving at the RTP system.

3.1. Report Block Structure

[illegible]

Delay metrics block

3.2. Definition of Fields in Burst/Gap Loss Report Block

Block type (BT): 8 bits

A Burst/Gap Loss Report Block is identified by the constant NBGL.

[Note to RFC Editor: please replace NBGL with the IANA provided RTCP XR block type for this block.]

Interval Metric flag (I): 1 bit

This field is used to indicate whether the Packet Delay Variation metrics block is an Interval or a Cumulative report, that is, whether the reported values apply to the most recent measurement interval duration between successive metrics reports (I=1) (the Interval Duration) or to the accumulation period characteristic of cumulative measurements (I=0) (the Cumulative Duration).

Reserved (resv): 7 bits

These bits are reserved. They SHOULD be set to zero by senders and MUST be ignored by receivers.

block length: 16 bits

The length of this report block in 32-bit words, minus one. For the Delay block, the block length is equal to 5.

SSRC of source: 32 bits

As defined in Section 4.1 of [\[RFC3611\]](#).

Threshold: 8 bits

The Threshold is equivalent to Gmin in [\[RFC3611\]](#), i.e. the number of successive packets that must be received prior to and following a lost frame in order for this lost frame to be regarded as part of a gap.

Sum of Burst Durations (ms): 24 bits

The total duration of bursts of lost frames in the period of the report (Interval or Cumulative).

If the measured value exceeds 0xFFFFFD, the value 0xFFFFFE SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFFF SHOULD be reported.

Packets lost in bursts: 24 bits

The total number of packets lost during loss bursts.

If the measured value exceeds 0xFFFFFD, the value 0xFFFFFE SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFFF SHOULD be reported.

Total packets expected in bursts: 24 bits

The total number of packets expected during loss bursts (that is, the sum of received packets and lost packets).

If the measured value exceeds 0xFFFFFD, the value 0xFFFFFE SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFFF SHOULD be reported.

Number of bursts: 16 bits

The number of bursts in the period of the report (Interval or Cumulative).

If the measured value exceeds 0xFFFFD, the value 0xFFFFE SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFF SHOULD be reported.

Sum of Squares of Burst Durations (ms-squared): 36 bits

The sum of the squares of burst durations (where individual burst durations are expressed in ms) over in the period of the report (Interval or Cumulative). The units for this quantity are milliseconds-squared.

If the measured value exceeds 0xFFFFFFFFD, the value 0xFFFFFFFFFE SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFFFFFF SHOULD be reported.

3.3. Derived metrics based on reported metrics

The metrics described here are intended to be used as described in this section, in conjunction with information from the Measurement Information block (which MUST be present in the same RTCP packet as the Burst/Gap Loss block) and also with the metric "cumulative number of packets lost" provided in standard RTCP [\[RFC3550\]](#). These metrics provides information relevant to statistical parameters, including:

- *The fraction of packets discarded during bursts
- *The fraction of packets discarded during gaps
- *burst duration mean
- *burst duration variance

The details on calculation these parameters in the metrics are described in [\[SUMSTAT\]](#).

4. Considerations for Voice-over-IP applications

This metric block is applicable to a broad range of RTP applications. Where the metric is used with a Voice-overIP (VoIP) application, the following considerations apply.

RTCP XR views a call as being divided into bursts, which are periods during which the loss rate is high enough to cause noticeable call quality degradation (generally over 5 percent loss rate), and gaps, which are periods during which lost packets are infrequent and hence call quality is generally acceptable.

If Voice Activity Detection is used the Burst and Gap Duration shall be determined as if silence frames had been sent, i.e. a period of silence in excess of Gmin frames MUST terminate a burst condition.

The recommended value for the threshold Gmin in [\[RFC3611\]](#) results in a Burst being a period of time during which the call quality is degraded to a similar extent to a typical PCM Severely Errored Second [\[SDES\]](#).

5. SDP Signaling

[\[RFC3611\]](#) defines the use of SDP (Session Description Protocol) [\[RFC4566\]](#) for signaling the use of XR blocks. XR blocks MAY be used without prior signaling.

```
rtcp-xr-attrib = "a=" "rtcp-xr" ":" [xr-format *(SP xr-format)] CRLF
```

(defined in [RFC3611])

```
xr-format =/ xr-bgd-block
```

```
xr-bgd-block = "brst-gap-dscrd"
```

This section augments the SDP [\[RFC4566\]](#) attribute "rtcp-xr" defined in [\[RFC3611\]](#) by providing an additional value of "xr-format" to signal the use of the report block defined in this document.

[6. IANA Considerations](#)

New block types for RTCP XR are subject to IANA registration. For general guidelines on IANA considerations for RTCP XR, refer to [\[RFC3611\]](#).

[6.1. New RTCP XR Block Type value](#)

This document assigns the block type value NDEL in the IANA "RTCP XR Block Type Registry" to the "Burst/Gap Discard Metrics Block".
[Note to RFC Editor: please replace NBDG with the IANA provided RTCP XR block type for this block.]

[6.2. New RTCP XR SDP Parameter](#)

This document also registers a new parameter "brst-gap-dscrd" in the "RTCP XR SDP Parameters Registry".

[6.3. Contact information for registrations](#)

The contact information for the registrations is:

Geoff Hunt (r.geoff.hunt@gmail.com)

Orion 2 PP3, Adastral Park, Martlesham Heath, Ipswich IP5 3RE, United Kingdom

[7. Security Considerations](#)

It is believed that this proposed RTCP XR report block introduces no new security considerations beyond those described in [\[RFC3611\]](#). This block does not provide per-packet statistics so the risk to confidentiality documented in Section 7, paragraph 3 of [\[RFC3611\]](#) does not apply.

8. Contributors

The authors gratefully acknowledge the comments and contributions made by Bruce Adams, Philip Arden, Amit Arora, Bob Biskner, Kevin Connor, Claus Dahm, Randy Ethier, Roni Even, Jim Frauenthal, Albert Higashi, Tom Hock, Shane Holthaus, Paul Jones, Rajesh Kumar, Keith Lantz, Mohamed Mostafa, Amy Pendleton, Colin Perkins, Mike Ramalho, Ravi Raviraj, Albrecht Schwarz, Tom Taylor, and Hideaki Yamada.

9. Changes from previous version

Changed BNF for SDP following Christian Groves' and Tom Taylor's comments (4th and 5th May 2009), now aligned with RFC 5234 section 3.3 "Incremental Alternatives".
Updated references.

10. References

10.1. Normative References

[RFC2119]	Bradner, S. , "Key words for use in RFCs to Indicate Requirement Levels", March 1997.
[RFC3611]	Friedman, T., Caceres, R. and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", November 2003.
[RFC4566]	Handley, M., Jacobson, V. and C. Perkins, "SDP: Session Description Protocol", July 2006.
[RFC3550]	Schulzrinne, H., " RTP: A Transport Protocol for Real-Time Applications ", RFC 3550, July 2003.

10.2. Informative References

, "

[DISCARD]	Hunt, G., "RTCP XR Report Block for Discard metric Reporting", ID draft-ietf-rtcp-xr-discard-02, May 2009.
[SUMSTAT]	Zorn, G., "RTCP XR for Summary Statistics Metrics Reporting", ID draft-zorn-xrblock-rtcp-xr-al-stat-03, October 2011.
[MONARCH]	Hunt, G., "Monitoring Architectures for RTP", ID draft-ietf-avtcore-monarch-04, August 2011.
[PMOLFRAME]	Clark, A. and B. Claise, "Framework for Performance Metric Development", ID draft-ietf-pmol-metrics-framework-12, July 2011.
[SDES]	", URL http://www.its.bldrdoc.gov/projects/devglossary/_severely_errored_second.html , October 2011.

Authors' Addresses

Geoff Hunt Hunt Unaffiliated EMail: r.geoff.hunt@gmail.com

Alan Clark Clark Telchemy Incorporated 2905 Premiere Parkway, Suite 280 Duluth, GA 30097 USA EMail: alan.d.clark@telchemy.com

Rachel Huang editor Huang Huawei Technologies Co., Ltd. 101 Software Avenue, Yuhua District Nanjing, Jiangsu 210012 China EMail: Rachel@huawei.com

Qin Wu Wu Huawei 101 Software Avenue, Yuhua District Nanjing, Jiangsu 210012 China EMail: sunseawq@huawei.com