

Audio/Video Transport Working Group	G. Hunt
Internet-Draft	Unaffiliated
Intended status: Standards Track	A. Clark
Expires: April 19, 2012	Telchemy
	G. Zorn, Ed.
	Network Zen
	Q. Wu
	Huawei
	October 17, 2011

RTCP XR Report Block for Discard metric Reporting
draft-ietf-xrblock-rtcp-xr-discard-00.txt

[Abstract](#)

This document defines an RTCP XR Report Block that allows the reporting of a simple discard count metric for use in a range of RTP applications.

[Status of this Memo](#)

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 19, 2012.

[Copyright Notice](#)

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

[Table of Contents](#)

- *1. [Introduction](#)

- *1.1. [Discard Report Block](#)
- *1.2. [RTCP and RTCP XR Reports](#)
- *1.3. [Performance Metrics Framework](#)
- *1.4. [Applicability](#)
- *2. [Terminology](#)
- *2.1. [Standards Language](#)
- *3. [Discard Metric Report Block](#)
- *3.1. [Report Block Structure](#)
- *3.2. [Definition of Fields in Discard Metric Report Block](#)
- *4. [SDP Signaling](#)
- *5. [IANA Considerations](#)
- *5.1. [New RTCP XR Block Type value](#)
- *5.2. [New RTCP XR SDP Parameter](#)
- *5.3. [Contact information for registrations](#)
- *6. [Security Considerations](#)
- *7. [Contributors](#)
- *8. [Changes from previous version](#)
- *9. [References](#)
- *9.1. [Normative References](#)
- *9.2. [Informative References](#)
- *[Authors' Addresses](#)

[1. Introduction](#)

[1.1. Discard Report Block](#)

This draft defines a new block type to augment those defined in [\[RFC3611\]](#) for use in a range of RTP applications. The new block type supports the reporting of the number of packets which are received correctly but are never played out, typically because they arrive too late to be played out (buffer underflow) or too early (buffer

overflow). The metric is applicable both to systems which use packet loss repair techniques (such as forward error correction [\[RFC5109\]](#) or retransmission [\[RFC4588\]](#)) and to those which do not. This metric is useful for identifying the existence, and characterising the severity, of a packet transport problem which may affect users' perception of a service delivered over RTP. The metric belongs to the class of transport-related terminal metrics defined in [\[MONARCH\]](#) (work in progress).

[1.2.](#) RTCP and RTCP XR Reports

The use of RTCP for reporting is defined in [\[RFC3550\]](#). [\[RFC3611\]](#) defined an extensible structure for reporting using an RTCP Extended Report (XR). This draft defines a new Extended Report block that MUST be used as defined in [\[RFC3550\]](#) and [\[RFC3611\]](#).

[1.3.](#) Performance Metrics Framework

The Performance Metrics Framework [\[PMOLFRAME\]](#) provides guidance on the definition and specification of performance metrics. Metrics described in this draft either reference external definitions or define metrics generally in accordance with the guidelines in [\[PMOLFRAME\]](#).

[1.4.](#) Applicability

This metric is believed to be applicable to a large class of RTP applications which use a jitter buffer.

[2.](#) Terminology

[2.1.](#) Standards Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [\[RFC2119\]](#). In addition, the following terms are defined:


Received, Lost and Discarded

A packet shall be regarded as lost if it fails to arrive within an implementation-specific time window. A packet that arrives within this time window but is too early or late to be played out shall be regarded as discarded. A packet shall be classified as one of received (or OK), discarded or lost. The Discard Metric counts only discarded packets. The metric "cumulative number of packets lost" defined in [\[RFC3550\]](#) reports a count of packets lost from the media stream (single SSRC within single RTP session). Similarly the metric "number of packets discarded" reports a count of packets discarded from the media stream (single SSRC within single RTP session) arriving at the receiver. Another metric defined in [\[POSTREPAIRLOSS\]](#)

is available to report on packets which are not recovered by any repair techniques which may be in use.

3. Discard Metric Report Block

3.1. Report Block Structure



3.2. Definition of Fields in Discard Metric Report Block

Block type (BT): 8 bits

A Discard Metric Report Block is identified by the constant ND.

[Note to RFC Editor: please replace ND with the IANA provided RTCP XR block type for this block.]

Interval Metric flag (I): 1 bit

This field is used to indicate whether the Packet Delay Variation metrics block is an Interval or a Cumulative report, that is, whether the reported values apply to the most recent measurement interval duration between successive metrics reports (I=1) (the Interval Duration) or to the accumulation period characteristic of cumulative measurements (I=0) (the Cumulative Duration).

Reserved (resv): 7 bits

These bits are reserved. They SHOULD be set to zero by senders and MUST be ignored by receivers.

block length: 16 bits

The length of this report block in 32-bit words, minus one. For the Delay block, the block length is equal to 2.

SSRC of source: 32 bits

As defined in Section 4.1 of [\[RFC3611\]](#).

number of packets discarded: 32 bits

Number of packets discarded over the period (Interval or Cumulative) covered by this report.

If the measured value exceeds 0xFFFFFFFF, the value 0xFFFFFFFF SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFFFFFF SHOULD be reported.

Note that the number of packets expected in the period covered by the metric (whether interval or cumulative) is available from the difference between a pair of extended sequence numbers in the Measurement Identity block, so need not be repeated in this block.

[4. SDP Signaling](#)

[RFC3611] defines the use of SDP (Session Description Protocol) [\[RFC4566\]](#) for signaling the use of XR blocks. XR blocks MAY be used without prior signaling.

```
rtcp-xr-attrb = "a=" "rtcp-xr" ":" [xr-format *(SP xr-format)] CRLF
```

(defined in [RFC3611])

```
xr-format =/ xr-pd-block
```

```
xr-pd-block = "pkt-dscrd"
```

This section augments the SDP [\[RFC4566\]](#) attribute "rtcp-xr" defined in [\[RFC3611\]](#) by providing an additional value of "xr-format" to signal the use of the report block defined in this document.

[5. IANA Considerations](#)

New block types for RTCP XR are subject to IANA registration. For general guidelines on IANA considerations for RTCP XR, refer to [\[RFC3611\]](#).

[5.1. New RTCP XR Block Type value](#)

This document assigns the block type value ND in the IANA "RTCP XR Block Type Registry" to the "Discard Metrics Block".

[Note to RFC Editor: please replace ND with the IANA provided RTCP XR block type for this block.]

5.2. New RTCP XR SDP Parameter

This document also registers a new parameter "pkt-dscrd" in the "RTCP XR SDP Parameters Registry".

5.3. Contact information for registrations

The contact information for the registrations is:

Geoff Hunt (r.geoff.hunt@gmail.com)

Orion 2 PP3, Adastral Park, Martlesham Heath, Ipswich IP5 3RE, United Kingdom

6. Security Considerations

It is believed that this proposed RTCP XR report block introduces no new security considerations beyond those described in [\[RFC3611\]](#). This block does not provide per-packet statistics so the risk to confidentiality documented in Section 7, paragraph 3 of [\[RFC3611\]](#) does not apply.

7. Contributors

The authors gratefully acknowledge the comments and contributions made by Bruce Adams, Philip Arden, Amit Arora, Bob Biskner, Kevin Connor, Claus Dahm, Randy Ethier, Roni Even, Jim Frauenthal, Albert Higashi, Tom Hock, Shane Holthaus, Paul Jones, Rajesh Kumar, Keith Lantz, Mohamed Mostafa, Amy Pendleton, Colin Perkins, Mike Ramalho, Ravi Raviraj, Albrecht Schwarz, Tom Taylor, and Hideaki Yamada.

8. Changes from previous version

Changed BNF for SDP following Christian Groves' and Tom Taylor's comments (4th and 5th May 2009), now aligned with RFC 5234 section 3.3 "Incremental Alternatives".
Updated references.

9. References

9.1. Normative References

[RFC2119]	Bradner, S. , "Key words for use in RFCs to Indicate Requirement Levels", March 1997.
------------------	---

[RFC3611]	Friedman, T., Caceres, R. and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", November 2003.
[RFC4566]	Handley, M., Jacobson, V. and C. Perkins, "SDP: Session Description Protocol", July 2006.
[RFC3550]	Schulzrinne, H., " RTP: A Transport Protocol for Real-Time Applications ", RFC 3550, July 2003.

9.2. Informative References

[DISCARD]	Hunt, G., "RTCP XR Report Block for Discard metric Reporting", ID draft-ietf-rtcp-xr-discard-02, May 2009.
[MONARCH]	Wu, Q., "Monitoring Architectures for RTP", ID draft-ietf-avtcore-monarch-04, August 2011.
[PMOLFRAME]	Clark, A. and B. Claise, "Framework for Performance Metric Development", ID draft-ietf-pmol-metrics-framework-12, July 2011.
[POSTREPAIRLOSS]	Hunt, G., "RTCP XR Report Block for Post-Repair Loss metric Reporting", ID draft-ietf-rtcp-xr-postrepair-loss-02, May 2009.
[RFC4588]	Rey, J., " RTP Retransmission Payload Format ", RFC 4588, July 2006.
[RFC5109]	Li, A., " RTP Payload Format for Generic Forward Error Correction ", RFC 5109, July 2006.

[Authors' Addresses](#)

Geoff Hunt Hunt Unaffiliated EMail: r.geoff.hunt@gmail.com

Alan Clark Clark Telchemy Incorporated 2905 Premiere Parkway, Suite 280 Duluth, GA 30097 USA EMail: alan.d.clark@telchemy.com

Glen Zorn editor Zorn Network Zen 77/440 Soi Phoomjit, Rama IV Road Phra Khanong, Khlong Toie Bangkok, 10110 Thailand Phone: +66 (0) 87 502 4274 EMail: gwz@net-zen.net

Qin Wu Wu Huawei 101 Software Avenue, Yuhua District Nanjing, Jiangsu 210012 China EMail: sunseawq@huawei.com