

Audio/Video Transport Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: December 31, 2012

G. Hunt  
Unaffiliated  
A. Clark  
Telchemy  
G. Zorn  
Network Zen  
Q. Wu  
Huawei  
June 29, 2012

**RTCP XR Report Block for Discard Count metric Reporting**  
**draft-ietf-xrblock-rtcp-xr-discard-04.txt**

**Abstract**

This document defines an RTCP XR Report Block that allows the reporting of a simple discard count metric for use in a range of RTP applications.

**Status of this Memo**

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 31, 2012.

**Copyright Notice**

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">1.1.</a>	Discard Count Report Block . . . . .	<a href="#">3</a>
<a href="#">1.2.</a>	RTCP and RTCP XR Reports . . . . .	<a href="#">3</a>
<a href="#">1.3.</a>	Performance Metrics Framework . . . . .	<a href="#">3</a>
<a href="#">1.4.</a>	Applicability . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Terminology . . . . .	<a href="#">4</a>
<a href="#">2.1.</a>	Standards Language . . . . .	<a href="#">4</a>
<a href="#">3.</a>	Discard Count Metric Report Block . . . . .	<a href="#">5</a>
<a href="#">3.1.</a>	Report Block Structure . . . . .	<a href="#">5</a>
<a href="#">3.2.</a>	Definition of Fields in Discard Metric Report Block . . . . .	<a href="#">5</a>
<a href="#">4.</a>	SDP Signaling . . . . .	<a href="#">7</a>
<a href="#">5.</a>	IANA Considerations . . . . .	<a href="#">8</a>
<a href="#">5.1.</a>	New RTCP XR Block Type value . . . . .	<a href="#">8</a>
<a href="#">5.2.</a>	New RTCP XR SDP Parameter . . . . .	<a href="#">8</a>
<a href="#">5.3.</a>	Contact information for registrations . . . . .	<a href="#">8</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">9</a>
<a href="#">7.</a>	Acknowledgments . . . . .	<a href="#">10</a>
<a href="#">8.</a>	References . . . . .	<a href="#">11</a>
<a href="#">8.1.</a>	Normative References . . . . .	<a href="#">11</a>
<a href="#">8.2.</a>	Informative References . . . . .	<a href="#">11</a>
	Authors' Addresses . . . . .	<a href="#">12</a>



## **1. Introduction**

### **1.1. Discard Count Report Block**

This draft defines a new block type to augment those defined in [\[RFC3611\]](#) for use in a range of RTP applications. The new block type supports the reporting of the number of packets which are received correctly but are never played out, typically because they arrive too late to be played out (buffer underflow) or too early (buffer overflow). The metric is applicable both to systems which use packet loss repair techniques (such as forward error correction [\[RFC5109\]](#) or retransmission [\[RFC4588\]](#)) and to those which do not.

This metric is useful for identifying the existence, and characterising the severity, of a packet transport problem which may affect users' perception of a service delivered over RTP.

The metric belongs to the class of transport-related terminal metrics defined in [\[MONARCH\]](#) (work in progress).

### **1.2. RTCP and RTCP XR Reports**

The use of RTCP for reporting is defined in [\[RFC3550\]](#). [\[RFC3611\]](#) defined an extensible structure for reporting using an RTCP Extended Report (XR). This draft defines a new Extended Report block that MUST be used as defined in [\[RFC3550\]](#) and [\[RFC3611\]](#).

### **1.3. Performance Metrics Framework**

The Performance Metrics Framework [\[RFC6390\]](#) provides guidance on the definition and specification of performance metrics. The RTP Monitoring Architectures [\[MONARCH\]](#) provides guideline for reporting block format using RTCP XR. The Metrics Block described in this document are in accordance with the guidelines in [\[RFC6390\]](#) and [\[MONARCH\]](#).

### **1.4. Applicability**

This metric is believed to be applicable to a large class of RTP applications which use a jitter buffer.



## **2. Terminology**

### **2.1. Standards Language**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

In addition, the following terms are defined:

Received, Lost and Discarded

A packet shall be regarded as lost if it fails to arrive within an implementation-specific time window. A packet that arrives within this time window but is too early or late to be played out or thrown away before playout (e.g., packet duplication or redundancy) shall be regarded as discarded. A packet shall be classified as one of received (or OK), discarded or lost. The Discard Count Metric counts only discarded packets. The metric "cumulative number of packets lost" defined in [[RFC3550](#)] reports a count of packets lost from the media stream (single SSRC within single RTP session). Similarly the metric "number of packets discarded" reports a count of packets discarded from the media stream (single SSRC within single RTP session) arriving at the receiver. Another metric defined in [[RFC5725](#)] is available to report on packets which are not recovered by any repair techniques which may be in use.



### 3. Discard Count Metric Report Block

#### 3.1. Report Block Structure




Figure 1: Report Block Structure

#### 3.2. Definition of Fields in Discard Metric Report Block

Block type (BT): 8 bits

A Discard Count Metric Report Block is identified by the constant PDC.

[Note to RFC Editor: please replace PDC with the IANA provided RTCP XR block type for this block.]

Interval Metric flag (I): 2 bits

This field is used to indicate whether the Discard Count Metric is an Interval or Cumulative metric, Sample metric, that is, whether the reported values applies to the most recent measurement interval duration between successive metrics reports (I=10) (the Interval Duration) or to the accumulation period characteristic of cumulative measurements (I=11) (the Cumulative Duration) or is a sampled instantaneous value (I=01) (Sampled Value). In this document, Discard Count Metric is not measured at a particular time instant but over one or several reporting intervals. Therefore Discard Count Metric MUST not be chosen as Sampled Metric.

Discard Type (DT): 2bits

This field is used to identify the discard type used in this report block. The discard type is defined as follows:





00: Report packet discarded due to too early to be played out.

01: Report packet discarded due to too late to be played out.

10: Report packet discarded due to both early and late to be played out.

11: Report the total number of discarded packets in the interval. The reasons to discard packet include too early to be played out, too late to be played out, being thrown away before playout.

Reserved (resv): 5 bits

These bits are reserved. They SHOULD be set to zero by senders and MUST be ignored by receivers.

block length: 16 bits

The length of this report block in 32-bit words, minus one. For the Delay block, the block length is equal to 2.

SSRC of source: 32 bits

As defined in [Section 4.1 of \[RFC3611\]](#).

number of packets discarded: 32 bits

Number of packets discarded over the period (Interval or Cumulative) covered by this report.

If the measured value exceeds 0xFFFFFFFF, the value 0xFFFFFFFF MUST be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFFFFFF MUST be reported.

Note that the number of packets expected in the period covered by the metric (whether interval or cumulative) is available from the difference between a pair of extended sequence numbers in the Measurement Information block [[MEASI](#)], so need not be repeated in this block.



#### **4. SDP Signaling**

[RFC3611] defines the use of SDP (Session Description Protocol) [RFC4566] for signaling the use of XR blocks. XR blocks MAY be used without prior signaling.

This section augments the SDP [RFC4566] attribute "rtcp-xr" defined in [RFC3611] by providing an additional value of "xr-format" to signal the use of the report block defined in this document.

rtcp-xr-attrib = "a=" "rtcp-xr" ":" [xr-format \*(SP xr-format)] CRLF

(defined in [RFC3611])

xr-format =/ xr-pdc-block

xr-pdc-block = "pkt-dscrd-count"



## **5. IANA Considerations**

New block types for RTCP XR are subject to IANA registration. For general guidelines on IANA considerations for RTCP XR, refer to [\[RFC3611\]](#).

### **5.1. New RTCP XR Block Type value**

This document assigns the block type value PDC in the IANA "RTCP XR Block Type Registry" to the "Discard Count Metrics Block".

[Note to RFC Editor: please replace PDC with the IANA provided RTCP XR block type for this block.]

### **5.2. New RTCP XR SDP Parameter**

This document also registers a new parameter "pkt-dscrd" in the "RTCP XR SDP Parameters Registry".

### **5.3. Contact information for registrations**

The following contact information is provided for all registrations in this document:

Geoff Hunt (r.geoff.hunt@gmail.com)

Orion 2 PP3, Adastral Park, Martlesham Heath, Ipswich IP5 3RE, United Kingdom



## **6. Security Considerations**

It is believed that this proposed RTCP XR report block introduces no new security considerations beyond those described in [[RFC3611](#)]. This block does not provide per-packet statistics so the risk to confidentiality documented in [Section 7](#), paragraph 3 of [[RFC3611](#)] does not apply.



## **7. Acknowledgments**

The authors gratefully acknowledge the comments and contributions made by Bruce Adams, Philip Arden, Amit Arora, Bob Biskner, Kevin Connor, Claus Dahm, Randy Ethier, Roni Even, Jim Frauenthal, Albert Higashi, Tom Hock, Shane Holthaus, Paul Jones, Rajesh Kumar, Keith Lantz, Mohamed Mostafa, Amy Pendleton, Colin Perkins, Mike Ramalho, Ravi Raviraj, Albrecht Schwarz, Tom Taylor, and Hideaki Yamada, Kevin Gross, Varun Singh, Claire Bi, Roni Even, Dan Romascanu.

## **8. References**

### **8.1. Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", March 1997.
- [RFC3550] Schulzrinne, H., "RTP: A Transport Protocol for Real-Time Applications", [RFC 3550](#), July 2003.
- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", November 2003.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", July 2006.

### **8.2. Informative References**

- [MEASI] Hunt, G., "Measurement Identity and information Reporting using SDP item and XR Block", ID [draft-ietf-xrblock-rtcp-xr-meas-identity-06](#), April 2012.
- [MONARCH] Wu, Q., "Monitoring Architectures for RTP", ID [draft-ietf-avtcore-monarch-12](#), April 2012.
- [RFC4588] Rey, J., "RTP Retransmission Payload Format", [RFC 4588](#), July 2006.
- [RFC5109] Li, A., "RTP Payload Format for Generic Forward Error Correction", [RFC 5109](#), July 2006.
- [RFC5725] Begen, A., "RTCP XR Report Block for Post-Repair Loss metric Reporting", [RFC 5725](#), February 2010.
- [RFC6390] Clark, A. and B. Claise, "Framework for Performance Metric Development", [RFC 6390](#), October 2011.



Authors' Addresses

Geoff Hunt  
Unaffiliated

Email: [r.geoff.hunt@gmail.com](mailto:r.geoff.hunt@gmail.com)

Alan Clark  
Telchemy Incorporated  
2905 Premiere Parkway, Suite 280  
Duluth, GA 30097  
USA

Email: [alan.d.clark@telchemy.com](mailto:alan.d.clark@telchemy.com)

Glen Zorn  
Network Zen  
77/440 Soi Phoomjit, Rama IV Road  
Phra Khanong, Khlong Toie  
Bangkok 10110  
Thailand

Phone: +66 (0) 87 502 4274  
Email: [gwz@net-zen.net](mailto:gwz@net-zen.net)

Qin Wu  
Huawei  
101 Software Avenue, Yuhua District  
Nanjing, Jiangsu 210012  
China

Email: [sunseawq@huawei.com](mailto:sunseawq@huawei.com)

