

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: November 15, 2012

G. Hunt  
Unaffiliated  
A. Clark  
Telchemy  
Q. Wu  
Huawei  
R. Schott  
DT  
G. Zorn  
Network Zen  
May 14, 2012

**RTCP XR Blocks for QoE Metric Reporting**  
**draft-ietf-xrblock-rtcp-xr-qoe-01**

Abstract

This document defines an RTCP XR Report Block including two new segment types and associated SDP parameters that allow the reporting of QoE metrics for use in a range of RTP applications.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 15, 2012.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">1.1.</a>	QoE Metrics Report Block . . . . .	<a href="#">3</a>
<a href="#">1.2.</a>	RTCP and RTCP XR Reports . . . . .	<a href="#">3</a>
<a href="#">1.3.</a>	Performance Metrics Framework . . . . .	<a href="#">3</a>
<a href="#">1.4.</a>	Applicability . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Terminology . . . . .	<a href="#">4</a>
<a href="#">2.1.</a>	Standards Language . . . . .	<a href="#">4</a>
<a href="#">3.</a>	QoE Metrics Block . . . . .	<a href="#">5</a>
<a href="#">3.1.</a>	Metric Block Structure . . . . .	<a href="#">5</a>
<a href="#">3.2.</a>	Definition of Fields in QoE Metrics Block . . . . .	<a href="#">6</a>
<a href="#">3.2.1.</a>	Single Stream per SSRC Segment . . . . .	<a href="#">7</a>
<a href="#">3.2.2.</a>	Multi-Channel per SSRC Segment . . . . .	<a href="#">9</a>
<a href="#">4.</a>	SDP Signaling . . . . .	<a href="#">10</a>
<a href="#">5.</a>	IANA Considerations . . . . .	<a href="#">11</a>
<a href="#">5.1.</a>	New RTCP XR Block Type value . . . . .	<a href="#">11</a>
<a href="#">5.2.</a>	New RTCP XR SDP Parameter . . . . .	<a href="#">11</a>
<a href="#">5.3.</a>	Contact information for registrations . . . . .	<a href="#">11</a>
<a href="#">5.4.</a>	New registry of calculation algorithms for single stream per SSRC segment . . . . .	<a href="#">11</a>
<a href="#">5.5.</a>	New registry of calculation algorithms for multi-channel per SSRC segment . . . . .	<a href="#">12</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">13</a>
<a href="#">7.</a>	Authors . . . . .	<a href="#">13</a>
<a href="#">8.</a>	Acknowledgements . . . . .	<a href="#">13</a>
<a href="#">9.</a>	References . . . . .	<a href="#">13</a>
<a href="#">9.1.</a>	Normative References . . . . .	<a href="#">13</a>
<a href="#">9.2.</a>	Informative References . . . . .	<a href="#">14</a>
<a href="#">Appendix A.</a>	Change Log . . . . .	<a href="#">15</a>
<a href="#">A.1.</a>	<a href="#">draft-ietf-xrblock-rtcp-xr-qoe-01</a> . . . . .	<a href="#">15</a>
<a href="#">A.2.</a>	<a href="#">draft-ietf-xrblock-rtcp-xr-qoe-00</a> . . . . .	<a href="#">15</a>
	Authors' Addresses . . . . .	<a href="#">15</a>



## **1. Introduction**

### **1.1. QoE Metrics Report Block**

This draft defines a new block type to augment those defined in [[RFC3611](#)], for use in a range of RTP applications.

The new block type provides information on multimedia quality using one of several standard metrics.

The metrics belong to the class of application level metrics defined in [[MONARCH](#)] (work in progress).

### **1.2. RTCP and RTCP XR Reports**

The use of RTCP for reporting is defined in [[RFC3550](#)]. [[RFC3611](#)] defined an extensible structure for reporting using an RTCP Extended Report (XR). This draft defines a new Extended Report block that MUST be used as defined in [RFC3550](#) and [RFC3611](#).

### **1.3. Performance Metrics Framework**

The Performance Metrics Framework [[PMOL](#)] provides guidance on the definition and specification of performance metrics. Metrics described in this draft either reference external definitions or define metrics generally in accordance with the guidelines in [[PMOL](#)].

### **1.4. Applicability**

The QoE Metrics Report Block can be used in any application of RTP for which QoE measurement algorithms are defined.

The factors that affect real-time AV application quality can be split into two categories. The first category consists of transport-dependent factors such as packet loss, delay and jitter (which also translates into losses in the playback buffer). The factors in the second category are application-specific factors that affect real time application (e.g., video) quality and are sensitivity to network errors. These factors can be but not limited to video codec and loss recovery technique, coding bit rate, packetization scheme, and content characteristics.

Compared with application-specific factors, the transport-dependent factors sometimes are not sufficient to measure real time data quality, since the ability to analyze the real time data in the application layer provides quantifiable measurements for subscriber Quality of Experience (QoE) that may not be captured in the transmission layers or from the RTP layer down. In a typical



scenario, monitoring of the transmission layers can produce statistics suggesting that quality is not an issue, such as the fact that network jitter is not excessive. However, problems may occur in the service layers leading to poor subscriber QoE. Therefore monitoring using only network-level measurements may be insufficient when application layer content quality is required.

In order to provide accurate measures of real time application quality when transporting real time contents across a network, the synthetical multimedia quality Metrics is highly required which can be conveyed in the RTCP XR packets[RFC3611] and may have the following three benefits:

- o Tuning the content encoder algorithm to satisfy real time data quality requirements.
- o Determining which system techniques to use in a given situation and when to switch from one technique to another as system parameters change.
- o Verifying the continued correct operation of an existing system.

## **2. Terminology**

### **2.1. Standards Language**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

The terminology used is

Numeric formats S X:Y

where S indicates a two's complement signed representation, X the number of bits prior to the decimal place and Y the number of bits after the decimal place.

Hence 8:8 represents an unsigned number in the range 0.0 to 255.996 with a granularity of 0.0039. S7:8 would represent the range -127.996 to +127.996. 0:16 represents a proper binary fraction with range

0.0 to 1 - 1/65536 = 0.9999847

though note that use of flag values at the top of the numeric range slightly reduces this upper limit. For example, if the 16-bit values 0xffffe and 0xfffff are used as flags for "over-range" and "unavailable" conditions, a 0:16 quantity has range 0.0 to 1 - 3/65536 = 0.9999542



### **3. QoE Metrics Block**

This block reports the multimedia application performance or quality beyond the information carried in the standard RTCP packet format. Information is recorded about multimedia application QoE metric which provides a measure that is indicative of the user's view of a service. Multimedia application QoE metric is commonly expressed as a MOS ("Mean Opinion Score"), MOS is on a scale from 1 to 5, in which 5 represents excellent and 1 represents unacceptable. MOS scores are usually obtained using subjective testing or using objective algorithm. However Subjective testing to estimate the multimedia quality may be not suitable for measuring the multimedia quality since the results may vary from test to test. Therefore using objective algorithm to calculate MOS scores is recommended. ITU-T recommendations define the methodologies for assessment of the performance of multimedia stream


[[G.107](#)][P.564][[G.1082](#)][P.NAMS][[P.NBAMS](#)] and provides a method to evaluate QoE estimation algorithms and objective model for video and audio. Hence this document recommends vendors and implementers to use these International Telecommunication Union (ITU)-specified methodologies to measure parameters when possible.

#### **3.1. Metric Block Structure**

The report block contents are dependent upon a series of flag bits carried in the first part of the header. Not all parameters need to be reported in each block. Flags indicate which are and which are not reported. The fields corresponding to unreported parameters MUST be present, but are set to zero. The receiver MUST ignore any QoE Metrics Block with a non-zero value in any field flagged as unreported. The encoding of QoE metrics block payload consists of a series of 32 bit units called segments that describe MOS Type, MoS algorithm and MoS value.

The QoE Metrics Block has the following format:





### 3.2. Definition of Fields in QoE Metrics Block

Block type (BT): 8 bits

The QoE Metrics Block is identified by the constant <SMQ>.

Interval Metric flag (I): 2 bit

This field is used to indicate whether the QoE metrics are Interval or Cumulative metrics, that is, whether the reported values applies to the most recent measurement interval duration between successive metrics reports (I=10) (the Interval Duration) or to the accumulation period characteristic of cumulative measurements (I=11) (the Cumulative Duration) or is a sampled instantaneous value (I=01) (Sampled Value).

Rsd.:6 bits

This field is reserved for future definition. In the absence of such a definition, the bits in this field MUST be set to zero and MUST be ignored by the receiver.

Block Length: 16 bits

The length of this report block in 32-bit words, minus one. For the QoE Metrics Block, the block length is variable length.

SSRC of source: 32 bits

As defined in [Section 4.1 of \[RFC3611\]](#).



Segment i: 32 bits

There are two segment types defined in this document: single stream per SSRC segment, multi-channel audio per SSRC segment. Multi-channel per SSRC segment is used to deal with the case where multiple elementary streams or components are carried in one RTP stream while single stream per SSRC segment is used to deal with the case where there is no more than one elementary stream or component in one RTP stream. The left two bits of the section determine its type. If the leftmost bit of the segment is zero, then it is single stream segment. If the leftmost bit is one and the second bit is zero, then it is multi-channel audio segment. Note that two segment types can not be present in the same metric block.

### **3.2.1. Single Stream per SSRC Segment**

```

+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|0|R| MT |CAlg| PT |Rsv. | MOS Value |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Segment Type ( S): 1 bit

A zero identifies this as a single stream segment. Single stream means there is only one elementary stream carried in one RTP stream. The single stream segment can be used to report the MoS value associated with this elementary stream. If there are multiple streams and they want to use the single stream segment to report the MOS value, they should be carried in the separate RTP streams with different SSRC. In this case, multiple QoE Metrics Blocks are required to report the MOS value corresponding to each stream using single stream segment.

Reserved (R): 1bit

The bit in this field is reserved. It MUST be set to zero and MUST be ignored by the receiver if the leftmost bit of Single Stream Per SSRC Segment is set to 0.

MoS Type (MT): 4 bits

This field is used to indicate the MOS type to be reported. The MOS type is defined as follows:



0000 MOS-LQ - Listening Quality MoS.  
0001 MOS-CQ - Conversation Quality MoS.  
0010 MOS-A - Audio Quality MOS.  
0010 MOS-V - Video Quality MOS.  
0011 MOS-AV - Audio-Video Quality MOS.  
0100~1111 - Reserved for future definitions.

MoS-LQ measures the quality of audio for listening purposes only while MoS-CQ measures the quality of audio for conversation purpose only. MoS-A, MoS-V and MoS-AV measures the quality of audio application, the quality of video application and Audio-Video application respectively. Both MoS-LQ and MoS-CQ are commonly used in VoIP applications. MOS-LQ uses either wideband audio codec or narrowband audio codec, or both and does not take into account any of bidirectional effects, such as delay and echo. MOS-CQ uses narrowband codec and takes into account listening quality in each direction, as well as the bidirectional effects. G.107 and P.564 and ETSI TS101 329-5 specify three MoS algorithms that are used to estimate speech quality or conversation quality. P.NAMS and P.NBAMS specify two MoS algorithms that are used to estimate multimedia quality including video quality, audio quality and audio-video quality. If MoS type is MoS-LQ and MoS-CQ, the MoS value can be calculated based on ITU-T G.107[G.107], ITU-T P.564 [[P.564](#)] or ETSI TS 101 329-5 [[ETSI](#)], if the MoS type is MoS-V or MoS-AV, the MoS value can be calculated based on ITU-T P.NAMS [[P.NAMS](#)] or ITU-T P.NBAMS [[P.NBAMS](#)]. If new MOS types are defined, they can be added by an update to this document. If the receiver does not understand the MOS type defined in this document it should discard this report. If MoS Type does not match the MoS algorithm in the report (e.g., specify a voice MOS algorithm for a video quality MOS), the receiver should also discard this report.

Calculation Algorithm (CALg): 3 bits

000 - ITU-T P.564 Compliant Algorithm [[P.564](#)] (Voice)  
001 - G.107 [[G.107](#)] (Voice)  
010 - ETSI TS 101 329-5 Annex E [ETSI] (Voice)  
011 - ITU-T P.NAMS [[P.NAMS](#)] (Multimedia)  
100 - ITU-T P.NBAMS [[P.NBAMS](#)] (Multimedia)  
101~111 - Reserved for future extension.

Payload Type (PT): 7 bits

QoE metric reporting for a single stream will depend on the payload format in use. This field identifies the format of the RTP payload. For RTP sessions where multiple payload formats can be negotiated or the payload format changes during the mid-session, the value of this field will be used to indicate what payload



format was in use for the reporting interval.

Rsd.:3 bits

This field is reserved for future definition. In the absence of such a definition, the bits in this field MUST be set to zero and MUST be ignored by the receiver.

MOS Value: 13 bits

The estimated mean opinion score for multimedia application quality is defined as including the effects of delay, loss, discard, jitter and other effects that would affect multimedia quality . It is expressed in numeric format 6:7 with the value in the range 0.0 to 63.992. The valid the measured value ranges from 0.0 to 50.0, corresponding to MoS x 10 as for MoS. If the measured value is over ranged, the value 0xFFFE SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFF SHOULD be reported. Values other than 0xFFFE, 0xFFFF and the valid range defined above MUST NOT be sent and MUST be ignored by the receiving system.

### **3.2.2. Multi-Channel per SSRC Segment**

```

+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|1|0| MT |CAlg| PT |CHID| MOS Value |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Segment Type ( S): 1 bit

A one identifies this as either a multi-channel segment or multi-layer segment.

Media Type (M): 1bit

A zero identifies this as a multi-channel per SSRC segment.

MoS Type (MT): 4 bits

As defined in [Section 3.2.1](#) of this document. If the value of this field is not for MoS-CQ or MoS-LQ, the receiver using multi-channel segment should discard this invalid segment with the wrong MoS Type.



Calculation Algorithm (CALg): 3 bits

000 - ITU-T P.564 Compliant Algorithm [[P.564](#)] (Voice)  
001 - G.107 [[G.107](#)] (Voice)  
010 - ETSI TS 101 329-5 Annex E, [ETSI] (Voice)  
011~100 - Reserved.  
101~111 - Reserved for future extension.

Payload Type (PT): 7 bits

As defined in [Section 3.2.1](#) of this document.

Channel Identifier (CHID): 3 bits

If multiple channels of audio are carried in one RTP stream, each channel of audio will be viewed as a independent channel(e.g., left channel audio, right channel audio). This field is used to identify each channel carried in the same media stream. The default Channel mapping follows static ordering rule described in the [section 4.1 of \[RFC3551\]](#). However there are some payload formats that use different channel mappings, e.g., AC-3 audio over RTP [[RFC4184](#)] only follow AC-3 channel order scheme defined in [[ATSC](#)]. Enhanced AC-3 Audio over RTP [[RFC4598](#)] uses dynamic channel transform mechanism. In order that the appropriate channel mapping can be determined, QoE reports need to be tied to an RTP payload format, i.e., including the payload type of the reported media according to [[MONARCH](#)] and using Payload Type to determine the appropriate channel mapping.

(Editor's Note: It is not clear that the channel mapping in [RFC 3551 Section 4.1](#) is the only one in use)

Rsd.: 3 bits

This field is reserved for future definition. In the absence of such a definition, the bits in this field MUST be set to zero and MUST be ignored by the receiver.

MOS Value: 13 bits

As defined in [Section 3.2.1](#) of this document.

#### **4. SDP Signaling**

One new parameter is defined for the report block defined in this document to be used with Session Description Protocol (SDP) [[RFC4566](#)]



using the Augmented Backus-Naur Form (ABNF) [[RFC5234](#)]. It has the following syntax within the "rtcp-xr" attribute [[RFC3611](#)]:

```
rtcp-xr-attr = "a=rtcp-xr:"  
               [xr-format *(SP xr-format)] CRLF  
xr-format = qoe-metrics  
qoe-metrics = "multimedia-quality-metrics"
```

Refer to [Section 5.1 of RFC 3611](#) [[RFC3611](#)] for a detailed description and the full syntax of the "rtcp-xr" attribute.

## **[5.](#) IANA Considerations**

New block types for RTCP XR are subject to IANA registration. For general guidelines on IANA considerations for RTCP XR, refer to [[RFC3611](#)].

### **[5.1.](#) New RTCP XR Block Type value**

This document assigns the block type value NDEL in the IANA "RTCP XR Block Type Registry" to the "QoE Metrics Block".

[Note to RFC Editor: please replace SMQ with the IANA provided RTCP XR block type for this block.]

### **[5.2.](#) New RTCP XR SDP Parameter**

This document also registers a new parameter "qoe-metrics" in the "RTCP XR SDP Parameters Registry".

### **[5.3.](#) Contact information for registrations**

The contact information for the registrations is:

Qin Wu  
sunseawq@huawei.com  
101 Software Avenue, Yuhua District  
Nanjing, JiangSu 210012 China

### **[5.4.](#) New registry of calculation algorithms for single stream per SSRC segment**

This document creates a new registry for single stream per SSRC segment defined in the [section 3.2.1](#) to be called "RTCP XR QoE metric block - multimedia application Calculation Algorithm" as a sub-registry of the "RTP Control Protocol Extended Reports (RTCP XR) Block Type Registry". This registry applies to the multimedia



session where each type of media are sent in a separate RTP stream. Specially this registry also applies to the layered video session where each layer video are sent in a separate RTP stream. Policies for this new registry are as follows:

- o The information required to support this assignment is an unambiguous definition of the new metric, covering the base measurements and how they are processed to generate the reported metric. This should include the units of measurement, how values of the metric are reported in the one 16-bit fields "MoS Value".
- o The review process for the registry is "Specification Required" as described in [Section 4.1 of \[RFC5226\]](#).
- o Entries in the registry are integers. The valid range is 0 to 7 corresponding to the 3-bit field "CAlg" in the block. Values are to be recorded in decimal.
- o Initial assignments are as follows:
  1. ITU-T P.564 Compliant Algorithm [[P.564](#)] (Voice)
  2. G.107 [[G.107](#)] (Voice)
  3. ETSI TS 101 329-5 Annex E [ETSI] (Voice)
  4. ITU-T P.NAMS [[P.NAMS](#)] (Multimedia)
  5. ITU-T P.NBAMS [[P.NBAMS](#)] (Multimedia)

#### **5.5. New registry of calculation algorithms for multi-channel per SSRC segment**

This document creates a new registry for multi-channel per SSRC segment defined in the [section 3.2.3](#) to be called "RTCP XR QoE metric block - multi-channel application Calculation Algorithm" as a sub-registry of the "RTP Control Protocol Extended Reports (RTCP XR) Block Type Registry" if multi-channel voice data are carried in the same RTP stream. Policies for this new registry are as follows:

- o The information required to support this assignment is an unambiguous definition of the new metric, covering the base measurements and how they are processed to generate the reported metric. This should include the units of measurement, how values of the metric are reported in the one 16-bit fields "MoS Value".
- o The review process for the registry is "Specification Required" as described in [Section 4.1 of \[RFC5226\]](#).
- o Entries in the registry are integers. The valid range is 0 to 7 corresponding to the 3-bit field "CAlg" in the block. Values are to be recorded in decimal.
- o Initial assignments are as follows:



1. ITU-T P.564 Compliant Algorithm [[P.564](#)] (Voice)
2. G.107 [[G.107](#)] (Voice)
3. ETSI TS 101 329-5 Annex E [ETSI] (Voice)

## **[6.](#) Security Considerations**

The new RTCP XR report blocks proposed in this document introduces no new security considerations beyond those described in [[RFC3611](#)].

## **[7.](#) Authors**

This draft merges ideas from two different drafts addressing the QoE metric Reporting issue. The authors of these drafts are listed below (in alphabetical order) :

Alan Clark < alan.d.clark@telchemy.com >  
Geoff Hunt < r.geoff.hunt@gmail.com >  
Martin Kastner < martin.kastner@telchemy.com >  
Kai Lee < leekai@ctbri.com.cn >  
Roland Schott < roland.schott@telekom.de >  
Qin Wu < sunseawq@huawei.com >  
Glen Zorn < gwz@net-zen.net >

## **[8.](#) Acknowledgements**

The authors would like to thank Alan Clark, Bill Ver Steeg, David R Oran, Ali Begen, Colin Perkins, Roni Even, Youqing Yang, Wenxiao Yu and Yinliang Hu for their valuable comments and suggestions on this document.

## **[9.](#) References**

### **[9.1.](#) Normative References**

- [ATSC] U.S. Advanced Television Systems Committee (ATSC), "ATSC Standard: Digital Audio Compression (AC-3), Revision B", ATSC Doc A/52B, June 2005.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3550] Schulzrinne, H., "RTP: A Transport Protocol for Real-Time Applications", [RFC 3550](#), July 2003.



- [RFC3551] Schulzrinne, H. and S. Casner, "RTP Profile for Audio and Video Conferences with Minimal Control", [RFC 3551](#), July 2003.
- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", [RFC 3611](#), November 2003.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), July 2006.
- [RFC5226] Narten, T., "Guidelines for Writing an IANA Considerations Section in RFCs", [RFC 5226](#), May 2008.
- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.

## **9.2. Informative References**

- [ETSI] ETSI, "Quality of Service (QoS) measurement methodologies", ETSI TS 101 329-5 V1.1.1, November 2000.
- [G.107] ITU-T, "The E Model, a computational model for use in transmission planning", ITU-T Recommendation G.107, April 2009.
- [G.1082] ITU-T, "Measurement-based methods for improving the robustness of IPTV performance", ITU-T Recommendation G.1082, April 2009.
- [MONARCH] Wu, Q., "Monitoring Architectures for RTP", ID [draft-ietf-avtcore-monarch-00](#), April 2011.
- [P.564] ITU-T, "Conformance testing for narrowband Voice over IP transmission quality assessment models", ITU-T Recommendation P.564, July 2006.
- [P.NAMS] ITU-T, "Non-intrusive parametric model for the Assessment of performance of Multimedia Streaming", ITU-T Recommendation P.NAMS, November 2009.
- [P.NBAMS] ITU-T, "non-intrusive bit-stream model for assessment of performance of multimedia streaming", ITU-T Recommendation P.NBAMS, November 2009.
- [PMOL] Clark, A. and B. Claise, "Framework for Performance Metric Development", ID [draft-ietf-pmol-metrics-framework-12](#), July 2011.



- [RFC4184] Link, B., Hager, T., and J. Flaks, "RTP Payload Format for AC-3 Audio", [RFC 4184](#), October 2005.
- [RFC4598] Link, B., "Real-time Transport Protocol (RTP) Payload Format for Enhanced AC-3 (E-AC-3) Audio", [RFC 4598](#), July 2006.

## **Appendix A. Change Log**

### **A.1. draft-ietf-xrblock-rtcp-xr-qoe-01**

The following are the major changes compared to previous version:

- o Remove layered support from the QoE metric draft.
- o Allocate 7 bits in the block header for payload type to indicate what type of payload format is in use and add associated definition of payload type.
- o Clarify using Payload Type to determine the appropriate channel mapping in the definition of Channel Identifier.

### **A.2. draft-ietf-xrblock-rtcp-xr-qoe-00**

The following are the major changes compared to previous version:

- o Allocate one more bit in the single stream per SSC segment to get alignment with the other two segment type.

## **Authors' Addresses**

Geoff Hunt  
Unaffiliated

Email: [r.geoff.hunt@gmail.com](mailto:r.geoff.hunt@gmail.com)

Alan Clark  
Telchemy Incorporated  
2905 Premiere Parkway, Suite 280  
Duluth, GA 30097  
USA

Email: [alan.d.clark@telchemy.com](mailto:alan.d.clark@telchemy.com)



Qin Wu  
Huawei  
101 Software Avenue, Yuhua District  
Nanjing, Jiangsu 210012  
China

Email: sunseawq@huawei.com

Roland Schott  
Deutsche Telekom Laboratories  
Deutsche-Telekom-Allee 7  
Darmstadt 64295  
Germany

Email: Roland.Schott@telekom.de

Glen Zorn  
Network Zen  
77/440 Soi Phoomjit, Rama IV Road  
Phra Khanong, Khlong Toie  
Bangkok 10110  
Thailand

Phone: +66 (0) 87 502 4274  
Email: gwz@net-zen.net

