

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: April 21, 2013

A. Clark
Telchemy
Q. Wu
Huawei
R. Schott
DT
G. Zorn
Network Zen
October 18, 2012

**RTP Control Protocol (RTCP) Extended Report (XR) Blocks for QoE Metric
Reporting
draft-ietf-xrblock-rtcp-xr-qoe-03**

Abstract

This document defines an RTP Control Protocol (RTCP) Extended Report (XR) Block including two new segment types and associated SDP parameters that allow the reporting of QoE metrics for use in a range of RTP applications.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 21, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	QoE Metrics Report Block	3
1.2.	RTCP and RTCP XR Reports	3
1.3.	Performance Metrics Framework	3
1.4.	Applicability	3
2.	Terminology	4
2.1.	Standards Language	4
3.	QoE Metrics Block	5
3.1.	Metric Block Structure	5
3.2.	Definition of Fields in QoE Metrics Block	6
3.2.1.	Single Stream per SSRC Segment	7
3.2.2.	Multi-Channel audio per SSRC Segment	9
4.	SDP Signaling	11
5.	IANA Considerations	11
5.1.	New RTCP XR Block Type value	11
5.2.	New RTCP XR SDP Parameter	11
5.3.	Contact information for registrations	11
5.4.	New registry of calculation algorithms for single stream segment	12
5.5.	New registry of calculation algorithms for multi-channel audio segment	12
6.	Security Considerations	13
7.	Authors	13
8.	Acknowledgements	13
9.	References	13
9.1.	Normative References	13
9.2.	Informative References	14
Appendix A.	Change Log	15
A.1.	draft-ietf-xrblock-rtcp-xr-qoe-03	15
A.2.	draft-ietf-xrblock-rtcp-xr-qoe-02	15
A.3.	draft-ietf-xrblock-rtcp-xr-qoe-01	15
A.4.	draft-ietf-xrblock-rtcp-xr-qoe-00	16
	Authors' Addresses	16

1. Introduction

1.1. QoE Metrics Report Block

This document defines a new block type to augment those defined in [\[RFC3611\]](#), for use in a range of RTP applications.

The new block type provides information on multimedia quality using one of several standard metrics.

The metrics belong to the class of application level metrics defined in [\[MONARCH\]](#).

1.2. RTCP and RTCP XR Reports

The use of RTCP for reporting is defined in [\[RFC3550\]](#). [\[RFC3611\]](#) defined an extensible structure for reporting using an RTCP Extended Report (XR). This draft defines a new Extended Report block for use with [\[RFC3550\]](#) and [\[RFC3611\]](#).

1.3. Performance Metrics Framework

The Performance Metrics Framework [\[RFC6390\]](#) provides guidance on the definition and specification of performance metrics. The RTP Monitoring Architectures [\[MONARCH\]](#) provides guideline for reporting block format using RTCP XR. The XR Block described in this document are in accordance with the guidelines in [\[RFC6390\]](#) and [\[MONARCH\]](#).

1.4. Applicability

The QoE Metrics Report Block can be used in any application of RTP for which QoE measurement algorithms are defined.

The factors that affect real-time AV application quality can be split into two categories. The first category consists of transport-dependent factors such as packet loss, delay and jitter (which also translates into losses in the playback buffer). The factors in the second category are application-specific factors that affect real time application (e.g., video) quality and are sensitivity to network errors. These factors can be but not limited to video codec and loss recovery technique, coding bit rate, packetization scheme, and content characteristics.

Compared with application-specific factors, the transport-dependent factors sometimes are not sufficient to measure real time data quality, since the ability to analyze the real time data in the application layer provides quantifiable measurements for subscriber Quality of Experience (QoE) that may not be captured in the

transmission layers or from the RTP layer down. In a typical scenario, monitoring of the transmission layers can produce statistics suggesting that quality is not an issue, such as the fact that network jitter is not excessive. However, problems may occur in the service layers leading to poor subscriber QoE. Therefore monitoring using only network-level measurements may be insufficient when application layer content quality is required.

In order to provide accurate measures of real time application quality when transporting real time contents across a network, the synthetical multimedia quality Metrics is highly required which can be conveyed in the RTCP XR packets[RFC3611] and may have the following three benefits:

- o Tuning the content encoder algorithm to satisfy real time data quality requirements.
- o Determining which system techniques to use in a given situation and when to switch from one technique to another as system parameters change.
- o Verifying the continued correct operation of an existing system.

2. Terminology

2.1. Standards Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

The terminology used is

Numeric formats S X:Y

where S indicates a two's complement signed representation, X the number of bits prior to the decimal place and Y the number of bits after the decimal place.

Hence 8:8 represents an unsigned number in the range 0.0 to 255.996 with a granularity of 0.0039. S7:8 would represent the range -127.996 to +127.996. 0:16 represents a proper binary fraction with range

0.0 to 1 - $1/65536 = 0.9999847$

though note that use of flag values at the top of the numeric range slightly reduces this upper limit. For example, if the 16-bit values 0xffffe and 0xffff are used as flags for "over-range" and "unavailable" conditions, a 0:16 quantity has range

0.0 to 1 - 3/65536 = 0.9999542

3. QoE Metrics Block

This block reports the multimedia application performance or quality beyond the information carried in the standard RTCP packet format. Information is recorded about multimedia application QoE metric which provides a measure that is indicative of the user's view of a service. Multimedia application QoE metric is commonly expressed as a MOS ("Mean Opinion Score"), MOS is on a scale from 1 to 5, in which 5 represents excellent and 1 represents unacceptable. MOS scores are usually obtained using subjective testing or using objective algorithm. However Subjective testing to estimate the multimedia quality may be not suitable for measuring the multimedia quality since the results may vary from test to test. Therefore using objective algorithm to calculate MOS scores is recommended. ITU-T recommendations define the methodologies for assessment of the performance of multimedia stream [G.107][P.564][G.1082][P.1201][P.1202] and provides a method to evaluate QoE estimation algorithms and objective model for video and audio. Hence this document recommends vendors and implementers to use these International Telecommunication Union (ITU)-specified methodologies to measure parameters when possible.

Editor's note: P.NAMS and P.NBAMS are replaced with P.1201 and P.1202. However P.1201 is further splitted into P.1201.1 and P.1201.2 and P.1202 is futher splitted into P.1202.1 and P.1202.2. So shall we reference parent document P.1201 and P.1202 or reference derived documents P.1201.1,P.1201.2, P.1202.1,P.1202.2?

3.1. Metric Block Structure

The report block contents are dependent upon a series of flag bits carried in the first part of the header. Not all parameters need to be reported in each block. Flags indicate which are and which are not reported. The fields corresponding to unreported parameters MUST be present, but are set to zero. The receiver MUST ignore any QoE Metrics Block with a non-zero value in any field flagged as unreported. The encoding of QoE metrics block payload consists of a series of 32 bit units called segments that describe MOS Type, MoS algorithm and MoS value.

Editor's note: MOS values for narrowband, wideband, super wideband and fullband codecs; these MOS values occupy the same range. For video application, MoS values for SD resolution, HD resolution video also occupy the same ranges and hence the QoE block needs to

indicate what the MOS reference is.

Editor's Note: If we add MoS reference concept, 32 bit segment is not sufficient. Therefore it was suggested to expand 32 bit segment into 48 bit segment to support MoS reference feature.

The QoE Metrics Block has the following format:

```

      0               1               2               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      BT=QMB      | I |   Reserved   |      Block Length      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     SSRC of source              |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Segment 1                    |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Segment 2                    |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     .....                       |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Segment n                    |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

3.2. Definition of Fields in QoE Metrics Block

Block type (BT): 8 bits

The QoE Metrics Block is identified by the constant <QMB>.

Interval Metric flag (I): 2 bits

This field is used to indicate whether the QoE metrics are Interval or Cumulative metrics, that is, whether the reported values applies to the most recent measurement interval duration between successive metrics reports (I=10) (the Interval Duration) or to the accumulation period characteristic of cumulative measurements (I=11) (the Cumulative Duration) or is a sampled instantaneous value (I=01) (Sampled Value).

Reserved.: 6 bits

This field is reserved for future definition. In the absence of such a definition, the bits in this field MUST be set to zero and MUST be ignored by the receiver.

Block Length: 16 bits

The length of this report block in 32-bit words, minus one. For the QoE Metrics Block, the block length is variable length.

SSRC of source: 32 bits

As defined in [Section 4.1 of \[RFC3611\]](#).

Segment i: 32 bits

There are two segment types defined in this document: single stream per SSRC segment, multi-channel audio per SSRC segment. Multi-channel audio per SSRC segment is used to deal with the case where Multi-channel audios are carried in one RTP stream while single stream per SSRC segment is used to deal with the case where each media stream is identified by SSRC and sent in separate RTP stream. The left two bits of the section determine its type. If the leftmost bit of the segment is zero, then it is single stream segment. If the leftmost bit is one, then it is multi-channel audio segment. Note that two segment types can not be present in the same metric block.

3.2.1. Single Stream per SSRC Segment

```

+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|S| MT |CAlg| PT |Rsv. | MOS Value |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

+-----+-----+
| Editor's Note: If we add | Editor's Note: Shall we need to |
| MoS reference concept, we | support MoS Scaling concept in the |
| should give a definition | future draft? One point on the list |
| of MoS reference which | is MoS Scaling concept is implicitly |
| covers both audio | used within the industry when |
| application and video | quoting MOS scores for codecs and |
| application. | measurements. |
+-----+-----+

```

Segment Type (S): 1 bit

This field is used to identify the segment type used in this report block. A zero identifies this as a single stream segment. Single stream means there is only one media stream carried in one RTP stream. The single stream segment can be used to report the MoS value associated with this media stream identified by SSRC. If there are multiple media streams and they want to use the

single stream per SSRC segment to report the MOS value, they should be carried in the separate RTP streams with different SSRC. In this case, multiple QoE Metrics Blocks are required to report the MOS value corresponding to each media stream using single stream segment.

MoS Type (MT): 4 bits

This field is used to indicate the MOS type to be reported. The MOS type is defined as follows:

- 0000 MOS-LQ - Listening Quality MoS.
- 0001 MOS-CQ - Conversation Quality MoS.
- 0010 MOS-A - Audio Quality MOS.
- 0010 MOS-V - Video Quality MOS.
- 0011 MOS-AV - Audio-Video Quality MOS.
- 0100~1111 - Reserved for future definitions.

MoS-LQ measures the quality of audio for listening purposes only while MoS-CQ measures the quality of audio for conversation purpose only. MoS-A, MoS-V and MoS-AV measures the quality of audio application, the quality of video application and Audio-Video application respectively. Both MoS-LQ and MoS-CQ are commonly used in VoIP applications. MOS-LQ uses either wideband audio codec or narrowband audio codec, or both and does not take into account any of bidirectional effects, such as delay and echo. MOS-CQ uses narrowband codec and takes into account listening quality in each direction, as well as the bidirectional effects.

Calculation Algorithm (CALg): 3 bits

- 000 - ITU-T P.564 Compliant Algorithm [[P.564](#)] (Voice)
- 001 - G.107 [[G.107](#)] (Voice)
- 010 - ETSI TS 101 329-5 Annex E [ETSI] (Voice)
- 011 - TTC JJ201.01 [[TTC](#)] (Voice)
- 100 - ITU-T P.1201 [[P.1201](#)] (Multimedia)
- 101 - ITU-T P.1202 [[P.1202](#)] (Video)
- 110~111 - Reserved for future extension.

G.107 and P.564 and ETSI TS101 329-5 specify three Calculation algorithms or MoS algorithms that are used to estimate speech quality or conversation quality. P.NAMS and P.NBAMS specify two MoS algorithms that are used to estimate multimedia quality including video quality, audio quality and audio-video quality. If MoS type is MoS-LQ and MoS-CQ, the MoS value can be calculated based on ITU-T G.107[[G.107](#)], ITU-T P.564 [[P.564](#)] or ETSI TS 101 329-5 [[ETSI](#)], if the MoS type is MoS-V or MoS-AV, the MoS value can be calculated based on ITU-T P.NAMS [[P.1201](#)] or ITU-T P.NBAMS

[P.1202]. If new MOS types are defined, they can be added by an update to this document. If the receiver does not understand the MOS type defined in this document it should discard this report. If MoS Type does not match the MoS algorithm in the report (e.g., specify a voice MOS algorithm for a video quality MOS), the receiver should also discard this report.

Payload Type (PT): 7 bits

QoE metrics reporting depends on the payload format in use. This field identifies the format of the RTP payload. For RTP sessions where multiple payload formats can be negotiated or the payload format changes during the mid-session), the value of this field will be used to indicate what payload format was in use for the reporting interval.

Rsd.:3 bits

This field is reserved for future definition. In the absence of such a definition, the bits in this field MUST be set to zero and MUST be ignored by the receiver.

MOS Value: 14 bits

The estimated mean opinion score for multimedia application quality is defined as including the effects of delay, loss, discard, jitter and other effects that would affect multimedia quality. It is expressed in numeric format 6:8 with the value in the range 0.0 to 63.996. The valid the measured value ranges from 0.0 to 50.0, corresponding to MoS x 10 as for MoS. If the measured value is over ranged, the value 0xFFFE SHOULD be reported to indicate an over-range measurement. If the measurement is unavailable, the value 0xFFFF SHOULD be reported. Values other than 0xFFFE, 0xFFFF and the valid range defined above MUST NOT be sent and MUST be ignored by the receiving system.

3.2.2. Multi-Channel audio per SSRC Segment

```

+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|S| MT  |CAlg|      PT      |CHID|      MOS Value      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Segment Type (S): 1 bit

This field is used to identify the segment type used in this report block. A one identifies this as a multi-channel audio segment.

Media Type (M): 1bit

A zero identifies this as a multi-channel per SSRC segment.

MoS Type (MT): 4 bits

As defined in [Section 3.2.1](#) of this document. If the value of this field is not corresponding to MoS-CQ or MoS-LQ, the receiver using multi-channel segment should discard this invalid segment with the wrong MoS Type.

Calculation Algorithm (CALg): 3 bits

000 - ITU-T P.564 Compliant Algorithm [[P.564](#)] (Voice)
001 - G.107 [[G.107](#)] (Voice)
010 - ETSI TS 101 329-5 Annex E, [ETSI] (Voice)
011 - TTC JJ201.01 [[TTC](#)] (Voice)
100~111 - Reserved for future extension.

Payload Type (PT): 7 bits

As defined in [Section 3.2.1](#) of this document.

Channel Identifier (CHID): 3 bits

If multiple channels of audio are carried in one RTP stream, each channel of audio will be viewed as a independent channel(e.g., left channel audio, right channel audio). This field is used to identify each channel carried in the same media stream. The default Channel mapping follows static ordering rule described in the [section 4.1 of \[RFC3551\]](#). However there are some payload formats that use different channel mappings, e.g., AC-3 audio over RTP [[RFC4184](#)] only follow AC-3 channel order scheme defined in [[ATSC](#)]. Enhanced AC-3 Audio over RTP [[RFC4598](#)] uses dynamic channel transform mechanism. In order that the appropriate channel mapping can be determined, QoE reports need to be tied to an RTP payload format, i.e., including the payload type of the reported media according to [[MONARCH](#)] and using Payload Type to determine the appropriate channel mapping.

Rsd.: 3 bits

This field is reserved for future definition. In the absence of such a definition, the bits in this field MUST be set to zero and MUST be ignored by the receiver.

MOS Value: 14 bits

As defined in [Section 3.2.1](#) of this document.

4. SDP Signaling

One new parameter is defined for the report block defined in this document to be used with Session Description Protocol (SDP) [[RFC4566](#)] using the Augmented Backus-Naur Form (ABNF) [[RFC5234](#)]. It has the following syntax within the "rtcp-xr" attribute [[RFC3611](#)]:

```
xr-format = qoe-metrics
qoe-metrics = "QoE metrics"
```

Refer to [Section 5.1 of RFC 3611](#) [[RFC3611](#)] for a detailed description and the full syntax of the "rtcp-xr" attribute.

5. IANA Considerations

New block types for RTCP XR are subject to IANA registration. For general guidelines on IANA considerations for RTCP XR, refer to [[RFC3611](#)].

5.1. New RTCP XR Block Type value

This document assigns the block type value MMQ in the IANA "RTCP XR Block Type Registry" to the "QoE Metrics Block".

[Note to RFC Editor: please replace MMQ with the IANA provided RTCP XR block type for this block.]

5.2. New RTCP XR SDP Parameter

This document also registers a new parameter "qoe-metrics" in the "RTCP XR SDP Parameters Registry".

5.3. Contact information for registrations

The contact information for the registrations is:

Qin Wu
sunseawq@huawei.com
101 Software Avenue, Yuhua District
Nanjing, JiangSu 210012 China

5.4. New registry of calculation algorithms for single stream segment

This document creates a new registry for single stream per SSRC segment defined in the [section 3.2.1](#) to be called "RTCP XR QoE metric block - multimedia application Calculation Algorithm" as a sub-registry of the "RTP Control Protocol Extended Reports (RTCP XR) Block Type Registry". This registry applies to the multimedia session where each type of media are sent in a separate RTP stream. Specially this registry also applies to the layered video session where each layer video are sent in a separate RTP stream. Policies for this new registry are as follows:

- o The information required to support this assignment is an unambiguous definition of the new metric, covering the base measurements and how they are processed to generate the reported metric. This should include the units of measurement, how values of the metric are reported in the one 16-bit fields "MoS Value".
- o The review process for the registry is "Specification Required" as described in [Section 4.1 of \[RFC5226\]](#).
- o Entries in the registry are integers. The valid range is 0 to 7 corresponding to the 3-bit field "CAlg" in the block. Values are to be recorded in decimal.
- o Initial assignments are as follows:
 1. ITU-T P.564 Compliant Algorithm [[P.564](#)] (Voice)
 2. G.107 [[G.107](#)] (Voice)
 3. ETSI TS 101 329-5 Annex E [ETSI] (Voice)
 4. TTC JJ201.01 [[TTC](#)] (Voice)
 5. ITU-T P.1201 [[P.1201](#)] (Multimedia)
 6. ITU-T P.1202 [[P.1202](#)] (Video)

5.5. New registry of calculation algorithms for multi-channel audio segment

This document creates a new registry for multi-channel audio per SSRC segment defined in the [section 3.2.2](#) to be called "RTCP XR QoE metric block - multi-channel application Calculation Algorithm" as a sub-registry of the "RTP Control Protocol Extended Reports (RTCP XR) Block Type Registry" if multi-channel voice data are carried in the same RTP stream. Policies for this new registry are as follows:

- o The information required to support this assignment is an unambiguous definition of the new metric, covering the base measurements and how they are processed to generate the reported metric. This should include the units of measurement, how values of the metric are reported in the one 16-bit fields "MoS Value".

- o The review process for the registry is "Specification Required" as described in [Section 4.1 of \[RFC5226\]](#).
- o Entries in the registry are integers. The valid range is 0 to 7 corresponding to the 3-bit field "CAlg" in the block. Values are to be recorded in decimal.
- o Initial assignments are as follows:
 1. ITU-T P.564 Compliant Algorithm [[P.564](#)] (Voice)
 2. G.107 [[G.107](#)] (Voice)
 3. ETSI TS 101 329-5 Annex E [[ETSI](#)] (Voice)
 4. TTC JJ201.01 [[TTC](#)] (Voice)

[6.](#) Security Considerations

The new RTCP XR report blocks proposed in this document introduces no new security considerations beyond those described in [[RFC3611](#)].

[7.](#) Authors

This draft merges ideas from two drafts addressing the QoE metric Reporting issue. The authors of these drafts are listed below (in alphabetical order):

Alan Clark < alan.d.clark@telchemy.com >
Geoff Hunt < r.geoff.hunt@gmail.com >
Martin Kastner < martin.kastner@telchemy.com >
Kai Lee < leekai@ctbri.com.cn >
Roland Schott < roland.schott@telekom.de >
Qin Wu < sunseawq@huawei.com >
Glen Zorn < gwz@net-zen.net >

[8.](#) Acknowledgements

The authors would like to thank Bill Ver Steeg, David R Oran, Ali Begen, Colin Perkins, Roni Even, Youqing Yang, Wenxiao Yu and Yinliang Hu for their valuable comments and suggestions on this document.

[9.](#) References

[9.1.](#) Normative References

- [ATSC] U.S. Advanced Television Systems Committee (ATSC), "ATSC Standard: Digital Audio Compression (AC-3), Revision B", ATSC Doc A/52B, June 2005.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3550] Schulzrinne, H., "RTP: A Transport Protocol for Real-Time Applications", [RFC 3550](#), July 2003.
- [RFC3551] Schulzrinne, H. and S. Casner, "RTP Profile for Audio and Video Conferences with Minimal Control", [RFC 3551](#), July 2003.
- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", [RFC 3611](#), November 2003.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), July 2006.
- [RFC5226] Narten, T., "Guidelines for Writing an IANA Considerations Section in RFCs", [RFC 5226](#), May 2008.
- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.

9.2. Informative References

- [ETSI] ETSI, "Quality of Service (QoS) measurement methodologies", ETSI TS 101 329-5 V1.1.1, November 2000.
- [G.107] ITU-T, "The E Model, a computational model for use in transmission planning", ITU-T Recommendation G.107, April 2009.
- [G.1082] ITU-T, "Measurement-based methods for improving the robustness of IPTV performance", ITU-T Recommendation G.1082, April 2009.
- [MONARCH] Wu, Q., "Monitoring Architectures for RTP", ID [draft-ietf-avtcore-monarch-22](#), September 2012.
- [P.1201] ITU-T, "Parametric non-intrusive assessment of audiovisual media streaming quality", ITU-T Recommendation P.1201, October 2012.
- [P.1202] ITU-T, "non-intrusive bit-stream model for assessment of performance of multimedia streaming", ITU-T Recommendation P.1202, October 2012.
- [P.564] ITU-T, "Conformance testing for narrowband Voice over IP

transmission quality assessment models", ITU-T Recommendation P.564, July 2006.

- [RFC4184] Link, B., Hager, T., and J. Flaks, "RTP Payload Format for AC-3 Audio", [RFC 4184](#), October 2005.
- [RFC4598] Link, B., "Real-time Transport Protocol (RTP) Payload Format for Enhanced AC-3 (E-AC-3) Audio", [RFC 4598](#), July 2006.
- [RFC6390] Clark, A. and B. Claise, "Framework for Performance Metric Development", [RFC 6390](#), October 2011.
- [TTC] TTC 201.01 (Japan), "A method for speech quality assessment for Voice over IP".

Appendix A. Change Log

A.1. draft-ietf-xrblock-rtcp-xr-qoe-03

The following are the major changes compared to previous version:

- o Add one new reference to support TTC JJ201.01.
- o Update two references P.NAMS and P.NBAMS.
- o Other Editorial changes based on comments applied to PDV and Delay drafts.

A.2. draft-ietf-xrblock-rtcp-xr-qoe-02

The following are the major changes compared to previous version:

- o Remove leftmost second bit since it is useless.
- o Change 13bits MoS value field into 14 bits to increase MoS precision.
- o Fix some typo and make some editorial changes.

A.3. draft-ietf-xrblock-rtcp-xr-qoe-01

The following are the major changes compared to previous version:

- o Remove layered support from the QoE metric draft.
- o Allocate 7 bits in the block header for payload type to indicate what type of payload format is in use and add associated definition of payload type.
- o Clarify using Payload Type to determine the appropriate channel mapping in the definition of Channel Identifier.

[A.4. draft-ietf-xrblock-rtcp-xr-qoe-00](#)

The following are the major changes compared to previous version:

- o Allocate one more bit in the single stream per SSC segment to get alignment with the other two segment type.

Authors' Addresses

Alan Clark
Telchemy Incorporated
2905 Premiere Parkway, Suite 280
Duluth, GA 30097
USA

Email: alan.d.clark@telchemy.com

Qin Wu
Huawei
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: sunseawq@huawei.com

Roland Schott
Deutsche Telekom Laboratories
Deutsche-Telekom-Allee 7
Darmstadt 64295
Germany

Email: Roland.Schott@telekom.de

Glen Zorn
Network Zen
77/440 Soi Phoomjit, Rama IV Road
Phra Khanong, Khlong Toie
Bangkok 10110
Thailand

Phone: +66 (0) 87 502 4274
Email: gwz@net-zen.net

