

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: May 23, 2014

H. Asaeda
NICT
Q. Wu
R. Huang
Huawei
November 19, 2013

**RTP Control Protocol (RTCP) Extended Report (XR) Blocks for
Synchronization Delay and Offset Metrics Reporting
draft-ietf-xrblock-rtcp-xr-synchronization-07**

Abstract

This document defines two RTP Control Protocol (RTCP) Extended Report (XR) Blocks that allow the reporting of synchronization delay and offset metrics for use in a range of RTP applications.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 23, 2014.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Synchronization Delay and Offset Metrics Reporting Blocks	3
1.2.	RTCP and RTCP XR Reports	3
1.3.	Performance Metrics Framework	3
1.4.	Applicability	3
2.	Terminology	4
2.1.	Standards Language	4
3.	RTP Flows Initial Synchronization Delay Report Block	5
3.1.	Metric Block Structure	5
3.2.	Definition of Fields in RTP Flow Initial Synchronization Delay Metrics Block	5
4.	RTP Flows Synchronization Offset Metrics Block	6
4.1.	Metric Block Structure	7
4.2.	Definition of Fields in RTP Flow General Synchronization Offset Metrics Block	7
5.	SDP Signaling	9
5.1.	SDP rtcp-xr-attrib Attribute Extension	9
5.2.	Offer/Answer Usage	10
6.	IANA Considerations	10
7.	Security Considerations	10
8.	Acknowledgements	11
9.	References	11
9.1.	Normative References	11
9.2.	Informative References	12
Appendix A.	Metrics represented using RFC6390 Template	12
Appendix B.	Change Log	13
B.1.	draft-ietf-xrblock-rtcp-xr-synchronization-07	13
B.2.	draft-ietf-xrblock-rtcp-xr-synchronization-06	13
B.3.	draft-ietf-xrblock-rtcp-xr-synchronization-05	13
B.4.	draft-ietf-xrblock-rtcp-xr-synchronization-04	14
B.5.	draft-ietf-xrblock-rtcp-xr-synchronization-03	14
B.6.	draft-ietf-xrblock-rtcp-xr-synchronization-02	14
	Authors' Addresses	14

[1.](#) Introduction

1.1. Synchronization Delay and Offset Metrics Reporting Blocks

This document defines two new block types to augment those defined in [\[RFC3611\]](#), for use in a range of RTP applications.

The first new block type supports reporting of Initial Synchronization Delay to establish multimedia session. Information is recorded about time difference between the start of RTP sessions and the time the RTP receiver acquires all components of RTP sessions in the multimedia session [\[RFC6051\]](#).

The second new block type supports reporting of the relative synchronization offset time of two arbitrary streams (e.g., between audio and video streams), with the same RTCP CNAME included in RTCP SDP packets [\[RFC3550\]](#).

These metrics belong to the class of transport level metrics defined in [\[RFC6792\]](#).

1.2. RTCP and RTCP XR Reports

The use of RTCP for reporting is defined in [\[RFC3550\]](#). [\[RFC3611\]](#) defined an extensible structure for reporting using an RTCP Extended Report (XR). This document defines a new Extended Report block for use with [\[RFC3550\]](#) and [\[RFC3611\]](#).

1.3. Performance Metrics Framework

The RTP Monitoring Architectures [\[RFC6792\]](#) provides guideline for reporting block format using RTCP XR. The new report block described in this memo is in compliance with the monitoring architecture specified in [\[RFC6792\]](#).

1.4. Applicability

When joining each session in layered video sessions [\[RFC6190\]](#) or the multimedia session, a receiver may not synchronize playout across the multimedia session or layered video session until RTCP SR packets have been received on all components of RTP sessions. The component RTP session are referred to as each RTP session for each media type in multimedia session or separate RTP session for each layer in the layered video session. For multicast session, the initial synchronization delay metric varies with the session bandwidth, the number of members, and the number of senders in the session. The RTP flow Initial synchronization delay block defined in this document can be used to report such metric, i.e., the initial synchronization delay to receive all the RTP streams belonging to the same multimedia session or layered video session. In the absence of packet loss, the

initial synchronization delay equals to the average time taken to receive the first RTCP packet in the RTP session with the longest RTCP reporting interval. In the presence of packet loss, the media synchronization should rely on the in-band mapping of RTP and NTP-format timestamps [[RFC6051](#)] or wait until the reporting interval has passed, and the next RTCP SR packet is sent.

Receivers of the RTP flow initial synchronization delay block could use this metric to compare with targets (i.e., Service Level Agreement or thresholds of the system) to help ensure the quality of real-time application performance.

In an RTP multimedia session, there can be an arbitrary number of streams carried in different RTP sessions, with the same RTCP CNAME. These streams may be not synchronized with each other. For example, one audio stream and one video stream belong to the same session, and the audio stream is transmitted lagging behind video stream for multiple tens of milliseconds [[TR-126](#)]. The RTP Flows Synchronization Offset block can be used to report such synchronization offset between video stream and audio stream. This block is also applied to the case where an RTP session can contain media streams with media from multiple media types. The metrics defined in the RTP flows synchronization Offset block can be used by network manager for trouble shooting and dealing with user experience issues.

[2.](#) Terminology

[2.1.](#) Standards Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

In addition, the following terms are defined:

Initial Synchronization Delay:

A multimedia session comprises a set of concurrent RTP sessions among a common group of participants, using one RTP session for each media type. The initial synchronization Delay is the average time for receiver to synchronize all components of a multimedia session [[RFC6051](#)].

Synchronization Offset:

Synchronization between two media streams must be maintained to ensure satisfactory QoE. Two media streams can be of the same or

different media type belonging to one RTP session or in different media types belonging to one multimedia session. The Synchronization Offset is the relative time difference of the two media streams that need to be synchronized.

3. RTP Flows Initial Synchronization Delay Report Block

This block is sent by RTP receivers and reports Initial synchronization delay beyond the information carried in the standard RTCP packet format. Information is recorded about time difference between the start of multimedia session and the time when the RTP receiver acquires all components of RTP sessions [[RFC6051](#)] measured at the receiving end of RTP stream.

This block needs only be exchanged occasionally, for example sent once at the start of RTP session.

3.1. Metric Block Structure

The RTP Flows Initial Synchronization Delay Report Block has the following format:

```

0                               1                               2                               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|   BT=RFISD   |  Reserved   |           Block length=2           |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     SSRC of Source                                     |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     Initial Synchronization Delay                                     |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

3.2. Definition of Fields in RTP Flow Initial Synchronization Delay Metrics Block

Block type (BT): 8 bits

The RTP Flows Initial Synchronization Delay Report Block is identified by the constant <RFISD>.

[Note to RFC Editor: please replace RFISD with the IANA provided RTCP XR block type for this block.]

Reserved: 8 bits

This field is reserved for future definition. In the absence of such a definition, the bits in this field MUST be set to zero and ignored by the receiver.

Block length: 16 bits

The constant 2, in accordance with the definition of this field in [Section 3 of RFC 3611](#) [[RFC3611](#)].

SSRC of source: 32 bits

The SSRC of the media source SHALL be set to the value of the SSRC identifier carried in any arbitrary component of RTP sessions belonging to the same multimedia session.

Initial Synchronization Delay: 32 bits

The average delay, expressed in units of 1/65536 seconds, from the beginning of multimedia session [[RFC6051](#)] to the time when RTCP packets are received on all of the components RTP sessions. It is recommended that the beginning of multimedia session is chosen as the time when the receiver has joined the first RTP session of the multimedia session. The value of the initial synchronization delay is calculated based on received RTCP SR packets or the RTP header extension containing in-band mapping of RTP and NTP-format timestamps [[RFC6051](#)]. If there is no packet loss, the initial synchronization delay is expected to be equal to the average time taken to receive the first RTCP packet in the RTP session with the longest RTCP reporting interval or the average time taken to receive the first RTP header extension containing in-band mapping of RTP and NTP-format timestamps.

If the measurement is unavailable, the value of this field with all bits set to 1 MUST be reported.

4. RTP Flows Synchronization Offset Metrics Block

In the RTP multimedia sessions or one RTP session, there can be an arbitrary number of Media streams and each media stream (e.g., audio stream or video stream) is sent in a separate RTP stream. In case of one RTP session, each media stream or each medium uses different SSRC. The receiver associates RTP streams to be synchronized by means of RTCP CNAME contained in the RTCP Source Description (SDS) packets [[RFC3550](#)].

This block is sent by RTP receivers and reports synchronization offset of two arbitrary RTP streams that needs to be synchronized in the RTP multimedia session. Information is recorded about the

relative average time difference between two arbitrary RTP streams (one is reporting stream, the other is reference stream) with the same CNAME and measured at the receiving end of RTP stream. In order to tell what the offset of reporting stream is relative to, the block for reference stream with synchronization offset of zero should be reported.

Instances of this Block refer by Synchronization source (SSRC) to the separate auxiliary Measurement Information block [[RFC6776](#)] which describes measurement periods in use (see [[RFC6776](#)] [section 4.2](#)). This metrics block relies on the measurement period in the Measurement Information block indicating the span of the report and SHOULD be sent in the same compound RTCP packet as the measurement information block. If the measurement period is not received in the same compound RTCP packet as this Block, this Block MUST be discarded.

[4.1.](#) Metric Block Structure

The RTP Flow General Synchronization Offset Report Block has the following format:

```

      0                               1                               2                               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      BT=RFS0      | I | Reserved |      Block length=3      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                                     SSRC of source          |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      Synchronization Offset, most significant word          |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      Synchronization Offset, least significant word          |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

[4.2.](#) Definition of Fields in RTP Flow General Synchronization Offset Metrics Block

Block type (BT): 8 bits

The RTP Flow General Synchronization Offset Report Block is identified by the constant <RFS0>.

[Note to RFC Editor: please replace RFS0 with the IANA provided RTCP XR block type for this block.]

Interval Metric Flag (I): 2 bits

This field is used to indicate whether the Burst/Gap Discard Summary Statistics metrics are Sampled, Interval or Cumulative metrics:

I=10: Interval Duration - the reported value applies to the most recent measurement interval duration between successive metrics reports.

I=11: Cumulative Duration - the reported value applies to the accumulation period characteristic of cumulative measurements.

I=01: Sampled Value - the reported value is a sampled instantaneous value.

In this document, the value I=00 is the reserved value and MUST NOT be used.

Reserved: 6 bits

This field is reserved for future definition. In the absence of such a definition, the bits in this field MUST be set to zero and MUST be ignored by the receiver.

Block length: 16 bits

The constant 3, in accordance with the definition of this field in [Section 3 of RFC 3611](#) [[RFC3611](#)].

SSRC of Source: 32 bits

The SSRC of the media source SHALL be set to the value of the SSRC identifier of the reporting RTP stream to which the XR relates.

Synchronization Offset: 64 bits

The synchronization offset of the reporting RTP stream relative to the reference stream with the same CNAME. The calculation of Synchronization Offset is similar to Difference D calculation in the [RFC3550](#). That is to say, if S_i is the NTP timestamp from the reporting RTP packet i , and R_i is the time of arrival in NTP timestamp units for reporting RTP packet i , S_j is the NTP timestamp from the reference RTP packet j , and R_j is the time of arrival in NTP timestamp units for reference RTP packet j , then the value of the synchronization offset D may be expressed as

$$D(i,j) = (R_j - R_i) - (S_j - S_i) = (R_j - S_j) - (R_i - S_i)$$

If in-band delivery of NTP-format timestamps is supported [[RFC6051](#)], S_i and S_j should be obtained directly from the RTP packets where NTP timestamps are available. If not, S_i and S_j should be calculated from their corresponding RTP timestamps. The value of the synchronization offset is represented using a 64-bit signed NTP-format timestamp as defined in [[RFC5905](#)], which is 64-bit signed fixed-point number with the integer part in the first 32 bits and the fractional part in the last 32 bits. A positive value of the synchronization offset means that the reporting stream leads before the reference stream, while a negative one means the reporting stream lags behind the reference stream. The synchronization offset of zero means the stream is the reference stream.

If the measurement is unavailable, the value of this field with all bits set to 1 MUST be reported.

5. SDP Signaling

[RFC3611] defines the use of SDP (Session Description Protocol) [[RFC4566](#)] for signaling the use of XR blocks. XR blocks MAY be used without prior signaling.

5.1. SDP rtcp-xr-attr Attribute Extension

Two new parameters are defined for the two report blocks defined in this document to be used with Session Description Protocol (SDP) [[RFC4566](#)] using the Augmented Backus-Naur Form (ABNF) [[RFC5234](#)]. They have the following syntax within the "rtcp-xr" attribute [[RFC3611](#)]:

```
xr-format = xr-rfisd-block  
           / xr-rfso-block
```

```
xr-rfisd-block = "rtp-flow-init-syn-delay"  
xr-rfso-block = "rtp-flow-syn-offset"
```

Refer to [Section 5.1 of RFC 3611](#) [[RFC3611](#)] for a detailed description and the full syntax of the "rtcp-xr" attribute.

5.2. Offer/Answer Usage

When SDP is used in offer-answer context, the SDP Offer/Answer usage defined in [\[RFC3611\]](#) applies.

6. IANA Considerations

New report block types for RTCP XR are subject to IANA registration. For general guidelines on IANA allocations for RTCP XR, refer to [Section 6.2 of \[RFC3611\]](#).

This document assigns two new block type values in the RTCP XR Block Type Registry:

Name: RFISD
Long Name: RTP Flows Initial Synchronization Delay
Value <RFISD>
Reference: [Section 3](#)

Name: RFSO
Long Name: RTP Flows Synchronization Offset Metrics Block
Value <RFSO>
Reference: [Section 4](#)

This document also registers two new SDP [\[RFC4566\]](#) parameters for the "rtcp-xr" attribute in the RTCP XR SDP Parameters Registry:

- * "rtp-flow-init-syn-delay "
- * "rtp-flow-syn-offset"

The contact information for the registrations is:

Qin Wu
sunseawq@huawei.com
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012, China

7. Security Considerations

The new RTCP XR report blocks proposed in this document introduces no new security considerations beyond those described in [\[RFC3611\]](#).

8. Acknowledgements

The authors would like to thank Bill Ver Steeg, David R Oran, Ali Begen, Colin Perkins, Roni Even, Kevin Gross, Jing Zhao, Fernando Boronat Segui, Mario Montagud Climent, Youqing Yang, Wenxiao Yu and Yinliang Hu, Jonathan Lennox for their valuable comments and suggestions on this document.

9. References

9.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, [RFC 3550](#), July 2003.
- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", [RFC 3611](#), November 2003.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), July 2006.
- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.
- [RFC5905] Mills, D., Martin, J., Burbank, J., and W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification", [RFC 5905](#), June 2010.
- [RFC6051] Perkins, C. and T. Schierl, "Rapid Synchronisation of RTP Flows", [RFC 6051](#), November 2010.
- [RFC6190] Wenger, S., Wang, Y., Schierl, T., and A. Eleftheriadis, "RTP Payload Format for Scalable Video Coding", [RFC 6190](#), May 2011.
- [RFC6776] Wu, Q., "Measurement Identity and information Reporting using SDES item and XR Block", [RFC 6776](#), August 2012.

9.2. Informative References

- [RFC6390] Clark, A. and B. Claise, "Guidelines for Considering New Performance Metric Development", [RFC 6390](#), October 2011.
- [RFC6792] Wu, Q., "Guidelines for Use of the RTP Monitoring Framework", [RFC 6792](#), November 2012.
- [TR-126] BBF Forum, "Triple-play Services Quality of Experience (QoE) Requirements", December 2006.
- [Y.1540] ITU-T, "ITU-T Rec. Y.1540, IP packet transfer and availability performance parameters", November 2007.

Appendix A. Metrics represented using [RFC6390](#) Template

RFC EDITOR NOTE: please change XXXX in [RFCXXXX] by the new RFC number, when assigned.

a. Initial Synchronization Delay Metric

- * Metric Name: RTP Initial Synchronization Delay
- * Metric Description: See [Section 2.1](#), Initial Synchronization Delay term [RFCXXXX].
- * Method of Measurement or Calculation: See [section 3.2](#), Initial Synchronization Delay definition [RFCXXXX].
- * Units of Measurement: See [section 3.2](#), Initial Synchronization Delay definition [RFCXXXX].
- * Measurement Point(s) with Potential Measurement Domain: See [section 3](#), 1st paragraph [RFCXXXX].
- * Measurement Timing: See [section 3](#), 2nd paragraph [RFCXXXX] for measurement timing.
- * Use and applications: See [section 1.4](#) [RFCXXXX].
- * Reporting model: See [RFC3611](#).

b. Synchronization Offset Metric

- * Metric Name: RTP Synchronization Offset Delay
- * Metric Description: See [Section 2.1](#), Synchronization Offset term [RFCXXXX].
- * Method of Measurement or Calculation: See [section 4.2](#), Initial Synchronization Delay definition [RFCXXXX].
- * Units of Measurement: See [section 4.2](#), Initial Synchronization Delay definition [RFCXXXX].
- * Measurement Point(s) with Potential Measurement Domain: See [section 4](#), 2nd paragraph [RFCXXXX].
- * Measurement Timing: See [section 4](#), 3rd paragraph [RFCXXXX] for measurement timing and [section 4.2](#) [RFCXXXX] for Interval Metric flag.
- * Use and applications: See [section 1.4](#) [RFCXXXX].
- * Reporting model: See [RFC3611](#).

[Appendix B](#). Change Log

Note to the RFC-Editor: please remove this section prior to publication as an RFC.

[B.1](#). [draft-ietf-xrblock-rtcp-xr-synchronization-07](#)

The following are the major changes compared to previous version:

Minor Editorial changes.

[B.2](#). [draft-ietf-xrblock-rtcp-xr-synchronization-06](#)

The following are the major changes compared to previous version:

Some Editorial changes.

[B.3](#). [draft-ietf-xrblock-rtcp-xr-synchronization-05](#)

The following are the major changes compared to previous version:

Editorial changes and typo fixed.

B.4. draft-ietf-xrblock-rtcp-xr-synchronization-04

The following are the major changes compared to previous version:

Additional text to clarify on how to distinguish report stream from reference stream.
Other Editorial changes.

B.5. draft-ietf-xrblock-rtcp-xr-synchronization-03

The following are the major changes compared to previous version:

Remove the need to signal the reference source in the synchronisation offset metrics RTCP XR report.
Apply [RFC6390](#) template to metrics in the appendix.
Other editorial changes to get inline with other XRBLOCK drafts.

B.6. draft-ietf-xrblock-rtcp-xr-synchronization-02

The following are the major changes compared to previous version:

Editorial change based on comments raised on the list and in the IETF85 meeting

Authors' Addresses

Hitoshi Asaeda
National Institute of Information and Communications Technology
4-2-1 Nukui-Kitamachi
Koganei, Tokyo 184-8795
Japan

Email: asaeda@nict.go.jp

Qin Wu
Huawei Technologies Co., Ltd.
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: sunseawq@huawei.com

Rachel Huang
Huawei Technologies Co., Ltd.
101 Software Avenue, Yuhua District
Nanjing, Jiangsu 210012
China

Email: Rachel@huawei.com