

Network Working Group
Internet-Draft
Expires: December 25, 2005

S. Iino
S. Govindan
M. Sugiura
H. Cheng
Panasonic
June 23, 2005

Wireless LAN Control Protocol (WiCoP)
draft-iino-capwap-wicop-02.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on December 25, 2005.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

The popularity of wireless local area networks (WLANs) has led to wide spread deployments across different establishments. It has also translated in to increasing scale of the WLANs. Large-scale deployments made of large numbers of wireless termination points (WTPs) and covering substantial areas are increasingly common.

The Wireless LAN Control Protocol (WiCoP) described in this document allows for the control and provisioning of large-scale WLANs. It enables central management of these networks and realizes the objectives set forth for the control and provisioning of wireless access points (CAPWAP).

Table of Contents

1.	Requirements notation	3
2.	Terminology	4
3.	Introduction	5
4.	Protocol Overview	7
5.	WiCoP Format	9
5.1	WiCoP Header	9
5.2	WiCoP Control Packet	12
5.2.1	WiCoP Control Messages	13
5.2.2	WiCoP Control Message Elements	13
5.2.3	WiCoP Control Message Description	26
5.3	WiCoP Data Packet	36
5.4	WiCoP Timers	37
5.4.1	Active Presence Timer	37
5.4.2	Feedback Interval	37
5.4.3	Response Timer	37
5.4.4	Wireless Connectivity Timer	38
6.	WiCoP Processes	39
6.1	Initialization	39
6.2	Capabilities Exchange	39
6.3	Connection	40
6.4	Configuration	40
6.4.1	Logical Groups	41
6.4.2	Resource Control	42
6.5	Operation	42
6.5.1	Updates	43
6.5.2	Feedback and Statistics	43
6.5.3	Non-periodic Events	44
6.5.4	Firmware Trigger	44
6.5.5	Wireless Terminal Management	44
6.5.6	Key Configuration	47
7.	WiCoP Performance	52
7.1	Operational Efficiency	52
7.2	Semantic Efficiency	52
8.	Summary and Conclusion	53
9.	Security Considerations	54
10.	References	54
	Authors' Addresses	55
	Intellectual Property and Copyright Statements	57

1. Requirements notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

2. Terminology

This document follows the terminologies of [[I-D.ietf-capwap-arch](#)] and [[I-D.ietf-capwap-objectives](#)].

3. Introduction

The popularity of wireless local area networks (WLANs) has led to numerous but incompatible designs and solutions. The CAPWAP Architecture Taxonomy [[I-D.ietf-capwap-arch](#)] describes major variations of these designs. Among them, the local-MAC and split-MAC architecture designs are notable categories.

Wireless LAN Control Protocol (WiCoP) recognizes the major architecture designs and presents a common platform on which WLAN entities of different designs can be accommodated. This enables interoperability among wireless termination points (WTPs) and WLAN access controllers (ACs) of distinct architecture designs. WiCoP therefore allows for cost-effective WLAN expansions. It can also accommodate future developments in WLAN technologies. Figure 1 illustrates the WiCoP operational structure in which distinct control elements are utilized for local-MAC and split-MAC WTPs.

WiCoP also addresses the increasing trend of shared infrastructure WLANs. Here, WLAN management needs to distinguish and isolate control for the different logical groups sharing a single physical WLAN. WiCoP manages WLANs through a series of tunnels that separate traffic based on logical groups.

The WiCoP operational structure in Figure 1 shows that each WTP uses a number of tunnels to distinguish and separate traffic for control and for each logical group. The protocol allows for managing WLANs in a manner consistent with the logical groups that share the physical infrastructure.




Figure 1

From Figure Figure 1 WiCoP establishes and operates control tunnels and logical group tunnels between the AC and two types of WTPs. The control tunnels are used to transport WiCoP messages dealing with the configuration, monitoring and management of WTPs as a physical whole. The logical group tunnels serve to separate traffic among each of the logical groups constituting a physical WTP.

4. Protocol Overview

The Wireless LAN Control Protocol (WiCoP) focuses on enabling interoperability in shared infrastructure WLANs. It is designed for use with different wireless technologies. This document provides both the general operations of WiCoP and also specific use-cases with respect to IEEE 802.11 based systems.

The state machine for WiCoP is illustrated in Figure 2.




Figure 2

The Initialization state represents the initial states of WTPs and AC. A WTP or AC in this state powers on, clears internal registers, runs hardware self-tests and resets network interfaces.

The Capabilities Exchange state represents initial protocol exchange between a WTP and an AC. A WTP in this state determines possible ACs from which it can receive management services. An AC in this state determines the capabilities of the WTP and the WTP's compatibility with the management services it offers.

The Connection state represents the creation of a security infrastructure between WTP and AC. This involves mutual authentication and the establishment of a secure connection between the WiCoP entities.

The Configuration state represents the exchange of long-term operational parameters and settings between a WTP and AC. A WTP in this state receives configuration information to allow it to operate consistently within the WLAN managed by the AC. An AC in this state provides configuration information to the WTP based on the WTP's capabilities and network policies.

The Operation state represents the active exchange of WiCoP monitoring and management messages. WTPs send regular status updates to and receive corresponding management instructions from the AC. This state also involves firmware and configuration updates arising from changes in network conditions and administrative policies.

5. WiCoP Format

WiCoP uses separate packets for control and data message transfer between the AC and WTPs. A common header is used for both types of packets in which a single-bit flag distinguishes between them. This section presents the packet formats for WiCoP packets.

5.1 WiCoP Header

Figure 3 illustrates the WiCoP common header for control and data packets.




Figure 3

Version Field

This field indicates the protocol version.

'M' Field

The MAC-type field, 'M', distinguishes between local-MAC WTPs and split-MAC WTPs. It is used to efficiently realize interoperability between WTPs of the two different designs. A '0' value indicates WiCoP exchanges with a split-MAC WTP while a '1' value indicates WiCoP exchanges with a local-MAC WTP.

The presence of this classification bit in the WiCoP common header serves to expedite processing of WiCoP and WLAN traffic at the AC. So with a single parsing of the WiCoP common header once, the AC will be able to determine the appropriate processing required for the particular WiCoP packet.

'D' Field

The differentiator field, 'D', is used to distinguish between WTP variants within a type of WTP design. The CAPWAP Architecture Taxonomy [[I-D.ietf-capwap-arch](#)] illustrates that the split-MAC design allows encryption/decryption to be performed at either the WTP or the AC. The Architecture Taxonomy also indicates that the local-MAC design allows authentication to take place at either the WTP or the AC.

WiCoP acknowledges these major variants and accommodates them using the 'D' field in conjunction with the 'M' field. So for a split-MAC WTP, the 'D' field is used to indicate location of encryption/decryption while for a local-MAC WTP, the 'D' field is used to indicate location of authentication. The following table highlights their usage.

'M'	'D'	Description
0	0	Split-MAC WTP - Encryption/decryption is performed at WTP
0	1	Split-MAC WTP - Encryption/decryption is performed at AC
1	0	Local-MAC WTP - Authentication is performed by WTP
1	1	Local-MAC WTP - Authentication is performed by AC

Similar to the 'M' field, the presence of this classification in the WiCoP common header helps expedite processing at the AC with a single parsing. By incorporating the classification bits in the WiCoP common header, where it is available for all packets of a session, the AC processing can be expedited. Alternatively, the AC would have to check each arriving packet against an internal register and consequently delay processing.

'C' Field

This field distinguishes between a WiCoP control and WiCoP data packet. Each type of information is tunneled separately across the WiCoP tunnel interfaces between WTPs and the AC. A '0' value for the 'C' field indicates a data packet while a '1' value indicates a control packet.

The 'C' field is also used to assign WiCoP packets to distinct data and control tunnels between AC and WTP. WiCoP also maintains logical groups in WLANs with the 'C' field.

'R' Field

The retransmission field, 'R', is used to differentiate between first and subsequent transmission of WiCoP packets. The 'R' field is used for critical WiCoP packets such as those relating to security key exchanges. A '0' value for the 'R' field indicates the first transmission of a WiCoP packet while a '1' value indicates a retransmission.

'E' Field

The encryption field, 'E', is used to indicate if the WiCoP packet is encrypted between the AC and WTPs. The 'E' field is used for those WiCoP packets that are exchanged during initialization. A '0' value indicates the WiCoP packet is unencrypted while a '1' value indicates the packet is encrypted.

'F' Field

The fragmentation field indicates if the packet is a fragment of a larger packet. A '0' value indicates a non-fragmented packet while a '1' value indicates a fragmented packet. The 'F', 'L', 'Fragment ID' and 'Fragment No.' fields are used together.

'L' Field

This field is used to indicate the last fragment of a larger packet. It is only valid when the 'F' field has a '1' value. A '0' value for the 'L' field indicates the last fragment of a larger packet while a '1' value indicates an intermediate fragment of a larger packet. The 'F', 'L', 'Fragment ID' and 'Fragment No.' fields are used together.

Fragment ID Field

The Fragment ID identifies the larger packet which has been fragmented. It is used to distinguish between fragments of different large packets. This field is valid only when the 'F' field has a '1' value. The 'F', 'L', 'Fragment ID' and 'Fragment No.' fields are used together.

Fragment No. Field

The fragment number field identifies the sequence of fragments of a

larger packet. The value of the Fragment No. field is incremented for each fragment of a larger packet so as to show the order of fragments. This field is valid only when the 'F' field has a '1' value. The 'F', 'L', 'Fragment ID' and 'Fragment No.' fields are used together.

Length Field

This field specifies the length of the WiCoP payload following the header.

5.2 WiCoP Control Packet

The WiCoP control header follows the WiCoP common header. It is highlighted in Figure 5.




Figure 5

The control packet adds four additional fields to the common header. These are described below;

Msg Type Field

The message type field specifies the type of control message transported in the packet. The list of control messages is presented below.

Seq Num Field

The sequence number field is used to map WiCoP request and response sequences. The initiator of a WiCoP request message increments the Seq Num field for each new request message. The responder then uses these values of the Seq Num fields in its corresponding response messages.

Msg Element Length Field

This field specifies the length in bytes of the subsequent WiCoP control message element.

[5.2.1](#) WiCoP Control Messages

The list of WiCoP control messages is shown below;

Message	Msg Type
-----	-----
Capabilities	1
Capabilities Response	2
Connection	3
Connection Response	4
Configuration Request	5
Configuration Response	6
Configuration Data	7
Configuration Data Response	8
Configuration Trigger	9
Configuration Trigger Response	10
Feedback	11
Feedback Response	12
Reset	13
Reset Response	14
Firmware Download	15
Firmware Download Response	16
Terminal Addition	17
Terminal Addition Response	18
Terminal Deletion	19
Terminal Deletion Response	20
Key Configuration	21
Key Configuration Response	22
Notification	23
Notification Response	24

[5.2.2](#) WiCoP Control Message Elements

WiCoP control messages each include a control message header followed by one or more message elements. The message elements are shown in the following table.

Message Element	Type	Description
WTP-Info	1	Information regarding WTPs, such as manufacturer ID, MAC address, etc.
Cap-from-WTP	2	QoS abilities (WME) and security abilities (IEEE 802.11i) are included
Conf-If-Data	3	PHY information for each wireless interface
Conf-WTP-Data	4	Information regarding logical groups on a per-logical group basis (e.g. per-virtual AP)
Cap-to-WTP	5	Setup data sent to WTPs by AC on a per-logical group basis
QoS-Value	6	QoS setup (access categories)
Timer-Init-Value	7	Initial values of timers such as aging, echo interval etc.
Terminal-Data	8	Information relevant to wireless terminals - BSSID, association ID, etc.
BSSID	9	BSSID, and terminal MAC address
Encryption-Data	10	Details of the security framework - cipher suit, operation mode etc.
EAP-Frame	11	EAP frame
Statistics	12	Various statistics information - transmission attempts, FCS errors etc.
Interface-Error	13	Type of wireless interface failure
FROM-Error	14	Flash ROM Error information
QoS-Capability	15	Network congestion information
TFTP-Data	16	Firmware related details

Result	17	Result of protocol operations -	
		success or failure	
OID	18	SNMP OIDs	
GTK-Flag	19	Determines type of GTK - new or	
		existing	
+-----+	+-----+	+-----+	+-----+

Each message element comprises a number of information items that are detailed below. The length of each information item is specified in bytes.

WTP-Info:

Information included in the WTP-Info message element is provided on a per-WTP basis. So each WTP exchanges one WTP-Info message element.

+-----+	+-----+	+-----+	+-----+
Item	Length	Syntax	Description
+-----+	+-----+	+-----+	+-----+
Manufacturer	8	DisplayString	Manufacturer ID
ID			
MAC Address	6	PhyAddress	WTP MAC Address
Firmware	8	DisplayString	Firmware version of
Version			WTP
Start Time	4	TimeTicks	Starting time of WTP
			(UNIX Time)
+-----+	+-----+	+-----+	+-----+

Cap-from-WTP:

Information included in the Cap-from-WTP message element is provided on a per-WTP basis. So each WTP exchanges one Cap-from-WTP message element.

Item	Length	Syntax	Description
802.11e Cap Length	2	Integer	Length of 802.11e Capabilities
802.11e Capabilities	Variable	OCTETString	802.11e capabilities of WTP. If WTP does not have such capabilities, this field is filled with '0'
802.11i Cap Length	2	Integer	Length of 802.11i Capabilities
802.11i Capabilities	Variable	OCTETString	802.11i capabilities of WTP. If WTP does not have such capabilities, this field is filled with '0'
AuthType	2	OCTETString	Type of authentication mechanism used between WTP and AC

Conf-If-Data

The Conf-If-Data message element relates to the wireless interface. So a WTP with many interfaces will include corresponding numbers of Conf-If-Data message elements within its control messages to the AC. Conf-If-Data message elements are indexed by the If ID information item.

Item	Length	Syntax	Description
If ID	1	Integer	Denotes identification of a wireless interface
Current Power	1	Integer	Current Power Level ('1' = Max; '2' = 1/2; '3' = 1/4; '4' = 1/8)

Radio Channel	1	Integer	Radio channel of operation
2Dot4Mode	1	Integer	Interface mode in 2.4GHz. ('1' = IEEE 802.11b; '2' = IEEE 802.11g; '3' = Both)

Conf-WTP-Data

Configuration information is provided on the basis of logical groups such as virtual APs. So there are multiple Conf-WTP-Data message elements to address the many logical groups within a WLAN managed by WiCoP. Conf-WTP-Data message elements are indexed by the BSSID information item.

Item	Length	Syntax	Description
BSSID	6	OCTETString	BSSID
ESSID	32	OCTETString	ESSID
BSSID - TunnelID	32	OCTETString	Mapping for logical groups across BSSID and WiCoP tunnels
Beacon Period	1	Integer	Time interval between Beacon transmissions
DTIM Period	1	Integer	DTIM period of Beacon transmissions
AnyRejectFlag	1	Integer	Flag indicating WTP rejection of any Probe Request within any SSID - ('1' = Rejected; '2' = Not Rejected)
SSID Stealth Flag	1	Integer	Flag indicating inclusion of ESSID within Beacon Frames ('1' = ESSID included; '2' = ESSID not included)

Operation Rate Set	2	Integer	Data rates supported by WTP for terminal being added using 12 bit format for 1.1, 2.2, 3.55, 4.6, 5.9, 6.11, 7.12, 8.18, 9.24, 10.36, 11.48 and 12.54 Mbps
Encryption Type	1	Integer	Encryption Type - （'1' = OFF; '2' = WEP40; '3' = WEP104; '4' = WEP128)
Encryption Key	16	OCTETString	Static Encryption Key
+-----+-----+-----+-----+			

Cap-to-WTP:

Capabilities information is provided on the basis of logical groups such as virtual APs. So there are multiple Cap-to-WTP message elements to address the many logical groups within a WLAN managed by WiCoP. Conf-to-WTP message elements are indexed by the BSSID information item. If logical groups are created by other means, their corresponding identifier is used as the index.

Item	Length	Syntax	Description
BSSID	6	OCTETString	BSSID
802.11e Cap Length	2	Integer	Length of 802.11e Capabilities
802.11e Capabilities	Variable	OCTETString	802.11e capabilities of WTP. If WTP does not have such capabilities, this field is filled with '0'
802.11i Cap Length	2	Integer	Length of 802.11i Capabilities

802.11i	Variable	OCTETString	802.11i capabilities	
Capabilities			of WTP. If WTP does	
			not have such	
			capabilities, this	
			field is filled with	
			'0'	
+-----+	+-----+	+-----+	+-----+	+-----+

QoS-Value:

QoS parameters are assigned for each logical group to address their respective individual conditions and requirements. QoS-Value message elements are provided on a per-logical group basis. They are indexed by the BSSID information item. If logical groups are created by other means, their corresponding identifier is used as the index.

Item	Length	Syntax	Description	
+-----+	+-----+	+-----+	+-----+	+-----+
BSSID	6	OCTETString	BSSID	
WTP AC_BE	2	Integer	AC Parameters Record	
			AC_BE in WTP	
WTP AC_BK	2	Integer	AC Parameters Record	
			AC_BK in WTP	
WTP AC_VI	2	Integer	AC Parameters Record	
			AC_VI in WTP	
WTP AC_VO	2	Integer	AC Parameters Record	
			AC_VO in WTP	
TE AC_BE	2	Integer	AC Parameters Record	
			AC_BE in terminals	
TE AC_BK	2	Integer	AC Parameters Record	
			AC_BK in terminals	
TE AC_VI	2	Integer	AC Parameters Record	
			AC_VI in terminals	
TE AC_VO	2	Integer	AC Parameters Record	
			AC_VO in terminals	
+-----+	+-----+	+-----+	+-----+	+-----+

Timer-Init-Value:

WiCoP timers are used for the WTP as a whole. So the Timer-Init-Value message element is provided on a per-WTP basis.

Item	Length	Syntax	Description
BSSID	6	OCTETString	BSSID
Response Timer	4	Integer	Initial value of Response Timer
Active Presence Timer	4	Integer	Initial value of Active Presence Timer
Feedback Interval Timer	4	Integer	Initial value of Feedback Interval Timer

Terminal-Data:

The Terminal-Data message element is applicable for both local-MAC and split-MAC WTP designs. In the case of local-MAC, Terminal-Data is sent from WTPs to the AC. In the case of split-MAC, Terminal-Data is sent from the AC to WTPs. So the direction of usage depends on the type of WTP at which wireless terminal operations are performed. Some information items may be optional for use with specific WTP designs.

Item	Length	Syntax	Description
BSSID	6	PhyAddress	BSSID in which terminal is being added
MAC Address	6	PhyAddress	MAC address of terminal being added
Association ID	2	Integer	Association ID of terminal being added

Operation	2	Integer	Data rates supported	
Rate Set			by WTP for terminal	
			being added using 12	
			bit format for 1.1,	
			2.2, 3.55, 4.6, 5.9,	
			6.11, 7.12, 8.18,	
			9.24, 10.36, 11.48 and	
			12.54 Mbps	
Listen	2	Integer	Listen period	
Period				
+-----+	+-----+	+-----+	+-----+	+-----+

BSSID:

The BSSID message element is used to identify logical groups within a WLAN. WiCoP may be extended for other types of logical groups by simply including additional message elements.

+-----+	+-----+	+-----+	+-----+	+-----+
Item	Length	Syntax	Description	
+-----+	+-----+	+-----+	+-----+	+-----+
BSSID	6	PhyAddress	BSSID in which	
			terminal is being	
			added	
MAC Address	6	PhyAddress	MAC address of	
			terminal being added	
+-----+	+-----+	+-----+	+-----+	+-----+

Encryption-Data:

The Encryption-Data message element contains information relevant for configuring security keys at WTPs. It is used in architectures in which the authentication and encryption points are located in distinct WLAN entities.

Item	Length	Syntax	Description
MAC Address	6	PhyAddress	MAC address of terminal
Operation	1	Integer	Operational Mode ('1' = Set Key; '2' = Delete Key)
Key Index	1	Integer	Key Index - valid when Operational Mode = Set Key
Key Flag	1	Integer	Key Flag ('1' = Unicast Key or PTK; '2' = Broadcast Key or GTK) - valid only when Operational Mode = Set Key
Cipher Suit	1	Integer	Encryption Type ('1' = WEP40; '2' = WEP104; '3' = WEP128; '4' = TKIP; '5' = AES) - valid only when Operational Mode = Set Key
Key	32	OCTETString	Key body - valid only when Operational Mode = Set Key

EAP-Frame:

The EAP-Frame message element is used to carry EAP frames used in the configuration and management of the WLAN.

Item	Length	Syntax	Description
MAC Address	6	PhyAddress	MAC address of terminal
EAP	Variable	OCTETString	EAP Frames

Statistics:

Statistics information covers all aspects of WTPs. As such, this message element is provided on a per-WTP basis. WiCoP messages containing the Statistics message element simultaneously serve as keep alive signals between WTPs and AC.

Item	Length	Syntax	Description
OutOctet	4	Counter 32	Octet number of frame WTP transmits
Transmit Count	4	Counter 32	Total number of frames transmitted by WTP
Successful Transmit Count	4	Counter 32	Total number of ACKs received
ACK Failure Count	4	Counter 32	Total number of failed ACKs
InOctets	4	Counter 32	Octet number of frame WTP receives
Receive Count	4	Counter 32	Total number of frames received by WTP
Receive Discard	4	Counter 32	Total number of received frames that are discarded
Retransmission Count	4	Counter 32	Number of WTP retransmission attempts"
Duplicate Receive Count	4	Counter 32	Number of duplicate frames received by WTP
FCS Error Receive Count	4	Counter32	Number to frames received with FCS errors

Unknown	4	Counter 32	Number of unknown	
Frame			protocol frames	
Receive			received	
Count				
Beacon	4	Counter 32	Number of transmitted	
Transmit			Beacon frames	
Count				
Probe	4	Counter 32	Number of transmitted	
Transmit			Probe Response frames	
Count				
Probe	4	Counter 32	Number of received	
Receive			Probe Response frames	
Count				
Decrypt CRC	4	Counter 32	Number of received	
Error Count			frames that cannot	
			decrypt	
+-----+	+-----+	+-----+	+-----+	+-----+

Interface-Error:

This message element is used to exchange information on error conditions related to the wireless interface.

Item	Length	Syntax	Description	
+-----+	+-----+	+-----+	+-----+	+-----+
Interface	1	Integer	Interface ID	
Index				
Error Type	1	Integer	Type of error ('1' =	
			Unrecoverable; '2' =	
			Recoverable)	
+-----+	+-----+	+-----+	+-----+	+-----+

FROM-Error:

The FROM-Error message element is used to exchange information on error conditions related to flash ROMs in WTPs or the AC.

Item	Length	Syntax	Description
FROM Index	1	Integer	FROM ID
Error Type	1	Integer	Type of error ('1' = Unrecoverable; '2' = Recoverable)

QoS Capability:

The QoS-Capability message element is used to exchange information concerning the EDCA and HCCA capabilities of WTPs.

Item	Length	Syntax	Description
EDCA	1	Integer	EDCA Capability ('1' = Capable; '2' = Not capable)
HCCA	1	Integer	HCCA Capability ('1' = Capable; '2' = Not capable)

TFTP-Data:

This message element is for firmware data from AC to WTPs.

Item	Length	Syntax	Description
TFTP Data	Variable	OCTETString	Details of TFTP

Result:

The Result message element is used in all WiCoP response messages to indicate the status of WiCoP request messages.

Item	Length	Syntax	Description
Result Code	1	Integer	'1' = OK; '2' = NG

OID:

The OID message element is used for general configuration information specified by OIDs.

Item	Length	Syntax	Description
Length	1	Integer	Length of OID String and OID Value
OID String	Variable	OCTETString	Object Identifier that is assigned according to Basic Encoding Rules (BER)
Value	Variable	OCTETString	Value

GTK-Flag:

The GTK-Flag message element is used to inform the WTP on the type of GTK used and correspondingly how the KeyMIC is to be computer.

Item	Length	Syntax	Description
GTK Flag	1	Integer	Determines the type of GTK ('1' = New; '2' = Existing)

5.2.3 WiCoP Control Message Description

Message: Capabilities

Direction: WTP -> AC

Type: Request

Description: WTPs send Capabilities message upon transitioning from the Initialization state to Capabilities Exchange state. The message serves to discover and identify the controlling AC of the WLAN and to provide it with identification and capabilities information. In the IEEE 802.11 use-case, the Capabilities message also specifies the WTP's IEEE 802.11e and IEEE 802.11i features.

TLV: The Capabilities message includes message elements of types 1 and 2.

```

+-----+
|  Capabilities  |
+-----+
|    WTP-Info    |
|                |
|  Cap-from-WTP  |
+-----+

```

Message: Capabilities Response

Direction: AC -> WTP

Type: Response

Description: This message is sent by an AC after examining the compatibility of the WTP and its capabilities. The compatibility is with respect to the MAC architecture that can be supported by the AC. If the WTP is determined to be compatible, the Capabilities Response message also contains information on the capabilities of the AC.

TLV: The Capabilities Response message includes message elements of types 5 and 17. The Cap-to-WTP message elements are distinguished based on BSSIDs to represent different logical groups.

```

+-----+
| Capabilities Response |
+-----+
|   Cap-to-WTP 1       |
|   Cap-to-WTP ...     |
|   Cap-to-WTP n       |
|       Result         |
+-----+

```

Message: Connection

Direction: WTP -> AC

Type: Request

Description: The Connection message initiates the mutual security association between AC and WTPs. This message carries the first message of the chosen security protocol. The specific security mechanism for the authentication is out of scope of the WiCoP specifications.

TLV: The Connection message includes message elements of type 2.

```
+-----+
|  Connection  |
+-----+
| Cap-from-WTP |
+-----+
```

Message: Connection Response

Direction: AC -> WTP

Type: Response

Description: After completion of the security protocol exchange, this message indicates the result of the WTP-AC security association. If successful, it also represents the admission of the WTP into the WLAN.

TLV: Type 17 message element is included.

```
+-----+
| Connection Response |
+-----+
|           Result           |
+-----+
```

Message: Configuration Request

Direction: WTP -> AC

Type: Request

Description: This message starts the Configuration state for the WTP. It is a request for configuration information from the WTPs to the AC.

Message: Configuration Response

Direction: AC -> WTP

Type: Response

Description: This is an acknowledgement for the Configuration Request message.

TLV: Type 17 message element is included.

```
+-----+
| Configuration Response |
+-----+
|           Result           |
+-----+
```

Message: Configuration Data

Direction: AC -> WTP

Type: Request

Description: Configuration information including operational parameters, QoS settings and timer values is sent using the Configuration Data message. This message is also used for configuration updates in the Operation state of WiCoP.

TLV: This message includes message elements of type 3, 4, 5, 6 and 7. The Conf-WTP-Data and QoS-Value message elements are identified by BSSIDs to denote logical groups, while the Conf-If-Data message elements are identified by If-IDs to denote multiple wireless radios.


```

+-----+
| Configuration Data |
+-----+
| Conf-If-Data 1     |
|                   |
| Conf-If-Data ...   |
|                   |
| Conf-If-Data n     |
|                   |
| Conf-WTP-Data 1    |
|                   |
| Conf-WTP-Data ...  |
|                   |
| Conf-WTP-Data n    |
|                   |
|   Cap-to-WTP 1     |
|                   |
|   Cap-to-WTP ...   |
|                   |
|   Cap-to-WTP n     |
|                   |
|   QoS-Value 1      |
|                   |
|   QoS-Value ...    |
|                   |
|   QoS-Value n      |
|                   |
| Timer-Init-Value   |
+-----+

```

Message: Configuration Data Response

Direction: WTP -> AC

Type: Response

Description: This is an acknowledgement for the Configuration Data message.

TLV: Type 17 message element is included.

```

+-----+
| Configuration Data Response |
+-----+
|           Result           |
+-----+

```

Message: Configuration Trigger

Direction: AC -> WTP

Type: Request

Description: This message is used to trigger the activation of the configuration information sent in earlier Configuration messages.

Message: Configuration Trigger Response

Direction: WTP -> AC

Type: Response

Description: This is an acknowledgement of the Configuration Trigger. This response message is sent before activation of the configuration information.

TLV: Message elements of type 17 are included.

```
+-----+
| Configuration Trigger Response |
+-----+
|           Result           |
+-----+
```

Message: Reset

Direction: AC -> WTP

Type: Request

Description: This message from the AC instructs the WTP to clear registers and revert to initial conditions.

Message: Reset Response

Direction: WTP -> AC

Type: Response

Description: This is an acknowledgement for the Reset message to the AC.

TLV: Message elements of type 17 are included.

```
+-----+
| Reset Response |
+-----+
|     Result     |
+-----+
```


Message: Feedback

Direction: WTP <-> AC

Type: Request

Description:

WTP: The Feedback message is used to send regular statistics information to the AC. It also serves as a keepalive indicator used to update the Active Presence Timer maintained by the AC.

AC: The Feedback message is used to determine the active state of WTPs.

TLV: This message includes message elements of type 12.

```
+-----+
|  Feedback  |
+-----+
| Statistics  |
+-----+
```

Message: Feedback Response

Direction: WTP <-> AC

Type: Response

Description: This is an acknowledgement for Feedback messages.

TLV: Message elements of type 17 are included.

```
+-----+
| Feedback Response |
+-----+
|      Result      |
+-----+
```

Message: Firmware Download

Direction: AC -> WTP

Type: Request

Description: This message is used to instruct WTPs to update their firmware. The message element contains information regarding the new firmware.

TLV: Message elements of type 16 are included.


```
+-----+
| Firmware Download |
+-----+
|   TFTP-Data   |
+-----+
```

Message: Firmware Download Response

Direction: WTP -> AC

Type: Request Response

Description: This is an acknowledgement for the Firmware Download message.

TLV: Message elements of type 17 are included.

```
+-----+
| Firmware Download Response |
+-----+
|           Result           |
+-----+
```

Message: Notification

Direction: WTP <-> AC

Type: Request

Description: This message is used to indicate non-periodic events. It may be sent by either WTPs or the AC. Notification messages indicate failures, non-periodic changes etc.

TLV: Message elements of types 13 and 14 are included.

```
+-----+
| Notification |
+-----+
| Interface-Error |
|                 |
|   FROM-Error   |
+-----+
```

Message: Notification Response

Direction: WTP <-> AC

Type: Response

Description: This is an acknowledgement for the Notification message. It may be followed by Configuration messages to rectify errors.

TLV: Message elements of type 17 are included.

```

+-----+
| Notification Response |
+-----+
|           Result           |
+-----+

```

Message: Terminal Addition

Direction: WTP <-> AC

Type: Request

Description: This message may be sent from WTPs or the AC depending on the WTP type in consideration. In both cases it is sent in response to an IEEE 802.11 association frame.

For split-MAC WTPs, Terminal Addition is sent from the AC to the WTPs and includes information on the wireless terminal relevant to the WTP.

For local-MAC WTPs, Terminal Addition is sent from a WTP to the AC and contains information on the wireless terminal relevant to the AC.

TLV: Message elements of type 8 are included.

```

+-----+
| Terminal Addition |
+-----+
|   Terminal-Data   |
+-----+

```

Message: Terminal Addition Response

Direction: WTP <-> AC

Type: Response

Description: This is an acknowledgement sent from either WTPs or the AC depending on the WTP type in consideration.

TLV: Message elements of type 17 are included.

```

+-----+
| Terminal Addition Response |
+-----+
|           Result           |
+-----+

```


Message: Terminal Deletion

Direction: WTP <-> AC

Type: Request

Description: This message is sent in response to a disconnection of a wireless terminal. It can be sent from WTPs or the AC. In both cases, Terminal Deletion instructs the recipient to remove any state information relating to the specific wireless terminal. The message is sent in response to an IEEE 802.11 disassociation frame, IEEE 802.11 deauthentication frame or due to the expiration of the Active Presence Timer.

For split-MAC WTPs, Terminal Deletion is sent from the AC to the WTPs.

For local-MAC WTPs, Terminal Deletion is sent from the WTPs to the AC.

TLV: Message elements of type 9 are included.

```
+-----+
| Terminal Deletion |
+-----+
|      BSSID      |
+-----+
```

Message: Terminal Deletion Response

Direction: WTP <-> AC

Type: Response

Description: This is an acknowledgement sent from either WTPs or the AC depending on the WiCoP interface.

TLV: Message elements of type 17 are included.

```
+-----+
| Terminal Addition Response |
+-----+
|      Result      |
+-----+
```

Message: Key Configuration

Direction: AC -> WTP

Type: Request

Description: This message is used when authentication and encryption

points are located in distinct WLAN entities. WiCoP uses it cases where 'M' = 0 and 'D' = 0 or where 'M' = 1 and 'D' = 1. It is used to configure security key information from the AC to the WTPs.

TLV: The following message elements are included for Key Configuration.

```

+-----+
| Key Configuration |
+-----+
|      GTK-Flag      |
|                    |
| Encryption-Data    |
|                    |
|      EAP-Frame     |
+-----+

```

Message: Key Configuration Response

Direction: WTP -> AC

Type: Response

Description: This is an acknowledgement for the Key Configuration message.

TLV: Message elements of type 17 are included.

```

+-----+
| Key Configuration Response |
+-----+
|           Result           |
+-----+

```

[5.3](#) WiCoP Data Packet

WiCoP data packets include the WiCoP common header followed by a payload. Data packets are used to distinguish traffic from control when both control and data paths are identical. Such a scenario would involve data traffic of the WTPs traversing the AC. However, given the diversity of large-scale WLAN deployments, there are scenarios in which data and control paths are distinct. WiCoP can be used in both cases.

The WiCoP data packet format is illustrated below in Figure 7 together with the WiCoP common header.




Figure 7

5.4 WiCoP Timers

WiCoP uses a number of timers to determine WLAN status and maintain system performance. Timers are maintained by all WiCoP entities.

5.4.1 Active Presence Timer

The Active Presence Timer is used by each WiCoP entity - AC and WTPs - to verify the presence of each other. The absence of a reply to the Feedback message within the expiration of the Active Presence Timer indicates the corresponding entity is inactive. Contingency operations such as reset are used in this case. The value of the Active Presence Timer ranges from 10 to 300 seconds with a default value of 30 seconds.

5.4.2 Feedback Interval

Feedback messages are periodic with the frequency defined by the Feedback Interval. The interval is set during WTP configuration. It has a value ranging from 1 to 100 seconds and a default value of 10 seconds.

The Feedback Interval timer sets the periodicity of WLAN system audits. So with this timer, the WLAN controller receives regular information on the state of the WLAN and all its WTPs.

5.4.3 Response Timer

This is a general purpose timer used to limit the elapsed time between transmission of a request message and receipt of a corresponding response message. The value of this timer ranges from

1 to 3 seconds with a default value of 1 second.

[5.4.4](#) Wireless Connectivity Timer

This timer triggers any changes in wireless connectivity. WiCoP uses this timer to send Notification and other messages relating to wireless conditions. It is also used to trigger the disconnection of mobile terminals without disassociation. The value of the Wireless Connectivity Timer ranges from 1 minute to 86,400 minutes with a default value of 10 minutes.

6. WiCoP Processes

The processes of the Wireless LAN Control Protocol are described in this section with respect to the operational state in which they occur.

6.1 Initialization

The Initialization state represents the initial conditions of WiCoP entities. WTPs and ACs in this state are powered on, run hardware self-check tests and reset network interfaces.

State transition: Initialization -> Capabilities Exchange

WTP: Automatically upon detecting an active network interface

AC: Upon receiving a Capabilities message from a WTP

6.2 Capabilities Exchange

The Capabilities Exchange state allows WTPs to first find an AC and then to exchange capabilities information with it.

WiCoP is designed to control WLANs with both local-MAC and split-MAC WTPs. The differences in their respective functional characteristics are determined in this state.

The WTP first broadcasts a Capabilities message as soon as it transitions from its Initialization state. The Capabilities message serves to discover ACs and contains information on its identity and capabilities.

The AC receiving the Capabilities message transitions from its Initialization state. It examines compatibility with respect to the WTP type, its capabilities and responds with an appropriate Capabilities Response message.

The WTP continues to send Capabilities messages at an interval specified by the Response Timer until it receives a Capabilities Response message from an AC.

The AC maintains a count of Capabilities messages received from a given WTP, which it uses to ignore WTPs after a limit. This is to ensure that rogue WTPs which are not compatible with the AC do not repeatedly attempt connections. The limit of connection attempts is 3 within 60 seconds.

State transition: Capabilities Exchange -> Connection

WTP: Upon receiving a positive Capabilities Response message from an AC

AC: Upon receiving a Connection Request message from a WTP

6.3 Connection

The Connection state involves establishing a security infrastructure between WTPs and an AC.

The WTP sends a Connection message to trigger the authentication and security mechanism. So this message initiates an IPSec security association.

The AC sends a positive Connection Response message after establishment of the security association or a negative Connection Response message if an error occurs. The AC also monitors the receipt of WiCoP control messages to prevent replay attacks.

The security association between AC and WTPs covers mutual authentication and also protection for integrity, confidentiality and modification protection for subsequent traffic exchanges.

In order to avoid forceful disconnections of legitimate WTPs after a successful Connection, the AC ignores Capabilities messages received with a previously registered WTP identification.

State transition: Connection -> Configuration

WTP: Upon successful establishment of security infrastructure marked by sending of a Configuration Request message

AC: Upon receiving Configuration Request message from WTP after successful establishment of security infrastructure

State transition: Connection -> Capabilities Exchange

WTP: Upon expiry of WTP Response Timer before receipt of positive Connection Response message from AC or upon receipt of negative Connection Response message

AC: Upon expiry of AC Response Timer before receipt of Configuration Request message from WTP

6.4 Configuration

The Configuration state is one in which relatively long-term operational parameters such as those for identification and logical groups, are exchanged. These parameters are based on previously exchanged capabilities information and network policies.

The WTP sends a Configuration Request message to the AC.

The AC first acknowledges the WTP's Configuration Request, after which it sends appropriate configuration information in subsequent

Configuration Data messages. WiCoP includes MIB objectives as message elements in some Configuration Data messages so as to simplify WTP configuration.

The WTP acknowledges Configuration Data messages individually or en bloc with Configuration Data Response messages. The Response timer is maintained at both WTP and AC to track the exchanges.

The AC also establishes relevant processing schedules according to the WTP's architecture design. For example, for split-MAC WTPs, the AC arranges its processing schedule to parse IEEE 802.11 control and management messages while for local-MAC WTPs, the AC arranges schedules processing so as to bypass parsing of IEEE 802.11 management messages.

The AC sends a Configure Trigger message after sending all relevant configuration information to the WTP.

The WTP acknowledges a Configure Trigger message with a Configure Trigger Response message before activating the previously exchanged configuration parameters.

In order to avoid forceful disconnections of legitimate WTPs after successful Configuration, the AC ignores Capabilities messages received with a previously registered WTP identification.

State transition: Configuration -> Operation

WTP: After receiving final Configuration Data message from AC

marked by receipt of a Configure Trigger message from the AC

AC: Upon receiving acknowledgement for Configure Trigger message

marked by receipt of Configure Trigger Response message from WTP

State transition: Configuration -> Capabilities Exchange

WTP: Upon expiry of WTP Response Timer before receipt of

Configure Trigger message from AC

AC: Upon expiry of AC Response Timer before receipt of Configure

Data Response message or Configure Trigger Response message

The following describe major configuration aspects of WiCoP.

6.4.1 Logical Groups

Configuration Data messages are used to establish logical groups in the WLAN and also to separate traffic among them. The logical groups are established based on network administrative policies and other external considerations. In the IEEE 802.11 use-case, logical groups are established with BSSID-based virtual APs and are separated over the WiCoP interface using tunnels.

The AC assigns particular BSSIDs of the WTP to specific VLAN tunnels. This assignment is specified to the WTP using the BSSID-TunnelID parameter in the Configuration Data message. The logical group mapping therefore works across the wireless and WiCoP interfaces.

The WTP then identifies the specified BSSID and VLAN tunnel as corresponding to one logical group. It creates internal state such that traffic belonging to the logical group is kept distinct from that of other logical groups.

The AC and WTP also use distinct VLAN tunnels for data and control traffic. The 'C' field in the WiCoP header is used to distinguish and assign WiCoP packets to particular data and control VLAN tunnels.

6.4.2 Resource Control

The AC sends QoS information using QoS-Value message elements in Configuration Data messages. The QoS-Value message element contains values for EDCA and HCCA parameters. This information is specified for each of the logical groups. In the IEEE 802.11 use-case, QoS-Value message elements are specified for each BSSID.

The WTP configures QoS parameters locally and also forwards relevant settings to wireless terminals in appropriate encapsulations. In the IEEE 802.11 use-case, QoS parameters are sent to wireless terminals in corresponding Beacon or Probe Response frames.

6.5 Operation

This is the active operation state of the WLAN in which short-term dynamics are examined.

The WTP begins operations according to the operational parameters exchanged in the previous Configuration state.

The AC monitors WTPs according to network administrative policies and configurations.

In order to avoid forceful disconnections of legitimate WTPs after successful Operation setup, the AC ignores Capabilities messages received with a previously registered WTP identification.

State transition: Operation -> Capabilities Exchange

WTP: Upon expiry of WTP Active Presence Timer before receipt of Feedback Response message from AC

AC: Upon expiry of AC Active Presence Timer before receipt of Feedback message from WTP

State transition: Operation -> Initialization

WTP: Upon receipt of Reset message from AC

AC: Upon receipt of Reset Response message from WTP

The following describe major operation aspects of WiCoP.

6.5.1 Updates

The dynamic nature of WLAN systems requires regular updates to network operations.

The AC sends additional configuration information in the Configuration Data messages. This is applicable to establishment of new logical groups, changes to existing logical groups, changes in QoS settings etc. Configuration information is followed by a Configure Trigger message.

The WTP sends a Configure Trigger Response before activating the additional configuration information.

Configuration updates can be used to clear statistics information by reflecting initial values.

An extreme case of configuration update involves use of the Reset message from the AC, which instructs the WTP to revert to initial conditions. The WTP replies with a Reset Response message before reverting to its initial state.

6.5.2 Feedback and Statistics

The Operation state also sees regular feedback being sent by WTPs to the AC.

The WTP sends Feedback messages to indicate various statistics and congestion condition information. Feedback also includes information on the state of the WTP and wireless medium such as queue levels and channel interference. Feedback messages are sent with a frequency defined by the Feedback Interval. In addition to statistics, the Feedback message also serves as a WTP keepalive indicator to the AC. So Feedback messages combine statistics information together with WTP status information.

The AC monitors Feedback messages for their statistics value and implicit indication of WTP activity. The AC also tracks the state of congestion at wireless terminals and WTPs. This information enables the AC to adapt its downstream transmissions, such as scheduling transmission away from congested WTPs, so as to relieve congestion.

The AC additionally uses the Feedback message to randomly determine the active state of WTPs. An active WTP replies with a corresponding Feedback Response message.

6.5.3 Non-periodic Events

The WTP and AC use the Notification message for non-periodic events. They send Notification messages to indicate error conditions or drastic changes in congestion state.

The recipient of the Notification message acknowledges with a Notification Response message. The response may contain information on rectifying the error or may simply be an acknowledgement of the Notification.

6.5.4 Firmware Trigger

The AC sends a Firmware Download message to update firmware at WTPs. The Firmware Download message contains TFTP information, which the WTP uses to refresh its firmware. This is used when a new version of firmware is available for the WTPs.

The WTP acknowledges new firmware with a Firmware Download Response message after which it is activated.

6.5.5 Wireless Terminal Management

The Operation state of WiCoP also involves configuration of WTPs and the AC with wireless terminal specific information.

Here the Terminal Addition message is used in response to a new wireless terminal entering the WLAN. This message may be sent by either the WTPs or the AC depending on the WiCoP interface being used. The recipient of this message replies with the Terminal Addition Response message.

The Terminal Deletion message is used when a wireless terminal leaves the WLAN. This is used to delete state information that was maintained by either the WTPs or the AC. It is acknowledged with the Terminal Deletion Response message.

Figure 8 below illustrates the exchange of Terminal Addition and Terminal Deletion messages for both local-MAC and split-MAC based WiCoP interfaces.

Here the WiCoP Terminal Addition message is triggered as a response to IEEE 802.11 Association message. In the case of local-MAC architecture, the WTP sends the message to the AC. However, in the

split-MAC architecture, Terminal Addition is sent from AC to the WTP.




Figure 8

6.5.6 Key Configuration

One of the differences between split-MAC and local-MAC WTPs is the location of the over-the-air encryption. Some split-MAC and local-MAC WTPs perform encryption locally while others leave it to the AC. WiCoP accommodates these differences by enabling security key configuration in those cases where encryption is performed at the WTP. The encryption setup process is therefore contingent on the WiCoP protocol interface.

When dynamic WEP is used, the WiCoP Key Configuration message is used to notify WTPs of encryption keys for each associated wireless terminal. Here, the EAPoL Key frame is encapsulated in the Key Configuration message and sent to a WTP. Upon receiving the Key Configuration message, the WTP sets the encryption key in its local security table, decapsulates the EAPoL Key frame and forwards it to the wireless terminal. This is illustrated in Figure 9.




Figure 9

When WPA or IEEE 802.11i is used in WLAN architectures in which the

authenticator is located at the AC and encryption points at WTPs, the exchanges of the 4-way handshake are managed distinctly. This is because the AC is no longer in a position to calculate the KeyMIC as it is not aware of the KeyRSC sequence counter. So here, WiCoP Key Configuration message is used to transport the 3rd message of the 4-way handshake - containing the EAPoL-Key - with unassigned KeyRSC and KeyMIC fields. When the WTP receives the WiCoP Key Configuration message, it first assigns the sequence number value to the KeyRSC field. Then, the WTP calculates the KeyMIC value using the PTK and KeyRSC. So the WiCoP Key Configuration message allows the KeyMIC to be calculated at the WTPs instead of the AC. The GTK-Flag message element is used to determine how the KeyMIC is calculated - in case of new GTK, KeyMIC is computed with a KeyRSC value of 0 and in case of an existing GTK, KeyMIC is computed with a KeyRSC value corresponding to the actual counter.

Figure 10 illustrates this case where the WiCoP common header is either 'M' = 0 and 'D' = 0 or 'M' = 1 and 'D' = 1.




Figure 10

The 1st, 2nd and 4th messages of the 4-way handshake are transported in WiCoP data packets that are assigned priorities similar to that of WiCoP control packets.

Similarly, for the group key handshake in WPA and IEEE 802.11i, the 1st message of the handshake is transported using the WiCoP Key Configuration message with unassigned KeyRSC. The WTP again assigns the sequence number value to the KeyRSC and then calculates the KeyMIC. The 2nd message of the handshake however is transported in WiCoP data packets with priorities similar to that of WiCoP control packets. This is illustrated in Figure 11.




Figure 11

The Key Configuration Response message is used by the WTP to notify the AC of the encryption setup process.

7. WiCoP Performance

WiCoP is an efficient protocol. This section illustrates various examples of its efficiency.

7.1 Operational Efficiency

The fact that WiCoP requires a single operation to distinguish and manage WTPs of different designs makes it operationally efficient. Because WiCoP assigns dedicated classification bits in the common header, an AC needs to parse incoming packets only once to determine the particular manner in which it is to be processed. Without the dedicated classifications in the common header, an AC would have to perform a lookup after parsing every incoming packet, which would result in delaying processing. The scale and sensitivity of large-scale deployments require that WLAN control protocols be efficient in operation.

7.2 Semantic Efficiency

In certain cases, WiCoP combines utilities in a single operation. One particular case is that of statistics and activity feedback. Here, WTPs send regularly send a single Feedback message containing statistics and other state information, which also acts as an implicit keepalive mechanism. This helps to reduce the number of message exchanges and also simplifies protocol implementation. Similarly, the Capabilities messages serves the purpose of finding ACs and also informing them of WTP capabilities and design.

8. Summary and Conclusion

The Wireless LAN Control Protocol presents a solution for managing large-scale WLANs with diverse elements. It addresses the challenges presented in the CAPWAP Problem Statement [I-D.ietf-capwap-problem-statement] and realizes the requirements of the CAPWAP Objectives [I-D.ietf-capwap-objectives].

WiCoP enables integral control of split-MAC and local-MAC WTPs by defining appropriate differentiators within the protocol message exchanges and processes. It addresses architecture designs in which the authenticator and encryption points are located on distinct entities. And in doing so, WiCoP realizes the interoperability objective and its benefits.

WiCoP also addresses shared WLAN deployments by configuring and managing WTPs on a logical group basis. It is further provisioned to separate control and data traffic within WLANs. So the protocol addresses the objectives of logical groups and traffic separation.

Overall, the specifications presented in this document allows for an effective WLAN control and provisioning protocol.

9. Security Considerations

Illegitimate WTPs and ACs pose a significant threat to WLAN security. This can be mitigated by requiring all WiCoP entities to be mutually authenticated before initiating critical protocol exchanges. WiCoP includes a trigger for a suitable authentication mechanism. This is to accommodate different security mechanism that may be used between WTPs and AC depending on the nature of the deployment.

In extension to mutual authentication, the subsequent exchange of protocol information between WTPs and AC need to be protected. The exchanges have to be protected against alterations of any sort and DoS attacks. Also, the information should not be accessible to any third party. Encryption of protocol exchanges is therefore necessary. WiCoP includes appropriate procedures to select and establish a security association between WTPs and AC in the Connection state.

Architecture designs in which authentication is performed at the AC and encryption at the WTPs can be exposed to the threat of replay attacks. Since the AC will not be aware of the exact value of the sequence counter, it will not make the corresponding assignment within the 4-way handshake. This leaves the wireless terminal to accept all incoming frames including illegitimate frames as it cannot verify the sequence counter value. Such a threat needs to be protected against by allowing the WTP to assign the correct value of the sequence counter. WiCoP accomplishes this by sending the 3rd message of the 4-way handshake within a control message to the WTP, which then updates the sequence counter field before forwarding to the wireless terminals.

Another issue to consider is that of rogue WTPs using identifiers similar to that of legitimate WTPs. In such instances, a rogue WTP can send a Capabilities message to the AC thereby causing disconnection of the existing legitimate WTP of the same identifier. It is important for the AC to ignore Capabilities messages received with existing identifiers.

10. References

[I-D.ietf-capwap-arch]

Yang, L., Zerfos, P., and E. Sadot, "Architecture Taxonomy for Control and Provisioning of Wireless Access Points(CAPWAP)", [draft-ietf-capwap-arch-06](#) (work in progress), November 2004.

[I-D.ietf-capwap-objectives]

Govindan, S., "Objectives for Control and Provisioning of

Wireless Access Points (CAPWAP)",
[draft-ietf-capwap-objectives-03](#) (work in progress),
June 2005.

[I-D.ietf-capwap-problem-statement]
Calhoun, P., "CAPWAP Problem Statement",
[draft-ietf-capwap-problem-statement-02](#) (work in progress),
September 2004.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

Authors' Addresses

Satoshi Iino
Panasonic Mobile Communications
600, Saedo-cho
Tsuzuki-ku
Yokohama 224 8539
Japan

Phone: +81 45 938 3789
Email: iino.satoshi@jp.panasonic.com

Saravanan Govindan
Panasonic Singapore Laboratories
Block 1022, Tai Seng Industrial Estate
#06-3530, Tai Seng Avenue
Singapore 534 415
Singapore

Phone: +65 6550 5441
Email: saravanan.govindan@sg.panasonic.com

Mikihito Sugiura
Panasonic Mobile Communications
600, Saedo-cho
Tsuzuki-ku
Yokohama 224 8539
Japan

Phone: +81 45 938 3789
Email: sugiura.mikihito@jp.panasonic.com

Hong Cheng
Panasonic Singapore Laboratories
Block 1022, Tai Seng Industrial Estate
#06-3530, Tai Seng Avenue
Singapore 534 415
Singapore

Phone: +65 6550 5447

Email: hong.cheng@sg.panasonic.com

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

