

Network Working Group
Internet Draft
Intended status: Standards Track
Expires: August 29, 2012

S. Jiang
Huawei Technologies Co., Ltd
G. Chen
China Mobile
Feb 27, 2012

**A Generic IPv6 Addresses Registration Solution
Using DHCPv6
draft-jiang-dhc-addr-registration-04.txt**

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 29, 2012.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Abstract

In the IPv6 address allocation scenarios, host self-generated addresses are notionally conflicted with the network managed address architecture. These addresses need to be registered in the networking management plate for the purposes of central address administration. This document introduces a generic address registration solution using DHCPv6, and defines one new ND option and one new DHCPv6 option in order to propagate the solicitations of registering self-generated addresses. The registration procedure reuses the existing IA_NA in the DHCPv6 protocol.

Table of Contents

1.	Introduction & Requirements	3
2.	Terminology	3
3.	Overview of Generic Address Registration Solution	3
4.	Propagating the Address Registration Solicitation	4
4.1.	ND Address Registration Solicitation Option	5
4.2.	DHCPv6 Address Registration Solicitation Option	6
5.	DHCPv6 Address Registration Procedure	7
5.1.	DHCPv6 Address Registration Request	7
5.2.	DHCPv6 Address Registration Acknowledge	8
6.	Security Considerations	8
7.	IANA Considerations	8
8.	Acknowledgments	9
9.	References	9
9.1.	Normative References	9
9.2.	Informative References	10
	Author's Addresses	10

1. Introduction & Requirements

In the IPv6 address allocation scenarios, there are many host self-generated addresses, such as addresses in IPv6 Stateless Address Configuration [RFC4862, [RFC4941](#)] scenario and Cryptographically Generated Addresses (CGA, [[RFC3972](#)]), and etc. These addresses are notionally conflicted with the network managed address architecture, such as Dynamic Host Configuration Protocol for IPv6 (DHCPv6, [[RFC3315](#)]) managed network or network with Access Control List.

Many operators of enterprise networks and similarly tightly administered networks have expressed the desire to be at least aware the hosts' addresses when moving to IPv6. Furthermore, they may want to stop the usage of some hosts' addresses for various reasons.

A useful way to give network administrators most of what they want, while at the same time retaining compatibility with normal stateless configuration would be: if the self-generated IPv6 addresses are used, they may need to be registered in the networking management plate. The host may be required to perform this registration since only registered IPv6 addresses may access the network resources in some scenarios.

In order to fulfill the abovementioned practice, this document introduces a new Neighbor Discovery (ND) option and a new DHCPv6 option to propagate the address registration solicitation from network management to hosts. DHCPv6 protocol is suitable to perform the address registration procedure while the address registration server may play by a DHCPv6 server or a stand-alone server. The existing IA_NA in the DHCPv6 protocol is reused for the registration procedure.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119](#) [[RFC2119](#)].

3. Overview of Generic Address Registration Solution

By current default, the hosts with self-generated addresses do not register their addresses to any network devices. However, this may result that the network may reject the access request from these devices if the address registration is requested.

As showed in below Figure 1, in the generic address registration solution, proposed by this document, the network management plate firstly propagates the solicitations of registering self-generated addresses, by messages from either local router (step 1a in Figure 1) or DHCPv6 server (step 1b in Figure 1).

By received such solicitations, a host using the self-generated address SHOULD send an address registration request message to the address registration server (step 2 in Figure 1). The address registration server may be acted by a DHCPv6 server. By received the address registration request, the address registration server records the requested address in the address database, which MAY be used by other network functions, such as DNS or ACL, etc. The address registration server should also assign lifetimes for the requested address. An acknowledgement is sent back to the host with the assigned lifetimes (step 3 in Figure 1).




Figure 1: address registration procedure

By received the acknowledgement, the host can use the registered address. It SHOULD use the assigned preferred and valid lifetime for the corresponded address.

4. Propagating the Address Registration Solicitation

In order to indicate or force the hosts with self-generated addresses to register their addresses and the appointed address registration server, new solicitation options need to be defined.

There are more than one mechanisms in which configuration parameters could be pushed to the end hosts. The address registration

solicitation option can be carried in Router Advertisement (RA) message, which is broadcasted by local routers. In the DHCPv6 managed network, it can also be carried in DHCPv6 messages.


More precisely it defines one new ND option and one new DHCPv6 option that convey a Fully Qualified Domain Name (FQDN, as per [Section 3.1 of \[RFC1035\]](#)) of address registration(s). In order to make use of these options, this document assumes appropriate name resolution means (see [Section 6.1.1 of \[RFC1123\]](#)) are available on the host client. The use of the FQDN may benefit for load-balancing purposes.

By receiving the address registration solicitation option(s), a host SHOULD register its self-generated addresses, if there are any, to the appointed registration server. The solicitation options may include the IPv6 address(es) of address registration server.

In principle, hosts must receive a prefix from either RA message [RFC4861] or DHCPv6 message [I-D.ietf-dhc-host-gen-id] so that they can generate an IPv6 address by themselves. The Address Registration Solicitation options could be propagated together with prefix assignment information.

4.1. ND Address Registration Solicitation Option

The ND Address Registration Solicitation Option allows routers to propagate the solicitation for hosts to register their self-generated address. This option also carries a domain name of the appointed address registration server. This option SHOULD be propagated together with ND Prefix Information Option, [Section 4.6.2](#), [[RFC4861](#)]. The format of the ND Address Registration Solicitation Option is described as follows:



Fields:

- Type (TBA1)
- Length The length of the option in units of 8 octets, including the Type and Length fields. The value 0 is invalid. The receiver MUST discard a message that contains this value.
- Pad Length The number of padding octets beyond the end of the Domain Name field but within the length specified by the Length field.
- Reserved Padding bits. It is for future use also. The value MUST be initialized to zero by the sender, and MUST be ignored by the receiver.
- Domain Name A fully qualified domain name of the appointed address registration server. The domain name is encoded as specified in [Section 8 of \[RFC3315\]](#). Any possible future updates to [Section 8](#) of the [Section 8 of \[RFC3315\]](#) also apply to this option.
- Padding: A variable-length field making the option length a multiple of 8, containing as many octets as specified in the Pad Length field. Padding octets MUST be set to zero by senders and ignored by receivers.

[4.2.](#) DHCPv6 Address Registration Solicitation Option

The DHCPv6 Address Registration Solicitation Option allows DHCPv6 server to propagate the solicitation for hosts to register their self-generated address. This option also carries a domain name of the appointed address registration server. This option SHOULD be propagated together with DHCPv6 Prefix Information Option, [Section 5](#), [\[I-D.ietf-dhc-host-gen-id\]](#). The format of the DHCPv6 Address Registration Solicitation Option is described as follows:

```

0          1          2          3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|  OPTION_Adr_Reg_Solicitation  |      option-len      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                               |                          |
|                               |                          |
|                               |                          |
|                               |                          |
|                               |                          |
|                               |                          |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

option-code OPTION_Adr_Reg_Solicitation (TBA2).

option-len Length of this option in octets (option-code and
option-len are not included).

Domain Name A fully qualified domain name of the appointed
address registration server. The domain name is
encoded as specified in [Section 8 of \[RFC3315\]](#). Any
possible future updates to [Section 8](#) of the [Section
8 of \[RFC3315\]](#) also apply to this option.

5. DHCPv6 Address Registration Procedure

The current DHCPv6 protocol is reused as the address registration
protocol while a DHCPv6 server plays as address registration server.
Identity Association for Non-temporary Addresses (IA_NA) [\[RFC3315\]](#) is
reused in order to fulfill the address registration interactions.

5.1. DHCPv6 Address Registration Request

The host with self-generated address(es) sends a DHCPv6 Request
message to the appointed address registration server, which may be a
DHCPv6 server.

The DHCPv6 Request message SHOULD contain at least one IA_NA option.
The IA_NA option SHOULD contain at least one IA Address option. The
host SHOULD set the T1 and T2 fields in any IA_NA options, and the
preferred-lifetime and valid-lifetime fields in the IA Address
options to 0.

By received, the address registration server MUST register the
requested address in its address database, which MAY be used by other
network functions, such as DNS or ACL, etc. The address registration
server SHOULD also assign the lifetimes for these registered
addresses.

The address database contains both the self-generated addresses and the DHCPv6 assigned addresses. They MAY be marked different in the database.

5.2. DHCPv6 Address Registration Acknowledge

The address registration server sends a Reply message as the response to registration requests.

The DHCPv6 Reply message SHOULD contain at least one IA_NA option. The IA_NA option SHOULD contain at least one IA Address option. The server SHOULD set the T1 and T2 fields in any IA_NA options, and the preferred-lifetime and valid-lifetime fields in the IA Address options following the rules defined in [Section 22 in \[RFC3315\]](#).

By received the acknowledgement from the server, the host can use the registered address to access the network. It SHOULD use the values in the preferred and valid lifetime fields for the preferred and valid lifetimes of the address.

Note: the host MAY continue to use expired address, such as Locators as Upper-Layer Identifiers (ULID) in Shim6 protocol [\[RFC5533\]](#), etc.; but the network MAY refuse the network access from such addresses.

6. Security Considerations

An attacker may use a faked address registration request option to indicate hosts reports their address to a malicious server and collect the user information. These attacks may be prevented by using Secure Neighbor Discovery (SEND, [\[RFC3971\]](#)) if RA Address Registration Request Option is used, or AUTH option [\[RFC3315\]](#) or Secure DHCPv6 [\[I-D.ietf-dhc-secure-dhcpv6\]](#) if DHCPv6 Address Registration Request Option is used.

7. IANA Considerations

This document defines a new Neighbor Discovery [\[RFC4861\]](#) option, which MUST be assigned Option Type values within the option numbering space for Neighbor Discovery Option Type:

The Address Registration Solicitation Option (TBA1), described in [Section 4.1](#).

This document defines one new DHCPv6 [\[RFC3315\]](#) option, which MUST be assigned Option Type values within the option numbering space for DHCPv6 options:

The OPTION_Adr_Reg_Solicitation (TBA2), described in [Section 4.2](#);

8. Acknowledgments

The authors would like to thank Ralph Dorm, Ted Lemon, Bernie Volz and other member of DHC WG for valuable comments.

9. References

9.1. Normative References

- [RFC1035] Mockapetris, P., "Domain names - implementation and specification", STD 13, [RFC 1035](#), November 1987.
- [RFC1123] Braden, R., "Requirements for Internet Hosts - Application and Support", STD 3, [RFC 1123](#), October 1989.
- [RFC2119] S. Bradner, "Key words for use in RFCs to Indicate Requirement Levels", [RFC2119](#), March 1997.
- [RFC3315] R. Droms, Ed., J. Bound, B. Volz, T. Lemon, C. Perkins and M. Carne, "Dynamic Host Configure Protocol for IPv6", [RFC3315](#), July 2003.
- [RFC3971] J. Arkko, J. Kempf, B. Zill, P. Nikander, "SEcure Neighbor Discovery (SEND) ", [RFC 3971](#), March 2005.
- [RFC3972] T. Aura, "Cryptographically Generated Address", [RFC3972](#), March 2005.
- [RFC4861] T. Narten, E. Nordmark, W. Simpson, and H. Soliman, "Neighbor Discovery for IP version 6 (IPv6)", [RFC 4861](#), September 2007
- [RFC4862] S. Thomson, T. Narten and T. Jinmei, "IPv6 Stateless Address Autoconfiguration", [RFC4862](#), September 2007.
- [RFC4941] T. Narten, R. Draves and S. Krishnan, "Privacy Extensions for Stateless Address Autoconfiguration in IPv6", [RFC 4941](#), September 2007.
- [RFC5533] E. Nordmark, and M. Bagnulo, "Shim6: Level 3 Multihoming Shim Protocol for IPv6", [RFC 5533](#), June 2009.

9.2. Informative References

- [I-D.ietf-dhc-secure-dhcpv6]
S. Jiang and S. Shen, "Secure DHCPv6 Using CGAs", [draft-ietf-dhc-secure-dhcpv6](#) (work in progress), December, 2011.
- [I-D.ietf-dhc-host-gen-id]
S. Jiang, F. Xia, and B. Sarikaya, "Prefix Assignment in DHCPv6", [draft-ietf-dhc-host-gen-id](#) (work in progress), November, 2011.

Author's Addresses

Sheng Jiang
Huawei Technologies Co., Ltd
Q14, Huawei Campus
No.156 Beiqing Road
Hai-Dian District, Beijing 100095
Phone: 86-10-82882681
Email: jiangsheng@huawei.com

Gang Chen
China Mobile
53A, Xibianmennei Ave., Xuanwu District, Beijing
P.R. China
Phone: 86-13910710674
Email: phdgang@gmail.com