

Network Working Group
Internet-Draft
Intended status: Informational
Expires: January 13, 2022

W. J
Y. Liu
China Mobile
S. Chen
Huawei
July 12, 2021

Traffic Steering using BGP Flowspec with SRv6 Policy
draft-jiang-idr-ts-flowspec-srv6-policy-04

Abstract

BGP Flow Specification (FlowSpec) [[RFC8955](#)] has been proposed to distribute BGP FlowSpec NLRI to FlowSpec clients to mitigate (distributed) denial-of-service attacks, and to provide traffic filtering in the context of a BGP/MPLS VPN service. Recently, traffic steering applications in the context of SRv6 using FlowSpec also attract attention. This document introduces the usage of BGP FlowSpec to steer packets into an SRv6 Policy.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 13, 2022.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Definitions and Acronyms	3
3.	Operations	3
4.	Application Example	4
5.	IANA Considerations	5
6.	Security Considerations	5
7.	Contributors	6
8.	Acknowledgements	6
9.	References	6
9.1.	Normative References	6
9.2.	Informative References	7
	Authors' Addresses	7

[1.](#) Introduction

Segment Routing IPv6 (SRv6) is a protocol designed to forward IPv6 data packets on a network using the source routing model. SRv6 enables the ingress to add a segment routing header (SRH) [[RFC8754](#)] to an IPv6 packet and push an explicit IPv6 address stack into the SRH. After receiving the packet, each transit node updates the IPv6 destination IP address in the packet and segment list to implement hop-by-hop forwarding.

SRv6 Policy [[I-D.ietf-spring-segment-routing-policy](#)] is a tunneling technology developed based on SRv6. An SRv6 Policy is a set of candidate paths consisting of one or more segment lists, that is, segment ID (SID) lists. Each SID list identifies an end-to-end path from the source to the destination, instructing a device to forward traffic through the path rather than the shortest path computed using an IGP. The header of a packet steered into an SRv6 Policy is augmented with an ordered list of segments associated with that SRv6

Policy, so that other devices on the network can execute the instructions encapsulated into the list.

The headend of an SRv6 Policy may learn multiple candidate paths for an SRv6 Policy. Candidate paths may be learned via a number of different mechanisms, e.g., CLI, NetConf, PCEP, or BGP.

[RFC8955] defines the flow specification (FlowSpec) that allows to convey flow specifications and traffic Action/Rules associated (rate-limiting, redirect, remark ...). BGP Flow specifications are encoded within the MP_REACH_NLRI and MP_UNREACH_NLRI attributes. Rules (Actions associated) are encoded in Extended Community attribute. The BGP Flow Specification function allows BGP Flow Specification routes that carry traffic policies to be transmitted to BGP Flow Specification peers to steer traffic.

This document proposes BGP flow specification usage that are used to steer data flow into an SRv6 Policy as well as to indicate Tailend function.

2. Definitions and Acronyms

- o FlowSpec: Flow Specification
- o SR: Segment Routing
- o SRv6: IPv6 Segment Routing
- o SID: Segment Identifier
- o SRH: Segment Routing Header
- o TE: Traffic Engineering

3. Operations

An SRv6 Policy [[I-D.ietf-spring-segment-routing-policy](#)] is identified through the tuple <headend, color, endpoint>. In the context of a specific headend, one may identify an SRv6 policy by the <color, endpoint> tuple. The headend is the node where the SRv6 policy is instantiated/implemented. The headend is specified as an IPv4 or IPv6 address and is expected to be unique in the domain. The endpoint indicates the destination of the SRv6 policy. The endpoint is specified as an IPv6 address and is expected to be unique in the domain. The color is a 32-bit numerical value that associates the SRv6 Policy, and it defines an application-level network Service Level Agreement (SLA) policy.

Assume one or multiple SRv6 Policies are already setup in the SRv6 HeadEnd device. In order to steer traffic into a specific SRv6 policy at the Headend, one can use the SRv6 color extended community and endpoint to map to a satisfying SRv6 policy, and steer traffic into this specific policy.

[I-D.ietf-idr-flowspec-redirect-ip] defines the redirect to IPv4 and IPv6 Next-hop action. The IPv6 next-hop address in the Flow-spec Redirect to IPv6 Extended Community can be used to specify the endpoint of the SRv6 Policy. When the packets reach to the TailEnd device, some specific function information identifiers can be used to decide how to further process the flows. Several endpoint functions are already defined, e.g., End.DT6: Endpoint with decapsulation and IPv6 table lookup, and End.DX6: Endpoint with decapsulation and IPv6 cross-connect. The BGP Prefix-SID defined in [RFC8669] is utilized to enable SRv6 VPN services [I-D.ietf-bess-srv6-services]. SRv6 Services TLVs within the BGP Prefix-SID Attribute can be used to indicate the endpoint functions.

This document proposes to carry the Color Extended Community and BGP Prefix-SID Attribute in the context of a Flowspec NLRI [RFC8955] to an SRv6 Headend to steer traffic into one SRv6 policy, as well as to indicate specific Tailend functions.

In this document, the usage of at most one Color Extended Community in combination at most one BGP Prefix SID Attribute is discussed. For the case that a flowspec route carries multiple Color Extended Communities and/or a BGP Prefix SID Attribute, a protocol extension to Flowspec is required, and is thus out of the scope of this document.

However, the method proposed in this document still supports load balancing to the tailend device. To achieve that, the headend device CAN set up multiple paths in one SRv6 policy, and use a Flowspec route to indicate the specific SRv6 policy.

4. Application Example

In following scenario, BGP FlowSpec Controller signals the function information (SRv6 SID: Service_id_x) to the HeadEnd device.



Figure 1: Steering the Flow into SRv6 Policy

When the headend device (as a Flowspec client) receives such instructions, it will steer the flows matching the criteria in the Flowspec route into the SRv6 Policy matching the tuple (Endpoint: TailEnd's Address, Color: C1). And the packets of such flows will be encapsulated with SRH using the SR List<S1, S2, S3, Service_id_x>. When the packets reach to the TailEnd device, they will be further processed per the function denoted by the Service_id_x.

For the cases of intra-AS and inter-AS traffic steering using this method, the usages of Flowspec Color Extended Community with BGP prefix SID are the same for both scenarios. The difference lie between the local SRv6 policy configurations. For the inter-domain case, the operator can configure an inter-domain SRv6 policy/path at the Headend device. For the intra-domain case, the operator can configure an intra-domain SRv6 policy/path at the Headend device.

5. IANA Considerations

No IANA actions are required for this document.

6. Security Considerations

This document does not change the security properties of SRv6 and BGP.

7. Contributors

The following people made significant contributions to this document:

Yunan Gu
Huawei
Email: guyunan@huawei.com

Shunwan Zhaung
Huawei
Email: zhuangshunwan@huawei.com

Haibo Wang
Huawei
Email: rainsword.wang@huawei.com

Jie Dong
Huawei
Email: jie.dong@huawei.com

8. Acknowledgements

TBD.

9. References

9.1. Normative References

- [I-D.ietf-bess-srv6-services]
Dawra, G., Filsfils, C., Talaulikar, K., Raszuk, R., Decraene, B., Zhuang, S., and J. Rabadan, "SRv6 BGP based Overlay Services", [draft-ietf-bess-srv6-services-07](#) (work in progress), April 2021.
- [I-D.ietf-idr-flowspec-redirect-ip]
Uttaro, J., Haas, J., Texier, M., Karch, A., Ray, S., Simpson, A., and W. Henderickx, "BGP Flow-Spec Redirect to IP Action", [draft-ietf-idr-flowspec-redirect-ip-02](#) (work in progress), February 2015.
- [I-D.ietf-idr-segment-routing-te-policy]
Previdi, S., Filsfils, C., Talaulikar, K., Mattes, P., Rosen, E., Jain, D., and S. Lin, "Advertising Segment Routing Policies in BGP", [draft-ietf-idr-segment-routing-te-policy-11](#) (work in progress), November 2020.

[I-D.ietf-idr-tunnel-encaps]

Patel, K., Velde, G. V. D., Sangli, S. R., and J. Scudder,
"The BGP Tunnel Encapsulation Attribute", [draft-ietf-idr-tunnel-encaps-22](#) (work in progress), January 2021.

[I-D.ietf-spring-segment-routing-policy]

Filsfils, C., Talaulikar, K., Voyer, D., Bogdanov, A., and
P. Mattes, "Segment Routing Policy Architecture", [draft-ietf-spring-segment-routing-policy-11](#) (work in progress),
April 2021.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", [BCP 14](#), [RFC 2119](#),
DOI 10.17487/RFC2119, March 1997,
<<https://www.rfc-editor.org/info/rfc2119>>.

[RFC8669] Previdi, S., Filsfils, C., Lindem, A., Ed., Sreekantiah,
A., and H. Gredler, "Segment Routing Prefix Segment
Identifier Extensions for BGP", [RFC 8669](#),
DOI 10.17487/RFC8669, December 2019,
<<https://www.rfc-editor.org/info/rfc8669>>.

[RFC8955] Loibl, C., Hares, S., Raszuk, R., McPherson, D., and M.
Bacher, "Dissemination of Flow Specification Rules",
[RFC 8955](#), DOI 10.17487/RFC8955, December 2020,
<<https://www.rfc-editor.org/info/rfc8955>>.

9.2. Informative References

[RFC4456] Bates, T., Chen, E., and R. Chandra, "BGP Route
Reflection: An Alternative to Full Mesh Internal BGP
(IBGP)", [RFC 4456](#), DOI 10.17487/RFC4456, April 2006,
<<https://www.rfc-editor.org/info/rfc4456>>.

[RFC8754] Filsfils, C., Ed., Dukes, D., Ed., Previdi, S., Leddy, J.,
Matsushima, S., and D. Voyer, "IPv6 Segment Routing Header
(SRH)", [RFC 8754](#), DOI 10.17487/RFC8754, March 2020,
<<https://www.rfc-editor.org/info/rfc8754>>.

Authors' Addresses

Wenying Jiang
China Mobile
Beijing
China

Email: jiangwenying@chinamobile.com

Yisong Liu
China Mobile
Beijing
China

Email: liuyisong@chinamobile.com

Shuanglong Chen
Huawei
Beijing
China

Email: chenshuanglong@huawei.com

