

Network Working Group
Internet-Draft
Intended status: Informational
Expires: November 14, 2013

L. Jin
F. Jounay
France Telecom
M. Bhatia
Alcatel-Lucent
S. Kini
Ericsson
May 13, 2013

Hub and Spoke Multipoint Label Switched Path Tunnels
draft-jjb-mpls-rsvp-te-hsmp-lsp-04

Abstract

There are applications that require bi-directional, co-routed and guaranteed communication from a root node to several leaf nodes in a hub and spoke fashion. To meet such application requirements in a Multi-protocol Label Switching (MPLS) network this draft defines a Hub and Spoke Multipoint Traffic Engineered Label Switched Path (HSMP TE LSP) with resource reservations for guaranteed communication. This draft also defines a protocol to setup such LSPs by re-using and extending P2MP RSVP-TE.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 14, 2013.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements Language	2
2.	Abbreviations and Terminology	3
3.	Applications	3
3.1.	Time Synchronization	3
3.2.	P2MP pseudowire	3
4.	Scalability issues	3
5.	Hub and Spoke Multipoint LSP	4
5.1.	Data plane	5
5.2.	Control Plane	5
6.	Acknowledgements	6
7.	IANA Considerations	6
8.	Security Considerations	6
9.	References	6
9.1.	Normative References	6
9.2.	Informative References	7
	Authors' Addresses	7

[1.](#) Introduction

There are many applications that require one-to-many bi-directional communication. Some of these applications are described in [Section 3](#) along with their requirements from the network. Making such applications work over a MPLS network by using both P2MP and P2P constructs results in scalability issues and these are discussed in [Section 4](#). This document defines a technique to do one-to-many bi-directional communication over an MPLS network that re-uses the existing P2MP and P2P constructs in MPLS but combines them in a scalable manner. This technique re-uses and extends the current traffic-engineered P2MP and P2P constructs and protocols. It is described in detail in [Section 5](#).

[1.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

[2.](#) Abbreviations and Terminology

HSMP LSP - Hub and Spoke Multipoint LSP

[3.](#) Applications

We describe two representative applications that require one-to-many bi-directional communication. The first is the 'Time Synchronization' application described in 2.1. The second is the P2MP pseudowire application and is described in [section 2](#).

[3.1.](#) Time Synchronization

Time Synchronization [[IEEE1588](#)] over an MPLS network is being defined in [[I-D.ietf-tictoc-1588overmpls](#)]. A scalable time-sync architecture requires the master to provide time synchronization to a large number of slaves. It requires the PTP messages to flow bi-directionally between master and slave in a hub and spoke manner. More importantly these messages must have the same delay in both directions. This requires the underlying network to reserve resources to transport PTP messages and also to co-route them in both directions to avoid any differences in the delays of the paths in both directions.

[3.2.](#) P2MP pseudowire

A P2MP PW [[I-D.ietf-pwe3-p2mp-pw](#)] is required for the VPMS service [[I-D.ietf-l2vpn-vpms-frmwk-requirements](#)]. In this application the root PE requires bi-directional communication with several leaf PEs. The underlying MPLS transport should support this type of communication for the P2MP PW in a reliable and efficient manner.

[4.](#) Scalability issues

A straightforward method to achieve one-to-many bi-directional communication with resource guarantees is to use a P2MP RSVP-TE tunnel from the hub PE to the spoke PEs and use P2P RSVP-TE tunnels

from each spoke PE to the hub PE. The spoke-to-hub P2P tunnels can be explicitly routed such that they are co-routed along the reverse direction of the P2MP tunnel. In this model, scalability issues arise both in the data plane and the control plane as explained below in this section.

For the purpose of this discussion, an application with a hub and spoke bi-directional communication over a tree topology MPLS network is illustrated in Figure 1. The hub LSR is A and the spoke LSRs are E, F, G, and H. For communication from the hub to the spokes, a P2MP LSP can be setup with A as the root and E, F, G and H as leaves. For communication from the spokes to the hub, a P2P LSP can be setup from each spoke to the hub.




Figure 1: Hub and spoke LSP over a tree topology

Each LSR along this tree will have to allocate a unique label for each of the P2P LSPs that go from spoke to hub through it. This leads to a linear increase in forwarding state at each LSR in proportion to the number of spoke nodes that are in its sub-tree. This has poor scaling characteristics in the data plane as the number of spoke nodes increase.

Each LSR also has to allocate control plane state for each of the P2P LSPs that go from spoke to hub through it. Each P2P LSP will need a

separate path state block (PSB) and a reservation state block (RSB) and these will store additional information on signaling attributes. This state is in addition to the state maintained for the P2MP LSP. Clearly this state too increases linearly with the number of spoke nodes that are in its sub-tree. This too has poor scaling characteristics in the control plane as the number of spoke nodes increase. Also the number of signaling messages increases linearly though some of it may be mitigated by using refresh reduction [[RFC2961](#)].

[5.](#) Hub and Spoke Multipoint LSP

To solve the issues identified in [Section 4](#) this document defines a hub and spoke traffic-engineered multipoint LSP (HSMP TE LSP) with resource reservations. Such an LSP is a combination of an explicitly routed uni-directional traffic-engineered P2MP LSP from the hub to the spokes and a co-routed uni-directional MP2P LSP from the spokes to the hub. The data plane for a HSMP TE LSP is explained in [Section 5.1](#) and the control plane is explained in [Section 5.2](#)

[5.1.](#) Data plane

In the direction from hub-to-spoke the data plane processing is the same as that of a P2MP LSP. In the direction from the spokes to the hub, each LSR allocates labels for its upstream LSRs. Each LSR merges the traffic received from multiple upstream LSRs before forwarding it on the LSP towards the hub. It should be noted that due to label merging the GAL processing in the direction from spoke to hub is not defined.

[5.2.](#) Control Plane

The signaling protocol to setup a HSMP TE LSP can re-use the signalling protocol for P2MP RSVP-TE [[RFC4875](#)] with some extensions. The hub and spokes of a HSMP LSP can be modeled the same as the source and leaves respectively of a P2MP LSP. A source-to-leaf (S2L) sub-LSP defined in [[RFC4875](#)] for the P2MP LSP is used to represent a hub-to-spoke communication of the HSMP LSP. To signal the bi-directional co-routed nature of the communication from the hub to the spoke, the extensions defined in [section 3 of \[RFC3473\]](#) must be used. Each Path message of a HSMP LSP LSR MUST have a Upstream_Label object. If a PathErr is received in response with a "Routing problem

/Unacceptable label value" indication then the Acceptable Label Set (if present) must be examined to allocate a label for the Upstream_Label object. If an LSR signaling an HSMP LSP receives PathErr messages with different Acceptable Label Sets from different neighboring LSRs then it may need to allocate more than one label to satisfy all the Acceptable Label Sets. The LSR should try to minimize the number of unique labels allocated for a HSMP LSP in such a case.

Pruning and grafting for a HSMP LSP follow the same procedures as for a P2MP LSP. During re-merge in addition to the procedures in [section 18.1.1 of \[RFC4875\]](#) the ingress or transit LSR that creates the branch would also be a re-merge LSR for the traffic from the spokes towards the hub. Also the re-merge node for the traffic from hub to spoke would be a branching node for traffic from the spokes to the hub. The LSR that is branching the traffic from the spokes to the hub would duplicate the traffic whereas the LSR that is re-merging the traffic should forward traffic only from one the incoming interfaces.

The HSMP LSP also requires bandwidth allocation that is asymmetric between the hub-to-spoke and the spoke-to-hub direction. At the same time it requires the spokes to be able to request different amounts of bandwidth towards the hub. The protocol extensions defined in [\[RFC6387\]](#) are used for asymmetric bandwidth allocation between the hub-to-spoke and spoke-to-hub directions. The UPSTREAM_TSPEC,

UPSTREAM_ADSPEC and UPSTREAM_FLOWSPEC objects are also used in a HSMP LSP. However in case of a HSMP LSP an intermediate LSR can receive different UPSTREAM_TSPECs in the Resv messages from neighboring LSRs. Combining these Tspecs and generating an appropriate UPSTREAM_FLOWSPEC towards each spoke is still under discussion. Also, processing a received UPSTREAM_FLOWSPEC and generating appropriate UPSTREAM FLOWSPECs in the hub to spoke direction is also under discussion.

[6.](#) Acknowledgements

We would like to thank Dimitri Papadimitriou, Yuji Kamite, Sebastien Jobert for their comments and feedback on the document.

[7.](#) IANA Considerations

This memo includes no request to IANA.

8. Security Considerations

The same security considerations apply as for the RSVP-TE P2MP LSP [[RFC4875](#)] specification.

9. References

9.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3473] Berger, L., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) Extensions", [RFC 3473](#), January 2003.
- [RFC4875] Aggarwal, R., Papadimitriou, D., and S. Yasukawa, "Extensions to Resource Reservation Protocol - Traffic Engineering (RSVP-TE) for Point-to-Multipoint TE Label Switched Paths (LSPs)", [RFC 4875](#), May 2007.
- [RFC6387] Takacs, A., Berger, L., Caviglia, D., Fedyk, D., and J. Meuric, "GMPLS Asymmetric Bandwidth Bidirectional Label Switched Paths (LSPs)", [RFC 6387](#), September 2011.

9.2. Informative References

- [I-D.ietf-l2vpn-vpms-frmwk-requirements]
Kamite, Y., JOUNAY, F., Niven-Jenkins, B., Brungard, D., and L. Jin, "Framework and Requirements for Virtual Private Multicast Service (VPMS)", [draft-ietf-l2vpn-vpms-frmwk-requirements-05](#) (work in progress), October 2012.

- [I-D.ietf-pwe3-p2mp-pw]
Sivabalan, S., Boutros, S., and L. Martini, "Signaling Root-Initiated Point-to-Multipoint Pseudowire using LDP", [draft-ietf-pwe3-p2mp-pw-04](#) (work in progress), March 2012.
- [I-D.ietf-tictoc-1588overmpls]
Davari, S., Oren, A., Bhatia, M., Roberts, P., and L. Montini, "Transporting Timing messages over MPLS Networks", [draft-ietf-tictoc-1588overmpls-04](#) (work in progress), February 2013.
- [IEEE1588]
IEEE 1588-2008, "IEEE Standard for a Precision Clock Synchronization Protocol for Networked Measurement and Control Systems ", 2008.
- [RFC2961] Berger, L., Gan, D., Swallow, G., Pan, P., Tommasi, F., and S. Molendini, "RSVP Refresh Overhead Reduction Extensions", [RFC 2961](#), April 2001.
- [RFC4090] Pan, P., Swallow, G., and A. Atlas, "Fast Reroute Extensions to RSVP-TE for LSP Tunnels", [RFC 4090](#), May 2005.

Authors' Addresses

Lizhong Jin

Email: lizho.jin@gmail.com

Frederic Jounay
France Telecom

Email: frederic.Jounay@orange.ch

Alcatel-Lucent

Email: manav.bhatia@alcatel-lucent.com

Sriganesh Kini
Ericsson

Email: sriganesh.kini@ericsson.com