

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: April 14, 2018

S. Kille  
Isode Ltd  
October 11, 2017

**LDAP Schema for supporting XMPP in White Pages  
draft-kille-ldap-xmpp-schema-10**

Abstract

The Extensible Messaging and Presence Protocol (XMPP) identifies users by use of JID (Jabber IDs). Lightweight Directory Access Protocol (LDAP) enables provision of a white pages service with schema relating to users and support for internet protocols. This specification defines schema to enable XMPP JIDs to be associated with objects in an LDAP directory so that this information can be used with white pages applications.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 14, 2018.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1.](#) Introduction . . . . . [2](#)
- [2.](#) Conventions Used in This Document . . . . . [2](#)
- [3.](#) Schema Definition . . . . . [2](#)
  - [3.1.](#) Object Class . . . . . [2](#)
  - [3.2.](#) Attribute . . . . . [3](#)
- [4.](#) IANA Considerations . . . . . [3](#)
- [5.](#) Security Considerations . . . . . [4](#)
- [6.](#) Normative References . . . . . [4](#)
- [Appendix A.](#) Acknowledgements . . . . . [6](#)
- Author's Address . . . . . [6](#)

**1. Introduction**

Extensible Messaging and Presence Protocol (XMPP) [[RFC6120](#)] identifies users by use of JID (Jabber IDs). Lightweight Directory Access Protocol (LDAP) [[RFC4510](#)] enables provision of a white pages service with schema relating to users and support for internet protocols defined in [[RFC4519](#)]. This specification defines schema to enable XMPP JIDs to be associated with LDAP directory objects so that this information can be used with white pages applications.

The LDAP schema for storing JIDs is defined to enable JIDs to be associated with any object stored in the directory. This is done by associating the new JID Attribute with a new Auxiliary Object Class (JIDObject).

**2. Conventions Used in This Document**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

**3. Schema Definition**

This section defines the schema used to store JIDs in the directory.

**3.1. Object Class**

This section defines a new Auxiliary Object Class (JIDObject) which MAY be associated with any structural Object Class. This Object Class is used to augment entries for objects that act or may act as an XMPP client. The JID attribute is optional, to enable configuring

Kille

Expires April 14, 2018

[Page 2]

an object that is allowed to have an associated JID but does not currently have one.

```
( 1.3.6.1.1.23.1 NAME 'JIDObject'  
  AUXILIARY  
  MAY jid )
```

### 3.2. Attribute

This section defines the JID attribute referenced by the JIDObject Auxiliary Object Class. The syntax of the JID attribute MUST follow the rules of [RFC7622]. The JID stored MUST be a bare JID (e.g., a JID such as romeo@shakespeare.example.com representing a human user) and not a full JID (e.g. a JID such as romeo@shakespeare.example.com/AABBCC representing a specific XMPP client used by the human user and identified by the resource AABBCC). Note that the LDAP directory server is not expected to enforce this syntax. The syntax rules are for LDAP clients setting this attribute, noting that human usage is a key target. Applications using this attribute should format that string in a manner appropriate to the application and XMPP applications SHOULD apply [RFC7622] to the attribute. The directory service doesn't enforce the JID syntax and values are compared according to the matching rules specified in the attribute definition.

NOTE: The directory string syntax and the caseIgnoreMatch matching rule are chosen to allow entry and matching of values according to common rules used within the directory, for convenience for users and administrators as well as implementers. As this syntax and matching rules differs from [RFC7622] false positive and false negative can possibly occur. This is not anticipated to cause operational issues (based on implementation experience with similar syntax/matching rule mismatches).

```
( 1.3.6.1.1.23.2 NAME 'jid'  
  EQUALITY caseIgnoreMatch  
  SUBSTR caseIgnoreSubstringsMatch  
  SYNTAX 1.3.6.1.4.1.1466.115.121.1.15 )
```

1.3.6.1.4.1.1466.115.121.1.15 refers to the Directory String syntax defined in [RFC4517].

### 4. IANA Considerations

The following registrations have been made in the LDAP Registry <<https://www.iana.org/assignments/ldap-parameters/ldap-parameters.xhtml>> in line with BCP 64 [RFC4520].

Kille

Expires April 14, 2018

[Page 3]

## Object Identifier Registration

An object identifier has been assigned to support the registrations necessary for this specification, by an entry in the Internet Directory Numbers (iso.org.dod.internet.directory [1.3.6.1.1.]) registry:

Decimal: 23  
Name: xmpp  
Description: LDAP schema for XMPP

Two object identifiers have been assigned:

### 'JIDObject' Descriptor Registration

Name: JIDObject  
Type: 0  
OID: 1.3.6.1.1.23.1

### 'jid' Descriptor Registration

Name: jid  
Type: A  
OID: 1.3.6.1.1.23.2

## 5. Security Considerations

XMPP JIDs are often personal identifiers enabling electronic communication, with similar considerations to email addresses. This schema enables publishing of this information in LDAP directories which may be corporate or public services. Care should be taken to only publish JID information which is acceptable to be linked to the LDAP object and be made accessible to all LDAP users. The general LDAP Security Considerations specified in [[RFC4510](#)] also apply.

## 6. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC4510] Zeilenga, K., Ed., "Lightweight Directory Access Protocol (LDAP): Technical Specification Road Map", [RFC 4510](#), DOI 10.17487/RFC4510, June 2006, <<https://www.rfc-editor.org/info/rfc4510>>.

Kille

Expires April 14, 2018

[Page 4]

- [RFC4517] Legg, S., Ed., "Lightweight Directory Access Protocol (LDAP): Syntaxes and Matching Rules", [RFC 4517](#), DOI 10.17487/RFC4517, June 2006, <<https://www.rfc-editor.org/info/rfc4517>>.
- [RFC4519] Sciberras, A., Ed., "Lightweight Directory Access Protocol (LDAP): Schema for User Applications", [RFC 4519](#), DOI 10.17487/RFC4519, June 2006, <<https://www.rfc-editor.org/info/rfc4519>>.
- [RFC4520] Zeilenga, K., "Internet Assigned Numbers Authority (IANA) Considerations for the Lightweight Directory Access Protocol (LDAP)", [BCP 64](#), [RFC 4520](#), DOI 10.17487/RFC4520, June 2006, <<https://www.rfc-editor.org/info/rfc4520>>.
- [RFC6120] Saint-Andre, P., "Extensible Messaging and Presence Protocol (XMPP): Core", [RFC 6120](#), DOI 10.17487/RFC6120, March 2011, <<https://www.rfc-editor.org/info/rfc6120>>.
- [RFC7622] Saint-Andre, P., "Extensible Messaging and Presence Protocol (XMPP): Address Format", [RFC 7622](#), DOI 10.17487/RFC7622, September 2015, <<https://www.rfc-editor.org/info/rfc7622>>.





**Appendix A. Acknowledgements**

Thanks to Alexey Melnikov for suggestions on preparing this draft.  
Thanks to Alan Murdock, Yoav Nir, Peter Saint-Andre and Kurt Zeilenga  
for review comments.

Author's Address

Steve Kille  
Isode Ltd  
14 Castle Mews  
Hampton, Middlesex TW12 2NP  
UK

EMail: Steve.Kille@isode.com

Kille

Expires April 14, 2018

[Page 6]