

Network Working Group
Internet-Draft
Intended status: Informational
Expires: 6 November 2022

M. Koster, Ed.
Stalworthy Computing, Ltd.
G. Illyes, Ed.
H. Zeller, Ed.
L. Sassman, Ed.
Google LLC.
5 May 2022

Robots Exclusion Protocol
draft-koster-rep-07

Abstract

This document specifies and extends the "Robots Exclusion Protocol" method originally defined by Martijn Koster in 1996 for service owners to control how content served by their services may be accessed, if at all, by automatic clients known as crawlers.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 6 November 2022.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

Internet-Draft

REP

May 2022

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements Language	3
2.	Specification	3
2.1.	Protocol Definition	3
2.2.	Formal Syntax	3
2.2.1.	The User-Agent Line	5
2.2.2.	The Allow and Disallow Lines	5
2.2.3.	Special Characters	6
2.2.4.	Other Records	7
2.3.	Access Method	7
2.3.1.	Access Results	8
2.3.1.1.	Successful Access	8
2.3.1.2.	Redirects	8
2.3.1.3.	Unavailable Status	8
2.3.1.4.	Unreachable Status	9
2.3.1.5.	Parsing Errors	9
2.4.	Caching	9
2.5.	Limits	9
3.	Security Considerations	9
4.	IANA Considerations	9
5.	Examples	9
5.1.	Simple Example	9
5.2.	Longest Match	10
6.	References	10
6.1.	Normative References	10
6.2.	Informative References	11
	Authors' Addresses	11

[1.](#) Introduction

This document applies to services that provide resources that clients can access through URIs as defined in [[RFC3986](#)]. For example, in the

context of HTTP, a browser is a client that displays the content of a web page.

Crawlers are automated clients. Search engines for instance have crawlers to recursively traverse links for indexing as defined in [\[RFC8288\]](#).

It may be inconvenient for service owners if crawlers visit the entirety of their URI space. This document specifies the rules originally defined by the "Robots Exclusion Protocol" [\[ROBOTSTXT\]](#) that crawlers are expected to obey when accessing URIs.

These rules are not a form of access authorization.

[1.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [\[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

[2.](#) Specification

[2.1.](#) Protocol Definition

The protocol language consists of rule(s) and group(s) that the service makes available in a file named 'robots.txt' as described in [section 2.3](#):

- * Rule: A line with a key-value pair that defines how a crawler may access URIs. See [section 2.2.2](#).
- * Group: One or more user-agent lines that is followed by one or more rules. The group is terminated by a user-agent line or end of file. See [section 2.2.1](#). The last group may have no rules, which means it implicitly allows everything.

[2.2.](#) Formal Syntax

Below is an Augmented Backus-Naur Form (ABNF) description, as described in [[RFC5234](#)].

Internet-Draft

REP

May 2022

```
robotstxt = *(group / emptyline)
group = startgroupline                ; We start with a user-agent
      *(startgroupline / emptyline)  ; ... and possibly more
                                      ; user-agents
      *(rule / emptyline)            ; followed by rules relevant
                                      ; for UAs
```

```
startgroupline = *WS "user-agent" *WS ":" *WS product-token EOL
```

```
rule = *WS ("allow" / "disallow") *WS ":"
      *WS (path-pattern / empty-pattern) EOL
```

```
; parser implementors: add additional lines you need (for
; example, sitemaps), and be lenient when reading lines that don't
; conform. Apply Postel's law.
```

```
product-token = identifier / "*"
path-pattern = "/" *UTF8-char-noctl ; valid URI path pattern
empty-pattern = *WS
```

```
identifier = 1*(%x2D / %x41-5A / %x5F / %x61-7A)
comment = "#" *(UTF8-char-noctl / WS / "#")
emptyline = EOL
EOL = *WS [comment] NL ; end-of-line may have
                        ; optional trailing comment
NL = %x0D / %x0A / %x0D.0A
WS = %x20 / %x09
```

```
; UTF8 derived from RFC3629, but excluding control characters
```

```

UTF8-char-noctl = UTF8-1-noctl / UTF8-2 / UTF8-3 / UTF8-4
UTF8-1-noctl = %x21 / %x22 / %x24-7F ; excluding control, space, '#'
UTF8-2 = %xC2-DF UTF8-tail
UTF8-3 = %xE0 %xA0-BF UTF8-tail / %xE1-EC 2UTF8-tail /
          %xED %x80-9F UTF8-tail / %xEE-EF 2UTF8-tail
UTF8-4 = %xF0 %x90-BF 2UTF8-tail / %xF1-F3 3UTF8-tail /
          %xF4 %x80-8F 2UTF8-tail

UTF8-tail = %x80-BF

```

[2.2.1.](#) The User-Agent Line

Crawlers set a product token to find relevant groups. The product token MUST contain only "a-zA-Z_" characters. The product token SHOULD be part of the identification string that the crawler sends to the service (for example, in the case of HTTP, the product name SHOULD be in the user-agent header). The identification string SHOULD describe the purpose of the crawler. Here's an example of an HTTP header with a link pointing to a page describing the purpose of the ExampleBot crawler which appears both in the HTTP header and as a product token:

+=====+=====+	
HTTP header	robots.txt
	user-agent line
+=====+=====+	
user-agent: Mozilla/5.0	user-agent:
(compatible; ExampleBot/0.1;	ExampleBot
https://www.example.com/bot.html)	
+-----+-----+	

Table 1: Example of a user-agent header and user-

Crawlers MUST find the group that matches the product token exactly, and then obey the rules of the group. If there is more than one group matching the user-agent, the matching groups' rules MUST be combined into one group. The matching MUST be case-insensitive. If no matching group exists, crawlers MUST obey the first group with a user-agent line with a "*" value, if present. If no group satisfies either condition, or no groups are present at all, no rules apply.

2.2.2. The Allow and Disallow Lines

These lines indicate whether accessing a URI that matches the corresponding path is allowed or disallowed.

To evaluate if access to a URI is allowed, a robot MUST match the paths in allow and disallow rules against the URI. The matching SHOULD be case sensitive. The most specific match found MUST be used. The most specific match is the match that has the most octets. If an allow and disallow rule is equivalent, the allow SHOULD be used. If no match is found amongst the rules in a group for a matching user-agent, or there are no rules in the group, the URI is allowed. The /robots.txt URI is implicitly allowed.

Octets in the URI and robots.txt paths outside the range of the US-ASCII coded character set, and those in the reserved range defined by [RFC3986], MUST be percent-encoded as defined by [RFC3986] prior to comparison.

If a percent-encoded US-ASCII octet is encountered in the URI, it MUST be unencoded prior to comparison, unless it is a reserved character in the URI as defined by [RFC3986] or the character is outside the unreserved character range. The match evaluates positively if and only if the end of the path from the rule is reached before a difference in octets is encountered.

For example:

+=====+=====+=====+

Path	Encoded Path	Path to Match
/foo/bar?baz=quz	/foo/bar?baz=quz	/foo/bar?baz=quz
/foo/bar?baz=http ://foo.bar	/foo/bar?baz=http%3A %2F%2Ffoo.bar	/foo/bar?baz=http%3A %2F%2Ffoo.bar
/foo/bar/U+E38384	/foo/bar/%E3%83%84	/foo/bar/%E3%83%84
/foo/ bar/%E3%83%84	/foo/bar/%E3%83%84	/foo/bar/%E3%83%84
/foo/ bar/%62%61%7A	/foo/bar/%62%61%7A	/foo/bar/baz

Table 2: Examples of matching percent-encoded URI components

The crawler SHOULD ignore "disallow" and "allow" rules that are not in any group (for example, any rule that precedes the first user-agent line).

Implementers MAY bridge encoding mismatches if they detect that the robots.txt file is not UTF8 encoded.

2.2.3. Special Characters

Crawlers SHOULD allow the following special characters:

Character	Description	Example
"#"	Designates an end of line comment.	"allow: / # comment in line" "# comment on its own line"
"\$"	Designates the	"allow: /this/path/exactly\$"

	end of the match	
	pattern.	
+-----+	+-----+	+-----+
"*"	Designates 0 or	"allow: /this/*/exactly"
	more instances of	
	any character.	
+-----+	+-----+	+-----+

Table 3: List of special characters in robots.txt files

If crawlers match special characters verbatim in the URI, crawlers SHOULD use "%" encoding. For example:

+=====+	+=====+
Percent-encoded Pattern	URI
+-----+	+-----+
/path/file-with-a-%2A.html	https://www.example.com/path/
	file-with-a-*.html
+-----+	+-----+
/path/foo-%24	https://www.example.com/path/
	foo-\$
+-----+	+-----+

Table 4: Example of percent-encoding

[2.2.4.](#) Other Records

Clients MAY interpret other records that are not part of the robots.txt protocol. For example, 'sitemap' [[SITEMAPS](#)]. Parsing of other records MUST NOT interfere with the parsing of explicitly defined records in [section 2](#).

[2.3.](#) Access Method

The rules MUST be accessible in a file named "/robots.txt" (all lower case) in the top level path of the service. The file MUST be UTF-8 encoded (as defined in [[RFC3629](#)]) and Internet Media Type "text/plain" (as defined in [[RFC2046](#)]).

As per [[RFC3986](#)], the URI of the robots.txt is:

"scheme:[//authority]/robots.txt"

For example, in the context of HTTP or FTP, the URI is:

`http://www.example.com/robots.txt`

`https://www.example.com/robots.txt`

`ftp://ftp.example.com/robots.txt`

[2.3.1.](#) Access Results

[2.3.1.1.](#) Successful Access

If the crawler successfully downloads the robots.txt, the crawler MUST follow the parseable rules.

[2.3.1.2.](#) Redirects

The server may respond to a robots.txt fetch request with a redirect, such as HTTP 301 and HTTP 302. The crawlers SHOULD follow at least five consecutive redirects, even across authorities (for example, hosts in case of HTTP), as defined in [[RFC1945](#)].

If a robots.txt file is reached within five consecutive redirects, the robots.txt file MUST be fetched, parsed, and its rules followed in the context of the initial authority.

If there are more than five consecutive redirects, crawlers MAY assume that the robots.txt is unavailable.

[2.3.1.3.](#) Unavailable Status

Unavailable means the crawler tries to fetch the robots.txt, and the server responds with unavailable status codes. For example, in the context of HTTP, unavailable status codes are in the 400-499 range.

If a server status code indicates that the robots.txt file is unavailable to the client, then crawlers MAY access any resources on the server.

[2.3.1.4.](#) Unreachable Status

If the robots.txt is unreachable due to server or network errors, this means the robots.txt is undefined and the crawler MUST assume complete disallow. For example, in the context of HTTP, an unreachable robots.txt has a response code in the 500-599 range. For other undefined status codes, the crawler MUST assume the robots.txt is unreachable.

If the robots.txt is undefined for a reasonably long period of time (for example, 30 days), clients MAY assume the robots.txt is unavailable or continue to use a cached copy.

[2.3.1.5.](#) Parsing Errors

Crawlers SHOULD try to parse each line of the robots.txt file. Crawlers MUST use the parseable rules.

[2.4.](#) Caching

Crawlers MAY cache the fetched robots.txt file's contents. Crawlers MAY use standard cache control as defined in [[RFC2616](#)]. Crawlers SHOULD NOT use the cached version for more than 24 hours, unless the robots.txt is unreachable.

[2.5.](#) Limits

Crawlers MAY impose a parsing limit that MUST be at least 500 kibibytes (KiB).

[3.](#) Security Considerations

The Robots Exclusion Protocol is not a substitute for more valid content security measures. Listing URIs in the robots.txt file exposes the URI publicly and thus makes the URIs discoverable.

[4.](#) IANA Considerations

This document has no actions for IANA.

[5.](#) Examples

[5.1.](#) Simple Example

The following example shows:

- * foobot: A regular case. A single user-agent token followed by rules.

- * barbot and bazbot: A group that's relevant for more than one user-agent.
- * quxbot: An empty group at end of the file.

```
User-Agent : foobot
Disallow : /example/page.html
Disallow : /example/disallowed.gif
```

```
User-Agent : barbot
User-Agent : bazbot
Allow : /example/page.html
Disallow : /example/disallowed.gif
```

```
User-Agent: quxbot
```

```
EOF
```

[5.2.](#) Longest Match

The following example shows that in the case of two rules, the longest one is used for matching. In the following case, `/example/page/disallowed.gif` MUST be used for the URI `example.com/example/page/disallow.gif`.

```
User-Agent : foobot
Allow : /example/page/
Disallow : /example/page/disallowed.gif
```

[6.](#) References

[6.1.](#) Normative References

- [RFC1945] Berners-Lee, T., Fielding, R., and H. Frystyk, "Hypertext Transfer Protocol -- HTTP/1.0", [RFC 1945](#), DOI 10.17487/RFC1945, May 1996, <<https://www.rfc-editor.org/info/rfc1945>>.
- [RFC2046] Freed, N. and N. Borenstein, "Multipurpose Internet Mail

Extensions (MIME) Part Two: Media Types", [RFC 2046](#), DOI 10.17487/RFC2046, November 1996, <<https://www.rfc-editor.org/info/rfc2046>>.

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

Koster, et al.

Expires 6 November 2022

[Page 10]

Internet-Draft

REP

May 2022

- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), DOI 10.17487/RFC2616, June 1999, <<https://www.rfc-editor.org/info/rfc2616>>.
- [RFC3629] Vergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, [RFC 3629](#), DOI 10.17487/RFC3629, November 2003, <<https://www.rfc-editor.org/info/rfc3629>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), DOI 10.17487/RFC5234, January 2008, <<https://www.rfc-editor.org/info/rfc5234>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8288] Nottingham, M., "Web Linking", [RFC 8288](#), DOI 10.17487/RFC8288, October 2017, <<https://www.rfc-editor.org/info/rfc8288>>.

[6.2.](#) Informative References

- [ROBOTSTXT] "Robots Exclusion Protocol", n.d.,

<<http://www.robotstxt.org/>>.

[SITEMAPS] "Sitemaps Protocol", n.d.,
<<https://www.sitemaps.org/index.html>>.

Authors' Addresses

Martijn Koster (editor)
Stalworthy Computing, Ltd.
Suton Lane
Wymondham, Norfolk
NR18 9JG
United Kingdom
Email: m.koster@greenhills.co.uk

Koster, et al.

Expires 6 November 2022

[Page 11]

Internet-Draft

REP

May 2022

Gary Illyes (editor)
Google LLC.
Brandschenkestrasse 110
CH-8002 Zurich
Switzerland
Email: garyilleyes@google.com

Henner Zeller (editor)
Google LLC.
1600 Amphitheatre Pkwy
Mountain View, CA, 94043
United States of America
Email: henner@google.com

Lizzi Sassman (editor)
Google LLC.
Brandschenkestrasse 110
CH-8002 Zurich
Switzerland
Email: lizzi@google.com

