

Internet Architecture Board (IAB)  
Internet-Draft  
Intended status: Best Current Practice  
Expires: December 20, 2018

K. Watsen  
Juniper Networks  
Q. Wu  
Huawei Technologies  
June 18, 2018

**Handling Long Lines in Artwork in Drafts**  
**draft-kwatsen-netmod-artwork-folding-03**

Abstract

This document introduces a simple and yet time-proven strategy for handling long lines in artwork in drafts using a backslash ('\') character where line-folding has occurred. The strategy works on any text based artwork, producing consistent results regardless the artwork content. Using a per-artwork header, the strategy is both self-documenting and enables automated reconstitution of the original artwork.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 20, 2018.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1. Introduction . . . . .](#) [2](#)
- [2. Requirements Language . . . . .](#) [3](#)
- [3. Goals . . . . .](#) [3](#)
  - [3.1. Automated folding of long lines in artwork . . . . .](#) [3](#)
  - [3.2. Automated reconstitution of original artwork . . . . .](#) [3](#)
- [4. Limitations . . . . .](#) [3](#)
  - [4.1. Doesn't work well on graphical artwork . . . . .](#) [3](#)
  - [4.2. Doesn't work as well as format-specific options . . . . .](#) [4](#)
- [5. Solution . . . . .](#) [4](#)
  - [5.1. Header . . . . .](#) [4](#)
  - [5.2. Folding . . . . .](#) [5](#)
  - [5.3. Unfolding . . . . .](#) [5](#)
  - [5.4. Example . . . . .](#) [6](#)
- [6. Security Considerations . . . . .](#) [7](#)
- [7. IANA Considerations . . . . .](#) [7](#)
- [8. References . . . . .](#) [8](#)
  - [8.1. Normative References . . . . .](#) [8](#)
  - [8.2. Informative References . . . . .](#) [8](#)
- [Appendix A. POSIX Shell Script . . . . .](#) [9](#)
- [Acknowledgements . . . . .](#) [13](#)
- [Authors' Addresses . . . . .](#) [13](#)

**1. Introduction**

Internet drafts many times contain artwork that exceed the 72 character limit specified by [RFC 7994 \[RFC7994\]](#). The "xml2rfc" utility, in an effort to maintain clean formatting, issues a warning whenever artwork lines exceed 69 characters. According to RFC Editor, there is currently no convention in place for how to handle long lines, other than clearly indicating that some manipulation has occurred.

This document introduces a simple and yet time-proven strategy for handling long lines using a backslash ('\') character where line-folding has occurred. The strategy works on any text based artwork, producing consistent results regardless the artwork content. Using a per-artwork header, the strategy is both self-documenting and enables automated reconstitution of the original artwork.



## **2. Requirements Language**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14 \[RFC2119\] \[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

## **3. Goals**

### **3.1. Automated folding of long lines in artwork**

Automated folding of long lines is needed in order to support draft compilations that entail a) validation of source input files (e.g., YANG, XML, JSON, ABNF, ASN.1) and/or b) dynamic generation of output (e.g., tree diagrams) that are stitched into the final draft to be submitted.

Generally, in order for tooling to be able to process input files, the files must be in their original/natural state, which may include having some long lines. Thus, these source files need to be modified before inclusion in the draft in order to satisfy the line length limits. This modification SHOULD be automated to reduce effort and errors resulting from manual effort.

Similarly, dynamically generated output (e.g., tree diagrams) must also be modified, if necessary, in order for the resulting I-D to satisfy the line length limits. When needed, this effort again SHOULD be automated to reduce effort and errors resulting from manual effort.

### **3.2. Automated reconstitution of original artwork**

Automated reconstitution of the original artwork is needed to support validation of artwork extracted from drafts. Already YANG modules are extracted from drafts and validated as part of the [draft-submission](#) process. Additionally, there has been some discussion regarding needing to do the same for examples contained within drafts ([\[yang-doctors-list\]](#)). Thus, it SHOULD be possible to mechanically reconstitute artwork in order to satisfy the tooling input parsers.

## **4. Limitations**

### **4.1. Doesn't work well on graphical artwork**

While the solution presented in this document will work on any kind of text-based artwork, it is most useful on artwork that represents sourcecode (e.g., YANG, XML, JSON, etc.) or, more generally, on



artwork that has not been laid out in two dimensions (e.g., diagrams).

The issue regards the readability of the folded artwork in the draft. Artwork that is unpredictable is especially susceptible is looking bad when folded; falling into this category are most UML diagrams. Artwork that is somewhat structured (e.g., YANG tree diagrams [[RFC8340](#)]) fair better when folded, as the eyes seem to be able to still see the vertical lines, even when they are interrupted.

It is thus NOT RECOMMENDED to use the solution presented in this document on graphical artwork.

#### **4.2. Doesn't work as well as format-specific options**

The solution presented in this document works generically for all artwork, as it only views artwork as plain text. However, various formats sometimes have mechanisms that can be used to prevent long lines.

For instance, some source formats allow any quoted string to be broken up into substrings separated by a concatenation character ('+'), any of which can be on a different line.

In another example, some languages allow factoring out chunks of code out into "functions" or "groupings". Using such call outs is especially helpful when in some deeply-nested code, as it typically resets the indentation back to the first column.

As such, it is RECOMMENDED that authors do as much as possible within the selected format to avoid long lines.

### **5. Solution**

The following two sections provide the folding and unfolding algorithms that MUST be implemented to align with this BCP.

#### **5.1. Header**

Any artwork that has been folded as specified by this document MUST contain the header described in this section.

The header is two lines long.

The first line is the following 53-character string that has been padded with roughly equal numbers of equal ('=') characters to reach the artwork's maximum line length. This line is self-describing in three ways: use of '\ ' character, identification of BCP/RFC, and



identification of what the maximum line length is for the artwork. Following is the minimal header string (53-characters):

```
=== NOTE: '\' line wrapping per BCP XX (RFC XXXX) ===
```

The second line is a blank line. This line provides visual separation for the readability.

## 5.2. Folding

Scan the artwork to see if any line exceeds the desired maximum. If no line exceeds the desired maximum, exit (this artwork does not need to be folded).

Ensure that the desired maximum is not less than the minimum header, which is 53 characters. If the desired maximum is less than this minimum, exit (this artwork can not be folded).

Scan the artwork to ensure no existing lines already end with a '\' character on the desired maximum column, as this would lead to an ambiguous result. If such a line is found, exit (this artwork cannot be folded).

For each line in the artwork, from top-to-bottom, if the line exceeds the desired maximum, then fold the line at the desired maximum column by inserting the string "\\n" (backslash followed by line return) at the column before the maximum column. Note that the column before needs to be used in order to enable the '\' character to be placed on the desired maximum column. The result of this operation is that the character that was on the maximum column is now the first character of the next line.

Continue in this manner until reaching the end of the artwork. Note that this algorithm naturally addresses the case where the remainder of a folded line is still longer than the desired maximum, and hence needs to be folded again, ad infinitum.

## 5.3. Unfolding

Scan the beginning of the artwork for the header described in [Section 5.1](#). If the header is not present, starting on the first line of the artwork, exit (this artwork does not need to be unfolded).

Calculate the folding-column used from the length of the provided header.

Remove the 2-line header from the artwork.





For each line in the artwork, from top-to-bottom, if the line has a '\' on the folding-column followed by a '\n' character, then remove both the '\' and '\n' characters, which will bring up the next line, and then scan the remainder of the line to see if it again has a '\' after folding-column characters followed by a '\n' character, and so on.

Continue in this manner until reaching the end of the artwork.

#### **5.4. Example**

The following self-documenting example illustrates the result of the folding algorithm running over a specific artwork input.

The specific input used cannot be presented here, as it would again need to be folded. Alas, only the result can be provided.

Some things to note about the following example:

- o This artwork is exactly 69 characters wide, the widest possible before `xml2rfc` starts to issue warnings.
- o The line having the 'x' character on the 69th column would've been illegal input had the '\' been used.







## **8. References**

### **8.1. Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

### **8.2. Informative References**

- [RFC7994] Flanagan, H., "Requirements for Plain-Text RFCs", [RFC 7994](#), DOI 10.17487/RFC7994, December 2016, <<https://www.rfc-editor.org/info/rfc7994>>.
- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [yang-doctors-list] "[yang-doctors] automating yang doctor reviews", <<https://mailarchive.ietf.org/arch/msg/yang-doctors/DCfBqgfZPAD7afzeDF1Q1Xm2X3g>>.



**Appendix A. POSIX Shell Script**

This non-normative appendix section includes a shell script that can both fold and unfold artwork based on the solution presented in this document.

As a testament for the simplicity of this solution, note that at the core of the script are the following two one-liners:

For folding:

```
gsed "/.\{$testcol\}/s/\(.\{$foldcol\}\)/\1\\\n/g"
```

For unfolding:

```
gsed ":x; /[\^t]\\\{$foldcol\\\}\\\n$/N; s\\\n\t/; tx; s\t//g"
```

Disclaimer: this script has the limitation of disallowing the input file from containing any TAB ('\t') characters.

```
====START SCRIPT====
```

```
===== NOTE: '\ ' line wrapping per BCP XX (RFC XXXX) =====
```

```
#!/bin/bash
```

```
#
```

```
# the only reason why /bin/sh isn't being used
```

```
# is because "echo -n" is broken on the Mac.
```

```
print_usage() {
```

```
  echo
```

```
  echo "Folds the text file, only if needed, at the specified"
```

```
  echo "column, according to BCP XX."
```

```
  echo
```

```
  echo "Usage: $0 [-c <col>] [-r] -i <infile> -o <outfile>"
```

```
  echo
```

```
  echo "  -c: column to fold on (default: 69)"
```

```
  echo "  -r: reverses the operation"
```

```
  echo "  -i: the input filename"
```

```
  echo "  -o: the output filename"
```

```
  echo "  -d: show debug messages"
```

```
  echo "  -h: show this message"
```

```
  echo
```

```
  echo "Exit status code: zero on success, non-zero otherwise."
```

```
  echo
```

```
}
```

```
# global vars, do not edit
```

```
debug=0
```





```

reversed=0
infile=""
outfile=""
maxcol=69 # default, may be overridden by param
hdr_txt==== NOTE: '\ ' line wrapping per BCP XX (RFC XXXX) ====
equal_chars="====="

fold_it() {
  # since upcoming tests are >= (not >)
  testcol=`expr "$maxcol" + 1`

  # check if file needs folding
  grep ".\{$testcol\}" $infile >> /dev/null 2>&1
  if [ $? -ne 0 ]; then
    if [[ $debug -eq 1 ]]; then
      echo "nothing to do"
    fi
    cp $infile $outfile
    return 0
  fi

  foldcol=`expr "$maxcol" - 1` # for the inserted '\ ' char

  # ensure file doesn't have any '\ ' char on $maxcol already
  # - as this would lead to false positives...
  grep "^\.\{$foldcol\}\\\\\$" $infile >> /dev/null 2>&1
  if [ $? -eq 0 ]; then
    echo
    echo "Error: infile has a '\\\ ' on column $maxcol already."
    echo
    exit 1
  fi

  # calculate '=' character-filled header
  length=${#hdr_txt}
  left_sp=`expr \( "$maxcol" - "$length" \) / 2`
  right_sp=`expr "$maxcol" - "$length" - "$left_sp"`
  header=`printf "%.*s%*.s" "$left_sp" "$equal_chars" "$hdr_txt" "\
$right_sp" "$equal_chars"`

  # generate outfile and return
  echo -ne "$header\n\n" > $outfile
  gsed "/.\{$testcol\}/s/\(.\{$foldcol\}\)/\1\\\\\n/g" < $infile >> \
$outfile
  return 0
}

```



```
unfold_it() {
# check if it looks like a BCP XX header
line=`head -n 1 $infile | fgrep "$hdr_txt"`
if [ $? -ne 0 ]; then
    if [[ $debug -eq 1 ]]; then
        echo "nothing to do"
    fi
    cp $infile $outfile
    return 0
fi

# determine what maxcol value was used
maxcol=${#line}

# output all but the first two lines (the header) to wip (work in \
progress) file
awk "NR>2" $infile > /tmp/wip

# unfold wip file
foldcol=`expr "$maxcol" - 1` # for the inserted '\' char
gsed ":x; /[\t]\{${foldcol}\}\$/N; s/>\n\t/; tx; s/\t//g"\
/tmp/wip > $outfile

# clean up and return
rm /tmp/wip
return 0
}

process_input() {
while [ "$1" != "" ]; do
    if [ "$1" == "-h" -o "$1" == "--help" ]; then
        print_usage
        exit 1
    fi
    if [ "$1" == "-d" ]; then
        debug=1
    fi
    if [ "$1" == "-c" ]; then
        maxcol="$2"
        shift
    fi
    if [ "$1" == "-r" ]; then
        reversed=1
    fi
    if [ "$1" == "-i" ]; then
        infile="$2"
        shift
    fi
done
}
```



```
    fi
    if [ "$1" == "-o" ]; then
        outfile="$2"
        shift
    fi
    shift
done

if [ -z "$infile" ]; then
    echo
    echo "Error: infile parameter missing (use -h for help)"
    echo
    exit 1
fi

if [ -z "$outfile" ]; then
    echo
    echo "Error: outfile parameter missing (use -h for help)"
    echo
    exit 1
fi

if [ ! -f "$infile" ]; then
    echo
    echo "Error: specified file \"$infile\" is does not exist."
    echo
    exit 1
fi

min_supported=${#hdr_txt}
if [ $maxcol -lt $min_supported ]; then
    echo
    echo "Error: the folding column cannot be less than $min_support\
ed"
    echo
    exit 1
fi

max_supported=`expr ${#equal_chars} + ${#hdr_txt} + ${#equal_chars}\
}`
if [ $maxcol -gt $max_supported ]; then
    echo
    echo "Error: the folding column cannot be more than $max_support\
ed"
    echo
    exit 1
fi
```



```
}

main() {
  if [ "$#" == "0" ]; then
    print_usage
    exit 1
  fi

  process_input $@

  if [[ $reversed -eq 0 ]]; then
    fold_it
    code=$?
  else
    unfold_it
    code=$?
  fi
  exit $code
}

main "$@"

====END SCRIPT====
```

#### Acknowledgements

The authors thank the RFC Editor for confirming that there are no set convention today for handling long lines in artwork.

#### Authors' Addresses

Kent Watsen  
Juniper Networks

EMail: kwatsen@juniper.net

Qin Wu  
Huawei Technologies

EMail: bill.wu@huawei.com



