

Internet Engineering Task Force
Internet-Draft
Updates: [5234](#) (if approved)
Intended status: Standards Track
Expires: February 19, 2015

P. Kyzivat
August 18, 2014

Case-Sensitive String Support in ABNF
draft-kyzivat-case-sensitive-abnf-01

Abstract

This document extends the base definition of ABNF (Augmented Mackus-Naur Form) to include a way to specify ASCII string literals that are matched in a case-sensitive manner.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 19, 2015.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	Updates to RFC5234	2
2.1.	Terminal values - literal text strings	2
2.2.	ABNF Definition of ABNF - char-val	4
3.	IANA Considerations	4
4.	Security Considerations	4
5.	Normative References	4
	Author's Address	4

[1.](#) Introduction

The base definition of ABNF (Augmented Backus-Naur Form) supports ASCII string literals. Matching of these literals is done in a case-insensitive manner. While this is often the desired behavior, in some situations case-sensitive matching of string literals is needed. Literals for case-sensitive matching must be specified using the numeric representation of those characters. That is inconvenient and error prone both to write and to read.

This document extends ABNF to have two different types of ASCII string literals. One type is matched using case-sensitive matching, while the other is matched using case-insensitive matching. These types are denoted using type prefixes, similar to the type prefixes used with numeric values. If no prefix is used, then case-insensitive matching is used, consistent with previous behavior.

This document is structured as a set of changes to the full ABNF specification [[RFC5234](#)].

[2.](#) Updates to [RFC5234](#)

This document makes changes to two parts of [RFC5234](#). The two changes are:

- o Replace the last half of [section 2.3 of RFC5234](#) (beginning with "ABNF permits the specification of literal text strings") with the contents of [Section 2.1](#) below.
- o Replace the <char-val> rule in [section 4 of RFC5234](#) with the contents of [Section 2.2](#) below.

[2.1.](#) Terminal values - literal text strings

ABNF permits the specification of literal text strings directly, enclosed in quotation marks. Hence:

Kyzivat

Expires February 19, 2015

[Page 2]

Internet-Draft

Case-Sensitive String Support in ABNF

August 2014

```
command      = "command string"
```

Literal text strings are interpreted as a concatenated set of printable characters. The character set for these strings is US-ASCII.

Literal text strings in ABNF may be either case sensitive or case insensitive. The form of matching used with a literal text string is denoted by a prefix to the quoted string. The following prefixes are allowed:

```
%s          = case-sensitive
%i          = case-insensitive
```

If no prefix is present then the string is case-insensitive.

Hence:

```
rulename = %i"aBc"
```

and:

```
rulename = "abc"
```

will both match "abc", "Abc", "aBc", "abC", "ABc", "aBC", "AbC", and "ABC".

In contrast:

```
rulename = %s"aBc"
```

will match only "aBc", and will not match "abc", "Abc", "abC", "ABc", "aBC", "AbC", or "ABC".

The way that has been used in the past to define a rule that is case sensitive is to specify the individual characters numerically.

For example:

```
rulename      = %d97 %d98 %d99
```

or

```
rulename      = %x61.62.63
```

will match only the string that comprises only the lowercase characters, abc. This mechanism has a clear readability

disadvantage, with respect to using a literal text string with a prefix, and now the prefix mechanism is preferred.

[2.2.](#) ABNF Definition of ABNF - char-val

```
char-val      = case-insensitive-string /  
                case-sensitive-string
```

```
case-insensitive-string =  
    [ "%i" ] quoted-string
```

```
case-sensitive-string =  
    "%s" quoted-string
```

```
quoted-string  = DQUOTE *(%x20-21 / %x23-7E) DQUOTE  
                ; quoted string of SP and VCHAR  
                ; without DQUOTE
```

[3.](#) IANA Considerations

This memo includes no request to IANA.

[4.](#) Security Considerations

Security is truly believed to be irrelevant to this document.

[5.](#) Normative References

[RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax

Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.

Author's Address

Paul Kyzivat
Massachusetts
US

Email: pkyzivat@alum.mit.edu