

Network Working Group
Internet-Draft
Intended status: Informational
Expires: 23 November 2022

D. Liu
J. Halpern
C. Zhang
Ericsson
22 May 2022

Interface Stack Table Definition and Example for Point-to-Point (P2P)
Interface over LAN
draft-liu-lsr-p2poverlan-11

Abstract

[RFC 5309](#) defines the Point-to-Point (P2P) circuit type, one of the two circuit types used in the link state routing protocols, and highlights that it is important to identify the correct circuit type when forming adjacencies, flooding link state database packets, and monitoring the link state.

This document provides advice about the ifStack for the P2P interface over LAN ifType to facilitate operational control, maintenance and statistics.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 23 November 2022.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document.

Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Table of Contents

1.	Introduction	2
2.	Requirements Language	3
3.	Interface Stack Table for P2P Interface Type	3
3.1.	P2P Interface higher-layer-if and lower-layer-if	3
3.2.	P2P Interface Statistics	4
3.3.	P2P Interface Administrative State	4
4.	Security Considerations	5
5.	IANA Considerations	5
6.	Acknowledgements	5
7.	References	5
7.1.	Normative references	5
7.2.	Informative References	6
Appendix A.	Examples	6
	Authors' Addresses	10

[1.](#) Introduction

[RFC5309] defines the P2P circuit type and highlights that it is important to identify the correct circuit type when forming adjacencies, flooding link state database packets, and monitoring the link state.

To simplify configuration and operational control, it is helpful to represent the fact that an interface is to be considered a P2P interface over LAN type explicitly in the interface stack. This enables, for example, routing protocols to automatically inherit the correct operating mode from the interface stack without further configuration (No need to explicitly configure the P2P interface in routing protocols).

It is helpful to map the P2P interface over LAN type in the interface management stack table. If no entry specifies the P2P interface lower layer, management tools lose the ability to retrieve and measure properties specific to lower layers.

The P2P interface over LAN type is intended to be used solely as a means to signal in standard network management protocols that make use of ifStackTables that the upper layer interface is P2P interface, and thus the upper and lower layers of P2P over LAN type will be expected to apply appropriate semantics: In general, P2P over LAN

type higher layer SHOULD always be "ipForward" (Value 142, [\[Assignment\]](#)), and the P2P over LAN type lower layer SHOULD be any appropriate link data layer of "ipForward".

The assignment of 303, as the value for p2pOverLan ifType was made by Expert Review [\[Assignment\]](#). So the purpose of this document is to request IANA to add this document as a reference to ifType 303, as well as suggest how to use ifStackTable for the P2P interface over LAN type, and provide examples.

It should be noted that this document reflects the operating model used on some routers. Other routers that use different models may not represent a P2P as an ifIndex.

[2.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#) [\[RFC8174\]](#).

[3.](#) Interface Stack Table for P2P Interface Type

[3.1.](#) P2P Interface higher-layer-if and lower-layer-if

If a device implements the IF-MIB [\[RFC2863\]](#), each entry in the "/interfaces/interface" list (in "Interface Management YANG") in the operational state is typically mapped to one ifEntry as required in [\[RFC8343\]](#). Therefore the P2P interface over LAN type should also be fully mapped to one ifEntry by defining the "ifStackTable" ("higher-layer-if" and "lower-layer-if", defined in [\[RFC8343\]](#)).

In ifStackTable the P2P interface over LAN type higher layer SHALL be network layer "ipForward" to enable IP routing, and the P2P interface over LAN type lower layer SHOULD be any link data layer that can be bound to "ipForward" including "ethernetCsmacd", "ieee8023adLag", "l2vlan", and so on (defined in IANA).

The P2P interface over LAN type ifStackTable can be defined along the lines of following example (In the example, "lower-layer-if" takes "ethernetCsmacd" but in fact, "lower-layer-if" can be any other available link data layer. See [Appendix A](#) for more examples) which complies with [\[RFC8343\]](#) [\[RFC6991\]](#):

<CODE BEGINS>

```
<interface>
  <name>isis_int</name>
  <type>ianaift:ipForward</type>
</interface>

<interface>
  <name>eth1</name>
  <type>ianaift:ethernetCsmacd</type>
</interface>

<interface>
  <name>p2p</name>
  <type>ianaift:p2pOverLan</type>
  <higher-layer-if>isis_int</higher-layer-if>
  <lower-layer-if>eth1</lower-layer-if>
  <enabled>>false</enabled>
  <admin-status>down</admin-status>
  <oper-status>down</oper-status>
  <statistics>
    <discontinuity-time>
      2021-04-01T03:00:00+00:00
    </discontinuity-time>
    <!-- counters now shown here -->
  </statistics>
</interface>
```

<CODE ENDS>

Figure 1

[3.2.](#) P2P Interface Statistics

Because multiple IP interfaces can be bound to one physical port, the statistics on the physical port SHOULD be a complete set which includes statistics of all upper layer interfaces. Therefore, each p2p interface collects and displays traffic that has been sent to it via higher layers or received from it via lower layers.

[3.3.](#) P2P Interface Administrative State

The P2P interface can be shutdown independently of the underlying interface.

If the P2P interface is administratively up, then the "oper-status", defined in [[RFC8343](#)], of that interface SHALL fully reflect state of the underlying interface; if the P2P interface is administratively down, then the "oper-status" of that interface SHALL be down. Examples can be found in [Appendix A](#).

[4.](#) Security Considerations

The writable attribute "admin-status" of p2poverlan ifType is inherited from [[RFC8343](#)]. Other objects associated with the p2poverlan ifType are read-only. With this in mind, the considerations discussed [Section 7 of \[RFC8343\]](#) otherwise apply to the p2poverlan ifType.

[5.](#) IANA Considerations

In the Interface Types registry, IANA has assigned a value of 303 for p2pOverLan [[Assignment](#)] with a reference of [[RFC5309](#)]. IANA is requested to amend the reference for that code point to be to this document and to make a similar amendment in the YANG iana-if-type module (originally specified in [[RFC7224](#)]) which currently points to [[RFC8561](#)], as this document explains how the ifType is to be used.

[6.](#) Acknowledgements

The authors would like to thank Rob Wilton for his reviews and valuable comments and suggestions.

7. References

7.1. Normative references

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), DOI 10.17487/RFC2863, June 2000, <<https://www.rfc-editor.org/info/rfc2863>>.
- [RFC5309] Shen, N., Ed. and A. Zinin, Ed., "Point-to-Point Operation over LAN in Link State Routing Protocols", [RFC 5309](#), DOI 10.17487/RFC5309, October 2008, <<https://www.rfc-editor.org/info/rfc5309>>.
- [RFC7224] Bjorklund, M., "IANA Interface Type YANG Module", [RFC 7224](#), DOI 10.17487/RFC7224, May 2014, <<https://www.rfc-editor.org/info/rfc7224>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

Liu, et al.

Expires 23 November 2022

[Page 5]

Internet-Draft

IfStackTable for P2poverLAN interface

May 2022

- [RFC8343] Bjorklund, M., "A YANG Data Model for Interface Management", [RFC 8343](#), DOI 10.17487/RFC8343, March 2018, <<https://www.rfc-editor.org/info/rfc8343>>.
- [RFC8561] Ahlberg, J., Ye, M., Li, X., Spreafico, D., and M. Vaupotic, "A YANG Data Model for Microwave Radio Link", [RFC 8561](#), DOI 10.17487/RFC8561, June 2019, <<https://www.rfc-editor.org/info/rfc8561>>.

7.2. Informative References

- [Assignment] "Interface Types (ifType)", <<https://www.iana.org/assignments/smi-numbers/smi-numbers.xhtml#smi-numbers-5>>.

[RFC6991] Schoenwaelder, J., Ed., "Common YANG Data Types",
[RFC 6991](https://www.rfc-editor.org/info/rfc6991), DOI 10.17487/RFC6991, July 2013,
<<https://www.rfc-editor.org/info/rfc6991>>.

Appendix A. Examples

In the case of underlying interface is VLAN sub-interface, the ifStackTable should be defined as:

<CODE BEGINS>

```
<interface>
  <name>isis_int</name>
  <type>ianaift:ipForward</type>
</interface>

<interface>
  <name>eth1_valn1</name>
```

```

    <type>ianaift:l2vlan</type>
</interface>

<interface>
  <name>p2p</name>
  <type>ianaift:p2pOverLan</type>
  <higher-layer-if>isis_int</higher-layer-if>
  <lower-layer-if>eth1_valn1</lower-layer-if>
  <enabled>>false</enabled>
  <admin-status>down</admin-status>
  <oper-status>down</oper-status>
  <statistics>
    <discontinuity-time>
      2021-04-01T03:00:00+00:00
    </discontinuity-time>
    <!-- counters now shown here -->
  </statistics>
</interface>
<CODE ENDS>

```

Figure 2

In the case of underlying interface is LAG, the ifStackTable should be defined as:

<CODE BEGINS>


```

<interface>
  <name>isis_int</name>
  <type>ianaift:ipForward</type>
</interface>

<interface>
  <name>eth1_lag1</name>
  <type>ianaift:ieee8023adLag</type>
</interface>

<interface>
  <name>p2p</name>
  <type>ianaift:p2pOverLan</type>
  <higher-layer-if>isis_int</higher-layer-if>
  <lower-layer-if>eth1_lag1</lower-layer-if>
  <enabled>>false</enabled>
  <admin-status>down</admin-status>
  <oper-status>down</oper-status>
  <statistics>
    <discontinuity-time>
      2021-04-01T03:00:00+00:00
    </discontinuity-time>
    <!-- counters now shown here -->
  </statistics>
</interface>
<CODE ENDS>

```

Figure 3

In the case of P2P interface and underlying interface are both administratively up, and the underlying interface operational status is up:

```

<CODE BEGINS>
  <interface>
    <name>p2p</name>
    <type>ianaift:p2pOverLan</type>
    <higher-layer-if>isis_int</higher-layer-if>
    <lower-layer-if>eth1</lower-layer-if>
    <admin-status>up</admin-status>
    <oper-status>up</oper-status>
  </interface>
<CODE ENDS>

```

Figure 4

In the case of P2P interface and underlying interface are administratively up, but the underlying interface operational status is down:

```
<CODE BEGINS>
  <interface>
    <name>p2p</name>
    <type>ianaift:p2pOverLan</type>
    <higher-layer-if>isis_int</higher-layer-if>
    <lower-layer-if>eth1</lower-layer-if>
    <admin-status>up</admin-status>
    <oper-status>down</oper-status>
  </interface>
<CODE ENDS>
```

Figure 5

In the case of P2P interface is administratively down:

```
<CODE BEGINS>
  <interface>
    <name>p2p</name>
    <type>ianaift:p2pOverLan</type>
    <higher-layer-if>isis_int</higher-layer-if>
    <lower-layer-if>eth1</lower-layer-if>
    <admin-status>down</admin-status>
    <oper-status>down</oper-status>
  </interface>
<CODE ENDS>
```

Figure 6

In the case of P2P interface is administratively up but underlying is administratively down:

```
<CODE BEGINS>
  <interface>
    <name>p2p</name>
    <type>ianaift:p2pOverLan</type>
    <higher-layer-if>isis_int</higher-layer-if>
    <lower-layer-if>eth1</lower-layer-if>
    <admin-status>up</admin-status>
    <oper-status>down</oper-status>
  </interface>
<CODE ENDS>
```

Figure 7

Liu, et al.

Expires 23 November 2022

[Page 9]

Internet-Draft

IfStackTable for P2poverLAN interface

May 2022

Authors' Addresses

Daiying Liu
Ericsson
No.5 Lize East street
Beijing
100102
China
Email: harold.liu@ericsson.com

Joel Halpern
Ericsson
Email: joel.halpern@ericsson.com

Congjie Zhang
Ericsson
Email: congjie.zhang@ericsson.com

