

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: May 3, 2017

X. Liu
Kuatro Technologies
I. Bryskin
Huawei Technologies
V. Beeram
Juniper Networks
T. Saad
Cisco Systems Inc
H. Shah
Ciena
S. Litkowski
Orange Business Service
October 30, 2016

YANG Data Model for Layer 3 TE Topologies
draft-liu-teas-yang-sr-te-topo-01

Abstract

This document defines a YANG data model for Segment Routing (SR) topology and Segment Routing (SR) traffic engineering (TE) topology.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 3, 2017.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of

publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Terminology	2
2.	Modeling Considerations	3
2.1.	Segment Routing (SR) topology	3
2.2.	Segment Routing (SR) TE topology	3
2.3.	Relations to ietf-segment-routing	4
2.4.	Open Items	4
3.	Model Structure	4
4.	YANG Module	6
5.	IANA Considerations	11
6.	Security Considerations	11
7.	References	11
7.1.	Normative References	11
7.2.	Informative References	12
	Authors' Addresses	12

[1.](#) Introduction

This document defines a YANG [[RFC7950](#)] data model for describing the presentations of Segment Routing (SR) topology and Segment Routing (SR) traffic engineering (TE) topology.

[1.1.](#) Terminology

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [[RFC2119](#)].


The following terms are defined in [[RFC7950](#)] and are not redefined here:

- o augment
- o data model
- o data node

2. Modeling Considerations


2.1. Segment Routing (SR) topology

The Layer 3 network topology model is discussed in [\[I-D.ietf-i2rs-yang-l3-topology\]](#). The Segment Routing (SR) topology model proposed in this document augments and uses the `ietf-l3-unicast-igp-topology` module defined in [\[I-D.ietf-i2rs-yang-l3-topology\]](#). SR related attributes are covered in the `ietf-sr-topology` model.



2.2. Segment Routing (SR) TE topology

When traffic engineering is enabled on an SR topology, there will be associations between objects in SR topologies and objects in TE topologies. An SR TE topology is both an SR topology and a layer 3 TE topology. Multiple inheritance is used to achieve such relations.



Each type of topologies is indicated by "network-types" defined in [\[I-D.ietf-i2rs-yang-network-topo\]](#). For the three types of topologies above, the data representations are:

L3 Topology:

```
/nw:networks/nw:network/nw:network-types/l3-unicast-topology
```

L3 TE Topology:

```
/nw:networks/nw:network/nw:network-types/l3-unicast-topology/l3-te
```

SR Topology:

```
/nw:networks/nw:network/nw:network-types/l3-unicast-topology/sr
```

SR TE Topology: (multiple inheritance)

```
/nw:networks/nw:network/nw:network-types/l3-unicast-topology/l3-te
```

```
/nw:networks/nw:network/nw:network-types/l3-unicast-topology/sr
```

2.3. Relations to ietf-segment-routing

[[I-D.ietf-spring-sr-yang](#)] defines ietf-segment-routing that is a model intended to be used on network elements to configure or operate segment routing; ietf-sr-topology defined in this document is intended to be used on a controller for the network-wide operations such as path computation.

SR topology model shares many modeling constructs defined in ietf-segment-routing. The module ietf-sr-topology uses the types and groupings defined in ietf-segment-routing.

2.4. Open Items

- a. Protection on link: The feature of link protection will be modeled in the next revision.
- b. Link bundle: The feature of link bundle will be modeled in the next revision.

3. Model Structure

The model tree structure of the Segment Routing (SR) topology module is as shown below:

```
module: ietf-sr-topology
augment /nw:networks/nw:network/nw:network-types/
l3t:l3-unicast-topology:
  +--rw sr!
augment /nw:networks/nw:network/l3t:l3-topology-attributes:
  +--rw sr
```



```
    +--rw config
      +--rw srgb* [lower-bound upper-bound]
        +--rw lower-bound    uint32
        +--rw upper-bound    uint32
augment /nw:networks/nw:network/nw:node/l3t:l3-node-attributes:
  +--rw sr
    +--rw config
      | +--rw srgb* [lower-bound upper-bound]
      | | +--rw lower-bound    uint32
      | | +--rw upper-bound    uint32
      | +--rw node-capabilities
      |   +--rw transport-planes* [transport-plane]
      |   | +--rw transport-plane  identityref
      |   +--rw readable-label-stack-depth?  uint8
    +--ro state
      +--ro information-source?      enumeration
      +--ro information-source-state
      | +--ro credibility-preference?  uint16
      +--ro node-capabilities
        +--ro transport-planes* [transport-plane]
        | +--ro transport-plane  identityref
        +--ro readable-label-stack-depth?  uint8
augment /nw:networks/nw:network/nw:node/l3t:l3-node-attributes/
l3t:prefix:
  +--rw sr!
    +--rw value-type?      enumeration
    +--rw start-sid        uint32
    +--rw range?          uint32
    +--rw algorithm?       identityref
    +--rw last-hop-behavior? enumeration {sid-last-hop-behavior}?
    +--rw is-local?        boolean
augment /nw:networks/nw:network/nw:node/nt:termination-point/
l3t:l3-termination-point-attributes:
augment /nw:networks/nw:network/nt:link/l3t:l3-link-attributes:
  +--rw sr
    +--rw config
      | +--rw sid?          uint32
      | +--rw value-type?   enumeration
      | +--rw is-local?     boolean
      | +--ro is-part-of-set? boolean
      | +--ro is-on-lan?    boolean
    +--ro state
      +--ro information-source?      enumeration
      +--ro information-source-state
      +--ro credibility-preference?  uint16
```


4. YANG Module

```
<CODE BEGINS> file "ietf-sr-topology@2016-10-28.yang"
module ietf-sr-topology {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-sr-topology";
  prefix "srt";

  import ietf-network {
    prefix "nw";
  }
  import ietf-network-topology {
    prefix "nt";
  }
  import ietf-l3-unicast-topology {
    prefix "l3t";
  }
  import ietf-segment-routing-common {
    prefix "sr-cmn";
  }

  organization "TBD";
  contact "TBD";
  description "L3 TE Topology model";

  revision 2016-10-28 {
    description "Initial revision";
    reference "TBD";
  }

  grouping sr-topology-type {
    description
      "Identifies the SR topology type.";
    container sr {
      presence "Indicates SR Topology";
      description
        "Its presence identifies the SR topology type.";
    }
  }

  augment "/nw:networks/nw:network/nw:network-types/"
    + "l3t:l3-unicast-topology" {
    description
      "Defines the SR topology type.";
    uses sr-topology-type;
  }
}
```



```
augment "/nw:networks/nw:network/l3t:l3-topology-attributes" {
  when "../nw:network-types/l3t:l3-unicast-topology/sr" {
    description "Augment only for SR topology.";
  }
  description "Augment topology configuration";
  uses sr-topology-attributes;
}

augment "/nw:networks/nw:network/nw:node/l3t:l3-node-attributes" {
  when "../../nw:network-types/l3t:l3-unicast-topology/sr" {
    description "Augment only for SR topology.";
  }
  description "Augment node configuration.";
  uses sr-node-attributes;
}

augment "/nw:networks/nw:network/nw:node/l3t:l3-node-attributes"
+ "/l3t:prefix" {
  when "../../nw:network-types/l3t:l3-unicast-topology/sr" {
    description "Augment only for SR topology.";
  }
  description "Augment node prefix.";
  uses sr-node-prefix-attributes;
}

augment "/nw:networks/nw:network/nw:node/nt:termination-point/"
+ "l3t:l3-termination-point-attributes" {
  when "../../nw:network-types/l3t:l3-unicast-topology/"
+ "sr" {
    description "Augment only for SR topology.";
  }
  description "Augment termination point configuration";
  uses sr-tp-attributes;
}

augment "/nw:networks/nw:network/nt:link/l3t:l3-link-attributes" {
  when "../../nw:network-types/l3t:l3-unicast-topology/sr" {
    description "Augment only for SR topology.";
  }
  description "Augment link configuration.";
  uses sr-link-attributes;
}

grouping sr-topology-attributes {
  description "SR topology scope attributes.";
  container sr {
    description
      "Containing SR attributes.";
  }
}
```



```
    container config {
      description
        "Configuraiton attributes.";
      uses sr-cmn:srgb-cfg;
    }
  } // sr
} // sr-topology-attributes

grouping information-source-attributes {
  description
    "The attributes identifying source that has provided the
    related information, and the source credibility.";
  leaf information-source {
    type enumeration {
      enum "unknown" {
        description "The source is unknown.";
      }
      enum "locally-configured" {
        description "Configured entity.";
      }
      enum "ospfv2" {
        description "OSPFv2.";
      }
      enum "ospfv3" {
        description "OSPFv3.";
      }
      enum "isis" {
        description "ISIS.";
      }
      enum "system-processed" {
        description "System processed entity.";
      }
      enum "other" {
        description "Other source.";
      }
    }
  }
  description
    "Indicates the source of the information.";
}

container information-source-state {
  description
    "The container contains state attributes related to
    the information source.";
  leaf credibility-preference {
    type uint16;
    description
      "The preference value to calculate the traffic
      engineering database credibility value used for
```



```
        tie-break selection between different
        information-source values.
        Higher value is more preferable.";
    }
}
} // information-source-attributes

grouping sr-node-attributes {
    description "SR node scope attributes.";
    container sr {
        description
            "Containing SR attributes.";
        container config {
            description
                "Configuraiton attributes.";
            uses sr-cmn:srgb-cfg;
            uses sr-cmn:node-capabilities;
        } // config
        container state {
            config false;
            description
                "Operational state data.";
            uses information-source-attributes;
            uses sr-cmn:node-capabilities;
        }
    } // sr
} // sr-node-attributes

grouping sr-node-prefix-attributes {
    description "Containing SR attributes for a prefix.";
    container sr {
        presence "Presence indicates SR is enabled.";
        description
            "Containing SR attributes for a prefix.";
        uses sr-cmn:prefix-sid-attributes;
        uses sr-cmn:last-hop-behavior;
        leaf is-local {
            type boolean;
            description
                "'true' if the SID is local.";
        }
    } // sr
} // sr-node-prefix-attributes

grouping sr-tp-attributes {
    description "SR termination point scope attributes";
} // sr-tp-attributes
```



```
grouping sr-link-attributes {
  description "SR link scope attributes";
  container sr {
    description
      "Containing SR attributes.";
    container config {
      description
        "Configuraiton attributes.";
      leaf sid {
        type uint32;
        description
          "SID.";
      }
      uses sr-cmn:sid-value-type;
      leaf is-local {
        type boolean;
        description
          "'true' if the SID is local.";
      }
      leaf is-part-of-set {
        type boolean;
        config false;
        description
          "'true' if the SID is part of a set.";
      }
      leaf is-on-lan {
        type boolean;
        config false;
        description
          "'true' if on a lan.";
      }
    }
    container state {
      config false;
      description
        "Operational state data.";
      uses information-source-attributes;
    }
  } // sr
} // sr-link-attributes
}
<CODE ENDS>
```


5. IANA Considerations

RFC Ed.: In this section, replace all occurrences of 'XXXX' with the actual RFC number (and remove this note).

This document registers the following namespace URIs in the IETF XML registry [[RFC3688](#)]:

```
-----  
URI: urn:ietf:params:xml:ns:yang:ietf-sr-topology  
Registrant Contact: The IESG.  
XML: N/A, the requested URI is an XML namespace.  
-----
```

This document registers the following YANG modules in the YANG Module Names registry [[RFC6020](#)]:

```
-----  
name:          ietf-sr-topology  
namespace:     urn:ietf:params:xml:ns:yang:ietf-sr-topology  
prefix:        srt  
reference:     RFC XXXX  
-----
```

6. Security Considerations

The configuration, state, action and notification data defined in this document are designed to be accessed via the NETCONF protocol [[RFC6241](#)]. The data-model by itself does not create any security implications. The security considerations for the NETCONF protocol are applicable. The NETCONF protocol used for sending the data supports authentication and encryption.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC6021] Schoenwaelder, J., Ed., "Common YANG Data Types", [RFC 6021](#), DOI 10.17487/RFC6021, October 2010, <<http://www.rfc-editor.org/info/rfc6021>>.

- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<http://www.rfc-editor.org/info/rfc6241>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<http://www.rfc-editor.org/info/rfc7950>>.

7.2. Informative References

- [I-D.ietf-i2rs-yang-network-topo]
Clemm, A., Medved, J., Varga, R., Tkacik, T., Bahadur, N., Ananthakrishnan, H., and X. Liu, "A Data Model for Network Topologies", [draft-ietf-i2rs-yang-network-topo-06](#) (work in progress), September 2016.
- [I-D.ietf-i2rs-yang-l3-topology]
Clemm, A., Medved, J., Varga, R., Tkacik, T., Liu, X., Bryskin, I., Guo, A., Ananthakrishnan, H., Bahadur, N., and V. Beeram, "A YANG Data Model for Layer 3 Topologies", [draft-ietf-i2rs-yang-l3-topology-04](#) (work in progress), September 2016.
- [I-D.ietf-teas-yang-te-topo]
Liu, X., Bryskin, I., Beeram, V., Saad, T., Shah, H., and O. Dios, "YANG Data Model for TE Topologies", [draft-ietf-teas-yang-te-topo-06](#) (work in progress), October 2016.
- [I-D.ietf-spring-sr-yang]
Litkowski, S., Qu, Y., Sarkar, P., and J. Tantsura, "YANG Data Model for Segment Routing", [draft-ietf-spring-sr-yang-05](#) (work in progress), October 2016.

Authors' Addresses

Xufeng Liu
Kuatro Technologies
8281 Greensboro Drive, Suite 200
McLean VA 22102
USA

EMail: xliu@kuatrotech.com

Igor Bryskin
Huawei Technologies

EMail: Igor.Bryskin@huawei.com

Vishnu Pavan Beeram
Juniper Networks

EMail: vbeeram@juniper.net

Tarek Saad
Cisco Systems Inc

EMail: tsaad@cisco.com

Himanshu Shah
Ciena

EMail: hshah@ciena.com

Stephane Litkowski
Orange Business Service

EMail: stephane.litkowski@orange.com

