

|                                 |                  |  |
|---------------------------------|------------------|--|
| Internet Engineering Task Force | C. Griffiths     |  |
| (ALTO)                          | J. Livingood     |  |
| Internet-Draft                  | R. Woundy        |  |
| Intended status: Informational  | Comcast          |  |
| Expires: May 1, 2009            | October 28, 2008 |  |

[TOC](#)

## Comcast's ISP Experiences In a Recent P4P Technical Trial draft-livingood-woundy-p4p-experiences-01

### Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with Section 6 of BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on May 1, 2009.

### Abstract

This document describes the experiences of Comcast, a large cable broadband Internet Service Provider (ISP) in the U.S., in a recent Proactive Network Provider Participation for P2P (P4P) technical trial. This trial used iTracker technology being considered by the IETF, as part of what is currently known as the Application Layer Transport Optimization (ALTO) Birds of a Feather (BoF).

---

### Table of Contents

- [1.](#) Requirements Language
- [2.](#) Introduction
- [3.](#) High-Level Details

- [4.](#) High-Level Trial Results
    - [4.1.](#) Impact on Downloads, or Downstream Traffic
    - [4.2.](#) Impact on Uploads, or Upstream Traffic
  - [5.](#) Differences Between the P4P iTrackers Used
    - [5.1.](#) P4P Fine Grain
    - [5.2.](#) P4P Coarse Grain
    - [5.3.](#) P4P Generic Weighted
  - [6.](#) Next Steps
  - [7.](#) Security Considerations
  - [8.](#) IANA Considerations
  - [9.](#) Acknowledgements
  - [10.](#) Normative References
  - [§](#) Authors' Addresses
  - [§](#) Intellectual Property and Copyright Statements
- 

## 1. Requirements Language

[TOC](#)

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119 \(Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," March 1997.\)](#) [RFC2119].

---

## 2. Introduction

[TOC](#)

Comcast is a large broadband ISP, based in the U.S., serving the majority of its customers via cable modem technology. A trial was recently conducted with Pando Networks, Yale, and several ISP members of the P4P Working Group, which is part of the Distributed Computing Industry Association (DCIA). Comcast is a member of the P4P Working Group, whose mission is to work with Internet service providers (ISPs), peer to peer (P2P) companies, and technology researchers to develop "P4P" mechanisms that accelerate distribution of content and optimize utilization of ISP network resources. P4P theoretically allows P2P networks to optimize traffic within each ISP, reducing the volume of data traversing the ISP's infrastructure and creating a more manageable flow of data. P4P can also accelerate P2P downloads for end users.

P4P's so-called "iTracker" technology was conceptually discussed with the IETF at the Peer to Peer Infrastructure (P2Pi) Workshop held on May 22, 2008, at the Massachusetts Institute of Technology (MIT). This work was discussed in greater detail at the 72nd meeting of the IETF, in Dublin, Ireland, in the ALTO BoF on July 29, 2008. Since that time, discussion of iTrackers has continued with participants of the ALTO BoF and P2Pi Workshop, as the IETF community plans for a second BoF at the 73rd meeting of the IETF in November, 2008. At IETF 72, Comcast offered to share P4P trial data

with the community, and to present this in some detail at the next ALTO BoF.

The P4P trial was conducted, in cooperation with Pando, Yale, and three other P4P member ISPs, from July 2 to July 17, 2008. This was the first P4P trial over a cable broadband network. The trial used a Pando P2P client, and Pando distributed a special 21 MB licensed video file as in order to measure the effectiveness of P4P iTrackers. A primary objective of the trial was to measure the effects that increasing the localization of P2P swarms would have on P2P uploads, P2P downloads, and ISP networks, in comparison to normal P2P activity.

---

### 3. High-Level Details

[TOC](#)

There were five different swarms for the content used in the trial. The first was a random P2P swarm, as a control group. The second, third, and fourth used different P4P iTrackers: Generic, Coarse Grained, and Fine Grained. The fifth was a proprietary Pando mechanism. (The results of the fifth swarm, while very good, are not included here since our focus is on open standards and a mechanism which may be leveraged for the benefit of the entire community of P2P clients.) During the trial, there were 15,518 downloads to Comcast-based P2P clients. Comcast deployed an iTracker server in our production network to support this trial, and configured multiple iTracker files to provide varying levels of localization to clients.

In the trial itself, a P2P client begins a P2P session by querying a pTracker, which runs and manages the P2P network. The pTracker occasionally queries the iTracker, which in this case was maintained by Comcast, the ISP. Other ISPs either managed their own iTracker or used Pando or Yale to host their iTracker files. The iTracker returns network topology information to the pTracker, which then communicates with P2P clients, in order to enable P2P clients to make network-aware decisions regarding peers.

---

### 4. High-Level Trial Results

[TOC](#)

Trial data was collected by Pando Networks and Yale University, and raw trial results were shared with Comcast and all of the other ISPs involved in the trial. Analysis of the raw results was performed by Pando and Yale, and these organizations delivered an analysis of the P4P trial. Using the raw data, Comcast also analyzed the trial results. Furthermore, the raw trial results for Comcast were shared with Net Forecast, Inc., which performed an independent analysis of the trial for Comcast.

---

#### 4.1. Impact on Downloads, or Downstream Traffic

[TOC](#)

The results of the trial indicated that P4P can improve the speed of downloads to P2P clients. In addition, P4P was effective in localizing P2P traffic within the Comcast network.

---

Impact of P4P on Downloads:

| Swarm              | Global Avg bps | Change | Comcast Avg bps | Change |
|--------------------|----------------|--------|-----------------|--------|
| Random (Control)   | 144,045 bps    | n/a    | 254,671 bps     | n/a    |
| -----              | -----          | -----  | -----           | -----  |
| P4P Fine Grained   | 162,344 bps    | +13%   | 402,043 bps     | +57%   |
| -----              | -----          | -----  | -----           | -----  |
| P4P Generic Weight | 163,205 bps    | +13%   | 463,782 bps     | +82%   |
| -----              | -----          | -----  | -----           | -----  |
| P4P Coarse Grained | 166,273 bps    | +15%   | 471,218 bps     | +85%   |

**Table 1: Data Collected with Pando Networks and Yale University**

---

#### 4.2. Impact on Uploads, or Upstream Traffic

[TOC](#)

An analysis of the effects of P4P on upstream utilization and Internet transit was also interesting. It did not appear that P4P significantly increased upstream utilization in our access network; in essence uploading was already occurring no matter what and P4P in and of itself did not appear to materially increase uploading for this specific, licensed content. (P4P is not intended as a solution for the potential of network congestion to occur.) Random was 143,236 MB and P4P Generic Weight was 143,143 MB, while P4P Coarse Grained was 139,669 MB. We also observed that P4P reduced outgoing Internet traffic by an average of 34% at peering points. Random was 134,219 MB and P4P Generic Weight was 91,979 MB, while P4P Coarse Grained was 86,652 MB.

In terms of downstream utilization, we observed that P4P reduced incoming Internet traffic by an average of 80% at peering points. Random was 47,013 MB and P4P Generic Weight was 8,610 MB, while P4P Coarse Grained was 7,764 MB. However, we did notice that download activity in our access network increased somewhat, from 56,030 MB for Random, to 59,765 MB for P4P Generic Weight, and 60,781 MB for P4P Coarse Grained.

During the trial, downloads peaked at 24,728 per day, per swarm, or nearly 124,000 per day for all five swarms. The swarm size peaked at

11,703 peers per swarm, or nearly 57,000 peers for all five swarms. We observed a comparable number of downloads in each of the five swarms.

---

## 5. Differences Between the P4P iTrackers Used

[TOC](#)

Given the size of the Comcast network, it was felt that in order to truly evaluate the iTracker application we would need to test various network topologies that reflected our network and would help gauge the level of effort and design requirements necessary to get correct statistical data out of the trial. In all cases, iTrackers were configured with automation in mind, so that any successful iTracker configuration would be automatically updating, rather than manually configured on an on-going basis. All iTrackers were hosted on the same small server, and it appeared to be relatively easy and inexpensive to scale up an iTracker infrastructure should P4P-like mechanisms become standardized and widely adopted.

---

### 5.1. P4P Fine Grain

[TOC](#)

The Fine Grain topology was the first and most complex iTracker that we built for this trial. It was a detailed mapping of Comcast backbone-connected network Autonomous System Numbers (ASN) to IP Aggregates which were weighted based on priority and distance from each other. Included in this design was a prioritization of all Peer and Internet transit connected ASNs to our backbone to ensure that P4P traffic would prefer settlement free and lower cost networks first, and then more expensive transit links. This attempted to optimize and lower transit costs associated with this traffic. We then took the additional step of detailing each ASN and IP aggregate into IP subnets down to our Optical Transport Nodes (OTN) where all Cable Modem Termination Systems (CMTS) reside. This design gave a highly localized and detailed description of our network for the iTracker to disseminate. This design defined 1,182 iTracker node identifiers, and resulted in a 210,727 line configuration file.

This iTracker was obviously the most time-consuming to create and the most complex to maintain. Trial results indicated that this level of localization was too high, and was less effective compared to lower levels of localization.

---

### 5.2. P4P Coarse Grain

[TOC](#)

Given the level of detail in the Fine Grain design, it was important that we also enable a high-level design which still used priority and weighting mechanisms for our backbone and transit links. The

Coarse Grain design was a limited or summarized version of the Fine Grain design, which used the ASN to IP Aggregate and weighted data for transit links, but removed all additional localization data. This insured we would get similar data sets from the Fine Grain design, but without the more detailed localization of each of our networks off of our backbone. This design defined 22 iTracker node identifiers, and resulted in a 1,461 line configuration file.

From an overall cost, complexity, risk, and effectiveness standpoint, this was judged to be the optimal iTracker for Comcast. Importantly, this did not require revealing the complex, internal network topology that the Fine Grain did. Updates to this iTracker were also far simpler to automate, which will better ensure that it is accurate over time, and keeps administrative overhead relatively low. However, the differences, costs, and benefits of Coarse Grain and Generic Weighted (see below) likely merit further study.

---

### 5.3. P4P Generic Weighted

[TOC](#)

The Generic Weighted design was a copy of the Coarse Grained design but instead of using our ISP-designated priority and weights, all weights were defaulted to pre-determined parameters that the Yale team had designed. All other data was replicated from the Coarse Grain design. Providing the information necessary to support the Generic Weighted iTracker was roughly the same as for Coarse Grain.

---

## 6. Next Steps

[TOC](#)

One objective of this document is to share with the IETF community the results of one P4P trial in a large broadband network, given skepticism regarding both the benefits to P2P users and to ISPs. From the perspective of P2P users, P4P potentially delivers faster P2P downloads. At the same time, ISPs can increase the localization of swarms, enabling them to reduce bytes flowing over transit points, while also delivering an optimized P2P experience to customers. However, an internal analysis of varying levels of iTracker adoption by ISPs leads us to believe that, while P4P-type mechanisms are valuable on a single ISP basis, the value of P4P increases dramatically as many ISPs choose to deploy it.

We believe these results can inform the technical discussion in the IETF over how to use iTracker mechanisms. Should such a mechanism be standardized, the use of ISP-provided iTrackers should probably be an opt-in feature for P2P users, or at least a feature of which they are explicitly aware of and which has been enabled by default in a particular P2P client. In this way, P2P users could choose to opt-in either explicitly or by their choice of P2P client in order to choose to use the iTracker to improve performance, which benefits both the user and the ISP at the same time. Importantly in terms of privacy, the iTracker makes available only network topology

information, and would not in its current form enable an ISP, via the iTracker, to determine what P2P clients were downloading what content.

It is also possible that an iTracker type of mechanism, in combination with a P2P cache, could further improve P2P download performance, which merits further study. In addition, this was a limited trial that, while very promising, indicates a need for additional technical investigation and trial work. Such follow-up study should explore the effects of P4P when more P2P client software variants are involved, with larger swarms, and with additional and more technically diverse content (file size, file type, duration of content, etc.).

---

## 7. Security Considerations

[TOC](#)

There are no security considerations to include at this time.

---

## 8. IANA Considerations

[TOC](#)

There are no IANA considerations in this document.

---

## 9. Acknowledgements

[TOC](#)

The authors wish to acknowledge the hard work of all of the P4P working group members, and specifically the focused efforts of the teams at both Pando and Yale for the trial itself. Finally, the authors recognize and appreciate Peter Sevcik and John Bartlett, of NetForecast, Inc., for their valued independent analysis of the trial results.

---

## 10. Normative References

[TOC](#)

|           |   |
|-----------|---|
| [RFC2119] | <a href="#">Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels,"</a> BCP 14, RFC 2119, March 1997 ( <a href="#">TXT</a> , <a href="#">HTML</a> , <a href="#">XML</a> ). |
|-----------|---|

---

## Authors' Addresses

[TOC](#)

|  |                 |
|--|-----------------|
|  | Chris Griffiths |
|--|-----------------|

|        |  |
|--------|--|
|        | Comcast Cable Communications   |
|        | One Comcast Center   |
|        | 1701 John F. Kennedy Boulevard   |
|        | Philadelphia, PA 19103   |
|        | US   |
| Email: | <a href="mailto:chris_griffiths@cable.comcast.com">chris_griffiths@cable.comcast.com</a> |
| URI:   | <a href="http://www.comcast.com">http://www.comcast.com</a>                              |
|        |  |
|        | Jason Livingood  |
|        | Comcast Cable Communications   |
|        | One Comcast Center   |
|        | 1701 John F. Kennedy Boulevard   |
|        | Philadelphia, PA 19103   |
|        | US   |
| Email: | <a href="mailto:jason_livingood@cable.comcast.com">jason_livingood@cable.comcast.com</a> |
| URI:   | <a href="http://www.comcast.com">http://www.comcast.com</a>                              |
|        |  |
|        | Richard Woundy   |
|        | Comcast Cable Communications   |
|        | 27 Industrial Avenue   |
|        | Chelmsford, MA 01824   |
|        | US   |
| Email: | <a href="mailto:richard_woundy@cable.comcast.com">richard_woundy@cable.comcast.com</a>   |
| URI:   | <a href="http://www.comcast.com">http://www.comcast.com</a>                              |

---

## Full Copyright Statement

[TOC](#)

Copyright © The IETF Trust (2008).

This document is subject to the rights, licenses and restrictions contained in BCP 78, and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in BCP 78 and BCP 79.



Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).