TEAS Y. Lee Internet-Draft Samsung Electronics

Intended status: Informational

Intended Status: Informational

Expires: January 13, 2022 Volta Networks
LM. Contreras
Telefonica

DC aware TE topology model draft-llc-teas-dc-aware-topo-model-01

Abstract

This document proposes the extension of the TE topology model for including information related to data center resource capabilities.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of $\underline{\mathsf{BCP}}$ 78 and $\underline{\mathsf{BCP}}$ 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at https://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 13, 2022.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to $\underline{\text{BCP }78}$ and the IETF Trust's Legal Provisions Relating to IETF Documents

(https://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

X. Liu

July 12, 2021

Table of Contents

<u>1</u> .	Introduction										2
<u>2</u> .	Datacenter information										2
<u>3</u> .	Model structure										3
<u>4</u> .	Security Considerations										5
<u>5</u> .	IANA Considerations										<u>5</u>
<u>6</u> .	References										<u>5</u>
Ackr	nowledgments										6
Auth	nors' Addresses										6

1. Introduction

More and more service providers are deploying cloud computing facilities in order to host different kinds of services and applications. Such facilities can be generally referred as Datacenter Points of Presence (DC-PoPs). Those DCs will consist on a number of servers and networking elements for connecting all of them with the transport network. Depending on the number of servers in the data center, there will be distinct capabilities in terms of CPUs, memory and storage available for deploying and running the aforementioned services.

In such distributed and interconnected DC-PoPs, both computing and topological information are of interest for determining the optimal DC where to deploy a given service or application.

This document propose a DC-aware extension for the topology model.

2. Datacenter information

The relevant information for datacenter capabilities can be described in different ways. One potential manner is to describe resource capabilities such as CPU, memory, storage, etc. This can be done in terms of total, used and free capacity for each of the parameters of interest. Another form of populating the information is by describing those resource capabilities as a bundled, usually referred as quota or flavor. In this respect, reference bundles such as the ones proposed by the Common Network Function Virtualisation Infrastructure Telecom Taskforce (CNTT), which is an initiative jointly promoted by GSMA and the Linux Foundation [CNTT], [GSMA].

Focusing on the CNTT ongoing work, the flavors there defined are characterized according to:

o Type of instance (T): the types of instances are characterized as B (Basic), or N (Network Intensive). The latter can come with

Lee, et al. Expires January 13, 2022 [Page 2]

extensions for network acceleration for offloading network intensive operations to hardware.

- o Interface Option (I): it refers to the associated bandwidth of the network interface.
- o Compute flavor (F): it refers to a given predefined combination of resources in terms of virtual CPU, RAM, disk, and bandwidth for the management interface.
- o Optional storage extension (S): allows to request additional storage capacity.
- o Optional hardware acceleration characteristics (A): to request specific acceleration capabilities for improving the performance of the infrastructure.

Additional information can refer to the management capabilities of the compute infrastructure, such as hypervisor details or virtualization technologies available.

Finally, all can be complemented with information related to the networking details for reaching the aforementioned compute capabilities (IP addressed, bandwidth, etc).

3. Model structure

```
module: ietf-dcpop-dc
  +--rw dcpop
     +--rw dc* [id]
     | +--rw hypervisor* [id]
     | | +--rw ram
       l +--rw used?
                     uint32
         | +--rw free? uint32
         +--rw disk
        | +--rw total? uint32
      l +--rw free?
                      uint32
         +--rw vcpu
        | +--rw total? uint16
      | | +--rw free?
                      uint16
      | +--rw instance* -> /dcpop/dc/instance/id
       | +--rw id
                      string
       | +--rw name?
                      string
      +--rw instance* [id]
     | | +--rw flavor
```

Lee, et al. Expires January 13, 2022 [Page 3]

```
| +--rw disk?
                    uint32
      +--rw ram?
                    uint32
      +--rw vcpus?
                    uint16
      +--rw id?
                     string
      +--rw name?
                     string
   +--rw image
      +--rw checksum
                        string
      +--rw size
                        uint32
      +--rw format
      | +--rw container?
                           enumeration
        +--rw disk?
                            enumeration
      +--rw id?
                       string
      +--rw name?
                       string
   +--rw hypervisor? -> /dcpop/dc/hypervisor/id
   +--rw port*
                       -> /dcpop/dc/network/subnetwork/port/id
   +--rw project?
                       string
  +--rw status?
                       enumeration
  +--rw id
                       string
  +--rw name?
                       string
+--rw image* [id]
 +--rw checksum
                   string
                    uint32
   +--rw size
   +--rw format
   | +--rw container?
                        enumeration
   | +--rw disk?
                         enumeration
   +--rw id
                     string
   +--rw name?
                     string
+--rw flavor* [id]
| +--rw disk?
                 uint32
  +--rw ram?
                  uint32
| +--rw vcpus?
                 uint16
 +--rw id
                  string
| +--rw name?
                  string
+--rw dc-monitoring-param* [name]
 +--rw name
                         string
| +--rw value-string?
                         string
+--rw network* [id]
| +--rw subnetwork* [id]
   | +--rw port* [id]
      | +--rw ip-address?
                            inet:ip-address
        +--rw instance?
                             -> /dcpop/dc/instance/id
        +--rw project?
                             string
        +--rw status?
                             enumeration
        +--rw id
                             string
        +--rw name?
                             string
      +--rw project?
                      string
      +--rw status?
                      enumeration
      +--rw id
                       string
```

Lee, et al. Expires January 13, 2022 [Page 4]

```
string
          +--rw dhcp-agent* [id]
       | | +--rw enabled? boolean
        | | +--rw pools* [ip-address]
       | | | +--rw ip-address
                                 inet:ip-address
         | +--rw project?
                           string
         | +--rw status?
                           enumeration
       | | +--rw id
                            string
       string
       +--rw project?
                           string
       | +--rw status?
                           enumeration
       | +--rw id
                           string
       | +--rw name?
                           string
      | | +--rw dcpop-ref?
                            -> /dcpop/dcpop-id
       +--rw ap*
                                 -> /actn-vn:actn/ap
/access-point-list/access-point-id
      | +--rw dcpop-ref?
                                  -> /dcpop/dcpop-id
     | +--rw id
                                 string
      | +--rw name?
                                 string
     +--rw dcpop-id? string
```

4. Security Considerations

The data-model in this document does not have any security implications. The model is designed to be accessed via NETCONF [RFC6241], thus the security considerations for the NETCONF protocol are applicable here.

5. IANA Considerations

This draft does not include any IANA considerations

6. References

- [GSMA] "Cloud Infrastructure Reference Model, Version 1.0",
 November 2020, <https://www.gsma.com/newsroom/wp-content/
 uploads//NG.126-v1.0-2.pdf>.

Lee, et al. Expires January 13, 2022 [Page 5]

Acknowledgments

The work of L.M. Contreras has been partly funded by the European Commission through the H2020 project 5GROWTH (Grant Agreement no. 856709).

Authors' Addresses

Young Lee Samsung Electronics Seoul South Korea

Email: younglee.tx@gmail.com

Xufeng Liu Volta Networks

Email: xufeng.liu.ietf@gmail.com

Luis M. Contreras
Telefonica
Ronda de la Comunicacion, s/n
Sur-3 building, 3rd floor
Madrid 28050
Spain

Email: luismiguel.contrerasmurillo@telefonica.com

URI: http://lmcontreras.com/