MMUSIC S. Loreto
Internet-Draft G. Camarillo

Intended status: Standards Track Ericsson
Expires: February 24, 2011 August 23, 2010

Stream Control Transmission Protocol (SCTP)-Based Media Transport in the Session Description Protocol (SDP)

<u>draft-loreto-mmusic-sctp-sdp-06</u>

#### Abstract

SCTP (Stream Control Transmission Protocol) is a transport protocol used to establish associations between two endpoints. This document describes how to express media transport over SCTP in SDP (Session Description Protocol). This document defines the 'SCTP' and 'SCTP/DTLS' protocol identifiers for SDP.

#### Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of  $\underline{\mathsf{BCP}}$  78 and  $\underline{\mathsf{BCP}}$  79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <a href="http://datatracker.ietf.org/drafts/current/">http://datatracker.ietf.org/drafts/current/</a>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 24, 2011.

## Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <a href="BCP-78">BCP-78</a> and the IETF Trust's Legal Provisions Relating to IETF Documents (<a href="http://trustee.ietf.org/license-info">http://trustee.ietf.org/license-info</a>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as

Internet-Draft	The SCT	P nrotocol	identifier	for S	ŊΡ
TIILEI IIEL-DI AI L	1116 361	L DIOLOCOT	TOCILCTITCI	101 31	דע

August 2010

described in the Simplified BSD License.

# Table of Contents

<u>1</u> .	Intro	duct	ion																					<u>3</u>
<u>2</u> .	Termi	nolo	gy .																					3
<u>3</u> .	Proto	col	Iden	tif:	ier																			3
4.	The S	etup	and	Coi	nne	cti	on	Αt	ttr	ibι	ıtε	es	ar	nd	As	SC	ci	.at	ic	n				
	Manag	emen	t.																					<u>4</u>
<u>5</u> .	Multi	homi	ng .																					4
<u>6</u> .	Examp	les																						<u>5</u>
	<u>.1</u> . A	•																						
6	<u>.2</u> . E	xist	ing	Coni	nect	tio	n	Reι	ıse															<u>6</u>
6	<u>.3</u> . S	DP d	escr	ipt:	ion	fo	r	DTL	_S	Cor	nne	ect	ic	n										<u>6</u>
<u>7</u> .	Secur	ity	Cons	ide	rat:	ion	S																	<u>6</u>
	IANA																							
<u>9</u> .	Norma	tive	Ref	erei	nces	5																		<u>7</u>
Auth	nors'	Addr	esse	S																				8

#### 1. Introduction

SDP (Session Description Protocol) [RFC4566] provides a generalpurpose format for describing multimedia sessions in announcements or invitations. RFC4145 [RFC4145] specifies a general mechanism for describing and establishing TCP (Transmission Control Protocol) streams. RFC 4572 [RFC4572] extends RFC4145 [RFC4145] for describing TCP-based media streams that are protected using TLS (Transport Layer Security) [RFC4346].

This document defines a new protocol identifier, 'SCTP', to describe SCTP-based [RFC4960] media streams. Additionally, this document specifies the use of the 'setup' and 'connection' SDP attributes to establish SCTP associations. These attributes were defined in RFC4145 [RFC4145] for TCP. This document discusses their use with SCTP.

Additionaly this document define a new protocol identifier, 'SCTP/ DTLS', to establish secure SCTP-based media streams over DTLS (Datagram Transport Layer Security) [RFC4347], as specified in [<u>I-D.ietf-tsvwg-dtls-for-sctp</u>], using SDP. The authentication certificates are interpreted and validated as defined in RFC4572 [RFC4572]. Self-signed certificates can be used securely, provided that the integrity of the SDP description is assured as defined in RFC4572 [RFC4572].

TLS is designed to run on top of a byte-stream oriented transport protocol providing a realible, in-sequence delivery like TCP. Since no-one so far has implemented SCTP over TLS, due to some serious limitations described in [I-D.ietf-tsvwg-dtls-for-sctp], this document does not make use of TLS over SCTP as described in RFC3436 [RFC3436].

## 2. Terminology

In this document, the key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" are to be interpreted as described in BCP 14, RFC 2119 [RFC2119] and indicate requirement levels for compliant implementations.

#### 3. Protocol Identifier

The following is the format for an 'm' line, as specified in RFC4566 [RFC4566]:

m=<media> <port> <proto> <fmt> ...

This document defines two new values for the 'proto' field: 'SCTP' and 'SCTP/DTLS'.

The 'SCTP' protocol identifier is similar to both the 'UDP' and 'TCP' protocol identifiers in that it only describes the transport protocol and not the upper-layer protocol. Media described using an 'm' line containing the 'SCTP' protocol identifier are carried using SCTP [RFC4960].

The 'SCTP/DTLS' protocol identifier indicates that the media described will use the Datagram Transport Layer Security (DTLS)  $[\underline{\mathsf{RFC4347}}]$  over SCTP as specified in  $[\underline{\mathsf{I-D.ietf-tsvwg-dtls-for-sctp}}]$ .

An 'm' line that specifies 'SCTP' or 'SCTP/DTLS' MUST further qualify the application-layer protocol using an fmt identifier.

An 'm' line that specifies 'SCTP/DTLS' MUST further provide a certificate fingerprint. An SDP attribute (an 'a' line) is used to transport and exchange end point certificate. The authentication certificates are interpreted and validated as defined in [RFC4572].

# 4. The Setup and Connection Attributes and Association Management

The use of the 'setup' and 'connection' attributes in the context of an SCTP association is identical to the use of these attributes in the context of a TCP connection. That is, SCTP endpoints MUST follow the rules in Sections 4 and 5 of RFC 4145 [RFC4145] when it comes to the use of the 'setup' and 'connection' attributes in offer/answer [RFC3264] exchanges.

The management of an SCTP association is identical to the management of a TCP connection. That is, SCTP endpoints MUST follow the rules in <u>Section 6 of RFC 4145</u> [<u>RFC4145</u>] to manage SCTP associations. Whether to use the SCTP ordered or unordered delivery service is up to the applications using the SCTP association.

## 5. Multihoming

An SCTP endpoint, unlike a TCP endpoint, can be multihomed. An SCTP endpoint is considered to be multihomed if it has more than one IP address. A multihomed SCTP endpoint informs a remote SCTP endpoint about all its IP addresses using the address parameters of the INIT or the INIT-ACK chunk (depending on whether or not the multihomed endpoint is the one initiating the establishment of the association). Therefore, once the address provided in the 'c' line has been used to establish the SCTP association (i.e., to send the INIT chunk), address management is performed using SCTP. This means that two SCTP endpoints can use addresses that were not listed in the 'c' line but that were negotiated using SCTP mechanisms.

Some intermediaries performing firewall control use the addresses in offer/answer exchanges to perform media authorization. That is, they will not let media through unless it is sent to the address in the 'c' line. Therefore, it is RECOMMENDED that SCTP endpoints use a main address all the time (e.g., they do not send retransmissions to a backup address) and that they send a re-INVITE every time they change that address.

## 6. Examples

The following examples show the use of the 'setup' and 'connection' SDP attributes. As discussed in <u>Section 4</u>, the use of this attributes with an SCTP association is identical to their use with a TCP connection. For the purpose of brevity, the main portion of the session description is omitted in the examples, which only show 'm' lines and their attributes (including 'c' lines).

# 6.1. Actpass/Passive

An offerer at 192.0.2.2 signals its availability for an SCTP association at SCTP port 54111. Additionally, this offerer is also willing to initiate the SCTP association:

> m=image 54111 SCTP \* c=IN IP4 192.0.2.2 a=setup:actpass a=connection:new

The endpoint at 192.0.2.1 responds with the following description:

m=image 54321 SCTP \* c=IN IP4 192.0.2.1 a=setup:passive a=connection:new

This will cause the offerer (at 192.0.2.2) to initiate an SCTP association to port 54321 at 192.0.2.1.

# 6.2. Existing Connection Reuse

Subsequent to the exchange in <u>Section 6.1</u>, another offer/answer exchange is initiated in the opposite direction. The endpoint at 192.0.2.1, which now acts as the offerer, wishes to continue using the existing association:

m=application 54321 SCTP \*
c=IN IP4 192.0.2.1
a=setup:passive
a=connection:new

Figure 1

The endpoint at 192.0.2.2 also wishes to use the existing SCTP association and responds with the following description:

m=application 9 SCTP \*
c=IN IP4 192.0.2.2
a=setup:active
a=connection:new

Figure 2

The existing SCTP association between 192.0.2.2 and 192.0.2.1 will be reused.

# <u>6.3</u>. SDP description for DTLS Connection

An offerer at 192.0.2.2 signals the availability of a T.38 fax session over SCTP/DTLS.

m=image 54111 SCTP/DTLS t38
c=IN IP4 192.0.2.2
a=setup:actpass
a=connection:new
a=fingerprint:SHA-1 \

4A:AD:B9:B1:3F:82:18:3B:54:02:12:DF:3E:5D:49:6B:19:E5:7C:AB

# 7. Security Considerations

See RFC 4566 [RFC4566] for security considerations on the use of SDP in general. See RFC 3264 [RFC3264], RFC 4145 [RFC4145] and RFC 4572 [RFC4572] for security considerations on establishing media streams using offer/answer exchanges. See RFC 4960 [RFC4960] for security considerations on SCTP in general and [I-D.ietf-tsvwg-dtls-for-sctp] for security consideration using DTLS on top of SCTP. This

specification does not introduce any new security consideration in addition to the ones discussed in those specifications.

## 8. IANA Considerations

This document defines a new proto value: SCTP. Its format is defined in <u>Section 3</u>. This proto value should be registered by the IANA under "Session Description Protocol (SDP) Parameters" under "proto".

The SDP specification, [RFC4566], states that specifications defining new proto values, like the SCTP and SCTP/DTLS proto values defined in this RFC, must define the rules by which their media format (fmt) namespace is managed. For the SCTP protocol, new formats SHOULD have an associated MIME registration. Use of an existing MIME subtype for the format is encouraged. If no MIME subtype exists, it is RECOMMENDED that a suitable one is registered through the IETF process [RFC2048] by production of, or reference to, a standardstrack RFC that defines the transport protocol for the format.

#### 9. Normative References

- [RFC2048] Freed, N., Klensin, J., and J. Postel, "Multipurpose Internet Mail Extensions (MIME) Part Four: Registration Procedures", <u>BCP 13</u>, <u>RFC 2048</u>, November 1996.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC3264] Rosenberg, J. and H. Schulzrinne, "An Offer/Answer Model with Session Description Protocol (SDP)", <u>RFC 3264</u>, June 2002.
- [RFC4145] Yon, D. and G. Camarillo, "TCP-Based Media Transport in the Session Description Protocol (SDP)", RFC 4145, September 2005.
- [RFC4346] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.1", <u>RFC 4346</u>, April 2006.
- [RFC4347] Rescorla, E. and N. Modadugu, "Datagram Transport Layer Security", <u>RFC 4347</u>, April 2006.
- [RFC3436] Jungmaier, A., Rescorla, E., and M. Tuexen, "Transport Layer Security over Stream Control Transmission Protocol", RFC 3436, December 2002.

- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", RFC 4566, July 2006.
- [RFC4572] Lennox, J., "Connection-Oriented Media Transport over the Transport Layer Security (TLS) Protocol in the Session Description Protocol (SDP)", RFC 4572, July 2006.
- [RFC4960] Stewart, R., "Stream Control Transmission Protocol", RFC 4960, September 2007.

# [I-D.ietf-tsvwg-dtls-for-sctp]

Tuexen, M., Seggelmann, R., and E. Rescorla, "Datagram Transport Layer Security (DTLS) for Stream Control Transmission Protocol (SCTP)", draft-ietf-tsvwg-dtls-for-sctp-05 (work in progress), March 2010.

## Authors' Addresses

Salvatore Loreto Ericsson Hirsalantie 11 Jorvas 02420 Finland

Email: Salvatore.Loreto@ericsson.com

Gonzalo Camarillo Ericsson Hirsalantie 11 Jorvas 02420 Finland

Email: Gonzalo.Camarillo@ericsson.com