Internet Engineering Task Force

Internet-Draft

Intended status: Standards Track

Expires: October 20, 2017

L. Velvindron, Ed. Hackers.mu April 18, 2017

Increase minimum recommended modulus size to 2048 bits draft-lvelvindron-curdle-dh-group-exchange-00

Abstract

The Diffie-Hellman (DH) Group Exchange for the Secure Shell (SSH) Transport layer Protocol specifies that servers and clients should support groups with a modulus length of k bits, where the recommended minumum value is 1024 bits. Recent security research has shown that a minimum value of 1024 bits is insufficient against state-sponsored actors. As such, this document formally updates RFC 4419 [RFC4419] such that the minimum recommended value for k is 2048 bits and the group size is 2048 bits at minimum.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of $\underline{\mathsf{BCP}}$ 78 and $\underline{\mathsf{BCP}}$ 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 20, 2017.

Copyright Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

$\underline{1}$. Introduction	2
<u>1.1</u> . Requirements Language	2
2. 2048 bits DH Group	2
3. Security Considerations	2
<u>4</u> . References	3
4.1. Normative References	3
4.2. Informative References	3
Author's Address	3

1. Introduction

RFC4419 [RFC4419] specifies a recommended minimum size of 1024 bits for k, which is the modulus length of the DH Group. It also suggests that in all cases, the size of the group needs be at least 1024 bits. This document updates RFC 4419 [RFC4419] so that the minimum recommended size be 2048 bits.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in <a href="https://recommended.org/recom

2. 2048 bits DH Group

Recent research [LOGJAM] strongly suggests that DH groups that are 1024 bits can be broken by state actors, and possibly an organization with enough computing resources. The authors show how they are able to break 768 bits DH group and extrapolate the attack to 1024 bits DH groups. In their analysis, they show that breaking 1024 bits can be done with enough computing resources. This document updates section 3 Paragraph 9: Servers and clients SHOULD support groups with a modulus length of k bits where 2048 <= k <= 8192. The recommended minimum values for min and max are 2048 and 8192, respectively. This document also updates Section 3 Paragraph 11: In all cases, ths size of the group SHOULD be at least 2048 bits.

3. Security Considerations

This document discusses security issues of DH groups that are 1024 bits in size, and formally updates the minimum size of DH groups to be 2048 bits.

4. References

4.1. Normative References

[LOGJAM] Adrian, D., Bhargavan, K., Durumeric, Z., Gaudry, P., Green, M., Halderman, J., Heninger, N., Springall, D., ThomA(C), E., Valenta, L., VanderSloot, B., Wustrow, E., Zanella-BA(C)guelin, S., and P. Zimmermann, "Imperfect Forward Secrecy: How Diffie-Hellman Fails in Practice", ACM Conference on Computer and Communications Security (CCS) 2015, 2015, https://weakdh.org/imperfect-forward-secrecy-ccs15.pdf>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", BCP 14, RFC 2119,
DOI 10.17487/RFC2119, March 1997,
http://www.rfc-editor.org/info/rfc2119.

4.2. Informative References

[RFC4419] Friedl, M., Provos, N., and W. Simpson, "Diffie-Hellman Group Exchange for the Secure Shell (SSH) Transport Layer Protocol", RFC 4419, DOI 10.17487/RFC4419, March 2006, http://www.rfc-editor.org/info/rfc4419.

Author's Address

Loganaden Velvindron (editor) Hackers.mu 88, Avenue De Plevitz Roches Brunes MU

Phone: +230 59762817 Email: logan@hackers.mu