

**TFTP Timeout Interval and Transfer Size Options**

Abstract

The Trivial File Transfer Protocol [1] is a simple, lock-step, file transfer protocol which allows a client to get or put a file onto a remote host.

This document describes two TFTP options. The first allows the client and server to negotiate the Timeout Interval. The second allows the side receiving the file to determine the ultimate size of the transfer before it begins. The TFTP Option Extension mechanism is described in [2].

Status of this Memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

To learn the current status of any Internet-Draft, please check the "1id-abstracts.txt" listing contained in the Internet-Drafts Shadow Directories on ds.internic.net (US East Coast), nic.nordu.net (Europe), ftp.isi.edu (US West Coast), or munnari.oz.au (Pacific Rim).

Timeout Interval Option Specification

The TFTP Read Request or Write Request packet is modified to include the timeout option as follows:

```
+-----+-----+-----+-----+-----+-----+-----+-----+
| opc  |filename| 0 | mode  | 0 | timeout| 0 | #secs | 0 |
+-----+-----+-----+-----+-----+-----+-----+-----+
```

opc

The opcode field contains either a 1, for Read Requests, or 2, for Write Requests, as defined in [1].

filename

The name of the file to be read or written, as defined in [1]. This is a NULL-terminated field.

mode

The mode of the file transfer: "netascii", "octet", or "mail", as defined in [1]. This is a NULL-terminated field.

timeout

The Timeout Interval option, "timeout" (case in-sensitive). This is a NULL-terminated field.

#secs

The number of seconds to wait before retransmitting, specified in ASCII. Valid values range between "1" and "255" octets, inclusive. This is a NULL-terminated field.

For example:

```

+-----+-----+---+-----+---+-----+---+-----+---+
|  1  | foobar | 0 | binary | 0 | timeout| 0 |   1  | 0 |
+-----+-----+---+-----+---+-----+---+-----+---+

```

is a Read Request, for the file named "foobar", in binary transfer mode, with a timeout interval of 1 second.

If the server is willing to accept the timeout option, it sends an Option Acknowledgment (OACK) to the client. The specified timeout value must match the value specified by the client.

Transfer Size Option Specification

The TFTP Read Request or Write Request packet is modified to include the tsize option as follows:

```

+-----+-----+---+-----+---+-----+---+-----+---+
|  opc  |filename| 0 | mode  | 0 | tsize | 0 | size | 0 |
+-----+-----+---+-----+---+-----+---+-----+---+

```

opc

The opcode field contains either a 1, for Read Requests, or 2, for Write Requests, as defined in [1].



filename

The name of the file to be read or written, as defined in [1]. This is a NULL-terminated field.

mode

The mode of the file transfer: "netascii", "octet", or "mail", as defined in [1]. This is a NULL-terminated field.

tsize

The Transfer Size option, "tsize" (case in-sensitive). This is a NULL-terminated field.

size

The size of the file to be transfered. This is a NULL-terminated field.

For example:

```

+-----+-----+---+-----+---+-----+---+-----+---+
|  2   | foobar | 0 | binary | 0 | tsize | 0 | 673312 | 0 |
+-----+-----+---+-----+---+-----+---+-----+---+

```

is a Write Request, with the 673312-octet file named "foobar", in binary transfer mode.

In Read Request packets, a size of "0" is specified in the request and the size of the file, in octets, is returned in the OACK. If the file is too large for the client to handle, it may abort the transfer with an Error packet (error code 3). In Write Request packets, the size of the file, in octets, is specified in the request and echoed back in the OACK. If the file is too large for the server to handle, it may abort the transfer with an Error packet (error code 3).

Security Considerations

The basic TFTP protocol has no security mechanism. This is why it has no rename, delete, or file overwrite capabilities. This document does not add any security to TFTP; however, the specified extensions do not add any additional security risks.

References

[1] Sollins, K., "The TFTP Protocol (Revision 2)", Request for Comments 1350 (STD 33), October 1992.

[2] Malkin, G., Harkin, A., "TFTP Option Extension", Internet Draft,



[draft-ietf-tftpexts-options-02.txt](#), December 1994.

Authors' Addresses

Gary Scott Malkin  
Bay Networks  
8 Federal Street  
Billerica, MA 01821

Phone: (978) 916-4237  
EMail: gmalkin@baynetworks.com

Art Harkin  
Internet Services Project  
Information Networks Division  
19420 Homestead Road MS 43LN  
Cupertino, CA 95014

Phone: (408) 447-3755  
EMail: ash@cup.hp.com

