

CCAMP
Internet-Draft
Intended status: Informational
Expires: August 16, 2014

G. Martinelli, Ed.
Cisco
X. Zhang, Ed.
Huawei Technologies
G. Galimberti
Cisco
A. Zanardi
D. Siracusa
CREATE-NET
February 12, 2014

Information Model for Wavelength Switched Optical Networks (WSONs) with
Impairments Validation
[draft-martinelli-ccamp-wson-iv-info-03](#)

Abstract

This document defines an information model to support Impairment-Aware (IA) Routing and Wavelength Assignment (RWA) function. This operation might be required in Wavelength Switched Optical Networks (WSON) that already support RWA and the information model defined here goes in addition and it is fully compatible with the already defined information model for impairment-free RWA process in WSON.

This information model shall support all control plane architectural options defined for WSON with impairment validation.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 16, 2014.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Definitions, Applicability and Properties	3
2.1.	Definitions	3
2.2.	Applicability	4
2.3.	Properties	5
3.	ITU-T List of Optical Parameters	6
4.	Background from WSO _N -RWA Information Model	7
5.	Optical Impairment Information Model	8
5.1.	The Optical Impairment Vector	9
5.2.	Node Information	9
5.2.1.	Impairment Matrix	10
5.2.2.	Impairment Resource Block Information	12
5.3.	Link Information	12
5.4.	Path Information	12
6.	Encoding Considerations	13
7.	Control Plane Architectures	13
7.1.	IV-Centralized	14
7.2.	IV-Distributed	14
8.	Acknowledgements	14
9.	Contributing Authors	14
10.	IANA Considerations	16
11.	Security Considerations	16
12.	References	16
12.1.	Normative References	16
12.2.	Informative References	16
Appendix A.	ITU-T Liason Tracking	17
	Authors' Addresses	17

1. Introduction

In the context of Wavelength Switched Optical Network (WSON), [RFC6163] describes the basic framework for a GMPLS and PCE-based Routing and Wavelength Assignment (RWA) control plane. The associated information model [I-D.ietf-ccamp-rwa-info] defines all information/parameters required by an RWA process.

There are cases of WSON where optical impairments plays a significant role and are considered as important constraints. The framework document [RFC6566] defines problem scope and related control plane architectural options for the Impairment Aware Routing and Wavelength Assignment (IA-RWA) operation. Options include different combinations of Impairment Validation (IV) and RWA functions in term of different combination of control plane functions (i.e., PCE, Routing, Signaling).

This document provides an information model for the impairment aware case to allow the impairment validation function implemented in the control plane or enabled by control plane available information. This model goes in addition to [I-D.ietf-ccamp-rwa-info] and it shall support any control plane architectural option described by the framework document (see sections 4.2 and 4.3 of [RFC6566]) where a set of control plane combinations of control plane functions vs. IV function is provided.

2. Definitions, Applicability and Properties

This section provides some concepts to help understand concepts used along the document and to make a clear separation about what coming from data plane definitions (ITU-T G recommendations) and are taken as input for this Information Model. The first sub-section provides raw definitions while the Applicability sections reuses the defined concepts to scope this document.

2.1. Definitions

- o Computational Model / Optical Computational Model.
Defined by ITU standard documents. In this context we look for models that are able to compute optical impairments for a given lightpath.
- o Information Model.
It is defined by IETF (this draft) and provides the set of information required by the Computational Model to be applied.
- o Level of Approximation.

This concept refer to the Computational Model as it may compute optical impairment with a certain level of uncertainty. This level is generally not measured but [[RFC6566](#)] make a rough classification about it.

- o Feasible Path.

It is the output of the CSPF with RWA-IV capability. It's a path that satisfies the constraints in particular the optical impairment constraints. The path, instantiated through wavelength, may actually work or not work depending of the level of approximation.

- o Existing Service Disruption.

A known effect to optical network designers is the cross-interaction among adjacent (spectrum) wavelengths, e.g., a wavelength may experience some increased BER due to the setting up of an adjacent wavelength. Solving this problem is a typical optical network design activity. Just as an example a simple method is adding optical margins (e.g., additional OSNR), other complex and detailed methods exist.

2.2. Applicability

This document targets at Scenario C defined in [[RFC6566](#)] [section 4.1.1](#). as approximate impairment estimation. The Approximate concept refer to the fact that this Information Model cover information mainly provided by the [[ITU.G680](#)] Computational Model.

Computational models having no approximation, referred as IV-Detailed in the [[RFC6566](#)], currently does not exist in term of ITU-T recommendation. They generally refer to non-linear optical impairment and they are usually vendor specific.

The current information model does not speculate about mathematical formula used to fill up information model parameters hence, it does not preclude changing the computational model. At the same time authors does not believe this Information Model is exhaustive and if necessary further documents will cover additional models as long as they become available.

The result of RWA-IV process implementing this Information Model will result in a path (a wavelength in the data plane) that have better chance to be feasible than if it was computed without any IV function. The Existing Service Disruption, as per the definition above, would still be a problem left to network designers: this model does not replace by any means the optical network design phase. The Information Model targets, the GMPLS context with the related relationship between data plane(s) and control plane.

2.3. Properties

An information model may have several attributes or properties that need to be defined for each optical parameter made available to the control plane. The properties will help to determine how the control plane can deal with a specific impairment parameter, depending on architectural options chosen within the overall impairment framework [RFC6566]. In some case, properties value will help to identify the level of approximation supported by the IV process.

- o Time Dependency

This identifies how an impairment parameter may vary with time. There could be cases where there is no time dependency, while in other cases there may be need of re-evaluation after a certain time. In this category, variations in impairments due to environmental factors such as those discussed in [G.sup47] are considered. In some cases, an impairment parameter that has time dependency may be considered as a constant for approximation. In this information model, we do neglect this property.

- o Wavelength Dependency

This property identifies if an impairment parameter can be considered as constant over all the wavelength spectrum of interest or not. Also in this case a detailed impairment evaluation might lead to consider the exact value while an approximation IV might take a constant value for all wavelengths. In this information model, we consider both case: dependency / no dependency on a specific wavelength. This property appears directly in the information model definitions and related encoding.

- o Linearity

As impairments are representation of physical effects, there are some that have a linear behavior while other are non-linear. Linear approximation is in scope of Scenario C of [RFC6566]. During the impairment validation process, this property implies that the optical effect (or quantity) satisfies the superposition principle, thus a final result can be calculated by the sum of each component. The linearity implies the additivity of optical quantities considered during an impairment validation process. The non-linear effects in general does not satisfy this property. The information model presented in this document however, easily allow introduction of non-linear optical effects with a linear approximated contribution to the linear ones.

- o Multi-Channel

There are cases where a channel's impairments take different values depending on the aside wavelengths already in place, this

is mostly due to non-linear impairments. The result would be a dependency among different LSPs sharing the same path. This information model do not cosider this kind of property.

The following table summarize the above considerations where in the first column reports the list of properties to be considered for each optical parameter, while the second column states if this property is taken into account or not by this information model.

Property	Info Model Awareness
Time Dependency	no
Wavelength Dependency	yes
Linearity	yes
Multi-channel	no

Table 1: Optical Impairment Properties

3. ITU-T List of Optical Parameters

[EDITOR NOTE: To better integrate material coming from ITU WD06-31 October 2013 and future liasons]

As stated by [Section 2.2](#) this Information Model does not intend to be exhaustive and targets an approximate computational model although not precluding future evolutions towards more detailed impairments estimation methods.

On the same line, ITU SG15/Q6 provides a list of optitical parameters with following observations:

- (a) the problem of calculating the non-linear impairments in a multi-vendor environment is not solved. The transfer functions works only for the so called [[ITU.G680](#)] "Situation 1".
- (b) The generated list of parameters is not definitive or exhaustive.

In particular, [[ITU.G680](#)] contains many parameters that would be required to estimate linear impairments and [[ITU.G697](#)] contains information on which parameters can be monitored in an optical network.

[ITU.G671] contains some additional parameters defintions required by here above recomandation.

The list of optical parameters starts from [\[ITU.G680\]](#) [Section 9](#) which provides the optical computational models for the following:

- P1 OSNR. [Section 9.1](#)
- P2 Optical Power. As per [Section 9.1](#), required by Optical Computation Model for OSNR calculation.
- P3 Chromatic Dispersion (CD). [Section 9.2](#)
- P4 Polarization Mode Dispersion (PMD). [Section 9.3](#)
- P5 Polarization Dependent Loss (PDL). [Section 9.3](#)

In addition to the above, the following list of parameters has been mentioned by ITU SG15/Q6.

- P6 Channel Frequency Range [\[ITU.G671\]](#).
- P7 Ripple
- P8 Channel Signal-Spontaneous noise figure. This is considered within OSNR computational model above.
- P9 Differential Group Delay [\[ITU.G671\]](#). Required for PMD above.
- P10 Reflectance.
- P11 Isolation.
- P12 Channel extinction.
- P13 Non-Linear Coefficient (for a fibre segment). Needed for non-linear impairment

[4.](#) Background from WSON-RWA Information Model

In this section we report terms already defined for the WSON-RWA (impairment free) as in [\[I-D.ietf-ccamp-rwa-info\]](#) and [\[I-D.ietf-ccamp-general-constraint-encode\]](#). The purpose is to provide essential information that will be reused or extended for the impairment case.

In particular [\[I-D.ietf-ccamp-rwa-info\]](#) defines the connectivity matrix as the following:


```
ConnectivityMatrix ::= <MatrixID> <ConnType> <Matrix>
```

According to [[I-D.ietf-ccamp-general-constraint-encode](#)], this definition is further detailed as:

```
ConnectivityMatrix ::=  
    <MatrixID> <ConnType> ((<LinkSet> <LinkSet>) ...)
```

This second formula highlights how the connectivity matrix is built by pairs of LinkSet objects identifying the internal connectivity capability due to internal optical node constraint(s). It's essentially binary information and tell if a wavelength or a set of wavelengths can go from an input port to an output port.

As an additional note, connectivity matrix belongs to node information and is purely static. Dynamic information related to the actual usage of the connections is available through specific extension to link information.

Furthermore [[I-D.ietf-ccamp-rwa-info](#)] define the resource block as follow:

```
ResourceBlockInfo ::= <ResourceBlockSet> [<InputConstraints>]  
    [<ProcessingCapabilities>] [<OutputConstraints>]
```

Which is an efficient way to model constrains of a WSON node.

5. Optical Impairment Information Model

The idea behind this information model is to categorize the impairment parameters into three types and extend the information model already defined for impairment-free WSONs. The three categories are:

- o Node Information. The concept of connectivity matrix is reused and extended to introduce an impairment matrix, which represents the impairments suffered on the internal path between two ports. In addition, the concept of Resource Block is also reused and extended to provide an efficient modelization of per-port impairment.
- o Link Information representing impairment information related to a specific link or hop.

- o Path Information representing the impairment information related to the whole path.

All the above three categories will make use of a generic container, the Impairment Vector, to transport optical impairment information.

This information model however will allow however to add additional parameters beyond the one defined by [\[ITU.G680\]](#) in order to support additional computational models. This mechanism could eventually be applicable to both linear and non-linear parameters.

This information model makes the assumption that the each optical node in the network is able to provide the control plane protocols with its own parameter values however, no assumption is made on how the optical node gets those value information (e.g. internally computed, provisioned by a network management system, etc.). To this extent, the information model intentionally ignores all internal detailed parameters that are used by the formulas of the Optical Computational Model (i.e., "transfer function") and simply provides the object containers to carry results of the formulas.

[5.1.](#) The Optical Impairment Vector

Optical Impairment Vector (OIV) is defined as a list of optical parameters to be associated to a WSON node or a WSON link. It is defined as:

```
<OIV> ::= ([<LabelSet>] <OPTICAL_PARAM>) ...
```

The optional LabelSet object enables wavelength dependency property as per Table 1. LabelSet has its definition in [\[I-D.ietf-ccamp-general-constraint-encode\]](#).

OPTICAL_PARAM. This object represents an optical parameter. The Impairment vector can contain a set of parameters as identified by [\[ITU.G697\]](#) since those parameters match the terms of the linear impairments computational models provided by [\[ITU.G680\]](#). This information model does not speculate about the set of parameters (since defined elsewhere, e.g. ITU-T), however it does not preclude extensions by adding new parameters.

[5.2.](#) Node Information

5.2.1. Impairment Matrix

Impairment matrix describes a list of the optical parameters that applies to a network element as a whole or ingress/egress port pairs of a network element. Wavelength dependency property of optical parameters is also considered.

```
ImpairmentMatrix ::= <MatrixID> <ConnType>  
    ((<LinkSet> <LinkSet> <OIV>) ...)
```

Where:

MatrixID. This ID is a unique identifier for the matrix. It shall be unique in scope among connectivity matrices defined in [[I-D.ietf-ccamp-rwa-info](#)] and impairment matrices defined here.

ConnType. This number identifies the type of matrix and it shall be unique in scope with other values defined by impairment-free WSON documents.

LinkSet. Same object definition and usage as [[I-D.ietf-ccamp-general-constraint-encode](#)]. The pairs of LinkSet identify one or more internal node constrain.

OIV. The Optical Impairment Vector defined above.

The model can be represented as a multidimensional matrix shown in the following picture


```
[EDITOR NODE: first run of the information model does looks for
generality not for optimizing the quantity of information. We'll
deal with optimization in a further step.]
```


5.2.2. Impairment Resource Block Information

This information model reuse the definition of Resource Block Information adding the associated impairment vector.

```
ResourceBlockInfo ::= <ResourceBlockSet> [<InputConstraints>]  
    [<ProcessingCapabilities>] [<OutputConstraints>] [<OIV>]
```

The object ResourceBlockInfo is than used as specified within [\[I-D.ietf-ccamp-rwa-info\]](#).

5.3. Link Information

For the list of optical parameters associated to the link, the same approach used for the node-specific impairment information can be applied. The link-specific impairment information is extended from [\[I-D.ietf-ccamp-rwa-info\]](#) as the following:

```
<DynamicLinkInfo> ::= <LinkID> <AvailableLabels>  
    [<SharedBackupLabels>] [<OIV>]
```

DynamicLinkInfo is already defined in [\[I-D.ietf-ccamp-rwa-info\]](#) while OIV is the Optical Impairment Vector is defined in the previous section.

5.4. Path Information

There are cases where the optical impariments can only be described as a contrains on the overall end to end path. In such case, the optical impariment and/or parameter, cannot be derived (using a simple function) from the set of node / link contributions.

An equivalent case is the option reported by [\[RFC6566\]](#) on IV-Candidate paths where, the control plane knows a list of optically feasible paths so a new path setup can be selected among that list. Independent from the protocols and functions combination (i.e. RWA vs. Routing vs. PCE), the IV-Candidates imply a path property stating that a path is optically feasible.

```
<PathInfo> ::= <OIV>
```


[EDITOR NOTE: section to be completed, especially to evaluate protocol implications. Likely resemble to RSVP ADSPEC].

6. Encoding Considerations

Details about encoding will be defined in a separate document [[I-D.martinelli-ccamp-wson-iv-encode](#)] however worth remembering that, within [[ITU.G697](#)] Appending V, ITU already provides a guideline for encoding some optical parameters.

In particular [[ITU.G697](#)] indicates that each parameter shall be represented by a 32 bit floating point number.

Values for optical parameters are provided by optical node and it could provide by direct measurement or from some internal computation starting from indirect measurement. In such cases could be useful to understand the variance associated with the value of the optical parameter hence, the encoding shall provide the possibility to include a variance as well.

This kind of information will enable IA-RWA process to make some additional considerations on wavelength feasibility. [[RFC6566](#)] [Section 4.1.3](#) reports some considerations regarding this degree of confidence during the impairment validation process.

7. Control Plane Architectures

This section briefly describes how the definitions contained in this information model will match the architectural options described by [[RFC6566](#)].

The first assumption is that the WSON GMPLS extensions are available and operational. To such extent, the WSON-RWA will provide the following information through its path computation (and RWA process):

- o The wavelengths connectivity, considering also the connectivity constraints limited by reconfigurable optics, and wavelengths availability.
- o The interface compatibility at the physical level.
- o The Optical-Electro-Optical (OEO) availability within the network (and related physical interface compatibility). As already stated by the framework this information it's very important for impairment validation:
 - A. If the IV functions fail (path optically infeasible), the path computation function may use an available OEO point to find a

feasible path. In normally operated networks OEO are mainly used to support optically unfeasible path than mere wavelength conversion.

- B. The OEO points reset the optical impairment information since a new light is generated.

7.1. IV-Centralized

Centralized IV process is performed by a single entity (e.g., a PCE). Given sufficient impairment information, it can either be used to provide a list of paths between two nodes, which are valid in terms of optical impairments. Alternatively, it can help validate whether a particular selected path and wavelength is feasible or not. This requires distribution of impairment information to the entity performing the IV process.

[EDITOR NOTE: to be completed]

7.2. IV-Distributed

For the distributed IV process, common computational models are needed together with the information model defined in this document. Computational models for the optical impairments are defined by ITU standard body. The currently available computation models are reported in [[ITU.G680](#)] and only cover the linear impairment case. This does not require the distribution of impairment information since they can be collected hop-by-hop using a control plane signaling protocol.

[EDITOR NOTE: to be completed]

8. Acknowledgements

Authors would like to thank ITU SG15/Q6 and in particular Pete Anslow for providing text and information to CCAMP through joint meetings and liaisons.

9. Contributing Authors

This document was the collective work of several authors. The text and content of this document was contributed by the editors and the co-authors listed below (the contact information for the editors appears in appropriate section and is not repeated below):

Moustafa Kattan
Cisco
DUBAI, 500321
UNITED ARAB EMIRATES

Email: mkattan@cisco.com

Young Lee
Huawei
1700 Alma Drive, Suite 100
Plano, TX 75075
USA

Phone: +1 972 509 5599 x2240
Fax: +1 469 229 5397
Email: ylee@huawei.com

Greg M. Bernstein
Grotto Networking
Fremont, CA
USA

Phone: +1 510 573 2237
Email: gregb@grotto-networking.com

Fatai Zhang
Huawei
F3-5-B R&D Center, Huawei Base
Bantian, Longgang District
P.R. China

Phone: +86-755-28972912
Email: zhangfatai@huawei.com

Federico Pederzolli
CREATE-NET
via alla Cascata 56/D, Povo
Trento 38123
Italy

Email: federico.pederzolli@create-net.org

10. IANA Considerations

This document does not contain any IANA requirement.

11. Security Considerations

This document defines an information model for impairments in optical networks. If such a model is put into use within a network it will by its nature contain details of the physical characteristics of an optical network. Such information would need to be protected from intentional or unintentional disclosure.

12. References

12.1. Normative References

[ITU.G671]

International Telecommunications Union, "Transmission characteristics of optical components and subsystems", ITU-T Recommendation G.671, February 2012.

[ITU.G680]

International Telecommunications Union, "Physical transfer functions of optical network elements", ITU-T Recommendation G.680, July 2007.

[ITU.G697]

International Telecommunications Union, "Optical monitoring for dense wavelength division multiplexing systems", ITU-T Recommendation G.697, February 2012.

12.2. Informative References

[I-D.ietf-ccamp-general-constraint-encode]

Bernstein, G., Lee, Y., Li, D., and W. Imajuku, "General Network Element Constraint Encoding for GMPLS Controlled Networks", [draft-ietf-ccamp-general-constraint-encode-13](#) (work in progress), November 2013.

[I-D.ietf-ccamp-rwa-info]

Lee, Y., Bernstein, G., Li, D., and W. Imajuku, "Routing and Wavelength Assignment Information Model for Wavelength Switched Optical Networks", [draft-ietf-ccamp-rwa-info-19](#) (work in progress), November 2013.

[I-D.martinelli-ccamp-wson-iv-encode]

Martinelli, G., Zanardi, A., Zhang, X., Galimberti, G., and D. Siracusa, "Information Encoding for WSON with Impairments Validation", [draft-martinelli-ccamp-wson-iv-encode-02](#) (work in progress), July 2013.

[RFC6163] Lee, Y., Bernstein, G., and W. Imajuku, "Framework for GMPLS and Path Computation Element (PCE) Control of Wavelength Switched Optical Networks (WSONs)", [RFC 6163](#), April 2011.

[RFC6566] Lee, Y., Bernstein, G., Li, D., and G. Martinelli, "A Framework for the Control of Wavelength Switched Optical Networks (WSONs) with Impairments", [RFC 6566](#), March 2012.

Appendix A. ITU-T Liason Tracking

[EDITOR NOTE: appendix reserved to track liason to/from ITU related to this draft]

Authors' Addresses

Giovanni Martinelli (editor)
Cisco
via Philips 12
Monza 20900
Italy

Phone: +39 039 2092044
Email: giomarti@cisco.com

Xian Zhang (editor)
Huawei Technologies
F3-5-B R&D Center, Huawei Base
Bantian, Longgang District
Shenzen 518129
P.R. China

Phone: +86 755 28972465
Email: zhang.xian@huawei.com

Gabriele M. Galimberti

Cisco

Via Philips,12

Monza 20900

Italy

Phone: +39 039 2091462

Email: ggalimbe@cisco.com

Andrea Zanardi

CREATE-NET

via alla Cascata 56/D, Povo

Trento 38123

Italy

Email: andrea.zanardi@create-net.org

Domenico Siracusa

CREATE-NET

via alla Cascata 56/D, Povo

Trento 38123

Italy

Email: domenico.siracusa@create-net.org

