

Network Working Group

L.

Masinter

Internet-Draft

Adobe

Obsoletes: [2388](#) (if approved)

September 20,

2013

Intended status: Standards Track

Expires: March 22, 2014

**Returning Values from Forms: multipart/form-data  
draft-masinter-multipart-form-data-02**

Abstract

This specification defines an Internet Media Type, multipart/form-data, which can be used by a wide variety of applications and transported by a wide variety of protocols as a way of returning a set of values as the result of a user filling out a form. It replaces [RFC 2388](#).

NOTE

The Currently, XML source for this Internet Draft may be found in [1], as well as an issue tracker.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months

and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on March 22, 2014.

Copyright Notice

Masinter  
1]

Expires March 22, 2014

[Page

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document.

Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1.](#) Introduction . . . . . 2
- [2.](#) Definition of multipart/form-data . . . . . 3
  - [2.1.](#) Boundary . . . . . 3
  - [2.2.](#) filename attribute . . . . . 3
  - [2.3.](#) Multiple files for one form field . . . . . 4
  - [2.4.](#) Content-Type . . . . . 4
  - [2.5.](#) The charset parameter . . . . . 4
  - [2.6.](#) The `_charset_` field . . . . . 4
  - [2.7.](#) Content-Transfer-Encoding . . . . . 4
  - [2.8.](#) Other Content- headers . . . . . 5
- [3.](#) Operability considerations . . . . . 5
  - [3.1.](#) Non-ASCII field names and values . . . . . 5
    - [3.1.1.](#) Avoid creating forms with non-ASCII field names . . . 5
    - [3.1.2.](#) Ampersand hash encoding . . . . . 5
    - [3.1.3.](#) Interpreting forms and creating form-data . . . . . 5
    - [3.1.4.](#) Parsing and interpreting form data . . . . . 6
  - [3.2.](#) Ordered fields and duplicated field names . . . . . 6
  - [3.3.](#) Interoperability with web applications . . . . . 6

<a href="#">3.4.</a>	Correlating form data with the original form . . . . .	7
<a href="#">4.</a>	Security Considerations . . . . .	7
<a href="#">5.</a>	Media type registration for multipart/form-data . . . . .	7
<a href="#">6.</a>	References . . . . .	8
<a href="#">6.1.</a>	Normative References . . . . .	8
<a href="#">6.2.</a>	Informative References . . . . .	8
<a href="#">Appendix A.</a>	Changes from <a href="#">RFC 2388</a> . . . . .	9
<a href="#">Appendix B.</a>	Alternatives . . . . .	9
	Author's Address . . . . .	9

**[1.](#) Introduction**

In many applications, it is possible for a user to be presented with a form. The user will fill out the form, including information that is typed, generated by user input, or included from files that the user has selected. When the form is filled out, the data from the form is sent from the user to the receiving application.

The definition of multipart/form-data is derived from one of those applications, originally set out in [[RFC1867](#)] and subsequently incorporated into [[HTML3.2](#)] and [[HTML4](#)], where forms are expressed in HTML, and in which the form values are sent via HTTP or electronic mail. This representation is widely implemented in numerous web browsers and web servers.

However, multipart/form-data can be used for forms that are presented using representations other than HTML (spreadsheets, Portable Document Format, etc), and for transport using other means than electronic mail or HTTP. This document defines the representation of form values independently of the application for which it is used.

## **2. Definition of multipart/form-data**

The media-type multipart/form-data generally follows the model of multipart MIME data streams as described in [[RFC2046](#)] [Section 5.1](#).

In forms, there are a series of fields to be supplied by the user who fills out the form. Each field has a name. Within a given form, the names SHOULD be unique. After a form has been "filled out" and "submitted" (processes defined by the form), the result is a set of values for each field, the form-data.

"multipart/form-data" contains a series of parts. Each part MUST contain a Content-Disposition header [[RFC2183](#)] where the disposition type is "form-data", and where the disposition contains an (additional) parameter of "name"; the value of the parameter is the original field name in the form. For example, a part might contain a header:

```
Content-Disposition: form-data; name="user"
```

with the value corresponding to the entry of the "user" field.

### **2.1. Boundary**

As with other multipart types, the parts are delimited with a boundary, selected such that it does not occur in any of the data. Each field of the form is sent, in the order defined by the sending application and form, as a part of the multipart stream. The boundary is supplied as a "boundary" parameter to the multipart/form-data type, e.g.,

```
multipart/form-data;boundary="-AaB03x"
```

## 2.2. filename attribute

Masinter  
3]

Expires March 22, 2014

[Page

For form data that represents the content of a local file, a name for the file SHOULD be supplied as well, by using a "filename" parameter of the Content-Distribution header. (The SHOULD is to allow file uploads that result from drag-and-drop in systems where the file name is meaningless, private, where the uploaded 'file' is streamed directly from a device, where the file name is not user visible and thus would be unrecognized). For compatibility with other multipart types, the value of the filename parameter MUST be restricted to US-ASCII. File names normally visible to users which contain non-ASCII characters SHOULD be encoded using the `&#nn` method described in [Section 3.1.2](#).

### **2.3. Multiple files for one form field**

If the value of a form field is a set of files rather than a single file, that value MUST be transmitted by supplying each in a separate part, but all with the same "name" parameter.

### **2.4. Content-Type**

Each part has an (optional) "Content-Type", which defaults to "text/plain". If the contents of a file are to be sent, the file data is labeled with an appropriate media type, if known, or "application/octet-stream".

### **2.5. The charset parameter**

In the case where a field value is text the charset parameter for the Content-Type: text/plain may be used to indicate the character encoding used in that part. For example, a form with a text field in which a user typed 'Joe owes `<eu>100`' where `<eu>` is the Euro symbol might have form data returned as:

```
--AaB03x
content-disposition: form-data; name="field1"
content-type: text/plain;charset=windows-1250
content-transfer-encoding: quoted-printable
```

```
Joe owes =80100.
--AaB03x
```

### **2.6. The `_charset_` field**

Forms have the convention that the value of a form entry with entry name "`_charset_`" and type "hidden" is automatically set to the name of the form-charset. In this case, the value of the default charset of each text/plain part without a charset parameter is the supplied value.

Masinter  
4]

Expires March 22, 2014

[Page



## **2.7. Content-Transfer-Encoding**

When used in transports which do not allow arbitrary binary data, each part that cannot be represented within the transport SHOULD be encoded and the "content-transfer-encoding" header supplied in that part. For example, some email transports use a 7BIT encoding. [See [section 5 of \[RFC2046\]](#) for more details.] (When transferred via HTTP, Content-Transfer-Encoding the form-data values SHOULD NOT be used.)

## **2.8. Other Content- headers**

The multipart/form-data media type does not support any MIME headers in the parts other than Content-Type, Content-Disposition, and (when appropriate), Content-Transfer-Encoding.

## **3. Operability considerations**

### **3.1. Non-ASCII field names and values**

MIME headers in multipart/form-data are required to consist only of 7-bit data in the US-ASCII character set. While [[RFC2388](#)] suggested that non-ASCII field names should be encoded according to the method in [[RFC2047](#)] if they contain characters outside of US-ASCII, practice varies.

This specification makes three recommendations for three different states of workflow.

#### **3.1.1. Avoid creating forms with non-ASCII field names**

For broadest interoperability with existing deployed software, those creating forms SHOULD avoid non-ASCII field names. This should not be a burden, because in general the field names are not visible to users.

#### **3.1.2. Ampersand hash encoding**

multipart/form-data uses an encoding for characters that are not allowed in a context using an encoding which replace the character by

a string consisting of an ampersand character (&), a "#" character, one or more ASCII digits representing the Unicode code point of the character in base ten, and finally a semicolon character (;).

#### **3.1.3. Interpreting forms and creating form-data**

Some applications of this specification will supply a character encoding to be used for creation of the multipart/form-data result. In particular, [[HTML5](#)] uses

o the value of an accept-charset attribute of the <form> element,

if

there is one,

- o the character encoding of the document containing the form, if it is US-ASCII compatible,

Masinter  
5]

Expires March 22, 2014

[Page

- o otherwise UTF-8.

Call this the form-charset. Any field name or file name which is not

in US-ASCII must be encoded using the `&#nn;` encoding in [Section 3.1.2](#)

multipart/form-data parts which do not have a Content-Type header and

which are not the result of supplying a local file MUST be transformed by the same algorithm.

#### [3.1.4.](#) Parsing and interpreting form data

While this specification provides guidance for creation of multipart/

form-data, interpreters of multipart/form-data should be aware of the

variety of implementations. Currently, deployed browsers differ as to how they encode multipart/form-data. For this reason the matching

of form elements to form-data parts may rely on a fuzzier match. In particular, some form-data generators might have followed the advice of [\[RFC2388\]](#) and used the [\[RFC2047\]](#) "encoded-word" method of encoding

non-ASCII values:

```
encoded-word = "=?" charset "?" encoding "?" encoded-text "=?"
```

Others have been known to follow [\[RFC2231\]](#) or to send unencoded UTF-8

or even unencoded strings in the form-charset.

Generally, interpreting multipart/form-data, even from conforming generators, may require knowing the charset used in form encoding, in

cases where the `_charset_` field value or a charset parameter of a text/plain Content-Type header is not supplied.

#### [3.2.](#) Ordered fields and duplicated field names

Form processors given forms with a well-defined ordering SHOULD send back results in the order received and preserve duplicate field names, in order. Intermediaries MUST NOT reorder the results. (Note that there are some forms which do not define a natural order of appearance.)

#### [3.3.](#) Interoperability with web applications

Many web applications use the "application/x-url-encoded" method for returning data from forms. This format is quite compact, e.g.:

name=Xavier+Xantico&verdict=Yes&colour=Blue&happy=sad&Utf%F6r=Send

However, there is no opportunity to label the enclosed data with content type, apply a charset, or use other encoding mechanisms.

Many form-interpreting programs (primarily web browsers) now implement and generate multipart/form-data, but an existing application might need to optionally support both the application/x-url-encoded format as well.

### **3.4. Correlating form data with the original form**

This specification provides no specific mechanism by which multipart/form-data can be associated with the form that caused it to be transmitted. This separation is intentional; many different forms might be used for transmitting the same data. In practice, applications may supply a specific form processing resource (in HTML, the ACTION attribute in a FORM tag) for each different form. Alternatively, data about the form might be encoded in a "hidden field" (a field which is part of the form but which has a fixed value to be transmitted back to the form-data processor.)

## **4. Security Considerations**

It is important when interpreting the filename of the Content-Disposition header to not overwrite files in the recipients address space inadvertently.

User applications that request form information from users must be careful not to cause a user to send information to the requestor or a third party unwillingly or unwittingly. For example, a form might request 'spam' information to be sent to an unintended third party, or private information to be sent to someone that the user might not actually intend. While this is primarily an issue for the representation and interpretation of forms themselves, rather than the data representation of the result of form transmission, the transportation of private information must be done in a way that does not expose it to unwanted prying.

With the introduction of form-data that can reasonably send back the content of files from user's file space, the possibility that a user might be sent an automated script that fills out a form and then sends the user's local file to another address arises. Thus, additional caution is required when executing automated scripting where form-data might include user's files.

## **5. Media type registration for multipart/form-data**

Media Type name: multipart

Media subtype name: form-data

Required parameters: boundary

Optional parameters: none

Encoding considerations: multipart/form-data is frequently used to

send arbitrary binary data. For use in transports that restrict the encoding to 7BIT or 8BIT, each part is encoded separately.

Masinter  
7]

Expires March 22, 2014

[Page

Security Considerations Applications which receive forms and process them must be careful not to supply data back to the requesting form processing site that was not intended to be sent by the recipient. This is a consideration for any application that generates a multipart/form-data. See [Section 4](#) of this document.

## **6. References**

### **6.1. Normative References**

- [RFC1806] Troost, R. and S. Dorner, "Communicating Presentation Information in Internet Messages: The Content-Disposition Header", [RFC 1806](#), June 1995.
- [RFC1867] Nebel, E. and L. Masinter, "Form-based File Upload in HTML", [RFC 1867](#), November 1995.
- [RFC2046] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", [RFC 2046](#), November 1996.
- [RFC2047] Moore, K., "MIME (Multipurpose Internet Mail Extensions) Part Three: Message Header Extensions for Non-ASCII Text", [RFC 2047](#), November 1996.
- [RFC2183] Troost, R., Dorner, S. and K. Moore, "Communicating Presentation Information in Internet Messages: The Content-Disposition Header Field", [RFC 2183](#), August 1997.
- [RFC2184] Freed, N. and K. Moore, "MIME Parameter Value and Encoded Word Extensions: Character Sets, Languages, and Continuations", [RFC 2184](#), August 1997.
- [RFC2231] Freed, N. and K. Moore, "MIME Parameter Value and Encoded Word Extensions: Character Sets, Languages, and Continuations", [RFC 2231](#), November 1997.

### **6.2. Informative References**

- [HTML3.2] Raggett, D., "HTML 3.2 Reference Specification", World Wide Web Consortium Recommendation REC-html32-19970114, January 1997, <<http://www.w3.org/TR/REC-html32-19970114>>.
- [HTML4] Raggett, D., Hors, A. and I. Jacobs, "HTML 4.0 Recommendation", World Wide Web Consortium REC-html40-971218, December 1997, <<http://www.w3.org/TR/REC-html40-971218>>.
- [HTML5] Berjon, R., Faulkner, S., Leithead, T., Navara, E., O'Connor, E. and S. Pfeiffer, "HTML5", September 2013, <<http://www.w3.org/html/wg/drafts/html/CR/>>.

Masinter  
8]

Expires March 22, 2014

[Page



[RFC2388] Masinter, L., "Returning Values from Forms: multipart/form-data", [RFC 2388](#), August 1998.

#### **Appendix A. Changes from [RFC 2388](#)**

Now, multiple files submitted as part of a single <input type=file multiple> element will result in each file having its own field; the "sets of files" feature ("multipart/mixed") in 2388 is not used.

The `_charset_` convention and use of an explicit encoding charset is documented.

Explicit advice about non-ASCII field names is given, the use of [RFC 2047](#) is deprecated (not used for encoding, but form interpreters should be aware.).

The relationship of the ordering of fields within a form and the ordering of returned values within "multipart/form-data" was not defined before, nor was the handling of the case where a form has multiple fields with the same name.

More prescriptive about order and duplicates.

Remove obsolete discussion of alternatives.

#### **Appendix B. Alternatives**

There are numerous alternative ways in which form data can be encoded; many are listed in [[RFC2388](#)] under "Other data encodings rather than multipart". The multipart/form-data encoding has a high overhead and performance impact if there are many fields with short values. However, in practice, for the forms in use, for example, in HTML, the average overhead is not significant.

#### Author's Address

Larry Masinter  
Adobe

Email: [masinter@adobe.com](mailto:masinter@adobe.com)

URI: <http://larry.masinter.net>

Masinter  
9]

Expires March 22, 2014

[Page