Internet Engineering Task Force Internet-Draft Intended status: Standards Track Expires: January 21, 2016 J. Mauch J. Snijders NTT July 20, 2015

Require BGP implementers to advertise no routes draft-mauch-bgp-reject-00.txt

Abstract

This document describes a solution to a common routing security problem inherent in vendors with their security practices.

Foreword

A placeholder to list general observations about this document.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in <u>RFC 2119</u> [<u>1</u>].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>http://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 21, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to $\frac{\text{BCP }78}{\text{Provisions}}$ and the IETF Trust's Legal Provisions Relating to IETF Documents

Mauch & Snijders Expires January 21, 2016

[Page 1]

(<u>http://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

| <u>1</u> . | Introduction | 2 |
|------------|------------------------------------|----------|
| <u>2</u> . | Definitions and Accronyms | <u>3</u> |
| <u>3</u> . | Solution Requirements | <u>3</u> |
| <u>4</u> . | Acknowledgements | <u>3</u> |
| <u>5</u> . | Security Considerations | <u>3</u> |
| <u>6</u> . | References | <u>3</u> |
| <u>6</u> | <u>.1</u> . Normative References | <u>3</u> |
| <u>6</u> | <u>.2</u> . Informative References | <u>4</u> |
| Aut | hors' Addresses | <u>4</u> |

1. Introduction

BGP speaking devices have many default settings which need to be revisited as part of improving the routing ecosystem. There is a need to provide guidace to BGP implementors for the default behaviors of a well functioning internet ecosystem. Routing leaks [3] are part of the problem, but software defects and operator misconfigurations are just a few of the attacks on internet stability we aim to address.

Usually BGP speaking devices accept all routes from a configured peer or neighbor. This practice dates back to the early days of internet protocols in being very permissive in offering routing information to allow all networks to reach each other. With the core of the internet becoming more densely interconnected the risk of a misbehaving edge device or BGP speaking customer poses significant risks to the reachability of critical services.

This proposal intends to solve this situation with the requiring the explicity configuration of BGP policy for any non-iBGP speaking session such as customers, peers or confederation boundaries. When this solution is implemented, devices will no longer pass routes without explicit policy.

2. Definitions and Accronyms

o BGP: Border Gateway Protocol [2]

3. Solution Requirements

The following requirements apply to the solution described in this document:

- o Software MUST NOT accept routes from an eBGP peer without an operator configuring a policy
- o Software MUST NOT require a configuration directive to operate in this mode.
- o Software MUST NOT send routes to an eBGP peer without an operator configuring a policy
- o Software MUST provide protection from internal failures preventing the advertisement and acceptance of routes
- o Software MAY provide a configuration option to disable this security capability.

4. Acknowledgements

The authors would like to thank the following people for their comments and support: [TBD].

<u>5</u>. Security Considerations

This document addresses the basic security posture of a BGP speaking device within a network. Operators have a need for implementors to address the problem through a behavior change to mitigate against possible attacks from a permissive security posture. Attacks and inadvertent advertisements cause business impact necessitating this default behavior.

<u>6</u>. References

6.1. Normative References

- [1] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, March 1997.
- [2] Rekhter, Y., Li, T., and S. Hares, "A Border Gateway Protocol 4 (BGP-4)", <u>RFC 4271</u>, January 2006.

<u>6.2</u>. Informative References

Authors' Addresses

Jared Mauch NTT Communications, Inc. 8285 Reese Lane Ann Arbor Michigan 48103 US

Email: jmauch@us.ntt.net

Job Snijders NTT Communications, Inc. Amsterdam NL

Email: job@ntt.net