

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: November 5, 2016

A. Melnikov  
Isode Ltd  
May 4, 2016

**Message Authorizing Email Header Field and its use for Draft & Release  
draft-melnikov-mmhs-authorizing-users-14**

**Abstract**

This document describes a procedure for when an Military Message Handling System (MMHS) message is composed by one user and is only released to the mail transfer system when one or more authorizing users authorize release of the message by adding the MMHS-Authorizing-Users header field. The resulting message can be optionally signed by the sender and/or reviewer, allowing recipients to verify both the original signature (if any) and review signatures.

**Status of This Memo**

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 5, 2016.

**Copyright Notice**

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Conventions Used in This Document . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Draft and Release procedure . . . . .	<a href="#">3</a>
<a href="#">3.1.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">3.2.</a>	Handling of Initial Message Submission by MSA . . . . .	<a href="#">3</a>
<a href="#">3.3.</a>	Review by Authorizing User(s) . . . . .	<a href="#">4</a>
<a href="#">3.3.1.</a>	Processing of Encrypted Messages . . . . .	<a href="#">5</a>
<a href="#">3.3.2.</a>	Authorizing S/MIME signatures . . . . .	<a href="#">5</a>
<a href="#">3.4.</a>	Role of other Messaging Agents at the sender's domain . . . . .	<a href="#">6</a>
<a href="#">3.4.1.</a>	MDA at the sender's domain . . . . .	<a href="#">6</a>
<a href="#">3.4.2.</a>	Border MTA at the sender's domain . . . . .	<a href="#">6</a>
<a href="#">4.</a>	MMHS-Authorizing-Users header field . . . . .	<a href="#">6</a>
<a href="#">5.</a>	Updated MIXER mapping . . . . .	<a href="#">7</a>
<a href="#">5.1.</a>	Mapping from <a href="#">RFC 5322</a> /MIME to X.400 . . . . .	<a href="#">7</a>
<a href="#">5.2.</a>	Mapping from X.400 to <a href="#">RFC 5322</a> /MIME . . . . .	<a href="#">7</a>
<a href="#">6.</a>	IANA Considerations . . . . .	<a href="#">8</a>
<a href="#">7.</a>	Security Considerations . . . . .	<a href="#">8</a>
<a href="#">7.1.</a>	Forged Header Fields . . . . .	<a href="#">8</a>
<a href="#">7.2.</a>	Intentionally Malformed Header Fields . . . . .	<a href="#">9</a>
<a href="#">8.</a>	References . . . . .	<a href="#">9</a>
<a href="#">8.1.</a>	Normative References . . . . .	<a href="#">9</a>
<a href="#">8.2.</a>	Informative References . . . . .	<a href="#">10</a>
<a href="#">Appendix A.</a>	Acknowledgements . . . . .	<a href="#">11</a>
	Author's Address . . . . .	<a href="#">11</a>

## [1.](#) Introduction

In some secure environments email messages can't be released to the MTS (Message Transfer System) and, thus delivered to recipients, unless they are authorized by one or more authorizing users (e.g. Releasing Officers or Release Authorities). This document describes how this mechanism can be realized by an additional Internet Email [[RFC5322](#)] header field and optionally protected using S/MIME [[RFC5750](#)] [[RFC5751](#)] or DKIM [[RFC6376](#)].

This document describes a procedure for how an email message composed by one user can be released to the MTS when one or more authorizing users authorize and optionally countersign the message. The MMHS-Authorizing-Users header field (see [Section 4](#)) communicates which user(s) authorized the message. If S/MIME signed, the resulting message allows recipients to verify both the original (if any) and counter signatures. The original S/MIME signature generated by the sender (if any) is unaffected by additional S/MIME review signatures.

Melnikov

Expires November 5, 2016

[Page 2]

## **2. Conventions Used in This Document**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#).

The formal syntax uses the Augmented Backus-Naur Form (ABNF) [\[RFC5234\]](#) notation including the core rules defined in [Appendix B of RFC 5234](#) [\[RFC5234\]](#). Terms not defined in this document are taken from [\[RFC5322\]](#).

## **3. Draft and Release procedure**

### **3.1. Terminology**

**Drafter:** Any email user that composes a message (Draft Message) needing authorisation before it is released to its intended recipients.

**Authorizing User (also Releaser or Authorizer):** The mailbox of a user or a group of users that must inspect and authorise the release of Draft Message before it can be sent. An organization may require more than one Authorizing User to authorize release of a Draft Message.

### **3.2. Handling of Initial Message Submission by MSA**

The original email message to be sent doesn't include the MMHS-Authorizing-Users header field. It may or may not include sender's S/MIME signature.

The message to be sent is first submitted over SMTP [\[RFC6409\]](#). The specific mechanism for how it arrives to authorizing user(s) is not specified in this document. One possibility is for the Message Submission Agent (MSA) to redirect all email messages not addressed to authorizing users and not submitted by authorizing users to a preconfigured mailbox(es) that can be accessed by authorizing user(s). Another possibility is for the MSA to redirect all email messages without the MMHS-Authorizing-Users header field and/or corresponding S/MIME review signatures to a preconfigured mailbox(es) that can be accessed by authorizing user(s).

In order to prevent a malicious sender from bypassing or altering Draft and Release procedure, MSA MUST check that MMHS-Authorizing-Users header field (if present) is syntactically valid, contains email addresses of entities authorized to act as authorizing users and, when review signatures are used, that every entity listed has one or more matching review signature (or signature) which is valid.



### **3.3. Review by Authorizing User(s)**

Each user agent that is used by an authorized user MUST perform the following steps (if there are multiple authorizing users, the whole sequence of steps below is repeated for each authorizing user):

1. Verify the origination of the message (From/Sender header fields). The exact mechanism to do that is out of scope for this document, but one example is by verifying the S/MIME signature, making sure that the signature protects all header fields (i.e. wrapped by message/rfc822, as described in [Section 3.1 of \[RFC5751\]](#)) and that it matches the sender of the message, as described in [\[RFC5750\]](#). Another example is by verifying a DKIM signature [\[RFC6376\]](#) (added by Drafter's MUA or MSA) that covers From/Sender header fields.
2. Check if the message already contains the MMHS-Authorizing-Users header field with the email address of the authorizing user. (This can happen, for example, if email system is misconfigured and thus contains a loop, or if a malicious sender or attacker is trying to affect authorization procedure.) If the message doesn't contain the email address of the authorizing user in the MMHS-Authorizing-Users header field, then go to the next step. If MMHS-Authorizing-Users header field contains the email address of the authorizing user, verify validity of the header field (for example by checking for S/MIME signature/review signature or for DKIM signature) and also verify that the email address associated with the signature matches the email address of the authorizing user. If the validity of the MMHS-Authorizing-Users header field can be verified, go to step 5 below. Otherwise, return the message to sender (bounce) or redirect the message to a designated abuse mailbox.
3. Allow the authorizing user to review content of the message. Some of the checks can be automated (for example search for keywords). (See [Section 3.3.1](#) for additional considerations.) If based on the check the authorizing user is happy to release the message to MTS (or to the next authorizing user, if multiple authorizations are required), the UA SHOULD enable the authorizing user to protect additions to the MMHS-Authorizing-Users header field, for example by allowing to add S/MIME review signature (if S/MIME is used for protecting MMHS-Authorizing-Users header field. See [Section 3.3.2](#) for more details). If the authorizing user wants to reject the message, it SHOULD be returned to drafter with an explanatory note or MAY be discarded. The authorizing user can also choose to forward the message to another authorizing user for additional approval or become a new Drafter of the message. If the authorizing user becomes the new



Drafter, its UA MUST strip any existing email addresses from the MMHS-Authorizing-Users header field.

4. If there is an existing MMHS-Authorizing-Users header field containing the email address of the authorizing user, skip this step. Otherwise, insert a new MMHS-Authorizing-Users header field (if absent) containing the email address of the authorizing user or append the email address of the authorizing user to the end of the existing MMHS-Authorizing-Users header field.
5. The (possibly) updated email message is either released to the MTS, or to the next authorizing user, as per email system configuration. Note that if the authorizing user updates the message in a manner that invalidates existing S/MIME/DKIM signature(s), the authorizing user becomes the Drafter, and need to reapply any protections.

### **3.3.1. Processing of Encrypted Messages**

Any encrypted message sent in an environment where Draft and Release procedure is in force needs to be also encrypted to all authorizing users, so that they can perform review of the message. If a User Agent used by an authorizing user can't decrypt the message, it SHOULD notify the sender (which can be the drafter or a previous authorizing user) about the problem using a non delivery DSN or through some other means. The ciphertext that cannot be decrypted by the Authorizing User MAY be included in the notification to aid debugging. A possible reason not to notify the sender is in order to avoid Denial-of-Service attacks, for example if an attacker discovers a way to inject fake messages with encryption that doesn't validate in order to overflow sender's INBOX.

### **3.3.2. Authorizing S/MIME signatures**

If S/MIME were not used, the Authorizing User can become the original signer of the message.

If a message is signed with multiple signatures (for example using different cryptographic algorithms, as described in [[RFC5752](#)]), all of the signatures that can be verified by an authorizing user SHOULD be signed with a review signature (authorizing signatures). A recipient of the message can consider any chain of review signatures that matches MMHS-Authorizing-Users header field values as valid, only if all signatures in the chain verify. All of the signatures that cannot be verified MUST be stripped by the Authorizing User Agent.



When triple wrapping [[RFC2634](#)] is used, authorizing signatures are applied to the outer level, so that it can be verified by MTAs without the need to decrypt content.

### **[3.4.](#) Role of other Messaging Agents at the sender's domain**

#### **[3.4.1.](#) MDA at the sender's domain**

If a message being sent is to be delivered within the sender's domain, Message Delivery Agents (MDAs) are responsible for ensuring that the message was properly authorized by authorizing user(s), as determined by the sender's domain email system configuration. They verify presence and validity of MMHS-Authenticating-Users header field in the message, as well as validity of associated signatures on the message.

Note that the above requirements don't apply to direct delivery to any user designated as an Authorizing User.

#### **[3.4.2.](#) Border MTA at the sender's domain**

Sender's domain border MTAs are responsible for ensuring that all messages that leave sender's domain were properly authorized by authorizing user(s), as determined by the sender's domain email system configuration. They verify presence and validity of MMHS-Authenticating-Users header field in outgoing messages, as well as validity of associated signatures on the message.

## **[4.](#) MMHS-Authenticating-Users header field**

The MMHS-Authenticating-Users header field specifies the list of authorizing users (or entities(\*)) that countersigned this email message (for example using S/MIME) before it was authorized for release to MTS. Each user/entity is described by her/his/its email address.

(\*) Note that in some environments identities of authorizing users are required to be hidden from recipients of email messages, so upon receipt MMHS-Authenticating-Users might contain an email address associated with a group of possible users. Such email addresses need to have signatures that don't disclose group membership.

The MMHS-Authenticating-Users header field specified in this document MUST NOT appear more than once in message headers. (An email message that contains multiple MMHS-Authenticating-Users is malformed. An agent processing such malformed message SHOULD either return it to sender (if possible) or fix the message so that it only contains one copy of the header field.)



```
MMHS-Authorizing-Users = "MMHS-Authorizing-Users:"  
                        mailbox-list CRLF
```

```
mailbox-list = <Defined in RFC 5322>
```

## 5. Updated MIXER mapping

This section provides an updated version of the MIXER mapping specified in [[RFC2156](#)] for MMHS applications.

### 5.1. Mapping from [RFC 5322](#)/MIME to X.400

In the absence of the MMHS-Authorizing-Users header field, From and Sender header fields are mapped to their X.400 equivalents as specified in [[RFC2156](#)].

If MMHS-Authorizing-Users header field is present:

1. If the Sender header field is present, it is mapped to IPMS Heading.originator, otherwise the first From header field address is mapped to IPMS Heading.originator.
2. Map the From header field address(es) and the MMHS-Authorizing-Users header field address(es) to IPMS Heading.authorizing-users, skipping the first From header field address if it was mapped to IPMS Heading.originator.

### 5.2. Mapping from X.400 to [RFC 5322](#)/MIME

Mapping from X.400 to Internet is controlled by whether or not a particular message is considered to be a military message. A message is considered to be a military message (as defined by ACP 123 [[ACP123](#)] and also specified in STANAG 4406 [[STANAG-4406](#)]) if there are any MMHS heading extensions present. Alternatively, this MAY be done by configuration (i.e. all messages can be considered to be military messages).

For non military messages, mapping from X.400 as specified in [[RFC2156](#)] is used.

For military messages, the following mapping is used:

1. IPMS Heading.originator is mapped to From header field.
2. The IPMS Heading.authorizing-users is mapped to MMHS-Authorizing-Users header field.



## **6. IANA Considerations**

IANA is requested to add the MMHS-Authorizing-Users header field specified in [Section 4](#) to the "Provisional Message Header Field Names", defined by Registration Procedures for Message Header Fields [[RFC3864](#)]. The registration template is as follows:

Header field name: MMHS-Authorizing-Users

Applicable protocol: mail ([[RFC5322](#)])

Status: provisional

Author/Change controller: Alexey Melnikov <[alexey.melnikov@isode.com](mailto:alexey.melnikov@isode.com)>

Specification document(s): [[RFC XXXX]]

Related information:

## **7. Security Considerations**

In some military environments, the identities of authorizing users are required to be hidden from recipients of email messages. This can be accomplished by using a group address for the MMHS-Authorizing-Users. In this way, the recipient will know that it was released by an Authorizing User in that group, but the recipient will not know which one of them took the action.

For those organizations that wish to not disclose authorizing users' group membership, care must also be taken to ensure the information included in the certificate used for signing email messages does not disclose individuals in the group.

Further security considerations are described in subsections of this section.

### **7.1. Forged Header Fields**

A malicious sender may add/change an MMHS-Authorizing-Users header field to bypass or alter the message authorization procedure invoked for messages with no MMHS-Authorizing-Users header field. For that reason it is important for agents and clients that rely on the validity of the MMHS-Authorizing-Users header field to also verify the review signature (or a similar protection mechanism), that confirms that a particular person or entity authorized release of a message.



## **7.2. Intentionally Malformed Header Fields**

It is possible for an attacker to add an MMHS-Authorizing-Users header field that is extraordinarily large or otherwise malformed in an attempt to discover or exploit weaknesses in header field parsing code. Implementations MUST thoroughly verify all such header fields received from MTAs and be robust against intentionally as well as unintentionally malformed header fields.

## **8. References**

### **8.1. Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2156] Kille, S., "MIXER (Mime Internet X.400 Enhanced Relay): Mapping between X.400 and [RFC 822](#)/MIME", [RFC 2156](#), DOI 10.17487/RFC2156, January 1998, <<http://www.rfc-editor.org/info/rfc2156>>.
- [RFC5322] Resnick, P., Ed., "Internet Message Format", [RFC 5322](#), DOI 10.17487/RFC5322, October 2008, <<http://www.rfc-editor.org/info/rfc5322>>.
- [RFC6409] Gellens, R. and J. Klensin, "Message Submission for Mail", STD 72, [RFC 6409](#), DOI 10.17487/RFC6409, November 2011, <<http://www.rfc-editor.org/info/rfc6409>>.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), DOI 10.17487/RFC5234, January 2008, <<http://www.rfc-editor.org/info/rfc5234>>.
- [RFC2634] Hoffman, P., Ed., "Enhanced Security Services for S/MIME", [RFC 2634](#), DOI 10.17487/RFC2634, June 1999, <<http://www.rfc-editor.org/info/rfc2634>>.
- [RFC5750] Ramsdell, B. and S. Turner, "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 3.2 Certificate Handling", [RFC 5750](#), DOI 10.17487/RFC5750, January 2010, <<http://www.rfc-editor.org/info/rfc5750>>.



- [RFC5751] Ramsdell, B. and S. Turner, "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 3.2 Message Specification", [RFC 5751](#), DOI 10.17487/RFC5751, January 2010, <<http://www.rfc-editor.org/info/rfc5751>>.
- [RFC6376] Crocker, D., Ed., Hansen, T., Ed., and M. Kucherawy, Ed., "DomainKeys Identified Mail (DKIM) Signatures", STD 76, [RFC 6376](#), DOI 10.17487/RFC6376, September 2011, <<http://www.rfc-editor.org/info/rfc6376>>.
- [ACP123] "Common Messaging strategy and procedures", ACP 123(B), May 2009.

## **8.2. Informative References**

- [RFC3864] Klyne, G., Nottingham, M., and J. Mogul, "Registration Procedures for Message Header Fields", [BCP 90](#), [RFC 3864](#), DOI 10.17487/RFC3864, September 2004, <<http://www.rfc-editor.org/info/rfc3864>>.
- [STANAG-4406] "STANAG 4406 Edition 2: Military Message Handling System", STANAG 4406 Ed. 2, March 2005.
- [I-D.melnikov-smime-msa-to-md] Ottaway, W. and A. Melnikov, "Domain-based signing and encryption using S/MIME", [draft-melnikov-smime-msa-to-md-04](#) (work in progress), March 2014.
- [RFC5752] Turner, S. and J. Schaad, "Multiple Signatures in Cryptographic Message Syntax (CMS)", [RFC 5752](#), DOI 10.17487/RFC5752, January 2010, <<http://www.rfc-editor.org/info/rfc5752>>.



## **Appendix A. Acknowledgements**

Many thanks for reviews and text provided by Steve Kille, Jim Schaad, Russ Housley, David Wilson, Chris Bonatti and Sean Turner.

Some text in this document was copied from [RFC 7001](#).

### Author's Address

Alexey Melnikov  
Isode Ltd  
14 Castle Mews  
Hampton, Middlesex TW12 2NP  
UK

EMail: Alexey.Melnikov@isode.com

