

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: July 15, 2016

A. Melnikov  
Isode Ltd  
January 12, 2016

Updated DNSSEC-based TLS Server Identity Check Procedure for Email  
Related Protocols  
draft-melnikov-uta-dnssec-email-tls-certs-00

## Abstract

This document describes DNSSEC-based TLS server identity verification procedure for SMTP Submission, IMAP, POP and ManageSieve clients.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 15, 2016.

## Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Internet-Draft DNSSEC-based TLS Server Identity Check for Email January 2016

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Conventions Used in This Document . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Email Server Certificate Verification Rules . . . . .	<a href="#">3</a>
<a href="#">4.</a>	Compliance Checklist for Certification Authorities . . . . .	<a href="#">5</a>
4.1.	Notes on handling of delegated email services by Certification Authorities . . . . .	<a href="#">5</a>
5.	Compliance Checklist for Mail Service Providers and Certificate Signing Request generation tools . . . . .	<a href="#">6</a>
5.1.	Notes on hosting multiple domains . . . . .	<a href="#">7</a>
<a href="#">6.</a>	Examples . . . . .	<a href="#">8</a>
<a href="#">7.</a>	Operational Considerations . . . . .	<a href="#">9</a>
<a href="#">8.</a>	IANA Considerations . . . . .	<a href="#">9</a>
<a href="#">9.</a>	Security Considerations . . . . .	<a href="#">9</a>
<a href="#">10.</a>	References . . . . .	<a href="#">9</a>
10.1.	Normative References . . . . .	<a href="#">9</a>
10.2.	Informative References . . . . .	<a href="#">11</a>
<a href="#">Appendix A.</a>	Acknowledgements . . . . .	<a href="#">13</a>
<a href="#">Appendix B.</a>	Changes since <a href="#">draft-melnikov-uta-dnssec-email-tls-</a> <a href="#">certs-00</a> . . . . .	<a href="#">13</a>
Author's Address	. . . . .	<a href="#">13</a>

[1.](#) Introduction

Use of TLS by SMTP Submission, IMAP, POP and ManageSieve clients is described in [\[RFC3207\]](#), [\[RFC3501\]](#), [\[RFC2595\]](#) and [\[RFC5804\]](#) respectively. Each of the documents describes slightly different rules for server certificate identity verification (or doesn't define any rules at all). In reality, email client and server developers implement many of these protocols at the same time, so it would be good to define modern and consistent rules for verifying email server identities using TLS.

This document describes the updated TLS server identity verification procedure for SMTP Submission [\[RFC6409\]](#) [\[RFC3207\]](#), IMAP [\[RFC3501\]](#), POP [\[RFC1939\]](#) and ManageSieve [\[RFC5804\]](#) clients. It replaces [Section 2.4 of RFC 2595](#).

Note that this document doesn't apply to use of TLS in MTA-to-MTA SMTP.

This document provides a consistent TLS server identity verification

procedure across multiple email related protocols. This should make it easier for Certification Authorities and ISPs to deploy TLS for email use, and would enable email client developers to write more secure code.

Internet-Draft DNSSEC-based TLS Server Identity Check for Ema January 2016

## 2. Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

The following terms or concepts are used through the document:

reference identifier: (formally defined in [[RFC6125](#)]) One of the domain names that the email client (an SMTP, IMAP, POP3 or ManageSieve client) associates with the target email server. For some identifier types, the identifier also includes an application service type. Reference identifiers are used for performing name checks on server certificates.

CN-ID, DNS-ID, SRV-ID and URI-ID are identifier types (see [[RFC6125](#)] for details). For convenience, their short definitions from [[RFC6125](#)] are listed below:

CN-ID = a Relative Distinguished Name (RDN) in the certificate subject field that contains one and only one attribute-type-and-value pair of type Common Name (CN), where the value matches the overall form of a domain name (informally, dot-separated letter-digit-hyphen labels).

DNS-ID = a subjectAltName entry of type dNSName

SRV-ID = a subjectAltName entry of type otherName whose name form is SRVName

URI-ID = a subjectAltName entry of type uniformResourceIdentifier whose value includes both (i) a "scheme" and (ii) a "host" component (or its equivalent) that matches the "reg-name" rule (where the quoted terms represent the associated [[RFC5234](#)] productions from [[RFC3986](#)]).

This document uses the phrase 'RRSet is "insecure"' as defined in [Section 2.1.1 of \[RFC7672\]](#). Similarly, 'RRSet is "secure"' if it is not "insecure".

### 3. Email Server Certificate Verification Rules

During a TLS negotiation, an email client (i.e., an SMTP, IMAP, POP3 or ManageSieve client) MUST check its understanding of the server identity (client's reference identifiers) against the server's identity as presented in the server Certificate message, in order to prevent man-in-the-middle attacks. This check is only performed after the server certificate passes certification path validation as

Internet-Draft DNSSEC-based TLS Server Identity Check for Email January 2016

described in [Section 6 of \[RFC5280\]](#). Matching is performed according to the rules specified in [Section 6 of \[RFC6125\]](#), including the relative order of matching of different identifier types, "certificate pinning" and the procedure on failure to match. The following inputs are used by the verification procedure used in [\[RFC6125\]](#):

1. For DNS-ID and CN-ID identifier types the client MUST use one or more of the following as "reference identifiers": (a) the domain portion of the user's email address, (b) the hostname it used to open the connection (without CNAME canonicalization). The client MAY also use (c) a value securely derived from (a) or (b), such as using "secure" DNSSEC [\[RFC4033\]](#) [\[RFC4034\]](#) [\[RFC4035\]](#) validated lookup or a value obtained from the local hostname file.
2. When using email service discovery procedure specified in [\[RFC6186\]](#) the client MUST also use the domain portion of the user's email address as another "reference identifier" to compare against SRV-ID identifier in the server certificate. If DNSSEC protected SRV lookup (and all CNAME leading to it) are "secure", the email client MAY also use the resulting hostname from such lookup as DNS-ID/CN-ID reference identifier types. (This also corresponds to the case (c) above.)

The rules and guidelines defined in [\[RFC6125\]](#) apply to an email server certificate, with the following supplemental rules:

1. Support for the DNS-ID identifier type (subjectAltName of dNSName type [\[RFC5280\]](#)) is REQUIRED in Email client software

implementations.

2. Support for the SRV-ID identifier type (subjectAltName of SRVName type [[RFC4985](#)]) is REQUIRED for email client software implementations that support [[RFC6186](#)] and don't rely on DNSSEC protection of DNS SRV records. List of SRV-ID types for email services is specified in [[RFC6186](#)]. For the ManageSieve protocol the service name "sieve" is used.
3. URI-ID identifier type (subjectAltName of uniformResourceIdentifier type [[RFC5280](#)]) MUST NOT be used by clients for server verification, as URI-ID were not historically used for email.
4. For backward compatibility with deployed software CN-ID identifier type (CN attribute from the subject name, see [[RFC6125](#)]) MAY be used for server identity verification.

Internet-Draft DNSSEC-based TLS Server Identity Check for Email January 2016

5. Email protocols allow use of certain wildcards in identifiers presented by email servers. The "\*" wildcard character MAY be used as the left-most name component of DNS-ID or CN-ID in the certificate. For example, a DNS-ID of \*.example.com would match a.example.com, foo.example.com, etc. but would not match example.com. Note that the wildcard character MUST NOT be used as a fragment of the left-most name component (e.g., \*oo.example.com, f\*o.example.com, or foo\*.example.com).

#### [4.](#) Compliance Checklist for Certification Authorities

1. CA MUST support issuance of server certificates with DNS-ID identifier type (subjectAltName of dNSName type [[RFC5280](#)]). (Note that some DNS-IDs may refer to domain portions of email addresses, so they might not have corresponding A/AAAA DNS records.)
2. CA MUST support issuance of server certificates with SRV-ID identifier type (subjectAltName of SRVName type [[RFC4985](#)]) for each type of email service.
3. For backward compatibility with deployed client base, CA MUST

support issuance of server certificates with CN-ID identifier type (CN attribute from the subject name, see [[RFC6125](#)]).

4. CA MAY allow "\*" (wildcard) as the left-most name component of DNS-ID or CN-ID in server certificates it issues.

#### [4.1.](#) Notes on handling of delegated email services by Certification Authorities

[RFC6186] provides an easy way for organizations to autoconfigure email clients. It also allows for delegation of email services to an email hosting provider. When connecting to such delegated hosting service an email client that attempts to verify TLS server identity needs to know that if it connects to `imap.hosting.example.net` that such server is authorized to provide email access for an email such as `alice@example.org`. In absence of SRV-IDs, users of compliant email clients would be forced to manually confirm exception, because the TLS server certificate verification procedures specified in this document would result in failure to match the TLS server certificate against the expected domain(s). One way to provide such authorization is for the TLS certificate for `imap.hosting.example.net` to include SRV-ID(s) (or DNS-ID) for the `example.org` domain. Another way is for DNS SRV lookups to be protected by DNSSEC.

A certification authority that receives a Certificate Signing Request containing multiple unrelated DNS-IDs and/or SRV-IDs (e.g. DNS-ID of

`example.org` and DNS-ID of `example.com`) needs to verify that the entity that supplied such Certificate Signing Request is authorized to provide email service for all requested domains.

The ability to issue certificates that contain an SRV-ID (or a DNS-ID for the domain part of email addresses) implies the ability to verify that entities requesting them are authorized to run email service for these SRV-IDs/DNS-IDs. In particular, certification authorities that can't verify such authorization (whether for a particular domain or in general) MUST NOT include such email SRV-IDs/DNS-IDs in certificates they issue. This document doesn't specify exact mechanism(s) that can be used to achieve this. However, a few special case recommendations are listed below.

A certification authority willing to sign a certificate containing a

particular DNS-ID SHOULD also support signing a certificate containing one or more of email SRV-IDs for the same domain, because the SRV-ID effectively provides more restricted access to an email service for the domain (as opposed to unrestricted use of any services for the same domain, as specified by DNS-ID).

A certification authority which also provides DNS service for a domain can use DNS information to validate SRV-IDs/DNS-IDs for the domain.

A certification authority which is also a Mail Service Provider for a hosted domain can use that knowledge to validate SRV-IDs/DNS-IDs for the domain.

#### 5. Compliance Checklist for Mail Service Providers and Certificate Signing Request generation tools

Mail Service Providers and Certificate Signing Request generation tools

1. MUST include the DNS-ID identifier type in Certificate Signing Requests for the host name(s) where the email server(s) are running. They SHOULD include the DNS-ID identifier type in Certificate Signing Requests for the domain portion of served email addresses.
2. If the email services provided are discoverable using DNS SRV as specified in [[RFC6186](#)], the Mail Service Provider MUST (a) include the SRV-ID identifier type for each type of email service in Certificate Signing Requests and/or (b) make sure that relevant SRV records are DNSSEC protected and "secure".

3. SHOULD include CN-ID identifier type for the host name where the email server(s) is running in Certificate Signing Requests for backward compatibility with deployed email clients. (Note, a certificate can only include a single CN-ID, so if a mail service is running on multiple hosts, either each host has to use different certificate with its own CN-ID, a single certificate with multiple DNS-IDs, or a single certificate with wildcard in CN-ID can be used).

4. MAY include "\*" (wildcard) as the left-most name component of DNS-ID or CN-ID in Certificate Signing Requests.

#### 5.1. Notes on hosting multiple domains

A server that hosts multiple domains needs to do one of the following (or some combination thereof):

1. Use DNS SRV records to redirect each hosted email service to a fixed domain, deploy TLS certificate(s) for that single domain, and instruct users to configure their clients with appropriate pinning (unless the SRV records can always be obtained via DNSSEC). Some email clients come with preloaded list of pinned certificates for some popular domains, which can avoid the need for manual confirmation.
2. Use a single TLS certificate that includes a complete list of all the domains it is serving.
3. Serve each domain on its own IP/port, using separate TLS certificates on each IP/port.
4. Use Server Name Indication (SNI) TLS extension [[RFC6066](#)] to select the right certificate to return during TLS negotiation. Each domain has its own TLS certificate in this case.

Each of these deployment choices have their scaling or operational disadvantages when the list of domains changes. Use of DNS SRV without SRV-ID requires manual confirmation from users or ubiquitous availability of DNSSEC and its APIs. A single certificate (the second choice) requires that when a domain is added, then a new Certificate Signing Request that includes a complete list of all the domains needs to be issued and passed to a CA in order to generate a new certificate. Separate IP/port can avoid regenerating the certificate, but requires more transport layer resources. Use of TLS SNI requires each emailclient to use it.

domains. DNSSEC protected SRV records can address scaling issues caused by use of TLS in multi-tenanted environments.

## 6. Examples

Consider an IMAP-accessible email server which supports both IMAP and IMAPS (IMAP-over-TLS) at the host "mail.example.net" servicing email addresses of the form "user@example.net". A certificate for this service needs to include DNS-IDs of "example.net" (because it is the domain portion of emails) and "mail.example.net" (this is what a user of this server enters manually, if not using [RFC6186](#)). It might also include CN-ID of "mail.example.net" for backward compatibility with deployed infrastructure.

Consider the IMAP-accessible email server from the previous paragraph which is additionally discoverable via DNS SRV lookups in domain "example.net" (DNS SRV records "\_imap.\_tcp.example.net" and "\_imaps.\_tcp.example.net"). In addition to DNS-ID/CN-ID identity types specified above, a certificate for this service also needs to include SRV-IDs of "\_imap.example.net" (when STARTTLS is used on the IMAP port) and "\_imaps.example.net" (when TLS is used on IMAPS port). See [RFC6186](#) for more details. (Note that unlike DNS SRV there is no "\_tcp" component in SRV-IDs). If DNS SRV are DNSSEC protected, email clients that perform DNSSEC validation of SRV records would check for DNS-IDs that contain the target of SRV records, instead of SRV-IDs.

Consider the IMAP-accessible email server from the first paragraph which is running on a host also known as "mycompany.example.com". In addition to DNS-ID identity types specified above, a certificate for this service also needs to include DNS-ID of "mycompany.example.com" (this is what a user of this server enters manually, if not using [RFC6186](#)). It might also include CN-ID of "mycompany.example.com" instead of the CN-ID "mail.example.net" for backward compatibility with deployed infrastructure. (This is so, because a certificate can only include a single CN-ID)

Consider an SMTP Submission server at the host "submit.example.net" servicing email addresses of the form "user@example.net" and discoverable via DNS SRV lookups in domain "example.net" (DNS SRV records "\_submission.\_tcp.example.net"). A certificate for this service needs to include SRV-IDs of "\_submission.example.net" (see [RFC6186](#)) along with DNS-IDs of "example.net" and "submit.example.net". It might also include CN-ID of "submit.example.net" for backward compatibility with deployed infrastructure.

Consider a host "mail.example.net" servicing email addresses of the form "user@example.net" and discoverable via DNS SRV lookups in domain "example.net", which runs SMTP Submission, IMAPS and POP3S (POP3-over-TLS) and ManageSieve services. Each of the servers can use their own certificate specific to their service (see examples above). Alternatively they can all share a single certificate that would include SRV-IDs of "\_submission.example.net", "\_imaps.example.net", "\_pop3s.example.net" and "\_sieve.example.net" along with DNS-IDs of "example.net" and "mail.example.net". It might also include CN-ID of "mail.example.net" for backward compatibility with deployed infrastructure.

## [7.](#) Operational Considerations

[Section 5](#) covers operational considerations (in particular use of DNS SRV for autoconfiguration) related to generating TLS certificates for email servers so that they can be successfully verified by email clients. Additionally, [Section 5.1](#) talks about operational considerations related to hosting multiple domains.

## [8.](#) IANA Considerations

This document doesn't require any action from IANA.

## [9.](#) Security Considerations

The goal of this document is to improve interoperability and thus security of email clients wishing to access email servers over TLS protected email protocols, by specifying a consistent set of rules that email service providers, email client writers and Certification Authorities can use when creating server certificates.

TLS Server Identity Check for Email relies on use of trustworthy DNS hostnames when constructing "reference identifiers" that are checked against an email server certificate. Such trustworthy names are either entered manually (for example if they are advertised on a Mail Service Provider's website), explicitly confirmed by the user (e.g. if they are a target of a DNS SRV lookup) or derived using a secure third party service (e.g. DNSSEC-protected SRV records which are verified by the client or trusted local resolver).

## [10.](#) References

### [10.1.](#) Normative References

[RFC1939] Myers, J. and M. Rose, "Post Office Protocol - Version 3",

Internet-Draft DNSSEC-based TLS Server Identity Check for Ema January 2016

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC3207] Hoffman, P., "SMTP Service Extension for Secure SMTP over Transport Layer Security", [RFC 3207](#), DOI 10.17487/RFC3207, February 2002, <<http://www.rfc-editor.org/info/rfc3207>>.
- [RFC3501] Crispin, M., "INTERNET MESSAGE ACCESS PROTOCOL – VERSION 4rev1", [RFC 3501](#), DOI 10.17487/RFC3501, March 2003, <<http://www.rfc-editor.org/info/rfc3501>>.
- [RFC4985] Santesson, S., "Internet X.509 Public Key Infrastructure Subject Alternative Name for Expression of Service Name", [RFC 4985](#), DOI 10.17487/RFC4985, August 2007, <<http://www.rfc-editor.org/info/rfc4985>>.
- [RFC5804] Melnikov, A., Ed. and T. Martin, "A Protocol for Remotely Managing Sieve Scripts", [RFC 5804](#), DOI 10.17487/RFC5804, July 2010, <<http://www.rfc-editor.org/info/rfc5804>>.
- [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 5280](#), DOI 10.17487/RFC5280, May 2008, <<http://www.rfc-editor.org/info/rfc5280>>.
- [RFC6125] Saint-Andre, P. and J. Hodges, "Representation and Verification of Domain-Based Application Service Identity within Internet Public Key Infrastructure Using X.509 (PKIX) Certificates in the Context of Transport Layer Security (TLS)", [RFC 6125](#), DOI 10.17487/RFC6125, March 2011, <<http://www.rfc-editor.org/info/rfc6125>>.
- [RFC6186] Daboo, C., "Use of SRV Records for Locating Email Submission/Access Services", [RFC 6186](#), DOI 10.17487/RFC6186, March 2011, <<http://www.rfc-editor.org/info/rfc6186>>.

- [RFC6409] Gellens, R. and J. Klensin, "Message Submission for Mail", STD 72, [RFC 6409](#), DOI 10.17487/RFC6409, November 2011, <<http://www.rfc-editor.org/info/rfc6409>>.

Internet-Draft DNSSEC-based TLS Server Identity Check for Ema January 2016

- [RFC7672] Dukhovni, V. and W. Hardaker, "SMTP Security via Opportunistic DNS-Based Authentication of Named Entities (DANE) Transport Layer Security (TLS)", [RFC 7672](#), DOI 10.17487/RFC7672, October 2015, <<http://www.rfc-editor.org/info/rfc7672>>.

## [10.2.](#) Informative References

- [RFC2595] Newman, C., "Using TLS with IMAP, POP3 and ACAP", [RFC 2595](#), DOI 10.17487/RFC2595, June 1999, <<http://www.rfc-editor.org/info/rfc2595>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<http://www.rfc-editor.org/info/rfc3986>>.
- [RFC4033] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "DNS Security Introduction and Requirements", [RFC 4033](#), DOI 10.17487/RFC4033, March 2005, <<http://www.rfc-editor.org/info/rfc4033>>.
- [RFC4034] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "Resource Records for the DNS Security Extensions", [RFC 4034](#), DOI 10.17487/RFC4034, March 2005, <<http://www.rfc-editor.org/info/rfc4034>>.
- [RFC4035] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "Protocol Modifications for the DNS Security Extensions", [RFC 4035](#), DOI 10.17487/RFC4035, March 2005, <<http://www.rfc-editor.org/info/rfc4035>>.

- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), DOI 10.17487/RFC5234, January 2008, <<http://www.rfc-editor.org/info/rfc5234>>.
- [RFC6066] Eastlake 3rd, D., "Transport Layer Security (TLS) Extensions: Extension Definitions", [RFC 6066](#), DOI 10.17487/RFC6066, January 2011, <<http://www.rfc-editor.org/info/rfc6066>>.
- [RFC6698] Hoffman, P. and J. Schlyter, "The DNS-Based Authentication of Named Entities (DANE) Transport Layer Security (TLS) Protocol: TLSA", [RFC 6698](#), DOI 10.17487/RFC6698, August 2012, <<http://www.rfc-editor.org/info/rfc6698>>.

- [RFC7711] Miller, M. and P. Saint-Andre, "PKIX over Secure HTTP (POSH)", [RFC 7711](#), DOI 10.17487/RFC7711, November 2015, <<http://www.rfc-editor.org/info/rfc7711>>.

---

Internet-Draft DNSSEC-based TLS Server Identity Check for Ema January 2016

[Appendix A](#). Acknowledgements

The editor of this document copied lots of text from [RFC 2595](#) and [RFC 6125](#), [RFC 7672](#), so the hard work of editors of these document is appreciated.

[Appendix B](#). Changes since [draft-melnikov-uta-dnssec-email-tls-certs-00](#)

[[Note to RFC Editor: Please delete this section before publication]]

TBD

Author's Address

Alexey Melnikov  
Isode Ltd  
14 Castle Mews  
Hampton, Middlesex TW12 2NP

UK

EMail: Alexey.Melnikov@isode.com