

Workgroup: HTTP
Internet-Draft:
draft-momoka-httpbis-settings-enable-
websockets-02
Updates: [8441](#), [9220](#) (if approved)
Published: 30 March 2023
Intended Status: Standards Track
Expires: 1 October 2023
Authors: (M. Yamamoto)
The University of Tokyo/WIDE Project

SETTINGS_ENABLE_WEBSOCKETS settings parameter for HTTP/2 and HTTP/3

Abstract

This document proposes a new HTTP settings parameter, `SETTINGS_ENABLE_WEBSOCKETS`. This parameter indicates whether the server supports bootstrapping WebSockets over the established connection.

Discussion Venues

This note is to be removed before publishing as an RFC.

Discussion of this document takes place on the HTTP Working Group mailing list (ietf-http-wg@w3.org), which is archived at <https://lists.w3.org/Archives/Public/ietf-http-wg/>.

Source for this draft and an issue tracker can be found at <https://github.com/momoka0122y/draft-settings-enable-websockets>.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 1 October 2023.

Copyright Notice

Copyright (c) 2023 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

- [1. Introduction](#)
- [2. SETTINGS_ENABLE_WEBSOCKETS Parameter](#)
- [3. SETTINGS_ENABLE_CONNECT_PROTOCOL Parameter](#)
- [4. Security Considerations](#)
- [5. IANA Considerations](#)
 - [5.1. HTTP/2 Setting](#)
 - [5.2. HTTP/3 Setting](#)
- [6. References](#)
 - [6.1. Normative References](#)
 - [6.2. Informative References](#)
- [Acknowledgments](#)
- [Author's Address](#)

1. Introduction

The mechanisms for running the WebSocket protocol [[RFC6455](#)] over a single stream of an HTTP/2 and HTTP/3 connection is defined in [[RFC8441](#)] and [[RFC9220](#)]. The extended CONNECT mechanism is used for bootstrapping WebSockets from HTTP/2 and HTTP/3. Support for the extended CONNECT mechanism is advertised using HTTP/2 and HTTP/3 settings parameter `SETTINGS_ENABLE_CONNECT_PROTOCOL`.

However, the support of extended CONNECT does not necessarily indicate support for WebSockets over that HTTP connection. Other protocols such as [[WEBTRANSPORT](#)] also use extended CONNECT and send `SETTINGS_ENABLE_CONNECT_PROTOCOL` settings parameters as well.

Suppose the server supports Extended CONNECT and has a `wss://` URL, but does not support bootstrapping WebSockets over this HTTP connection. In this case, a client attempting to initiate a WebSocket handshake using Extended CONNECT will fail, and the client would need to create a WebSocket connection using the HTTP/1.1 Upgrade mechanism.

This is why a `SETTINGS_ENABLE_WEBSOCKETS` settings parameter is needed.

2. `SETTINGS_ENABLE_WEBSOCKETS` Parameter

This document defines the `SETTINGS_ENABLE_WEBSOCKETS` parameter for HTTP/2 and HTTP/3. A server can send this setting to inform a client that it supports bootstrapping WebSockets over the HTTP connection.

The value of the parameter MUST be 0 or 1.

This parameter has no default value, as its absence indicates a lack of information from the server.

If the server supports bootstrapping WebSockets over the HTTP connection, it SHOULD include the `SETTINGS_ENABLE_WEBSOCKETS` parameter in the `SETTINGS` frame with a value of 1. If the server does not support bootstrapping WebSockets over the HTTP connection it SHOULD send the parameter with a value of 0.

A server MUST NOT send a `SETTINGS_ENABLE_WEBSOCKETS` parameter with the value of 0 after previously sending a value of 1.

A client MUST NOT send this setting parameter. Receipt of this parameter by a server does not have any impact.

The `SETTINGS_ENABLE_WEBSOCKETS` parameter is an explicit signal about the server support for bootstrapping WebSockets on the connection. Where a server declares it does not support WebSockets, clients can avoid sending WebSocket handshake requests that would fail. This saves unnecessary work for both client and server, and potentially reduces delays. For instance, a client that learns an HTTP/2 or HTTP/3 connection does not support WebSockets via the setting, could instead attempt to create a WebSocket using the HTTP/1.1 Upgrade mechanism at the immediate moment it is required.

Other protocols also rely on the extended `CONNECT` extension for bootstrapping. This mechanism provides clients with a stronger signal about whether the WebSocket protocol is supported on a connection. This can help improve compatibility with other extended `CONNECT`-based protocols by avoiding the client making assumption about the supported protocols.

Clients that do not implement this extension will not be able to use its signal. In order to support legacy deployments, clients MAY initiate a WebSocket request when they receive `SETTINGS_ENABLE_WEBSOCKETS` with a value of 0, or if the parameter is omitted from received settings. Such requests could fail, introducing additional latency, which this extension is intended to help avoid.

A server that sends `SETTINGS_ENABLE_WEBSOCKETS` with a value of 0 or omits the parameter MUST NOT treat reception of the a WebSocket request as a stream or connection error. Instead, the server can reject the request with a suitable status code.

3. `SETTINGS_ENABLE_CONNECT_PROTOCOL` Parameter

A server which sends `SETTINGS_ENABLE_WEBSOCKETS` parameter MUST also send the `SETTINGS_ENABLE_CONNECT_PROTOCOL = 1`.

4. Security Considerations

This document introduces no new security considerations beyond those discussed in [[RFC8441](#)].

5. IANA Considerations

5.1. HTTP/2 Setting

IANA is requested to register the following entry in the "HTTP/2 Settings" registry maintained at <https://www.iana.org/assignments/http2-parameters>:

Code: TBD

Name: `SETTINGS_ENABLE_WEBSOCKETS`

Initial Value: None

Specification: This document

5.2. HTTP/3 Setting

IANA is requested to register the following entry in the "HTTP/3 Settings" registry maintained at <https://www.iana.org/assignments/http3-parameters>:

Value: TBD

Setting Name: `SETTINGS_ENABLE_WEBSOCKETS`

Default: None

Status: provisional

Reference: This document

Change Controller: Momoka Yamamoto (IETF if this document is approved)

Contact: Momoka Yamamoto (HTTP_WG; HTTP working group; ietf-http-wg@w3.org if this document is approved)

6. References

6.1. Normative References

- [HTTP] Fielding, R., Ed., Nottingham, M., Ed., and J. Reschke, Ed., "HTTP Semantics", RFC 9110, DOI 10.17487/RFC9110, April 2022, <<https://www.rfc-editor.org/rfc/rfc9110>>.
- [HTTP/2] Thomson, M., Ed. and C. Benfield, Ed., "HTTP/2", RFC 9113, DOI 10.17487/RFC9113, April 2022, <<https://www.rfc-editor.org/rfc/rfc9113>>.
- [HTTP/3] Bishop, M., Ed., "Hypertext Transfer Protocol Version 3 (HTTP/3)", RFC 9114, DOI 10.17487/RFC9114, April 2022, <<https://www.rfc-editor.org/rfc/rfc9114>>.
- [RFC6455] Fette, I. and A. Melnikov, "The WebSocket Protocol", RFC 6455, DOI 10.17487/RFC6455, December 2011, <<https://www.rfc-editor.org/rfc/rfc6455>>.
- [RFC8441] McManus, P., "Bootstrapping WebSockets with HTTP/2", RFC 8441, DOI 10.17487/RFC8441, September 2018, <<https://www.rfc-editor.org/rfc/rfc8441>>.
- [RFC9220] Hamilton, R., "Bootstrapping WebSockets with HTTP/3", RFC 9220, DOI 10.17487/RFC9220, June 2022, <<https://www.rfc-editor.org/rfc/rfc9220>>.

6.2. Informative References

- [WEBTRANSPORT] Vasiliev, V., "The WebTransport Protocol Framework", Work in Progress, Internet-Draft, draft-ietf-webtransport-overview-05, 24 January 2023, <<https://datatracker.ietf.org/doc/html/draft-ietf-webtransport-overview-05>>.

Acknowledgments

TODO acknowledge people.

Thank you for reading this draft. :)

Author's Address

Momoka Yamamoto
The University of Tokyo/WIDE Project
Japan

Email: momoka.my6@gmail.com

Additional contact information:

Japan

The University of Tokyo/WIDE Project