RSA
B. Trammell
ETH Zurich

Transport of Real-time Inter-network Defense (RID) Messages draft-moriarty-post-inch-rid-transport-03.txt

Abstract

The Incident Object Description Exchange Format (IODEF) defines a common XML format for document exchange, and Realtime Internetwork Defense (RID) defines extensions to IODEF intended for the cooperative handling of security incidents within consortia of network operators and enterprises. This document specifies a transport protocol for RID based upon the passing of RID messages over HTTP/TLS.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 1, 2011.

Copyright Notice

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

1. Introduction

The Incident Object Description Exchange Format (IODEF) (Danyliw, R., Meijer, J., and Y. Demchenko, "The Incident Object Description Exchange Format," December 2007.) [RFC5070] describes an XML document format for the purpose of exchanging data between Computer Security Incident Response Teams (CSIRTs) or those responsible for security incident handling for network providers (NPs). The defined document format provides an easy way for CSIRTs to exchange data in a way which can be easily parsed.

IODEF defines a message format, not a transport protocol, as the sharing of messages is assumed to be out of scope in order to allow CSIRTs to exchange and store messages in a way most suited to their established incident handling processes. However, Real-time Internetwork Defense (RID) (Moriarty, K., "Real-time Inter-network Defense," April 2010.) [I-D.moriarty-post-inch-rid] do require a specification of a transport protocol to ensure interoperability among members in a RID consortium. This document specifies the transport of RID messages within HTTP (Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1," June 1999.) [RFC2616] Request and Response messages transported over TLS (Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2," August 2008.) [RFC5246] (herein, HTTP/TLS). Note that any IODEF message may also be transported using this mechanism, by sending it as a RID Report message.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119] (Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," March 1997.).

3. Transmission of RID Messages over HTTP/TLS

This section specifies the details of the transport of RID messages over HTTP/TLS. In this arrangement, each RID server is both an HTTP/TLS server and an HTTP/TLS Client. When a RID message must be sent, the sending RID system connects to the receiving RID system and sends the message, optionally receiving a message in reply. All RID systems MUST

be prepared to accept HTTP/TLS connections from any RID peer with which it communicates, in order to support callback for delayed replies (see below).

BCP 56 (Moore, K., "On the use of HTTP as a Substrate," February 2002.) [RFC3205] contains a number of important considerations when using HTTP for application protocols. These include the size of the payload for the application, whether the application will use a web browser, whether the protocol should be defined on a port other than 80, and if the security provided through HTTP/TLS suits the needs of the new application.

It is acknowledged within the scope of these concerns that HTTP/TLS is not ideally suited for RID transport, as the former is a client-server protocol and the latter a message-exchange protocol; however, the ease of implementation of RID systems over HTTP/TLS outweighs these concerns. Consistent with BCP 56, RID systems will listen for TCP connections on port [IANA NOTE: assigned port goes here]. Every RID system participating in a consortium MUST listen for HTTP/TLS connections on the assigned port.

All RID messages sent in HTTP Requests MUST be sent using the POST with a Request-URI of /; additional Request-URI paths are reserved for future use by RID.

<u>Table 1</u> lists the allowable RID message types in an HTTP Response for a given RID message type in the Request. A RID system MUST be prepared to handle an HTTP Response of the given type(s) when sending the corresponding HTTP Request. A RID system MUST NOT send an HTTP Response containing any RID message other than the one corresponding to the one sent in the HTTP Request.

As the queries and replies in a RID message exchange may be significantly separated in time, the receiving RID system MAY return 202 Accepted, terminate the connection, and connect to the requesting RID system and sending the RID reply in an HTTP Request at a later time. This mechanism is referred to in this document as "RID callback". When performing RID callback, a responding system MUST connect to the network- and transport-layer addresses from which the original request was sent; there is no mechanism in RID for redirected callback. While a RID system SHOULD return the reply in an HTTP Response if it is available immediately or within a generally accepted HTTP client time out (about thirty seconds), this is not mandatory, and as such RID systems MUST be prepared for a query to be met with a 202 Accepted, an empty Response body, a connection termination and a callback. Note that all RID messages require a response from the receiving RID system, so a sending RID system can expect either an immediate response or a callback.

RID systems accepting a callback message in an HTTP Request MUST return 202 Accepted.

Table 1 lists the allowable request/response pairs for RID.

Request RID type	Callback	Result	Response RID type
TraceRequest		200	RequestAuthorization
TraceRequest		200	Result
TraceRequest		202	[empty]
RequestAuthorization	X	202	[empty]
Result	X	202	[empty]
Investigation		200	Result
Investigation		202	[empty]
Report	X	202	[empty]
IncidentQuery		200	Report
IncidentQuery		202	[empty]

Table 1

For security purposes, RID systems SHOULD NOT return 3xx Redirect response codes, and MUST NOT follow any 3xx Redirect. When a RID System's address changes, contact point information within the consortium must be updated out of band.

If a RID system receives an improper RID message in an HTTP Request, it MUST return an appropriate 4xx Client Error result code to the requesting RID system. If a RID system cannot process a RID message received in an HTTP Request due to an error on its own side, it MUST return an appropriate 5xx Server Error result code to the requesting RID system.

Note that HTTP provides no mechanism for signaling to a server that a response body is not a valid RID message. If an RID system receives and improper RID message in an HTTP Response, or cannot process a RID message received in an HTTP Response due to an error on its own side, it MUST log the error and present it to the RID system administrator for handling; the error logging format is an implementation detail and is considered out of scope for this specification.

RID systems MUST support and SHOULD use HTTP/1.1 persistent connections as described in [RFC2616] (Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1," June 1999.). RID systems MUST support chunked transfer encoding on the HTTP server side to allow the implementation of clients that do not need to precalculate message sizes before constructing HTTP headers.

RID systems MUST use TLS for confidentiality, identification, and strong mutual authentication as in [RFC2818] (Rescorla, E., "HTTP Over TLS," May 2000.); see Section 4 (Security Considerations) below for details.

4. Security Considerations

All security considerations of related documents MUST be considered, especially the <u>Incident Object Description Exchange Format (IODEF)</u> (Danyliw, R., Meijer, J., and Y. Demchenko, "The Incident Object Description Exchange Format," December 2007.) [RFC5070] and <u>Real-time Inter-network Defense (RID) (Moriarty, K., "Real-time Inter-network Defense," April 2010.)</u> [I-D.moriarty-post-inch-rid]. The transport described herein is built on the foundation of these documents; the security considerations contained therein are incorporated by reference.

For transport confidentiality, identification, and authentication, TLS with mutual authentication MUST be used to secure the HTTP connection as in [RFC2818] (Rescorla, E., "HTTP Over TLS," May 2000.). The session MUST use non-NULL cypher suites for authentication, integrity, and confidentiality; sessions MAY be renegotiated within these constraints. Although TLS implementations typically support the older SSL protocol, a RID peer MUST NOT request, offer, or use SSL 2.0 , due to known security vulnerabilities in this protocol; see Appendix E of [RFC5246] (Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2," August 2008.) for more.

Each RID consortium SHOULD use a trusted public key infrastructure (PKI) to manage identities for RID systems participating in TLS connections. At minimum, each RID system MUST trust a set of X.509 Issuer identities ("Certificate Authorities") to authenticate RID system peers with which it is willing to exchange information, and/or a specific white list of X.509 Subject identities of RID system peers directly.

RID systems MUST provide for the verification of the identity of a RID system peer presenting a valid and trusted certificate, by verifying the fully qualified domain name or other network-layer identifier against that stored in the certificate, if available. More information on best practices in peer identity verification is available in [I-D.saintandre-tls-server-id-check] (Saint-Andre, P. and J. Hodges, "Representation and Verification of Domain-Based Application Server Identity in Certificates Used with Transport Layer Security," June 2010.).

5. IANA Considerations

Consistent with <u>BCP 56 (Moore, K., "On the use of HTTP as a Substrate," February 2002.)</u> [RFC3205], since RID over HTTP/TLS is a substantially new service, and should be controlled at the consortium member network's border differently than HTTP/TLS, it requires a new port number. IANA has assigned port [IANA NOTE: assign port number here]/tcp

to RID with service name [IANA NOTE: assign service name here; request 'rid'] over HTTP/TLS.

6. References

6.1. Normative References

[RFC2119]	Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," BCP 14, RFC 2119, March 1997 (TXT, HTML, XML).
[RFC2616]	Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol HTTP/1.1," RFC 2616, June 1999 (TXT, PS, PDF, HTML, XML).
[RFC2818]	Rescorla, E., "HTTP Over TLS," RFC 2818, May 2000 (TXT).
[RFC5070]	Danyliw, R., Meijer, J., and Y. Demchenko, "The Incident Object Description Exchange Format," RFC 5070, December 2007 (TXT).
[RFC5246]	Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2," RFC 5246, August 2008 (TXT).
[I-D.moriarty- post-inch-rid]	Moriarty, K., "Real-time Inter-network Defense," draft-moriarty-post-inch-rid-11 (work in progress), April 2010 (TXT).

6.2. Informative References

[RFC3205]	Moore, K., "On the use of HTTP as a Substrate," BCP 56, RFC 3205, February 2002 (TXT).
[I-D.saintandre-	Saint-Andre, P. and J. Hodges, "Representation and
tls-server-id-	<u>Verification of Domain-Based Application Server</u>
check]	<u>Identity in Certificates Used with Transport Layer</u>
	<pre>Security," draft-saintandre-tls-server-id-check-06</pre>
	(work in progress), June 2010 (TXT).

Authors' Addresses

Kathleen M	1. Moriarty
RSA, The S	Security Division of EMC

	174 Middlesex Turnpike
	Bedford MA 01730
	United States
Email:	Moriarty_Kathleen@EMC.com
	Brian H. Trammell
	Swiss Federal Institute of Technology Zurich
	Gloriastrasse 35
	8092 Zurich
	Switzerland
Phone:	+41 44 632 70 13
Email:	trammell@tik.ee.ethz.ch