Independent Submission Internet-Draft Intended status: Standards Track Expires: September 6, 2020 K. Murchison FastMail March 5, 2020

JMAP for Sieve Scripts draft-murchison-jmap-sieve-01

Abstract

This document specifies a data model for managing Sieve scripts on a server using JMAP.

Open Issues

- o How should doing /set{create} with an existing script name be handled? Should it fail or overwrite the existing script? Should the /set request include an 'overwrite' boolean argument?
- o Should setting isActive==true on a script automatically deactivate any other existing active script, or should the client have to do so itself (as is currently documented)?
- o Do we want/need a SieveScript/copy method?
- o Do we want to leverage <u>draft-ietf-jmap-quotas</u> to query Sieve script storage quotas?

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>https://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 6, 2020.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>https://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

<u>1</u> . Introduction	<u>2</u>
<u>1.1</u> . Notational Conventions	<u>3</u>
<u>1.2</u> . Terminology	<u>3</u>
<u>1.3</u> . Addition to the Capabilities Object	<u>3</u>
<pre>1.3.1. urn:ietf:params:jmap:sieve</pre>	<u>3</u>
<u>2</u> . Sieve Scripts	<u>4</u>
<pre>2.1. SieveScript/get</pre>	<u>5</u>
<pre>2.2. SieveScript/set</pre>	<u>5</u>
<pre>2.3. SieveScript/validate</pre>	<u>5</u>
<u>3</u> . Security Considerations	<u>6</u>
$\underline{4}$. IANA Considerations	<u>6</u>
<u>4.1</u> . JMAP Capability Registration for "sieve"	<u>6</u>
<u>4.2</u> . JMAP Error Codes Registry	<u>7</u>
<u>4.2.1</u> . scriptIsActive	<u>7</u>
<u>5</u> . Acknowledgments	<u>7</u>
<u>6</u> . References	<u>7</u>
<u>6.1</u> . Normative References	<u>7</u>
<u>6.2</u> . Informative References	<u>8</u>
<u>Appendix A</u> . Change History (To be removed by RFC Editor before	
publication)	<u>8</u>
Author's Address	<u>8</u>

<u>1</u>. Introduction

JMAP ([<u>RFC8620</u>] - JSON Meta Application Protocol) is a generic protocol for synchronizing data, such as mail, calendars or contacts, between a client and a server. It is optimized for mobile and web environments, and aims to provide a consistent interface to different data types. Murchison

Expires September 6, 2020

[Page 2]

This specification defines a data model for managing Sieve [RFC5228] scripts on a server using JMAP. The data model is designed to allow a server to provide consistent access to the same scripts via ManageSieve [RFC5804] as well as JMAP, however the functionality offered over the two protocols may differ.

<u>1.1</u>. Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in <u>BCP</u> <u>14</u> [<u>RFC2119</u>] [<u>RFC8174</u>] when, and only when, they appear in all capitals, as shown here.

Type signatures, examples, and property descriptions in this document follow the conventions established in <u>Section 1.1 of [RFC8620]</u>. Data types defined in the core specification are also used in this document.

<u>1.2</u>. Terminology

The same terminology is used in this document as in the core JMAP specification, see [RFC8620], Section 1.6.

The term SieveScript (with this specific capitalization) is used to refer to the data type defined in this document and instances of those data types.

<u>1.3</u>. Addition to the Capabilities Object

The capabilities object is returned as part of the JMAP Session object; see [RFC8620], Section 2. This document defines one additional capability URI.

<u>1.3.1</u>. urn:ietf:params:jmap:sieve

This represents support for the SieveScript data type and associated API methods. The value of this property in the JMAP Session capabilities property is an empty object.

The value of this property in an account's accountCapabilities property is an object that MUST contain the following information on server capabilities:

o *maxNumberRedirects*: "UnsignedInt|null" The maximum number of Sieve "redirect" actions a script can perform during a single evaluation (see [RFC5804], Section 1.7), or "null" for no limit. Murchison

Expires September 6, 2020

[Page 3]

- o *maxNumberScripts*: "UnsignedInt|null" The maximum number of Sieve scripts the server is willing to store for the user, or "null" for no limit.
- o *maxSizeScript*: "UnsignedInt|null" The maximum size (in octets)
 of a Sieve script the server is willing to store for the user, or
 "null" for no limit.
- o *sieveExtensions*: "String[]" A list of Sieve extensions (as listed in Sieve "require" action [RFC5228], Section 3.2) supported by the Sieve engine.
- o *notificationMethods*: "String[]|null" A list of URI schema parts
 [RFC3986] for notification methods supported by the Sieve
 "enotify" extension [RFC5435], or "null" if the extension is not
 supported by the Sieve engine.
- o *externalLists*: "String[]|null" A list of URI schema parts
 [<u>RFC3986</u>] for externally stored list types supported by the Sieve
 "extlists" extension [<u>RFC6134</u>], or "null" if the extension is not
 supported by the Sieve engine.

2. Sieve Scripts

A *SieveScript* object represents a single script on the server and has the following properties:

- o *id*: "Id" (immutable; server-set) The id of the script.
- o *name*: "String" The user-visible name for the script, subject to the requirements in [RFC5804], Section 1.6.
- o *content*: "String" The Sieve code in the script. Note that any double (") quote or backslash (\) characters appearing in the script content MUST be escaped by prefixing them with a backslash (\).
- o *isActive*: "Boolean" (default: false) Is this the user's active script?

Murchison Expires September 6, 2020 [Page 4]

```
Example (using the Imap4Flags [RFC5232] Extension):
{
    "id": "665c423a-6991-4733-8c7c-52b299572c66",
    "name": "example.siv",
    "content":
        "require [ \"imap4flags\" ];\r\nkeep :flags \"\\\\flagged\";",
    "isActive": false
}
```

2.1. SieveScript/get

This is a standard "/get" method as described in <u>[RFC8620]</u>, <u>Section 5.1</u>. The _ids_ argument may be "null" to fetch all at once.

This method provides similar functionality to the GETSCRIPT and LISTSCRIPTS commands in [<u>RFC5804</u>].

2.2. SieveScript/set

This is a standard "/set" method as described in [RFC8620], Section 5.3.

This method provides similar functionality to the PUTSCRIPT, DELETESCRIPT, RENAMESCRIPT, and SETACTIVE commands in [<u>RFC5804</u>].

Per [RFC5804], Section 1.4, a user may have multiple Sieve scripts on the server, yet only one script may be active. Therefore, when changing the active script, the call to this method MUST both set the _isActive_ argument on the currently active script to "false" and set it to "true" on the script to be activated.

The following extra SetError type is defined:

For "create" and "update":

o *scriptIsActive*: The "isActive" argument was true and the user already has another active script. The SetError object SHOULD also include the *id* property of the currently active script.

2.3. SieveScript/validate

This method is used by the client to verify Sieve script validity without storing the script on the server.

The method provides similar functionality to the CHECKSCRIPT command in [<u>RFC5804</u>].

Murchison

Expires September 6, 2020

[Page 5]

The server MUST check the submitted script for syntactic validity, which includes checking that all Sieve extensions mentioned in Sieve script "require" statement(s) are supported by the Sieve interpreter. (Note that if the Sieve interpreter supports the Sieve "ihave" extension [<u>RFC5463</u>], any unrecognized/unsupported extension mentioned in the "ihave" test MUST NOT cause the syntactic validation failure.)

The *SieveScript/validate* method takes the following arguments:

- o *accountId*: "Id" The id of the account to use.
- o *content*: "String" The Sieve code to validate. Note that any double (") quote or backslash (\) characters appearing in the script content MUST be escaped by prefixing them with a backslash (\).

The response has the following arguments:

- o *accountId*: "Id" The id of the account used for this call.
- o *isValid*: "Boolean" Is the Sieve code valid?
- o *errorDescription*: "String" A description of the error to show to the user, or an empty string if the Sieve code is valid.

3. Security Considerations

All security considerations of JMAP [<u>RFC8620</u>] apply to this specification.

4. IANA Considerations

4.1. JMAP Capability Registration for "sieve"

IANA will register the "sieve" JMAP Capability as follows:

Capability Name: "urn:ietf:params:jmap:sieve"

Specification document: this document

Intended use: common

Change Controller: IETF

Security and privacy considerations: this document, Section 3

Murchison Expires September 6, 2020 [Page 6]

4.2. JMAP Error Codes Registry

The following sub-section registers a new error code in the JMAP Error Codes registry, as defined in [<u>RFC8620</u>].

4.2.1. scriptIsActive

JMAP Error Code: scriptIsActive

Intended use: common

Change controller: IETF

Reference: This document, section 2.5

Description: The client tried to activate a Sieve script, but another acript is already active.

5. Acknowledgments

The concepts in this document are based largely on those in [<u>RFC5804</u>]. The author would like to thank the authors of that document for providing both inspiration and some borrowed text for this document.

<u>6</u>. References

6.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, DOI 10.17487/RFC2119, March 1997, <<u>https://www.rfc-editor.org/info/rfc2119</u>>.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, <u>RFC 3986</u>, DOI 10.17487/RFC3986, January 2005, <<u>https://www.rfc-editor.org/info/rfc3986</u>>.
- [RFC5228] Guenther, P., Ed. and T. Showalter, Ed., "Sieve: An Email Filtering Language", <u>RFC 5228</u>, DOI 10.17487/RFC5228, January 2008, <<u>https://www.rfc-editor.org/info/rfc5228</u>>.
- [RFC5435] Melnikov, A., Ed., Leiba, B., Ed., Segmuller, W., and T. Martin, "Sieve Email Filtering: Extension for Notifications", <u>RFC 5435</u>, DOI 10.17487/RFC5435, January 2009, <<u>https://www.rfc-editor.org/info/rfc5435</u>>.

Murchison Expires September 6, 2020 [Page 7]

- [RFC5804] Melnikov, A., Ed. and T. Martin, "A Protocol for Remotely Managing Sieve Scripts", <u>RFC 5804</u>, DOI 10.17487/RFC5804, July 2010, <<u>https://www.rfc-editor.org/info/rfc5804</u>>.
- [RFC6134] Melnikov, A. and B. Leiba, "Sieve Extension: Externally Stored Lists", <u>RFC 6134</u>, DOI 10.17487/RFC6134, July 2011, <<u>https://www.rfc-editor.org/info/rfc6134</u>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in <u>RFC</u> 2119 Key Words", <u>BCP 14</u>, <u>RFC 8174</u>, DOI 10.17487/RFC8174, May 2017, <<u>https://www.rfc-editor.org/info/rfc8174</u>>.
- [RFC8620] Jenkins, N. and C. Newman, "The JSON Meta Application Protocol (JMAP)", <u>RFC 8620</u>, DOI 10.17487/RFC8620, July 2019, <<u>https://www.rfc-editor.org/info/rfc8620</u>>.

<u>6.2</u>. Informative References

- [RFC5232] Melnikov, A., "Sieve Email Filtering: Imap4flags Extension", <u>RFC 5232</u>, DOI 10.17487/RFC5232, January 2008, <<u>https://www.rfc-editor.org/info/rfc5232</u>>.
- [RFC5463] Freed, N., "Sieve Email Filtering: Ihave Extension", <u>RFC 5463</u>, DOI 10.17487/RFC5463, March 2009, <https://www.rfc-editor.org/info/rfc5463>.
- <u>Appendix A</u>. Change History (To be removed by RFC Editor before publication)

Changes since -00:

- o Added IANA registration for "scriptIsActive" JMAP error code.
- o Added open issue about /set{create} with an existing script name.

Author's Address

Kenneth Murchison Fastmail US LLC 1429 Walnut Street - Suite 1201 Philadelphia, PA 19102 USA

Email: murch@fastmailteam.com

Murchison Expires September 6, 2020 [Page 8]