

Network Working Group
Internet-Draft
Intended status: Informational
Expires: January 13, 2014

S. Nandakumar
C. Jennings
Cisco
July 12, 2013

SDP for the WebRTC
draft-nandakumar-rtcweb-sdp-02

Abstract

The Web Real-Time Communication (WebRTC) [[WEBRTC](#)] working group is charged to provide protocol support for direct interactive rich communication using audio, video and data between two peers' web browsers. Within the WebRTC framework, Session Description protocol (SDP) [[RFC4566](#)] is used for negotiating session capabilities between the peers. Such a negotiation happens based on the SDP Offer/Answer exchange mechanism described in the [RFC 3264](#) [[RFC3264](#)].

This document serves an introductory purpose in describing the role of SDP for the most common WebRTC use-cases.

The SDP examples provided in this document are still a work in progress, but aim to align closest to the evolving standards.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 13, 2014.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal

Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1. Introduction](#) [3](#)
- [2. Terminology](#) [3](#)
- [3. SDP and the WebRTC](#) [3](#)
- [4. Offer/Answer and the WebRTC](#) [4](#)
- [5. WebRTC Session Description Examples](#) [5](#)
 - [5.1. Secure Two-Way Audio,Video and Data with RTCP Feedback . .](#) [5](#)
 - [5.2. Secure Two-way Audio,Video,Data and remove data stream . .](#) [11](#)
 - [5.3. Secure Two-Way Audio,Video with BUNDLE Support Unknown . .](#) [15](#)
 - [5.4. Secure Two-Way Audio,Video w/BUNDLE Support Known](#) [22](#)
 - [5.5. Secure Two-Way Audio,Video w/BUNDLE Unsupported](#) [26](#)
 - [5.6. Successful One Way Session with 2 Video Streams](#) [30](#)
 - [5.7. Sendonly Simulcast w/2 cameras and 2 encodings per camera](#) [34](#)
 - [5.8. Successful SVC Video Stream](#) [40](#)
 - [5.9. Successful Simulcast Video Streams with Retransmission . .](#) [44](#)
 - [5.10. Successful 1-way Simulcast with 2 resolutions and RTX - One resolution rejected](#) [48](#)
 - [5.11. Simulcast Video Stream with Forward Error Correction . . .](#) [52](#)
- [6. WebRTC <-> Legacy Interop Examples](#) [56](#)
 - [6.1. Successful legacy Interop Fallback with bundle-only . . .](#) [56](#)
- [7. IANA Considerations](#) [61](#)
- [8. Change Log](#) [61](#)
- [9. References](#) [62](#)
 - [9.1. Normative References](#) [62](#)
 - [9.2. Informative References](#) [62](#)
- [Authors' Addresses](#) [64](#)

1. Introduction

Javascript Session Exchange Protocol(JSEP) [[JSEP](#)] specifies a generic protocol needed to generate [[RFC3264](#)] offers and answers negotiated between the WebRTC peers for setting up, updating and tearing down a multimedia session. For this purpose, SDP is used to construct [[RFC3264](#)] offers/answers for describing (media and non-media) streams as appropriate for recipients of a session description to participate in the session.

The remainder of this document is organized as follows: [Section 3](#) and 4 provides an overview of SDP and the Offer/Answer exchange mechanism. [Section 5](#) and 6 provide sample SDP usages for the most common WebRTC use-cases.

2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

3. SDP and the WebRTC

The purpose of this section is to provide a general overview of SDP and its components. For a more in-depth understanding, the readers are advised to refer to [[RFC4566](#)].

The Session Description Protocol (SDP) [[RFC4566](#)] describes multimedia sessions, which can be audio, video, whiteboards, fax, modem, and other streams. It provides a general purpose, standard representation to describe various aspects of multimedia session such as media capabilities, transport addresses and related metadata in a transport agnostic manner, for the purposes of session announcement, session invitation and parameter negotiation.

As of today SDP is widely used in the context of Session Initiation Protocol, Real-time Transport Protocol and Real-time Streaming Protocol.

Below figure introduces high-level breakup of SDP into components that semantically describe a multimedia session, in our case, say, a WebRTC session [[WEBRTC](#)]. It by no means captures everything about SDP and hence, should be used for informational purposes only.

[[WEBRTC](#)] proposes JavaScript application to fully control the signaling plane of a multimedia session as described in the JSEP

specification [[JSEP](#)]. JSEP provides mechanisms to create session characterisation and media definition information to conduct the session based on SDP exchanges.

In this context,SDP serves two purposes:

- Provide grammatical structure syntatically

- Semantically convey partipant's intention and capabilities.

4. Offer/Answer and the WebRTC

This section introduces SDP Offer/Answer Exchange mechanism mandated by WebRTC for negotitating session capabilities while setting up,updating and tearing down a WebRTC session. This section is intentionally brief in nature and interested readers are recommended to [[RFC3264](#)] for specific details on the protocol operation.

The Offer/Answer [[RFC3264](#)] model specifies rule for the bilateral exchange of Session Description Protocol (SDP) messages for creation of multimedia streams. It defines protocol with involved participants exchanging desired session characteristics from each others perspective modelled on SDP to negotiate the session between them.

In the most basic form,the protocol operation begins by one of the participants sending an initial SDP offer describing its intent to start a multimedia communication session. The participant receiving the offer MAY generate an SDP answer accepting the offer or it MAY reject the offer. If the session is accepted the Offer/Answer model guarantees a common view of the multimedia session between the participants.

At any time, either participant MAY generate a new SDP offer that updates the session in progress.

With in the context of WebRTC, the Offer/Answer model defines the state-machinery for WebRTC peers to negotiate session descriptions between them during the initial setup stages as well as for eventual session updates. Javascript Session Establishment Protocol specification [[JSEP](#)] for WebRTC provides the mechanism for generating [[RFC3264](#)] SDP offers and answers in order for both sides of the session to agree upon details such as list of media formats to be sent/received, bandwidth information, crypto parameters, transport parameters, for example.

The following sections provide samples of SDP message details and exchanges for the most common WebRTC usecases.

5. WebRTC Session Description Examples

A typical web based real-time multimedia communication session can be characterized as below:

- It has zero or more Audio only, Video only or Audio/Video Media streams
- MAY contain zero or more non-media data streams
- All the streams are secured with DTLS/SRTP
- ICE processing for NAT Traversal
- Sessions over IPv4-only, IPv6-only, dual-stack based clients.

As mentioned earlier [[WEBRTC](#)] proposes using SDP based Offer/Answer model to negotiate multimedia session between peers' browsers. Building on the concepts from the previous sections, the following subsections attempt to describe the usage of SDP for the most common WebRTC use-cases.

In all the use-cases, Alice and Bob are assumed to be the WebRTC peers unless mentioned otherwise. Pointers to appropriate RFCs and notes are provided, wherever necessary, against the SDP lines.

5.1. Secure Two-Way Audio, Video and Data with RTCP Feedback

This use-case allows two users to participate in a two-way communication session securely on their WebRTC enabled Web browsers.

```

title WebRTC Session - 2-Way Secure Audio, Video with RTCP Feedback
Alice->Bob: Offer(Audio:G.711,Opus,iLBC Video:H.264,VP8)
Bob->Alice: Answer(Audio:Opus,DTMF Video:H.264)
Alice->Bob: Two-way Opus Audio, H.264 Video
note right of Alice
  Session also supports RTP/RTCP Mux, RTCP feedback (nack,pli)
end note

```

More specifically, this use-case demonstrates following aspects of a WebRTC session

- SRTP with DTLS based encryption
- RTP and RTCP Muxing
- RTCP based feedback and reduced size support
- ICE processing for NAT Traversal
- Audio Codec Offered : PCMU, Opus, iLBC
- Audio Codec Answered : Opus
- Video Codecs Offered: H.264, VP8
- Video Codecs Answered: H.264
- Data Channel Support

The tables (5.1 and 5.2) below capture in detail, the initial SDP Offer and Answer messages exchanged.

The exact SDP parameters specified for Data-Channel is still under the WG discussion and is expected to be updated once the final decision is reached..

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20518 0 IN IP4 0.0.0.0	[RFC4566] - Session Origin Information
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245] - Session Level ICE parameter
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245] - Session Level ICE parameter
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c7:7 0:9d:1f:66:79:a8:07	[RFC5245] - Session DTLS Fingerprint for SRTP
a=rtcp-rsize	[RFC5506] - Alice intends to use reduced size RTCP for this session
m=audio 54609 RTP/SAVPF 0 109 98	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
a=rtpmap:0 PCMU/8000	[RFC3551] G.711 Audio Codec
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rt p-opus] - Opus Codec 48khz, 2 channels
a=ptime:20	[draft-ietf-payload-rt p-opus] - Opus packetization of 20ms
a=rtpmap:98 iLBC/8000	[RFC3952] - Internet Low Bitrate Codec
a=fmtp:98 mode=20	[RFC3952]
a=sendrecv	[RFC3264] - Alice can send and recv audio
a=rtcp-mux	[RFC5761] - Alice can perform RTP/RTCP Muxing on port 54609
b=AS:64	[RFC4566] - Audio Session B/W of 64kbps

b=RS:800	[RFC3556] - RTCP b/w
	allocated to active
	data senders
b=RR:2400	[RFC3556] - RTCP b/w
	allocated to receivers
a=candidate:0 1 UDP 2113667327	[RFC5245] - Host ICE
192.168.1.4 54609 typ host	Candidate
a=candidate:1 1 UDP 694302207	[RFC5245] - Server
24.23.204.141 54609 typ srflx raddr	Reflexive ICE
192.168.1.4 rport 54609	Candidate for the
	above host candidate
a=candidate:0 2 UDP 2113667326	[RFC5245] - Second
192.168.1.4 64678 typ host	Host Candidate
a=candidate:1 2 UDP 1694302206	[RFC5245] - Server
24.23.204.141 64678 typ srflx raddr	Reflexive Candidate
192.168.1.4 rport 64678	for the Second Host
	Candidate
a=rtcp-fb:109 nack	[RFC5104] - Indicates
	NACK RTCP feedback
	support
m=video 62537 RTP/SAVPF 99 120	[RFC4566]
a=msid:ma tb	Identifies
	RTCMediaStream ID (ma)
	and
	RTCMediaStreamTrack ID
	(tb)
c= IN IP4 24.23.204.141	[RFC4566]
a=rtpmap:99 H264/90000	[RFC3984] - H.264
	Video Codec
a=fmtp:99	[RFC3984]
profile-level-id=4d0028;packetization-mode=1	
a=rtpmap:120 VP8/90000	[draft-ietf-payload-vp
	8] - VP8 video codec
a=sendrecv	[RFC3264] - Alice can
	send and recv video
a=rtcp-mux	[RFC5761] - Alice can
	perform RTP/RTCP
	Muxing on port 62537
b=AS:256	[RFC4566] - Audio
	Session B/W of 256kbps
b=RS:800	[RFC3556] - RTCP b/w
	allocated to active
	data senders
b=RR:2400	[RFC3556] - RTCP b/w
	allocated to receivers
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 62537 typ host	

a=candidate:1 1 UDP 1694302207	[RFC5245]
24.23.204.141 62537 typ srflx raddr	
192.168.1.4 rport 62537	
a=candidate:0 2 2113667326 192.168.1.4	[RFC5245]
54721 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 54721 typ srflx raddr	
192.168.1.4 rport 54721	
a=rtcp-fb:99 nack pli	[RFC5104] - Indicates
	support for Picture
	loss Indication and
	NACK
a=rtcp-fb:99 ccm fir	[RFC5104] - Full Intra
	Frame Request-Codec
	Control Message
	support
a=rtcp-fb:120 nack pli	[RFC5104] - Indicates
	support for Picture
	loss Indication and
	NACK
a=rtcp-fb:120 ccm fir	[RFC5104] - Full Intra
	Frame Request-Codec
	Control Message
	support
m=application 56966 DTLS/SCTP 5000	[draft-ietf-rtcweb-dat
	a-channel]
c= IN IP4 24.23.204.141	[RFC4566]
a=sctpmap:5000 webrtc-Datachannel 1	[draft-ietf-mmusic-sct
	p-sdp] - One data
	stream of type chat
a=webrtc-Datachannel:5000	[draft-ietf-mmusic-sct
stream=1;label="channel	p-sdp]
1";subprotocol="chat";	
a=sendrecv	[RFC3264] - Alice can
	send and recv
	non-media data
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.7 56966 typ host	
a=candidate:1 1 UDP 1694302207	[RFC5245]
24.23.204.141 56966 typ srflx raddr	
192.168.1.7 rport 56966	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.7 51641 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 51641 typ srflx raddr	
192.168.1.7 rport 51641	

+-----+-----+

Table 1: 5.1 SDP Offer

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=bob 16833 0 IN IP4 0.0.0.0	[RFC4566] - Session Origin Information
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:c300d85b	[RFC5245] - Session Level ICE username frag
a=ice-pwd:de4e99bd291c325921d5d47efbabd9a2	[RFC5245] - Session Level ICE password
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c7:70 :9d:1f:66:79:a8:07	[RFC5245] - Session DTLS Fingerprint for SRTP
a=rtcp-rsize	[RFC5506] - Alice intends to use reduced size RTCP for this session
m=audio 49203 RTP/SAVPF 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 98.248.92.77	[RFC4566]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus] - Bob accept only Opus Codec
a=ptime:20	[draft-ietf-payload-rtp-opus]
a=sendrecv	[RFC3264] - Bob can send and recv audio
a=rtcp-mux	[RFC5761] - Bob can perform RTP/RTCP Muxing on port 49203
b=AS:64	[RFC4566] - Audio Session b/w of 64kbps
b=RS:800	[RFC3556] - RTCP b/w allocated to active data senders
b=RR:2400	[RFC3556] - RTCP b/w allocated to receivers

a=candidate:0 1 UDP 2113667327	[RFC5245] - Host ICE
192.168.1.7 49203 typ host	Candidate for Opus
	Stream
a=ccandidate:1 1 UDP 1694302207	[RFC5245] - Server
98.248.92.77 49203 typ srflx raddr	Reflexive ICE
192.168.1.7 rport 49203	Candidate for the
	above host candidate
a=candidate:0 2 UDP 2113667326	[RFC5245] - Second
192.168.1.7 60065 typ host	Host Candidate
a=candidate:1 2 UDP 1694302206	[RFC5245] - Server
98.248.92.77 60065 typ srflx raddr	Reflexive Candidate
192.168.1.7 rport 60065	for the Second Host
	Candidate
m=video 63130 RTP/SAVPF 99	[RFC4566]
a=msid:ma tb	Identifies
	RTCMediaStream ID
	(ma) and
	RTCMediaStreamTrack
	ID (tb)
c= IN IP4 98.248.92.771	[RFC4566]
a=rtpmap:99 H264/90000	[RFC3984] - Bob
	accepts H.264 Video
	Codec.
a=fmtp:99	[RFC3984]
profile-level-id=4d0028;packetization-mod	
e=1	
a=sendrecv	[RFC3264] - Bob can
	send and recv video
a=rtcp-mux	[RFC5761] - Bob can
	perform RTP/RTCP
	Muxing on port 63130
b=AS:256	[RFC4566] - Audio
	Session B/W of
	256kbps
b=RS:800	[RFC3556] - RTCP b/w
	allocated to active
	data senders
b=RR:2400	[RFC3556] - RTCP b/w
	allocated to
	receivers
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.7 63130 typ host	
a=candidate:1 1 UDP 1694302207	[RFC5245]
98.248.92.77 63130 typ srflx raddr	
192.168.1.7 rport 63130	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.7 56607 typ host	

a=candidate:1 2 UDP 1694302206	[RFC5245]
98.248.92.77 56607 typ srflx raddr	
192.168.1.7 rport 56607	
a=rtcp-fb:99 nack pli	[RFC5104] - Indicates
	support for Picture
	loss Indication and
	NACK
a=rtcp-fb:99 ccm fir	[RFC5104] - Full
	Intra Frame
	Request-Codec Control
	Message support
m=application 55700 DTLS/SCTP 5000	[draft-ietf-mmusic-sc
	tp-sdp]
c= IN IP4 98.248.92.771	[RFC4566]
a=sctpmap:5000 webrtc-Datachannel 1	[draft-ietf-mmusic-sc
	tp-sdp]
a=webrtc-Datachannel:5000	[draft-ietf-mmusic-sc
stream=1;label="channel	tp-sdp]
1";subprotocol="chat";	
a=sendrecv	[RFC3264] - Bob can
	send and recv
	non-media data
a=candidate:0 1 UDP 2113667327	[RFC5245] - Refer 4.1
192.168.1.7 55700 typ host	SDP Offer
a=candidate:1 1 UDP 1694302207	[RFC5245] Refer 4.1
98.248.92.77 55700 typ srflx raddr	SDP Offer
192.168.1.7 rport 55700	
a=candidate:0 2 UDP 2113667326	[RFC5245] Refer 4.1
192.168.1.7 58137 typ host	SDP Offer
a=candidate:1 2 UDP 1694302206	[RFC5245] Refer 4.1
98.248.92.77 58137 typ srflx raddr	SDP Offer
192.168.1.7 rport 581371	

Table 2: 5.1 SDP Answer

5.2. Secure Two-way Audio, Video, Data and remove data stream

This scenario builds upon from the usecase in the [section 5.1](#) It extends by Alice removing data-stream once the session is in progress.

There is an ongoing discussion with in the working group to allow addition and deletion of streams using partial Offer/Answer exchanges based on m=lines. Once a final decision is reached, the following example shall be updated to reflect the same.

title WebRTC Session (Audio,Video,Datachannel) - Drop Datachannel
note right of Alice

Alice & Bob are in a two-way audio,video and datachannel session.

Alice decides to stop the datachannel stream

end note

Alice->Bob: Offer(Audio:Opus Video:VP8, Application: Drop)

Bob->Alice: Answer(Audio:Opus Video:VP8, Application:Drop)

Alice->Bob: Two-way Opus Audio and VP8 Video

As a precondition, A Two-Way Audio,Video and Data Session is already setup.

SDP Contents	RFC#/Notes
v=1	[RFC4566] Incremented version to indicate the update
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c7:70 :9d:1f:66:79:a8:07	[RFC5245]
a=rtcp-rsize	[RFC5506]
m=audio 54609 RTP/SAVPF 0 109 98	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
a=ptime:20	[draft-ietf-payload-rtp-opus]
a=rtpmap:98 iLBC/8000	[RFC3952] - Internet Low Bitrate Codec
a=fmtp:98 mode=20	[RFC3952]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327 192.168.1.4 54609 typ host	[RFC5245]

a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.141 54609 typ srflx raddr	
192.168.1.4 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.4 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 64678 typ srflx raddr	
192.168.1.4 rport 64678	
a=rtcp-fb:109 nack	[RFC5104]
m=video 62537 RTP/SAVPF 99 120	[RFC4566]
a=msid:ma tb	Identifies
	RTCMediaStream ID
	(ma) and
	RTCMediaStreamTrack
	ID (tb)
c= IN IP4 24.23.204.141	[RFC4566]
a=rtpmap:99 H264/90000	[RFC3984]
a=fmtp:99	[RFC3984]
profile-level-id=4d0028;packetization-mod	
e=1	
a=rtpmap:120 VP8/90000	[draft-ietf-payload-v
	p8]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 62537 typ host	
a=candidate:1 1 UDP 1694302207	[RFC5245]
24.23.204.141 62537 typ srflx raddr	
192.168.1.4 rport 62537	
a=candidate:0 2 2113667326 192.168.1.4	[RFC5245]
54721 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 54721 typ srflx raddr	
192.168.1.4 rport 54721	
a=rtcp-fb:99 nack pli	[RFC5104]
a=rtcp-fb:99 ccm fir	[RFC5104]
a=rtcp-fb:120 nack pli	[RFC5104]
a=rtcp-fb:120 ccm fir	[RFC5104]
m=application 0 DTLS/SCTP 5000	[draft-ietf-mmusic-sc
	tp-sdp] - Port 0
	indicates dropping
	data stream
c= IN IP4 24.23.204.141	[RFC4566]
a=sctmap:5000 webrtc-Datachannel 1	[draft-ietf-mmusic-sc
	tp-sdp]
a=webrtc-Datachannel:5000	[draft-ietf-mmusic-sc
stream=1;label="channel	tp-sdp]
1";subprotocol="chat";	

| a=sendrecv | [[RFC3264](#)] |
 +-----+-----+

Table 3: 5.2 SDP Updated Offer w/DataChannel Drop

SDP Contents	RFC#/Notes
v=1	[RFC4566]
o=bob 16833 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:c300d85b	[RFC5245]
a=ice-pwd:de4e99bd291c325921d5d47efbabd9a	[RFC5245]
2	
a=fingerprint:sha-1	[RFC5245]
99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c7:70	
:9d:1f:66:79:a8:07	
a=rtcp-rsize	[RFC5506]
m=audio 49203 RTP/SAVPF 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 98.248.92.77	[RFC4566]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-r tp-opus]
a=ptime:20	[draft-ietf-payload-r tp-opus]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.7 49203 typ host	
a=ccandidate:1 1 UDP 1694302207	[RFC5245]
98.248.92.77 49203 typ srflx raddr	
192.168.1.7 rport 49203	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.7 60065 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
98.248.92.77 60065 typ srflx raddr	
192.168.1.7 rport 60065	
m=video 63130 RTP/SAVPF 99	[RFC4566]
a=msid:ma tb	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (tb)

c= IN IP4 98.248.92.771	[RFC4566]	
a=rtpmap:99 H264/90000	[RFC3984]	
a=fmtp:99	[RFC3984]	
profile-level-id=4d0028;packetization-mod		
e=1		
a=sendrecv	[RFC3264]	
a=rtcp-mux	[RFC5761]	
a=candidate:0 1 UDP 2113667327	[RFC5245]	
192.168.1.7 63130 typ host		
a=candidate:1 1 UDP 1694302207	[RFC5245]	
98.248.92.77 63130 typ srflx raddr		
192.168.1.7 rport 63130		
a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.7 56607 typ host		
a=candidate:1 2 UDP 1694302206	[RFC5245]	
98.248.92.77 56607 typ srflx raddr		
192.168.1.7 rport 56607		
a=rtcp-fb:99 nack pli	[RFC5104]	
a=rtcp-fb:99 ccm fir	[RFC5104]	
m=application 0 DTLS/SCTP 5000	[draft-ietf-mmusic-sc]	
	tp-sdp]	Bob accepts
		dropping the data
		stream
c= IN IP4 98.248.92.771	[RFC4566]	
a=sctpmap:5000 webrtc-Datachannel 1	[draft-ietf-mmusic-sc]	
	tp-sdp]	
a=webrtc-Datachannel:5000	[draft-ietf-mmusic-sc]	
stream=1;label="channel	tp-sdp]	
1";subprotocol="chat";		
a=sendrecv	[RFC3264]	

Table 4: 5.2 SDP Updated Answer

5.3. Secure Two-Way Audio, Video with BUNDLE Support Unknown

This use-case demonstrates a successful audio and video media streams multiplexing scenario using SDP BUNDLE negotiation framework [[draft-ietf-mmusic-sdp-bundle-negotiation](#)]

Since Alice is unsure of the Bob's support for BUNDLE framework, the SDP example below shows

- o An SDP Offer, in which the Alice assigns unique addresses to each "m=" line in the BUNDLE group, and requests the Answerer to select the Offerer's BUNDLE address.
- o An SDP Answer, in which the Bob selects the BUNDLE address for the Offerer, and assigns its own local BUNDLE address to each "m=" line in the BUNDLE group.

- o A subsequent SDP Offer from Alice, which is used to perform a BUNDLE Address Synchronization (BAS).

Once the Offer/Answer exchange completes, both Alice and Bob each end up using single RTP Session for both the Media Streams.

title WebRTC Session - 2-Way Secure Audio,Video with BUNDLE

Alice->Bob: Offer(Audio:Opus Video:VP8) with BUNDLE support and unique addresses.

Bob->Alice: Answer(Audio:Opus Video:VP8) indicating its support for BUNDLE

Alice->Bob: Updated Offer(Audio:Opus Video:VP8) for Bundle Address Synchronization.

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20518 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=rtcp-rsize	[RFC5506]
a=group:BUNDLE foo bar	[draft-ietf-mmusic-sdp-bundle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 54609 RTP/SAVPF 109	[RFC4566]
a=mid:foo	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
b=AS:200	[RFC4566]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
a=ptime:20	[draft-ietf-payload-rtp-opus]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:11111	[RFC5576]
a=candidate:0 1 UDP 2113667327 192.168.1.4 54609 typ host	[RFC5245]
a=candidate:1 1 UDP 694302207 24.23.204.141 54609 typ srflx raddr 192.168.1.4 rport 54609	[RFC5245]
a=candidate:0 2 UDP 2113667326	[RFC5245]
a=candidate:1 2 UDP 1694302206 24.23.204.141 64678 typ srflx raddr 192.168.1.4 rport 64678	[RFC5245]
m=video 62537 RTP/SAVPF 120	[RFC4566]

a=mid:bar	[RFC5888] Video m=line
	part of the Bundle group
	with a unique port number
a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
c= IN IP4 24.23.204.141	[RFC4566]
b=AS:1756	[RFC4566]
a=rtptime:120 VP8/90000	[draft-ietf-payload-vp8]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:22222	[RFC5576]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 62537 typ host	
a=candidate:1 1 UDP 1694302207	[RFC5245]
24.23.204.141 62537 typ srflx raddr	
192.168.1.4 rport 62537	
a=candidate:0 2 2113667326	[RFC5245]
192.168.1.4 54721 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 54721 typ srflx raddr	
192.168.1.4 rport 54721	

Table 5: 5.3 SDP Offer w/BUNDLE

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=bob 16833 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:c300d85b	[RFC5245]
a=ice-pwd:de4e99bd291c325921d5d47efb abd9a2	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=rtcp-rsize	[RFC5506]
a=group:BUNDLE foo bar	[draft-ietf-mmusic-sdp-bun dle-negotiation] Bob supports BUNDLE semantics .
m=audio 49203 RTP/SAVPF 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
a=mid:foo	[RFC5888] Audio m=line part of the BUNDLE group
c= IN IP4 98.248.92.77	[RFC4566]
b=AS:200	[RFC4566]
a=rtmpmap:109 opus/48000/2	[draft-ietf-payload-rtp-op us]
aptime:20	[draft-ietf-payload-rtp-op us]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:33333	[RFC5576]
a=candidate:0 1 UDP 2113667327 192.168.1.7 49203 typ host	[RFC5245]
a=candidate:1 1 UDP 1694302207 98.248.92.77 49203 typ srflx raddr 192.168.1.7 rport 49203	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.7 60065 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 98.248.92.77 60065 typ srflx raddr 192.168.1.7 rport 60065	[RFC5245]
m=video 49203 RTP/SAVPF 120	[RFC4566]

a=mid:bar	[RFC5888] Video m=line
	part of the BUNDLE group
	with the port from audio
	line repeated
a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
b=AS:1756	[RFC4566]
c= IN IP4 98.248.92.77	[RFC4566]
a=rtpmap:120 VP8/90000	[draft-ietf-payload-vp8]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:44444	[RFC5576]
a=candidate:0 1 UDP 2113667327	[RFC5245] - Candidate
192.168.1.7 49203 typ host	lines identical with the
	audio m-line.
a=candidate:1 1 UDP 1694302207	[RFC5245]
98.248.92.77 49203 typ srflx raddr	
192.168.1.7 rport 49203	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.7 60065 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
98.248.92.77 60065 typ srflx raddr	
192.168.1.7 rport 60065	

Table 6: 5.3 SDP Answer w/BUNDLE

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20518 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474a f08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=rtcp-rsize	[RFC5506]
a=group:BUNDLE foo bar	[draft-ietf-mmusic-sdp-bun- dle-negotiation]
m=audio 54609 RTP/SAVPF 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and
	RTCMediaStreamTrack ID
a=mid:foo	(ta) [RFC5888] - Port number
	finalized as Bundle Address.
c= IN IP4 24.23.204.141	[RFC4566]
b=AS:200	[RFC4566]
a=rtptime:109 opus/48000/2	[draft-ietf-payload-rtp-op- us]
a=ptime:20	[draft-ietf-payload-rtp-op- us]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:11111	[RFC5576]
a=candidate:0 1 UDP 2113667327 192.168.1.4 54609 typ host	[RFC5245]
a=candidate:1 1 UDP 694302207 24.23.204.141 54609 typ srflx raddr 192.168.1.4 rport 54609	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.4 64678 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 24.23.204.141 64678 typ srflx raddr 192.168.1.4 rport 64678	[RFC5245]
m=video 54609 RTP/SAVPF 120	[RFC4566]
a=msid:ma tb	Identifies RTCMediaStream ID (ma) and
	RTCMediaStreamTrack ID
	(tb)

a=mid:bar	[RFC5888] - Same Bundle
	address from the audio
	m=line
c= IN IP4 24.23.204.141	[RFC4566]
b=AS:1756	[RFC4566]
a=rtpmap:120 VP8/90000	[draft-ietf-payload-vp8]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:22222	[RFC5576]
a=candidate:0 1 UDP 2113667327	[RFC5245] - Candidate
192.168.1.4 54609 typ host	lines identical with the
	audio m-line.
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.141 54609 typ srflx raddr	
192.168.1.4 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.4 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 64678 typ srflx raddr	
192.168.1.4 rport 64678	

Table 7: 5.3 SDP Offer for BAS

5.4. Secure Two-Way Audio, Video w/BUNDLE Support Known

This use-case is a successful audio and video stream multiplexing scenario, with Alice and Bob aware of each others support for SDP BUNDLE framework [[draft-ietf-mmusic-sdp-bundle-negotiation](#)].

title WebRTC Session - 2-Way Secure Audio, Video with BUNDLE Support Known
 Alice->Bob: Offer(Audio:Opus Video:VP8) with identical port numbers
 Bob->Alice: Answer(Audio:Opus Video:VP8) with identical port numbers
 Alice->Bob: Two-way Opus Audio, H.264 Video over a single 5-tuple

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20518 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=rtcp-rsize	[RFC5506]
a=group:BUNDLE foo bar	[draft-ietf-mmusic-sdp-bundle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics.
m=audio 10000 RTP/SAVPF 109 a=msid:ma ta	[RFC4566] Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
a=mid:foo	[RFC5888] - Audio m=line part of BUNDLE group
c= IN IP4 24.23.204.141	[RFC4566]
b=AS:200	[RFC4566]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
a=ptime:20	[draft-ietf-payload-rtp-opus]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:11111	[RFC5576]
a=candidate:0 1 UDP 2113667327 192.168.1.4 10000 typ host	[RFC5245]
a=candidate:1 1 UDP 694302207 24.23.204.141 10000 typ srflx raddr 192.168.1.4 rport 10000	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.4 64678 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 24.23.204.141 64678 typ srflx raddr 192.168.1.4 rport 64678	[RFC5245]
m=video 10000 RTP/SAVPF 120	[RFC4566]

a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
a=mid:bar	[RFC5888] - Video m=line
	with Bundle address same
	as the audio m=line
c= IN IP4 24.23.204.141	[RFC4566]
b=AS:1000	[RFC4566]
a=rtpmap:120 VP8/90000	[draft-ietf-payload-vp8]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:22222	[RFC5576]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 10000 typ host	
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.141 10000 typ srflx raddr	
192.168.1.4 rport 10000	
a=candidate:0 2 2113667326	[RFC5245]
192.168.1.4 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 64678 typ srflx raddr	
192.168.1.4 rport 64678	

Table 8: 5.4 SDP Offer w/BUNDLE

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=bob 16833 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:c300d85b	[RFC5245]
a=ice-pwd:de4e99bd291c325921d5d47efb abd9a2	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=rtcp-rsize	[RFC5506]
a=group:BUNDLE foo bar	[draft-ietf-mmusic-sdp-bun dle-negotiation] - Bob supports BUNDLE semantics .
m=audio 20000 RTP/SAVPF 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
a=mid:foo	[RFC5888] - Audio m=line part of the BUNDLE group
b=AS:200	[RFC4566]
c= IN IP4 98.248.92.77	[RFC4566]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-op us]
aptime:20	[draft-ietf-payload-rtp-op us]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:33333	[RFC5576]
a=candidate:0 1 UDP 2113667327 192.168.1.7 20000 typ host	[RFC5245]
a=candidate:1 1 UDP 1694302207 98.248.92.77 20000 typ srflx raddr 192.168.1.7 rport 20000	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.7 60065 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 98.248.92.77 60065 typ srflx raddr 192.168.1.7 rport 60065	[RFC5245]
m=video 20000 RTP/SAVPF 120	[RFC4566]

a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
a=mid:bar	[RFC5888] - Video m=line
	with Bundle address same
	as the audio m=line
b=AS:1000	[RFC4566]
c= IN IP4 98.248.92.77	[RFC4566]
a=rtpmap:120 VP8/90000	[draft-ietf-payload-vp8]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:44444	[RFC5576]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.7 20000 typ host	
a=candidate:1 1 UDP 1694302207	[RFC5245]
98.248.92.77 20000 typ srflx raddr	
192.168.1.7 rport 20000	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.7 60065 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
98.248.92.77 60065 typ srflx raddr	
192.168.1.7 rport 60065	

Table 9: 5.4 SDP Answer w/BUNDLE

5.5. Secure Two-Way Audio,Video w/BUNDLE Unsupported

This use-case illustrates SDP Offer/Answer exchange when the far-end (Bob) either doesn't support media bundling or doesn't want to group m=lines over a single 5-tuple.

On successful Offer/Answer exchange, Alice and Bob each end up using separate RTP sessions for audio and video media streams respectively.

title WebRTC Session - 2-Way Secure Audio,Video with BUNDLE Unsupported
 Alice->Bob: Offer(Audio:Opus Video:VP8) with BUNDLE support, unique port numbers
 Bob->Alice: Answer(Audio:Opus Video:VP8) with no BUNDLE support, unique port numbers
 Alice->Bob: Two-way Opus Audio, H.264 Video over 2 different RTP sessions.

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20518 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474a f08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=rtcp-rsize	[RFC5506]
a=group:BUNDLE foo bar	[draft-ietf-mmusic-sdp-bun dle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 55232 RTP/SAVPF 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
a=mid:foo	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
c= IN IP4 24.23.204.141	[RFC4566]
b=AS:200	[RFC4566]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-op us]
a=ptime:20	[draft-ietf-payload-rtp-op us]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:11111	[RFC5576]
a=candidate:0 1 UDP 2113667327 192.168.1.4 55232 typ host	[RFC5245]
a=candidate:1 1 UDP 694302207 24.23.204.141 55232 typ srflx raddr 192.168.1.4 rport 55232	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.4 64678 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 24.23.204.141 64678 typ srflx raddr 192.168.1.4 rport 64678	[RFC5245]
m=video 54332 RTP/SAVPF 120	[RFC4566]

a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
a=mid:bar	[RFC5888] Video m=line
	part of the BUNDLE group
	with a unique port number
c= IN IP4 24.23.204.141	[RFC4566]
b=AS:1000	[RFC4566]
a=rtpmap:120 VP8/90000	[draft-ietf-payload-vp8]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:22222	[RFC5576]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 54332 typ host	
a=candidate:1 1 UDP 1694302207	[RFC5245]
24.23.204.141 54332 typ srflx raddr	
192.168.1.4 rport 54332	
a=candidate:0 2 2113667326	[RFC5245]
192.168.1.4 54721 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 54721 typ srflx raddr	
192.168.1.4 rport 54721	

Table 10: 5.5 SDP Offer w/BUNDLE

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=bob 16833 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:c300d85b	[RFC5245]
a=ice-pwd:de4e99bd291c325921d5d47efbabd9a	[RFC5245]
2	
a=fingerprint:sha-1	[RFC5245]
99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c7:70	
:9d:1f:66:79:a8:07	
a=rtcp-rsize	[RFC5506]
m=audio 53214 RTP/SAVPF 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
b=AS:200	[RFC4566]
c= IN IP4 98.248.92.77	[RFC4566]
a=rtptime:109 opus/48000/2	[draft-ietf-payload-r tp-opus]
a=ptime:20	[draft-ietf-payload-r tp-opus]
a=sendrecv	[RFC3264]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.7 53214 typ host	
a=candidate:1 1 UDP 1694302207	[RFC5245]
98.248.92.77 53214 typ srflx raddr	
192.168.1.7 rport 53214	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.7 60065 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
98.248.92.77 60065 typ srflx raddr	
192.168.1.7 rport 60065	
m=video 58679 RTP/SAVPF 120	[RFC4566]
a=msid:ma tb	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (tb)
b=AS:2000	[RFC4566]
c= IN IP4 98.248.92.77	[RFC4566]
a=rtptime:120 VP8/90000	[draft-ietf-payload-v p8]
a=sendrecv	[RFC3264]

a=candidate:0 1 UDP 2113667327	[RFC5245]	
192.168.1.7 58679 typ host		
a=candidate:1 1 UDP 1694302207	[RFC5245]	
98.248.92.77 58679 typ srflx raddr		
192.168.1.7 rport 58679		
a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.7 56607 typ host		
a=candidate:1 2 UDP 1694302206	[RFC5245]	
98.248.92.77 56607 typ srflx raddr		
192.168.1.7 rport 56607		
+-----+-----+-----+		

Table 11: 5.5 SDP Answer without BUNDLE

5.6. Successful One Way Session with 2 Video Streams

In this scenario Alice and Bob engage in one-way multimedia session with Bob receiving two video streams, one corresponding to Alice's video and other corresponding to her presentation slides.

```

title 1 Way Audio & Video w/2 Video Streams
note right of Alice
Alice offers 2 sendonly video streams
one for her video feed and other for her presentation slides.
end note
Alice->Bob: Offer(Audio:Opus, Video1,2: VP8)
note right of Bob
Bob accepts Alice's offer
end note
Bob->Alice: Answer(Audio:Opus, Video1,2: VP8)
Alice->Bob: One-way Opus Audio, VP8 Video
note right of Alice
Bob can hear Alice and see her video feed as well
as her presentation slides.
end note

```


SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c7:70 :9d:1f:66:79:a8:07	[RFC5245]
a=rtcp-rsize	[RFC5506]
m=audio 54609 RTP/SAVPF 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-r tp-opus]
a=ptime:20	[draft-ietf-payload-r tp-opus]
a=sendonly	[RFC3264] - Send only audio stream
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327 192.168.1.4 54609 typ host	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.4 64678 typ host	[RFC5104]
m=video 62537 RTP/SAVPF 120	[RFC4566]
a=msid:ma tb	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (tb)
c= IN IP4 24.23.204.141	[RFC4566]
a=rtpmap:120 VP8/90000	[draft-ietf-payload-v p8]
a=content:speaker	[RFC4796] - Stream 1 for Alice's video
a=sendonly	[RFC3264] - Send only video stream
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327 192.168.1.4 62537 typ host	[RFC5245]

a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.4 54721 typ host		
m=video 62539 RTP/SAVPF 120	[RFC4566]	
a=msid:mb ta	Identifies	
	RTCMediaStream ID	
	(mb) and	
	RTCMediaStreamTrack	
	ID (ta)	
c= IN IP4 24.23.204.141	[RFC4566]	
a=rtpmap:120 VP8/90000	[draft-ietf-payload-v	
	p8]	
a=content:slides	[RFC4796] - Stream 2	
	for Alice's slides	
a=sendonly	[RFC3264] - Send only	
	video stream	
a=rtcp-mux	[RFC5761]	
a=candidate:0 1 UDP 2113667327	[RFC5245]	
192.168.1.4 62539 typ host		
a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.4 54723 typ host		

Table 12: 5.6 SDP Offer

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=bob 16833 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:c300d85b	[RFC5245]
a=ice-pwd:de4e99bd291c325921d5d47efbabd9a2	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c7:70 :9d:1f:66:79:a8:07	[RFC5245]
a=rtcp-rsize	[RFC5506]
m=audio 49203 RTP/SAVPF 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 98.248.92.77	[RFC4566]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-r tp-opus]
a=ptime:20	[draft-ietf-payload-r tp-opus]
a=recvonly	[RFC3264] - Receive only audio stream
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327 192.168.1.7 49203 typ host	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.7 60065 typ host	[RFC5245]
m=video 63130 RTP/SAVPF 120	[RFC4566]
a=msid:ma tb	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (tb)
c= IN IP4 98.248.92.771	[RFC4566]
a=rtpmap:120 VP8/90000	[draft-ietf-payload-v p8]
a=content:speaker	[RFC4796] - Stream 1 for Alice's Video
a=recvonly	[RFC3264] - Receive Only Video Stream 1
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327 192.168.1.7 63130 typ host	[RFC5245]

a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.7 56607 typ host		
m=video 63133 RTP/SAVPF 120	[RFC4566]	
a=msid:mb ta	Identifies	
	RTCMediaStream ID	
	(mb) and	
	RTCMediaStreamTrack	
	ID (ta)	
c= IN IP4 98.248.92.771	[RFC4566]	
a=rtpmap:120 VP8/90000	[draft-ietf-payload-v	
	p8]	
a=content:slides	[RFC4796] - Stream 2	
	for Alice's Slides	
a=recvonly	[RFC3264] - Receive	
	Only Video Stream 2	
a=rtcp-mux	[RFC5761]	
a=candidate:0 1 UDP 2113667327	[RFC5245]	
192.168.1.7 63133 typ host		
a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.7 56609 typ host		
+-----+-----+		

Table 13: 5.6 SDP Answer

5.7. Sendonly Simulcast w/2 cameras and 2 encodings per camera

This SDP below shows Offer/Answer exchange with audio and two video streams each of which can send two different resolutions.

One video stream supports VP8, while the other supports H.264.

bundle-only framework is used along with BUNDLE grouping framework to enable multiplexing of all the 5 streams (audio stream + 4 video streams) over a single RTP Session.

title 1 Way Successful Simulcast

note right of Alice

Alice offers 2 sendonly video streams with 2 simulcast encodings per stream

end note

Alice->Bob: Offer(Audio:Opus,Video1:VP8,Video2:H.264) with bundle-only for video

note left of Bob

Bob accepts Alice's offer and 2 encodings per stream

end note

Alice->Bob: One-Way 1 Opus, 2 H.264 and 2 VP8 video streams.

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=group:BUNDLE m0 m1 m2	[draft-ietf-mmusic-sdp-bundle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
a=ptime:20	[draft-ietf-payload-rtp-opus]
a=sendonly	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:11111	[RFC5576]
a=candidate:0 1 UDP 2113667327 192.168.1.4 54609 typ host	[RFC5245]
a=candidate:1 1 UDP 694302207 24.23.204.141 54609 typ srflx raddr 192.168.1.4 rport 54609	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.4 64678 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 24.23.204.141 64678 typ srflx raddr 192.168.1.4 rport 64678	[RFC5245]
m=video 0 RTP/SAVPF 98 100	bundle-only video line with port number set to zero

a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m1	[RFC5888] Video m=line
	part of BUNDLE group
a=rtpmap:98 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:100 VP8/90000	[draft-ietf-payload-vp8]
a=imageattr:98 [x=1280,y=720]	[RFC6236]Camera-1,Encoding
	-1 Resolution
a=fmtp:98 max-fr=30	[RFC4566]
a=imageattr:100 [x=640,y=480]	[RFC6236]
	Camera-1,Encoding-2
	Resolution
a=fmtp:100 max-fr=15	[RFC4566]
a=ssrc-group:SIMULCAST 12345 45678	[RFC5576]
a=ssrc:12345	[RFC5576]
a=ssrc:45678	[RFC5576]
a=ssrc:12345 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62
	22bis] Camera-1,Encoding-1
	SSRC with Session CNAME
a=ssrc:45678 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62
	22bis] Camera-1,Encoding-2
	SSRC with Session CNAME
a=sendonly	[RFC3264] - Send only
	video stream
a=rtcp-mux	[RFC5761]
a=bundle-only	Add reference to unified
	plan when available
m=video 0 RTP/SAVPF 98 100	bundle-only video line
	with port number set to
	zero
a=msid:ma tc	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tc)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m2	[RFC5888] Video m=line
	part of BUNDLE group
a=rtpmap:98 H264/90000	[RFC3984]
a=rtpmap:100 H264/90000	[RFC3984]
a=fmtp:98	[RFC3984]Camera-2,Encoding
profile-level-id=4d0028;packetizatio	-1 Resolution
n-mode=1;max-fr=30	

a=fmtp:100	[RFC3984] Camera-1, Encoding
profile-level-id=4d0028;packetizatio	-2 Resolution
n-mode=1;max-fr=15	
a=ssrc:67890	[RFC5576]
a=ssrc:56789	[RFC5576]
a=ssrc-group:SIMULCAST 67890 56789	[RFC5576]
a=ssrc:67890 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62
	22bis] Camera-1, Encoding-1
	SSRC with Session CNAME
a=ssrc:56789 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62
	22bis] Camera-1, Encoding-2
	SSRC with Session CNAME
a=sendonly	[RFC3264] - Send only
	video stream
a=rtcp-mux	[RFC5761]
a=bundle-only	Add reference to unified
	plan when available

Table 14: 5.8 SDP Offer

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:ufrag:c300d85b	[RFC5245]
a=ice-pwd:de4e99bd291c325921d5d47efb	[RFC5245]
abd9a2	
a=fingerprint:sha-1	[RFC5245]
99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:	
c7:70:9d:1f:66:79:a8:07	
a=group:BUNDLE m0 m1 m2	[draft-ietf-mmusic-sdp-bun
	dle-negotiation] Alice
	supports grouping of
	m=lines under BUNDLE
	semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line
	part of BUNDLE group with
	a unique port number

a=msid:ma ta	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(ta)
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-op
	us]
a=ptime:20	[draft-ietf-payload-rtp-op
	us]
a=sendonly	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:22222	[RFC5576]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 54609 typ host	
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.141 54609 typ srflx raddr	
192.168.1.4 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.4 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 64678 typ srflx raddr	
192.168.1.4 rport 64678	
m=video 54609 RTP/SAVPF 98 100	BUNDLE accepted with port
	repeated from the audio
	port
a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m1	[RFC5888] Video m=line
	part of BUNDLE group
a=rtpmap:98 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:100 VP8/90000	[draft-ietf-payload-vp8]
a=imageattr:98 [x=1280,y=720]	[RFC6236] Camera-1, Encoding
	-1 Resolution
a=fmtp:98 max-fr=30	[RFC4566]
a=imageattr:100 [x=640,y=480]	[RFC6236]
	Camera-1, Encoding-2
	Resolution
a=fmtp:100 max-fr=15	[RFC4566]
a=ssrc-group:SIMULCAST 54321 87654	[RFC5576]
a=ssrc:54321	[RFC5576]
a=ssrc:87654	[RFC5576]
a=ssrc:54321 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62
	22bis] Camera-1, Encoding-1
	SSRC with Session CNAME

a=ssrc:87654 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62]
	22bis] Camera-1,Encoding-2
	SSRC with Session CNAME
a=sendonly	[RFC3264] - Send only
	video stream
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 54609 typ host	
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.141 54609 typ srflx raddr	
192.168.1.4 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.4 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 64678 typ srflx raddr	
192.168.1.4 rport 64678	
a=rtcp-mux	[RFC5576]
a=bundle-only	Add reference to unified
	plan when available
m=video 54609 RTP/SAVPF 98 100	BUNDLE accepted with port
	repeated from the audio
	port
c= IN IP4 24.23.204.141	[RFC4566]
a=msid:ma tc	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tc)
a=mid:m2	[RFC5888] Video m=line
	part of BUNDLE group
a=rtpmap:98 H264/90000	[RFC3984]
a=rtpmap:10 H264/90000	[RFC3984]
a=fmtp:98	[RFC3984]Camera-2,Encoding
profile-level-id=4d0028;packetizatio	-1 Resolution
n-mode=1;max-fr=30	
a=fmtp:100	[RFC3984]Camera-1,Encoding
profile-level-id=4d0028;packetizatio	-2 Resolution
n-mode=1;max-fr=15	
a=ssrc:90876	[RFC5576]
a=ssrc:89754	[RFC5576]
a=ssrc-group:SIMULCAST 90876 89754	[RFC5576]
a=ssrc:90876 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62]
	22bis] Camera-1,Encoding-1
	SSRC with Session CNAME
a=ssrc:89754 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62]
	22bis] Camera-1,Encoding-2
	SSRC with Session CNAME

a=sendonly	[RFC3264] - Send only	
	video stream	
a=candidate:0 1 UDP 2113667327	[RFC5245]	
192.168.1.4 54609 typ host		
a=candidate:1 1 UDP 694302207	[RFC5245]	
24.23.204.141 54609 typ srflx raddr		
192.168.1.4 rport 54609		
a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.4 64678 typ host		
a=candidate:1 2 UDP 1694302206	[RFC5245]	
24.23.204.141 64678 typ srflx raddr		
192.168.1.4 rport 64678		
a=rtcp-mux	[RFC5576]	
a=bundle-only	Add reference to unified	
	plan when available	
+-----+-----+-----+		

Table 15: 5.8 SDP Answer

5.8. Successful SVC Video Stream

This section shows an SDP Offer/Answer for a session with an audio and a single video stream. The video stream is layered coding at 3 different resolutions based on [[RFC5583](#)]. The video m=line shows 3 streams with last stream (payload 100) dependent on streams with payload 96 and 97 for decoding.

```

title 2 way SVC Video
note right of Alice
Alice offers 3 sendonly video stream with 3 layers of SVC
end note
Alice->Bob: Offer(Audio:Opus Video: H.264 SVC) bundle-only
note left of Bob
Bob accepts Alice's Offered Codec operation points
end note
Bob->Alice: Answer(Video: H.264) bundle-only
Alice->Bob: One-Way H.264 Video with codec points as indicated by Bob.
    
```


SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c 7:70:9d:1f:66:79:a8:07	[RFC5245]
a=group:BUNDLE m0 m1	[draft-ietf-mmusic-sdp-bundle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
a=ptime:20	[draft-ietf-payload-rtp-opus]
a=sendonly	[RFC3264]
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327 192.168.1.4 54609 typ host	[RFC5245]
a=candidate:1 1 UDP 694302207 24.23.204.141 54609 typ srflx raddr 192.168.1.4 rport 54609	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.4 64678 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 24.23.204.141 64678 typ srflx raddr 192.168.1.4 rport 64678	[RFC5245]
m=video 0 RTP/SAVPF 96 97 100	bundle-only video line with port number set to zero

a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tc)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m1	[RFC5888] Audio m=line
	part of BUNDLE group
a=msid:ma tb	Add appropriate reference
	when available
b=AS:2500	[RFC4566]
a=rtpmap:96 H264/90000	[RFC3984]
a=fmtp:96	[RFC3984]H.264 Layer 1
profile-level-id=4d0028;packetization	
-mode=1;max-fr=30;max-fs=8040	
a=rtpmap:97 H264/90000	[RFC3984]
a=fmtp:97	[RFC3984] H.264 Layer 2
profile-level-id=4d0028;packetization	
-mode=1;max-fr=15;max-fs=1200	
a=rtpmap:100 H264-SVC/90000	[RFC3984]
a=fmtp:100	[RFC3984]
profile-level-id=4d0028;packetization	
-mode=1;max-fr=30;max-fs=8040	
a=depend:100 lay m1:96,97;	[RFC5583]Layer 3
	dependent on layers 1 and
	2
a=sendonly	[RFC3264] - Send only
	video stream
a=rtcp-mux	[RFC5761]
a=bundle-only	Add reference to unified
	plan when available

Table 16: 5.9 SDP Offer with SVC

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c 7:70:9d:1f:66:79:a8:07	[RFC5245]
a=group:BUNDLE m0 m1	[draft-ietf-mmusic-sdp-bundle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.142	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
a=ptime:20	[draft-ietf-payload-rtp-opus]
a=sendonly	[RFC3264]
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327 192.168.1.5 54609 typ host	[RFC5245]
a=candidate:1 1 UDP 694302207 24.23.204.142 54609 typ srflx raddr 192.168.1.5 rport 54609	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.5 64678 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 24.23.204.142 64678 typ srflx raddr 192.168.1.5 rport 64678	[RFC5245]
m=video 54609 RTP/SAVPF 96 100	BUNDLE accepted Bundle address same as audio m=line.

a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
c= IN IP4 24.23.204.142	[RFC4566]
a=mid:m1	[RFC5888] Video m=line
	part of BUNDLE group
b=AS:2500	[RFC4566]
a=rtpmap:96 H264/90000	[RFC3984]
a=fmtp:96	[RFC3984]H.264 Layer 1
profile-level-id=4d0028;packetization	
-mode=1;max-fr=30;max-fs=8040	
a=rtpmap:100 H264-SVC/90000	[RFC3984]
a=fmtp:100	[RFC3984]
profile-level-id=4d0028;packetization	
-mode=1;max-fr=30;max-fs=8040	
a=depend:100 lay m1:96;	[RFC5583] Bob chooses 2
	Codec Operation points
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.5 54609 typ host	
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.142 54609 typ srflx raddr	
192.168.1.5 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.5 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.142 64678 typ srflx raddr	
192.168.1.5 rport 64678	
a=recvonly	[RFC3264] - Receive only
	video stream
a=rtcp-mux	[RFC5761]
a=bundle-only	Add reference to unified
	plan when available

Table 17: 5.9 SDP Answer with SVC

5.9. Successful Simulcast Video Streams with Retransmission

This section shows an SDP Offer/Answer exchange for a simulcast scenario with 2 two resolutions and has [RFC4588] style retransmission flows.


```

title Simulcast Streams with Retransmission
note right of Alice
Alice offers single audio and simulcasted video stream
end note
Alice->Bob: Offer(Audio:Opus Video:VP8 with 2 resolutions and RTX Stream)
bundle-only
note right of Bob
Bob accepts all the streams offered by Alice
end note
Bob->Alice: Answer(Audio:Opus Video:VP8 with 2 resolutions and RTX Stream)
bundle-only
note right of Alice
Successful 2 way simulcast session with associated retransmission streams
end note

```

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474a f08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=group:BUNDLE m0 m1	[draft-ietf-mmusic-sdp-bun dle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-op us]
a=ptime:20	[draft-ietf-payload-rtp-op us]
a=sendonly	[RFC3264]

| a=rtcp-mux | [[RFC5761](#)] |
| a=ssrc:11111 | [[RFC5576](#)] |

a=candidate:0 1 UDP 2113667327	[RFC5245]	
192.168.1.4 54609 typ host		
a=candidate:1 1 UDP 694302207	[RFC5245]	
24.23.204.141 54609 typ srflx raddr		
192.168.1.4 rport 54609		
a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.4 64678 typ host		
a=candidate:1 2 UDP 1694302206	[RFC5245]	
24.23.204.141 64678 typ srflx raddr		
192.168.1.4 rport 64678		
m=video 0 RTP/SAVPF 98 100 101 103	bundle-only video line	
	with port number set to	
	zero	
a=msid:ma tb	Identifies RTCMediaStream	
	ID (ma) and	
	RTCMediaStreamTrack ID	
	(tb)	
c= IN IP4 24.23.204.141	[RFC4566]	
a=mid:m1	[RFC5888] Audio m=line	
	part of BUNDLE group	
b=AS:1756	[RFC4566]	
a=rtpmap:98 VP8/90000	[draft-ietf-payload-vp8]	
a=rtpmap:100 VP8/90000	[draft-ietf-payload-vp8]	
a=rtpmap:101 VP8/90000	[draft-ietf-payload-vp8]	
a=rtpmap:103 VP8/90000	[draft-ietf-payload-vp8]	
a=fmtp:98 max-fr=30;max-fs=8040	[RFC4566]	
a=fmtp:100 max-fr=15;max-fs=1200	[RFC4566]	
a=fmtp:101 apt=98;rtx-time=3000	[RFC4588]	
a=fmtp:103 apt=100;rtx-time=3000	[RFC4588]	
a=ssrc-group:SIMULCAST 12345 78990	Simulcast group	
a=ssrc-group:FID 12345 34567	[RFC5888]	
a=ssrc-group:FID 78990 90887	[RFC5888]	
a=ssrc:12345	[RFC5576]	
a=ssrc:78990	[RFC5576]	
a=ssrc:34567	[RFC5576]	
a=ssrc:90887	[RFC5576]	
a=sendrecv	[RFC3264]	
a=rtcp-mux	[RFC5761]	
a=bundle-only	Add reference to unified	
	plan when available	

Table 18: 5.10 SDP Offer w/Simulcast, RTX

SDP Contents	RFC#/Notes	
v=0	[RFC4566]	

o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]	
s=	[RFC4566]	
t=0 0	[RFC4566]	
a=ice-ufrag:074c6550	[RFC5245]	
a=ice-pwd:a28a397a4c3f31747d1ee3474a	[RFC5245]	
f08a068		
a=fingerprint:sha-1	[RFC5245]	
99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:		
c7:70:9d:1f:66:79:a8:07		
a=group:BUNDLE m0 m1	[draft-ietf-mmusic-sdp-bun	
	dle-negotiation] Alice	
	supports grouping of	
	m=lines under BUNDLE	
	semantics	
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]	
a=msid:ma ta	Identifies RTCMediaStream	
	ID (ma) and	
	RTCMediaStreamTrack ID	
	(ta)	
c= IN IP4 24.23.204.142	[RFC4566]	
a=mid:m0	[RFC5888] Audio m=line	
	part of BUNDLE group with	
	a unique port number	
a=rtpmap:0 PCMU/8000	[RFC3551]	
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-op	
	us]	
a=ptime:20	[draft-ietf-payload-rtp-op	
	us]	
a=sendonly	[RFC3264]	
a=rtcp-mux	[RFC5761]	
a=ssrc:33333	[RFC5576]	
a=candidate:0 1 UDP 2113667327	[RFC5245]	
192.168.1.5 54609 typ host		
a=candidate:1 1 UDP 694302207	[RFC5245]	
24.23.204.142 54609 typ srflx raddr		
192.168.1.5 rport 54609		
a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.5 64678 typ host		
a=candidate:1 2 UDP 1694302206	[RFC5245]	
24.23.204.142 64678 typ srflx raddr		
192.168.1.5 rport 64678		
m=video 54609 RTP/SAVPF 98 100 101	BUNDLE accepted with	
103	Bundle address identical	
	to audio m-line	
a=msid:ma tb	Identifies RTCMediaStream	
	ID (ma) and	
	RTCMediaStreamTrack ID	
	(tb)	

c= IN IP4 24.23.204.142	[RFC4566]	
a=mid:m1	[RFC5888]	Video m=line
		part of BUNDLE group
b=AS:1756	[RFC4566]	
a=rtpmap:98 VP8/90000	[draft-ietf-payload-vp8]	
a=rtpmap:100 VP8/90000	[draft-ietf-payload-vp8]	
a=rtpmap:101 VP8/90000	[draft-ietf-payload-vp8]	
a=rtpmap:103 VP8/90000	[draft-ietf-payload-vp8]	
a=fmtp:98 max-fr=30;max-fs=8040	[RFC4566]	
a=fmtp:100 max-fr=15;max-fs=1200	[RFC4566]	
a=fmtp:101 apt=98;rtx-time=3000	[RFC4588]	
a=fmtp:103 apt=100;rtx-time=3000	[RFC4588]	
a=candidate:0 1 UDP 2113667327	[RFC5245]	
192.168.1.5 54609 typ host		
a=candidate:1 1 UDP 694302207	[RFC5245]	
24.23.204.142 54609 typ srflx raddr		
192.168.1.5 rport 54609		
a=candidate:0 2 UDP 2113667326	[RFC5245]	
192.168.1.5 64678 typ host		
a=candidate:1 2 UDP 1694302206	[RFC5245]	
24.23.204.142 64678 typ srflx raddr		
192.168.1.5 rport 64678		
a=ssrc-group:SIMULCAST 54321 77656		Simulcast group
a=ssrc-group:FID 54321 88776	[RFC5888]	
a=ssrc-group:FID 77656 12908	[RFC5888]	
a=ssrc:54321	[RFC5576]	
a=ssrc:77656	[RFC5576]	
a=ssrc:88776	[RFC5576]	
a=ssrc:12908	[RFC5576]	
a=sendrecv	[RFC3264]	
a=rtcp-mux	[RFC5761]	
a=bundle-only		Add reference to unified
		plan when available

Table 19: 5.10 SDP Answer w/Simulcast, RTX

5.10. Successful 1-way Simulcast with 2 resolutions and RTX - One resolution rejected

This section shows an SDP Offer/Answer exchange for a simulcast scenario with 2 two resolutions and has [[RFC4588](#)] style re-transmission flows.

It also showcases when Bob rejects one of the Simulcast Video Stream which results in the rejection of the associated repair stream implicitly


```

title Simulcast Streams with Retransmission
note right of Alice
Alice offers single audio and simulcasted video stream
end note
Alice->Bob: Offer(Audio:Opus Video:VP8 with 2 resolutions and RTX Streams)
bundle-only
note right of Bob
Bob accepts one simulcast,rtx and rejects the other
end note
Bob->Alice: Answer(Audio:Opus Video:VP8 with 1 resolution and the RTX Stream)
bundle-only
note right of Alice
Successful 1 way session with 1 Video Stream and the associated RTX Stream
end note
    
```

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=group:BUNDLE m0 m1	[draft-ietf-mmusic-sdp-bundle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
a=ptime:20	[draft-ietf-payload-rtp-opus]
a=sendonly	[RFC3264]

| a=rtcp-mux | [[RFC5761](#)] |
| a=ssrc:11111 | [[RFC5576](#)] |

a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 54609 typ host	
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.141 54609 typ srflx raddr	
192.168.1.4 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.4 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 64678 typ srflx raddr	
192.168.1.4 rport 64678	
m=video 0 RTP/SAVPF 98 100 101 103	bundle-only video line
	with port number set to
	zero
a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m1	[RFC5888] Audio m=line
	part of BUNDLE group
b=AS:1756	[RFC4566]
a=rtpmap:98 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:100 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:101 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:103 VP8/90000	[draft-ietf-payload-vp8]
a=fmtp:98 max-fr=30;max-fs=8040	[RFC4566]
a=fmtp:100 max-fr=15;max-fs=1200	[RFC4566]
a=fmtp:101 apt=98;rtx-time=3000	[RFC4588]
a=fmtp:103 apt=100;rtx-time=3000	[RFC4588]
a=ssrc-group:SIMULCAST 12345 78990	Simulcast group
a=ssrc-group:FID 12345 34567	[RFC5888]
a=ssrc-group:FID 78990 90887	[RFC5888]
a=ssrc:12345	[RFC5576]
a=ssrc:78990	[RFC5576]
a=ssrc:34567	[RFC5576]
a=ssrc:90887	[RFC5576]
a=sendonly	[RFC3264]
a=rtcp-mux	[RFC5761]
a=bundle-only	Add reference to unified
	plan when available

Table 20: 5.11 SDP Offer w/Simulcast, RTX

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=group:BUNDLE m0 m1	[draft-ietf-mmusic-sdp-bundle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.142	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
a=ptime:20	[draft-ietf-payload-rtp-opus]
a=recvonly	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:33333	[RFC5576]
a=candidate:0 1 UDP 2113667327 192.168.1.5 54609 typ host	[RFC5245]
a=candidate:1 1 UDP 694302207 24.23.204.142 54609 typ srflx raddr 192.168.1.5 rport 54609	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.5 64678 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 24.23.204.142 64678 typ srflx raddr 192.168.1.5 rport 64678	[RFC5245]
m=video 54609 RTP/SAVPF 98 101	BUNDLE accepted with Bundle address identical to audio m-line

a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
c= IN IP4 24.23.204.142	[RFC4566]
a=mid:m1	[RFC5888] Video m=line
	part of BUNDLE group
b=AS:1756	[RFC4566]
a=rtpmap:98 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:101 VP8/90000	[draft-ietf-payload-vp8]
a=fmtp:98 max-fr=30;max-fs=8040	[RFC4566]
a=fmtp:101 apt=98;rtx-time=3000	[RFC4588]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.5 54609 typ host	
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.142 54609 typ srflx raddr	
192.168.1.5 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.5 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.142 64678 typ srflx raddr	
192.168.1.5 rport 64678	
a=ssrc-group:FID 54321 88776	[RFC5888]
a=ssrc:54321	[RFC5576]
a=ssrc:88776	[RFC5576]
a=recvonly	[RFC3264]
a=rtcp-mux	[RFC5761]
a=bundle-only	Add reference to unified
	plan when available

Table 21: 5.11 SDP Answer no Simulcast

[5.11.](#) Simulcast Video Stream with Forward Error Correction

This section shows an SDP Offer/Answer exchange for Simulcast video stream at two resolutions and has [[RFC5956](#)] style FEC flows.

On completion of Offer/Answer exchange, one audio stream, 2 simulcast video streams and 2 associated FEC streams are sent over a single 5-Tuple as part of bundle-only and BUNDLE framework.

title Simulcast Streams with Forward Error Correction
 note right of Alice
 Alice offers single audio and simulcasted video stream
 end note
 Alice->Bob: Offer(Audio:Opus Video:VP8 with 2 resolutions with FEC Streams)
 bundle-only
 note right of Bob
 Bob accepts simulcast stream as well as FEC streams
 end note
 Bob->Alice: Answer(Audio:Opus Video:VP8 with 2 resolutions with FEC Streams)
 bundle-only
 note right of Alice
 Successful Session with 4 video streams (Simulcast + FEC) and 1 Audio Stream

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=group:BUNDLE m0 m1	[draft-ietf-mmusic-sdp-bundle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
aptime:20	[draft-ietf-payload-rtp-opus]
a=sendonly	[RFC3264]
a=rtcp-mux	[RFC5761]

| a=ssrc:11111

| [[RFC5576](#)]

|

Nandakumar & Jennings Expires January 13, 2014

[Page 53]

a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 54609 typ host	
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.141 54609 typ srflx raddr	
192.168.1.4 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.4 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 64678 typ srflx raddr	
192.168.1.4 rport 64678	
m=video 0 RTP/SAVPF 98 100 101 103	bundle-only video line
	with port number set to
	zero
a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m1	[RFC5888] Video m=line
	part of BUNDLE group
b=AS:2500	[RFC4566]
a=rtpmap:98 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:100 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:101	[RFC5956]
1d-interleaved-parityfec/90000	
a=rtpmap:103	[RFC5956]
1d-interleaved-parityfec/90000	
a=fmtp:98 max-fr=30;max-fs=8040	[RFC4566]
a=fmtp:100 max-fr=15;max-fs=1200	[RFC4566]
a=fmtp:101 L=5; D=10;	[RFC5956]
repair-window=200000	
a=fmtp:103 L=5; D=10;	[RFC5956]
repair-window=200000	
a=ssrc-group:SIMULCAST 12345 78990	Simulcast group
a=ssrc-group:FEC-FR 12345 34567	[RFC5888]
a=ssrc-group:FEC-FR 78990 90887	[RFC5888]
a=ssrc:12345	[RFC5576]
a=ssrc:78990	[RFC5576]
a=ssrc:34567	[RFC5576]
a=ssrc:90887	[RFC5576]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=bundle-only	Add reference to unified
	plan when available

Table 22: 5.12 SDP Offer

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1 99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9: c7:70:9d:1f:66:79:a8:07	[RFC5245]
a=group:BUNDLE m0 m1	[draft-ietf-mmusic-sdp-bundle-negotiation] Alice supports grouping of m=lines under BUNDLE semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
a=msid:ma ta	Identifies RTCMediaStream ID (ma) and RTCMediaStreamTrack ID (ta)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line part of BUNDLE group with a unique port number
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-opus]
aptime:20	[draft-ietf-payload-rtp-opus]
a=sendonly	[RFC3264]
a=rtcp-mux	[RFC5761]
a=ssrc:33333	[RFC5576]
a=candidate:0 1 UDP 2113667327 192.168.1.4 54609 typ host	[RFC5245]
a=candidate:1 1 UDP 694302207 24.23.204.141 54609 typ srflx raddr 192.168.1.4 rport 54609	[RFC5245]
a=candidate:0 2 UDP 2113667326 192.168.1.4 64678 typ host	[RFC5245]
a=candidate:1 2 UDP 1694302206 24.23.204.141 64678 typ srflx raddr 192.168.1.4 rport 64678	[RFC5245]
m=video 54609 RTP/SAVPF 98 100 101 103	BUNDLE accepted with Bundle Address identical to audio m=line.

a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m1	[RFC5888] Video m=line
	part of BUNDLE group
b=AS:2500	[RFC4566]
a=rtpmap:98 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:100 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:101	[RFC5956]
1d-interleaved-parityfec/90000	
a=rtpmap:103	[RFC5956]
1d-interleaved-parityfec/90000	
a=fmtp:98 max-fr=30;max-fs=8040	[RFC4566]
a=fmtp:100 max-fr=15;max-fs=1200	[RFC4566]
a=fmtp:101 L=5; D=10;	[RFC5956]
repair-window=200000	
a=fmtp:103 L=5; D=10;	[RFC5956]
repair-window=200000	
a=ssrc-group:SIMULCAST 54321 77656	Simulcast group
a=ssrc-group:FEC-FR 54321 88776	[RFC5888]
a=ssrc-group:FEC-FR 77656 12908	[RFC5888]
a=ssrc:54321	[RFC5576]
a=ssrc:77656	[RFC5576]
a=ssrc:88776	[RFC5576]
a=ssrc:12908	[RFC5576]
a=sendrecv	[RFC3264]
a=rtcp-mux	[RFC5761]
a=bundle-only	Add reference to unified
	plan when available

Table 23: 5.12 SDP Offer

6. WebRTC <-> Legacy Interop Examples

In this section, we attempt to provide session descriptions showcasing inter-operability between a WebRTC end-point and a Legacy VOIP end-point. The ideas included in here are not fully baked into the standards yet.

6.1. Successful legacy Interop Fallback with bundle-only

In the scenario described below, Alice is a multi-stream capable WebRTC endpoint while Bob is a legacy VOIP end-point. The SDP Offer/Answer exchange demonstrates successful session setup with fallback

- to audio only stream negotiated via bundle-only framework between the end-points. Specifically,
 - o Offer from Alice describes 2 cameras via 2 video m=lines with both marked as bundle-only.
 - o Since Bob doesnot recognize either BUNDLE mechanism or bundle-only attribute, he accepts only the audio stream from Alice.

```

title Successful 2-Way WebRTC <-> VOIP Interop
note right of Alice
Alice is a multistream capable WebRTC end-point & Bob is behind a legacy VOIP
system
end note
Alice->Bob: Offer(Audio:Opus Video: 2 VP8, 2 H2.64 Streams) with bundle-only
offer
note right of Alice
Alice marks both the video streams as bundle-only
end note
Bob->Alice: Answer(Audio:Opus)
note right of Bob
  Bob accepts only Audio stream since he doesn't recognize
  bundle-only streams
end note
Alice->Bob: Two-way Opus Audio

```

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:074c6550	[RFC5245]
a=ice-pwd:a28a397a4c3f31747d1ee3474af08a068	[RFC5245]
a=fingerprint:sha-1	[RFC5245]
99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:	
c7:70:9d:1f:66:79:a8:07	
a=group:BUNDLE m0 m1 m2	[draft-ietf-mmusic-sdp-bun
	dle-negotiation] Alice
	supports grouping of
	m=lines under BUNDLE
	semantics
m=audio 54609 RTP/SAVPF 0 109	[RFC4566]
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m0	[RFC5888] Audio m=line
	part of BUNDLE group with
	a unique port number

a=msid:ma ta	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(ta)
a=rtpmap:0 PCMU/8000	[RFC3551]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-rtp-op
	us]
a=ptime:20	[draft-ietf-payload-rtp-op
	us]
a=sendonly	[RFC3264]
a=rtcp-mux	[RFC5761]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 54609 typ host	
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.141 54609 typ srflx raddr	
192.168.1.4 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.4 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 64678 typ srflx raddr	
192.168.1.4 rport 64678	
m=video 0 RTP/SAVPF 98 100	bundle-only video line
	with port number set to
	zero
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m1	[RFC5888] Video m=line
	part of BUNDLE group
a=msid:ma tb	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tb)
a=rtpmap:98 VP8/90000	[draft-ietf-payload-vp8]
a=rtpmap:100 VP8/90000	[draft-ietf-payload-vp8]
a=imageattr:98 [x=1280,y=720]	[RFC6236] Camera-1, Encoding
	-1 Resolution
a=fmtp:98 max-fr=30	[RFC4566]
a=imageattr:100 [x=640,y=480]	[RFC6236]
	Camera-1, Encoding-2
	Resolution
a=fmtp:100 max-fr=15	[RFC4566]
a=ssrc-group:SIMULCAST 12345 45678	[RFC5576]
a=ssrc:12345	[RFC5576]
a=ssrc:45678	[RFC5576]
a=ssrc:12345 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62
	22bis] Camera-1, Encoding-1
	SSRC with Session CNAME

a=ssrc:45678 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62
	22bis] Camera-1,Encoding-2
	SSRC with Session CNAME
a=bundle-only	Add reference to unified
	plan when available
m=video 0 RTP/SAVPF 101 103	bundle-only video line
	with port number set to
	zero
c= IN IP4 24.23.204.141	[RFC4566]
a=mid:m2	[RFC5888] Video m=line
	part of BUNDLE group
a=msid:ma tc	Identifies RTCMediaStream
	ID (ma) and
	RTCMediaStreamTrack ID
	(tc)
a=rtpmap:101 H264/90000	[RFC3984]
a=rtpmap:103 H264/90000	[RFC3984]
a=fmtp:101	[RFC3984]Camera-2,Encoding
profile-level-id=4d0028;packetizatio	-1 Resolution
n-mode=1;max-fr=30	
a=fmtp:100	[RFC3984]Camera-1,Encoding
profile-level-id=4d0028;packetizatio	-2 Resolution
n-mode=1;max-fr=15	
a=ssrc:67890	[RFC5576]
a=ssrc:56789	[RFC5576]
a=ssrc-group:SIMULCAST 67890 56789	[RFC5576]
a=ssrc:67890 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62
	22bis] Camera-1,Encoding-1
	SSRC with Session CNAME
a=ssrc:56789 cname:axzo1278npDlAzM73	[RFC5576]
	[draft-rescorla-avtcore-62
	22bis] Camera-1,Encoding-2
	SSRC with Session CNAME
a=bundle-only	Add reference to unified
	plan when available

Table 24: 6.1 SDP Simulcast bundle-only

SDP Contents	RFC#/Notes
v=0	[RFC4566]
o=alice 20519 0 IN IP4 0.0.0.0	[RFC4566]
s=	[RFC4566]
t=0 0	[RFC4566]
a=ice-ufrag:ufrag:c300d85b	[RFC5245]
a=ice-pwd:de4e99bd291c325921d5d47efbabd9a	[RFC5245]
2	
a=fingerprint:sha-1	[RFC5245]
99:41:49:83:4a:97:0e:1f:ef:6d:f7:c9:c7:70	
:9d:1f:66:79:a8:07	
m=audio 54609 RTP/SAVPF 109	[RFC4566]
c= IN IP4 24.23.204.141	[RFC4566]
a=rtpmap:109 opus/48000/2	[draft-ietf-payload-r
	tp-opus]
a=ptime:20	[draft-ietf-payload-r
	tp-opus]
a=sendonly	[RFC3264]
a=candidate:0 1 UDP 2113667327	[RFC5245]
192.168.1.4 54609 typ host	
a=candidate:1 1 UDP 694302207	[RFC5245]
24.23.204.141 54609 typ srflx raddr	
192.168.1.4 rport 54609	
a=candidate:0 2 UDP 2113667326	[RFC5245]
192.168.1.4 64678 typ host	
a=candidate:1 2 UDP 1694302206	[RFC5245]
24.23.204.141 64678 typ srflx raddr	
192.168.1.4 rport 64678	
m=video 0 RTP/SAVPF 98 100	Bob doesn't recognize
	bundle-only and hence
	rejects the video
	stream
c= IN IP4 24.23.204.141	[RFC4566]
a=rtpmap:98 VP8/90000	[draft-ietf-payload-v
	p8]
a=rtpmap:100 VP8/90000	[draft-ietf-payload-v
	p8]
a=imageattr:98 [x=1280,y=720]	[RFC6236]Camera-1,Enc
	oding-1 Resolution
a=fmtp:98 max-fr=30	[RFC4566]
a=imageattr:100 [x=640,y=480]	[RFC6236]
	Camera-1,Encoding-2
	Resolution
a=fmtp:100 max-fr=15	[RFC4566]

m=video 0 RTP/SAVPF 98 100	Bob doesn't recognize
	bundle-only and hence
	rejects the video
	stream
c= IN IP4 24.23.204.141	[RFC4566]
a=rtpmap:101 H264/90000	[RFC3984]
a=rtpmap:103 H264/90000	[RFC3984]
a=fmtp:101	[RFC3984] Camera-2, Enc
profile-level-id=4d0028;packetization-mod	oding-1 Resolution
e=1;max-fr=30	
a=fmtp:100	[RFC3984] Camera-1, Enc
profile-level-id=4d0028;packetization-mod	oding-2 Resolution
e=1;max-fr=15	
+-----+-----+	

Table 25: 6.2 SDP Answer

7. IANA Considerations

This document requires no actions from IANA.

8. Change Log

[RFC EDITOR NOTE: Please remove this section when publishing]

Changes from [draft-nandakumar-rtcweb-sdp-01](#)

- o Updated references to OPUS RTP Payload Specification.
- o Updated BUNDLE examples based on the latest [draft-ietf-mmusic-sdp-bundle-negotiation](#).
- o Added examples for multiple audio and video flows based on Unified Plan.
- o Added new examples for RTX and FEC streams
- o Updated Simulcast and SVC examples

Changes from [draft-nandakumar-rtcweb-sdp-00](#)

- o Fixed editorial comments on the mailing list.
- o Updated Data-channel SDP information based on [draft-ietf-mmusic-sctp-sdp](#).
- o Updated BUNDLE examples based on [draft-ietf-mmusic-sdp-bundle-negotiation](#).
- o Added examples for few more BUNDLE variants
- o Added new examples for Simulcast and SVC

9. References

9.1. Normative References

- [RFC3264] Rosenberg, J. and H. Schulzrinne, "An Offer/Answer Model with Session Description Protocol (SDP)", [RFC 3264](#), June 2002.
- [RFC4566] Handley, M., Jacobson, V., and C. Perkins, "SDP: Session Description Protocol", [RFC 4566](#), July 2006.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

9.2. Informative References

- [RFC5245] Rosenberg, J., "Interactive Connectivity Establishment (ICE): A Protocol for Network Address Translator (NAT) Traversal for Offer/Answer Protocols", [RFC 5245](#), July 2006.
- [WEBRTC] W3C, "WebRTC 1.0: Real-time Communication Between Browsers",
<<http://dev.w3.org/2011/webrtc/editor/webrtc.html>> .
- [JSEP] Uberti, J. and C. Jennigs, "Javascript Session Establishment Protocol", [draft-ietf-rtcweb-jsep-01](#) (work in progress), December 2012.
- [RFC5506] Johansson, I., "Support for Reduced-Size Real-Time Transport Control Protocol (RTCP): Opportunities and Consequences", [RFC 5506](#), April 2009.
- [RFC3551] Schulzrinne, H. and S. Casner, "RTP Profile for Audio and Video Conferences with Minimal Control", [RFC 3551](#), July 2003.
- [RFC3952] Duric, A. and S. Andersen, "Real-time Transport Protocol (RTP) Payload Format for internet Low Bit Rate Codec (iLBC) Speech", [RFC 3952](#), December 2004.
- [RFC4796] Hautakorpi, J. and G. Camarillo, "The Session Description Protocol (SDP) Content Attribute", [RFC 4796](#), February 2007.
- [RFC5761] Perkins, C. and M. Westerlund, "Multiplexing RTP Data and Control Packets on a Single Port", [RFC 5761](#), April 2010.
- [RFC3556] Casner, S., "Session Description Protocol (SDP) Bandwidth Modifiers for RTP Control Protocol (RTCP) Bandwidth",

[RFC 3556](#), July 2003.

- [RFC5104] Wenger, S., Chandra, U., Westerlund, M., and B. Burman, "Codec Control Messages in the RTP Audio-Visual Profile with Feedback (AVPF)", [RFC 5104](#), February 2008.
- [RFC4588] Rey, J., Leon, D., Miyazaki, A., Varsa, V., and R. Hakenberg, "RTP Retransmission Payload Format", [RFC 4588](#), July 2006.
- [RFC5956] Begen, A., "Forward Error Correction Grouping Semantics in the Session Description Protocol", [RFC 5956](#), September 2010.
- [RFC5888] Camarillo, G. and H. Schulzrinne, "RTP Payload Format for H.264 Video", [RFC 5888](#), June 2010.
- [RFC6236] Johansson, I. and K. Jung, "Negotiation of Generic Image Attributes in the Session Description Protocol (SDP)", [RFC 6236](#), May 2011.
- [[draft-ietf-payload-rtp-opus](#)]
Spittka, J., Vos, K., and JM. Valin, "RTP Payload Format for Opus Speech and Audio Codec", [draft-ietf-payload-rtp-opus-00](#) (work in progress), July 2012.
- [[draft-ietf-payload-vp8](#)]
Westin, P., Lundin, H., Glover, M., Uberti, J., and F. Galligan, "RTP Payload Format for VP8 Video", [draft-ietf-payload-vp8-05](#) (work in progress), August 2012.
- [RFC3984] Wenger, S., Hannuksela, M., Stockhammer, T., Westerlund, M., and D. Singer, "RTP Payload Format for H.264 Video", [RFC 3984](#), February 2005.
- [RFC5583] Schierl, T. and S. Wenger, "Signaling Media Decoding Dependency in the Session Description Protocol (SDP)", [RFC 5583](#), July 2009.
- [RFC5576] Lennox, J., Ott, J., and T. Schierl, "Source-Specific Media Attributes in the Session Description Protocol (SDP)", [RFC 5576](#), June 2009.
- [[draft-ietf-rtcweb-data-channel](#)]
Jesup, R., Loreto, S., and M. Tuexen, "RTCWeb Datagram Connection", [draft-ietf-rtcweb-data-channel-01](#) (work in progress), September 2012.

[\[draft-ietf-mmusic-sctp-sdp\]](#)

Loreto, S. and G. Camarillo, "Stream Control Transmission Protocol (SCTP)-Based Media Transport in the Session Description Protocol (SDP)", [draft-ietf-mmusic-sctp-sdp-03](#) (work in progress), September 2012.

[\[draft-ietf-mmusic-sdp-bundle-negotiation\]](#)

Holmberg, C., Alvestrand, H., and C. Jennings, "Multiplexing Negotiation Using Session Description Protocol (SDP) Port Numbers", [draft-ietf-mmusic-sdp-bundle-negotiation-04](#) (work in progress), February 2013.

[\[draft-lennox-mmusic-sdp-source-selection\]](#)

Lennox, J. and H. Schulzrinne, "Multiplexing Negotiation Using Session Description Protocol (SDP) Port Numbers", [draft-lennox-mmusic-sdp-source-selection-05](#) (work in progress), October 2012.

[\[draft-rescorla-avtcore-6222bis\]](#)

Rescorla, E. and A. Begen, "Guidelines for Choosing RTP Control Protocol (RTCP) Canonical Names (CNAMEs)", [draft-rescorla-avtcore-6222bis-00](#) (work in progress), October 2012.

Authors' Addresses

Suhas Nandakumar
Cisco
170 West Tasman Drive
San Jose, CA 95134
USA

Email: snandaku@cisco.com

Cullen Jennings
Cisco
170 West Tasman Drive
San Jose, CA 95134
USA

Phone: +1 408 421-9990
Email: fluffy@cisco.com

