

Network Working Group
Internet-Draft
Updates: RFC [2618](#) (if approved)
Expires: January 17, 2006

D. Nelson
Enterasys Networks
July 16, 2005

**RADIUS Auth Client MIB (IPv6)
draft-nelson-rfc2618bis-01.txt**

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on January 17, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This memo updates [RFC 2618](#) by deprecating the MIB table containing IPv4-only address formats and defining a new table to add support for version neutral IP address formats.

Table of Contents

1.	Terminology	3
2.	Introduction	3
3.	The Internet-Standard Management Framework	3
4.	Scope of Changes	3
5.	Structure of the MIB Module	4
6.	Deprecated Objects	4
7.	Definitions	4
8.	IANA Considerations	17
9.	Security Considerations	17
10.	References	18
10.1	Normative References	18
10.2	Informative References	19
	Author's Address	19
A.	Acknowledgments	19
	Intellectual Property and Copyright Statements	21

1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

This document uses terminology from [RFC 2865](#) [[RFC2865](#)].

2. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. The objects defined within this memo relate to the Remote Authentication Dial-In User Service (RADIUS) Authentication Client as defined in [RFC 2865](#) [[RFC2865](#)].

3. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

4. Scope of Changes

This document updates [RFC 2618](#) [[RFC2618](#)], RADIUS Authentication Client MIB, by deprecating the radiusAuthServerTable table and adding a new table, radiusAuthServerExtTable, containing radiusAuthServerInetAddressType, radiusAuthServerInetAddress, and radiusAuthClientServerInetPortNumber. The purpose of these added MIB objects is to support version neutral IP addressing formats. The existing table containing radiusAuthServerAddress and radiusAuthClientServerPortNumber is deprecated.

[RFC 4001](#) [[RFC4001](#)], which defines the SMI Textual Conventions for IPv6 addresses, contains the following recommendation.

'In particular, when revising a MIB module that contains IPv4 specific tables, it is suggested to define new tables using the textual conventions defined in this memo [[RFC 4001](#)] that support all

Nelson

Expires January 17, 2006

[Page 3]

versions of IP. The status of the new tables SHOULD be "current", whereas the status of the old IP version specific tables SHOULD be changed to "deprecated". The other approach, of having multiple similar tables for different IP versions, is strongly discouraged.'

5. Structure of the MIB Module

The structure of the MIB Module defined in this memo corresponds to the structure of the MIB Module defined in RADIUS Authentication Client MIB, [RFC 2618](#) [[RFC2618](#)]. This MIB module contains two scalars as well as a single table, the RADIUS Authentication Server Table, which contains one row for each RADIUS authentication server with which the client shares a secret.

Each entry in the RADIUS Authentication Server Table includes sixteen columns presenting a view of the activity of the RADIUS authentication client.

6. Deprecated Objects

The deprecated table in this MIB is carried forward from [RFC 2618](#) [[RFC2618](#)]. There are two conditions under which it MAY be desirable for managed entities to continue to support the deprecated table:

1. The managed entity only supports IPv4 address formats.
2. The managed entity supports both IPv4 and IPv6 address formats, and the deprecated table is supported for backwards compatibility with older management stations. This option SHOULD only be used when the IP addresses in the new table are in IPv4 format and can accurately be represented in both the new table and the deprecated table.

Managed entities SHOULD NOT instantiate the deprecated table containing IPv4-only address objects when the RADIUS server address represented in the table row is not an IPv4 address. Managed entities SHOULD NOT return inaccurate values of IP address or SNMP object access errors for IPv4-only address objects in otherwise populated tables.

7. Definitions

```
RADIUS-AUTH-CLIENT-MIB DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
    Counter32, Integer32, Gauge32,
    IPAddress, TimeTicks, mib-2          FROM SNMPv2-SMI
    SnmpAdminString                     FROM SNMP-FRAMEWORK-MIB
```

Nelson

Expires January 17, 2006

[Page 4]

```
InetAddressType, InetAddress,
InetPortNumber                FROM INET-ADDRESS-MIB
MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF;
```

```
radiusAuthClientMIB MODULE-IDENTITY
```

```
    LAST-UPDATED "200507150000Z" -- 15 Jul 2005
```

```
    ORGANIZATION "IETF RADIUS Working Group."
```

```
    CONTACT-INFO
```

```
        " Bernard Aboba
          Microsoft
          One Microsoft Way
          Redmond, WA 98052
          US
          Phone: +1 425 936 6605
          EMail: bernarda@microsoft.com"
```

```
    DESCRIPTION
```

```
        "The MIB module for entities implementing the client
         side of the Remote Authentication Dial-In User Service
         (RADIUS) authentication protocol."
```

```
    REVISION "9906110000Z" -- 11 Jun 1999
```

```
    DESCRIPTION "Initial version as published in RFC 2618"
```

```
    REVISION "200507150000Z" -- 15 Jul 2005
```

```
    DESCRIPTION "Revised version as published in RFC XXXX"
```

```
-- RFC Editor: replace xxx with actual RFC number at the time of
-- publication, and remove this note.
```

```
 ::= { radiusAuthentication 2 }
```

```
radiusMIB OBJECT-IDENTITY
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The OID assigned to RADIUS MIB work by the IANA."
```

```
 ::= { mib-2 67 }
```

```
radiusAuthClientExtMIB OBJECT-IDENTITY
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The OID assigned to RADIUS MIB Extension work by
         the IANA."
```

```
 ::= { mib-2 TBA }
```

```
-- RFC Editor: replace TBA with IANA assigned OID value, and
-- remove this note.
```

```
radiusAuthentication OBJECT IDENTIFIER ::= {radiusMIB 1}
```

Nelson

Expires January 17, 2006

[Page 5]

```
radiusAuthClientMIBObjects OBJECT IDENTIFIER
    ::= { radiusAuthClientMIB 1 }
```

```
radiusAuthClient OBJECT IDENTIFIER
    ::= { radiusAuthClientMIBObjects 1 }
```

```
radiusAuthClientInvalidServerAddresses OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Response packets
        received from unknown addresses."
    ::= { radiusAuthClient 1 }
```

```
radiusAuthClientIdentifier OBJECT-TYPE
    SYNTAX SnmpAdminString
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The NAS-Identifier of the RADIUS authentication client.
        This is not necessarily the same as sysName in MIB II."
    ::= { radiusAuthClient 2 }
```

```
radiusAuthServerTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RadiusAuthServerEntry
    MAX-ACCESS not-accessible
    STATUS deprecated
    DESCRIPTION
        "The (conceptual) table listing the RADIUS authentication
        servers with which the client shares a secret."
    ::= { radiusAuthClient 3 }
```

```
radiusAuthServerEntry OBJECT-TYPE
    SYNTAX RadiusAuthServerEntry
    MAX-ACCESS not-accessible
    STATUS deprecated
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
        authentication server with which the client shares
        a secret."
    INDEX { radiusAuthServerIndex }
    ::= { radiusAuthServerTable 1 }
```

```
RadiusAuthServerEntry ::= SEQUENCE {
    radiusAuthServerIndex Integer32,
    radiusAuthServerAddress IpAddress,
    radiusAuthClientServerPortNumber Integer32,
```

Nelson

Expires January 17, 2006

[Page 6]

```
radiusAuthClientRoundTripTime      TimeTicks,
radiusAuthClientAccessRequests    Counter32,
radiusAuthClientAccessRetransmissions Counter32,
radiusAuthClientAccessAccepts     Counter32,
radiusAuthClientAccessRejects     Counter32,
radiusAuthClientAccessChallenges  Counter32,
radiusAuthClientMalformedAccessResponses Counter32,
radiusAuthClientBadAuthenticators Counter32,
radiusAuthClientPendingRequests   Gauge32,
radiusAuthClientTimeouts          Counter32,
radiusAuthClientUnknownTypes      Counter32,
radiusAuthClientPacketsDropped     Counter32
}

radiusAuthServerIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      deprecated
    DESCRIPTION
        "A number uniquely identifying each RADIUS
        Authentication server with which this client
        communicates."
    ::= { radiusAuthServerEntry 1 }

radiusAuthServerAddress OBJECT-TYPE
    SYNTAX      IpAddress
    MAX-ACCESS  read-only
    STATUS      deprecated
    DESCRIPTION
        "The IP address of the RADIUS authentication server
        referred to in this table entry."
    ::= { radiusAuthServerEntry 2 }

radiusAuthClientServerPortNumber OBJECT-TYPE
    SYNTAX Integer32 (0..65535)
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The UDP port the client is using to send requests to
        this server."
    ::= { radiusAuthServerEntry 3 }

radiusAuthClientRoundTripTime OBJECT-TYPE
    SYNTAX TimeTicks
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The time interval (in hundredths of a second) between
```

Nelson

Expires January 17, 2006

[Page 7]

```
        the most recent Access-Reply/Access-Challenge and the
        Access-Request that matched it from this RADIUS
        authentication server."
 ::= { radiusAuthServerEntry 4 }

-- Request/Response statistics
--
-- TotalIncomingPackets = Accepts + Rejects + Challenges +
-- UnknownTypes
--
-- TotalIncomingPackets - MalformedResponses -
-- BadAuthenticators - UnknownTypes - PacketsDropped =
-- Successfully received
--
-- AccessRequests + PendingRequests + ClientTimeouts =
-- Successfully received
--
--

radiusAuthClientAccessRequests OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Access-Request packets sent
        to this server. This does not include retransmissions."
    ::= { radiusAuthServerEntry 5 }

radiusAuthClientAccessRetransmissions OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Access-Request packets
        retransmitted to this RADIUS authentication server."
    ::= { radiusAuthServerEntry 6 }

radiusAuthClientAccessAccepts OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Access-Accept packets
        (valid or invalid) received from this server."
    ::= { radiusAuthServerEntry 7 }

radiusAuthClientAccessRejects OBJECT-TYPE
    SYNTAX Counter32
```

Nelson

Expires January 17, 2006

[Page 8]

```
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
    "The number of RADIUS Access-Reject packets
    (valid or invalid) received from this server."
 ::= { radiusAuthServerEntry 8 }

radiusAuthClientAccessChallenges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Access-Challenge packets
        (valid or invalid) received from this server."
    ::= { radiusAuthServerEntry 9 }

-- "Access-Response" includes an Access-Accept, Access-Challenge
-- or Access-Reject

radiusAuthClientMalformedAccessResponses OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of malformed RADIUS Access-Response
        packets received from this server.
        Malformed packets include packets with
        an invalid length. Bad authenticators or
        Message Authenticator attributes or unknown types
        are not included as malformed access responses."
    ::= { radiusAuthServerEntry 10 }

radiusAuthClientBadAuthenticators OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Access-Response packets
        containing invalid authenticators or Message
        Authenticator attributes received from this server."
    ::= { radiusAuthServerEntry 11 }

radiusAuthClientPendingRequests OBJECT-TYPE
    SYNTAX Gauge32
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS Access-Request packets
```

Nelson

Expires January 17, 2006

[Page 9]

destined for this server that have not yet timed out or received a response. This variable is incremented when an Access-Request is sent and decremented due to receipt of an Access-Accept, Access-Reject or Access-Challenge, a timeout or retransmission."

```
::= { radiusAuthServerEntry 12 }
```

radiusAuthClientTimeouts OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of authentication timeouts to this server. After a timeout the client may retry to the same server, send to a different server, or give up. A retry to the same server is counted as a retransmit as well as a timeout. A send to a different server is counted as a Request as well as a timeout."

```
::= { radiusAuthServerEntry 13 }
```

radiusAuthClientUnknownTypes OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS packets of unknown type which were received from this server on the authentication port."

```
::= { radiusAuthServerEntry 14 }
```

radiusAuthClientPacketsDropped OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS packets of which were received from this server on the authentication port and dropped for some other reason."

```
::= { radiusAuthServerEntry 15 }
```

-- Extended MIB Objects

radiusAuthClientExtMIBNotifications OBJECT IDENTIFIER

```
::= { radiusAuthClientExtMIB 0 }
```

radiusAuthClientExtMIBObjects OBJECT IDENTIFIER

```
::= { radiusAuthClientExtMIB 1 }
```



```
radiusAuthClientExtMIBConformance    OBJECT IDENTIFIER
 ::= { radiusAuthClientExtMIB 2 }
```

```
radiusAuthServerExtTable OBJECT-TYPE
    SYNTAX      SEQUENCE OF RadiusAuthServerExtEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "The (conceptual) table listing the RADIUS authentication
        servers with which the client shares a secret."
    ::= { radiusAuthClientExtMIB 1 }
```

```
radiusAuthServerExtEntry OBJECT-TYPE
    SYNTAX      RadiusAuthServerExtEntry
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
        authentication server with which the client shares
        a secret."
    INDEX       { radiusAuthServerExtIndex }
    ::= { radiusAuthServerExtTable 1 }
```

```
RadiusAuthServerExtEntry ::= SEQUENCE {
    radiusAuthServerExtIndex          Integer32,
    radiusAuthServerInetAddressType  InetAddressType,
    radiusAuthServerInetAddress      InetAddress,
    radiusAuthClientServerInetPortNumber  InetPortNumber,
    radiusAuthClientExtRoundTripTime  TimeTicks,
    radiusAuthClientExtAccessRequests  Counter32,
    radiusAuthClientExtAccessRetransmissions  Counter32,
    radiusAuthClientExtAccessAccepts  Counter32,
    radiusAuthClientExtAccessRejects  Counter32,
    radiusAuthClientExtAccessChallenges  Counter32,
    radiusAuthClientExtMalformedAccessResponses  Counter32,
    radiusAuthClientExtBadAuthenticators  Counter32,
    radiusAuthClientExtPendingRequests  Gauge32,
    radiusAuthClientExtTimeouts        Counter32,
    radiusAuthClientExtUnknownTypes    Counter32,
    radiusAuthClientExtPacketsDropped  Counter32
}
```

```
radiusAuthServerExtIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A number uniquely identifying each RADIUS
```

Nelson

Expires January 17, 2006

[Page 11]

```

        Authentication server with which this client
        communicates."
 ::= { radiusAuthServerExtEntry 1 }

radiusAuthServerInetAddressType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The type of address format used for the
        radiusAuthServerInetAddress object."
 ::= { radiusAuthServerExtEntry 2 }

radiusAuthServerInetAddress OBJECT-TYPE
    SYNTAX      InetAddress
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The IP address of the RADIUS authentication
        server referred to in this table entry, using
        the IPv6 address format."
 ::= { radiusAuthServerExtEntry 3 }

radiusAuthClientServerInetPortNumber OBJECT-TYPE
    SYNTAX      InetPortNumber
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The UDP port the client is using to send requests
        to this server."
 ::= { radiusAuthServerExtEntry 4 }

radiusAuthClientExtRoundTripTime OBJECT-TYPE
    SYNTAX      TimeTicks
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The time interval (in hundredths of a second) between
        the most recent Access-Reply/Access-Challenge and the
        Access-Request that matched it from this RADIUS
        authentication server."
 ::= { radiusAuthServerExtEntry 5 }

-- Request/Response statistics
--
-- TotalIncomingPackets = Accepts + Rejects + Challenges +
-- UnknownTypes
```

Nelson

Expires January 17, 2006

[Page 12]

```
--
-- TotalIncomingPackets - MalformedResponses -
-- BadAuthenticators - UnknownTypes - PacketsDropped =
-- Successfully received
--
-- AccessRequests + PendingRequests + ClientTimeouts =
-- Successfully received
--
--

radiusAuthClientExtAccessRequests OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Request packets sent
         to this server. This does not include retransmissions."
    ::= { radiusAuthServerExtEntry 6 }

radiusAuthClientExtAccessRetransmissions OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Request packets
         retransmitted to this RADIUS authentication server."
    ::= { radiusAuthServerExtEntry 7 }

radiusAuthClientExtAccessAccepts OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Accept packets
         (valid or invalid) received from this server."
    ::= { radiusAuthServerExtEntry 8 }

radiusAuthClientExtAccessRejects OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Reject packets
         (valid or invalid) received from this server."
    ::= { radiusAuthServerExtEntry 9 }

radiusAuthClientExtAccessChallenges OBJECT-TYPE
    SYNTAX Counter32
```

Nelson

Expires January 17, 2006

[Page 13]

```
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of RADIUS Access-Challenge packets
    (valid or invalid) received from this server."
 ::= { radiusAuthServerExtEntry 10 }

-- "Access-Response" includes an Access-Accept, Access-Challenge
-- or Access-Reject

radiusAuthClientExtMalformedAccessResponses OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of malformed RADIUS Access-Response
        packets received from this server.
        Malformed packets include packets with
        an invalid length. Bad authenticators or
        Message Authenticator attributes or unknown types
        are not included as malformed access responses."
    ::= { radiusAuthServerExtEntry 11 }

radiusAuthClientExtBadAuthenticators OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Response packets
        containing invalid authenticators or Message
        Authenticator attributes received from this server."
    ::= { radiusAuthServerExtEntry 12 }

radiusAuthClientExtPendingRequests OBJECT-TYPE
    SYNTAX Gauge32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Request packets
        destined for this server that have not yet timed out
        or received a response. This variable is incremented
        when an Access-Request is sent and decremented due to
        receipt of an Access-Accept, Access-Reject or
        Access-Challenge, a timeout or retransmission."
    ::= { radiusAuthServerExtEntry 13 }

radiusAuthClientExtTimeouts OBJECT-TYPE
    SYNTAX Counter32
```

Nelson

Expires January 17, 2006

[Page 14]

```
MAX-ACCESS read-only
STATUS current
DESCRIPTION
    "The number of authentication timeouts to this server.
    After a timeout the client may retry to the same
    server, send to a different server, or
    give up. A retry to the same server is counted as a
    retransmit as well as a timeout. A send to a different
    server is counted as a Request as well as a timeout."
 ::= { radiusAuthServerExtEntry 14 }
```

```
radiusAuthClientExtUnknownTypes OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS packets of unknown type which
        were received from this server on the authentication
        port."
    ::= { radiusAuthServerExtEntry 15 }
```

```
radiusAuthClientExtPacketsDropped OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS packets of which were
        received from this server on the authentication port
        and dropped for some other reason."
    ::= { radiusAuthServerExtEntry 16 }
```

```
-- conformance information
```

```
radiusAuthClientMIBConformance OBJECT IDENTIFIER
    ::= { radiusAuthClientMIB 2 }
```

```
radiusAuthClientMIBCompliances OBJECT IDENTIFIER
    ::= { radiusAuthClientMIBConformance 1 }
```

```
radiusAuthClientMIBGroups OBJECT IDENTIFIER
    ::= { radiusAuthClientMIBConformance 2 }
```

```
radiusAuthClientExtMIBCompliances OBJECT IDENTIFIER
    ::= { radiusAuthClientExtMIBConformance 1 }
```

```
radiusAuthClientExtMIBGroups OBJECT IDENTIFIER
    ::= { radiusAuthClientExtMIBConformance 2 }
```



```
-- compliance statements
```

```
radiusAuthClientMIBCompliance MODULE-COMPLIANCE
```

```
    STATUS deprecated
```

```
    DESCRIPTION
```

```
        "The compliance statement for authentication clients  
        implementing the RADIUS Authentication Client MIB."
```

```
    MODULE -- this module
```

```
        MANDATORY-GROUPS { radiusAuthClientMIBGroup }
```

```
    ::= { radiusAuthClientMIBCompliances 1 }
```

```
radiusAuthClientExtMIBCompliance MODULE-COMPLIANCE
```

```
    STATUS current
```

```
    DESCRIPTION
```

```
        "The compliance statement for authentication  
        clients implementing the RADIUS Authentication  
        Client IPv6 Extensions MIB."
```

```
    MODULE -- this module
```

```
        MANDATORY-GROUPS { radiusAuthClientExtMIBGroup }
```

```
    ::= { radiusAuthClientExtMIBCompliances 1 }
```

```
-- units of conformance
```

```
radiusAuthClientMIBGroup OBJECT-GROUP
```

```
    OBJECTS { radiusAuthClientIdentifier,  
              radiusAuthClientInvalidServerAddresses,  
              radiusAuthServerAddress,  
              radiusAuthClientServerPortNumber,  
              radiusAuthClientRoundTripTime,  
              radiusAuthClientAccessRequests,  
              radiusAuthClientAccessRetransmissions,  
              radiusAuthClientAccessAccepts,  
              radiusAuthClientAccessRejects,  
              radiusAuthClientAccessChallenges,  
              radiusAuthClientMalformedAccessResponses,  
              radiusAuthClientBadAuthenticators,  
              radiusAuthClientPendingRequests,  
              radiusAuthClientTimeouts,  
              radiusAuthClientUnknownTypes,  
              radiusAuthClientPacketsDropped  
            }
```

```
    STATUS deprecated
```

```
    DESCRIPTION
```

```
        "The basic collection of objects providing management of  
        RADIUS Authentication Clients."
```



```
 ::= { radiusAuthClientMIBGroups 1 }

radiusAuthClientExtMIBGroup OBJECT-GROUP
    OBJECTS { radiusAuthClientIdentifier,
               radiusAuthClientInvalidServerAddresses,
               radiusAuthServerInetAddressType,
               radiusAuthServerInetAddress,
               radiusAuthClientServerInetPortNumber,
               radiusAuthClientExtRoundTripTime,
               radiusAuthClientExtAccessRequests,
               radiusAuthClientExtAccessRetransmissions,
               radiusAuthClientExtAccessAccepts,
               radiusAuthClientExtAccessRejects,
               radiusAuthClientExtAccessChallenges,
               radiusAuthClientExtMalformedAccessResponses,
               radiusAuthClientExtBadAuthenticators,
               radiusAuthClientExtPendingRequests,
               radiusAuthClientExtTimeouts,
               radiusAuthClientExtUnknownTypes,
               radiusAuthClientExtPacketsDropped
            }
    STATUS current
    DESCRIPTION
        "The collection of extended objects providing
         management of RADIUS Authentication Clients
         using version neutral IP address format."
    ::= { radiusAuthClientExtMIBGroups 1 }

END
```

8. IANA Considerations

This document requires IANA assignment of a number in the MIB-2 OID number space.

9. Security Considerations

There are no management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB via direct SNMP SET operations.

There are a number of managed objects in this MIB that may contain sensitive information. These are:

radiusAuthServerIPAddress This can be used to determine the address of the RADIUS authentication server with which the client is communicating. This information could be useful in mounting an attack on the authentication server.

radiusAuthServerInetAddress This can be used to determine the address of the RADIUS authentication server with which the client is communicating. This information could be useful in mounting an attack on the authentication server.

radiusAuthClientServerInetPortNumber This can be used to determine the port number on which the RADIUS authentication client is sending. This information could be useful in impersonating the client in order to send data to the authentication server.

It is thus important to control even GET access to these objects and possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMP versions prior to SNMPv3 do not provide a secure environment. Even if the network itself is secure (for example by using IPsec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is recommended that the implementers consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model [[RFC2574](#)] and the View-based Access Control Model [[RFC2575](#)] is recommended. Using these security features, customer/users can give access to the objects only to those principals (users) that have legitimate rights to GET or SET (change/create/delete) them.

[10. References](#)

[10.1 Normative References](#)

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2574] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", [RFC 2574](#), April 1999.
- [RFC2575] Wijnen, B., Presuhn, R., and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", [RFC 2575](#), April 1999.

- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), April 1999.
- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), April 1999.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.
- [RFC3418] Presuhn, R., "Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)", STD 62, [RFC 3418](#), December 2002.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.

[10.2](#) Informative References

- [RFC2618] Aboba, B. and G. Zorn, "RADIUS Authentication Client MIB", [RFC 2618](#), June 1999.
- [RFC2865] Rigney, C., Willens, S., Rubens, A., and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), June 2000.

Author's Address

David B. Nelson
Enterasys Networks
50 Minuteman Road
Andover, MA 01810
USA

Email: dnelson@enterasys.com

[Appendix A](#). Acknowledgments

The Authors of the original MIB are Bernard Aboba and Glen Zorn.

Many thanks to all reviewers, especially to Dave Harrington, Dan Romascanu, C.M. Heard, Bruno Pape and Greg Weber.

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

