

Network Working Group
Internet-Draft
Updates: RFC [2619](#) (if approved)
Expires: January 17, 2006

D. Nelson
Enterasys Networks
July 16, 2005

RADIUS Auth Server MIB (IPv6)
draft-nelson-rfc2619bis-01.txt

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on January 17, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This memo updates [RFC 2619](#) by deprecating the MIB table containing IPv4-only address formats and defining a new table to add support for version neutral IP address formats.

Internet-Draft

RADIUS Auth Server MIB (IPv6)

July 2005

Table of Contents

1.	Terminology	3
2.	Introduction	3
3.	The Internet-Standard Management Framework	3
4.	Scope of Changes	3
5.	Structure of the MIB Module	4
6.	Deprecated Objects	4
7.	Definitions	4
8.	IANA Considerations	19
9.	Security Considerations	19
10.	References	20
10.1	Normative References	20
10.2	Informative References	20
	Author's Address	21
A.	Acknowledgments	21
	Intellectual Property and Copyright Statements	22

1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

This document uses terminology from [RFC 2865](#) [[RFC2865](#)].

2. Introduction

This memo defines a portion of the Management Information Base (MIB) for use with network management protocols in the Internet community. The objects defined within this memo relate to the Remote Authentication Dial-In User Service (RADIUS) Authentication Server as defined in [RFC 2865](#) [[RFC2865](#)].

3. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].

Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the mechanisms defined in the Structure of Management Information (SMI). This memo specifies a MIB module that is compliant to the SMIV2, which is described in STD 58, [RFC 2578](#) [[RFC2578](#)], STD 58, [RFC 2579](#) [[RFC2579](#)] and STD 58, [RFC 2580](#) [[RFC2580](#)].

4. Scope of Changes

This document updates [RFC 2619](#) [[RFC2619](#)], RADIUS Authentication Server MIB, by deprecating the radiusAuthClientTable table and adding a new table, radiusAuthClientExtTable, containing

radiusAuthClientInetAddressType and radiusAuthClientInetAddress. The purpose of these added MIB objects is to support version neutral IP addressing formats. The existing table containing radiusAuthClientAddress is deprecated.

[RFC 4001](#) [[RFC4001](#)], which defines the SMI Textual Conventions for version neutral IP addresses, contains the following recommendation.

'In particular, when revising a MIB module that contains IPv4 specific tables, it is suggested to define new tables using the textual conventions defined in this memo [[RFC 4001](#)] that support all versions of IP. The status of the new tables SHOULD be "current",

Nelson

Expires January 17, 2006

[Page 3]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

July 2005

whereas the status of the old IP version specific tables SHOULD be changed to "deprecated". The other approach, of having multiple similar tables for different IP versions, is strongly discouraged.'

[5.](#) Structure of the MIB Module

The structure of the MIB Module defined in this memo corresponds to the structure of the MIB Module defined in RADIUS Authentication Server MIB, [RFC 2619](#) [[RFC2619](#)]. This MIB module contains fourteen scalars as well as a single table, the RADIUS Authentication Client Table, which contains one row for each RADIUS authentication client with which the server shares a secret.

Each entry in the RADIUS Authentication Client Table includes thirteen columns presenting a view of the activity of the RADIUS authentication server.

[6.](#) Deprecated Objects

The deprecated table in this MIB is carried forward from [RFC 2619](#) [[RFC2619](#)]. There are two conditions under which it MAY be desirable for managed entities to continue to support the deprecated table:

1. The managed entity only supports IPv4 address formats.
2. The managed entity supports both IPv4 and IPv6 address formats, and the deprecated table is supported for backwards compatibility with older management stations. This option SHOULD only be used when the IP addresses in the new table are in IPv4 format and can accurately be represented in both the new table and the

deprecated table.

Managed entities SHOULD NOT instantiate the deprecated table containing IPv4-only address objects when the RADIUS server address represented in the table row is not an IPv4 address. Managed entities SHOULD NOT return inaccurate values of IP address or SNMP object access errors for IPv4-only address objects in otherwise populated tables.

[7.](#) Definitions

4. Definitions

RADIUS-AUTH-SERVER-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY, OBJECT-TYPE, OBJECT-IDENTITY,
Counter32, Integer32,
IpAddress, TimeTicks, mib-2 FROM SNMPv2-SMI

Nelson

Expires January 17, 2006

[Page 4]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

July 2005

SnmpAdminString FROM SNMP-FRAMEWORK-MIB
InetAddressType, InetAddress,
InetPortNumber FROM INET-ADDRESS-MIB
MODULE-COMPLIANCE, OBJECT-GROUP FROM SNMPv2-CONF;

radiusAuthServMIB MODULE-IDENTITY

LAST-UPDATED "200507150000Z" -- 15 Jul 2005

ORGANIZATION "IETF RADIUS Working Group."

CONTACT-INFO

" Bernard Aboba
Microsoft
One Microsoft Way
Redmond, WA 98052
US
Phone: +1 425 936 6605
EMail: bernarda@microsoft.com"

DESCRIPTION

"The MIB module for entities implementing the server side of the Remote Authentication Dial-In User Service (RADIUS) authentication protocol."

REVISION "9906110000Z" -- 11 Jun 1999

DESCRIPTION "Initial version as published in [RFC 2619](#)"

REVISION "200507150000Z" -- 15 Jul 2005
DESCRIPTION "Revised version as published in RFC xxxx."

-- RFC Editor: replace xxxx with actual RFC number at the time of
-- publication, and remove this note.

::= { radiusAuthentication 1 }

radiusMIB OBJECT-IDENTITY
STATUS current
DESCRIPTION
 "The OID assigned to RADIUS MIB work by the IANA."
::= { mib-2 67 }

radiusAuthServerExtMIB OBJECT-IDENTITY
STATUS current
DESCRIPTION
 "The OID assigned to RADIUS MIB Extension
 work by the IANA."
::= { mib-2 TBA }

-- RFC Editor: replace TBA with IANA assigned OID value, and
-- remove this note.

radiusAuthentication OBJECT IDENTIFIER ::= {radiusMIB 1}

Nelson	Expires January 17, 2006	[Page 5]
--------	--------------------------	----------

Internet-Draft	RADIUS Auth Server MIB (IPv6)	July 2005
----------------	-------------------------------	-----------

radiusAuthServMIBObjects OBJECT IDENTIFIER
::= { radiusAuthServMIB 1 }

radiusAuthServ OBJECT IDENTIFIER
::= { radiusAuthServMIBObjects 1 }

radiusAuthServerExtMIBNotifications OBJECT IDENTIFIER
::= { radiusAuthServerExtMIB 0 }

radiusAuthServerExtMIBObjects OBJECT IDENTIFIER
::= { radiusAuthServerExtMIB 1 }

radiusAuthServIdent OBJECT-TYPE
SYNTAX SnmpAdminString

```

MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "The implementation identification string for the
    RADIUS authentication server software in use on the
    system, for example; `FNS-2.1'"
 ::= {radiusAuthServ 1}

```

radiusAuthServUpTime OBJECT-TYPE

```

SYNTAX        TimeTicks
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "If the server has a persistent state (e.g., a
    process), this value will be the time elapsed (in
    hundredths of a second) since the server process
    was started. For software without persistent state,
    this value will be zero."
 ::= {radiusAuthServ 2}

```

radiusAuthServResetTime OBJECT-TYPE

```

SYNTAX        TimeTicks
MAX-ACCESS    read-only
STATUS        current
DESCRIPTION
    "If the server has a persistent state (e.g., a process)
    and supports a `reset' operation (e.g., can be told to
    re-read configuration files), this value will be the
    time elapsed (in hundredths of a second) since the
    server was `reset.' For software that does not
    have persistence or does not support a `reset'
    operation, this value will be zero."
 ::= {radiusAuthServ 3}

```

radiusAuthServConfigReset OBJECT-TYPE

```

SYNTAX INTEGER { other(1),
                  reset(2),
                  initializing(3),
                  running(4)}
MAX-ACCESS    read-write
STATUS        current
DESCRIPTION

```

"Status/action object to reinitialize any persistent server state. When set to reset(2), any persistent server state (such as a process) is reinitialized as if the server had just been started. This value will never be returned by a read operation. When read, one of the following values will be returned:
 other(1) - server in some unknown state;
 initializing(3) - server (re)initializing;
 running(4) - server currently running."
 ::= {radiusAuthServ 4}

radiusAuthServTotalAccessRequests OBJECT-TYPE
 SYNTAX Counter32
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "The number of packets received on the authentication port."
 ::= { radiusAuthServ 5}

radiusAuthServTotalInvalidRequests OBJECT-TYPE
 SYNTAX Counter32
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "The number of RADIUS Access-Request packets received from unknown addresses."
 ::= { radiusAuthServ 6 }

radiusAuthServTotalDupAccessRequests OBJECT-TYPE
 SYNTAX Counter32
 MAX-ACCESS read-only
 STATUS current
 DESCRIPTION
 "The number of duplicate RADIUS Access-Request packets received."
 ::= { radiusAuthServ 7 }

radiusAuthServTotalAccessAccepts OBJECT-TYPE
 SYNTAX Counter32


```

        STATUS current
        DESCRIPTION
            "The number of RADIUS Access-Accept packets sent."
        ::= { radiusAuthServ 8 }

radiusAuthServTotalAccessRejects OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Reject packets sent."
    ::= { radiusAuthServ 9 }

radiusAuthServTotalAccessChallenges OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Access-Challenge packets sent."
    ::= { radiusAuthServ 10 }

radiusAuthServTotalMalformedAccessRequests OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of malformed RADIUS Access-Request
        packets received. Bad authenticators
        and unknown types are not included as
        malformed Access-Requests."
    ::= { radiusAuthServ 11 }

radiusAuthServTotalBadAuthenticators OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS Authentication-Request packets
        which contained invalid Message Authenticator
        attributes received."
    ::= { radiusAuthServ 12 }

radiusAuthServTotalPacketsDropped OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION

```

```
        "The number of incoming packets
        silently discarded for some reason other
        than malformed, bad authenticators or
        unknown types."
 ::= { radiusAuthServ 13 }
```

```
radiusAuthServTotalUnknownTypes OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS packets of unknown type which
        were received."
 ::= { radiusAuthServ 14 }
```

```
radiusAuthClientTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RadiusAuthClientEntry
    MAX-ACCESS not-accessible
    STATUS deprecated
    DESCRIPTION
        "The (conceptual) table listing the RADIUS
        authentication clients with which the server shares
        a secret."
 ::= { radiusAuthServ 15 }
```

```
radiusAuthClientEntry OBJECT-TYPE
    SYNTAX RadiusAuthClientEntry
    MAX-ACCESS not-accessible
    STATUS deprecated
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
        authentication client with which the server shares a
        secret."
    INDEX { radiusAuthClientIndex }
 ::= { radiusAuthClientTable 1 }
```

```
RadiusAuthClientEntry ::= SEQUENCE {
    radiusAuthClientIndex          Integer32,
    radiusAuthClientAddress        IPAddress,
    radiusAuthClientID             SnmpAdminString,
    radiusAuthServAccessRequests   Counter32,
    radiusAuthServDupAccessRequests Counter32,
    radiusAuthServAccessAccepts    Counter32,
    radiusAuthServAccessRejects    Counter32,
```

radiusAuthServAccessChallenges
radiusAuthServMalformedAccessRequests

Counter32,
Counter32,

Nelson

Expires January 17, 2006

[Page 9]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

July 2005

radiusAuthServBadAuthenticators Counter32,
radiusAuthServPacketsDropped Counter32,
radiusAuthServUnknownTypes Counter32

}

radiusAuthClientIndex OBJECT-TYPE

SYNTAX Integer32 (1..2147483647)

MAX-ACCESS not-accessible

STATUS deprecated

DESCRIPTION

"A number uniquely identifying each RADIUS
authentication client with which this server
communicates."

::= { radiusAuthClientEntry 1 }

radiusAuthClientAddress OBJECT-TYPE

SYNTAX IPAddress

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The NAS-IP-Address of the RADIUS authentication client
referred to in this table entry."

::= { radiusAuthClientEntry 2 }

radiusAuthClientID OBJECT-TYPE

SYNTAX SnmpAdminString

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The NAS-Identifier of the RADIUS authentication client
referred to in this table entry. This is not
necessarily the same as sysName in MIB II."

::= { radiusAuthClientEntry 3 }

-- Server Counters

--

-- Responses = AccessAccepts + AccessRejects + AccessChallenges

--

-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped - Responses = Pending
--
-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped = entries logged

radiusAuthServAccessRequests OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only

Nelson

Expires January 17, 2006

[Page 10]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

July 2005

STATUS deprecated

DESCRIPTION

"The number of packets received on the authentication
port from this client."

::= { radiusAuthClientEntry 4 }

radiusAuthServDupAccessRequests OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of duplicate RADIUS Access-Request
packets received from this client."

::= { radiusAuthClientEntry 5 }

radiusAuthServAccessAccepts OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS Access-Accept packets
sent to this client."

::= { radiusAuthClientEntry 6 }

radiusAuthServAccessRejects OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS deprecated

DESCRIPTION

"The number of RADIUS Access-Reject packets
sent to this client."

::= { radiusAuthClientEntry 7 }

radiusAuthServAccessChallenges OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The number of RADIUS Access-Challenge packets
 sent to this client."
 ::= { radiusAuthClientEntry 8 }

radiusAuthServMalformedAccessRequests OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The number of malformed RADIUS Access-Request

Nelson Expires January 17, 2006 [Page 11]

Internet-Draft RADIUS Auth Server MIB (IPv6) July 2005

 packets received from this client.
 Bad authenticators and unknown types are not included
 as malformed Access-Requests."
 ::= { radiusAuthClientEntry 9 }

radiusAuthServBadAuthenticators OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The number of RADIUS Authentication-Request packets
 which contained invalid Message Authenticator
 attributes received from this client."
 ::= { radiusAuthClientEntry 10 }

radiusAuthServPacketsDropped OBJECT-TYPE
SYNTAX Counter32
MAX-ACCESS read-only
STATUS deprecated
DESCRIPTION
 "The number of incoming packets from this
 client silently discarded for some reason other
 than malformed, bad authenticators or
 unknown types."
 ::= { radiusAuthClientEntry 11 }

```

radiusAuthServUnknownTypes OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS deprecated
    DESCRIPTION
        "The number of RADIUS packets of unknown type which
         were received from this client."
    ::= { radiusAuthClientEntry 12 }

-- new table

radiusAuthClientExtTable OBJECT-TYPE
    SYNTAX SEQUENCE OF RadiusAuthClientExtEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "The (conceptual) table listing the RADIUS
         authentication clients with which the server shares
         a secret."
    ::= { radiusAuthServerExtMIBObjects 1 }

radiusAuthClientExtEntry OBJECT-TYPE

```

Nelson Expires January 17, 2006 [Page 12]

Internet-Draft RADIUS Auth Server MIB (IPv6) July 2005

```

    SYNTAX RadiusAuthClientExtEntry
    MAX-ACCESS not-accessible
    STATUS current
    DESCRIPTION
        "An entry (conceptual row) representing a RADIUS
         authentication client with which the server shares a
         secret."
    INDEX { radiusAuthClientExtIndex }
    ::= { radiusAuthClientExtTable 1 }

```

```

RadiusAuthClientExtEntry ::= SEQUENCE {
    radiusAuthClientExtIndex          Integer32,
    radiusAuthClientInetAddressType  InetAddressType,
    radiusAuthClientInetAddress      InetAddress,
    radiusAuthClientExtID             SnmpAdminString,
    radiusAuthServExtAccessRequests  Counter32,
    radiusAuthServDupAccessRequests  Counter32,
    radiusAuthServExtAccessAccepts   Counter32,

```

```

radiusAuthServExtAccessRejects      Counter32,
radiusAuthServExtAccessChallenges   Counter32,
radiusAuthServExtMalformedAccessRequests Counter32,
radiusAuthServExtBadAuthenticators   Counter32,
radiusAuthServExtPacketsDropped      Counter32,
radiusAuthServExtUnknownTypes        Counter32
}

```

```

radiusAuthClientExtIndex OBJECT-TYPE
    SYNTAX      Integer32 (1..2147483647)
    MAX-ACCESS  not-accessible
    STATUS      current
    DESCRIPTION
        "A number uniquely identifying each RADIUS
         authentication client with which this server
         communicates."
    ::= { radiusAuthClientExtEntry 1 }

```

```

radiusAuthClientInetAddressType OBJECT-TYPE
    SYNTAX      InetAddressType
    MAX-ACCESS  read-only
    STATUS      current
    DESCRIPTION
        "The type of address format used for the
         radiusAuthClientInetAddress object."
    ::= { radiusAuthClientExtEntry 2 }

```

```

radiusAuthClientInetAddress OBJECT-TYPE
    SYNTAX      InetAddress

```

Nelson Expires January 17, 2006 [Page 13]

Internet-Draft RADIUS Auth Server MIB (IPv6) July 2005

```

MAX-ACCESS  read-only
STATUS      current
DESCRIPTION
    "The IP address of the RADIUS authentication
     client referred to in this table entry, using
     the version neutral IP address format."
::= { radiusAuthClientExtEntry 3 }

```

```

radiusAuthClientExtID OBJECT-TYPE
    SYNTAX      SnmpAdminString

```

```

MAX-ACCESS read-only
STATUS      current
DESCRIPTION
    "The NAS-Identifier of the RADIUS authentication client
    referred to in this table entry. This is not
    necessarily the same as sysName in MIB II."
 ::= { radiusAuthClientExtEntry 4 }

-- Server Counters

--
-- Responses = AccessAccepts + AccessRejects + AccessChallenges
--
-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped - Responses = Pending
--
-- Requests - DupRequests - BadAuthenticators - MalformedRequests -
-- UnknownTypes - PacketsDropped = entries logged

radiusAuthServExtAccessRequests OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of packets received on the authentication
        port from this client."
    ::= { radiusAuthClientExtEntry 5 }

radiusAuthServExtDupAccessRequests OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of duplicate RADIUS Access-Request
        packets received from this client."
    ::= { radiusAuthClientExtEntry 6 }

```

```

radiusAuthServExtAccessAccepts OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current

```


DESCRIPTION

"The number of RADIUS Access-Accept packets sent to this client."

::= { radiusAuthClientExtEntry 7 }

radiusAuthServExtAccessRejects OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Access-Reject packets sent to this client."

::= { radiusAuthClientExtEntry 8 }

radiusAuthServExtAccessChallenges OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Access-Challenge packets sent to this client."

::= { radiusAuthClientExtEntry 9 }

radiusAuthServExtMalformedAccessRequests OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of malformed RADIUS Access-Request packets received from this client. Bad authenticators and unknown types are not included as malformed Access-Requests."

::= { radiusAuthClientExtEntry 10 }

radiusAuthServExtBadAuthenticators OBJECT-TYPE

SYNTAX Counter32

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"The number of RADIUS Authentication-Request packets which contained invalid Message Authenticator attributes received from this client."

::= { radiusAuthClientExtEntry 11 }

```
radiusAuthServExtPacketsDropped OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of incoming packets from this
        client silently discarded for some reason other
        than malformed, bad authenticators or
        unknown types."
    ::= { radiusAuthClientExtEntry 12 }

radiusAuthServExtUnknownTypes OBJECT-TYPE
    SYNTAX Counter32
    MAX-ACCESS read-only
    STATUS current
    DESCRIPTION
        "The number of RADIUS packets of unknown type which
        were received from this client."
    ::= { radiusAuthClientExtEntry 13 }

-- conformance information

radiusAuthServMIBConformance OBJECT IDENTIFIER
    ::= { radiusAuthServMIB 2 }
radiusAuthServMIBCompliances OBJECT IDENTIFIER
    ::= { radiusAuthServMIBConformance 1 }
radiusAuthServMIBGroups OBJECT IDENTIFIER
    ::= { radiusAuthServMIBConformance 2 }

radiusAuthServerExtMIBConformance OBJECT IDENTIFIER
    ::= { radiusAuthServerExtMIB 2 }
radiusAuthServMIBExtCompliances OBJECT IDENTIFIER
    ::= { radiusAuthServExtMIBConformance 1 }
radiusAuthServMIBExtGroups OBJECT IDENTIFIER
    ::= { radiusAuthServMIBExtConformance 2 }

-- compliance statements

radiusAuthServMIBCompliance MODULE-COMPLIANCE
    STATUS deprecated
    DESCRIPTION
        "The compliance statement for authentication
        servers implementing the RADIUS Authentication
        Server MIB."
    MODULE -- this module
```

```
OBJECT          radiusAuthServConfigReset
WRITE-SYNTAX    INTEGER { reset(2) }
DESCRIPTION     "The only SETable value is 'reset' (2)."
```



```
::= { radiusAuthServMIBCompliances 1 }
```

```
radiusAuthServMIBExtCompliance MODULE-COMPLIANCE
    STATUS      current
    DESCRIPTION
        "The compliance statement for authentication
        servers implementing the RADIUS Authentication
        Server MIB."
    MODULE      -- this module
    MANDATORY-GROUPS { radiusAuthServMIBExtGroup }
```



```
OBJECT          radiusAuthServConfigReset
WRITE-SYNTAX    INTEGER { reset(2) }
DESCRIPTION     "The only SETable value is 'reset' (2)."
```



```
::= { radiusAuthServMIBCompliances 1 }
```

```
-- units of conformance
```

```
radiusAuthServMIBGroup OBJECT-GROUP
    OBJECTS {radiusAuthServIdent,
        radiusAuthServUpTime,
        radiusAuthServResetTime,
        radiusAuthServConfigReset,
        radiusAuthServTotalAccessRequests,
        radiusAuthServTotalInvalidRequests,
        radiusAuthServTotalDupAccessRequests,
        radiusAuthServTotalAccessAccepts,
        radiusAuthServTotalAccessRejects,
        radiusAuthServTotalAccessChallenges,
        radiusAuthServTotalMalformedAccessRequests,
        radiusAuthServTotalBadAuthenticators,
        radiusAuthServTotalPacketsDropped,
        radiusAuthServTotalUnknownTypes,
```

radiusAuthClientAddress,
radiusAuthClientID,
radiusAuthServAccessRequests,
radiusAuthServDupAccessRequests,
radiusAuthServAccessAccepts,
radiusAuthServAccessRejects,
radiusAuthServAccessChallenges,
radiusAuthServMalformedAccessRequests,

Nelson

Expires January 17, 2006

[Page 17]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

July 2005

radiusAuthServBadAuthenticators,
radiusAuthServPacketsDropped,
radiusAuthServUnknownTypes
}

STATUS deprecated

DESCRIPTION

"The collection of objects providing management of
a RADIUS Authentication Server."

::= { radiusAuthServMIBGroups 1 }

radiusAuthServMIBExtGroup OBJECT-GROUP

OBJECTS {radiusAuthServIdent,
radiusAuthServUpTime,
radiusAuthServResetTime,
radiusAuthServConfigReset,
radiusAuthServTotalAccessRequests,
radiusAuthServTotalInvalidRequests,
radiusAuthServTotalDupAccessRequests,
radiusAuthServTotalAccessAccepts,
radiusAuthServTotalAccessRejects,
radiusAuthServTotalAccessChallenges,
radiusAuthServTotalMalformedAccessRequests,
radiusAuthServTotalBadAuthenticators,
radiusAuthServTotalPacketsDropped,
radiusAuthServTotalUnknownTypes,
radiusAuthClientInetAddressType,
radiusAuthClientInetAddress,
radiusAuthClientExtID,
radiusAuthServExtAccessRequests,
radiusAuthServExtDupAccessRequests,
radiusAuthServExtAccessAccepts,
radiusAuthServExtAccessRejects,
radiusAuthServExtAccessChallenges,

```

        radiusAuthServExtMalformedAccessRequests,
        radiusAuthServExtBadAuthenticators,
        radiusAuthServExtPacketsDropped,
        radiusAuthServExtUnknownTypes
    }
STATUS    current
DESCRIPTION
    "The collection of objects providing management of
    a RADIUS Authentication Server."
 ::= { radiusAuthServMIBExtGroups 1 }

```

END

Nelson

Expires January 17, 2006

[Page 18]

Internet-Draft

RADIUS Auth Server MIB (IPv6)

July 2005

[8.](#) IANA Considerations

This document requires IANA assignment of a number in the MIB-2 OID number space.

[9.](#) Security Considerations

There are no management objects defined in this MIB that have a MAX-ACCESS clause of read-write and/or read-create. So, if this MIB is implemented correctly, then there is no risk that an intruder can alter or create any management objects of this MIB via direct SNMP SET operations.

There are a number of managed objects in this MIB that may contain sensitive information. These are:

radiusAuthClientIPAddress This can be used to determine the address of the RADIUS authentication client with which the server is communicating. This information could be useful in mounting an attack on the authentication client.

radiusAuthClientInetAddress This can be used to determine the address of the RADIUS authentication client with which the server is communicating. This information could be useful in mounting an attack on the authentication client.

It is thus important to control even GET access to these objects and

possibly to even encrypt the values of these object when sending them over the network via SNMP. Not all versions of SNMP provide features for such a secure environment.

SNMP versions prior to SNMPv3 do not provide a secure environment. Even if the network itself is secure (for example by using IPSec), there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB.

It is recommended that the implementers consider the security features as provided by the SNMPv3 framework. Specifically, the use of the User-based Security Model [[RFC2574](#)] and the View-based Access Control Model [[RFC2575](#)] is recommended. Using these security features, customer/users can give access to the objects only to those principals (users) that have legitimate rights to GET or SET (change/create/delete) them.

[10.](#) References

Nelson	Expires January 17, 2006	[Page 19]
--------	--------------------------	-----------

Internet-Draft	RADIUS Auth Server MIB (IPv6)	July 2005
----------------	-------------------------------	-----------

[10.1](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2574] Blumenthal, U. and B. Wijnen, "User-based Security Model (USM) for version 3 of the Simple Network Management Protocol (SNMPv3)", [RFC 2574](#), April 1999.
- [RFC2575] Wijnen, B., Presuhn, R., and K. McCloghrie, "View-based Access Control Model (VACM) for the Simple Network Management Protocol (SNMP)", [RFC 2575](#), April 1999.
- [RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), April 1999.
- [RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2",

STD 58, [RFC 2579](#), April 1999.

- [RFC2580] McCloghrie, K., Perkins, D., and J. Schoenwaelder, "Conformance Statements for SMIPv2", STD 58, [RFC 2580](#), April 1999.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), December 2002.
- [RFC3418] Presuhn, R., "Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)", STD 62, [RFC 3418](#), December 2002.
- [RFC4001] Daniele, M., Haberman, B., Routhier, S., and J. Schoenwaelder, "Textual Conventions for Internet Network Addresses", [RFC 4001](#), February 2005.

[10.2](#) Informative References

- [RFC2619] Zorn, G. and B. Aboba, "RADIUS Authentication Server MIB", [RFC 2619](#), June 1999.
- [RFC2865] Rigney, C., Willens, S., Rubens, A., and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", [RFC 2865](#), June 2000.

Nelson	Expires January 17, 2006	[Page 20]
--------	--------------------------	-----------

Internet-Draft	RADIUS Auth Server MIB (IPv6)	July 2005
----------------	-------------------------------	-----------

Author's Address

David B. Nelson
Enterasys Networks
50 Minuteman Road
Andover, MA 01810
USA

Email: dnelson@enterasys.com

[Appendix A](#). Acknowledgments

The Authors of the original MIB are Bernard Aboba and Glen Zorn.

Many thanks to all reviewers, especially to David Harrington, C.M. Heard and Bruno Pape.

Nelson	Expires January 17, 2006	[Page 21]
--------	--------------------------	-----------

Internet-Draft	RADIUS Auth Server MIB (IPv6)	July 2005
----------------	-------------------------------	-----------

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in

this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.