

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: August 29, 2013

M. Nottingham  
Akamai  
E. Wilde  
EMC  
February 25, 2013

Problem Details for HTTP APIs  
draft-nottingham-http-problem-03

## Abstract

This document defines a "problem detail" as a way to carry machine-readable details of errors in a HTTP response, to avoid the need to invent new error response formats for HTTP APIs.

## Note to Readers

This draft should be discussed on the apps-discuss mailing list [[1](#)].

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 29, 2013.

## Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

Internet-Draft

Problem Details

February 2013

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Requirements . . . . .	<a href="#">4</a>
<a href="#">3.</a>	The Problem Details JSON Object . . . . .	<a href="#">4</a>
<a href="#">3.1.</a>	Required Members . . . . .	<a href="#">5</a>
<a href="#">3.2.</a>	Optional Members . . . . .	<a href="#">5</a>
<a href="#">3.3.</a>	Extension Members . . . . .	<a href="#">5</a>
<a href="#">4.</a>	Defining New Problem Types . . . . .	<a href="#">6</a>
<a href="#">4.1.</a>	Example . . . . .	<a href="#">7</a>
<a href="#">5.</a>	Security Considerations . . . . .	<a href="#">7</a>
<a href="#">6.</a>	IANA Considerations . . . . .	<a href="#">8</a>
<a href="#">7.</a>	Acknowledgements . . . . .	<a href="#">9</a>
<a href="#">8.</a>	References . . . . .	<a href="#">9</a>
<a href="#">8.1.</a>	Normative References . . . . .	<a href="#">9</a>
<a href="#">8.2.</a>	Informative References . . . . .	<a href="#">10</a>
<a href="#">Appendix A.</a>	HTTP Problems and XML . . . . .	<a href="#">10</a>
	Authors' Addresses . . . . .	<a href="#">12</a>

Internet-Draft

Problem Details

February 2013

## 1. Introduction

HTTP [[RFC2616](#)] status codes are sometimes not sufficient to convey helpful information about an error. While humans behind Web browsers can be informed about the nature of the problem with an HTML response body, non-human consumers of so-called "HTTP APIs" are usually not.

This specification defines simple JSON [[RFC4627](#)] and XML [[W3C.REC-xml-20081126](#)] document formats to suit this purpose. They are designed to be reused by HTTP APIs, which can identify distinct "problem types" specific to their needs.

Thus, API clients can be informed of both the high-level error class (using the status code) and the finer-grained details of the problem (using one of these formats).

Consider a response that indicates that the client's account doesn't have enough credit. The 403 Forbidden status code might be deemed most appropriate to use, as it will inform HTTP-generic software (such as client libraries, caches and proxies) of the general semantics of the response.

However, that doesn't give the API client enough information about why the request was forbidden, the applicable account balance, or how to correct the problem. If these details are included in the response body in a machine-readable format, the client can treat it appropriately.

This specification does this by identifying a specific type of problem (e.g., "out of credit") with a URI [[RFC3986](#)]; APIs can do this by nominating new URIs under their control, or by reusing existing ones.

Additionally, problems can contain other information, such as a URI that identifies the specific occurrence of the problem (effectively giving an identifier to the concept "The time Joe didn't have enough

credit last Thursday"), which may be useful for support or forensic purposes. See below for a full list.

The data model for problem details is a JSON [[RFC4627](#)] object; when formatted as a JSON document, it uses the "application/api-problem+json" media type. [Appendix A](#) defines how to express them in an equivalent XML format, which uses the "application/api-problem+xml" media type.

Note that problem details are (naturally) not the only way to convey the details of a problem in HTTP; if the response is still a representation of a resource, for example, it's often preferable to

accommodate describing the relevant details in that application's format.

Instead, the aim of this specification is to define common error formats for those applications that need one, so that they aren't required to define their own, or worse, tempted to re-define the semantics of existing HTTP status codes.

## [2.](#) Requirements

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

## [3.](#) The Problem Details JSON Object

The canonical model for problem details is a JSON [[RFC4627](#)] object.

When serialised as a JSON document, that format is identified with the "application/api-problem+json" media type.

For example, a HTTP response carrying JSON problem details:

```
HTTP/1.1 403 Forbidden
Content-Type: application/api-problem+json
Content-Language: en
```

```
{
  "problemType": "http://example.com/probs/out-of-credit",
  "title": "You do not have enough credit.",
  "detail": "Your current balance is 30, but that costs 50.",
  "problemInstance": "http://example.net/account/12345/msgs/abc",
  "balance": 30,
  "accounts": ["http://example.net/account/12345",
               "http://example.net/account/67890"]
}
```

Here, the out-of-credit problem (identified by its `problemType` URI) indicates the reason for the 403 in `title`, gives a reference for the specific problem occurrence with `problemInstance`, gives occurrence-specific details in `detail`, and adds two extensions; `balance` conveys the account's balance, and `account` gives a link where the account can be topped up.

Note that `problemType` is case-sensitive in the JSON object, as are all other member names.

### [3.1.](#) Required Members

A problem details object MUST have the following members:

- o `"problemType"` (string) – An absolute URI [[RFC3986](#)] that identifies the problem type. When dereferenced, it SHOULD provide human-readable documentation for the problem type (e.g., using HTML).
- o `"title"` (string) – A short, human-readable summary of the problem type. It SHOULD NOT change from occurrence to occurrence of the problem, except for purposes of localisation.

Consumers MUST use the `problemType` string as the primary identifier for the problem type; the title string is advisory, and included only for users who are not aware of the semantics of the URI, and don't have the ability to discover them (e.g., offline log analysis). Consumers SHOULD NOT automatically dereference the `problemType` URI.

### [3.2.](#) Optional Members

Furthermore, a problem details object MAY have the following members:

- o `"httpStatus"` (number) – The HTTP status code set by the origin

- server for this occurrence of the problem.
- o "detail" (string) - An human readable explanation specific to this occurrence of the problem.
- o "problemInstance" (string) - An absolute URI that identifies the specific occurrence of the problem. It may or may not yield further information if dereferenced.

The `httpStatus` member, if present, is only advisory; it conveys the HTTP status code used for the convenience of the consumer. Generators **MUST** use the same status code in the actual HTTP response, to assure that generic HTTP software that does not understand this format still behaves correctly. See [Section 5](#) for further caveats regarding its use.

The `detail` member, if present, **SHOULD** focus on helping the client correct the problem, rather than giving debugging information.

Consumers **SHOULD NOT** parse the `detail` member for information; extensions are more suitable and less error-prone ways to obtain such information.

### [3.3.](#) Extension Members

Finally, problem type definitions **MAY** extend the problem details object with additional members.

Clients consuming problem details **MUST** ignore any such extensions that they don't recognise; this allows problem types to evolve and include additional information in the future.

## [4.](#) Defining New Problem Types

When an HTTP API needs to define a response that indicates an error condition, it might be appropriate to do so by defining a new problem type.

Before doing so, it's important to understand what they are good for, and what's better left to other mechanisms.

Problem details are not a debugging tool for the underlying

implementation; rather, they are a way to expose greater detail about the HTTP interface itself. New problem types need to carefully consider the Security Considerations ([Section 5](#)); in particular the risk of exposing attack vectors by exposing implementation internals through error messages.

Likewise, truly generic problems - i.e., conditions that could potentially apply to any resource on the Web - are usually better expressed as plain status codes. For example, a "write access disallowed" problem is probably unnecessary, since a 403 Forbidden status code on a PUT request is self-explanatory.

Finally, an application may have a more appropriate way to carry an error in a format that it already defines. Problem details are intended to avoid the necessity of establishing new "fault" or "error" document formats, not to replace existing domain-specific formats.

That said, it is possible to add support for problem details to existing HTTP APIs using HTTP content negotiation (e.g., using the Accept request header to indicate a preference for this format).

New problem type definitions MUST document:

1. A problemType URI (typically, with the "http" scheme),
2. A title that appropriately describes it (think short), and
3. The HTTP status code for it to be used with.

Problem types MAY specify the use of the Retry-After response header in appropriate circumstances.

A problem's problemType URI SHOULD resolve to HTML documentation that explains how to resolve the problem.

A problem type definition MAY specify additional members on the Problem Details object. For example, an extension might use typed links [[RFC5988](#)] to another resource that can be used by machines to resolve the problem.

If such additional members are defined, their names SHOULD start with a letter (ALPHA, as per [[RFC5234](#)] and SHOULD consist of characters from ALPHA, DIGIT and "\_" (so that it can be serialised in formats

other than JSON), and SHOULD be three characters or longer.

#### [4.1.](#) Example

For example, if you are publishing an HTTP API to your online shopping cart, you might need to indicate that the user is out of credit (our example from above), and therefore cannot make the purchase.

If you already have an application-specific format that can accommodate this information, it's probably best to do that. However, if you don't, you might consider using one of the problem details formats; JSON if your API is JSON-based, or XML if it uses that convention.

To do so, you might look for an already-defined `problemType` URI that suits your purposes. If one is available, you can reuse that URI by documenting use of both this specification and that specific URI value in your API.

If one isn't available, you'd reference this specification, mint and document a new `problemType` URI (which ought to be under your control and stable over time), an appropriate title and the HTTP status code that it will be used with, along with what it means and how it should be handled. This information could appear within the rest of your API's documentation.

In summary: a `problemInstance` URI will always identify a specific occurrence of a problem. On the other hand, `problemType` URIs can be reused if an appropriate description of a problem type is already available somewhere else, or they can be created for new problem types.

## [5.](#) Security Considerations

When defining a new problem type, the information included must be carefully vetted. Likewise, when actually generating a problem - however it is serialised - the details given must also be scrutinised.



the system, access to the system, or the privacy of users of the system.

Generators providing links to occurrence information are encouraged to avoid making implementation details such as a stack dump available through the HTTP interface, since this can expose sensitive details of the server implementation, its data, and so on.

The "httpStatus" member duplicates the information available in the HTTP status code itself, thereby bringing the possibility of disagreement between the two. Their relative precedence is not clear, since a disagreement might indicate that (for example) an intermediary has modified the HTTP status code in transit. As such, those defining problem types as well as generators and consumers of problems need to be aware that generic software (such as proxies, load balancers, firewalls, virus scanners) are unlikely to know of or respect the status code conveyed in this member.

## 6. IANA Considerations

This specification defines two new Internet media types [[RFC6838](#)]:

Type name: application  
Subtype name: api-problem+json  
Required parameters: None  
Optional parameters: None; unrecognised parameters should be ignored  
Encoding considerations: Same as [[RFC4627](#)]  
Security considerations: see [this document]  
Interoperability considerations: None.  
Published specification: [this document]  
Applications that use this media type: HTTP  
Additional information:  
    Magic number(s): n/a  
    File extension(s): n/a  
    Macintosh file type code(s): n/a  
Person & email address to contact for further information:  
    Mark Nottingham <mnot@mnot.net>  
Intended usage: COMMON  
Restrictions on usage: None.  
Author: Mark Nottingham <mnot@mnot.net>  
Change controller: IESG

Type name: application  
Subtype name: api-problem+xml  
Required parameters: None  
Optional parameters: None; unrecognised parameters  
should be ignored  
Encoding considerations: Same as [[RFC3023](#)]  
Security considerations: see [this document]  
Interoperability considerations: None.  
Published specification: [this document]  
Applications that use this media type: HTTP  
Additional information:  
    Magic number(s): n/a  
    File extension(s): n/a  
    Macintosh file type code(s): n/a  
Person & email address to contact for further information:  
    Mark Nottingham <mnot@mnot.net>  
Intended usage: COMMON  
Restrictions on usage: None.  
Author: Mark Nottingham <mnot@mnot.net>  
Change controller: IESG

## [7.](#) Acknowledgements

The authors would like to thank Jan Algermissen, Mike Amundsen, Subbu Allamaraju, Roy Fielding, Sam Johnston, Mike McCall, Julian Reschke, and James Snell for early review of this specification (even if some disagree with parts of it).

## [8.](#) References

### [8.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.
- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.
- [RFC4627] Crockford, D., "The application/json Media Type for

- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.

## [8.2.](#) Informative References

- [ISO-19757-2]  
International Organization for Standardization,  
"Information Technology --- Document Schema Definition  
Languages (DSDL) --- Part 2: Grammar-based Validation ---  
RELAX NG", ISO/IEC 19757-2, 2003.
- [RFC3023] Murata, M., St. Laurent, S., and D. Kohn, "XML Media  
Types", [RFC 3023](#), January 2001.
- [RFC5988] Nottingham, M., "Web Linking", [RFC 5988](#), October 2010.
- [RFC6838] Freed, N., Klensin, J., and T. Hansen, "Media Type  
Specifications and Registration Procedures", [BCP 13](#),  
[RFC 6838](#), January 2013.
- [W3C.REC-xml-20081126]  
Sperberg-McQueen, C., Yergeau, F., Maler, E., Paoli, J.,  
and T. Bray, "Extensible Markup Language (XML) 1.0 (Fifth  
Edition)", World Wide Web Consortium Recommendation REC-  
xml-20081126, November 2008,  
<<http://www.w3.org/TR/2008/REC-xml-20081126>>.

## URIs

- [1] <<https://www.ietf.org/mailman/listinfo/apps-discuss>>

## [Appendix A.](#) HTTP Problems and XML

Some HTTP-based APIs use XML [[W3C.REC-xml-20081126](#)] as their primary format convention. Such APIs MAY express problem details using the format defined in this appendix.

The OPTIONAL RELAX NG schema [[ISO-19757-2](#)] for the XML format is:

```
default namespace ns = "urn:ietf:rfc:XXXX"

start |= problem
problem =
  element problem {
    (element problemType { xsd:anyURI }
      & element title { xsd:string }
      & element detail { xsd:string }?
      & element httpStatus { xsd:positiveInteger }?
      & element problemInstance { xsd:anyURI }?),
    anyNsElement
  }
anyNsElement =
  (element ns:* { anyNsElement | text }
  | attribute * { text })*
```

The media type for this format is "application/api-problem+xml".

Extension arrays and objects can be serialised into the XML format by considering an element containing a child or children to represent an object, except for elements that contain only child element(s) named 'i', which are considered arrays. For example, an alternate version of the example above would appear in XML as:

```
HTTP/1.1 403 Forbidden
Content-Type: application/api-problem+xml
Content-Language: en
```

```
<?xml version="1.0" encoding="UTF-8"?>
<problem xmlns="urn:ietf:rfc:XXXX">
  <problemType>http://example.com/probs/out-of-credit</problemType>
  <title>You do not have enough credit.</title>
```

```
<detail>Your current balance is 30, but that costs 50.</detail>
<problemInstance>
  http://example.net/account/12345/msgs/abc
</problemInstance>
<balance>30</balance>
<accounts>
  <i>http://example.net/account/12345</i>
  <i>http://example.net/account/67890</i>
</accounts>
</problem>
```

Note that this format uses an XML Namespace. This is primarily to allow embedding it into other formats; it does not imply that it can be extended with content from other namespaces. The RELAX NG schema explicitly only allows elements from the one namespace used in the XML format. Any extension arrays and objects MUST be serialised

using that namespace.

#### Authors' Addresses

Mark Nottingham  
Akamai

Email: [mnot@mnot.net](mailto:mnot@mnot.net)  
URI: <http://www.mnot.net/>

Erik Wilde  
EMC

Email: [erik.wilde@emc.com](mailto:erik.wilde@emc.com)

