

DANE
Internet-Draft
Intended status: Standards Track
Expires: September 25, 2015

E. Osterweil
G. Wiley
T. Okubo
R. Lavu
A. Mohaisen
VeriSign, Inc.
March 24, 2015

Opportunistic Encryption with DANE Semantics and IPsec: IPSECA
draft-osterweil-dane-ipsec-02

Abstract

The query/response transactions of the Domain Name System (DNS) can disclose valuable meta-data about the online activities of DNS' users. The DNS Security Extensions (DNSSEC) provide object-level security, but do not attempt to secure the DNS transaction itself. For example, DNSSEC does not protect against information leakage, and only protects DNS data until the last validating recursive resolver. Stub resolvers are vulnerable to adversaries in the network between themselves and their validating resolver ("the last mile"). This document details a new DANE-like DNS Resource Record (RR) type called IPSECA, and explains how to use it to bootstrap DNS transactions through informing entries in IPsec Security Policy Databases (SPDs) and to subsequently verifying Security Associations (SAs) for OE IPsec tunnels.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 25, 2015.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the

Internet-Draft

OE with DANE and IPsec: IPSECA

March 2015

document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	What IPSECA Adds to DNSSEC Transactions	4
1.2.	IP-Centric IPsec Tunnel Discovery Using IPSECKEY	4
1.3.	Service-Centric IPsec Tunnel Discovery Using IPSECA and DANE	5
2.	The IPSECA Resource Record	6
2.1.	IPSECA RDATA Wire Format	7
2.1.1.	The Usage Field	7
2.1.2.	The Selector Field	7
2.1.3.	The Matching Field	8
2.1.4.	The Certificate Association Data Field	8
2.2.	IPSECA RR Presentation Format	9
2.3.	Domain Names used for IPSEC Records	9
2.4.	IPSECA RR Examples	9
2.4.1.	OE to a DNS Name Server Example	9
3.	Operational Considerations	11
4.	IANA Considerations	11
5.	Security Considerations	12
5.1.	Interactions	12
5.2.	Last Mile Security Analysis	12
6.	Acknowledgements	13
7.	References	13
7.1.	Normative References	13
7.2.	Informative References	14
Appendix A.	Name Server OE Configuration Example	15
Appendix B.	Recursive Resolver OE Configuration Example	16
	Authors' Addresses	16

1. Introduction

The query/response transactions of the Domain Name System (DNS) [[RFC1035](#)] can disclose valuable meta-data about the online activities of DNS' users. The DNS Security Extensions' (DNSSEC's) [[RFC4033](#)], [[RFC4034](#)], [[RFC4035](#)] core services (integrity, source authenticity, and secure denial of existence) are designed to secure data in DNS transactions by providing object-level security, but do not attempt to secure the DNS transaction itself. For example, DNSSEC does not attempt to protect the confidentiality of DNS transactions, does not protect data outside of the RRsets (including the DNS header, OPT record, etc.), and its DNS-specific protections expose opportunities for adversaries to identify DNS traffic, eavesdrop on DNS messages, and target DNS and its meta-data for attacks. As a result, a clever adversary may target just DNS traffic, discover the nature of a user's online browsing (from fully qualified domain names), interfere with the delivery of specific messages (though the DNS objects are not forgeable), or even attack "the last mile," between a resolver and a remote validating recursive resolver.

For example, the information leakage exposed by observing DNSSEC transactions, could enable an adversary to not only learn what Second Level Domains (SLDs) a user is querying (such as their bank, a funding agency, a security contractor, etc.), but could also inspect the fully qualified domain name(s) to learn the specific hosts visited, or in the case of certain DNS-based chat programs, information about ongoing conversations.

In addition, DNSSEC's design only protects DNS data until the last validating recursive resolver. If a client issues DNS queries from a stub resolver to a remote DNSSEC-aware resolver, then the network between these two ("the last mile") can be leveraged by an adversary to spoof responses, drop traffic, etc.

Clearly, these limitations do not invalidate the benefits of DNSSEC. DNSSEC still protects the actual DNS objects, protects against cache

poisoning attacks, and more. Rather, these limitations simply illustrate that there is more at stake than just valid DNS data.

This document details the motivation for, the synergy from, and a protocol to advertise and verify security credentials that can be used to verify Opportunistic Encryption (OE) IPsec [[RFC4301](#)], [[RFC6071](#)] tunnels for DNS transactions. Securing DNS transactions in this way is both necessary and sufficient for providing confidentiality of many types of DNS-transaction meta data, which can betray user privacy. This document details a new DANE-like [[RFC6698](#)] DNS Resource Record (RR) type called IPSECA, and explains how to use it to bootstrap entries in IPsec Security Policy Databases (SPDs) and

to subsequently verify Security Associations (SAs) for OE IPsec tunnels.

1.1. What IPSECA Adds to DNSSEC Transactions

DNSSEC's focus on object level security leaves the types of protections offered by IPsec unaddressed. Specifically, the way (or ways) to associate certificate(s) used by IPsec with a DNSSEC-aware name server need to be codified. This can be especially complicated if different IPsec certificates need to be discovered for different services that are running on the same IP address. This can become complicated if certificates are learned solely by the IP addresses of networked-services. This gap is inherently overcome during certificate discovery in DANE protocols by the concept of "Service Address Records," [I-D.[draft-ogud-dane-vocabulary](#)]. These Security Associations are defined by, and discovered by, domain names rather than just IP addresses. [[RFC6698](#)] standardizes a way for security associations of certificates to be made with service domains for TLS, rather than just IP addresses. As one of the underlying facilities of DANE's approach to certificate verification, this adds a necessary enhancement to IPsec certificate learning over approaches that are based solely on IP addresses in DNS (such as described in [[RFC4025](#)] and [[RFC4322](#)]).

The advantages of using DANE for IPsec OE also include other simplifications that the DANE protocol inherently offers all of its protocols. Such as, the automatic deauthorization of certificates that happens when they are removed from a DNS zone, which may (under many circumstances) obviate the need for extensive use of revocation

mechanisms (OCSP [[RFC6960](#)] or CRL [[RFC5280](#)]). Details of these relative trade offs is described in more detail in [[DANE SATIN12](#)].

It is also noteworthy that DANE offers flexibility that is not available in IP-centric certificate discovery and IP-centric OE [[RFC4322](#)], while still being backwards compatible with them. That is, while users can use IPSECA records to map OE IPsec tunnels to service names, they can also use IPSECA records in their reverse DNS zone in a similar fashion to the IPSECKEY [[RFC4025](#)] record used in [[RFC4322](#)]. However, while this document illustrates an example usage of DANE with IPsec OE, any specification for how the IPSECA resource record MUST get used with OE is beyond the scope of this document.

[1.2.](#) IP-Centric IPsec Tunnel Discovery Using IPSECKEY

In contrast to a DANE-centric discovery, [[RFC4025](#)] specifies a DNS resource record called IPSECKEY. The IPsec certificate learning described therein prescribes that relying parties learn the intended usage of IPsec certificates after they locate them in DNS and

retrieve them. The types of information that relying parties learn from IPSECKEY responses include: precedence, gateway type, algorithm, gateway, and possibly the public key. After learning the key and creating the Security Association, the relying party can use techniques like [[RFC4322](#)] to initialize an OE IPsec tunnel.

The inherent key learning and verification technique in [[RFC4322](#)] is based on learning tunnels from IP addresses only (IP-centric). Because of this technique's focus on IP-centric learning, operational entities running services on a specific IP address may not have access to annotate the reverse DNS zone for their services (especially if they are shared environments). So, this type of OE may often be a non-starter. One example would be when zones are hosted and/or served by cloud service providers. In this case, customers are almost certainly not allowed to annotate the reverse DNS zone for their providers.

[1.3.](#) Service-Centric IPsec Tunnel Discovery Using IPSECA and DANE

The suggested usage of this document is to aid in discovering where OE IPsec tunnels exist, and to act as an out of band verification substrate that can validate the certificates received during IPsec

key exchange. For example, if a DNS caching recursive resolver is configured to attempt OE IPsec tunnels to DNS name servers (using a specific key exchange protocol, like [\[RFC2409\]](#), [\[RFC5996\]](#), etc.), then when it receives a referral it SHOULD query name servers for corresponding IPSECA resource records. (we discuss the format of the resource record and domain names below in [Section 2](#)). When an IPSECA record is discovered by a resolver, that resolver SHOULD follow its configurations and setup an SPD entry, in order to signal its IPsec layer to attempt to attempt to establish an SA. Note, this document does not specify a new, or any modifications to any existing, IPsec key exchange protocols. Rather, after adding an SPD and after a successful tunnel establishment, the credentials used for the Security Association with the name server SHOULD be cross-checked with the IPSECA resource record(s).

When using IPSECA resource records to verify OE tunnels, clients MUST perform full DNSSEC validation of the DNSSEC chain of trust that leads to IPSECA RRs. As specified in [\[RFC6698\]](#):

"A [IPSECA] RRSet whose DNSSEC validation state is secure MUST be used as a certificate association for [IPsec] unless a local policy would prohibit the use of the specific certificate association in the secure TLSA RRSet.

If the DNSSEC validation state on the response to the request for the [IPSECA] RRSet is bogus, this MUST cause IPsec not to be

started or, if the IPsec negotiation is already in progress, MUST cause the connection to be aborted.

A [IPSECA] RRSet whose DNSSEC validation state is indeterminate or insecure cannot be used for [IPsec] and MUST be considered unusable."

This is to ensure that the SPD entries and SA(s) used for tunnels are fully verified. This verification MAY include local trust anchor processing, such that local DNSKEY resource records can be used to verify corresponding RRSIGs. Trust anchors (which may be distributed during dynamic host configuration) may be useful for bootstrapping. For example, consider the case where private address space [\[RFC1918\]](#) is used for internal recursive resolvers. Here, the locally provisioned DNS names for the private address space (in the reverse

Value	Acronym	Short Description	Reference
0	Cert	Full certificate	[RFC6698]
1	SPKI	SubjectPublicKeyInfo	[RFC6698]
2	DANE-TA	Trust anchor assertion	[RFC6698]
3-254		Unassigned	
255	PrivSel	Reserved for Private Use	[RFC6698]

Table 2: TLSA Selectors

2.1.3. The Matching Field

The meaning, semantics, and interpretation of the Matching field of the IPSECA resource record follow the specification described in [Section 2.3](#) of [I.D.[draft-ietf-dane-registry-acronyms](#)]:

Value	Acronym	Short Description	Reference
0	Full	No hash used	[RFC6698]
1	SHA2-256	256 bit hash by SHA2	[RFC6698]
2	SHA2-512	512 bit hash by SHA2	[RFC6698]
3-254		Unassigned	
255	PrivMatch	Reserved for Private Use	[RFC6698]

Table 3: TLSA Matching Types

2.1.4. The Certificate Association Data Field

The meaning, semantics, and interpretation of the Certificate Association Data field of the IPSECA resource record follow the specification of the same field in the TLSA resource record, described in [Section 2.1.4 of \[RFC6698\]](#):

"This field specifies the 'certificate association data' to be matched. These bytes are either raw data (that is, the full certificate or its SubjectPublicKeyInfo, depending on the selector) for matching type 0, or the hash of the raw data for matching types 1 and 2. The data refers to the certificate in the association, not to the TLS ASN.1 Certificate object."

[2.2.](#) IPSECA RR Presentation Format

</STUBBED OUT SECTION>

[2.3.](#) Domain Names used for IPSEC Records

The IPSECA resource record SHOULD be mapped to a domain name that is intuitive when discovering OE IPsec tunnels for specific services. The expected procedure for constructing the domain names for IPSECA records that enable OE for DNS (port 53) are:

1. The left-most label begins with an underscore character (_), followed by the decimal representation of the port number that corresponds to the service that should be conducted over IPsec. For example, the DNS transactions discussed in this document would result in "_53".
2. Next, the fully qualified domain name [[RFC1035](#)] of the service is appended to the right side. In the case of a DNS name server, that is its domain name. In the case of a service that is located using an IP address, the service address records MUST be its full reverse octet name (including the appropriate suffix, such as .in-addr.arpa. for IPv4 addresses and .ip6.arpa for IPv6 addresses).

Any custom configured tunnels and port mappings may result in local policies that use their own domain name format. Such custom OE tunnels are non-standard, and may not be discoverable by other relying parties.

[2.4.](#) IPSECA RR Examples

Because the IPSECA record is intended to be associated with a Service Address Record, it (implicitly) can also be associated with an IP address (through the reverse DNS). A few illustrative mappings are presented here as examples. These domain name / resource record mappings are not necessarily intended to update the processing of protocols like IKEv1 [[RFC2409](#)], IKEv2 [[RFC5996](#)], etc. or other OE protocols [[RFC4322](#)]. Rather, these mappings are intended to serve as examples of IPsec tunnels, and their proper configuration. They MAY be used in verifying Security Associations, but a protocol to do this is beyond the scope of this document.

[2.4.1.](#) OE to a DNS Name Server Example

Suppose a DNS zone example.com is served by the name servers

ns1.example.com and ns2.example.com. If the zone operators want to advertise their willingness to offer OE to their name servers using

IKEv2 [[RFC5996](#)], then the following domain names MUST be placed under the example.com zone (the contents of the resource records, below, are exemplary only and MAY have whatever values a zone operator chooses):

```
_53.ns1.example.com. IN IPSECA (  
  0 1 1 edeff39034cd2ee83446633a9fba  
    d815a579134ecd7636e51af92ec7  
    207fd490 ) ; Verify IPsec for DNS txns
```

```
_53.ns2.example.com. IN IPSECA (  
  0 1 1 edeff39034cd2ee83446633a9fba  
    d815a579134ecd7636e51af92ec7  
    207fd490 ) ; Verify IPsec for DNS txns
```

This example illustrates how a zone MAY indicate where an SPD entry and SA establishment endpoints exist for its name servers (note, they are not required to be the name servers themselves). Here, each name server is a tunnel end point, and these two name servers are mapped to service ports for DNS (port 53). The IPSECA records above indicate that they verify the CA who must have issued the IPsec certificate used and they represent a SHA256 hash of that certificate's SPKI.

Alternately, suppose an enterprise wants to configure OE for DNS transactions between its desktop clients and its recursive resolver. In this case, if the enterprise has configured their desktop clients (perhaps through DHCP) to forward their DNS queries to a caching recursive resolver at the IP address 192.168.1.2, then the following IPSECA mapping should be placed in an internally managed DNS reverse zone:

```
_53.2.1.168.192.in-addr.arpa. IN IPSECA (  
  3 0 2 8f6ea3c50b5c488bef74c7c4a17a  
    24e8b0f4777d13c211a29223b69a  
    ea7a89184ac4d272a2e3d9760966  
    fb3f220b39f7fdfb325998289e50  
    311ce0748f13c1ed ) ; Verify data in IKEv2 SA
```

This example illustrates how a caching recursive resolver MAY indicate where it will accept IPsec tunnel establishment and what the certificate used for a SA should be. Here the DNS service port and the IPSECA records describe the nature of the authentic certificate that SHOULD be used in an SA with this endpoint. In this example, the IPSECA records both specify that a DANE-EE cert should be expected in an SA with this resolver, and the SHA-512 hash of that full certificate should match the encoded value in the IPSECA

resource record.

Of note here is that since SAs MAY be identified by domain names (which map to IP addresses), some IP addresses may host services that offer IPsec, and some that do not. The IPSECA record allows hosts to advertise these nuanced configurations in the same way that these services are discovered (through the DNS itself).

[3.](#) Operational Considerations

Scaling IPsec connections to the full capacity that large recursive resolvers or large authoritative name servers operate at could be cause for concern. The additional overhead required to establish and maintain SAs could exceed the provisioning capacity of deployed systems. However, there are several relevant observations:

1. If a resolver enables OE, but no (or relatively few) name servers provision IPSECA records, then no IPsec tunnels will be established, and the load will remain static (or marginally increase).
2. If an authoritative name server provisions IPSECA record, it will only result in additional load if querying resolvers are configured to attempt OE.
3. Using white-listing techniques (such as those used during pilot deployments of AAAA records) would allow authoritative name servers to only return IPSECA responses to clients that have been white-listed. This would allow name servers to control the amount of IPsec overhead they incur. For the same reason, resolvers can be configured to only query for IPSECA records from

white-listed name servers.

[4.](#) IANA Considerations

This document uses a new DNS resource record type, called IPSECA. This resource record will need to have a new value assigned to it. Current implementations are advised to use a type number TYPE65347.

This document uses the same semantics and values as the TLSA resource record [[RFC6698](#)] for its Usage, Selector, and Matching fields. Any future use or modification of an IANA registry for that resource record will have similar effects on this resource record.

Osterweil, et al. Expires September 25, 2015 [Page 11]

Internet-Draft OE with DANE and IPsec: IPSECA March 2015

[5.](#) Security Considerations

This document details some of the benefits of using IPsec OE for DNS transactions. Such a utility does not reduce the benefits of other security protections. For example, the object-level security assurances that are offered by DNSSEC are cooperative with the session-level security of IPsec. Additional discussions are available in [[IPSEC APPEAL](#)]. Moreover, the protections described herein also offer cooperative benefits with higher layer protocol protections, like TLS [[RFC5246](#)]. Any combination of these types of protections offer both defense-in-depth (securing transactions at multiple levels) and offer security practitioners a larger mosaic of security tools from which to construct and maintain their security postures.

[5.1.](#) Interactions

This document requires that all fully qualified domain names [[RFC1035](#)] must be secured by DNSSEC. This includes domains in the reverse tree of DNS (which represent IP addresses).

The use of IPSECA resource records does not constitute a source of information leakage. Rather, it provides a mechanism to help bolster confidentiality, by obfuscating DNS transactions.

Expressing tunnel endpoints through DNS may allow adversaries a vehicle to learn where OE is being offered by name servers. However, OE tunnels to these name servers will only be attempted if querying resolvers are configured to attempt IPsec. As a result, adversaries may be able to learn of potential tunnel endpoints, but if they aim to disrupt active IPsec traffic, they must still observe which resolvers are trying to initiate IPsec communications. Therefore, adversaries would have no greater opportunity to disrupt IPsec traffic than they already do. They would still begin by (for example) observing VPN tunnel setup on wireless LANs (such as at public WiFi hot-spots).

[5.2.](#) Last Mile Security Analysis

For the last mile, we define one type of attack as the case where an adversary intercepts messages that can be undetectably spoofed. For example, if a zone (like example.com) has deployed DNSSEC, then if an adversary responds to a DNS query for www.exmaple.com, a validating DNS resolver should be able to detect the forgery. However, if an adversary responds to a query that is sent for a non-DNSSEC zone, a resolver cannot distinguish the spoofed response from an authentic response. In addition to this, many bootstrapping protocols (such as DHCP [[RFC2131](#)]) represent the first opportunity for an adversary to

disrupt DNS transactions (by subverting the bootstrapping of the resolver itself on stub-resolvers). Under this model, a DNS stub-resolver's security posture is enhanced by keeping an adversary's attack window to the smallest value possible.

Therefore, the attack window offered by DNS clients in a given time span T is comprised of the set of transactions that bootstrap configurations $W_{\text{cfg}}(T)$, plus any DNS transactions that are not verifiable. Of note, however, is that the DNSSEC transactions between stub-resolvers and recursive resolvers are not protected by DNSSEC's cryptography. The only indication of protections is a header bit (the AD bit), which is spoofable. As a result, the attack window includes all DNS transactions $W_{\text{rDNS}}(T)$.

From this, the attack window can be expressible as:

$$W(T) = W_{\text{cfg}}(T) + W_{\text{rDNS}}(T)$$

Of note is that under most circumstances, resolvers issue many more queries than configuration requests. So,

$$W_{\text{cfg}}(T) = 1, \text{ and } W_{\text{rDNS}}(T) \gg W_{\text{cfg}}(T).$$

However, consider the attack window when using OE: $\{W(T)\}$. If the initial configuration includes a DNSKEY trust anchor that can be used to verify DNSSEC data that corresponds to a resolver's corresponding reverse zone (i.e., the IPSECA RR under in-addr.arpa or ip6.arpa), then $\{W_{\text{cfg}}(T)\} = 1$ and $\{W_{\text{rDNS}}(T)\} = 0$. Therefore, since $W_{\text{rDNS}}(T) \gg W_{\text{cfg}}(T)$ and $\{W_{\text{rDNS}}(T)\} = 0$, then by the transitive property,

$$W(T) \gg \{W(T)\}.$$

6. Acknowledgements

The editors would like to express their thanks for the early support and insights given by Danny McPherson.

7. References

7.1. Normative References

- [RFC1035] Mockapetris, P., "Domain names - implementation and specification", STD 13, [RFC 1035](#), November 1987.
- [RFC1918] Rekhter, Y., Moskowitz, R., Karrenberg, D., Groot, G., and E. Lear, "Address Allocation for Private Internets",

Osterweil, et al. Expires September 25, 2015 [Page 13]

Internet-Draft OE with DANE and IPsec: IPSECA March 2015

[BCP 5](#), [RFC 1918](#), February 1996.

- [RFC4033] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "DNS Security Introduction and Requirements", [RFC 4033](#), March 2005.
- [RFC4034] Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "Resource Records for the DNS Security Extensions", [RFC 4034](#), March 2005.
- [RFC4035] Arends, R., Austein, R., Larson, M., Massey, D., and S.

Rose, "Protocol Modifications for the DNS Security Extensions", [RFC 4035](#), March 2005.

[RFC4301] Kent, S. and K. Seo, "Security Architecture for the Internet Protocol", [RFC 4301](#), December 2005.

[RFC6698] Hoffman, P. and J. Schlyter, "The DNS-Based Authentication of Named Entities (DANE) Transport Layer Security (TLS) Protocol: TLSA", [RFC 6698](#), August 2012.

[7.2](#). Informative References

[DANE_SATIN12]
Osterweil, E., Kaliski, B., Larson, M., and D. McPherson, "Reducing the X.509 Attack Surface with DNSSEC's DANE", Proceedings of Securing and Trusting Internet Names, SATIN '12, March 2012.

[I-D.[draft-ogud-dane-vocabulary](#)]
Gudmundsson, O., "Harmonizing how applications specify DANE-like usage", October 2013.

[I.D.[draft-ietf-dane-registry-acronyms](#)]
Gudmundsson, O., "Adding acronyms to simplify DANE conversations", January 2014.

[IPSEC_APPEAL]
Osterweil, E. and D. McPherson, "IPsec's Appeal: Protecting DNS Under the Covers", Verisign Labs Technical Report #1130006 Revision 1, January 2013.

[RFC2131] Droms, R., "Dynamic Host Configuration Protocol", [RFC 2131](#), March 1997.

[RFC2409] Harkins, D. and D. Carrel, "The Internet Key Exchange (IKE)", [RFC 2409](#), November 1998.

Osterweil, et al. Expires September 25, 2015 [Page 14]

Internet-Draft OE with DANE and IPsec: IPSECA March 2015

[RFC3596] Thomson, S., Huitema, C., Ksinant, V., and M. Souissi, "DNS Extensions to Support IP Version 6", [RFC 3596](#), October 2003.

- [RFC4025] Richardson, M., "A Method for Storing IPsec Keying Material in DNS", [RFC 4025](#), March 2005.
- [RFC4322] Richardson, M. and D. Redelmeier, "Opportunistic Encryption using the Internet Key Exchange (IKE)", [RFC 4322](#), December 2005.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), August 2008.
- [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", [RFC 5280](#), May 2008.
- [RFC5996] Kaufman, C., Hoffman, P., Nir, Y., and P. Eronen, "Internet Key Exchange Protocol Version 2 (IKEv2)", [RFC 5996](#), September 2010.
- [RFC6071] Frankel, S. and S. Krishnan, "IP Security (IPsec) and Internet Key Exchange (IKE) Document Roadmap", [RFC 6071](#), February 2011.
- [RFC6960] Santesson, S., Myers, M., Ankney, R., Malpani, A., Galperin, S., and C. Adams, "X.509 Internet Public Key Infrastructure Online Certificate Status Protocol - OCSP", [RFC 6960](#), June 2013.

[Appendix A](#). Name Server OE Configuration Example

<STUBBED OUT SECTION>

NAME SERVER SIDE

- o Config SPD to accept connections from any on port 53 only
- o Zones add IPSECA RRs for each NS domain name and configure DNSSEC:
<examples>

RESOLVER SIDE

- o resolver processing logic to intercept referrals and look for IPSECA RR(s).

- o When an IPSECA RR is found, create SPD for that IP and port 53.

</STUBBED OUT SECTION>

[Appendix B](#). Recursive Resolver OE Configuration Example

<STUBBED OUT SECTION>

RESOLVER SIDE

- o If public resolver, create SPD entry that only allows IPsec from port 53. If internal resolver, limit to addresses serviced.

REVERSE DNS ZONE

- o Add IPSECA RR(s) and configure DNSSEC

STUB SIDE

- o Configure reverse zone DNSKEY (if 1918) as a local TA (such as over DHCP). Then do onetime DNSSEC validation for fetching IPSECA RR.
- o Tools include dnskey-grab and/or NLnet Labs' xxxxx.

</STUBBED OUT SECTION>

Authors' Addresses

Eric Osterweil
VeriSign, Inc.
Reston, VA
USA

Email: eosterweil@verisign.com

Glen Wiley
VeriSign, Inc.
Reston, VA
USA

Email: gwiley@verisign.com

Internet-Draft

OE with DANE and IPsec: IPSECA

March 2015

Tomofumi Okubo
VeriSign, Inc.
Reston, VA
USA

Email: tomokubo@Verisign.com

Ramana Lavu
VeriSign, Inc.
Reston, VA
USA

Email: RLavu@verisign.com

Aziz Mohaisen
VeriSign, Inc.
Reston, VA
USA

Email: amohaisen@verisign.com

Osterweil, et al.

Expires September 25, 2015

[Page 17]