

Network Working Group
Internet-Draft
Intended Status: Informational
Expires: September 12, 2012

J. Parello
Cisco Systems, Inc.
March 12, 2012

Energy Management Terminology
draft-parello-eman-definitions-05

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on February, 2012.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as

described in Section 4.e of the [Trust Legal Provisions](#)

<Parello>

Expires September, 2012

[Page 1]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

and are provided without warranty as described in the
Simplified BSD License.

Abstract

This document contains definitions and terms used in the Energy Management Working Group. Each term contains a definition(s), example, and reference to a normative, informative or well know source. Terms originating in this draft should be either composed of or adapted from other terms in the draft with a source. The defined terms will then be used in other drafts as defined here.

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

Table of Contents

| | | |
|--------------------|--|--------------------|
| 1. | Introduction..... | 4 |
| 2. | Terminology..... | 5 |
| | Energy Device..... | 5 |
| | Energy Device Component..... | 5 |
| | Power Interface..... | 5 |
| | Energy Management..... | 5 |
| | Energy Management System (EnMS)..... | 6 |
| | ISO Energy Management System..... | 7 |
| | Energy..... | 7 |
| | Power..... | 7 |
| | Demand..... | 8 |
| | Power Quality..... | 8 |
| | Electrical Equipment..... | 8 |
| | Non-Electrical Equipment (Mechanical Equipment)..... | 9 |
| | Energy Object..... | 9 |
| | Electrical Energy Object..... | 9 |
| | Non-Electrical Energy Object..... | 9 |
| | Energy Monitoring..... | 9 |
| | Energy Control..... | 10 |
| | Energy Management Domain..... | 10 |
| | Energy Object Identification..... | 11 |
| | Energy Object Context..... | 11 |
| | Energy Object Relationship..... | 11 |
| | Aggregation Relationship..... | 12 |
| | Metering Relationship..... | 12 |
| | Power Source Relationship..... | 13 |
| | Proxy Relationship..... | 13 |
| | Energy Object Parent..... | 13 |
| | Energy Object Child..... | 14 |
| | Power State..... | 14 |
| | Power State Set..... | 14 |
| | Nameplate Power..... | 15 |
| 3. | Security Considerations..... | 15 |

| | | |
|--------------------|--|--------------------|
| 4. | IANA Considerations..... | 15 |
| 5. | Acknowledgments..... | 15 |
| 6. | References..... | 15 |
| | Normative References..... | 15 |
| | Informative References..... | 15 |
| 7. | Authors' Addresses..... | 16 |

OPEN ISSUE:

<parello>

Expires September 2012

[Page 3]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

- Energy Device is similar to Electrical Equipment? Note: anyway we need a definition for the related component.
- Should the Power Interface be called Energy Interface.
- Ideally, need normative references for Energy Device, Energy Device Component, and Power Interface.

[1.](#) Introduction

Within Energy Management there are terms that may seem obvious to a casual reader but in fact require a rigorous and sourced definition. To avoid any confusion in terms among the working group drafts, one glossary / lexicon of terms should exist that all drafts can refer to. This will avoid a review of terms multiplied across drafts.

This draft will contain a glossary of definitions of terms that can be agreed upon by the working group outside of the context of drafts and then included in or sourced to this draft.

Each term will contain a definition(s), a normative or informative reference, an optional example, an optional comment(s) listed a note(s).

All terms should be rooted with a well-known reference. If a definition is taken verbatim from a reference then the source is listed in square brackets. If a definition is derived from a well-

known reference then the source is listed as "Adapted from" with the reference listed in square brackets. If a defined term is newly defined here the reference will indicate as such by stating "herein" and if applicable list any composing terms from this document.

When applicable the [IEEE100] was used as the preferred source. If a term was not available from [IEEE100], then [IEC60050] was used. When there were multiple items from [IEEE100], [IEC60050] or [ISO50001], there were all included.

<parello>

Expires September 2012

[Page 4]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

[2](#). Terminology

Energy Device

An Energy Device is an Energy Object that may be monolithic or contain Energy Device Components.

EDITOR'S NOTE: see the list of open issues for this term

Energy Device Component

An Energy Device is an Energy Object contained in an Energy Device, for which the containing Energy Device provides individual energy management functions.

EDITOR'S NOTE: see the list of open issues for this term

Power Interface

A power interface is an Energy Object that serves as a

interconnection among Energy Objects, and participates in a Power Source Relationship.

EDITOR'S NOTE: see the list of open issues for this term

Energy Management

Energy Management is a set of functions for measuring, modeling, planning, and optimizing networks to ensure that the network elements and attached devices use energy efficiently and is appropriate for the nature of the application and the cost constraints of the organization.

Reference: Adapted from [[ITU-T-M-3400](#)]

Example: A set of computer systems that will poll electrical meters and store the readings

<parello>

Expires September 2012

[Page 5]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

NOTES:

1. Energy management refers to the activities, methods, procedures and tools that pertain to measuring, modeling, planning, controlling and optimizing the use of energy in networked systems [[NMF](#)].
2. Energy Management is a management domain which is congruent to any of FCAPS areas of management in the ISO/OSI Network Management Model [[TMN](#)]. Energy Management for communication networks and attached devices is a subset or part of an organization's greater Energy Management Policies.

Energy Management System (EnMS)

An Energy Management System is a combination of hardware and software used to administer a network with the primary purpose being Energy Management.

Reference: Adapted from [[1037C](#)]

Example: A single computer system that polls data from devices using SNMP

NOTES:

1. An Energy Management System according to [[ISO50001](#)] (ISO-EnMS) is a set of systems or procedures upon which organizations can develop and implement an energy policy, set targets, action plans and take into account legal requirements related to energy use. An EnMS allows organizations to improve energy performance and demonstrate conformity to requirements, standards, and/or legal requirements.
2. Example ISO-EnMS: Company A defines a set of policies and procedures indicating there should exist multiple computerized systems that will poll energy from their meters and pricing / source data from their local utility. Company A specifies that

<parello>

Expires September 2012

[Page 6]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

their CFO should collect information and summarize it quarterly to be sent to an accounting firm to produce carbon accounting reporting as required by their local government.

3. For the purposes of EMAN, the definition from [[1037C](#)] is the preferred meaning of an Energy Management System (EnMS). The definition from [[ISO50001](#)] can be referred to as ISO Energy Management System (ISO-EnMS).

ISO Energy Management System

Energy Management System as defined by [[ISO50001](#)]

Reference: herein

Energy

That which does work or is capable of doing work. As used by electric utilities, it is generally a reference to electrical energy and is measured in kilo-watt hours (kWh).

Reference: [[IEEE100](#)]

NOTES

1. Energy is the capacity of a system to produce external activity or perform work [[ISO50001](#)]

Power

The time rate at which energy is emitted, transferred, or received; usually expressed in watts (or in joules per second).

Reference: [[IEEE100](#)]

<parello>

Expires September 2012

[Page 7]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

Demand

The average value of power or a related quantity over a specified interval of time. Note: Demand is expressed in kilowatts, kilovolt-amperes, kilovars, or other suitable units.

Reference: [[IEEE100](#)]

NOTES:

1. typically kilowatts
2. Energy providers typically bill by Demand measurements as well as for maximum Demand per billing periods. Power values may spike during short-terms by devices, but Demand measurements recognize that maximum Demand does not equal maximum Power during an interval.

Power Quality

Characteristics of the electric current, voltage and frequencies at a given point in an electric power system, evaluated against a set of reference technical parameters. These parameters might, in some cases, relate to the compatibility between electricity supplied in an electric power system and the loads connected to that electric power system.

Reference: [[IEC60050](#)]

Electrical Equipment

A general term including materials, fittings, devices, appliances, fixtures, apparatus, machines, etc., used as a part of, or in connection with, an electric installation.

Reference: [[IEEE100](#)]

<parello>

Expires September 2012

[Page 8]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

Non-Electrical Equipment (Mechanical Equipment)

A general term including materials, fittings, devices appliances, fixtures, apparatus, machines, etc., used as a part of, or in connection with, non-electrical power installations.

Reference: Adapted from [[IEEE100](#)]

Energy Object

An Energy Object (EO) is a piece of equipment that is part of or attached to a communications network that is monitored, controlled, or aids in the management of another device for Energy Management.

Reference: herein

Electrical Energy Object

An Electrical Energy Object (EE0) is an Energy Object that is a piece of Electrical Equipment

Reference: herein, Electrical Equipment

Non-Electrical Energy Object

A Non-Electrical Energy Object (NEE0) an Energy Object that is a piece of Non-Electrical Equipment.

Reference: herein, Non-Electrical Equipment.

Energy Monitoring

Energy Monitoring is a part of Energy Management that deals with collecting or reading information from Energy Objects to aid in Energy Management.

Reference: herein

NOTES:

1. This could include Energy, Power, Demand, Power Quality, Context and/or Battery information.

<parello>

Expires September 2012

[Page 9]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

Energy Control

Energy Control is a part of Energy Management that deals with directing influence over Energy Objects.

Reference: herein

NOTES:

1. Typically in order to optimize or ensure its efficiency.

Provide Energy:

An Energy Object "provides" energy to another Energy Object if there is an energy flow from this Energy Object to the other one.

Reference: herein

Receive Energy:

An Energy Object "receives" energy from another Energy Object if there is an energy flow from the other Energy Object to this one.

Reference: herein

Energy Management Domain

An Energy Management Domain is a set of Energy Objects where all objects in the domain are considered one unit of management.

Reference: herein

Example: All EEO's drawing power from the same

distribution panel with the same AC voltage within a building, or all EEO's in a building for which there is one main meter, would comprise an Energy Management Domain.

NOTES:

1. Typically, this set will have as members all EO's that are powered from the same source.

<parello>

Expires September 2012

[Page 10]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

Energy Object Identification

Energy Object Identification is a set of attributes that enable an Energy Object to be: uniquely identified among all Energy Management Domains; linked to other systems; classified as to type, model, and or manufacturer.

Reference: herein

Energy Object Context

Energy Object Context is a set of attributes that allow an Energy Management System to classify the use of the Energy Object within an organization.

Reference: herein

NOTES:

1. The classification could contain the use and/or the ranking of the Energy Object as compared to other Energy Objects in the Energy Management Domain.

Energy Object Relationship

An Energy Object Relationship is a functional association among Energy Objects

NOTES

1. Relationships can be named and could include Aggregation, Metering, Power Source, and Proxy.

2. The Energy Object is the noun or entity in the relationship with the relationship described as the verb.

Example: If EO x is a piece of Electrical Equipment and EO y is an electrical meter clamped onto x's

<parello>

Expires September 2012

[Page 11]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

power cord, then x and y have a Metering Relationship. It follows that y meters x and that x is metered by y.

Reference: Adapted from [[CHEN](#)]

Aggregation Relationship

An Aggregation Relationship is an Energy Object Relationship where one Energy Object aggregates the Energy Management information of one or more other Energy Objects.

These Energy Objects are referred to as having an Aggregation Relationship.

Reference: herein

NOTES:

1. Aggregate values may be obtained by reading values from multiple Energy Objects and producing a single value of more significant meaning such as average, count, maximum, median, minimum, mode and most commonly sum [[SQL](#)].

Metering Relationship

A Metering Relationship is an Energy Object Relationship where one Energy Object measures the Power or Energy of one or more other Energy Objects.

These Energy Objects are referred to as having a Metering Relationship.

Reference: herein

Example: a PoE port on a switch measures the Power it

provides to the connected Energy Object.

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

Power Source Relationship

A Power Source Relationship is an Energy Object Relationship where one Energy Object is the source of or distributor of Power to one or more other Energy Objects.

These Energy Objects are referred to as having a Power Source Relationship.

Reference: herein

Example: a PDU provides power for a connected device.

Proxy Relationship

A Proxy Relationship is an Energy Object Relationship where one Energy Object provides the Energy Management capabilities on behalf of one or more other Energy Objects.

These Energy Objects are referred to as having a Proxy Relationship.

Reference: herein

Example: a protocol gateways device for Building Management Systems (BMS) with subtended devices.

Energy Object Parent

An Energy Object Parent is an Energy Object that participates in an Energy Object Relationship and is considered as providing the capabilities in the relationship.

Example: in a Metering Relationship, the Energy Object that is metering is called the Energy Object Parent, while the Energy Object that is metered is called the Energy Object Child.

Reference: herein

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

Energy Object Child

An Energy Object Child is an Energy Object that participates in an Energy Object Relationship and is considered as receiving the capabilities in the relationship.

Example: in a Metering Relationship, the Energy Object that is metering is called the Energy Object Parent, while the Energy Object that is metered is called the Energy Object Child.

Reference: herein

Power State

A Power State is a condition or mode of a device that broadly characterizes its capabilities, power consumption, and responsiveness to input.

Reference: Adapted from [[IEEE1621](#)]

NOTES:

1. A Power State can be seen as a power setting of an Energy Object that influences the power consumption, the available functionality, and the responsiveness of the Energy Object.
2. A Power State can be viewed as one method for Energy Control

Power State Set

A collection of Power States that comprise one named or logical grouping of control is a Power State Set.

Reference: herein

Example: The states {on, off, and sleep} as defined in [IEEE1621], or the 16 power states as defined by the [DMTF] can be considered two different Power State Sets.

<parello>

Expires September 2012

[Page 14]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

Nameplate Power

The Nameplate Power is the maximal (nominal) Power that a device can support.

Reference: herein

NOTES:

1. This is typically determined via load testing and is specified by the manufacturer as the maximum value required for operating the device. This is sometimes referred to as the worst-case Power. The actual or average Power may be lower. The Nameplate Power is typically used for provisioning and capacity planning.

[3.](#) Security Considerations

None

[4.](#) IANA Considerations

None

[5.](#) Acknowledgments

The author would like to thank the authors of the

current working group drafts for the discussions and definition clarifications

6. References

Normative References

Informative References

[IEEE100] "The Authoritative Dictionary of IEEE Standards Terms"
<http://ieeexplore.ieee.org/xpl/mostRecentIssue.jsp?punumber=4116785>

<parello>

Expires September 2012

[Page 15]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

[IEEE1621] "Standard for User Interface Elements in Power Control of Electronic Devices Employed in Office/Consumer Environments", IEEE 1621, December 2004.

[IEC60050] International Electrotechnical Vocabulary
<http://www.electropedia.org/iev/iev.nsf/welcome?openform>

[ISO50001] "ISO 50001:2011 Energy management systems - Requirements with guidance for use",
<http://www.iso.org/>

[DMTF] "Power State Management Profile DMTF DSP1027 Version 2.0" December 2009
http://www.dmtf.org/sites/default/files/standards/documents/DSP1027_2.0.0.pdf

[TMN] "TMN Management Functions : Performance Management", ITU-T M.3400

[NMF] "Network Management Fundamentals", Alexander Clemm, ISBN: 1-58720-137-2, 2007

[ITU-T-M-3400] TMN recommendation on Management Functions (M.3400), 1997

[CHEN] "The Entity-Relationship Model: Toward a Unified View of Data", Peter Pin-shan Chen, ACM Transactions on Database Systems, 1976

[1037C] US Department of Commerce, Federal Standard 1037C, <http://www.its.bldrdoc.gov/fs-1037/fs-1037c.htm>

[SQL] ISO/IEC 9075(1-4,9-11,13,14):2008

7. Authors' Addresses

John Parello
Cisco Systems, Inc.
3550 Cisco Way
San Jose, California 95134
US

Phone: +1 408 525 2339

<parello>

Expires September 2012

[Page 16]

Internet-Draft <[draft-parello-eman-definitions](#)> Mar 2012

Email: jparello@cisco.com

<parello>

Expires September 2012

[Page 17]