

Network Working Group
Internet-Draft
Intended status: Informational
Expires: August 22, 2013

C. Perkins
University of Glasgow
February 18, 2013

**On the Use of RTP Control Protocol (RTCP) Feedback for Unicast
Multimedia Congestion Control
draft-perkins-rmcat-rtp-cc-feedback-00**

Abstract

This memo discusses the types of congestion control feedback that it is possible to send using the RTP Control Protocol (RTCP), and their suitability of use in implementing congestion control for unicast multimedia applications.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 22, 2013.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Possible Models for RTCP Feedback	3
3.	What Feedback is Achievable With RTCP?	4
3.1.	Per-packet Feedback	4
3.2.	Per-frame Feedback	5
3.3.	Per-RTT Feedback	6
4.	Discussion and Conclusions	6
5.	Security Considerations	7
6.	IANA Considerations	7
7.	Informative References	7
	Author's Address	8

1. Introduction

The coming deployment of WebRTC systems raises the prospect that high quality video conferencing will see extremely wide use. To ensure the stability of the network in the face of this use, WebRTC systems will need to use some form of congestion control for their RTP-based media traffic. To develop such congestion control, it is necessary to understand the sort of congestion feedback that can be provided within the framework of RTP [[RFC3550](#)] and the RTP Control Protocol (RTCP). It then becomes possible to determine if this is sufficient for congestion control, or if some form of RTP extension is needed.

This memo considers the congestion feedback that can be sent using RTCP under the RTP/SAVPF profile [[RFC5124](#)] (the secure version of the RTP/AVPF profile [[RFC4585](#)]). This profile was chosen as it forms the basis for media transport in WebRTC [[I-D.ietf-rtcweb-rtp-usage](#)] systems. Nothing in this memo is specific to the secure version of the profile, or to WebRTC, however.

2. Possible Models for RTCP Feedback

Several questions need to be answered when providing RTCP reception quality feedback for congestion control purposes. These include:

- o How often is feedback needed?
- o How much overhead is acceptable?
- o How much, and what, data does each report contain?

The key question is how often does the receiver need to send feedback on the reception quality it is experiencing, and hence the congestion state of the network? Traditional congestion control protocols, such as TCP, send acknowledgements with every packet (or, at least, every couple of packets). That is straight-forward and low overhead when traffic is bidirectional and acknowledgements can be piggybacked onto return path data packets. It can also be acceptable, and can have reasonable overhead, to send separate acknowledgement packets when those packets are much smaller than data packets. It becomes a problem, however, when there is no return traffic on which to piggyback acknowledgements, and when acknowledgements are similar in size to data packets; this can be the case for some forms of media traffic, especially for voice over IP (VoIP) flows, but less so for video.

When considering multimedia traffic, it might make sense to consider less frequent feedback. For example, it might be possible to send a

feedback packet once per video frame, or once per network round trip time (RTT). This could still give sufficiently frequent feedback for the congestion control loop to be stable and responsive while keeping the overhead reasonable when the feedback cannot be piggybacked onto returning data. In this case, it is important to note that RTCP can send much more detailed feedback than simple acknowledgements. For example, if it were useful, it could be possible to use an RTCP extended report (XR) packet [[RFC3611](#)] to send feedback once per RTT comprising a bitmap of lost and received packets, with reception times, over that RTT. As long as feedback is sent frequently enough that the control loop is stable, and the sender is kept informed when data leaves the network (to provide an equivalent to ACK clocking in TCP), it is not necessary to report on every packet at the instant it is received (indeed, it is unlikely that a video codec can react instantly to a rate change anyway, and there is little point in providing feedback more often than the codec can adapt).

The amount of overhead due to congestion control feedback that is considered acceptable has to be determined. RTCP data is sent in separate packets to RTP data, and this has some cost in terms of additional header overhead compared to protocols that piggyback feedback on return path data packets. The RTP standards have long said that a 5% overhead for RTCP traffic generally acceptable, while providing the ability to change this fraction. Is this still the case for congestion control feedback? Or is there a desire to either see more responsive feedback and congestion control, possibility with a higher overhead, or is lower overhead wanted, accepting that this might reduce responsiveness of the congestion control algorithm?

Finally, the details of how much, and what, data is to be sent in each report will affect the frequency and/or overhead of feedback. There is a fundamental trade-off that the more frequently feedback packets are sent, the less data can be included in each packet to keep the overhead constant. Does the congestion control need high rate but simple feedback (e.g., like TCP acknowledgements), or is it acceptable to send more complex feedback less often?

[3.](#) What Feedback is Achievable With RTCP?

[3.1.](#) Per-packet Feedback

RTCP packets are sent as separate packets to RTP media data, and the protocol includes no mechanism for piggybacking an RTCP packet onto an RTP data packet. In addition, the RTCP timing rules are based on the size of the RTP session, the number of active senders, the RTCP packet size, and the configured RTCP bandwidth fraction, with randomisation to prevent synchronisation of reports; accordingly the

Perkins

Expires August 22, 2013

[Page 4]

RTCP packet transmission times are extremely unlikely to line up with RTP packet transmission times. As a result, RTCP cannot be used to send per-packet feedback in its current form.

All of these issues with using RTCP for per-packet feedback could be resolved in an update to the RTP protocol, of course. Such an update could change the RTCP timing rules, and might define a shim layer to allow multiplexing of RTP and RTCP into a single packet, or to extend the RTP header to piggyback feedback data. This sort of change would be a large, and almost certainly backwards incompatible, extension to the RTP protocol, and is unlikely to be completed quickly, but could be done if there was a need.

3.2. Per-frame Feedback

Consider one of the simplest scenarios for WebRTC: a point to point video call between two end systems. There will be four RTP flows in this scenario, two audio and two video, with all four flows being active for essentially all the time (the audio flows will likely use voice activity detection and comfort noise to reduce the packet rate during silent periods, and does not cause the transmissions to stop).

Assume all four flows are sent in a single RTP session, each using a separate SSRC. Further, assume each SSRC sends RTCP reports for all other SSRCs in the session (this gives the worst case for the RTCP overhead). When all members are senders like this, the RTCP timing rules in Sections 6.2 and 6.3 of [RFC3550] and [RFC4585] reduce to:

$$\text{rtcp_interval} = \text{avg_rtcp_size} * n / \text{rtcp_bw}$$

where avg_rtcp_size is measured in octets, and the rtcp_bw is the bandwidth available for RTCP, measured in octets per second (this will typically be 5% of the session bandwidth).

The average RTCP size will depend on the amount of feedback that is sent in each RTCP packet, on the number of members in the session, and on the size of source description (RTCP SDES) information sent. As a minimum, each RTCP packet will be a compound RTCP packet that contains an RTCP SR and an RTCP SDES packet. In the scenario above, each RTCP SR packet will contain three report blocks, once for each of the other RTP SSRCs sending data, for a total of 100 octets (this is 8 octets header, 20 octets sender info, and 3 * 24 octets report blocks). The RTCP SDES packet will comprise a header (4 octets), an SSRC (4 octets), a CNAME chunk, and padding. If the CNAME follows [I-D.ietf-avtcore-6222bis] and [I-D.ietf-rtcweb-rtp-usage] it will be 19 octets in size, and require 1 octet of padding. The resulting compound RTCP packet will be 128 octets in size. If sent in UDP/IPv4 with no IP options, the avg_rtcp_size will therefore be 156 octets,

including the header overhead. The value n in this scenario is 4, and the `rtcp_bw` is assumed to be 5% of the session bandwidth.

If it is desired to send RTCP feedback packets on average 30 times per second, to correspond to one RTCP report every frame for 30fps video, we can invert the above `rtcp_interval` calculation to get an `rtcp_bw` that gives an interval of 1/30th of a second or lower. This corresponds to an `rtcp_bw` of 18,720 octets per second (since $1/30 = 156 * 4 / 18,720$). This is 149,760 bits per second, which if 5% of the session bandwidth, gives a session bandwidth of approximately 2.8Mbps. That is, RTCP can report on every frame of video provided the session bandwidth is 2.8Mbps or larger, when every SSRC sends a report for every video frame.

If additional feedback beyond the standard report block is needed, the session bandwidth needed will increase. For example, with an additional 20 octets data being reported in each RTCP packet, the session bandwidth needed increases to 3.2Mbps for every SSRC to be able to report on every frame.

It might seem unnecessary to assign the same fraction of the RTCP bandwidth to reporting on the audio and video, since video is much higher rate, and so is presumably more likely to cause congestion. Sending audio and video in separate RTCP sessions with their own RTCP bandwidth fraction would give essentially double the RTCP bandwidth for each video source, since 5% of the video session bandwidth would be shared between two reporting SSRCs, rather than between the four reporting SSRCs in the single session case. This would hence reduce the session bandwidth to around 1.4Mbps or larger to allow reports on every frame. Extensions to split RTCP bandwidth unequally between participants in a single session could be defined to allow this to work with a single RTP session on a single UDP port, or two standard RTP sessions could be run on a single port, using a demultiplexing shim. RTCP already allows for different bandwidth fractions between senders and receivers, so this is a relatively small change to the protocol.

3.3. Per-RTT Feedback

The arguments made in [Section 3.2](#) apply to this case as well. The network RTT will usually be larger than the media framing interval, so sending feedback per RTT is less of a load on RTCP than sending feedback per frame.

4. Discussion and Conclusions

RTCP as it is currently specified cannot be used to send per-packet

congestion feedback. RTCP can, however, be used to send congestion feedback on each frame of video sent, provided the session bandwidth exceeds a couple of megabits per second (the exact rate depending on the number of session participants, the RTCP bandwidth fraction, and whether audio and video are sent in one or two RTP sessions). RTCP can likely also be used to send feedback on a per-RTT basis, provided the RTT is not too low.

If it is desired to use RTCP in something close to its current form for congestion feedback in WebRTC, the multimedia congestion control algorithm ought be designed to work with feedback sent roughly each frame or each RTT, rather than per packet, since that fits within the limitations of RTCP. That feedback can be a little more complex than just an acknowledgement, provided care is taken to consider the impact of the extra feedback on the overhead, possibly allowing for a degree of semantic feedback, meaningful to the codec layer as well as the congestion control algorithm.

Further study of the scenarios of interest is needed, to ensure that the analysis presented is applicable to other media topologies, and to sessions with different data rates and sizes of membership.

5. Security Considerations

The security considerations of [\[RFC3550\]](#), [\[RFC4585\]](#), and [\[RFC5124\]](#) apply.

6. IANA Considerations

There are no actions for IANA.

7. Informative References

[I-D.ietf-avtcore-6222bis]

Rescorla, E. and A. Begen, "Guidelines for Choosing RTP Control Protocol (RTCP) Canonical Names (CNAMEs)", [draft-ietf-avtcore-6222bis-00](#) (work in progress), December 2012.

[I-D.ietf-rtcweb-rtp-usage]

Perkins, C., Westerlund, M., and J. Ott, "Web Real-Time Communication (WebRTC): Media Transport and Use of RTP", [draft-ietf-rtcweb-rtp-usage-05](#) (work in progress), October 2012.

- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, [RFC 3550](#), July 2003.
- [RFC3611] Friedman, T., Caceres, R., and A. Clark, "RTP Control Protocol Extended Reports (RTCP XR)", [RFC 3611](#), November 2003.
- [RFC4585] Ott, J., Wenger, S., Sato, N., Burmeister, C., and J. Rey, "Extended RTP Profile for Real-time Transport Control Protocol (RTCP)-Based Feedback (RTP/AVPF)", [RFC 4585](#), July 2006.
- [RFC5124] Ott, J. and E. Carrara, "Extended Secure RTP Profile for Real-time Transport Control Protocol (RTCP)-Based Feedback (RTP/SAVPF)", [RFC 5124](#), February 2008.

Author's Address

Colin Perkins
University of Glasgow
School of Computing Science
Glasgow G12 8QQ
United Kingdom

Email: csp@csperkins.org

